

(12) **United States Patent**
Trahan et al.

(10) **Patent No.: US 10,506,076 B2**
(45) **Date of Patent: Dec. 10, 2019**

(54) **REMOTE BROWSING SESSION
MANAGEMENT WITH MULTIPLE
CONTENT VERSIONS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Amazon Technologies, Inc.**, Reno, NV
(US)

5,841,763 A * 11/1998 Leondires H04M 3/56
370/260

5,872,850 A 2/1999 Klein et al.
(Continued)

(72) Inventors: **Matthew L. Trahan**, Seattle, WA (US);
Jonathan A. Jenkins, Seattle, WA
(US); **Brett R. Taylor**, Bainbridge
Island, WA (US); **Adam J. Overton**,
Redmond, WA (US)

FOREIGN PATENT DOCUMENTS

CN 101960449 A 1/2011
CN 102077189 A 5/2011

(Continued)

(73) Assignee: **Amazon Technologies, Inc.**, Seattle,
WA (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

Lubonski, et al., An Adaptation Architecture to Improve User-
Perceived QoS of Multimedia Services for Enterprise Remote
Desktop Protocols. NG12005, pp. 149-156.

(Continued)

(21) Appl. No.: **14/256,618**

(22) Filed: **Apr. 18, 2014**

Primary Examiner — Lance Leonard Barry

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson
& Bear, LLP

(65) **Prior Publication Data**

US 2014/0380184 A1 Dec. 25, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/174,601, filed on
Jun. 30, 2011, now Pat. No. 8,706,860.

(51) **Int. Cl.**
H04L 29/06 (2006.01)
H04L 29/08 (2006.01)

(52) **U.S. Cl.**
CPC **H04L 67/42** (2013.01); **H04L 67/02**
(2013.01); **H04L 67/2838** (2013.01)


(58) **Field of Classification Search**
CPC ... H04L 67/42; H04L 29/08099; H04L 67/02;
H04L 67/06047; H04L 67/2838; G06F
3/0481; G06F 17/30861; G06F 17/30899

See application file for complete search history.

(57) **ABSTRACT**

A remote browsing process is directed to the generation and
management of a remote browse session at a network
computing provider. A client computing device requests one
or more requested network resources. The network comput-
ing provider instantiates a browse session instance and
retrieves the requested content. The network computing
provider provides the requested content to the client com-
puting device. The network computing provider also at least
partially processes the requested content for display, and
provides a processed representation of the requested content
to the client computing device. The client computing device
may update display of the requested content using the
processed representation of the requested content.

19 Claims, 11 Drawing Sheets



US 10,506,076 B2

Page 2

(56)	References Cited			2007/0027672 A1	2/2007	Decary et al.	
	U.S. PATENT DOCUMENTS			2007/0061700 A1 *	3/2007	Kothari	G06F 17/30905 715/234
	6,108,637 A	8/2000	Blumenau	2007/0094241 A1	4/2007	Blackwell et al.	
	6,138,156 A	10/2000	Fletcher et al.	2007/0115282 A1 *	5/2007	Turner	G06T 15/08 345/424
	6,182,133 B1	1/2001	Horvitz	2007/0118803 A1	5/2007	Walker et al.	
	6,377,257 B1 *	4/2002	Borrel	2007/0124693 A1	5/2007	Dominowska et al.	
			G06T 15/005 345/419	2007/0136696 A1 *	6/2007	Matthews	G06F 3/0481 715/854
	6,384,821 B1 *	5/2002	Borrel	2007/0160030 A1 *	7/2007	Cruz	H04L 12/2854 370/351
			G06T 15/00 345/421	2007/0288589 A1	12/2007	Chen et al.	
	6,430,624 B1	8/2002	Jamtgaard et al.	2008/0104502 A1	5/2008	Olston	
	6,560,620 B1	5/2003	Ching	2008/0183672 A1	7/2008	Canon et al.	
	6,625,624 B1	9/2003	Chen et al.	2008/0184128 A1	7/2008	Swenson et al.	
	6,654,784 B1 *	11/2003	Wei	2008/0320225 A1	12/2008	Panzer et al.	
			H04L 29/06 709/203	2009/0012969 A1	1/2009	Rail et al.	
	6,704,024 B2	3/2004	Robotham et al.	2009/0094339 A1	4/2009	Allen et al.	
	6,728,763 B1	4/2004	Chen	2009/0158141 A1	6/2009	Bauchot et al.	
	6,871,213 B1	3/2005	Graham et al.	2009/0164924 A1	6/2009	Flake et al.	
	6,871,236 B2	3/2005	Fishman et al.	2009/0204478 A1	8/2009	Kaib et al.	
	6,931,439 B1	8/2005	Hanmann et al.	2009/0210487 A1 *	8/2009	Westerhoff	G06T 15/005 709/203
	6,944,665 B2	9/2005	Brown et al.	2009/0217199 A1	8/2009	Hara et al.	
	7,003,442 B1	2/2006	Tsuda	2009/0225042 A1 *	9/2009	Andrews	G06F 3/04883 345/173
	7,054,952 B1	5/2006	Schwerdtfeger et al.	2009/0237728 A1	9/2009	Yamamoto	
	7,171,478 B2	1/2007	Lueckhoff et al.	2009/0244278 A1 *	10/2009	Taneja	G06Q 10/10 348/143
	7,191,211 B2	3/2007	Tuli	2009/0254867 A1	10/2009	Farouki et al.	
	7,353,252 B1	4/2008	Yang et al.	2009/0282021 A1	11/2009	Bennett	
	7,543,059 B2 *	6/2009	Johnson	2009/0287698 A1	11/2009	Marmaros et al.	
			G06F 17/3089 709/218	2009/0327517 A1	12/2009	Sivasubramanian et al.	
	7,584,423 B2	9/2009	Rohrbaugh et al.	2009/0327914 A1	12/2009	Adar et al.	
	7,975,000 B2	7/2011	Dixon et al.	2010/0036740 A1	2/2010	Barashi	
	8,010,545 B2	8/2011	Stefik et al.	2010/0057639 A1	3/2010	Schwarz et al.	
	8,185,621 B2	5/2012	Kasha	2010/0125507 A1	5/2010	Tarantino, III et al.	
	8,271,836 B2 *	9/2012	Hawkins	2010/0131594 A1	5/2010	Kashimoto	
			G06F 11/0709 709/224	2010/0138293 A1	6/2010	Ramer et al.	
	8,271,887 B2	9/2012	Offer et al.	2010/0218106 A1	8/2010	Chen et al.	
	8,316,124 B1	11/2012	Baumbach et al.	2010/0312788 A1	12/2010	Bailey	
	8,336,049 B2	12/2012	Medovich	2010/0318892 A1	12/2010	Teevan et al.	
	8,577,963 B2 *	11/2013	Trahan et al.	2010/0332513 A1	12/2010	Azar et al.	
	8,706,860 B2 *	4/2014	Trahan et al.	2011/0022957 A1	1/2011	Lee	
	8,799,412 B2	8/2014	Trahan et al.	2011/0029854 A1	2/2011	Nashi et al.	
	9,525,785 B2 *	12/2016	Salt	2011/0055203 A1	3/2011	Gutt et al.	
			H04N 1/00106	2011/0099294 A1	4/2011	Kapur et al.	
2001/0039490 A1	11/2001	Verbitsky et al.		2011/0119352 A1	5/2011	Perov	
2001/0039578 A1	11/2001	Tokumaru et al.		2011/0173177 A1	7/2011	Junqueira et al.	
2001/0052006 A1	12/2001	Barker et al.		2011/0178868 A1	7/2011	Garg et al.	
2002/0015042 A1 *	2/2002	Robotham	G06F 3/14 345/581	2011/0185025 A1	7/2011	Cherukuri et al.	
				2011/0191327 A1	8/2011	Lee	
2002/0030703 A1	3/2002	Robertson et al.		2011/0197121 A1	8/2011	Kletter	
2002/0184238 A1 *	12/2002	Chylla	H04N 1/00209	2011/0202848 A1	8/2011	Ismalon	
2002/0194302 A1	12/2002	Blumberg		2011/0208822 A1	8/2011	Rathod	
2003/0014478 A1	1/2003	Noble		2011/0246873 A1	10/2011	Tolle et al.	
2003/0023712 A1	1/2003	Zhao et al.		2011/0289074 A1	11/2011	Leban	
2003/0041106 A1	2/2003	Tuli		2011/0296341 A1	12/2011	Koppert	
2004/0066397 A1	4/2004	Walker et al.		2011/0302510 A1	12/2011	Harrison et al.	
2004/0083294 A1	4/2004	Lewis		2012/0022942 A1	1/2012	Holloway et al.	
2004/0139208 A1	7/2004	Tuli		2012/0072821 A1	3/2012	Bowling	
2004/0181613 A1	9/2004	Hashimoto et al.		2012/0084644 A1	4/2012	Robert et al.	
2004/0205448 A1	10/2004	Grefenstette et al.		2012/0096365 A1	4/2012	Wilkinson et al.	
2004/0220905 A1	11/2004	Chen et al.		2012/0143944 A1	6/2012	Reeves et al.	
2004/0243622 A1	12/2004	Morisawa		2012/0150844 A1	6/2012	Lindahl et al.	
2005/0010863 A1	1/2005	Zernik		2012/0151308 A1 *	6/2012	Falkenberg	G06F 17/30899 715/201
2005/0060643 A1	3/2005	Glass et al.		2012/0166922 A1	6/2012	Rolls	
2005/0071745 A1	3/2005	Ehrich et al.		2012/0185568 A1 *	7/2012	Broyde	H04N 21/23439 709/219
2005/0138382 A1	6/2005	Hougaard et al.		2012/0198516 A1	8/2012	Lim	
2005/0183039 A1	8/2005	Revis		2012/0215834 A1	8/2012	Chen et al.	
2005/0246193 A1	11/2005	Roever et al.		2012/0215919 A1	8/2012	Labat et al.	
2005/0278698 A1 *	12/2005	Verco	G06F 9/451 717/116	2012/0284629 A1	11/2012	Peters et al.	
				2012/0317295 A1	12/2012	Baird et al.	
2006/0095336 A1	5/2006	Heckerman et al.		2012/0331406 A1	12/2012	Baird et al.	
2006/0122889 A1	6/2006	Burdick et al.		2013/0031461 A1	1/2013	Hou et al.	
2006/0168510 A1	7/2006	Bryar et al.					
2006/0184421 A1	8/2006	Lipsky et al.					
2006/0248442 A1	11/2006	Rosenstein et al.					
2006/0248453 A1 *	11/2006	Bennett	G06F 17/30899 715/207				
2006/0277167 A1	12/2006	Gross et al.					
2006/0294461 A1	12/2006	Nadamoto et al.					
2007/0022072 A1	1/2007	Kao et al.					

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0080611 A1 3/2013 Li et al.
2013/0275488 A1 10/2013 Wang et al.
2013/0297739 A1* 11/2013 Faihe G06Q 10/101
709/217
2014/0067923 A1* 3/2014 Trahan et al. 709/203

FOREIGN PATENT DOCUMENTS

JP 2004-193979 7/2004
JP 2005-346734 12/2005
JP 2009-514045 A 4/2009
WO WO 97/38389 A2 10/1997
WO WO 01/73562 A1 10/2001
WO WO 2005/003998 A1 1/2005
WO WO 2009/090176 A1 7/2009

OTHER PUBLICATIONS

International Search Report and Written Opinion in PCT/US2012/
044711 dated Jan. 25, 2013.
International Preliminary Report on Patentability for PCT/US2012/
044711 dated Jan. 7, 2014.
International Search Report and Written Opinion in PCT/US2012/
044716 dated Sep. 25, 2012.
International Preliminary Report on Patentability for PCT/US2012/
044716 dated Jan. 7, 2014.

* cited by examiner




Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.






Fig. 7.

**Fig. 8.**

**Fig. 9.**





Fig. 10.

*Fig. 11.*

1

REMOTE BROWSING SESSION MANAGEMENT WITH MULTIPLE CONTENT VERSIONS

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. patent application Ser. No. 13/174,601, entitled REMOTE BROWSING SESSION MANAGEMENT and filed Jun. 30, 2011, now U.S. Pat. No. 8,706,806, the entirety of which is incorporated herein by reference.

BACKGROUND

Generally described, computing devices and communication networks can be utilized to exchange information. In a common application, a computing device can request content from another computing device via the communication network. For example, a user at a personal computing device can utilize a software browser application, typically referred to as a browser software application, to request a Web page from a server computing device via the Internet. In such embodiments, the user computing device can be referred to as a client computing device and the server computing device can be referred to as a content provider.

With reference to an illustrative example, a requested Web page, or original content, may be associated with a number of additional resources, such as images or videos, that are to be displayed with the Web page. In one specific embodiment, the additional resources of the Web page are identified by a number of embedded resource identifiers, such as uniform resource locators (“URLs”). In turn, software on the client computing devices, such as a browser software application, typically processes embedded resource identifiers to generate requests for the content. Accordingly, in order to satisfy a content request, one or more content providers will generally provide client computing devices data associated with the Web page as well as the data associated with the embedded resources.

Once the client computing device obtains the Web page and associated additional resources, the content may be processed in a number of stages by the software browser application or other client computing device interface. For example, and with reference to the above illustration, the software browser application may parse the Web page to process various Hypertext Markup Language (“HTML”) layout information and references to associated resources, may identify and process Cascading Style Sheets (“CSS”) information, may process and instantiate various Javascript code associated with the Web page, may construct a native object model to represent one or more components of the Web page, and may calculate various layout and display properties of the processed content for presentation to a user.

From the perspective of a user utilizing a client computing device, a user experience can be defined in terms of the performance and latencies associated with obtaining network content over a communication network, such as obtaining a Web page, processing embedded resource identifiers, generating requests to obtain embedded resources, and rendering content on the client computing device. Latencies and performance limitations of any of the above processes may diminish the user experience. Additionally, latencies and inefficiencies may be especially apparent on computing devices with limited resources, such as process-

2

ing power, memory or network connectivity such as notebooks, tablets, smartphones, and the like.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a block diagram illustrative of a content delivery environment including a number of client computing devices, content provider, a content delivery network service provider, and a network computing and storage provider;

FIG. 2 is a block diagram of the content delivery environment of FIG. 1 illustrating the generation and processing of a new browse session request from a client computing device to a network computing and storage provider;

FIG. 3 is a block diagram of the content delivery environment of FIG. 1 illustrating the generation and processing of a request for a network resource from a network computing and storage provider to a content provider;

FIG. 4 is a block diagram of the content delivery environment of FIG. 1 illustrating the generation and processing of one or more requests corresponding to one or more embedded resources from a network computing and storage provider to a content provider and content delivery network;

FIG. 5 is a block diagram of the content delivery environment of FIG. 1 illustrating the generation and processing of browse session data and user interaction data between a network computing and storage provider and client computing device;

FIG. 6 is a block diagram of the content delivery environment of FIG. 1 illustrating the generation and processing of an additional new browse session request from a client computing device to a network computing and storage provider;

FIG. 7 is a user interface diagram depicting an illustrative browser interface and display of browse session content;

FIG. 8 is a diagram depicting illustrative browser content processing actions as a series of processing subsystems;

FIG. 9 is a flow diagram illustrative of a new browse session routine implemented by network computing and storage provider;

FIG. 10 is a flow diagram illustrative of a client new browse session interaction routine implemented by a client computing device; and

FIG. 11 is a flow diagram illustrative of a process user interaction routine implemented by a client computing device.

DETAILED DESCRIPTION

Generally described, the present disclosure is directed to the generation and management of a remote application session between client computing devices and content providers in conjunction with a network computing and storage provider. Specifically, aspects of the disclosure will be described with regard to the request for a browse session by a client computing device with a content provider, the establishment of a remote browse session between the client computing device and a network computing and storage provider, and the transmission of browse session state data and client interaction data between the client computing device and the network computing and storage provider. Although aspects of the embodiments described in the disclosure will focus, for the purpose of illustration, on the

management of a remote browse session, one skilled in the art will appreciate that the techniques disclosed herein may be applied to any number of software processes or applications. Further, although various aspects of the disclosure will be described with regard to illustrative examples and embodiments, one skilled in the art will appreciate that the disclosed embodiments and examples should not be construed as limiting.

With reference to an illustrative example, a user may cause a client computing device to load a software browser application (henceforth referred to as a “browser”) for accessing content provided by one or more content providers. Illustratively, the accessed content may include a collection of one or more network resources (e.g., a Web page) and embedded resources such as images, video, audio, text, executable code, and other resources. In one embodiment, the browser may have a content display area or pane for displaying the accessed network content in addition to one or more local interface components, such as toolbars, menus, buttons, or other user interface controls. Local interface components may be managed and controlled by the software browser application or any other process executing or implemented locally at the client computing device. Illustratively, managing user interface controls locally may allow for a responsive user interface, as interactions by the user are processed locally on the client computing device.

Subsequent to the browser being loaded, a user or automated browser process may cause the client computing device to transmit a request to access content from a content provider by establishing a browse session with a network computing and storage provider across a private or public network. The browse session request may include information identifying one or more sources for the requested content. The identifiers can be in the form of network addresses of network resources, such as a Web site or other network accessible piece of content. For example, the user may select or enter a URL, (e.g., <http://www.xyzwebsite.com>) into a browser window, causing the client computing device to transmit a request for a new browse session to the network computing and storage provider, including the selected URL. The address or location of a network computing and storage provider capable to service the browse session request may be hardcoded into the browser, may be configurable by the user, may be obtained from a network address service, or may be determined in any other way.

In an illustrative embodiment, responsive to the browse session request received from the client computing device, the network computing and storage provider may instantiate or cause to have instantiated one or more computing components associated with the network computing and storage provider that will host a browser software application. For example, the network computing and storage provider can instantiate, or cause to have instantiated, an instance of a virtual machine that includes a software browser application capable of requesting resources from a communication network. Illustratively, in some situations, one or more devices associated with the network computing and storage provider may be located in a data center or other robustly networked computing environment, and, as compared to the client computing device, may experience relatively little latency or delay when obtaining network resources.

Using the instantiated network computing components, the network computing and storage provider may request the identified network resource(s) from one or more content providers, a content delivery network, or a local or associated cache component. For example, the browser software application on the instantiated network computing compo-

nent can process a primary network resource and then generate additional content requests for content identified in one or more embedded resource identifiers (e.g. pictures, video files, etc.). Illustratively, in the case of other, non-browser, applications, network resources, or content may include any file type or format known in the art and supported by the specific software application.

Having obtained the requested content (e.g., the requested network resource and embedded resources), the network computing and storage provider may identify a remote session browsing configuration specifying a remote session communication protocol for use in transmitting the requested content, user interaction data, intermediate processing results, and other information between the browser being executed on the client computing device and the browser being executed at the instantiated network computing component on the computing and storage provider. The information exchanged between the browser on the instantiated network computing component and the browser on the client computing device can be generally referred to as “browser session information.”

In addition to specifying a remote session communication protocol for transmitting information between the client computing device and the instantiated network computing component, in one embodiment, the identified remote session browsing configuration may specify that one or more processing actions to be performed on the requested content are to be performed at the network computing and storage provider rather than, or in addition to, at the client computing device. For purposes of illustration, the processing of network content by a browser may involve various processing actions before content can be rendered in an appropriate form on a client computing device. A Web page, for example, may be parsed and processed to process various HTML layout information and references to associated resources or embedded content such as CSS style sheets and Javascript, as well as embedded content objects such as images, video, audio, etc. Each object or piece of code may be parsed and processed before a representative object model corresponding to the web page may be constructed and processed further for layout and display. In accordance with the selected remote session browsing configuration, the client computing device and the instantiated network computing component may exchange processing results via browser session information (e.g., state data or display data representing the requested content).

FIG. 1 is a block diagram illustrative of a networked computing environment **100** for the management and processing of content requests. As illustrated in FIG. 1, the networked computing environment **100** includes a number of client computing devices **102** (generally referred to as clients) for requesting content and content processing from a content provider **104**, content delivery network (“CDN”) service provider **106**, or network computing and storage provider **107**. In an illustrative embodiment, the client computing devices **102** can correspond to a wide variety of computing devices including personal computing devices, laptop computing devices, hand-held computing devices, terminal computing devices, mobile devices (e.g., mobile phones, tablet computing devices, etc.), wireless devices, various electronic devices and appliances and the like. In an illustrative embodiment, the client computing devices **102** include necessary hardware and software components for establishing communications over a communication network **108**, such as a wide area network or local area network. For example, the client computing devices **102** may be equipped with networking equipment and browser software

applications that facilitate communications via the Internet or an intranet. The client computing devices **102** may have varied local computing resources such as central processing units and architectures, memory, mass storage, graphics processing units, communication network availability and bandwidth, etc.

The networked computing environment **100** can also include a content provider **104** in communication with the one or more client computing devices **102** or other service providers (e.g., CDN service provider **106**, network computing and storage provider **107**, etc.) via the communication network **108**. The content provider **104** illustrated in FIG. **1** corresponds to a logical association of one or more computing devices associated with a content provider. Specifically, the content provider **104** can include a web server component **110** corresponding to one or more server computing devices for obtaining and processing requests for content (such as Web pages) from the client computing devices **102** or other service providers. The content provider **104** can further include an origin server component **112** and associated storage component **114** corresponding to one or more computing devices for obtaining and processing requests for network resources from the CDN service provider. The content provider **104** can still further include an application server computing device **111**, such as a data streaming server, for processing streaming content requests. One skilled in the relevant art will appreciate that the content provider **104** can be associated with various additional computing resources, such as additional computing devices for administration of content and resources, DNS name servers, and the like. For example, although not illustrated in FIG. **1**, the content provider **104** can be associated with one or more DNS name server components that would be authoritative to resolve client computing device DNS queries corresponding to a domain of the content provider.

With continued reference to FIG. **1**, the networked computing environment **100** can further include a CDN service provider **106** in communication with the one or more client computing devices **102** and other service providers via the communication network **108**. The CDN service provider **106** illustrated in FIG. **1** corresponds to a logical association of one or more computing devices associated with a CDN service provider. Specifically, the CDN service provider **106** can include a number of Point of Presence (“POP”) locations **116**, **122**, **128** that correspond to nodes on the communication network **108**. Each CDN POP **116**, **122**, **128** includes a DNS component **118**, **124**, **130** made up of a number of DNS server computing devices for resolving DNS queries from the client computers **102**. Each CDN POP **116**, **122**, **128** also includes a resource cache component **120**, **126**, **132** made up of a number of cache server computing devices for storing resources from content providers and transmitting various requested resources to various client computers. The DNS components **118**, **124**, and **130** and the resource cache components **120**, **126**, **132** may further include additional software and/or hardware components that facilitate communications including, but not limited to, load balancing or load sharing software/hardware components.

In an illustrative embodiment, the DNS component **118**, **124**, **130** and resource cache component **120**, **126**, **132** are considered to be logically grouped, regardless of whether the components, or portions of the components, are physically separate. Additionally, although the CDN POPs **116**, **122**, **128** are illustrated in FIG. **1** as logically associated with the CDN service provider **106**, the CDN POPs will be geographically distributed throughout the communication network **108** in a manner to best serve various demographics

of client computing devices **102**. Additionally, one skilled in the relevant art will appreciate that the CDN service provider **106** can be associated with various additional computing resources, such as additional computing devices for administration of content and resources, and the like.

With further continued reference to FIG. **1**, the networked computing environment **100** can also include a network computing and storage provider **107** in communication with the one or more client computing devices **102**, the CDN service provider **106**, and the content provider **104** via the communication network **108**. The network computing and storage provider **107** illustrated in FIG. **1** also corresponds to a logical association of one or more computing devices associated with a network computing and storage provider. Specifically, the network computing and storage provider **107** can include a number of Point of Presence (“POP”) locations **134**, **142**, **148** that correspond to nodes on the communication network **108**. Each POP **134**, **142**, **148** includes a network computing component (NCC) **136**, **144**, **150** for hosting applications, such as data streaming applications, via a number of instances of a virtual machine, generally referred to as an instance of an NCC. One skilled in the relevant art will appreciate that NCC **136**, **144**, **150** would include physical computing device resources and software to provide the multiple instances of a virtual machine or to dynamically cause the creation of instances of a virtual machine. Such creation can be based on a specific request, such as from a client computing device, or the NCC can initiate dynamic creation of an instance of a virtual machine on its own. Each NCC POP **134**, **142**, **148** also includes a storage component **140**, **146**, **152** made up of a number of storage devices for storing any type of data used in the delivery and processing of network or computing resources, including but not limited to user data, state information, processing requirements, historical usage data, and resources from content providers that will be processed by an instance of an NCC **136**, **144**, **150** and transmitted to various client computers, etc. The NCCs **136**, **144**, **150** and the storage components **140**, **146**, **152** may further include additional software and/or hardware components that facilitate communications including, but not limited to, load balancing or load sharing software/hardware components for selecting instances of a virtual machine supporting a requested application and/or providing information to a DNS nameserver to facilitate request routing.

In an illustrative embodiment, NCCs **136**, **144**, **150** and the storage components **140**, **146**, **152** are considered to be logically grouped, regardless of whether the components, or portions of the components, are physically separate. For example, a network computing and storage provider **107** may maintain separate POPs for providing the NCC and the storage components. Additionally, although the NCC POPs **134**, **142**, **148** are illustrated in FIG. **1** as logically associated with a network computing and storage provider **107**, the NCC POPs will be geographically distributed throughout the communication network **108** in a manner to best serve various demographics of client computing devices **102**. Additionally, one skilled in the relevant art will appreciate that the network computing and storage provider **107** can be associated with various additional computing resources, such as additional computing devices for administration of content and resources, and the like. Even further, one skilled in the relevant art will appreciate that the components of the network computing and storage provider **107** and components of the CDN service provider **106** can be managed by the same or different entities.

With reference now to FIGS. 2-6, the interaction between various components of the networked computing environment 100 of FIG. 1 will be illustrated. Specifically, FIGS. 2-6 illustrate the interaction between various components of the networked computing environment 100 for the exchange of content between a client computing device 102 and a content provider 104 via the network computing and storage provider 107. For purposes of the example, however, the illustration has been simplified such that many of the components utilized to facilitate communications are not shown. One skilled in the relevant art will appreciate that such components can be utilized and that additional interactions would accordingly occur without departing from the spirit and scope of the present disclosure.

With reference to FIG. 2, the process can begin with the generation and processing of a browse session request from a client computing device 102 to a network computing and storage provider 107 will be described. Illustratively, the client computing device 102 may load a browser for viewing network content in response to an event or user request. Subsequent to the browser being loaded, the browser may be implemented to request a new browse session. From the perspective of the user of the client computing device, the request for the new browse session corresponds to the intended request to transmit the request to one or more corresponding content providers 104. Illustratively, this request may be generated automatically as a result of the browser loading (e.g., a request for a default or "home" page), or may be generated as a result of a user following a link or entering a network address into an address bar. As illustrated in FIG. 2, the browse session request is transmitted first to a network computing and storage provider 107. In an illustrative embodiment, the network computing and storage provider 107 utilizes a registration application program interface ("API") to accept browse session requests from the client computing device 102. The browse session request can include network address information corresponding to a requested network resource, which may be in any form, including, but not limited to, an Internet Protocol ("IP") address, a URL, a Media Access Control ("MAC") address, etc.

Subsequent to the receipt of the browse session request, the network computing and storage provider 107 may select an associated network computing component (hereinafter "NCC") point of presence (hereinafter "POP") such as NCC POP 142 to service the browse session request. The selection of the NCC POP may determine the processing and network resources available to the instantiated virtual machine. The selection of processing and network resources and the provisioning of software at the NCC POP instance may be done, at least in part, in order to optimize communication with content providers 104 and client computing devices 102.

With reference to FIG. 3, an illustrative interaction for generation and processing of a request for a network resource from a network computing and storage provider 107 to a content provider 104 will be described. As illustrated in FIG. 3, the selected NCC POP 142 may generate a browse session corresponding to one or more content providers based on a browse session request, such as the illustrative browse session request depicted in FIG. 2 above. Illustratively, instantiating a new browse session instance may include loading a new virtual machine instance and/or browser instance at the NCC POP 142, reserving or allocating device memory, storage or cache space, processor time, network bandwidth, or other computational or network resources for the new browse session.

Subsequent to initializing a new browse session instance, NCC POP 142 may provide a request for a network resource to a content provider 104 based on a network address included in the browse session request. For example, a browse session request may include a URL for a Web page, such as "http://www.xyzsite.com/default.htm." NCC POP 142 may resolve the URL to an IP address through a DNS resolver associated with the network computing and storage provider (not shown), and may request the Web page from the content provider 104 at the resolved IP address. In various embodiments, a network resource may be retrieved from any combination of content providers, content delivery network (hereinafter "CDN") servers, or caches associated with the network computing and storage provider 107. For example, the network computing and storage provider may check if a resource is stored in a local cache or in another server or service provider associated with the network computing and storage provider 107. If a network resource is stored in a local or associated location, the NCC POP 142 may retrieve the network resource from the local or associated location rather than from the third party content provider 104 or CDN service provider 106. Illustratively, the NCC POP 142 may provide requests for any number of network resources as included in the browse session request, and may obtain these network resources from any number of different sources, sequentially or in parallel.

As illustrated in FIG. 3, the content provider 104 receives the resource request from the NCC POP 142 and processes the request accordingly. In one embodiment, the content provider 104 processes the resource request as if it were originally provided by the client computing device 102. For example, the content provider 104 may select the type of content, ordering of content, or version of content according to the requirements of the requesting client computing device 102. In another embodiment, the content provider 104 may be provided with information that provides information associated with the NCC POP 142 for utilization in providing the requested content (e.g., an available amount of processing resources or network bandwidth).

Subsequent to obtaining the requested network resource from the content provider 104 (or other source designated by the content provider), the NCC POP 142 may process the network resource to extract embedded resource identifiers and gather information for determination of a remote session browsing configuration. For example, a network resource such as a Web page may include embedded CSS style information and Javascript as well as embedded resource identifiers to additional resources such as text, images, video, audio, animation, executable code, and other HTML, CSS, and Javascript files. In the process of extracting the embedded resource identifiers, the NCC POP 142 may gather information about the processed network resources for later use in the determination of a remote session browsing configuration as discussed below with reference to FIG. 4.

With reference to FIG. 4, an illustrative interaction for generation and processing of one or more requests corresponding to one or more embedded resources from a network computing and storage provider to a content provider and content delivery network is disclosed. As illustrated in FIG. 4, the selected NCC POP 142 may provide resource requests to one or more sources of content such as content provider 104 and CDN POP 116. The resource requests may correspond to embedded resources based on one or more embedded resource identifiers extracted from a requested network resource (e.g., a Web page) as described in FIG. 3 above. In various embodiments, embedded resources may be

retrieved from any combination of content providers, CDN servers, or caches associated with the network computing and storage provider **107**. For example, the network computing and storage provider may check if an embedded resource is stored in a local cache or in another server or service provider associated with the network computing and storage provider **107**. If an embedded resource is stored in a local or associated location, the NCC POP **142** may retrieve the embedded resource from the local or associated location rather than the third party content provider or CDN. Illustratively, the NCC POP **142** may provide requests for any number of embedded resources referenced by a network resource, and may obtain these embedded resources from any number of different sources, sequentially or in parallel. Subsequent to obtaining the requested resources, the NCC POP **142** may process the resources and requested content to determine a remote session browsing configuration for the processing and communication of content to the client computing device **102**.

With reference to FIG. **5**, an illustrative interaction for generation and processing of processing results and user interaction data between a network computing and storage provider and client computing device is disclosed. As previously described, in one embodiment, the respective browsers on the instantiated network computing component and the client computing device **102** can exchange browsers' session information related to the allocation and processing of the requested resources at the instantiated network computing component and client computing device. As illustrated in FIG. **5**, the selected NCC POP **142** may provide an initial processing result to the client computing device **102** over the network **108**. The initial processing result may correspond to requested network content, such as a Web page, along with associated embedded resources processed by the NCC POP **142** in accordance with a selected remote session browsing configuration as described in FIG. **4** above. The NCC POP **142** also makes a determination of which additional processes will be conducted at the NCC POP **142**, at the client computing device **102**, or both. Subsequent to receiving an initial processing result and the allocation of processes, the client computing device **102** may perform any remaining processing actions on the initial processing result as required by the selected remote session browsing configuration, and may display the fully processed content in a content display area of a browser. The client computing device **102** may process any local user interactions with local interface components or content elements locally, and may provide user interactions requiring remote processing to the network computing and storage provider **107**. The network computing and storage provider **107** may provide updated processing results to the client computing device in response to changes to the content or remote user interaction data from the client computing device.

With reference to FIG. **6**, a block diagram of the content delivery environment of FIG. **1** illustrating the generation and processing of an additional new browse session request from a client computing device to a network computing and storage provider is disclosed. As illustrated in FIG. **6**, a second new browse session request may be sent to network computing and storage provider **107** from client computing device **102** across network **108**. In an illustrative embodiment, the network computing and storage provider **107** utilizes a registration API to accept browse session requests from the client computing device **102**.

The additional browse session request may be generated by a client computing device **102** in response to a user opening up a new browser window with a new content

display area, opening a new content display area in an existing browser window (e.g., opening a new tab in a browser), requesting new network content in an existing content display area (e.g., following a link to a new network resource, or entering a new network address into the browser), or any other user interaction. For example, a user browsing a first Web page corresponding to a first browse session instance may follow a link that opens a new tab or browser window to view a second Web page. In one embodiment, any required steps of obtaining and processing content associated with the second Web page may be performed by the currently instantiated network computing component in which the browser can handle the processing of both resource requests. In another embodiment, the client computing device **102** request may be processed as a new browse session request to the network computing and storage provider **107**, including the network address of the second Web page. In this embodiment, the browser on the client computing device may not specifically request a separate browse session, and a user's interaction with the browser on the client computing device **102** may appear to be part of a same browsing session. As described above with regard to FIGS. **2** and **3**, the network computing and storage provider **107** may cause an instantiation of a network computing component for obtaining and processing content associated with the second web page. In other embodiments, a new browse session request may be generated by the client computing device **102** corresponding to sections of a network resource (e.g., frames of a Web page), individual network resources, or embedded resources themselves, data objects included in a set of content, or individual network resources.

Illustratively, the additional browse session request may include any number of pieces of data or information including, but not limited to, information associated with a user, information associated with the client computing device **102** (e.g., hardware or software information, a device physical or logical location, etc.), information associated with the network **108**, user or browser preferences (e.g., a requested remote session browse protocol, a preference list, a decision tree, or other information), information associated with the network computing and storage provider **107**, information associated with one or more pieces of requested network content (e.g., the network address of a network resource), etc. Requested content may include any manner of digital content, including Web pages or other documents, text, images, video, audio, executable scripts or code, or any other type of digital resource.

Subsequent to the receipt of the browse session request, the network computing and storage provider **107** may select an associated network computing component such as NCC POP **142** to service the browse session request. As discussed above with reference to FIG. **2**, a network computing and storage provider **107** may select an NCC POP to service a browse session request based on any number of factors, including, but not limited to available NCC POP resources (e.g., available memory, processor load, network load, etc.), a financial cost of servicing the browse session request at the NCC POP, the NCC POP location relative to a client computing device **102**, content provider **112**, or CDN POP **116**, a NCC POP cache status (e.g., whether a requested resource is already stored in an NCC POP cache), etc. In one embodiment, the network computing and storage provider **107** may select a number of NCC POPs to service a browse session request. Illustratively, although the network computing and storage provider **107** is depicted here for purposes of illustration as selecting NCC POP **142**, the network computing and storage provider **107** may select any extant

11

NCC POP to service the browse session request. For example, a single client computing device **102** may simultaneously or sequentially provide three different browse session requests to the network computing and storage provider **107** corresponding to different network resources. The network computing and storage provider **107** may select different NCC POPs for each browse session request, the same NCC POP for all three browse session requests, or any combination thereof. As discussed above, the decision whether to select a different NCC POP than was utilized for a previous or simultaneous browse session request may be made on the basis of available system resources, randomly, or according to any other factor as discussed above and with regards to FIG. 2.

FIG. 7 is a user interface diagram depicting an illustrative browser interface and display of browse session content. As described above with reference to FIG. 5, a browser **700** may have a content display area **702**, as well as one or more one or more local interface components. These local interface components may include toolbars, menus, buttons, address bars, scroll bars, window resize controls, or any other user interface controls. Illustratively, local interface components may be displayed as separate from the content display area or may be overlaid or embedded in the content display area.

Interactions with local interface components may be treated as local user interactions or remote user interactions depending on the processing required by the interaction and the remote session browsing configuration. For example, the selection of a preferences option in a browser menu may be handled entirely as a local user interaction by a browser. The processing required to display the menu, provide visual feedback regarding the selection, display the preferences window, and process the changes made to the browser preferences may be performed locally. As discussed above, processing user interactions locally may provide greater responsiveness at the browser as opposed to sending user interaction data to the NCC POP **142** for processing. As another example, when using a remote session browsing configuration that specifies extensive processing on the NCC POP **142** (e.g., a remote session browsing configuration using a remote session communication protocol such as RDP), the selection of a content refresh button in a browser toolbar may be handled both as a local user interaction and a remote user interaction. The limited processing required to provide interface feedback corresponding to the button selection may be handled at the client computing device **102** in order to provide the appearance of interface responsiveness, while the refresh command, which may require processing of the network content displayed in the content display area of the browser, may be sent as user interaction data to the NCC POP **142** for processing. The NCC POP **142** may then transmit updated processing results corresponding to the refreshed network content back to the client computing device **102** for display.

FIG. 8 is a diagram depicting illustrative browser content processing actions as a series of processing subsystems **800**. In many embodiments, a browser may process sets of content (e.g., network resources such as web pages and associated embedded resources) in a series of processing actions. Illustratively, and as described above with reference to FIGS. 3-5, a remote session browsing configuration may specify a split between processing actions performed at a network computing and storage provider (e.g., an NCC POP) and processing actions performed at a client computing device **102**. This split may designate some processing actions to be performed by each of the NCC POP and client computing device **102**, or may assign all processing actions

12

to a single device or component. For example, an NCC POP may perform all of these various processing actions at the browse session instance, and send fully processed RDP processing results to the client computing device **102** for bitmap assembly and display. Any number of different remote session browsing configurations may be used by one or more browse sessions instances running at an NCC POP.

One of skill in the relevant art will appreciate that the subsystems shown here are depicted for the purpose of illustration, and are not intended to describe a necessary order or a definitive list of browser subsystems. Various browser software components may implement additional or fewer browser subsystems than are shown here, and may order the subsystems or corresponding processing actions in any number of different ways. Although the processing subsystems **800** depicted here for purposes of illustration are directed at the processing of Web pages or other Web content, one of skill in the relevant art will appreciate that the processing of other file types or network resources may be broken up in a similar manner. For example, one of skill in the relevant art will appreciate that a similar schema may be developed for the processing of images, video, audio, database information, 3d design data, or any other file format or type of data known in the art. Similar schema may also be developed for any number of device operating system or software framework processing operations, such as scheduling, memory or file management, system resource management, process or service execution or management, etc. Further, although the HTML protocol and RDP remote session communication protocols are discussed herein for the purposes of example, one of skill in the relevant art will appreciate that a remote session browsing configuration may implement any number of remote communication protocols for any number of specified processing actions, and that a remote session browsing configuration may be formulated to perform any fraction or combination of the actions identified below at any combination of the client computing device **102** and network computing and storage provider **107**.

Illustratively, the first processing subsystem involved in the processing and display of network content is the networking subsystem **802**. Illustratively, the networking subsystem **802** may be responsible for all communication between the browser and content provider, including local caching of Web content. The networking subsystem is generally limited by the performance of the user's network. A remote session browsing configuration that splits processing actions at the networking subsystem **802** might include a remote session browsing configuration utilizing an HTML remote session communication protocol, where one or more caching or resource retrieval actions were performed at the NCC POP, but parsing and processing of the content was performed at the client computing device.

As network resources such as HTML documents are downloaded from the server they may be passed to an HTML subsystem **804** which parses the document, initiates additional downloads in the networking subsystem, and creates a structural representation of the document. Modern browsers may also contain related subsystems which are used for XHTML, XML and SVG documents. A remote session browsing configuration that splits processing actions at the HTML subsystem **804** might include a remote session browsing configuration utilizing an HTML remote session communication protocol, where an initial HTML page is processed at the NCC POP in order to extract embedded resource identifiers, but additional parsing and processing of the content is performed at the client computing device. In another embodiment, a remote session browsing configura-

tion that splits processing actions at the HTML subsystem **804** might perform initial processing to create the structural representation of the HTML document, and provides a processing result including the structural representation and associated embedded resources to the client computing device for processing.

When CSS is encountered, whether inside an HTML document or an embedded CSS document, it may be passed to a CSS subsystem **806** to parse the style information and create a structural representation that can be referenced later. Illustratively, a remote session browsing configuration that splits processing actions at a CSS subsystem **806** may construct a processing result including the CSS structural representation and HTML structural representation, and provide the processing result and associated embedded resources to the client computing device for processing.

HTML documents often contain metadata, for example the information described in a document header or the attributes applied to an element. The collections subsystem **808** may be responsible for storing and accessing this metadata. A remote session browsing configuration that splits processing actions at a collections subsystem **808** may construct a processing result including processed metadata along with any other structural representations discussed above, and provide the processing result and associated embedded resources to the client computing device for processing.

When Javascript is encountered, it may be passed directly to a JavaScript subsystem **810** responsible for executing the script. The Javascript subsystem **810** has been examined fully over the years, and may be one of the most well known browser subsystems in the art. A remote session browsing configuration that splits processing actions at a Javascript subsystem **810** may construct a processing result including an internal representation of one or more Javascript scripts, including, but not limited to state data or a representation of the script in a native or intermediate form, as well as any other processed structures or data discussed above, and provide the processing result and associated embedded resources to the client computing device for processing.

Because many JavaScript engines are not directly integrated into the browser, there may be a communication layer including the marshalling subsystem **812** between the browser and the script engine. Passing information through this communication layer may generally be referred to as marshaling. A remote session browsing configuration that splits processing actions at a marshalling subsystem **812** may construct a processing result including marshalling data as well as any other processed structures, scripts, or data discussed above, and provide the processing result and associated embedded resources to the client computing device for processing.

In some embodiments, JavaScript interacts with an underlying network resource such as a Web document through the Document Object Model APIs. These APIs may be provided through a native object model subsystem **814** that knows how to access and manipulate the document and is the primary interaction point between the script engine and the browser. Illustratively, a remote session browsing configuration that splits processing actions at a native object model subsystem **814** may construct a processing result including native object model state data or API calls as well as any other processed structures, scripts, or data discussed above, and provide the processing result and any other associated embedded resources to the client computing device for processing.

Once the document is constructed, the browser may need to apply style information before it can be displayed to the user. The formatting subsystem **816** takes the HTML document and applies styles. Illustratively, a remote session browsing configuration that splits processing actions at a formatting subsystem **816** may construct a processing result including an HTML representation with applied styles, as well as any other processed state data, API calls, structures, scripts, or data discussed above, and provide the processing result and any other associated embedded resources to the client computing device for processing.

In one embodiment, CSS is a block based layout system. After the document is styled, the next step, at a block building subsystem **818**, may be to construct rectangular blocks that will be displayed to the user. This process may determine things like the size of the blocks and may be tightly integrated with the next stage, layout. A remote session browsing configuration that splits processing actions at a block building subsystem **818** may construct a processing result including block information, as well as any other processed state data, API calls, structures, scripts, or data discussed above, and provide the processing result and any other associated embedded resources to the client computing device for processing.

Subsequent to the browser styling the content and constructing the blocks, it may go through the process of laying out the content. The layout subsystem **820** is responsible for this algorithmically complex process. Illustratively, a remote session browsing configuration that splits processing actions at a layout subsystem **820** may process the various state data, API calls, structures, scripts, or data discussed above to construct a processing result including layout information for the client computing device. Illustratively, an NCC POP may make use of various data or settings associated with the client computing device or browser (e.g., as provided in the initial browse session request) in order to generate a suitable layout for the client computing device. For example, a mobile device may provide a screen resolution and a display mode to the NCC POP. The NCC POP may base layout calculations on this screen resolution and display mode in order to generate a processing result corresponding to a content representation suitable for a browser running on the mobile device. Illustratively, in various embodiments, any other subsystem implemented by the NCC POP may make use of data associated with the client computing device or browser in generating a processing result for the client.

The final stage of the process may occur inside the display subsystem **822** where the final content is displayed to the user. This process is often referred to as drawing. A remote session browsing configuration that splits processing actions at the networking subsystem **802** might include a remote session browsing configuration utilizing an RDP remote session communication protocol, where nearly all processing is performed at the NCC POP, and a processing result including bitmap data and low level interface data are passed to the client computing device for display.

FIG. 9 is a flow diagram illustrative of a new browse session routine **900** implemented by network computing and storage provider **107** of FIG. 1. New browse session routine **900** begins at block **902**. At block **904**, the network computing and storage provider **107** receives a new browse session request from client computing device **102**. As previously described, the client computing device **102** may load a browser for viewing network content in response to an event or user request. Subsequent to the browser being loaded, the browser may be implemented request a new browse session. From the perspective of the user of the client

15

computing device, the request for the new browse session corresponds to the intended request to transmit the request to one or more corresponding content providers **104**. Illustratively, this request may be generated automatically as a result of the browser loading (e.g., a request for a default or “home” page), or may be generated as a result of a user following a link or entering a network address into an address bar. This browse session request may include one or more addresses or references to various network resources or other content requested by the client computing device **102**. In an illustrative embodiment, the browse session request is transmitted in accordance with an API.

At block **906** the network computing and storage provider **107** may select an associated NCC POP to instantiate a new browse session based on the browse session request. As discussed above with reference to FIG. 1, a network computing and storage provider **107** may include any number of NCC POPs distributed across any number of physical or logical locations. A network computing and storage provider **107** may select a NCC POP to service a browse session request based on any number of factors, including, but not limited to available NCC POP resources (e.g., available memory, processor load, network load, etc.), a financial cost of servicing the browse session request at the NCC POP, the NCC POP location relative to a client computing device **102**, content provider **104**, or CDN POP **116**, a NCC POP cache status (e.g., whether a requested resource is already stored in an NCC POP cache), etc.

In one embodiment, the network computing and storage provider **107** may select a number of NCC POPs to service a browse session request. For example, the network computing and storage provider **107** may select two NCC POPs with different logical locations in the network. Each NCC POP may independently request and process network content on the behalf of the client computing device **102**, and the client computing device **102** may accept data from the first NCC POP to return a processing result. Subsequent to being selected by the network computing and storage provider **107**, NCC POP **142** may obtain the browse session request. In one embodiment, NCC POP **142** may have the browse session request forwarded to it by a component of network computing and storage provider **107**. In another embodiment, NCC POP **142** or client computing device **102** may receive connection information allowing the establishment of direct communication between NCC POP **142** and client computing device **102**. Illustratively, NCC POP **142** may be provided with the browse session request originally provided to network computing and storage provider **107**, may be provided with a subset of information (e.g., just a network address of requested content), or may be provided additional information not included in the original browse session request.

Subsequent to the NCC POP **142** being selected, the network computing and storage provider **107** may cause the NCC POP **142** to instantiate a new browse session. Illustratively, instantiating a new browse session instance may include loading a new virtual machine instance and/or browser instance at the NCC POP **142**, reserving or allocating device memory, storage or cache space, processor time, network bandwidth, or other computational or network resources for the new browse session. Illustratively, one or more characteristics of the new browse session instance and/or browser instance may be based on client computing device **102** information included in the browse session request. For example, the browse session request may include a device type or browser type, a device screen resolution, a browser display area, or other information

16

defining the display preferences or capabilities of the client computing device **102** or browser. The NCC POP **142** may accordingly instantiate a virtual machine instance and/or a browser instance with the same or similar capabilities as the client computing device **102**. Illustratively, maintaining a virtual machine instance and/or browser with the same or similar capabilities as the client computing device **102** may allow the NCC POP **142** to process network content according to the appropriate dimensions and layout for display on the particular client computing device **102**.

In some embodiments, the NCC POP **142** may utilize an existing virtual machine instance and/or browser instance in addition to, or as an alternative to, instating a new browse session. For example, subsequent to the NCC POP **142** being selected, the network computing and storage provider **107** may cause the NCC POP **142** to associate an existing browser instance and/or virtual machine instance, such as one or more instances previously instantiated at the NCC POP **142**, with the new browse session request. Illustratively, an existing browser session and/or virtual machine instance may correspond to another browse session, remote application session, or other remote process associated with the user or client computing device **102**, or may be a previously instantiated software instance from an unrelated browse session or remote process. In other embodiments, the NCC POP **142** may instantiate a new browser or other application process in an existing virtual machine instance, or may combine the utilization of previously instantiated and newly instantiated software processes in any number of other ways. In still further embodiments, the network computing and storage provider or NCC POP **142** may instantiate any number of new virtual machine instances and/or browser instances (or make use of existing instantiated instances) based on a single browse session request.

At block **908** the network computing and storage provider **107** may provide a request for one or more network resources to a content provider or CDN service provider based on a network address included in the browse session request. In various embodiments, one or more network resources may be additionally or alternately retrieved from a cache local to the NCC POP **142** or otherwise associated with the network computing and storage provider **107**. One of skill in the art will appreciate that, in the case of other embodiments, the link or network address may correspond to a document or file stored in a digital file locker or other network storage location or at a cache component associated with the network computing and storage provider **107** or client computing device **102**. In some embodiments, the new session request may include a document or file in addition to or as an alternative to a network address. At block **910**, the network computing and storage provider **107** obtains the one or more network resources. Subsequent to obtaining the requested network resource, the NCC POP **142** may process the network resource to extract embedded resource identifiers.

At block **912**, the network computing and storage provider **107** may provide resource requests to one or more sources of content such as content providers, CDN service providers, and caches. The resource requests may correspond to embedded resources based on the one or more embedded resource identifiers extracted from the one or more network resource as described in block **910** above. At block **914**, the network computing and storage provider **107** may obtain these embedded resources from any number of different sources, sequentially or in parallel.

At block **916**, the network computing and storage provider **107** may process the one or more network resources

and associated embedded resources to determine a remote session browsing configuration for the processing and communication of content to the client computing device 102. A remote session browsing configuration may include any proprietary or public remote protocol allowing exchange of data and user interactions or requests between a client and a remote server. The remote session browsing configuration may illustratively include both a remote session communication protocol and a processing schema for providing processed (or unprocessed) content to a client computing device for display in the content display area of a browser.

Illustratively, a remote session browsing configuration may define or specify a remote session communication protocol, including, but not limited to, a network protocol, signaling model, transport mechanism, or encapsulation format for the exchange of state data, user interactions, and other data and content between the network computing and storage provider and the client computing device. Examples of remote session communication protocols known in the art include Remote Desktop Protocol (RDP), X-Windows protocol, Virtual Network Computing (VNC) protocol, Remote Frame Buffer protocol, HTML, etc. For example, RDP illustratively specifies a number of processing mechanisms for encoding client input (e.g., mouse movement, keyboard input, etc.) into protocol data units for provision to a remote computing device, and corresponding mechanisms for sending bitmap updates and low level interface information back to the client device. As another example, the HTML protocol illustratively provides a mechanism for providing files defining interface information and containing resources references from a server to a client, and a corresponding mechanism for a client computing device to provide requests for additional files and resources to the server. In one embodiment, the NCC POP 142 may provide an initial communication to the client computing device 102 after determining the remote session communication protocol. This initial communication may allow the client computing device 102 to prepare to receive communications in the selected remote session communication protocol, and, in the case of pull remote session communication protocols like HTTP, may cause the client computing device to send an initial resource request to the browse session instance running on the NCC POP 142.

Each remote session browsing configuration may additionally define a split of processing actions between the network computing and storage service (e.g., NCC POP 142) and the client computing device (e.g., client computing device 102). In one embodiment, a particular split of processing actions may be based on or mandated by a particular remote session communication protocol. In another embodiment, a remote session communication protocol may allow several different splits of processing actions depending on the implementation or configuration of the protocol. For the purpose of illustration, many pieces of network content (e.g., Web pages, video, Flash documents) may require various processing actions before being displayed on a computing device. A Web page, for example, may be parsed to process various HTML layout information and references to associated resources or embedded content such as CSS style sheets and Javascript, as well as embedded content objects such as images, video, audio, etc. The HTML and each referenced object or piece of code will typically be parsed and processed before a representative object model corresponding to the Web page may be constructed. This object model may then be processed further for layout and display in a content display area of a browser at the client computing device 102. Illustrative browser processing actions are

described in greater detail below with reference to FIG. 8. One of skill in the art will appreciate that, in the case of other embodiments or applications, various other processing actions may be required.

A remote session browsing configuration may specify that various of the processing actions required for display of piece of network content be performed at the remote computing device, such as the NCC POP 142, rather than at the client computing device 102. Network content partially (or wholly) processed at the network computing and storage provider may be referred to as a processing result. As discussed below, the split of processing actions may be associated with or linked to the remote session communication protocol used for exchanging data and client input between the NCC POP 142 and client computing device 102.

For example, a remote session communication protocol such as RDP that transmits a processing result including low level interface information and bitmaps to the client computing device 142 for display may be associated with a remote session browsing configuration that specifies performing all, or nearly all, of the necessary content processing actions at the NCC POP 142. While using RDP, the NCC POP 142 may, for example, run a full instance of a browser the NCC POP 142 and transmit a processing result consisting of bitmap updates corresponding to a representation of the displayed content to the client computing device 102. The client computing device 102, in this example, may merely be required to assemble the transmitted bitmap updates for display in the content display area of the browser, and may perform none of the processing of the actual HTML, Javascript, or data objects involved in the display of an illustrative piece of network content. As another example, a remote session browsing configuration utilizing a remote session communication protocol such as HTML may transmit network content in a largely unprocessed form. The client computing device 102 may thus perform all of the processing actions required for display of network content while the NCC POP 142 performs little or no processing.

The NCC POP 142 may base its determination of a remote session browsing configuration on any number of factors, including, but not limited to, one or more characteristics of one or more of the requested resources, content provider 104, or CDN service provider 106, one or more characteristics of the content address or domain, one or more characteristics of the client computing device 102, browser or application, user, one or more characteristics of the NCC POP 142, or one or more characteristics of the network or network connection, etc. Characteristics of requested resources may include, but are not limited to, a data format, a content type, a size, processing requirements, resource latency requirements, a number or type of interactive elements, a security risk, an associated user preference, a network address, a network domain, an associated content provider, etc. Characteristics of a content provider 104, CDN service provider 106, computing device 102, or NCC POP 142 may include, but are not limited to, processing power, memory, storage, network connectivity (e.g., available bandwidth or latency), a physical or logical location, predicted stability or risk of failure, a software or hardware profile, available resources (e.g., available memory or processing, or the number of concurrently open software applications), etc. The NCC POP 142 may further consider perceived security threats or risks associated with a piece of content or domain, preferences of a client computing device or a content provider, computing or network resource costs

(e.g., a financial cost of processing or bandwidth, resource usage, etc.), predetermined preferences or selection information, any additional processing overhead required by a particular remote session browsing configuration, a cache status (e.g., whether a particular resource is cached at a NCC POP **142**, at the client computing device **102**, or at other network storage associated with the network computing and storage provider), a predicted delay or time required to retrieve requested network content, a preferred content provider or agreements with a content provider for a particular remote session browsing configuration or level of service, a remote session browsing configuration being used for another (or the current) browse session by the same user, or any other factor.

In some embodiments, an NCC POP **142** may base a determination of a remote session browsing configuration on past behavior or practice. For example, an NCC POP **142** that has determined a remote browse session configuration for a particular resource in the past may automatically select the same remote browse session configuration when the resource is requested by the same (or potentially a different) user. As another example, a user that has a history of frequently accessing Web sites with extensive processing requirements may automatically be assigned a remote session browsing configuration that performs the majority of processing at the NCC POP **142**. In other embodiments, an NCC POP **142** may base a determination of a remote browse session configuration on predictions of future behavior. For example, an NCC POP **142** may base its determination of a remote browse session configuration for a particular resource on an analysis of past determinations made for a particular Web site, network domain, or set of related resources. A content provider that historically has provided video-heavy Web pages may be associated with a remote session browsing configuration that emphasizes video performance at the client computing device **102**. Illustratively, past historical analysis and future predictions may be considered as one or more of a number of factors on which to base the remote session browsing configuration determination process, or may be definitive in the decision making process. For example, once an NCC POP **142** determines a remote session browsing configuration for a particular content provider, it may skip the remote session browsing configuration determination process for any future resources served from the content provider. Illustratively, the NCC POP **142** may re-determine a remote session browsing configuration to be associated with the content provider after a fixed period of time, or after the NCC POP **142** has identified or determined a change in the content being served by the content provider.

In other embodiments, a network resource, Web site, network domain, content provider, or other network entity may specify or otherwise request the use of a particular remote browse session configuration in a resource tag, metadata, or other communication with an NCC POP **142**. The NCC POP **142** may treat the request as definitive, or may consider the request as one of multiple factors to be considered in the decision making process.

For example, a remote session browsing configuration utilizing a remote session communication protocol such as RDP may specify extensive processing to occur at the network computing and storage provider **107** (e.g., at NCC POP **142**) rather than at the client computing device **102**. The remote session browsing configuration may thus leverage the processing power of the NCC POP **142** to achieve lower latencies and presentation delay when dealing with network content that requires a great deal of pre-processing

(e.g., content with a great deal of CSS or Javascript information defining page layout). The NCC POP **142** may therefore select a remote session browsing configuration that performs a substantial amount of processing at the network computing and storage provider **107** and utilizes RDP or a similar remote session communication protocol for communication of processing-intensive content. Conversely, a remote session browsing configuration that utilizes a remote session communication protocol such as HTML may specify extensive processing at the client computing device **102** rather than at the network computing and storage provider **107**. The remote session communication protocol may thus achieve smaller delays and smoother presentation when presented with simple network content that requires very little processing or network content that requires rapid change in displayed content after its initial load. For example, a Web page with embedded video may perform better performing the majority of processing locally and utilizing HTML rather than RDP as a remote session communication protocol. A remote session browsing configuration specifying extensive processing at the network computing and storage provider **107** must process the video at the NCC POP **142** and rapidly send screen updates (e.g. by RDP) to the client computing device **102**, potentially requiring a great deal of bandwidth and causing choppy playback in the browser, while a remote session browsing configuration specifying local processing may provide raw video information directly to the client computing device **102** for display (e.g. by HTML), allowing for client side caching and a smoother playback of content.

As a further example, the NCC POP **142** in communication with a client computing device **102** with extremely limited processing power may elect to use a remote session browsing configuration that requires very little processing by the client computing device, for example, using RDP to transmit NCC POP **142** processed results. Conversely, an NCC POP **142** providing an extremely interactive Web page may elect to use a remote session browsing configuration that allows the client computing device **102** to handle user interactions locally in order to preserve interface responsiveness, for example, using HTML to transmit substantially unprocessed data. As a still further example, a NCC POP **142** may base the determination of a remote session browse configuration on preferences provided by the client computing device **102**. A client computing device **102** may illustratively include preferences for a remote session browse configuration in an initial browse session request, or at any other time. The NCC POP **142** may utilize these preferences as an alternative to, or in addition to any other factor or decision metric. Illustratively, allowing the client computing device **102** to set or influence the selection of a remote session browse configuration allows the NCC POP **142** to take user preferences in account when determining a remote session browse configuration. For example, a user worried about initial page load times may prefer to use a remote session browsing configuration heavy on remote processing and utilizing an RDP remote session communications protocol, while a user wishing to maintain an extremely responsive interface may prefer using a remote session browsing configuration that performs the majority of the processing on the client computing device **102**, for example, using an HTML remote session communication protocol.

Illustratively, the NCC POP **142** may base a determination of a remote browsing configuration on any factor or combination of factors. For example, the NCC POP **142** may select a remote session browsing configuration based on a single factor, or may assign weights to one or more factors

21

in making a determination. In some embodiments, the determination process of the NCC POP 142 may change based on one or more factors described above. For example, an NCC POP 142 communicating with a client computing device 102 over a network with a surplus of unused bandwidth may give a low weight to factors such as the network requirements of a remote browse session, and may give a higher weight to factors such as the latency of page interactions, while an NCC POP 142 communicating with a client computing device 102 over a limited bandwidth network may give a higher weight to factors dealing with the efficiency of the remote session browse protocol over a network.

In one embodiment, the NCC POP 142 may select a single remote session browsing configuration for a set of network content. For example, the NCC POP 142 may select a single remote session browsing configuration for a requested network resource such as a Web page. The NCC POP 142 may thus process the Web page together with all embedded content based on the selected remote browsing session protocol, and utilize the remote browsing session protocol to exchange user interaction data and updated browse session data for all embedded content associated with the Web page. In another embodiment, the NCC POP 142 may select different remote session browsing configurations for one or more resources in a set of network content. For example, a network resource such as a Web page may reference processing intensive embedded Javascript or CSS resources, as well as embedded video resources. The NCC POP 142 may select a first remote session browsing configuration for the Web page and all embedded resources excluding the embedded video resource, and a second remote session browsing configuration for the embedded video resource. Illustratively, this may result in the NCC POP 142 utilizing RDP to send a processing result to the client computing device 102 for display of the Web page and associated embedded resources, while utilizing HTTP to send the embedded video as a separate, unprocessed file. In one embodiment, the client computing device 102 may perform the minimal processing required to display the RDP processing result corresponding to the Web page and embedded resources, and may also perform additional processing necessary to display the embedded video, for example, overlaying the video on top of the displayed RDP representation of the Web page. Any number of remote session browsing configurations may be selected to correspond to any number of resources or objects included in a set of network content, regardless of whether resources or objects are obtained from a content provider 104 or CDN service provider 106 in one or more logical files or data structures.

Although the selection of a remote session browsing configuration is illustratively depicted herein as occurring after all network resources and associated embedded content have been obtained by the NCC POP 142, one skilled in the relevant art will appreciate that the selection of a remote session browsing configuration may be performed at any time. For example, the NCC POP 142 may select a remote session browsing configuration after receiving a new browse session request or related information from the client computing device, may select a remote session browsing configuration after obtaining a network resource, but before obtaining any associated embedded resources, or at any other time. In some embodiments, the NCC POP 142 may switch to a new remote session browsing configuration at some time subsequent to the client computing device 102 obtaining an initial processing result. Illustratively, the NCC POP 142 selecting a new remote session browsing configuration

22

ration may occur automatically after a certain time period or event or in response to a change in network conditions, NCC POP 142 or client computing device 102 load or computing resources, or any other factor described above as potentially influencing the choice of remote session browsing configuration. Illustratively, an NCC POP 142 dealing with other types or formats of information may select a remote session protocol based on any number of similar factors. For example, one of skill in the relevant art will appreciate that a similar schema may be developed for the processing of images, video, audio, database information, 3d design data, or any other file format or type of data known in the art.

The client computing device 102 may, in various embodiments, further instantiate a parallel browsing process sequentially or simultaneously with the request for a remote browse session. In one embodiment, a client computing device 102 may instantiate a traditional local browse session as known in the art (e.g., providing content requests from the browser and processing obtained resources locally) in addition to one or more remote browse instance executing at an NCC POP 142. In another embodiment, a client computing device 102 may be provided with unprocessed network resources by the NCC POP 142. Illustratively, the network resources may have been retrieved from one or more content providers, CDNs, or cache components by the NCC POP 142. The resources may be provided to the client computing device 102 to process locally in parallel with the remote browse instance executing at the NCC POP 142. In still further embodiments, the network computing and storage provider or NCC POP 142 may instantiate any number of new virtual machine instances and/or browser instances (or make use of existing instantiated instances) to process resources and/or send processing results to the client computing device 102 in parallel. Illustratively, the local browse session at the client computing device 102 and the remote browse session instance at the NCC POP 142 may execute in parallel.

In one embodiment, a local browse session executing at the client computing device 102 may obtain unprocessed content (e.g., html Web pages, embedded content, and other network resources) from the NCC POP 142 responsive to a browse session request. Illustratively, the content may have been retrieved by the NCC POP 142 from a content provider, CDN, or cache in response to the browse session request. The unprocessed content provided by the NCC POP 142 may include all the content associated with the browse session request or may supplement content existing in a cache of the client computing device, retrieved from a content provider or CDN, or obtained from some other source. In one embodiment, a client computing device 102 may obtain all requested content from a local cache, and may not obtain any unprocessed resources or content from the NCC POP 142. Subsequent to obtaining the unprocessed content, client computing device 102 may process the requested content in parallel with a remote browse session executing at the NCC POP 142. For example, as the local browse session executing at the client computing device 102 is processing the requested content, a remote browse session executing at the NCC POP 142 may be processing the same content at substantially the same time. Once the NCC POP 142 has performed a set of processing actions on the content to generate a processing result (e.g., as specified by a determined remote session browsing configuration), the NCC POP 142 may provide the processing result to the client computing device 102.

For the purpose of illustration, a client computing device 102 may require a longer load time to obtain and process

requested network resources than a browse session instance running at the NCC POP 142. For example, the NCC POP 142 may obtain and process content quickly due to its position on the network and the relative processing power of the local client computing device as compared to the NCC POP 142. Even if the NCC POP 142 provides the client computing device 102 with all requested network content, the client computing device 102 may still obtain a processing result from NCC POP 142 before the local browse session has fully completed processing the requested resources. The client computing device 102 may complete any further processing steps and display the obtained processing result before completing local processing and display of the content. Illustratively, this may allow the client computing device 102 to take advantage of an NCC POP 142's quicker content load time relative to a traditional local browse session. Prior to the local browse session completing the processing all requested resources, the browser may process any user interactions locally and/or remotely as described in FIGS. 5 and 11 below.

Once the local browse session has fully obtained and processed resources corresponding to the requested content, the computing device 102 may determine whether to continue to display results obtained from the NCC POP 142 (and process user interactions at the NCC POP 142) using the determined remote session browsing configuration or switch to processing user interactions locally. Switching to process user interactions locally may include replacing a displayed representation of the requested resources based on a processing result obtained from the NCC POP 142 with a local display of the requested resources. For example, a browser may display a representation of a Web page corresponding to a processing result from the NCC POP 142 (e.g., RDP display information representing the rendered page) until the browser is finished processing and rendering the Web page locally. The browser may then replace the representation from the NCC POP 142 with the locally rendered representation of the Web page. Illustratively, replacing one representation with another representation may be transparent to the user. For example, the local and NCC POP 142 representations of the Web page may be identical or substantially identical. In one embodiment, when the NCC POP 142 representation of the web page is displayed, the browser may send various user interactions with the displayed page to the NCC POP 142 for processing. When the locally rendered version of the Web page is displayed, user interactions may be processed locally at the browser. Illustratively, the determination of which representation of the requested resources to display (e.g., local or from the NCC POP 142) may be based on any of the same factors described with reference to determining a remote session browse protocol in above.

In one embodiment, the client computing device 102 may switch to processing user interactions locally as soon as local resources are fully loaded. Illustratively, the remote browse session instance running at the NCC POP 142 may be terminated after switching to local processing, or the remote browse session instance may be maintained as a backup in case of unresponsiveness or a failure with regards to the local browse session. For example, the client computing device 102 may process user interactions locally, as well as sending remote user interaction data to the NCC POP 142 in accordance with the selected remote session browsing configuration. The remote user interaction data may be used by the NCC POP 142 to keep the remote browse session instance fully in parallel with the local browse process being executed by the browser at the client computing device 102.

As long as the local browse session continues to handle user interactions, the NCC POP 142 may either refrain from sending updated processing results, or may send updated processing results ignored by the client computing device 102. If a problem develops with the local browse session at the client computing device 102, updated processing results may be provided to the client computing device 102 from the NCC POP 142 for processing and display in lieu of the local browse session. Illustratively, this switch from the local browse session to remote processing may be transparent to the user. In some embodiments, the client computing device 102 may switch from a local browse session to a remote browse session instance based on factors other than unresponsiveness or failure at the local browser. For example, the client computing device 102 or network computing and storage component 107 may select between a remote and local browse session based on any of the factors enumerated with regards to determining a remote session browse protocol above.

In another embodiment, the client computing device 102 may continue to process and display updated processing results from the NCC POP 142 even after the local browse session has fully loaded the requested content. The client computing device 102 may terminate the local browse session or may run the local browse session in parallel as a backup process in the converse of the example provided above. It should be appreciated that although the local browse session is described here for the purpose of illustration as being slower to load than the remote browse session instance, in some embodiments the local browse session may load the content faster than the remote browsing session, in which case the browser may process user interactions locally until the remote browse process has fully loaded the requested content. In some embodiments, the client computing device 102 may display and process user interactions through whichever browse session, local or remote, loads the requested content first.

In various other embodiments, the network computing and storage provider 107 may instantiate multiple remote browse session instances to run in parallel in addition to or as an alternative to instantiating a local browse session. Illustratively, these parallel browse session instances may utilize any of the same or different remote session browse protocols, and may act as backups in the manner described above with regard to a local browse session, or may be used and switched between as alternatives in order to maximize browser performance at the client computing device 102. For example, in response to one or more browse session requests, the network computing and storage provider 107 may instantiate a browse session instance running on a first NCC POP and utilizing an RDP protocol as well as browse session instance running on a second NCC POP utilizing an X-Windows protocol. The client computing device 102 or the network computing and storage provider 107 may determine which browse session instance and protocol should be used based on performance or resource usage considerations as described with regards to determining a remote session browse protocol above.

With continued reference to FIG. 9, at block 918, the network computing and storage provider 107 may process the obtained content, including the one or more requested network resources and embedded network resources, according to the determined remote session browsing configuration to generate an initial processing result. At block 920, the network computing and storage provider 107 may provide the initial processing result to the client for further processing and display in the content display area of the

25

browser. For the purposes of further example, an illustrative client new browse session interaction routine **1000** implemented by client computing device **102** is described below with reference to FIG. **10**. At block **922**, the start new browse session routine **900** ends.

FIG. **10** is a flow diagram illustrative of a client new browse session interaction routine **1000** implemented by client computing device **102**. New browse session interaction routine **1000** begins at block **1002** in response to an event or user request causing the client computing device **102** to load a browser for viewing network content. At block **1004**, the client computing device loads locally managed components of the browser, including all local interface components. As described above with reference to FIGS. **5** and **7**, local interface components may include toolbars, menus, buttons, or other user interface controls managed and controlled by the software browser application or any other process executing or implemented locally at the client computing device. At block **1006**, the client computing device **102** provides a request for a new browse session instance to the network computing and storage provider **107**. From the perspective of the user of the client computing device, the request for the new browse session corresponds to the intended request to transmit the request to one or more corresponding content providers **104**. In other embodiment, the new session request may correspond to a request to load a file or other document (e.g., a request to load an image in a photo-editing application, etc.). Illustratively, the request may be generated automatically as a result of the browser loading (e.g., a request for a default or “home” page), or may be generated as a result of a user following a link or entering a network address into an address bar. As illustrated with respect to FIG. **2**, the browse session request is transmitted first to a network computing and storage provider **107**. In an illustrative embodiment, the network computing and storage provider **107** utilizes a registration API to accept browse session requests from the client computing device **102**.

A browse session request may include any number of pieces of data or information including, but not limited to, information associated with a user, information associated with the client computing device **102** or software on the client computing device (e.g., hardware or software information, a device physical or logical location, etc.), information associated with the network **108**, user or browser preferences (e.g., a requested remote session browse protocol, a preference list, a decision tree, or other information), information associated with the network computing and storage provider **107**, information associated with one or more pieces of requested network content (e.g., the network address of a network resource), etc. For example, a browse session request from the client computing device **102** may include information identifying a particular client computing device hardware specification or a hardware performance level, latency and bandwidth data associated with recent content requests, a desired security level for processing different types of content, a predetermined preference list of remote session browse protocols, and one or more network addresses corresponding to requested network resources, among others. In another example, the browse session request can include information identifying a client computing device **102** screen resolution, aspect ratio, or browser display area in the browse session request may allow the network computing and storage provider **107** to customize the processing of network content for display on the client computing device. As previously described, the browse session request can include network address information corresponding to a requested network resource,

26

which may be in any form including, but not limited to, an Internet Protocol (“IP”) address, a URL, a Media Access Control (“MAC”) address, etc. In one embodiment, the request for a new browse session instance may correspond to the network computing and storage provider receiving a request for a new browse session instance at block **904** of FIG. **9** above.

At block **1008**, the client computing device **102** obtains an initial processing result from the network computing and storage provider **107**. Illustratively, the format and data included in the initial processing result may vary based on the remote session browsing configuration selected by the network computing and storage provider **107**. In one embodiment, the initial processing result may include or be preceded by data informing the client computing device **102** of the choice of remote session browsing configuration and/or establishing a connection over the remote session communication protocol corresponding to the selected remote session browsing configuration. As discussed above with reference to FIGS. **8** and **9**, the obtained initial processing result may include requested content with one or more processing actions performed by the network computing and storage provider **107**. Subsequent to obtaining the initial processing result, the client computing device **102** may perform any remaining processing actions on the initial processing result at block **1010**.

At block **1012**, the client computing device **102** displays the content corresponding to the processed initial processing result. For example, the client computing device **102** may display the processed client in the content display area **702** of a browser **700** as described in FIG. **7** above. In one embodiment, the processing result may only include display data corresponding to content displayed by a browser, and may not include display data corresponding to, for example, the interface controls of a browser instance at the NCC POP **142**, the desktop of a virtual machine instance corresponding to the browse session, or any other user interface of the NCC POP **142**. For example, the NCC POP **142** may process a Web page and associated content for display via RDP in a browser instance running in a virtual machine instance at the NCC POP **142**. The browser instance may have one or more interface elements such as toolbars, menus, scroll bars, etc., in addition to the displayed Web page. The NCC POP **142** may send an RDP processing result corresponding to the displayed Web page only, without any of the interface elements associated with the browser. Illustratively, including an RDP processing result corresponding to the displayed Web page only may allow the browser at the client computing instance **102** to display the Web page by assembling the RDP processing result in the content display area of the browser without any further processing. In another embodiment, the RDP processing result may include a full virtual machine desktop and browser window corresponding to the full interface displayed at the NCC POP **142** browse session instance. The client computing device may automatically identify the area of the RDP processing result corresponding to the requested content, and may display only this area in the content display area of the browser.

At block **1014**, the client computing device **102** processes local and remote user interactions. An illustrative routine for processing user interactions is provided below with reference to FIG. **11**. At block **1016** the routine ends. Illustratively, a browse session instance instantiated by the network computing content provider **107** may terminate when a browser window or content display area is closed, may terminate when a remote session browse protocol is replaced by a parallel process at the client computing device **102**, or

27

may terminate in accordance with a timer or other event. Illustratively, if a browse session has terminated automatically due to a time-out but has associated content still displayed in a browser at the client computing device 102, later attempts by the user to interact with the content may result in a new browse session request being provided to the network computing and storage service provider 107 to start a new browse session according to the last state of the terminated session. Illustratively, terminating a remote browse session after a time-out may allow the network computing storage provider 107 to save computing resources at the NCC POP. In one embodiment, this process may be transparent to the user at client computing device 102, even though the remote browse session has been terminated during the intervening period.

FIG. 11 is a flow diagram illustrative of a process user interaction routine 1100 implemented by a client computing device 102. Process user interaction routine 1100 begins at block 1102 in response to an interaction by a user. Illustratively, process user interaction routine 1100 may begin subsequent to the display of content in a content display area of a browser interface. For example, process user interaction routine 1100 may correspond to block 1014 of FIG. 10 above.

Illustratively, the displayed content may have one or more interactive elements, such as forms, buttons, animations, etc. User interaction with these interactive elements may require processing and display of updated content in the content display area. For example, selecting an element in a drop-down menu on a Web page may require processing and may change the configuration or visual appearance of the Web page or embedded resources. Illustratively, the processing required by user interaction with the displayed content may be handled as a local user interaction at the client computing device 102 or as a remote user interaction at the NCC POP 142 depending on the remote session browsing configuration in use. For example, if a remote session browsing configuration utilizing substantial local processing (e.g., sending unprocessed files over HTML), user interactions with displayed content may typically be handled as local user interactions at the client computing device 102. Illustratively, handling user interactions with displayed content as local user interactions at the client computing device 102 may allow for better responsiveness and fewer delays with simple user interactions (e.g., selection of a radio button, or typing text into a field), as interaction data corresponding to the interaction does not need to be sent to the NCC POP 142 for processing.

As a further example, if a remote session browsing configuration utilizing heavy remote processing of content (e.g., sending processed bitmap data over RDP) is being used as the remote session browsing configuration, all user interactions with displayed content may be handled as remote user interactions. For example, user input (e.g., keyboard inputs and cursor positions) may be encapsulated in RDP protocol data units and transmitted across network 108 to the NCC POP 142 for processing. Illustratively, the NCC POP 142 may apply the user interactions to the network content and transmit processing results consisting of updated bitmaps and interface data corresponding to an updated representation of the content back to the client computing device 102. Illustratively, handling user interactions with displayed content as remote user interactions at the NCC POP 142 may have a negative impact on interface responsiveness, as data is required to pass over the network and is limited by network latency; however, user interactions that require a substantial amount of processing may perform

28

better when handled as remote user interactions, as the processing latency of the NCC POP 142 may be substantially lower than the processing latency of the client computing device 102.

In addition to a content display area for displaying network content, a browser may have one or more local interface components, such as toolbars, menus, buttons, or other user interface controls. Interactions with local interface components may be treated as local user interactions or remote user interactions depending on the processing required by the interaction and the remote session browsing configuration as further depicted in illustrative FIG. 7. For example, some local interface components may be managed locally by browser code running on the client computing device, while other local interface components may have one or more locally managed aspects (e.g., button click feedback, scroll bar redraw, etc), and one or more remote managed aspects treated as remote user interactions (e.g., page refresh, requesting a page at an address in an address bar, etc.)

At block 1104, the client computing device 102 obtains a user interaction from the user. This user interaction may be an interaction with local interface components as described in FIG. 7 and above, or may be an interaction with any interactive elements of the content displayed in the content display area of the browser, such as form fields, buttons, animations, etc. User interaction with these local interface components or interactive elements of displayed content may require local and/or remote processing depending on the nature of the component or element and the processing split specified by the remote session browsing configuration as described in FIG. 7 and above. At block 1106, the client computing device 102 determines the interaction processing requirements for the obtained user interaction. At decision block 1108, if the user interaction has local aspects (e.g., button click feedback, a change to a local browser state, a content element being processed at the client computing device, etc.) the routine 1102 moves to block 1110 to process the local aspect or aspects of the user interaction at the client computing device 102 and subsequently update the local interface components at block 1112. Illustratively, and as discussed above, aspects of the interaction and updating interface components and elements locally allows a browser to provide responsive user interfaces and content. Subsequent to processing local aspect(s) of the user interaction, or if the user interaction has no local elements (e.g., a user interaction with a content element displayed in the content display area when using a remote session browsing configuration processing entirely on the server side and utilizing an RDP remote session communication protocol) the routine 1102 moves to decision block 1114. If the user interaction has remote aspects that require processing, the routine 1102 moves to block 1116 and provides remote user interaction data to the network computing and storage provider 107. Illustratively, in the case of a heavily server side remote session browsing configuration utilizing an RDP remote session communication protocol, the remote user interaction data may include input data such as a cursor position or keyboard input encapsulated in one or more RDP protocol data units. In some embodiments of remote session browsing configurations utilizing RDP or other remote session communication protocols, particular aspects of remote user interaction data such as cursor positions may be provided to the network computing and storage provider 107 on a continuous basis, while in other embodiments of remote session browse configurations remote user interaction data

may only be provided to the network computing and storage provider 107 when associated with a user interaction that requires remote processing.

At block 1118, the client computing device 102 obtains an updated processing result from the network computing and storage provider 107, the network computing and storage provider 107 having processed the remote user interaction data to generate an updated representation of the content. At block 1120, the client computing device 102 performs any additional processing required on the updated processing result (based on the remote session browsing configuration) and at block 1122 displays the updated processing result in the content display area of the browser. At block 1124 the process user interaction routine 1102 ends. Illustratively, the routine may be executed again any number of times in response to further user interactions with the browser and displayed content.

While illustrative embodiments have been disclosed and discussed, one skilled in the relevant art will appreciate that additional or alternative embodiments may be implemented within the spirit and scope of the present invention. For example, the techniques described herein may be utilized, without departing from the scope of the present invention, to allow remote processing management in any number of other software applications and processes, including, but not limited to, image or video editing software, database software, office productivity software, 3d design software, audio and sound processing applications, etc. Additionally, although many embodiments have been indicated as illustrative, one skilled in the relevant art will appreciate that the illustrative embodiments do not need to be combined or implemented together. As such, some illustrative embodiments do not need to be utilized or implemented in accordance with scope of variations to the present disclosure.

Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

Any process descriptions, elements, or blocks in the flow diagrams described herein and/or depicted in the attached FIGURES should be understood as potentially representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of the embodiments described herein in which elements or functions may be deleted, executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those skilled in the art. It will further be appreciated that the data and/or components described above may be stored on a computer-readable medium and loaded into memory of the computing device using a drive mechanism associated with a computer readable storing the computer executable components such as a CD-ROM, DVD-ROM, or network interface further, the component and/or data can be included in a single device or distributed in any manner. Accordingly, general purpose computing devices may be

configured to implement the processes, algorithms, and methodology of the present disclosure with the processing and/or execution of the various data and/or components described above.

It should be emphasized that many variations and modifications may be made to the above-described embodiments, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims.

What is claimed is:

1. A system comprising one or more server computing devices, the system configured to at least:

execute a server-side browser application;

receive, from a client computing device executing a client-side browser application separate from the server-side browser application, a request for network content, wherein the network content comprises a base resource referencing one or more embedded resources; determine, based at least partly on a characteristic of at least one of the client computing device or the network content, a first set of processing actions to be performed by the server-side browser application, and a second set of processing actions to be performed by the client-side browser application;

process, by the server-side browser application, the network content by performing the first set of processing actions on the base resource and the one or more embedded resources to generate a processed version of the network content;

transmit an unprocessed version of the network content to the client computing device, wherein the unprocessed version comprises the base resource, and wherein the client-side browser application is configured to use the unprocessed version to cause a representation of the network content to be displayed in a content display area of the client-side browser application; and

transmit the processed version of the network content to the client computing device, wherein the client-side browser application is configured to determine whether to perform the second set of processing actions on the processed version to update display of the representation of the network content in the content display area or to continue to display the representation of the network content using the unprocessed version.

2. The system of claim 1, wherein performing the first set of processing actions in the server-side browser application comprises executing executable instructions included in the network content, wherein the executable instructions are not transmitted to the client computing device.

3. The system of claim 1, wherein the server-side browser application communicates with the client-side browser application using a display-based communication protocol that specifies mechanisms for transmitting intermediate processing results of visual display updates via a network, and wherein the display-based communication protocol further specifies mechanisms for transmitting encoded graphical user interface input via a network.

4. The system of claim 1, wherein the characteristic of the client computing device comprises at least one of processing power, available memory, available storage, available bandwidth, latency of a network connection, physical location, logical location, predicted stability or risk of failure, or software profile.

5. A computer-implemented method comprising:

receiving, by server system comprising one or more server computing devices executing a server-side

31

browser application, a request for network content from a client computing device executing a client-side browser application, wherein the network content comprises a base resource referencing one or more embedded resources, and wherein the client-side browser application includes a content display area for displaying content;

determining, based at least partly on a characteristic of at least one of the client computing device or the network content, a first set of processing actions to be performed by the server-side browser application, and a second set of processing actions to be performed by the client-side browser application;

processing, by the server-side browser application, the network content by performing the first set of processing actions on the base resource and the one or more embedded resources to generate a processed version of the network content;

transmitting an unprocessed version of the network content to the client computing device, wherein the unprocessed version comprises the base resource, and wherein the client-side browser application is configured to use the unprocessed version to cause a representation of the network content to be displayed in the content display area; and

transmitting the processed version of the network content to the client computing device, wherein the client-side browser application is configured to determine whether to perform the second set of processing actions on the processed version to update display of the representation of the network content in the content display area, or to continue to display the representation of the network content using the unprocessed version.

6. The computer-implemented method of claim 5, wherein the processed version does not include a representation of a local interface of the client-side browser application.

7. The computer-implemented method of claim 5, wherein the server-side browser application communicates with the client-side browser application using a display-based communication protocol that specifies mechanisms for transmitting intermediate processing results of visual display updates via a network, and wherein the display-based communication protocol further specifies mechanisms for transmitting encoded graphical user interface input via a network.

8. The computer-implemented method of claim 7, wherein the display-based communication protocol comprises one of Remote Desktop Protocol (RDP), X-Windows protocol, Virtual Network Computing (VNC) protocol, or Remote Frame Buffer protocol.

9. The computer-implemented method of claim 5, further comprising:

receiving, subsequent to transmitting the processed version, interaction data from the client computing device, the interaction data based at least partly on a user interaction with the representation of the network content displayed in the content display area;

modifying, using the server-side browser application, a representation of the network content based at least partly on the interaction data to generate an updated version; and

transmitting the updated version to the client computing device, wherein the client-side browser application is configured to use the updated version to cause an updated representation of the network content to be displayed in the content display area.

32

10. The computer-implemented method of claim 5, wherein the characteristic of the network content comprises at least one of a data format, a content type, a size, a processing requirement, a resource latency requirement, a number or type of interactive elements, a security risk, an associated user preference, a network address, a network domain, or an associated content provider.

11. The computer-implemented method of claim 5, further comprising:

transmitting a second processed version of second network content to the client computing device, wherein the client-side browser application is configured to perform one or more processing actions on the second processed version to cause a representation of the second network content to be displayed in the content display area of the client-side browser application; and

transmitting a second unprocessed version of the second network content to the client computing device, wherein the client-side browser application is configured to determine whether to update display of the representation of the second network content using the second unprocessed version or to continue to display the representation of the second network content using the second processed version.

12. Non-transitory computer-readable storage including stored thereon executable instructions that, when executed by a server system comprising one or more server computing devices, cause the server system to at least:

receive, by a server-side browser application executing on the one or more server computing devices, a request for network content, wherein the network content comprises a base resource referencing one or more embedded resources, and wherein the request is received from a client-side browser application executing on a client computing device remote from the one or more server computing devices;

determine, by the server-side browser application based at least partly on a characteristic of at least one of the client computing device or the network content, a first set of processing actions to be performed by the server-side browser application and a second set of processing actions to be performed by the client-side browser application;

process, by the server-side browser application, the network content by performing the first set of processing actions on the base resource and the one or more embedded resources to generate a first version of the network content;

transmit a second version of the network content to the client computing device, wherein the second version comprises the base resource, and wherein the client-side browser application is configured to use the second version to cause a representation of the network content to be displayed in a content display area; and

transmit the first version of the network content to the client-side browser application, wherein the client-side browser application is configured to determine whether to update display of the representation of the network content using the first version or to continue to display the representation of the network content using the second version.

13. The non-transitory computer-readable storage of claim 12, wherein performing the first set of processing actions comprises executing executable instructions included in the network content, wherein the executable instructions are not transmitted to the client-side browser application.

33

14. The non-transitory computer-readable storage of claim 12, wherein the first version does not include a representation of a local interface of the client-side browser application.

15. The non-transitory computer-readable storage of claim 12, wherein the client-side browser application is configured to perform the second set of processing actions to generate a representation of the network content for display in the content display area.

16. The non-transitory computer-readable storage of claim 12, wherein the instructions, when executed by the server system, further cause the server system to at least: generate, responsive to receipt of interaction data indicative of a user interaction with a representation of the network content, an updated version of the network content based at least partly on the interaction data; and transmit, to the client-side browser application, the updated version of the network content.

17. The non-transitory computer-readable storage of claim 12, wherein the server-side browser application com-

34

municates with the client-side browser application using a display-based communication protocol that specifies mechanisms for transmitting intermediate processing results of visual display updates via a network, and wherein the display-based communication protocol further specifies mechanisms for transmitting encoded graphical user interface input via a network.

18. The non-transitory computer-readable storage of claim 17, wherein the display-based communication protocol comprises one of Remote Desktop Protocol (RDP), X-Windows protocol, Virtual Network Computing (VNC) protocol, or Remote Frame Buffer protocol.

19. The non-transitory computer-readable storage of claim 12, wherein the characteristic of the network content comprises at least one of a data format, a content type, a size, a processing requirement, a resource latency requirement, a number or type of interactive elements, a security risk, an associated user preference, a network address, a network domain, or an associated content provider.

* * * * *