

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199941127 B2
(10) Patent No. 747457

(54) Title
Progressive addition lenses

(51)⁷ International Patent Classification(s)
G02B 013/18

(21) Application No: **199941127**

(22) Application Date: **1999.07.26**

(30) Priority Data

(31) Number	(32) Date	(33) Country
09/126259	1998.07.30	US

(43) Publication Date : **2000.02.24**

(43) Publication Journal Date : **2000.02.24**

(44) Accepted Journal Date : **2002.05.16**

(71) Applicant(s)
Johnson and Johnson Vision Products, Inc.

(72) Inventor(s)
Russell A. Chipman; Patrick John Reardon

(74) Agent/Attorney
**FREEHILLS CARTER SMITH BEADLE, Level 43, 101 Collins Street, MELBOURNE
VIC 3000**

Abstract

The present invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses with reduced astigmatism. The lenses are
5 composed of a surface and a compensating surface, the surface geometries of which are defined by segments of a size suitable to be defined by a tenth order x,y polynomial with Zernike coefficients.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220

AUSTRALIA

Patents Act 1990

**COMPLETE SPECIFICATION
FOR A STANDARD PATENT**

ORIGINAL

Name of Applicant:	JOHNSON & JOHNSON VISION PRODUCTS, INC.
Actual Inventors:	Russell A. CHIPMAN and Patrick John REARDON
Address for service in Australia:	CARTER SMITH & BEADLE 2 Railway Parade Camberwell Victoria 3124 Australia
Invention Title:	PROGRESSIVE ADDITION LENSES

The following statement is a full description of this invention, including the best method of performing it known to us

PROGRESSIVE ADDITION LENSES

Field of the Invention

5 The present invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses with reduced astigmatism.

Background of the Invention

 The use of ophthalmic lenses for the correction of ametropia is well known.
10 For example, progressive addition lenses ("PAL's") are used for the treatment of presbyopia. On the front, or convex, surface of a PAL, three zones are provided: a distance vision zone with a refractive power suitable for distance vision; a near vision, or add power, zone, with refractive power for near vision; and an intermediate zone between the distance and near zones, with a refractive power for
15 intermediate distance vision.

 Inherent in ophthalmic lenses, such as PAL's, is an astigmatism introduced or caused by one or more of the lens surfaces, or a lens astigmatism. In PAL's, for example, the design of the front lens surface typically is constrained by the need to
20 provide a distance zone and an add zone of maximum width connected by the intermediate zone obeying the following conditions:

$f(x, y, z)$ is continuous:

$\partial f(x, y, z) / \partial(x, y)$ is continuous; and

$\partial^2 f(x, y, z) / \partial(x^2, y^2, xy)$ is continuous over all x, y, z .

25 Such a surface inevitably introduces an astigmatism into the lens. Generally, the back, or concave, lens surface of a lens is not used to compensate for the astigmatism introduced by the front surface and, in fact, may also contribute to the lens astigmatism. Rather, the back surface typically is a spherical or toric surface intended to combine with the front surface to provide the wearer's required
30 prescription.

Any number of lens designs have been tried to reduce lens astigmatism. However, although the known designs provide some minimal decrease in the astigmatism, large areas in the lenses' peripheries still are unusable due to the
 5 astigmatism.

Brief Description of the Drawings

FIG. 1 is a diagrammatic view of a front surface of a lens of the invention.
 FIG. 2 is a plan view of a compensating surface of a lens of the invention.
 10 FIG. 3 is a side view of one embodiment of the lens of the invention.
 FIG. 4 is a depiction of the radius distribution of the overall optical zone power if a front surface of a lens of the invention.
 FIG. 5 is a plan view of a compensating surface of a lens of the invention.
 FIG. 6 is a plan view of a compensating surface of a lens of the invention.

15

Description of the Invention and its Preferred Embodiments

The present invention provides lenses, as well as methods for their design and production, in which lens astigmatism, or the astigmatism caused by one or more surfaces of the lens, is reduced. For purposes of the invention, by "lens" or
 20 "lenses" is meant any ophthalmic lens including, without limitation, spectacle lenses, contact lenses, intraocular lenses and the like. Preferably, the lens of the invention is a spectacle lens and, more preferably, the spectacle lens is a progressive addition lens, or a lens in which one or more surfaces provide zones with refractive power suitable for distance, near and intermediate vision.

25

In the lenses of the invention, reduction of lens astigmatism is achieved by use of a compensating surface that compensates for the astigmatism introduced by the one or more of the other lens surfaces. By "compensate" is meant that the lens astigmatism is reduced by about 15 percent or greater, preferably about 25 percent
 30 or greater, more preferably about 35 percent or greater of the nominal add power, or desired add power, of the lens. In one embodiment, the invention comprises,

consists essentially of, and consists of a lens having an astigmatism caused by at least one surface of the lens, the lens comprising, consisting essentially of, and consisting of a front surface and a compensating surface that compensates for the lens astigmatism.

The lenses of the invention may be made of any known material suitable for their construction. If the lens is of a homogeneous composition, meaning that the lens material is of a uniform refractive index, the compensating surface may be the back surface of the lens. For example, the lens may have a toroidal, aspheric compensating surface designed to compensate for the astigmatism introduced by the front lens surface.

Alternatively, the lens may be multilayered, the compensating surface between the front and back lens surfaces. Thus, in another embodiment the invention comprises, consists essentially of, and consists of a lens having an astigmatism caused by at least one surface of the lens, the lens comprising, consisting essentially of, and consisting of, a front surface, a back surface, and a compensating surface that compensates for the lens astigmatism. The back surface may be of any desired shape such as spherical, aspherical, cylindrical, or toroidal.

The lens of the invention is produced by the method comprising, consisting essentially of, and consisting of the steps of: a.) dividing a front surface of a lens into a first plurality of segments, each of the plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment; b.) providing a compensating surface the compensating surface divided into a second plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment; and c.) optimizing the compensating surface to reduce the lens astigmatism.

Although, the method for producing and designing the lens of the invention may be used to design any lens, the invention will find its greatest utility in lenses that have an astigmatism producing surface, such as PAL's. Generally, in PAL's, this surface will be the front surface, but may be the back surface as well.

The design process of the invention begins with a three dimensional description of the front surface by any method known in the art. The front surface may contain the curvatures required for a PAL and be divided into distance, near and intermediate vision zones, the intermediate vision zone having a gradual change in refractive power along an eye path from the distance to the near zone.

In the present invention, the front surface is divided, or segmented, into a number of segments, shown in Fig. 1 as 101 through 125. The geometry of each segment is defined in terms of a tenth order x, y polynomial with Zernike coefficients. The number of zones, or segments, is determined by dividing the total area of the surface by the maximum area that can be covered by each segment. One ordinarily skilled in the art will recognize that this maximum area, or segment size, will depend on the portion of the surface under consideration and as well as a consideration of the maximum area that can be adequately modeled using a single, tenth order x, y polynomial with Zernike coefficients. Thus, the maximum area of a segment may vary from, for example, the distance power zone to the intermediate zone.

The coefficients of each polynomial are computed to provide the desired power profile, to minimize astigmatism, and to provide sag, or depth, across segment boundaries, and the like. These coefficients may be computed by any known method, such as by using commercially available, optical design software.

Referring to Fig. 1, the x and y coordinate axes of the front surface are orthogonal to one another and tangent to the lens surface at their origins. The sag of the surface, z, is perpendicular to the x, y plane. The tenth order polynomial may be obtained by any known optimization process, such as the use of commercial optimization software. The precise polynomial will depend on the weights placed on the various constraints defining the boundary conditions of each optimization task. These boundaries include, without limitation, sag and slope continuities with neighboring zones, minimization of Zernike coefficients, variations in power, and the like. By placing a larger weight on any given constraint, optimization is directed towards that object. For example, a segment with decreased astigmatism may be obtained if the sag continuity constraint is reduced.

The sag mismatch, or discontinuity, between segments for the front surface of the lens of the invention preferably ranges from about 0 to about 0.01 microns. A total of twenty-five zones are used in Fig. 1 covering a circular area of 23 mm in radius.

Generally, the front surface is defined in terms of a base spherical surface with sufficient power to provide the desired distance vision correction. To the base sphere is added the sag corresponding to the additional power desired at each point. It is a discovery of the invention that the use of a polynomial of an order lower than the tenth provides a poor segment fit. Also, it is a discovery that polynomials of an order higher than the tenth are problematic in that they are difficult to optimize and require a greater number of computations.

A compensating surface is then provided. The compensating surface is divided into a number of segments as shown in Fig. 2. The number and geometry of the segments being determined as for the front surface.

The purpose of the compensating surface is to reduce the lens astigmatism to by about 15 percent or greater, preferably about 25 percent or greater, more preferably about 35 percent or greater of the nominal add power of the lens. The compensating surface is defined in terms of a base sphere and point by point departures from sphericity required for the compensation desired. The geometry of each segment of the compensating surface is defined by a tenth order x, y polynomial with Zernike coefficients determined as described for the front surface and using an optimization process, such as for example one that includes a ray tracing task choosing a certain pupil diameter, and then measuring the size and shape of the image on an image surface constructed before the optimization started. The compensating surface is then optimized so that the lens astigmatism is reduced. One ordinarily skilled in the art will recognize that any number of optimization methods known in the art, as for example those disclosed in "*General Optics and Optical Design*" P. Pouroulis and J. MacDonald, Oxford Univ. Press (1997) incorporated herein by reference, may be used.

For example, trial functions may be combined with the front surface geometry and optimized to minimize the Zernike coefficients controlling the astigmatism. Optimization may be preformed by any known method, such as the use of optical design software and the assigning of appropriate weights to the Zernike coefficients that control astigmatism. Alternatively, the optimization is achieved by creating an image surface at the eye rotation point optimizing each compensating surface segment using a merit function that includes image quality or spot size at the image planes as well as the Zernike coefficients most directly controlling astigmatism.

Additional constraints also may be placed on the organization protocol, such as power as a function of x and y coordinates, and prism. The sag of each polynomial at the boundary of each segment may be such that a discontinuous of

continuous compensating surface is formed. By discontinuous is meant that the sag mismatch between segments is about 2 micron or greater. By a continuous surface is meant that the mismatch is less than about 2 microns. Preferably, a continuous surface is used. Other constraints may be placed in order to ensure that the slopes of power, astigmatism, and prism are continuous across segment boundaries.

The compensating surface is designed to provide either or both aspheric radially symmetric and radially asymmetric corrections for the radially symmetric and radially asymmetric astigmatism of the front and/or back surface. Alternatively, the compensating surface is designed to provide aspheric radially asymmetric corrections and a back surface is used to provide the radially symmetric corrections.

In the lens of the present invention, if a toric correction is required in addition to the multifocal add power, the back surface of the lens must be placed with the toric axis at a specific angular orientation with respect to the umbilical meridional. In this case, the compensating surface cannot form the lens' back surface because, the back surface cannot provide compensation for lens astigmatism. Thus, in such cases, one or more compensating surfaces between the front and back surface provide all of the lens astigmatism compensation.

In an embodiment of the present invention, the compensating surface may form the back lens surface, prior to application of any coatings, provided that no toric correction is required. The compensating surface may also be provided with radially symmetric aspheric corrections to minimize spherical aberration and further improve image quality. One ordinarily skilled in the art will recognize that the shape of the compensating surface will be determined by whether that surface is being used as the back surface of the lens or a surface intermediate the front and back surface.

The back surface of the lens of the invention is provided by defining the surface in terms of two radii of curvatures, corresponding to the base and toric curves as well as a radial aspheric component that is defined in terms of a conic section. The back surface is designed using segments defined by tenth order x, y polynomials with Zernike coefficients, as in the case of the front and compensating surfaces. The base curve of the back surface is selected to provide the spherical correction required by the prescription. In addition to providing the correct spherical and toric powers, the back surface may be aspherized to provide higher order corrections of the Zernike coefficients, such as the third order correction for coma, or the fourth order correction for spherical aberration. It is known by those ordinarily skilled in the art that the quality of the retinal image is significantly affected by aberrations arising from higher order Zernike coefficients, in addition to the lower order coefficients controlling defocus and astigmatism.

The lens of the invention may be made by any convenient method. Preferably, the lens is made by fabricating a lens that has a front surface of a specified geometry and a compensating surface with the desired geometry. The optical material used to form the lens of the invention may be any melt processable thermoplastic resin, including without limitation a polycarbonate of bisphenol-A, or a thermoset resin, including without limitation diethylene glycol bisallyl carbonate. The material may be formed into a lens by any known method, such as injection, compression, or cast molded, or a combination thereof, using any convenient means of polymerization.

In the case in which a back surface is provided in addition to the compensating surface, the lens may be formed by any known method. Preferably, a preform, that is a front surface and a compensating surface with the desired geometries, is placed with its concave surface in juxtaposition with a toric mold the molding surface of which is designed to provide the desired back surface geometry,

such as a toroidal, aspheric surface. The space between the preform and mold is filled with a polymerizable resin which is then polymerized to form a rigid, adherent layer permanently attached to the preform. The angular orientation between the principal meridian on the front surface and the toric axis of the mold may be adjusted prior to initiating polymerization so that the toric axis formed is at the desired orientation. In a preferred embodiment, the back surface provides only toric correction, although one ordinarily skilled in the art will recognize that it is possible to add any desired geometry by adding surface castings to the back surface.

In an alternative embodiment of the invention, a layer is provided that is bounded by the front surface and the compensating surface that is fabricated of an optical material of a high refractive index, meaning of a refractive index of at least 1.57. Suitable materials include, without limitation, polycarbonate, thermoset materials incorporating high index monomers, such as styrenes, 4-vinyl anisole, divinyl benzene, acrylate and methacrylate terminated monomers containing aromatic moieties such as alkoxylated bisphenol-A mono- and diacrylate, acrylate terminated aromatic polyurethanes, aromatic epoxides, or thermoplastic materials such as aromatic polyethers, polysulfides, and polyetherimides. A second layer bounded by the compensating surface and the back lens surface is provided that is fabricated of a material with a refractive index of less than about 1.57. The efficiency of compensation provided by the compensating surface will depend on the difference of the refractive indices of the two layers. The departure from sphericity, as measured by sag required for compensation, increases with the difference in refractive indices of the layers. In the embodiment, some or all of the desired spherical power may be provided by the layer bound by the front and compensating surfaces and the toric power may be provided by the layer bound by the compensating and back surface. The difference in refractive indices used preferably is the maximum that is obtainable considering the material selected and the need to minimize interfacial reflection.

As an alternative embodiment of the lens of the invention, some or all of the compensation desired for the compensating surface may be incorporated into the front surface. The back surface is fabricated of a material having a refractive index of at least 1.57 allowing the reduction in the difference of refractive indices between the two layers to be less.

Such a lens may be formed by molding, casting, or grinding the front surface of an optical preform, the geometry of which provides some or all of the spherical and add power desired. The concave surface of the preform forms the compensating surface, which surface is molded, casted, or ground to provide the desired compensating geometry. The preform is of a material having at least a 1.57 refractive index. The back lens surface is formed on the preform by any convenient means, preferably by providing a mold and polymerizing a resin layer situated between the concave preform surface and the mold surface. The resin refractive index is selected so as to provide the desired difference in indices between the layer bound by the front and compensating surface and that bound by the compensating surface and the back surface of the lens.

20

In another alternative embodiment of the invention, one or more compensating surfaces are used to reduce the reflection from that surface and provide correction for chromatic aberration as shown in Fig. 3. Referring to Fig. 3, a front surface 31, a first compensating surface 32, and a second compensating surface 33 are provided. Back surface 34 provides toric correction. The material used for the second compensating layer 33 may be selected to have a chromatic dispersion opposite that of the material used for the first compensating layer 32. Suitable materials useful to correct for chromatic aberration are materials that incorporate chromophores strongly absorptive at near infra-red wavelengths while having little or no optical absorption in the visible wavelength range. Examples o

30

such materials include, without limitation, naphthalocyanins exhibiting strong ligand field absorption in the 900 to 1000 nm range and d_2 to d_4 metal complexes with near infra-red ligand field absorptions, e.g., Fe^{2+} , Co^{2+} , Ni^{2+} chelates, and the like.

- 5 Preferably, more than one compensating surface is used to correct for chromatic aberration.

In yet another alternative, the constraint providing sag continuity between adjacent segments of the compensating surface may be selectively removed in order
10 to further reduce astigmatism in the segments. It is important to ensure that the resulting sag discontinuity does not introduce an unacceptable level of prism jump by adjusting the weights attached to the minimization of the prism discontinuity during the optimization process until the discontinuity is equal to or less than about 0.5 diopters.

15

In yet another embodiment, one or more compensating surfaces are used, all of which surfaces are continuous, discontinuous, or a mixture thereof. In still another embodiment, the compensating surfaces each are composed of continuous and discontinuous portions.

20

The invention will be clarified further by a consideration of the following, non-limiting examples.

Examples

Example 1

A front surface of a lens of the invention was designed by dividing a 23 mm diameter surface is divided as shown in Fig 1 into twenty-five segments, 101 through 125. Each segment was defined in terms of the tenth order, Zernike polynomial set forth on Table 1. The weights attached to the minimization of sag discontinuity at the segments' borders were adjusted until the sag discontinuity was 0.01 microns. On Table 1 is listed the coefficients of the tenth order polynomial used to fit segment 101. In Fig. 4 is shown the radius distribution over the overall optical zone of the front surface. CodeV, a commercially available optical design software available from Optical Research Associates, Pasadena California, was used to model the optical performance of this optic and scale the sag values as needed in order to change the magnitude of the add power from 2.00 diopters to 1.75 diopters.

Table 1

Term	Coefficient	Term	Coefficient	Term	Coefficient
X	2.9959E-04	X^4Y^2	-1.3287E-08	X^9	-5.7194E-14
Y	1.3627E-02	X^3Y^3	3.2104E-09	X^8Y	-1.1805E-13
X^2	-3.2144E-04	X^2Y^4	-2.1453E-08	X^7Y^2	-1.3143E-13
XY	-2.6844E-05	XY^5	1.6867E-08	X^6Y^3	2.1387E-13
Y^2	-2.2985E-04	Y^6	-1.1813E-09	X^5Y^4	2.9089E-14
X^3	-1.2719E-06	X^7	3.1168E-11	X^4Y^5	-1.2660E-13
X^2Y	-4.6118E-05	X^6Y	1.5823E-10	X^3Y^6	-2.1756E-14
XY^2	2.8283E-06	X^5Y^2	1.4535E-11	X^2Y^7	-1.0163E-14
Y^3	-2.3678E-05	X^4Y^3	1.7491E-10	XY^8	-1.3631E-13
X^4	-4.6537E-07	X^3Y^4	4.0348E-12	Y^9	3.6008E-13
X^3Y	-3.9656E-07	X^2Y^5	7.3962E-10	X^{10}	4.6851E-15
X^2Y^2	5.6116E-06	XY^6	7.6436E-11	X^9Y	2.8582E-14
XY^3	-1.5922E-07	Y^7	-1.8914E-10	X^8Y^2	1.0258E-14
Y^4	9.4637E-07	X^8	-5.1259E-12	X^7Y^3	1.1640E-14
X^5	-1.3593E-09	X^7Y	-1.4894E-11	X^6Y^4	-5.3647E-14
X^4Y	1.2154E-07	X^6Y^2	-1.2730E-11	X^5Y^5	2.8809E-14
X^3Y^2	1.3703E-09	X^5Y^3	-1.0932E-11	X^4Y^6	-4.3787E-15
X^2Y^3	-1.1170E-07	X^4Y^4	5.0458E-11	X^3Y^7	3.9563E-14
XY^4	-1.9973E-08	X^3Y^5	-1.8795E-11	X^2Y^8	-5.3160E-14
Y^5	4.2527E-08	X^2Y^6	4.7034E-11	XY^9	4.0808E-15
X^6	2.1750E-09	XY^7	-5.5050E-12	Y^{10}	6.3549E-15
X^5Y	3.3402E-09	Y^8	-1.3198E-12		

Example 2

5 Fig. 5 illustrates the x and y coordinates of the segments that constitute a compensating surface of the invention. Segment 51 contains the optical center of the optic and is the channel with a blend zone to the spherical section. Segment 52 is the distance zone and is left spherical. Segment 51 is described by the tenth order polynomial set forth on Table 2 obtained by optimizing this segment for minimum
 10 astigmatism and best image quality at an image surface as described above. The optimization protocol assigned specified weights to sag constraints at the top, $y = 10.0$, line, second order derivatives using the continuity conditions shown on Table 1, Zernike coefficients, and the spot size of the image formed at the image surface. The sag discontinuity with the channels segment 602 was maintained to a value of
 15 0.01 microns. On Table 2 is listed the coefficients of the polynomial developed to describe segment 53. The wings, segments 54 and 55, are tenth order polynomials optimized with sag, slopes, Zernike coefficients and spot size at the image surface.

20

25

30


Table 2

Term	Coefficient	Term	Coefficient	Term	Coefficient
X^0	4.0730E-03	X^1	-1.1190E-03	X^2	-1.7264E-03
X^3	-1.1712E-04	X^4	-1.2035E-04	X^5	3.5938E-05
X^6	4.4477E-06	X^7	2.9691E-07	X^8	1.1208E-08
X^9	2.2584E-10	X^{10}	1.8916E-12	Y	-5.9233E-02
XY	-1.0295E-02	X^2Y	-1.1153E-03	X^3Y	-4.9870E-07
X^4Y	-1.1567E-04	X^5Y	-1.1316E-05	X^6Y	-8.3565E-07
X^7Y	-3.0455E-08	X^8Y	-5.9808E-10	X^9Y	-4.9098E-12
Y^2	-1.0978E-04	XY^2	-9.1776E-05	X^2Y^2	1.9888E-05
X^3Y^2	1.3878E-05	X^4Y^2	2.6856E-06	X^5Y^2	2.4296E-12
X^6Y^2	1.1505E-08	X^7Y^2	2.4296E-10	X^8Y^2	2.7402E-07
Y^3	5.9516E-05	XY^3	-9.1729E-07	X^2Y^3	-3.9879E-05
X^3Y^3	-6.1659E-06	X^4Y^3	-4.9074E-07	X^5Y^3	-2.1523E-08
X^6Y^3	-4.9346E-10	X^7Y^3	-4.6135E-12	Y^4	-2.7018E-06
XY^4	-1.0059E-06	X^2Y^4	-1.8065E-7	X^3Y^4	-7.8954E-09
X^4Y^4	1.0659E-06	X^5Y^4	1.4961E-11	X^6Y^4	2.7573E-13
Y^5	-1.3605E-06	XY^5	-4.998E-07	X^2Y^5	-5.169E-08
X^3Y^5	-2.9916E-09	X^4Y^5	-8.5253E-11	X^5Y^5	-9.2168E-13
Y^6	-2.1353E-09	XY^6	-6.8412E-09	X^2Y^6	5.5626E-10
X^3Y^6	-2.0654E-11	X^4Y^6	-3.1664E-13	Y^7	-3.6560E-10
XY^7	-8.5806E-12	X^2Y^7	-4.2276E-13	X^3Y^7	9.0083E-14
X^8	-1.3447E-11	XY^8	8.6794E-13	X^2Y^8	3.0496E-14
Y^9	-5.3970E-14	XY^9	-5.0927E-15	Y^{10}	-2.0114E-14

Example 3

- 5 In Fig. 6 is shown a discontinuous compensating surface of the invention, or surface with a sag discontinuity exceeding about 2 microns. The spherical zone is represented by segment 601 and channel 602, having an upper blend zone. The 601 segment is spherical and the 602 segment is described by a tenth order polynomial obtained by optimizing this segment for minimum astigmatism and best image
- 10 quality at an image surface. The optimization protocol assigned specified weights to sag constraints at the top, $y = 10.0$ line, second order derivatives the continuity conditions of which are as described in Table 1, Zernike coefficients, and the spot size of the image formed at the image surface. Similarly, the add power zone segment 603 was described by a tenth order polynomial maintaining the sag
- 15 discontinuity with the channel segment 602 to below the value of 0.01 microns. The

wings, 604 and 613, are horizontal strips optimized with weight on the sag constraint, allowing the sag discontinuity to rise to a maximum specified value of 15
5 microns, while constraining the first derivatives as well as the second derivatives and the Zernike coefficients. The weight on prism continuity is relaxed to allow prism discontinuity up to a maximum level of 0.25 diopters.



THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a compensating surface wherein the compensating surface compensates for the lens astigmatism, the compensating surface comprising a plurality of segments wherein each of the plurality of segments is defined by a tenth order x, y polynomial with Zernike coefficients.
2. The lens of claim 1 wherein the lens is a spectacle lens.
3. The lens of claim 2 wherein the spectacle lens is a progressive addition lens.
4. The lens of claim 1 further comprising at least one additional compensating surface wherein the at least one additional compensating surface compensates for the lens astigmatism.
5. The lens of claim 4 wherein one of the at least one additional compensating surface is a discontinuous surface.
6. A lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a discontinuous compensating surface wherein the compensating surface compensates for the lens astigmatism, the compensating surface comprising a plurality of segments wherein each of the plurality of segments is defined by a tenth order x, y polynomial with Zernike coefficients.
7. The lens of claim 6 wherein the lens is a progressive addition spectacle lens.
8. The lens of claim 6 further comprising at least one additional compensating surface wherein the at least one additional compensating surface compensates for the lens astigmatism.



9. The lens of claim 8 wherein one of the at least one additional compensating surface is continuous.

10. The lens of claim 7 further comprising at least one additional compensating surface wherein the at least one additional compensating surface compensates for the lens astigmatism.

11. The lens of claim 10 wherein one of the at least one additional compensating surface is continuous.

10

12. A lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a continuous compensating surface wherein the compensating surface compensates for the lens astigmatism, the compensating surface comprising a plurality of segments wherein each of the plurality of segments is defined by a tenth order x, y polynomial with Zernike coefficients.

15

13. The lens of claim 12 wherein the lens is a progressive addition spectacle lens.

20

14. The lens of claim 12 further comprising at least one additional compensating surface wherein the at least one additional compensating surface compensates for the lens astigmatism.

25

15. The lens of claim 14 wherein one of the at least one additional compensating surface is discontinuous.

16. The lens of claim 13 further comprising at least one additional compensating surface wherein the at least one additional compensating surface compensates for the lens astigmatism.



17. The lens of claim 16 wherein one of the at least one additional compensating surface is discontinuous.

5 18. A method for providing a lens comprising the steps of:

10 a) dividing a front surface of a lens into a first plurality of segments, each of the plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define the geometry for each segment;

15 b) providing a compensating surface the compensating surface divided into a second plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment wherein the compensating surface compensates for the lens astigmatism; and

20 c) optimizing the compensating surface to reduce a lens astigmatism of the lens.

1 June 2001

FREEHILLS CARTER SMITH BEADLE

Patent Attorneys for the Applicant:

JOHNSON & JOHNSON VISION PRODUCTS, INC

25



30 9 99 4 1127

FIG. 1






FIG. 2

FIG. 3



30 9 99 4 1127

FIG. 4





FIG. 5

FIG. 6