



(51) International Patent Classification:
G06F 3/06 (2006.01) **G06F 13/10** (2006.01)
G11B 20/12 (2006.01) **G11B 27/11** (2006.01)
G11B 27/30 (2006.01)

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HOSTETTER, David G.** [US/US]; 120 Vista Lane, Louisville, Colorado 80027 (US). **MCCALLISTER, Ryan P.** [US/US]; 835 Lawson Way, Erie, Colorado 80516 (US).

(21) International Application Number: PCT/US2012/022884

(74) Agents: **BIR, David S.** et al.; Brooks Kushman P.C., 1000 Town Center, Twenty-Second Floor, Southfield, Michigan 48075 (US).

(22) International Filing Date: 27 January 2012 (27.01.2012)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Filing Language: English


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,

(26) Publication Language: English

(30) Priority Data: 13/018,176 31 January 2011 (31.01.2011) US

(71) Applicant (for all designated States except US): **ORACLE INTERNATIONAL CORPORATION** [US/US]; 500 Oracle Parkway, Redwood City, California 94065 (US).

(54) Title: SYSTEM AND METHOD FOR STORING DATA WITH HOST CONFIGURATION OF STORAGE MEDIA



(57) Abstract: Systems and methods for storing and retrieving data on a magnetic tape accessed by a tape drive having an associated tape drive processor in communication with a host computer having an associated host processor include writing data to at least one partition within a logical volume having an associated number of sections designated by the host computer from a predetermined number of sections associated with the magnetic tape, wherein each partition extends across one section.

FIG. 1



UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report (Art. 21(3))*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

SYSTEM AND METHOD FOR STORING DATA WITH HOST CONFIGURATION OF STORAGE MEDIA

TECHNICAL FIELD

[0001] The present disclosure relates to systems and methods for providing configurable access to storage media.

BACKGROUND

[0002] Network servers and other host computers may use different types of peripheral storage devices having different capacities, access times, and other operating characteristics suitable for various applications. Enterprise and data center solutions may employ multiple complementary data storage devices to achieve desired data availability, reliability, security, long-term accessibility, and cost effectiveness, among other considerations. Many networks use an automated schedule to archive data for long-term storage. Long-term storage devices may be implemented using a wide variety of storage technologies including magnetic and optical disk drives, solid-state drives, tape drives, or other types of storage devices. However, compromises among performance, capacity, and cost are often required. Tape drives continue to provide cost-effective, reliable, and energy efficient long-term data storage, particularly for high-volume backups, long-life archives, disaster recovery/business continuity, compliance, and various other applications that include inactive data.

[0003] As storage media densities have increased, time required for locating and retrieving data from peripheral storage devices has also increased, particularly for sequential storage devices such as tape drives, where data is appended to previously stored data. This may adversely impact performance of any applications or processes waiting for the data. For some applications, access time to data may be more important than maximizing the usable capacity of the storage media.

[0004] Discrete tape partitioning involves dividing a storage tape into multiple discrete partitions to address the time and expense required in reclaiming storage tapes by allowing a particular partition to be rewritten once data has expired from that partition. However, data stored within a particular partition must still be appended to any previously stored data, which may affect time required for storage and subsequent retrieval of the data. Furthermore, while discrete tape partitioning has existed for many years, it has significant drawbacks and has been unpopular with

developers as it requires the host to track which partitions contain valid data as well as the locations of the data objects or host files stored within the tape partitions. The host application is involved in processing at the end of each partition to properly direct an archive device (e.g., a tape drive) to the next applicable partition in both read and write operations.

SUMMARY

[0005] A method for storing and retrieving data on a magnetic tape accessed by a tape drive having an associated tape drive processor in communication with a host computer having an associated host processor includes reading or writing data in at least one partition within a logical volume having an associated number of sections designated by the host computer from a predetermined number of sections associated with the magnetic tape, wherein each partition extends across one section.

[0006] In one embodiment, a method for archiving data from a host computer to one of a plurality of magnetic tapes loadable into a tape drive in communication with the host computer includes communicating information from the host computer to the tape drive to enable host computer configuration of an associated magnetic tape. The method also includes dividing a data area of the associated magnetic tape into a plurality of sections, each section having a plurality of partitions, each partition extending substantially entirely across an associated section, the partitions within a section arranged generally across a width of the magnetic tape, associating at least one of the plurality of sections with a logical data volume designated by the host computer, and writing data from the logical data volume to the partitions within the at least one associated section. The method may also include communicating a writable partition mask from the host computer to the tape drive, wherein writing data includes controlling writing of data using a tape drive processor such that data is written to partitions designated by the writable partition mask. The writable partition mask designates logically adjacent partitions such that the tape drive moves from one partition to a logically adjacent partition without requiring additional host computer communication. In various embodiments, writing data includes reversing tape direction at section boundaries to write data in a serpentine fashion within the at least one section assigned by the host computer to a corresponding logical volume. The host computer has flexibility to associate a subset of the plurality of sections available on the magnetic tape to balance data access time and storage capacity.

[0007] Embodiments according to the present disclosure may also include a computer data storage system having a tape drive including an associated processor and memory for writing and reading data on an associated magnetic tape, the tape drive receiving information from a host computer to enable host computer configuration of the magnetic tape, allocating a data area of the magnetic tape to a plurality of sections, each section having a plurality of partitions, each partition extending substantially entirely across an associated section, and the partitions within a section arranged generally across a width of the magnetic tape, wherein the tape drive writes data received from the host computer to at least one section associated with a logical volume designated by the host computer. The computer data storage system may also include a host computer in communication with the tape drive with the host computer including a map that associates a logical volume with at least one of the plurality of sections.

[0008] Embodiments according to the present disclosure provide various advantages. For example, systems and methods for reading and writing data to magnetic tape according to the present disclosure allow the host computer to configure the magnetic tape storage based on a selected operating point that balances data access time and storage capacity for each logical volume. Embodiments according to the present disclosure allow customers to configure a tape drive using the host computer to meet particular application needs. By managing a library of magnetic tapes, customers can have a variety of capacity/access time characteristics available for different applications. Systems and methods according to the present disclosure provide different fast access storage solutions with a single tape cartridge. The tape cartridge can be sectioned so that users have the flexibility to choose access time and capacity operating points in increments of section size associated with a particular data volume. For example, assigning only a single section to a volume provides the fastest access time to the data, but the least amount of storage capacity for the volume. Adding more sections to a volume will make access time slower, but will increase storage capacity for the volume. In addition, systems or methods according to the present disclosure may be implemented using existing magnetic tape cartridges in many existing tape drive storage systems by updating tape drive firmware without requiring additional hardware components.

[0009] The above advantages and other advantages and features of the present disclosure will be readily apparent from the following detailed description of the preferred embodiments when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] Figure 1 is a block diagram illustrating operation of a representative system or method for storing and retrieving data according to embodiments of the present disclosure;

[0011] Figure 2 is a block diagram illustrating a representative physical tape layout for a tape having a plurality of sections according to embodiments of the present disclosure;

[0012] Figure 3 illustrates a logical tape layout for a tape section having a plurality of partitions according to embodiments of the present disclosure;

[0013] Figure 4 illustrates a physical tape layout for a tape section having a plurality of partitions according to embodiments of the present disclosure;

[0014] Figure 5 illustrates a logical tape layout for a tape having multiple sections each having multiple partitions associated with a single logical volume; and

[0015] Figure 6 is a simplified block diagram or flowchart illustrating operation of a system or method for storing and retrieving data on a magnetic tape according to embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

[0016] As those of ordinary skill in the art will understand, various features of the embodiments as illustrated and described with reference to any one of the Figures may be combined with features illustrated in one or more other Figures to produce embodiments of the present disclosure that are not explicitly illustrated or described. The combinations of features illustrated provide representative embodiments for typical applications. However, various combinations and modifications of the features consistent with the teachings of the present disclosure may be desired for particular applications or implementations.

[0017] Referring now to Figure 1, a representative embodiment of a computer data storage system demonstrates operation of a system or method for storing and retrieving data from a magnetic tape according to the present disclosure. In the simplified functional block diagram of Figure 1, system 10 includes a host computer or server 12 (e.g., a mainframe server) having an associated memory 14 and microprocessor that runs a host application 16. Host computer 12 may be used to

manage or coordinate control of data storage in one or more logical data volumes that may also be referred to as virtual tape volumes (VTVs). An optional virtual storage management module 18 may be used in conjunction with one or more associated archive devices 20. Virtual storage management module 18 may reside within host computer or server 12, or it may be located independent of the server 12 at any appropriate network location depending on the particular application and implementation, for example. Archive device 20 may include one or more data storage devices 22, such as magnetic tape drives, for example. Each storage device 22 may include an associated microprocessor 24 in communication with firmware (FW) 26 and various other types of memory 28.

[0018] Virtual storage management module 18 may perform various functions associated with storing and retrieving data from archive device 20. For example, virtual storage management module 18 may include a virtual tape storage control system (VTCS) 30 that communicates with host application 16 and directs a virtual tape storage subsystem (VTSS) 32. In turn, the VTSS routes host files either to archive device 20 or to a virtual tape library 34. According to various embodiments of the present disclosure, VTVs may be assigned or allocated to corresponding sections and partitions on magnetic media associated with one or more storage tapes or cartridges 36 that are housed within a tape library 38. Archive device 20 may access tapes housed within tape library 38 and loaded or mounted manually or using any of a number of automatic devices, including robotic assemblies that assist archive device 20 in selecting, mounting, and dismounting one of the storage tapes 36, for example. Virtual tape library 34 may be used to buffer or temporarily cache VTVs, which may ultimately be written to one of more sections of storage tapes 36 as described in greater detail herein.

[0019] As also illustrated in Figure 1, host computer 12 may include a writable partition mask 40 and mapping information 42 used to manage data storage on available partitions and to allocate or associate at least one of a plurality of sections on storage tape 36 with a logical data volume designated by host computer 12 via host application 16 or related software, for example. In operation, system 10 performs a method for storing and retrieving data on a magnetic tape 36 accessed by a tape drive 22 having an associated tape drive processor 24 in communication with a host computer 12 having an associated host processor that includes reading and/or writing data in at least one partition within a logical volume having an associated number of sections designated by host computer 12 from a predetermined number of sections associated with magnetic tape 36, wherein each partition extends across one section. In one embodiment, archive device 20 and tape

drive 22 receive writable partition mask 40 from host computer 12, which designates writable partitions on magnetic tape 36. Tape drive processor 24 uses writable mask 40 received from host computer 12 to control writing data only to partitions designated by mask 40 without requiring additional communication with host computer 12.

[0020] Referring now to Figure 2, a diagram illustrating a physical tape layout for a magnetic tape having a plurality of sections configurable by a host computer according to embodiments of the present disclosure is shown. Magnetic tape 36 generally includes a beginning-of-tape (BOT) area or region 50, an end-of- tape area 52 and a data area 54. BOT 50 is a physical feature of magnetic tape 50 that can be used by tape drive 22 to detect the beginning of the data area 54. BOT 50 may also generally refer to the leader portion of magnetic tape 36 that allows the tape to be loaded, threaded through the transport and take-up reel and advanced to data region 54 for subsequent reading or writing data when the volume is mounted. Similarly, EOT 52 may be used by tape drive 22 to detect the end of data region 54 or end of tape. A separate end of data designator (not shown) may also be used. Traditional tape drives read/write data to the tape by moving the tape from BOT 50 to EOT 52 before reversing the direction of tape travel from EOT 52 to BOT 50 to read/write data in a serpentine fashion. In contrast, various embodiments for archiving data according to the present disclosure include reversing tape direction at section boundaries to read or write data in a serpentine fashion within at least one section associated with a logical volume designated by the host computer as described in greater detail herein.

[0021] Magnetic tape 36 includes a data area 54 that is divided into a plurality of sections 60, 62, 64, 66. Each section 60, 62, 64, 66 extends vertically substantially across the width of tape 36. The predetermined number of sections associated with magnetic tape 36 (four in this example) cumulatively extend across substantially the entire data portion 54 from BOT 50 to EOT 52. In one embodiment, magnetic tape 36 is implemented by a $\frac{1}{2}$ " wide magnetic tape having a data portion length of about 279 meters with each section 60, 62, 64, 66 having a section length 70 of about 69 meters. Sections 60, 62, 64, and 66, each include a plurality of partitions as generally illustrated and described with respect to Figures 3-5.

[0022] Figure 3 is a diagram illustrating a logical magnetic tape layout for a representative tape section according to embodiments of the present disclosure. Representative tape section 60 includes a plurality of partitions generally vertically stacked or arranged across the width of tape 36

as generally represented by partitions 80, 82, 84, and 86. In one embodiment, tape 36 includes automatically linked partitions (ALPs) that include information for identifying a logically adjacent partition such that reading or writing from a designated partition to the logically adjacent partition is controlled by the tape drive processor 24 (Fig. 1) rather than the host computer 12 (Fig. 1), although the host computer may communicate writable mask 40 (Fig. 1) to tape drive 22, which is stored in memory 28. Representative partitions 80, 82, 84, 86 (and all intervening partitions not explicitly illustrated) extend substantially entirely across the length of an associated section 60. The number of sections per tape and the number of partitions per section may vary by application and implementation.

[0023] Figure 4 is a diagram illustrating a physical magnetic tape layout for a representative logical volume having two sections according to various embodiments of the present disclosure. In the representative example of Figure 4, logical volume 90 includes adjacent tape sections 64, 66 each having a plurality of partitions as generally illustrated in Figures 3 and 5. As previously described, the host computer designates the number of sections to be included in a particular logical volume 90 to balance data access time and storage capacity of a particular volume. For example, defining or associating a logical volume with a single section, such as illustrated in Figure 3, would result in a smaller available storage capacity for that logical volume and faster data access as compared to associating two (or more) sections with the logical volume as illustrated in Figure 4, resulting in twice the storage capacity but longer data access times.

[0024] As also shown in Figure 4, magnetic tape 36 generally includes a plurality of data bands, generally represented by data bands 92, 94. Each data band may include a plurality of data tracks, generally represented by tracks 96, for storing data. Tape 36 may also include one or more servo tracks (not shown) that may be used in aligning the read/write heads as known. Data written to a single partition may be spread across multiple tracks within sections 64, 66 associated with a logical data volume 90, depending on the particular size of the tape, number of partitions, number of sections, etc. However, each partition is recorded in only one section. For example, partitions 80, 82 may include data recorded on tracks 100, 102, and 104, while partitions 84, 86 may include data recorded on tracks 110, 112, and 114. As generally indicated in Figure 4, the tape drive controls direction of travel of tape 36 to reverse tape direction at section boundaries associated with a logical volume to read or write data within the logical volume in a serpentine fashion. For example, track 100 is read/written from section 64 to section 66, where the tape reverses direction to read/write

track 102 from section 66 to section 64, where tape direction is again reversed to read/write track 104 from section 64 to section 66. Of course, the tape sections and partitions may be allocated such that data is recorded in a single pass per partition, or some other number of passes per partition depending on the particular application and implementation.

[0025] Figure 5 illustrates a logical tape layout for a tape having multiple sections each having multiple partitions associated with a single logical volume according to various embodiments of the present disclosure. Similar to logical volume 90 illustrated with respect to the physical layout of tape 36 in Figure 4, logical volume 124 of Figure 5 includes two adjacent sections 120, 122. Each section 120, 122 includes a plurality of partitions 130, 132, 134, 136, etc. As shown in Figures 3 and 5, each partition 80, 130, etc. fills the width of an associated section 60, 120, respectively, along a corresponding length of tape 36. Partitions 130, 132, 134, 136 are logically adjacent and also consecutively numbered in a serpentine fashion in this example. However, logically adjacent partitions may be physically separated on tape 36 and may not be consecutively numbered.

[0026] Figure 6 is a flow chart illustrating operation of one embodiment of a system or method for reading and writing data to a configurable magnetic tape according to the present disclosure. As those of ordinary skill in the art will understand, the functions represented by the block diagram may be performed by software and/or hardware. Depending upon the particular processing strategy, such as event-driven, interrupt-driven, etc., the various functions may be performed in an order or sequence other than illustrated in the Figure. Similarly, one or more steps or functions may be repeatedly performed, although not explicitly illustrated. Likewise, various functions may be omitted depending on the particular implementation. Various functions known to those of skill in the art may not be explicitly illustrated or described, but are implied by the illustrated blocks or modules. In one embodiment, the functions illustrated are primarily performed by control logic implemented by software, instructions, or code stored in a computer readable storage medium and executed by a microprocessor-based controller to control operation of the system. While generally illustrated and described with respect to a magnetic tape drive, those of ordinary skill in the art will recognize that various functions may be applicable to various other types of peripheral storage devices.

[0027] As generally illustrated in Figure 6, a system or method according to one embodiment of the present disclosure includes a host computer in communication with a tape drive for

transferring data to one of a plurality of magnetic tapes loadable into the tape drive. The system or method may include communicating information from the host computer to the tape drive to enable host computer configuration of an associated magnetic tape as represented by block 200. The system or method may also include dividing a data area of the associated magnetic tape into a plurality of sections, each section having a plurality of partitions, each partition extending substantially entirely across an associated section, the partitions within a section arranged generally across a width of the magnetic tape as represented by block 202. Dividing the data area into a plurality of partitions may be performed during writing of data to the tape, or may be performed in advance during a tape initialization process depending on the particular implementation. The system or method continue by associating at least one of the plurality of sections with a logical data volume designated by the host computer as represented by block 204, and writing data from the logical data volume to the partitions within the at least one associated section as represented by block 206.

[0028] As also illustrated in Figure 6, the system or method may include communicating a writable partition mask from the host computer to the tape drive as represented by block 208. The writable partition mask is used by the tape drive to control writing (or reading) of data using the tape drive processor such that data is written to partitions designated by the writable partition mask from the host processor without requiring additional communication with the host computer. The system and method may also include reversing tape direction at section boundaries to write data in a serpentine fashion within the at least one section of a corresponding logical volume as represented by block 210. As previously described, each partition may be written in a single pass or in multiple passes. As also previously illustrated and described, a logical volume may be associated with a single section of the tape to provide faster data access. For a single section, tape direction is reversed at each section boundary. However, when two or more sections are associated with a logical volume, tape direction is reversed at the section boundaries associated with the first and last section of the logical volume, i.e. at the logical volume boundaries as defined by the associated sections, although each partition is contained within only one section.

[0029] As the previously described representative embodiments illustrate, systems and methods for reading and writing data to magnetic tape according to the present disclosure allow the host computer to configure the magnetic tape storage based on a selected operating point that balances data access time and storage capacity for each logical volume. Embodiments according to the present disclosure allow customers to configure a tape drive using the host computer to meet

particular application needs. By managing a library of magnetic tapes, customers can have a variety of capacity/access time characteristics available for different applications. Systems and methods according to the present disclosure provide different fast access storage solutions with a single tape cartridge. The tape cartridge can be sectioned so that users have the flexibility to choose their access time and capacity operating points in increments of section size associated with a particular data volume. For example, assigned only a single section to a volume provides the fastest access time to the data, but the least amount of storage capacity for the volume. Adding more sections to a volume will make access time slower, but will increase storage capacity for the volume. In addition, systems or methods according to the present disclosure may be implemented using existing magnetic tape cartridges in many existing tape drive storage systems by updating tape drive firmware without requiring additional hardware components.

[0030] While the best mode has been described in detail, those familiar with the art will recognize various alternative designs and embodiments within the scope of the following claims. While various embodiments may have been described as providing advantages or being preferred over other embodiments with respect to one or more desired characteristics, as one skilled in the art is aware, one or more characteristics may be compromised to achieve desired system attributes, which depend on the specific application and implementation. These attributes include, but are not limited to: cost, strength, durability, life cycle cost, marketability, appearance, packaging, size, serviceability, weight, manufacturability, ease of assembly, etc. The embodiments discussed herein that are described as less desirable than other embodiments or prior art implementations with respect to one or more characteristics are not outside the scope of the disclosure and may be desirable for particular applications.

WHAT IS CLAIMED IS:

1. A method for storing and retrieving data on a magnetic tape accessed by a tape drive having an associated tape drive processor in communication with a host computer having an associated host processor, the method comprising:

reading or writing data in at least one partition within a logical volume having an associated number of sections designated by the host computer from a predetermined number of sections associated with the magnetic tape, wherein each partition extends across one section.

2. The method of claim 1 further comprising:

receiving a mask from the host computer that designates writable partitions on the magnetic tape, wherein writing data includes writing data only to partitions designated by the mask received from the host computer.

3. The method of claim 1 wherein each section extends substantially across a width of a data portion of the tape and the predetermined number of sections collectively extend substantially across a length of a data portion of the tape.

4. The method of claim 1 wherein the magnetic tape includes a predetermined number of partitions per section.

5. The method of claim 4 wherein the partitions comprise automatically linked partitions that include information for identifying a logically adjacent partition such that reading or writing from a designated partition to the logically adjacent partition is controlled by the tape drive processor.

6. The method of claim 1 wherein reading or writing data comprises reversing direction of tape travel at the end of a section.

7. The method of claim 1 further comprising associating a plurality of sections from the predetermined number of sections associated with the magnetic tape with a single logical volume.

8. The method of claim 7 further comprising maintaining a volume map within the host computer that maps logical volumes to corresponding sections of the magnetic tape.

9. The method of claim 7 wherein the plurality of sections associated with the single logical volume is less than the predetermined number of sections associated with the magnetic tape.

10. The method of claim 1 wherein the magnetic tape includes a beginning of tape portion, an end of tape portion and a data portion and wherein the tape drive processor reverses direction of tape travel before reaching the end of the data portion.

11. A method for archiving data from a host computer to one of a plurality of magnetic tapes loadable into a tape drive in communication with the host computer, the method comprising:

communicating information from the host computer to the tape drive to enable host computer configuration of an associated magnetic tape;

dividing a data area of the associated magnetic tape into a plurality of sections, each section having a plurality of partitions, each partition extending substantially entirely across an associated section, the partitions within a section arranged generally across a width of the magnetic tape;

associating at least one of the plurality of sections with a logical data volume designated by the host computer; and

writing data from the logical data volume to the partitions within the at least one associated section.

12. The method of claim 11 further comprising:

communicating a writable partition mask from the host computer to the tape drive, wherein writing data includes controlling writing of data using a tape drive processor such that data is written to partitions designated by the writable partition mask from the host processor.

13. The method of claim 12 wherein the writable partition mask designates logically adjacent partitions such that the tape drive moves from one partition to a logically adjacent partition without requiring additional host computer communication.

14. The method of claim 11 wherein writing data comprises:
reversing tape direction at section boundaries to write data in a serpentine fashion within the at least one section.
15. The method of claim 11 wherein associating at least one of the plurality of sections comprises associating a subset of the plurality of sections associated with the magnetic tape.
16. A computer data storage system comprising:
a tape drive having an associated processor and memory for writing and reading data on an associated magnetic tape, the tape drive receiving information from a host computer to enable host computer configuration of the magnetic tape, allocating a data area of the magnetic tape to a plurality of sections, each section having a plurality of partitions, each partition extending substantially entirely across an associated section, and the partitions within a section arranged generally across a width of the magnetic tape, wherein the tape drive writes data received from the host computer to at least one section associated with a logical volume designated by the host computer.
17. The computer data storage system of claim 16 further comprising:
a host computer in communication with the tape drive, the host computer including a map that associates a logical volume with at least one of the plurality of sections.
18. The computer data storage system of claim 17 wherein the host computer communicates a writable partition mask to the tape drive to designate which partitions are available for writing data.
19. The computer data storage system of claim 18 wherein the tape drive processor positions the tape to move from a designated partition to a logically adjacent partition.
20. The computer data storage system of claim 16 wherein the tape drive processor reverses tape direction at section boundaries to read or write data in a serpentine fashion within the at least one section associated with the logical volume designated by the host computer.

1/4




FIG. 1

2/4




FIG. 2




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2012/022884

A. CLASSIFICATION OF SUBJECT MATTER

INV. G06F3/06 G11B20/12 G11B27/30 G06F13/10 G11B27/11
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G11B G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 485 321 A (LEONHARDT MICHAEL L [US] ET AL) 16 January 1996 (1996-01-16) the whole document -----	1-20
X	US 5 969 893 A (BASHAM ROBERT BEVERLEY [US] ET AL) 19 October 1999 (1999-10-19) the whole document -----	1,3-7, 9-11,16, 19,20
X,P	EP 2 317 428 A2 (ORACLE AMERICA INC [US]) 4 May 2011 (2011-05-04) the whole document -----	1,2,4,5, 7-10
A,P	----- EP 2 317 428 A2 (ORACLE AMERICA INC [US]) 4 May 2011 (2011-05-04) the whole document -----	3,6, 11-20
A	US 5 982 572 A (DAHLERUD OLE CHRISTIAN [NO]) 9 November 1999 (1999-11-09) column 2, line 37 - line 56 ----- -/-	2,8,12, 17,18



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

3 April 2012

Date of mailing of the international search report

17/04/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Maetz, Arnaud

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/022884

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 789 162 B1 (TALAGALA NISHA D [US] ET AL) 7 September 2004 (2004-09-07) paragraphs [0007], [0023], [0024], [0043], [0044] ----- US 7 620 765 B1 (OHR JAMES P [US] ET AL) 17 November 2009 (2009-11-17) column 6, line 21 - line 35; figures 4-5 -----	2,8,12, 17,18
A		2,8,12, 17,18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2012/022884

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5485321	A	16-01-1996	NONE		
US 5969893	A	19-10-1999	CN	1163458 A	29-10-1997
			DE	69714324 D1	05-09-2002
			DE	69714324 T2	20-02-2003
			EP	0795862 A2	17-09-1997
			JP	3266536 B2	18-03-2002
			JP	10003753 A	06-01-1998
			SG	50792 A1	20-07-1998
			US	5969893 A	19-10-1999
EP 2317428	A2	04-05-2011	EP	2317428 A2	04-05-2011
			JP	2011096252 A	12-05-2011
			US	2011107023 A1	05-05-2011
US 5982572	A	09-11-1999	DE	69129320 D1	04-06-1998
			DE	69129320 T2	20-08-1998
			EP	0482297 A2	29-04-1992
			JP	2710717 B2	10-02-1998
			JP	4263182 A	18-09-1992
			US	5982572 A	09-11-1999
US 6789162	B1	07-09-2004	US	6789162 B1	07-09-2004
			US	7783828 B1	24-08-2010
US 7620765	B1	17-11-2009	NONE		