



US 20200233497A1

(19) **United States**(12) **Patent Application Publication**
Gray(10) **Pub. No.: US 2020/0233497 A1**(43) **Pub. Date: Jul. 23, 2020**(54) **INTERACTIVE DISPLAY WITH TACTILE
FEEDBACK**(71) Applicant: **TACTILE DISPLAYS, LLC**, Dallas,
TX (US)(72) Inventor: **R. O'Neal Gray**, Dallas, TX (US)(21) Appl. No.: **16/840,025**(22) Filed: **Apr. 3, 2020****Related U.S. Application Data**

(63) Continuation of application No. 16/430,544, filed on Jun. 4, 2019, which is a continuation of application No. 16/132,678, filed on Sep. 17, 2018, now Pat. No. 10,459,523, which is a continuation of application No. 15/369,591, filed on Dec. 5, 2016, now Pat. No. 10,216,279, which is a continuation of application No. 12/849,530, filed on Aug. 3, 2010, now Pat. No. 9,513,705, which is a continuation-in-part of application No. 12/759,410, filed on Apr. 13, 2010, now Pat. No. 8,665,228.

(60) Provisional application No. 61/353,509, filed on Jun. 10, 2010.


Publication Classification(51) **Int. Cl.****G06F 3/01** (2006.01)**G06F 3/02** (2006.01)**G06F 3/0488** (2006.01)**G09B 21/00** (2006.01)**G06F 3/041** (2006.01)**G06F 3/0489** (2006.01)(52) **U.S. Cl.**CPC **G06F 3/016** (2013.01); **G06F 3/0202**
(2013.01); **G06F 3/04886** (2013.01); **G06F****2203/04809** (2013.01); **G06F 3/041** (2013.01);**G06F 3/0489** (2013.01); **G09B 21/003**

(2013.01)

(57)

ABSTRACT

An electronic device including a housing having a first surface and a second surface, and an interactive display having a keyboard-enabled mode and a keyboard-disabled mode. The interactive display includes a first image display device disposed at the first surface that displays image data, and a physical keypad disposed at the second surface that provides tactile feedback to a user only when the interactive display is in the keyboard-enabled mode, the physical keypad being substantially smooth when the interactive display is in the keyboard-disabled mode.






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A






FIG. 6B

**FIG. 7**

**FIG. 8**




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 18A




FIG. 18B




FIG. 19

INTERACTIVE DISPLAY WITH TACTILE FEEDBACK

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 16/430,544, filed Jun. 4, 2019, entitled Interactive Display With Tactile Feedback, which is a continuation of U.S. patent application Ser. No. 16/132,678, filed Sep. 17, 2018, entitled Interactive Display With Tactile Feedback, now U.S. Pat. No. 10,459,523, which is a continuation of U.S. patent application Ser. No. 15/369,591, filed Dec. 5, 2016, entitled Interactive Display With Tactile Feedback, now U.S. Pat. No. 10,216,279, which is a continuation of U.S. patent application Ser. No. 12/849,530, filed Aug. 3, 2010, entitled Interactive Display With Tactile Feedback, now U.S. Pat. No. 9,513,705, which claims priority to U.S. Provisional Patent Application 61/353,509, filed Jun. 10, 2010, and which is a continuation-in-part of U.S. patent application Ser. No. 12/759,410, entitled Energy Efficient Interactive Display With Energy Regenerative Keyboard, filed Apr. 13, 2010, no U.S. Pat. No. 8,665,228, the contents of which are incorporated by herein by reference in their entirety.

FIELD OF THE INVENTION

[0002] The present invention relates to interactive displays for electronic devices, and in particular to an interactive display that provide tactile feedback to a user when the user applies pressure to the interactive display.

SUMMARY OF THE INVENTION

[0003] An electronic device according to an exemplary embodiment of the present invention comprises: a housing comprising a first surface and a second surface; an interactive display having a keyboard-enabled mode and a keyboard-disabled mode, the interactive display comprising: a first image display device disposed at the first surface that displays image data; and a physical keypad disposed at the second surface that provides tactile feedback to a user only when the interactive display is in the keyboard-enabled mode, the physical keypad being substantially smooth when the interactive display is in the keyboard-disabled mode.

[0004] In at least one embodiment, the first image display device displays an imaged keypad comprising imaged keys when the interactive display is in the keyboard-enabled mode.

[0005] In at least one embodiment, the electronic device further comprises a second image display device disposed at the second surface.

[0006] In at least one embodiment, the physical keypad disposed at the second surface comprises one or more physical keys that control activation of the imaged keys within the imaged keypad.

[0007] In at least one embodiment, the physical keypad disposed at the second surface comprises one or more physical keys that perform a different function from the one or more imaged keys of the imaged keypad.

[0008] In at least one embodiment, the electronic device further comprises a sensor that detects user interaction with the physical keypad disposed on the second surface; and an image generator that displays within the first image display device an imaged representation of the user interaction with the physical keypad disposed on the second surface.

[0009] In at least one embodiment, the sensor comprises one or more of the following sensor types: a motion sensor, a thermal sensor and a pressure sensor.

[0010] In at least one embodiment, the imaged representation of the user interaction comprises an imaged depiction of the user's finger or thumb interacting with the imaged keypad.

[0011] In at least one embodiment, the first and second surfaces are opposite from one another.

[0012] In at least one embodiment, the first and second surfaces are angled relative to one another.

[0013] In at least one embodiment, the first and second surfaces are adjacent to one another.

[0014] In at least one embodiment, the physical keypad comprises piezoelectric material.

[0015] In at least one embodiment, the piezoelectric material is quartz.

[0016] In at least one embodiment, the physical keypad comprises magnetostrictive material.

[0017] In at least one embodiment, the image display device is selected from one of the following types of image display devices: liquid crystal displays, digital light processor displays, plasma displays and light emitting diode displays.

[0018] In at least one embodiment, the electronic device is selected from one of the following types of electronic devices: cell phones, personal digital assistants, gaming devices, e-books, automatic teller machines and data input devices.

[0019] An electronic device according to an exemplary embodiment of the present invention comprises: a housing comprising a first surface and a second surface; and an interactive display having an interactive mode and a non-interactive mode, the interactive display comprising: an image display device disposed at the first surface of the housing that displays a user-interactive imaged keypad in at least a portion of the image display device when the interactive display is in the interactive mode and that displays other image data in the at least a portion of the image display device when the interactive display is in the non-interactive mode; a substantially transparent physical keypad disposed at the second surface of the housing that provides tactile feedback to a user indicating location of keys within the imaged keypad; a sensor that detects user interaction with the physical keypad; and an image generator that displays an imaged representation of the user interaction with the physical keypad within the imaged keypad.

[0020] In at least one embodiment, the sensor comprises one or more of the following sensor types: a motion sensor, a thermal sensor and a pressure sensor.

[0021] In at least one embodiment, the imaged representation of the user interaction comprises an imaged depiction of the user's finger or thumb interacting with the imaged keypad.

[0022] An electronic device according to an exemplary embodiment of the present invention comprises: an interactive display having an interactive mode and a non-interactive mode, the interactive display comprising: an image display device that displays a user-interactive imaged keypad in at least a portion of the image display device when the interactive display is in the interactive mode and that displays other image data in the at least a portion of the image display device when the interactive display is in the non-interactive mode; and a substantially transparent physical

keypad that provides tactile feedback to a user indicating location of one or more imaged keys within the imaged keypad in response to one or more actuators disposed below the image display device.

[0023] An electronic device according to an exemplary embodiment of the present invention comprises: a housing comprising a first surface and a second surface; and an interactive display having an interactive mode and a non-interactive mode, the interactive display comprising: an image display device disposed at the first surface of the housing that displays a user-interactive imaged keypad in at least a portion of the image display device when the interactive display is in the interactive mode and that displays other image data in the at least a portion of the image display device when the interactive display is in the non-interactive mode; and a substantially transparent physical keypad disposed at the second surface of the housing that provides tactile feedback to a user indicating location of keys within the imaged keypad.

[0024] In at least one embodiment, the first and second surfaces are opposite from one another.

[0025] In at least one embodiment, the first and second surfaces are angled relative to one another.

[0026] In at least one embodiment, the first and second surfaces are adjacent to one another.

[0027] In at least one embodiment, the image display device is structured so as to form a seal for the electronic device.

[0028] In at least one embodiment, the physical keypad comprises one or more physical keys corresponding to the imaged keys.

[0029] In at least one embodiment, the image display device and the physical keypad are integral to one another.

[0030] In at least one embodiment, the one or more physical keys are made of substantially transparent material so that the imaged keys may be viewed within the one or more physical keys.

[0031] In at least one embodiment, the imaged keypad comprises one or more sub-keypads, each of the one or more sub-keypads being selectively activated.

[0032] In at least one embodiment, one or more portions of the physical keypad are selectively activated to correspond to the one or more sub-keypads.

[0033] In at least one embodiment, the physical keypad provides tactile feedback only when the interactive display is in the interactive mode.

[0034] In at least one embodiment, the physical keypad comprises piezoelectric material.

[0035] In at least one embodiment, the piezoelectric material is quartz.

[0036] In at least one embodiment, the physical keypad is made of a magnetostrictive material.

[0037] In at least one embodiment, the image display device is selected from one of the following types of image display devices: liquid crystal displays, digital light processor displays, plasma displays and light emitting diode displays.

[0038] In at least one embodiment, the image display device is a touchscreen image display device.

[0039] In at least one embodiment, the physical keypad comprises physical keys that extend through corresponding openings in the touchscreen image display device.

[0040] In at least one embodiment, the one or more actuators move at least one of the physical keypad and the

touchscreen display device relative to one another so that the one or more physical keys protrude through the openings in the touchscreen display device when the interactive display is in the interactive mode.

[0041] In at least one embodiment, one or more of the physical keys each comprises one or more magnetic elements.

[0042] In at least one embodiment, the touchscreen display device comprises one or more charged electrical circuit elements so that movement of the one or more physical keys comprising the one or more magnetic elements relative to the charged electrical circuits elements generate electricity.

[0043] In at least one embodiment, the electronic device further comprises a protective layer disposed between the physical keypad and the at least one magnetic actuator to prevent damage to the magnetic actuator resulting from contact with the physical keys.

[0044] In at least one embodiment, the electronic device is selected from one of the following types of electronic devices: cell phones, personal digital assistants, automatic teller machines and data input devices.

BRIEF DESCRIPTION OF THE DRAWINGS

[0045] The above and related objects, features and advantages of the present invention will be more fully understood by reference to the following, detailed description of the preferred, albeit illustrative, embodiment of the present invention when taken in conjunction with the accompanying figures, wherein:

[0046] FIGS. 1A and 1B are front views of an electronic device according to an exemplary embodiment of the present invention;

[0047] FIG. 2 is a plan view of an interactive display according to an exemplary embodiment of the present invention;

[0048] FIGS. 3A and 3B are cross-sectional views of an interactive display according to an exemplary embodiment of the present invention;

[0049] FIGS. 4A and 4B are cross-sectional views of an interactive display according to another exemplary embodiment of the present invention;

[0050] FIG. 5 is a plan view of an electronic device according to an exemplary embodiment of the present invention;

[0051] FIG. 6A and 6B are plan views of an electronic device according to another exemplary embodiment of the present invention;

[0052] FIG. 7 is a flowchart showing a method of manufacturing an interactive display according to an exemplary embodiment of the present invention;

[0053] FIG. 8 is a flowchart showing a method of operation of an interactive display according to an exemplary embodiment of the present invention;

[0054] FIG. 9 is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention

[0055] FIG. 10 is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention;

[0056] FIG. 11 is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention;

[0057] FIG. 12A is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention;

[0058] FIG. 12B is a detailed cross-sectional view of a section of the interactive display shown in FIG. 12A;

[0059] FIG. 13 is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention;

[0060] FIG. 14A is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention;

[0061] FIG. 14B is a plan view of the interactive display of FIG. 14A;

[0062] FIG. 15A is a back view of an electronic device according to an exemplary embodiment of the present invention;

[0063] FIG. 15B is a front view of an electronic device according to an exemplary embodiment of the present invention;

[0064] FIG. 15C is a back view of an electronic device according to an exemplary embodiment of the present invention;

[0065] FIG. 15D is a front view of an electronic device according to an exemplary embodiment of the present invention;

[0066] FIGS. 16A and 16B are cross-sectional views of an interactive display according to an exemplary embodiment of the present invention;

[0067] FIGS. 17A is a back view of an electronic device according to an exemplary embodiment of the present invention;

[0068] FIG. 17B is a front view of an electronic device according to an exemplary embodiment of the present invention;

[0069] FIGS. 18A and 18B are cross-sectional views of an interactive display according to an exemplary embodiment of the present invention; and

[0070] FIG. 19 is a cross-sectional view of an interactive display according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

[0071] The present invention is directed to an electronic device including an interactive display having an interactive mode in which a user-interactive keypad is displayed in at least a portion of the interactive display and a non-interactive mode in which other image data is displayed in the portion of the interactive display. The interactive display includes a substantially transparent keypad portion that provides tactile feedback to allow the user to locate individual keys within the keypad portion. The present invention is applicable to any electronic device having a touchscreen display, including, for example, personal digital assistants (PDAs), cell phones, automated teller machines (ATMs), computers (including laptop and desktop computers), gaming devices, television monitors, video conferencing equipment, e-books (e.g., Amazon Kindle™ and Barnes & Noble Nook™) remote control devices and any general data input device.

[0072] FIGS. 1A and 1B are front views of an electronic device, generally designated by reference number 1, according to an exemplary embodiment of the present invention. In the present embodiment, the electronic device 1 may be, for

example, a PDA, cell phone, a gaming device or other hand-held mobile device. The electronic device 1 includes a housing 10 and an interactive display 20. The housing 10 protects the internal electronic components of the electronic device 1, and clips or other similar elements may be disposed on the outside of the housing 10 to allow the electronic device to be attached to an object.

[0073] In FIG. 1A, the electronic device 1 is in an interactive mode. In this mode, an interactive keypad 22 is displayed within a portion of the interactive display 20. The interactive keypad 22 includes one or more imaged keys 26. Each imaged key 26 may be “pressed” by a user to input data to the electronic device 1 by applying physical pressure to the interactive display 20 over the imaged key 26. Such “touchscreen” technology is well known in the art, such as in U.S. Pat. Nos. 5,815,141, 6,297,811, and 5,784,054, the contents of which are incorporated herein by reference. One or more other images may be displayed in other portions of the interactive display 20. Also, in the interactive mode, the interactive display 20 includes physical keys 28, such as, for example, bumps, ridges, indented regions or any other type of physical alteration that provides tactile feedback to a user, that correspond with the imaged keys 26 within the interactive keypad 22.

[0074] In FIG. 1B, the electronic device 1 is in a non-interactive mode. In this mode, the interactive keypad 22 is not displayed within the interactive display 20 and one or more other images may fully occupy the interactive display 20. Also, in the non-interactive mode, the interactive display 20 may be automatically modified so as not to include the physical keys 28 (i.e., the interactive display 20 may be completely smooth). Alternatively, the physical keys 28 may be formed permanently within the interactive display 20. A switch (not shown) may be provided through the housing 10 to allow a user to alternate the electronic device 1 between the interactive mode and the non-interactive mode.

[0075] FIG. 2 is a plan view of an interactive display, generally designated by reference number 100, according to an exemplary embodiment of the present invention. The interactive display 100 is shown held within a frame element 110. The interactive display may include one or more physical keys 145. As explained in further detail below, the top surface of the physical keys 145 may be level with the top plane of the interactive display 100 when the interactive display 100 is in the non-interactive mode, and the top surface of the keys 145 may be moved outside the top plane of the interactive display 100 when the interactive display 100 is in the interactive mode so that bumps or protrusions are formed in the interactive display 100 that correspond with displayed imaged keys.

[0076] FIGS. 3A and 3B are cross-sectional views of the interactive display 100 taken along line 3-3 in FIG. 2. In FIG. 3A, the interactive display 100 is in the non-interactive mode, and in the FIG. 3B, the interactive display 100 is in the interactive mode. As shown in FIGS. 3A and 3B, the frame element 110 may include a bottom wall 112, side walls 114, 115 and top walls 116, 117. The interactive display 100 may be housed within the frame element 110 with the bottom surface of the interactive display 100 resting on the bottom wall 112 of the frame element 110. The interactive display 100 may include a display device 130, a physical keypad 140 including the physical keys 145 disposed over the display device 130, and a touchscreen panel 150 disposed over the physical keypad 140.

[0077] The display device **130** may be any suitable display device, such as, for example, a liquid crystal display (LCD), a digital light processing (DLP) display, a plasma display or a light-emitting diode (LED) display, to name a few. As is known in the art, the display device **130** may include programmable elements that emit and/or block light to generate images. In the present embodiment, the display device **130** may display an imaged keyboard when the interactive display **100** is in the interactive mode.

[0078] The physical keypad **140** is a generally flat sheet or plate. The physical keys **145** are formed on the top surface of the physical keypad **140**, and extend upwards towards the touchscreen panel **150**. The physical keypad **140** is preferably made of a transparent material, such as, for example, plastic or glass. Any number of physical keys **145** may be formed on the physical keypad **140**. In an exemplary embodiment, the number and shape of the physical keys **145** are made to correspond to the number and shape of the imaged keys in the imaged keyboard displayed by the display device **130**.

[0079] The touchscreen panel **150** may be a transparent panel that generates a programming signal when pressure is applied to one or more areas on the touchscreen panel **150**. Various programming signals generated by the touchscreen panel **150** may be sent to the display device **130**, resulting in formation or manipulation of images in the display device **130**. For example, a user may apply pressure to the touchscreen panel **150** to activate the imaged keyboard and place the interactive display **100** in the interactive mode. Any suitable touchscreen technology may be used for the touchscreen panel **150**, such as, for example, resistive touchscreens, surface acoustic wave touchscreens, capacitive touchscreens, infrared touchscreens, strain gauge touchscreens, optical imaging, dispersive signal technology, acoustic pulse recognition, total internal reflection, and diffused laser imaging, to name a few.

[0080] The touchscreen panel **150** may include a number of openings **152** that correspond with the physical keys **145** of the physical keypad **140**. The physical keys **145** extend through the openings **152**. When the interactive display **100** is in the non-interactive mode, the top surfaces of the physical keys **145** may be co-planar with the top surface of the touchscreen panel **150**. When the interactive display **100** is in the interactive mode, the top surfaces of the physical keys **145** may be raised or lowered relative to the top surface of the touchscreen panel **150**, so that the touchscreen panel **150** includes a number of protrusions or indentations that correspond to the imaged keys in the imaged keypad. Thus, when the interactive display **100** is in the interactive mode, a user is able to feel the location of the various imaged keys based on the tactile feedback provided by the protrusions or indentations in the touchscreen panel **150**.

[0081] In an exemplary embodiment of the present invention, first and second actuators **160**, **162**, located on either side of the frame element **110**, may be used to manipulate the physical keypad **140** and thereby raise and lower the physical keys **145** relative to the touchscreen panel **150**. The first and second actuators **160**, **162** may be any suitable actuators, such as, for example, mechanical actuators, such as springs, microelectromechanical devices (MEMS), piezoelectric actuators and magnetostrictive actuators, to name a few. It should be appreciated that the number of actuators is not limited to two, and any number of actuators located at any suitable position relative to the physical keypad **140** may be

used to raise and lower the physical keypad **140**. Alternatively, the actuators **160**, **162** may be used to raise and lower the touchscreen panel **150** rather than the physical keypad **140**.

[0082] In various exemplary embodiments of the present invention, the physical keys in the physical keypad may all be connected to the physical keypad so as to form a unitary structure, with no independent movement of the physical keys. Alternatively, each physical key may be independently moveable relative to the physical keypad and the other physical keys so that each physical key may have the ability to be physically “pressed” by a user. In this regard, each physical key may include, for example, a spring mechanism or may itself be made of a resilient material that is able to flex under pressure from a user’s finger/thumb. The physical keypad may also use conventional keypad technology, such as, for example, dome-switch keypad technology, so that manipulation of each physical key results in a corresponding function.

[0083] FIGS. 4A and 4B are cross sectional views of an interactive display, generally designated by reference number **200**, according to another exemplary embodiment of the present invention. In FIG. 4A, the interactive display **200** is in the non-interactive mode, and in the FIG. 4B, the interactive display **200** is in the interactive mode. As in the previous embodiment, the interactive display **200** may be housed within a frame element **210** including a bottom wall **212**, side walls **214**, **215** and top walls **216**, **217**. The interactive display **200** may include a display device **220**, a touchscreen panel **230** disposed over the display device **220**, and a physical keypad **240** disposed over the touchscreen panel **230**. As in the previous embodiment, the display device **220** may be, for example, an LCD display, a DLP display, a plasma display or a LED display. The touchscreen panel **230** may use any of the touchscreen technology as described regarding the previous embodiment.

[0084] The physical keypad **240** in the present embodiment may include physical keys **245** defined by a material that changes shape under the influence of an electric or magnetic field. For example, the physical keys **245** may be made of a piezoelectric material, such as, for example, quartz, or a magnetostrictive material, such as, for example, ferromagnetic thin films. In the embodiment shown in FIGS. 4A and 4B, the physical keys **245** are defined by a grid structure **246** of piezoelectric material formed within the physical keypad **240**. Thus, the grid structure **246** may either deflect downwards or upwards under the application of an electric field, thereby forming protrusions or indentations around the physical keys **245**. In the embodiment shown in FIG. 4B, the grid structure **246** is structured so as to deflect upwards when an electric field is applied, thereby forming protrusions that define the physical keys **245**. Thus, in the interactive mode, the user is able to feel the location of the physical keys **245**. Deformation of the physical keys **245** in this embodiment may also result in generation of electricity, which may be fed back to the interactive display **200** as a power source.

[0085] It should be appreciated that the present invention is not limited to the above described embodiments. For example, in other exemplary embodiments, each physical key may be made of two or more pieces of transparent material that are made to deflect relative to one another when the interactive display is switched between the interactive

and non-interactive modes so as to form appropriate protrusions or indentations in the interactive display that demark the physical keys. In such an embodiment, an additional transparent layer may be disposed over the physical keypad, so that when the two or more pieces of material that form the physical keys are deflected, smooth bumps or indentations are formed in the transparent layer.

[0086] Further, as shown in FIGS. 5 and 6A-B, the interactive display of the present invention may include any number and shape of imaged and physical keys. In particular, in the embodiment shown in FIG. 5, an electronic device 300, such as a personal digital assistant, may include an interactive display 320 that provides a full keypad 322, including physical keys 328 corresponding with imaged keys 326, when in the interactive mode. In the embodiment shown in FIGS. 6A and 6B, an electronic device 400, such as an ATM, may include an interactive display 420 that provides a partial keypad 422, including physical keys 428 corresponding with imaged keys 426, when in the interactive mode. In the case of ATMs, the imaged keys 426 may be displayed in various shapes. For example, as shown in FIG. 6A, the electronic device 400 may display imaged keys 426 that are generally square shaped, while in FIG. 6B the electronic device 400 may display imaged keys 426 that are generally rectangular shaped. The physical keys 428 of the electronic device 400 may be made to mirror the different shapes of the imaged keys 426. In this regard, controlled magnetic and/or electric fields may be delivered to the physical keypad of the electronic device 400 to result in the appropriately shaped physical key 428.

[0087] In other exemplary embodiments of the present invention, the interactive display may include separate regions, where one or more regions are interactive and one or more other regions are not interactive. Further, the interactive display may be composed of more than one display, where one or more of the displays are interactive and one or more other displays are not interactive.

[0088] FIG. 7 is a flowchart showing a method, generally designated by reference number 500, of manufacturing an interactive display according to an exemplary embodiment of the present invention. In the present method, various layers of the interactive display may be disposed over one another and adhered to one another to provide a unitary structure. For example, one or more of the various layers may be laminated to one another. In step S502, a physical keypad having physical keys is disposed over a display device. The display device may be any suitable display device, such as, for example, an LCD display, a DLP display or a LED display, to name a few. The physical keypad may include, for example, permanent physical keys or be constructed of material that results in generation of temporary physical keys upon application of an electric or magnetic field to the physical keypad. In step S504, a touchscreen panel is disposed over the display device. The touchscreen panel may have one or more openings through which physical keys of the physical keypad may protrude. In step S506 an actuator assembly is operably attached to the physical keypad and/or the touchscreen panel. The actuator assembly may be controlled to deliver an appropriate magnetic or electric field to the physical keypad so as to generate temporary physical keys. Alternatively, the physical keypad and the touchscreen panel may be movable relative to one another through control of the actuator assembly, in which case the actuator assembly may include any suitable actuator

that provides translation forces, such as, for example, springs, MEMS devices, and piezoelectric actuators, to name a few.

[0089] FIG. 8 is a flowchart showing a method of operation, generally designated by reference number 600, of an interactive display according to an exemplary embodiment of the present invention. In step S602, the interactive display generates a first control signal instructing the interactive display to switch into an interactive mode. In step S604, based on the second control signal, a display device of the interactive display displays user-interactive imaged keys of an imaged keypad. In step S606, based on the first control signal, a physical keypad of the interactive display is controlled to provide physical keys that correspond with the imaged keys of the imaged keypad. In step S608, the interactive display generates a second control signal instructing the interactive display to switch into a non-interactive mode. In step S610, based on the second control signal, the display device replaces the imaged keypad with other image data. In step S612, based on the second control signal, the physical keypad of the interactive display is controlled so as not to provide physical keys.

[0090] FIG. 9 is a cross sectional views of an interactive display, generally designated by reference number 700, according to another exemplary embodiment of the present invention. As in the previous embodiment, the interactive display 700 may be housed within a frame element 710 including a bottom wall 712, side walls 714, 715 and top walls 716, 717. The interactive display 700 may include a display device 720, a touchscreen panel 730 disposed over the display device 720, and a physical keypad 740 disposed over the touchscreen panel 730. As in the previous embodiment, the display device 720 may be, for example, an LCD display, a DLP display, a plasma display or a LED display. The touchscreen panel 730 may use any of the touchscreen technology as described regarding the previous embodiment.

[0091] The physical keypad 740 in the present embodiment may include physical keys 745. The physical keys 745 are preferably transparent and may be integrally formed with the remaining portions of the physical keypad 740 by a molding operation. In the exemplary embodiment shown in FIG. 9, the physical keys 745 protrude outwards away from the display device 720. However, in other exemplary embodiments, the physical keys 745 may protrude inwards towards the display device 720.

[0092] As shown in FIG. 9, the physical keys 745 on the right side of the physical keypad 740 may include top surfaces that are inclined towards the right, and the physical keys 745 on the left side of the physical keypad 740 may include top surfaces that are inclined towards the left. This arrangement prevents a user's finger from sliding off a physical key 745 onto an adjacent physical key 745. There may also be additional space provided between the left side physical keys 745 and right side physical keys 745 to allow for better viewing of the image when the interactive display 700 is in the non-interactive mode.

[0093] FIG. 10 is a cross sectional views of an interactive display, generally designated by reference number 800, according to another exemplary embodiment of the present invention. As in the previous embodiments, the interactive display 800 may be housed within a frame element 810 including a bottom wall 812, side walls 814, 815 and top walls 816, 817. The interactive display 800 may include a

display device **830**, a physical keypad **840** disposed over the display device **830**, and a touchscreen panel **850** disposed over the physical keypad **840**. The physical keys **845** of the physical keypad **840** may protrude through openings in the touchscreen panel **850** when the interactive display **800** is in the interactive mode. As in the previous embodiments, the display device **830** may be, for example, an LCD display, a DLP display, a plasma display or a LED display. The touchscreen panel **850** may use any of the touchscreen technology as described regarding the previous embodiments.

[0094] In the present embodiment, an actuator element **860** is disposed below the display device **830**. The actuator element **860** may be any type of suitable actuator, such as, for example, piezoelectric actuators or magnetostrictive actuators. It should be appreciated that the number of actuators is not limited to one, and any number of actuators located at any suitable position relative to the physical keypad **840** may be used to raise and lower the physical keypad **845**. Alternatively, the actuator element **860** may be used to raise and lower the touchscreen panel **850** rather than the physical keypad **840**. The structure of the present embodiment allows the display device **830** to be sealed with the frame element **810** so as to protect the actuator element **860** and other internal components from being damaged.

[0095] FIG. 11 is a cross sectional views of an interactive display, generally designated by reference number **900**, according to another exemplary embodiment of the present invention. As in the previous embodiments, the interactive display **900** may be housed within a frame element **910** including a bottom wall **912**, side walls **914**, **915** and top walls **916**, **917**. The interactive display **900** may include an actuator element **960**, a protective layer **930** disposed over the actuator element **960**, one or more sub-key pads **940** disposed over the protective layer **930**, and a touchscreen display device **950** disposed over the sub-key pads **940**. The use of the touchscreen display device **950** eliminates the need for a separate touchscreen panel, as in previous embodiments. The sub-key pads **940** may be individually operated by the actuator element **960**, so that different ones of the physical keys **940** may be made to protrude through openings in the touchscreen display device **950**. Thus, as an example, different physical keys **940** may provide tactile feedback to a user depending on the functional mode of the interactive display **900**. Although each sub-key pad **940** is shown in FIG. 11 having only one physical key **945**, it should be appreciated that each sub-key pad **940** may have any number of physical keys **945**.

[0096] The protective layer **930** is disposed between the sub-key pads **940** and the actuator element **960** so as to prevent damage to the actuator element **960** that may otherwise result from contact with the sub-key pads **940**. The protective layer **930** may be made of any suitable protective material that does not interfere with the function of the actuator element **960**, such as, for example, felt, cotton, plastic, insulators, cushioning material, etc. The protective material can even be air in one embodiment.

[0097] FIG. 11 is a cross sectional views of an interactive display, generally designated by reference number **1000**, according to another exemplary embodiment of the present invention. As in the previous embodiments, the interactive display **1000** may be housed within a frame element **1010** including a bottom wall **1012**, side walls **1014**, **1015** and top walls **1016**, **1017**. The interactive display **1000** may include

an actuator element **1060**, a physical keypad **1040** disposed over the actuator element **1060**, and a touchscreen display device **1030** disposed over the physical keypad **1040**. As in the previous embodiment, the physical keypad **1040** may be made up of separate sub-key pads (not shown). Further, a protective layer (not shown) may be disposed between the physical keypad **1040** and the actuator element **1060**.

[0098] In the present embodiment, each key **1045** of the physical keypad **1040** forms part of the touchscreen display device **1030**. In this regard, a touchscreen display element **1048** may be disposed within each key **1045**, so that images, such as corresponding imaged keys, may be displayed on each key **1045** as part of the overall image displayed by the touchscreen display device **1030**.

[0099] FIG. 12B is a detailed cross-sectional view of a section of the interactive display **1000**. As shown in this figure, a connective element **1070** may be disposed at the base of each key **1045** so as to provide for delivery of appropriate signals to the key **1045** to display an image within the corresponding touchscreen display element **1048**.

[0100] FIG. 13 is a cross-sectional view of a section of an interactive display, generally designated by reference number **1100**, according to another exemplary embodiment of the present invention. As in previous embodiment, the interactive display **1100** may be disposed within a frame element (not shown). The interactive display **1100** includes an actuator element **1160**, a protective layer **1170** disposed over the actuator element **1160**, a physical keypad **1140** disposed over the protective layer **1170** and a touchscreen display device **1130** disposed over the physical keypad **1140**. A portion **1135** of the touchscreen display device **1130** may be disposed within each key **1145** of the physical keypad **1140**. In this regard, the keys **1145** of the physical keypad **1140** may be substantially transparent, so that the portions **1135** of the touchscreen display device **1130** may be viewed through the top of each key **1145**.

[0101] FIG. 14A is a cross-sectional view of a section of an interactive display, generally designated by reference number **1200**, according to another exemplary embodiment of the present invention. As in the previous embodiment, the interactive display **1200** may be disposed within a frame element (not shown). The interactive display **1200** includes an actuator element **1260**, a protective layer **1270** disposed over the actuator element **1260**, a physical keypad **1240** disposed over the protective layer **1270** and a touchscreen display device **1230** disposed over the physical keypad **1240**. A permanent magnet **1280** is disposed within each key **1245** of the keypad **1240**. One or more charged electrical circuit elements **1290** may be disposed within the touchscreen display device **1230** adjacent each key **1245**. In an exemplary embodiment, the charged electrical circuit elements **1290** may be electromagnetic coils, and, as shown in FIG. 14B, the permanent magnets **1280** within each key **1245** may pass through a respective one of the electromagnetic coils. Movement of the key **1245**, and hence the permanent magnet **1280**, within a corresponding opening within the touchscreen display device **1230** relative to the charged electrical circuit elements **1290** results in generation of electricity. The movement of the keys **1245** may be due to switching of the interactive display between the interactive mode and the non-interactive mode, and may also result from user manipulation of the keys **1245**. The generated electricity may be fed back to the interactive display **1200** as a power source.

[0102] FIGS. 15A-15D are various views of an electronic device, generally designated by reference number 2000, according to another exemplary embodiment of the present invention. In the present embodiment, the electronic device 2000 may be, for example, a PDA, cell phone, or other hand-held mobile device. The electronic device 2000 includes a housing 2010 and an interactive display 2020.

[0103] FIGS. 15A and 15B show the electronic device 2000 in a keyboard-enabled mode. In particular, FIG. 15A is a back view of the electronic device 2000 in the keyboard-enabled mode, and FIG. 15B is a front view of the electronic device 2000 in the keyboard-enabled mode.

[0104] As shown in FIG. 15A, when the electronic device 2000 is switched to the keyboard-enabled mode, the back surface 2012 of the electronic device includes a physical keypad 2022 made up of physical keys 2028. As in previous embodiments, the physical keys 2028 may be formed by, for example, bumps, ridges, indented regions or any other type of physical alteration that provides tactile feedback to a user. At the same time, as shown in FIG. 15B, the interactive display 2020 disposed at the front surface 2014 of the electronic device 2000 may generate an imaged keypad 2024 made up of imaged keys 2026. However, it should be appreciated that, when the electronic device 2000 is in the keyboard-enabled mode, the imaged keypad 2024 need not be made available. For example, the interactive display 2020 may display other types of image data, such as, for example, selectable menus or moving video game images. In an exemplary embodiment, each of the imaged keys 2026 displayed on the front of the electronic device 2000 may correspond to a respective one of the physical keys 2028 disposed at the back of the electronic device 2000. In this regard, the imaged key 2026 corresponding to a pressed physical key 2028 may be shown as being activated, such as by, for example, illumination, change of size, or visual distortion of the corresponding imaged key 2026. Such an arrangement allows a user to “view” within the imaged keypad 2024 which physical keys 2028 are being pressed by the user, even though the physical keypad 2022 is disposed on the side of the electronic device 2000 that is actually out of view from the user.

[0105] In an alternative exemplary embodiment, the imaged keypad 2024 at the front of the electronic device 2000 and the physical keypad 2022 at the back of the electronic device 2000 together form a combination keypad made up of imaged keys 2026 and physical keys 2028, where the imaged keys 2026 perform functions different from those of the physical keys 2028. For example, the physical keys 2028 may include modifier keys, such as “control” and “shift” keys, lock keys, such as “num lock” and “caps lock”, navigation keys, such as arrow keys, “page up/page down” and “home/end”, and editing keys, such as “return”, “enter”, “backspace”, “insert”, “delete”, “tab” and space bar, while the image keys 2026 may include alphanumeric keys. In other embodiments, this configuration may be reversed, so that the image keys 2026 include modifier, navigation, lock, editing and navigation keys, while the physical keys 2028 include alphanumeric keys. Also, in other embodiments, the imaged keys 2026 and physical keys 2028 may include any suitable arrangement of modifier, navigation, lock, editing and alphanumeric keys. The combination of imaged keys 2026 and physical keys 2028 having varying functions and disposed on opposite surfaces of the electronic device 2000 allows for the use of both

thumbs and fingers to manipulate the keys. For example, the fingers on the underside of the electronic device 2000 may be used to input letters and numbers, while the thumbs on the top of the electronic device 2000 may be used to control spacing, paragraph changes, etc. The imaged keys 2026 and physical keys 2028 may be rearranged based on user preference, so that the user is able to choose which keys are available on different surfaces of the electronic device 2000. For example, the user may choose to arrange certain keys that are typically activated by the user’s thumb on one surface of the electronic device 2000 and certain keys that are typically activated by the user’s fingers on another surface.

[0106] FIGS. 15C and 15D show the electronic device 2000 in the keyboard-disabled mode. In particular, FIG. 15C is a back view of the electronic device 2000 in the keyboard-disabled mode, and FIG. 15D is a front view of the electronic device 2000 in the keyboard-disabled mode. In the keyboard-disabled mode, the physical keypad 2022 at the back surface 2012 is automatically modified so as not to include the physical keys 2028 (i.e., the physical keypad 2022 may be completely smooth). Alternatively, the physical keys 2028 may be formed permanently within the physical keypad 2022. Also, in the keyboard-disabled mode, the imaged keypad 2024 may not be displayed within the interactive display 2020 and one or more other images may fully occupy the interactive display 2020.

[0107] The physical keypad 2022 and imaged keypad 2024 may operate the same as in other exemplary embodiments of the present invention described herein, except that the physical keys 2028 provide tactile feedback to the user on a surface of the electronic device 2000 that is different from a surface on which the imaged keypad 2024 is displayed. For example, the physical keys 2028 may be automatically manipulated by actuators or through the use of material for the physical keys 2028 that changes shape under the influence of an electric or magnetic field. In this regard, FIGS. 16A and 16B are cross-sectional views of an interactive display 2100 according to another exemplary embodiment of the present invention. In FIG. 16A, the interactive display 2100 is in the keyboard-disabled mode, and in the FIG. 16B, the interactive display 2100 is in the keyboard-enabled mode. The interactive display 2100 may be housed within a frame element 2110 made up of a bottom wall 2112, side walls 2114, 2115 and top walls 2116, 2117. The interactive display 2100 may be housed within the frame element 2110 with the bottom surface of the interactive display 2100 resting on the bottom wall 2112 of the frame element 2110. The interactive display 2100 may include a physical keypad 2140 including physical keys 2145, a display device 2130 disposed over the physical keypad 2140, and a touchscreen panel 2150 disposed over the display device 2130.

[0108] The display device 2130 may be any suitable display device, such as, for example, a liquid crystal display (LCD), a digital light processing (DLP) display, a plasma display or a light-emitting diode (LED) display, to name a few. As is known in the art, the display device 2130 may include programmable elements that emit and/or block light to generate images. In the present embodiment, the display device 2130 may display an imaged keyboard when the interactive display 2100 is in the keyboard-enabled mode.

[0109] The physical keypad 2140 is a generally flat sheet or plate. The physical keys 2145 are formed on the top

surface of the physical keypad **2140**, and extend downwards towards the bottom wall **2112** of the frame element **2110**. The physical keypad **2140** may be made of a transparent material, such as, for example, plastic or glass. Any number of physical keys **2145** may be formed on the physical keypad **2140**. In an exemplary embodiment, the number and shape of the physical keys **2145** are made to correspond to the number and shape of the imaged keys in the imaged keyboard displayed by the display device **2130**.

[0110] The touchscreen panel **2150** may be a transparent panel that generates a programming signal when pressure is applied to one or more areas on the touchscreen panel **2150**. Various programming signals generated by the touchscreen panel **2150** may be sent to the display device **2130**, resulting in formation or manipulation of images in the display device **2130**. For example, a user may apply pressure to the touchscreen panel **2150** to activate the imaged keyboard and place the interactive display **2100** in the interactive mode. Any suitable touchscreen technology may be used for the touchscreen panel **2150**, such as, for example, resistive touchscreens, surface acoustic wave touchscreens, capacitive touchscreens, infrared touchscreens, strain gauge touchscreens, optical imaging, dispersive signal technology, acoustic pulse recognition, total internal reflection, and diffused laser imaging, to name a few.

[0111] The bottom wall **2112** of the frame element **2110** may include a number of openings **2152** that correspond with the physical keys **2145** of the physical keypad **2140**. The physical keys **2145** extend through the openings **2152**. When the interactive display **2100** is in the keyboard-disabled mode, the top surfaces of the physical keys **2145** may be co-planar with the bottom surface of the bottom wall **2112**. When the interactive display **2100** is in the keyboard-enabled mode, the top surfaces of the physical keys **2145** may be raised or lowered relative to the top surface of the bottom wall **2112**, so that the bottom wall **2112** includes a number of protrusions or indentations that correspond to the imaged keys in the imaged keypad. Thus, when the interactive display **2100** is in the keyboard-enabled mode, a user may be able to feel the location of the various imaged keys based on the tactile feedback provided by the protrusions or indentations in the bottom wall **2112**.

[0112] In an exemplary embodiment of the present invention, first and second actuators **2160**, **2162**, located on either side of the frame element **2110**, may be used to manipulate the physical keypad **2140** and thereby raise and lower the physical keys **2145** relative to the bottom wall **2112**. The first and second actuators **2160**, **2162** may be any suitable actuators, such as, for example, mechanical actuators, such as springs, microelectromechanical devices (MEMS), piezoelectric actuators and magnetostrictive actuators, to name a few. It should be appreciated that the number of actuators is not limited to two, and any number of actuators located at any suitable position relative to the physical keypad **2140** may be used to raise and lower the physical keypad **2140**.

[0113] FIGS. 17A-17B are various views of an electronic device, generally designated by reference number **3000**, according to another exemplary embodiment of the present invention. In the present embodiment, the electronic device **3000** may be, for example, a PDA, cell phone, or other hand-held mobile device. The electronic device **3000** includes a housing **3010** and an interactive display **3020**. The electronic device **3000** may have structural components that are the same as those of the electronic device **2000** of

the previous embodiment, except for additional components as described below that allow a user to view the motion of the user's fingers or thumbs underneath the electronic device **3000**.

[0114] FIGS. 17A and 17B show the electronic device **3000** in the keyboard-enabled mode. In particular, FIG. 17A is a back view of the electronic device **3000** in the keyboard-enabled mode, and FIG. 17B is a front view of the electronic device **3000** in the keyboard-enabled mode. As shown in FIG. 17A, when the electronic device **3000** is switched to the keyboard-enabled mode, the back surface **3012** of the electronic device includes a physical keypad **3022** made up of physical keys **3028**. As in previous embodiments, the physical keys **3028** may be formed by, for example, bumps, ridges, indented regions or any other type of physical alteration that provides tactile feedback to a user. At the same time, as shown in FIG. 17B, the interactive display **3020** disposed at the front surface **3014** of the electronic device **3000** may generate an imaged keypad **3024** made up of imaged keys **3026**. However, it should be appreciated that, when the electronic device **3000** is in the keyboard-enabled mode, the imaged keypad **3024** need not be made available. For example, the interactive display **3020** may display other types of image data, such as, for example, selectable menus or moving video game images. In an exemplary embodiment, each of the imaged keys **3026** displayed on the front of the electronic device **3000** may correspond to a respective one of the physical keys **3028** disposed at the back of the electronic device **3000**. In this regard, the imaged key **3026** corresponding to a pressed physical key **3028** may be shown as being activated, such as by, for example, illumination, change of size, or visual distortion of the corresponding imaged key **3026**. Such an arrangement allows a user to "view" within the imaged keypad **3024** which physical keys **3028** are being pressed by the user, even though the physical keypad **3022** is disposed on the side of the electronic device **3000** that is actually out of view from the user. Also, in the present embodiment, as the user moves his thumb/finger over the physical keys **3028**, an imaged representation **3030** of the user's thumb/finger is displayed within the imaged keypad **3024**, or if the imaged keypad **3024** is not displayed, the imaged representation **3030** may be shown relative to other displayed image data within the interactive display **3020**. The imaged representation **3030** may be a silhouette of the thumb/finger, as shown in FIG. 17B, or any other suitable representation, such as, for example, "blurred" or shadowed spots moving across the imaged keypad **3024** that follow the movement of the user's fingertips within the physical keypad **3022**.

[0115] The physical keypad **3022** and imaged keypad **3024** may operate the same as in the previous exemplary embodiment. That is, the physical keys **3028** may provide tactile feedback to the user on a surface of the electronic device **3000** that is different from a surface on which the imaged keypad **3024** is displayed. For example, the physical keys **3028** may be automatically manipulated by actuators or through the use of material for the physical keys **3028** that changes shape under the influence of an electric or magnetic field. In this regard, FIGS. 18A and 18B are cross-sectional views of an interactive display **3100** according to another exemplary embodiment of the present invention. In FIG. 18A, the interactive display **3100** is in the keyboard-disabled mode, and in the FIG. 18B, the interactive display **3100** is in the keyboard-enabled mode. The interactive display **3100**

may be housed within a frame element **3110** made up of a bottom wall **3112**, side walls **3114**, **3115** and top walls **3116**, **3117**. The interactive display **3100** may be housed within the frame element **3110** with the bottom surface of the interactive display **3100** resting on the bottom wall **3112** of the frame element **3110**. The interactive display **3100** may include a physical keypad **3140** including physical keys **3145**, a display device **3130** disposed over the physical keypad **3140**, and a touchscreen panel **3150** disposed over the display device **3130**.

[0116] The display device **3130** may be any suitable display device, such as, for example, a liquid crystal display (LCD), a digital light processing (DLP) display, a plasma display or a light-emitting diode (LED) display, to name a few. As is known in the art, the display device **3130** may include programmable elements that emit and/or block light to generate images. In the present embodiment, the display device **3130** may display an imaged keyboard when the interactive display **2100** is in the keyboard-enabled mode.

[0117] The physical keypad **3140** is a generally flat sheet or plate. The physical keys **3145** are formed on the top surface of the physical keypad **3140**, and extend downwards towards the bottom wall **3112** of the frame element **3110**. The physical keypad **3140** may be made of a transparent material, such as, for example, plastic or glass. Any number of physical keys **3145** may be formed on the physical keypad **3140**. In an exemplary embodiment, the number and shape of the physical keys **3145** are made to correspond to the number and shape of the imaged keys in the imaged keyboard displayed by the display device **3130**.

[0118] The touchscreen panel **3150** may be a transparent panel that generates a programming signal when pressure is applied to one or more areas on the touchscreen panel **3150**. Various programming signals generated by the touchscreen panel **3150** may be sent to the display device **3130**, resulting in formation or manipulation of images in the display device **3130**. For example, a user may apply pressure to the touchscreen panel **3150** to activate the imaged keyboard and place the interactive display **3100** in the keyboard-enabled mode. Any suitable touchscreen technology may be used for the touchscreen panel **3150**, such as, for example, resistive touchscreens, surface acoustic wave touchscreens, capacitive touchscreens, infrared touchscreens, strain gauge touchscreens, optical imaging, dispersive signal technology, acoustic pulse recognition, total internal reflection, and diffused laser imaging, to name a few.

[0119] The bottom wall **3112** of the frame element **3110** may include a number of openings **3152** that correspond with the physical keys **3145** of the physical keypad **3140**. The physical keys **3145** extend through the openings **3152**. When the interactive display **3100** is in the keyboard-disabled mode, the top surfaces of the physical keys **3145** may be co-planar with the bottom surface of the bottom wall **3112**. When the interactive display **3100** is in the keyboard-enabled mode, the top surfaces of the physical keys **3145** may be raised or lowered relative to the bottom surface of the bottom wall **3112**, so that the bottom wall **3112** includes a number of protrusions or indentations that correspond to the imaged keys in the imaged keypad. Thus, when the interactive display **3100** is in the keyboard-enabled mode, a user is able to feel the location of the various imaged keys based on the tactile feedback provided by the protrusions or indentations in the bottom wall **3112**.

[0120] In an exemplary embodiment of the present invention, first and second actuators **3160**, **3162**, located on either side of the frame element **3110**, may be used to manipulate the physical keypad **3140** and thereby raise and lower the physical keys **3145** relative to the bottom wall **3112**. The first and second actuators **3160**, **3162** may be any suitable actuators, such as, for example, mechanical actuators, such as springs, microelectromechanical devices (MEMS), piezoelectric actuators and magnetostrictive actuators, to name a few. It should be appreciated that the number of actuators is not limited to two, and any number of actuators located at any suitable position relative to the physical keypad **3140** may be used to raise and lower the physical keypad **3140**.

[0121] The interactive display **3100** may also include a sensor **3170** that detects user interaction with the physical keypad **3140**. The sensor **3170** may be any known or later-discovered sensor that is able to detect the presence and/or motion of the digits of a user's hand relative to the physical keypad **3140**. The sensor **3170** may be, for example, a motion sensor, a thermal sensor or a pressure sensor, or any combination of a variety of sensors. The sensor **3170** may generate electrical signals based on the detected user interaction, and the generated signals may be sent to an image generator. The image generator may use the generated signals to display in the imaged keypad **3023** an imaged representation of the user interaction. Thus, even though the user's thumbs or fingers may be out of view behind the electronic device **300**, the user will still have the ability to determine the location of his thumbs or fingers relative to the physical keys **3145** by viewing the imaged representation in the imaged keypad **3023**. In an exemplary embodiment, the electronic device **3000** may include a switch to allow the user to selectively activate the imaging of user interaction within the imaged keypad **3023**. In exemplary embodiments of the invention, the sensor **3170** may include a number of individual sensors, where each sensor corresponds to a particular physical key **3145** within the imaged keypad **3140**.

[0122] As shown in FIGS. **18A** and **18B**, the bottom surface of the bottom wall **3112** may include protrusions **3180** that are able to support the electronic device **3100** on a surface. In this regard, the protrusions **3180** may prevent any one of the physical keys **3145** from being inadvertently activated by contact of the electronic device **3100** with the surface.

[0123] FIGS. **19** is a cross-sectional views of an interactive display **4100** according to another exemplary embodiment of the present invention. In FIG. **19**, the interactive display **4100** is in the keyboard-disabled mode. The interactive display **4100** may be housed within a frame element **4110** made up of a first surface walls **4112**, **4113**, side walls **4114**, **4115** and second surface walls **4116**, **4117**. The interactive display **4100** includes a first surface display device **4130** and a first surface touchscreen panel **4150** disposed over the first surface display device **4130**. As in previously described embodiments, the display device **4130** may display an imaged keyboard when the interactive display **4100** is in the keyboard-enabled mode, where the imaged keyboard includes a number of imaged keys. However, it should be appreciated that the imaged keyboard need not be displayed when the interactive display **4100** is in the keyboard-enabled mode.

[0124] The interactive display **4100** may also include a physical keypad **4140**, a second surface touchscreen panel

4160 disposed over the physical keypad **4140**, and a second surface display device **4180** disposed over the touchscreen panel **4160**. The physical keypad **4140** in the present embodiment may include physical keys **4145** defined by a material that changes shape under the influence of an electric or magnetic field. For example, the physical keys **4145** may be made of a piezoelectric material, such as, for example, quartz, or a magnetostrictive material, such as, for example, ferromagnetic thin films. In the embodiment shown in FIG. 19, the physical keys **4145** are defined by a grid structure **4146** of piezoelectric material formed within the physical keypad **4140**. Thus, the grid structure **4146** may either deflect downwards or upwards under the application of an electric field, thereby forming protrusions or indentations around the physical keys **4145**. Thus, in the keyboard-enabled mode, the user is able to feel the location of the physical keys **4145**. Any number of physical keys **4145** may be formed on the physical keypad **4140**. In an exemplary embodiment, the number and shape of the physical keys **4145** are made to correspond to the number and shape of the imaged keys in the imaged keyboard that may be displayed by the first surface display device **4130**. Thus, when the interactive display **4100** is in the keyboard-enabled mode, a user is able to feel the location of the various imaged keys based on the tactile feedback provided by the physical keys **4145**.

[0125] As in the previous embodiment, the interactive display **4100** may also include a sensor **4170** that detects user interaction with the physical keypad **4140**. The sensor **4170** may generate electrical signals based on the detected user interaction, and the generated signals may be sent to an image generator. The image generator may use the generated signals to display in the imaged keypad an imaged representation of the user interaction.

[0126] Now that the preferred embodiments of the present invention have been shown and described in detail, various modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present invention is to be construed broadly and limited only by the appended claims and not by the foregoing specification.

What is claimed is:

1. An electronic device comprising:

a first display disposed at a first surface of the electronic device and which is an interactive display having an interactive mode and a non-interactive mode, the interactive display comprising a first image display device, wherein the first image display device displays a first user-interactive imaged keypad comprising first imaged keys in at least a portion of the first image

display device when the interactive display is in the interactive mode and that displays other image data in the at least a portion of the first image display device when the interactive display is in the non-interactive mode;

a physical keypad disposed over the first display, the physical keypad comprising structural features that correspond with the first imaged keys;

a second display disposed at a second surface of the electronic device, the second display comprising a second image display device configured to display a plurality of second imaged keys and other image data;

a sensor that detects user interaction with the physical keypad; and

an image generator that displays within the second image display device an imaged representation of the user interaction with the physical keypad.

2. The electronic device of claim 1, wherein the image display device is selected from one of the following types of image display devices: liquid crystal displays, digital light processor displays, plasma displays and light emitting diode displays.

3. The electronic device of claim 1, further comprising a touchscreen panel, and the physical keypad is disposed over the touchscreen panel.

4. The electronic device of claim 3, wherein the physical keypad is integral to the touchscreen panel.

5. The electronic device of claim 3, wherein the physical keypad is separate from the touchscreen panel.

6. The electronic device of claim 1, wherein the electronic device is selected from one of the following types of electronic devices: cell phones, personal digital assistants, automatic teller machines, data input devices, portable devices, hand-held devices, non-portable devices, and computers.

7. The electronic device of claim 1, wherein the sensor comprises one or more of the following sensor types: a motion sensor, a thermal sensor and a pressure sensor.

8. The electronic device of claim 1, wherein the imaged representation of the user interaction comprises an imaged depiction of the user's finger or thumb interacting with the imaged keypad.

9. The electronic device of claim 1, wherein shapes of the first imaged keys are reconfigurable.

10. The electronic device of claim 1, wherein the other types of image data comprise a selectable menu.

11. The electronic device of claim 1, wherein the structural features are bumps, ridges, or indented regions.

* * * * *