CONVENTION - COMPANY - PCT
(By Employment Contract & Applicant is Applicant in Basic Appln)

P/00/908b Section 29 (1) Regulation 3.1(2)

AUSTRALIA

PATENTS ACT 1990

NOTICE OF ENTITLEMENT

We, JANSSEN PHARMACEUTICA N.V., of Turnhoutseweg 30, Beerse, B-2340, Belgium, being the applicant and nomination person in respect of Application No. 76544/94, state the following:-

1. The person nominated for the grant of the patent has entitlement from the actual inventor as follows:

If a patent were granted to the actual inventor in respect of the invention the nominated person would be entitled to have the patent assigned to it.

2. The person nominated for the grant of the patent has entitlement from the applicant of the basic application listed in the declaration under Article 8 of the PCT as follows:

If a patent were granted to the applicant of the basic application the nominated person would be entitled to have the patent assigned to it.

3. The basic application listed in the declaration under Article 8 of the PCT is the first application made in a Convention country in respect of the invention.

For and on behalf of JANSSEN PHARMACEUTICA N.V.

(Signature)

January 17, 1996

(Date)

Name: Dirk Wante

JANSSEN PHARMACEUTICA

NAAMLOZE VENNOOTSCHAP
Turnhoutseweg, 30

BEERSE (BELGIE)

Fitle: Proxy Holder

File: 18506

(12) PATENT ABRIDGMENT (11) Document No. AU-B-76544/94 (19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 680294

(54) Title
ANTIBACTERIAL AND ANTIFOULING OXATHIAZINES AND THEIR OXIDES
International Patent Classification(s)

(51)6 A01N 043/88

(21) Application No.: 76544/94

(22) Application Date: 24.08.94

(87) PCT Publication Number: WO95/05739

(30) Priority Data

(31) Number (32) Date (33) 111352 24.08.93

Country
US UNITED STATES OF AMERICA

(43) Publication Date: 21.03.95

(44) Publication Date of Accepted Application: 24.07.97

(71) Applicant(s)

JANSSEN PHARMACEUTICA N.V.

(72) Inventor(s)
JOZEF FRANS ELISABETHA VAN GESTEL

(74) Attorney or Agent SHELSTON WATERS, Level 21, 60 Margaret Street, SYDNEY NSW 2000

(56) Prior Art Documents EP 0104940

(57) Claim


1. A method of controlling bacteria and fouling organisms, said method comprising administering to said bacteria or fouling organisms, or to the locus thereof, an effective antibacterial or antifouling amount of a compound having the formula

$$R^1 \xrightarrow{O_N} R$$
 (I),

wherein n is 0, 1 or 2; R¹ is hydrogen, C¹-4alkyl or benzyl; and R represents

(a) phenyl; phenyl substituted with 1 to 3 substituents independently selected from hydroxyl, halo, C¹-12alkyl, C⁵-6cycloalkyl, trihalomethyl, phenyl, C¹-5alkoxy, C¹-5alkylthio, tetrahydropyranyloxy, phenoxy, C¹-4alkylcarbonyl, phenylcarbonyl, C¹-4alkylsulfinyl, C¹-4alkylsulfonyl, carboxy or its alkali metal salt, C¹-4alkyloxy-carbonyl, C¹-4alkylaminocarbonyl, phenylaminocarbonyl, tolylaminocarbonyl, morpholinocarbonyl, amino, nitro, cyano, dioxolanyl or C¹-4alkyloxyiminomethyl; naphthyl; pyridinyl; thienyl; furanyl; or thienyl or furanyl substituted with one to three substituents independently selected from C¹-4alkyl, C¹-4alkyloxy, C¹-4alkylthio, halo, cyano, formyl, acetyl, benzoyl, nitro, C¹-4alkyloxycarbonyl, phenyl, phenylaminocarbonyl and C¹-4alkyloxyiminomethyl; or R represents a radical of formula

(10) 680294



wherein X is oxygen or sulfur; Y is nitrogen, CH or $C(C_{1-4}alkyloxy)$; and R" is hydrogen or $C_{1-4}alkyl$.

- 2. A method according to claim 1 of protecting non-living materials other than wood, and the objects made of or covered by said non-living materials, against bacteria and fouling organisms, said method comprising applying to the surface or incorporating into said materials or objects an effective antibacterial or antifouling amount of a compound of formula (I).
- 10. A coating composition comprising:
- (a) as active ingredient a compound of formula (I) as defined in claim 1, and
- (b) a polymer or copolymer or resin.

AU9476544

JT)

(51)	International	Patent	Classification	6:

A01N 43/88

A1

(11) International Publication Number:

WO 95/05739

(43) International Publication Date:

2 March 1995 (02.03.95)

(21) International Application Number:

PCT/EP94/02784

(22) International Filing Date:

24 August 1994 (24.08.94)

(30) Priority Data:

111,352

24 August 1993 (24.08.93)

00

(60) Parent Application or Grant

(63) Related by Continuation

US Filed on 111,352 (CIP) 24 August 1993 (24.08.93)

(71) Applicant (for all designated States except US): JANSSEN PHARMACEUTICA N.V. [BE/BE]; Turnhoutseweg 30, B-2340 Beerse (BE).

(72) Inventor; and

- (75) Inventor/Applicant (for US only): VAN GESTEL, Jozef, Frans, Elisabetha [BE/BE]; Renier Sniederspad 9, B-2350 Vosselaar (BE).
- (74) Agent: QUAGHEBEUR, Luc; Janssen Pharmaceutica N.V., Patent Dept., Turnhoutseweg 30, B-2340 Beerse (BE).

(81) Designated States: AM, AU, BB, BG, BR, BY, CA, CN, CZ, FI, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LV, MD, MG, MN, MW, NO, NZ, PL, RO, RU, SD, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD).

Published


With international search report.



(54) Title: ANTIBACTERIAL AND ANTIFOULING OXATHIAZINES AND THEIR OXIDES

(57) Abstract

Use of 3-aryl-5,6-dihydro-1,4,2-oxathiazines and their oxides having formula (I), wherein n is 0, 1 or 2; R¹ is hydrogen, C₁₋₄alkyl or benzyl; and R represents (a) phenyl; phenyl substituted with 1 to 3 substituents independently selected from hydroxyl, halo, C₁₋₁₂alkyl, C₅₋₆cycloalkyl, trihalomethyl, phenyl, C₁₋₅alkoxy, C₁₋₅alkylthio, tetrahydropyranyloxy, phencxy, C₁₋₄alkylcarbonyl, phenylcarbonyl, C₁₋₄alkylsulfinyl, C₁



4alkylsulfonyl, carboxy or its alkali metal salt, C₁₋₄alkyloxycarbonyl, C₁₋₄alkylaminocarbonyl, phenylaminocarbonyl, tolylaminocarbonyl, morpholinocarbonyl, amino, nitro, cyano, dioxolanyl or C₁₋₄alkyloxyiminomethyl; naphthyl; pyridinyl; thienyl, preferably when n is not 2; furanyl; or thienyl or furanyl substituted with one to three substituents independently selected from C₁₋₄alkyloxy, C₁₋₄alkylthio, halo, cyano, formyl, acetyl, benzoyl, nitro, C₁₋₄alkyloxycarbonyl, phenyl, phenylaminocarbonyl and C₁₋₄alkyloxyiminomethyl; or R represents a radical of formula (b) wherein X is oxygen or sulfur; Y is nitrogen, CH or C(C₁₋₄alkyloxy); and R'' is hydrogen or C₁₋₄alkyl, as an antibacterial, anti-yeast, antifungal, algicidal, anti-crustacean, molluscicidal and general antifouling agent and compositions containing the same.

ANTIBACTERIAL AND ANTIFOULING OXATHIAZINES AND THEIR OXIDES

5

10

15

20

The present invention concerns a method of controlling bacteria and fouling organisms with 3-aryl-5,6-dihydro-1,4,2-oxathiazines and their oxides, a method of protecting non-living materials other than wood, and industrial antibacterial and antifouling compositions. Surfaces of objects exposed to humid or aqueous environments are readily colonized by micro-organisms and occasionally by other, higher life forms such as molluses and crustacea. As these organisms settle on or attach to said surfaces, the value of the exposed objects diminishes. The exterior, but possibly also the interior of the object may deteriorate, the surface changes (e.g. from smooth, clean and streamlined to rough, foul and turbulent), the weight of the object increases by the deposit of the organisms and their remnants, and the vicinity of the object may become obstructed or encumbered. The function of the object and system involved lowers and the quality of the aqueous environment deteriorates. Similar problems beset industrially used compositions such as coatings, lubricants and the like. All these phenomena are referred to as fouling. The oxathiazines of the present method and their oxides are disclosed in US-4,569,690 as herbicides, plant fungicides, plant desiccants and defoliants.

The present invention provides a method of controlling bacteria and fouling organisms, said method comprising applying to said bacteria or fouling organisms, or to the locus thereof an effective antibacterial or antifouling amount of a compound having the formula

$$R^1 \xrightarrow{O_N} R$$
 (I),

wherein n is 0, 1 or 2; R¹ is hydrogen, C₁₋₄alkyl or benzyl; and R represents
(a) phenyl; phenyl substituted with 1 to 3 substituents independently selected from hydroxyl, halo, C₁₋₁₂alkyl, C₅₋₆cycloalkyl, trihalomethyl, phenyl, C₁₋₅alkoxy, C₁₋₅alkylthio, tetrahydropyranyloxy, phenoxy, C₁₋₄alkylcarbonyl, phenylcarbonyl, C₁₋₄alkylsulfinyl, C₁₋₄alkylsulfonyl, carboxy or its alkali metal salt, C₁₋₄alkyloxy-carbonyl, C₁₋₄alkylaminocarbonyl, phenylaminocarbonyl, tolylaminocarbonyl, morpholinocarbonyl, amino, nitro, cyano, dioxolanyl or C₁₋₄alkyloxyiminomethyl;

35 naphthyl; pyridinyl; thienyl; furanyl; or thienyl or furanyl



30

substituted with one to three substituents independently selected from C_{1-4} alkyl, C_{1-4} alkyloxy, C_{1-4} alkylthio, halo, cyano, formyl, acetyl, benzoyl, nitro, C_{1-4} alkyloxy-carbonyl, phenyl, phenylaminocarbonyl and C_{1-4} alkyloxyiminomethyl; or R represents a radical of formula

5

10

wherein X is oxygen or sulfur; Y is nitrogen, CH or $C(C_{1-4}alkyloxy)$; and R" is hydrogen or $C_{1-4}alkyl$.

The present invention also provides a method of protecting non-living materials other than wood, and the objects made of or covered by said non-living materials, against bacteria and/or fouling organisms, said method comprising applying to the surface or incorporating into said materials or objects an effective antibacterial or antifouling amount of a compound of formula (I).

In the foregoing definitions halo is generic to fluoro, chloro, bromo and iodo; C_{1-4} alkyl defines straight and branch chained saturated hydrocarbon radicals having from 1 to 4 carbon atoms comprising methyl, ethyl, n-propyl, 1-methylethyl, n-butyl, 1,1-dimethylethyl, 1-methylpropyl, 2-methylpropyl; C_{1-5} alkyl includes C_{1-4} alkyl radicals as defined above and saturated hydrocarbon radicals having five carbon atoms, e.g. n-pentyl and the branched pentyl isomers; C_{1-6} alkyl includes C_{1-5} alkyl radicals as defined above and six carbon containing homologs, e.g. n-hexyl and the branched hexyl isomers. C_{1-12} alkyl includes C_{1-6} alkyl and saturated hydrocarbon radicals having from 7 to 12 carbon atoms, e.g. heptyl, octyl, nonyl, decyl, undecyl and their isomers. The term alkali metal cation in particular is a sodium or potassium cation. Trihalomethyl defines a



methyl group being fully substituted with halo atoms, in particular trifluoromethyl and trichloromethyl. C_{1-4} alkyloxyiminomethyl defines a radical of formula $-CH=N-O-C_{1-4}$ alkyl.

Particular compounds of formula (I) for use in the method are those wherein n is 0, 1 or 2; R^1 is hydrogen, C_{1-4} alkyl 6, benzyl; and R represents phenyl; naphthyl; pyridinyl; thienyl; furanyl optionally substituted with 1 to 3 substituents independently selected from C_{1-4} alkyl and C_{2-5} alkyloxycarbonyl; or phenyl substituted with 1 or 2 substituents independently selected from hydroxyl, halo, C_{1-12} alkyl, C_{5-6} cycloalkyl, trihalomethyl, phenyl, C_{1-5} alkoxy, C_{1-5} alkylthio, tetrahydropyranyloxy, phenoxy, ______

10

20

 C_{2-5} alkylcarbonyl, phenylcarbonyl, C_{1-4} alkylsulfinyl, C_{1-4} alkylsulfonyl, carboxy or its alkali metal salt, C_{1-5} alkoxycarbonyl, C_{2-5} alkylaminocarbonyl, phenylaminocarbonyl, tolylaminocarbonyl, morpholinocarbonyl, amino, nitro, cyano, or dioxolanyl.

- Of interest are those compounds wherein n is 1 and R represents phenyl, thienyl or phenyl substituted with one or two substituents selected from halo and trihalomethyl; or those wherein n is 2 and R represents phenyl or phenyl substituted with one or two substituents selected from halo and trihalomethyl.
- Of further interest are the compounds wherein R¹ is hydrogen, n is 1 or 2, and R represents phenyl, C₁₋₆alkylphenyl, halophenyl, dihalophenyl, biphenyl, C₁₋₅alkyloxy-oxyphenyl, trihalomethylphenyl, nitrophenyl, phenyl substrituted with C₂₋₅alkyloxy-carbonyl, C₁₋₆alkylnitrophenyl, unsubstituted furanyl or thienyl, or furanyl or thienyl substituted with ethoxycarbonyl, cyano, chlorine or bromine.

Of particular interest are the compounds wherein R¹ is hydrogen, n is 1 or 2, and R represents 3-fluorophenyl, 4-chlorophenyl, 3,4-dichlorophenyl, 3,5-dichlorophenyl, 3-trifluoromethylphenyl, 4-trifluoromethylphenyl, 4-methylphenyl, 3-ethanonephenyl, 3-nitrophenyl, 3-methyl-4-nitrophenyl or 2-thienyl.

Also of further interest are those compounds of formula (I) wherein R^1 is hydrogen, R is a radical of formula (b) wherein X is sulfur, Y is nitrogen or CH, and R'' is hydrogen.

Preferred compounds are 5,6-dihydro-3-(2-thienyl)-1,4,2-oxathiazine, 4-oxide and 3-(4-chlorophenyl)-5,6-dihydro-1,4,2-oxathiazine, 4,4-dioxide.

All compounds of formula (I) can be prepared following the procedures described in US-4,569,690.

The compounds of formula (I) are active against gram-positive bacteria and, more importantly for use in material protection, also against gram-negative bacteria.
 Susceptible bacteria belong to genera such as Aeromonas, Alcaligenes, Brevibacterium, Cellulomonas, Citrobacter, Corynebacterium, Enterobacter, Escherichia, Klebsiella, Micrococcus, Proteus, Providencia, Pseudomonas, Shewanella, Acinobacter, Bacillus,
 Serratia, Staphylococcus, Streptococcus and Xanthomonas.

The compounds of formula (I) further are active against fouling organisms. The term "fouling organisms" is meant to comprise organisms that grow on or adhere to various

20

25

30

35

kinds of surfaces, in particular in humid or aqueous environments such as, marine waters, fresh waters, brackish waters, rain water, and also cooling water, drainage water, waste water and sewage. Foul ganisms are Algae such as, for example, Microalgae, e.g. Amphora, Achnanthes, Navicula, Amphipora, Melosira, Cocconeis, Chlamydomonas, Chlorella, Ulothrix, Anabaena, Phaeodactylum, Porphyridium; Macroalgae, e.g. Enteromorpha, Cladophora, Ectocarpus, Acrochaetium, Ceramium, Polysiphonia; Molluscs, e.g. Mytilus, Crustacea, e.g. Artemia, Balanus, Elminius Modestus, Verruca, Lepas and Ascidia, Hydrozoa and Bryozoa.

The present invention also provides a method for the preservation of non-living materials other than wood against fungi that spoil or destroy such materials. Said method involves treating such materials with an effective fungicidal amount of a compound of formula (I).

The compounds of formula (I) are useful to protect a wide variety of non-living materials other than wood, and the objects made thereof or covered thereby. Examples of non-living materials and the objects made thereof or covered thereby comprise adhesives; sizes; paper and cardboard; pulp; textiles; leather; paints; plastics, e.g. PVC and polyester; industrial compositions such as cooling media, e.g. cooling lubricants and cutting fluids, coating compositions, bath compositions (process liquids), lubricants and the like; metals and alloys such as iron and steel; building materials, e.g. bricks, (paving) stones, cement and concrete; decorating materials, e.g. plaster, tiles; and any other materials that can be contaminated or destroyed by bacteria, fungi or fouling organisms.

Of particular interest are coating materials conventionally employed for decorative and protective purposes. The present method is especially suited for protecting adherent coatings, whether clear or colored (i.e. comprising one or more dyes or pigments), and whether natural or synthetic, such as, for example, paints - especially antifouling paint compositions -, varnishes, lacquers, finishes, whitewash and similar coatings. The particular aptness of the present method of protecting said coating materials resides in the fact that the oxathiazines employed in the method not only effectively protect the coating material in storage containers, during "in can" conservation (especially against bacteria) thus ensuring a long pot (or can) life and good storage stability, but also effectively protect the coating material and optionally its underlying substrate when it has been applied as a film to said substrate ("film" conservation). The simultaneous utility of the oxathiazines for both "in can" and "film" conservation of coatings is of great practical value.

As constructions made of or covered by said non-living materials there can be mentioned

WO 95/05739 PCT/EP94/02784

-5-

swimming pools, baths, cooling water circulation circuits and industrial baths in various installations, e.g. in manufactering plants or in air-conditioning installations, the function of which can be impaired by the presence and/or the multiplication of bacteria and fouling organisms. Further examples are buildings and parts of buildings such as floors, outer and inner walls or ceilings, of places suffering from dampness such as cellars, bathrooms, kitchens, washing houses and the like, and which are hot-beds for bacteria and/or fouling organisms. The presence of these organisms not only is problematic from the viewpoint of hygiene and aesthetics, but also causes economic losses because said buildings and/or decorating materials deteriorate more rapidly than desired.

10

15

20

25

3C

the substrate and /or the topcoat.

The method is especially suitable to protect underwater objects such as, for example, shiphulls, harbour installations, drying docks, sluice-gates, locks, mooring masts, buoys, drilling platforms, bridges, pipelines, fishing nets, cables and any other object in constant or frequent contact with water, by applying to said objects an antifouling composition, e.g. paint composition, comprising an effective antifouling amount of a compound of formula (I).

In this context it should be noted that the present method provides a safer and ecologically more acceptable alternative for current methods using antifouling products based on heavy metals such as cuprous oxide and the like, or those based on organometallic derivatives such as organo-tin compounds. The toxicity of the oxathiazines to mammals is acceptable and as such they are less hazardous for humans whether these compounds reach the human body by direct physical contact (e.g. during handling or application) or via the food chain. Their bio-degradability ensures that they are less persistent in the environment and that they cause less and shorter environmental pollution and stress. The chemical stability of the oxathiazines furthermore implies that they are compatible with most non-living materials as such and do need special precautions such as the addition of agents for stabilizing the active ingredient. In materials that should form films such as lubricants, cutting fluids and coating materials, they do not impair the formation of uniform films and the practicability. In particular, in coating materials they do not impair rapid curing in practical circumstances such as room temperature and outdoor conditions, and allow for strong adhesion of the composition to

The method of application is chosen in accordance with the intended objective and the prevailing circumstances. For instance, the technique used in the case of protecting lubricants, coatings or cutting fluids comprises mixing the active ingredient in said lubricants, coatings or fluids either during the manufacturing process or alternatively

WO 95/05739 PCT/EP94/02784

-6-

afterwards in the finished product. The active ingredient can be added in neat form or dissolved or suspended in a sufficient amount of diluent. Preferably the diluent consists of one or more of the solvents as they occur in the final composition.

The method also comprises applying compounds of formula (I), optionally in an appropriate formulation, to non-living materials by any of the techniques known in the art such as, for example, brushing, spraying, atomising, dipping, soaking, immersing, scattering and pouring. In some instances, the application may involve impregnation techniques using pressure or vacuum systems, thermal systems, injection or diffusion.

10

15

20

25

30

35

Appropriate formulations are formulated following art-known procedures to emulsifiable concentrates, directly sprayable or dilutable solutions, dilute emulsions, wettable powders, soluble powders, pastes, dusts, granulates, coating compositions, e.g. paints in particular antifouling paint compositions -, lacquers and the like. For example, the active compound can be mixed with an extender, which consists of a liquid, semi-solid or solid carrier, and optionally surface-active agents such as emulsifiers and/or dispersing agents. In coating compositions, the active compound may advantageously be incorporated in polymers, copolymers or resins. These can consist of such monomers as dialkyl (dimethyl) siloxanes, (meth)acrylic acid, (meth)acrylic acid esters, vinyl and allyl alcohols and derived esters (e.g. vinyl acetate), maleic acid, styrene, vinylchloride, butadiene, acrylamide, acrylonitrile and the like copolymerizable monomers. As resins there may be mentioned alkyd resins, polyurethanes, epoxy resins, phenolic resins and urea-formaldehyde resins. Further useful additives in said compositions comprise water-repelling agents and surface slipping agents that are capable of imparting a low surface tension of the coating film formed by the polymer or copolymer in the coating compositions.

Any suitable carrier or additive that does not interfere with the antibacterial nor the antifouling activity of the active ingredient can be used in the compositions of the present invention. The solid carriers or fillers used e.g. for dusts and powders include various inert, porous and pulverous distributing agents of inorganic or organic nature such as, for example, the natural mineral fillers, e.g. calcite, talcum, kaolin, montmorillonite or attapulgite, or fillers of organic nature, e.g. powdered cork, sawdust and other fine pulverous materials. In order to improve their physical properties it can be advantageous to add highly dispersed silicic acid or highly dispersed absorbent polymers. Suitable granulated absorbent carriers are of the porous type, for example, pumice, broken brick, sepiolite or bentonite; and suitable nonsorbent carriers are materials such as calcite or

10

15

20

25

30

35

sand. The active ingredient is mixed with these carrier substances, for example, by being ground therewith; alternatively, the inert carrier substance is impregnated with a solution of the active component in a readily volatile solvent and the solvent is thereafter removed by heating or by filtering with suction at reduced pressure. By adding wetting and/or dispersing agents, such pulverous preparations can also be made readily wettable with water, so that suspensions are obtained upon dilution. Inert diluents used for the production of liquid preparations should preferably not be readily inflammable and should be as far as possible non-toxic to nontarget animals or plants and humans in the relevant surrounding. Diluents suitable for this purpose are, for example, water or, organic solvents such as, for example, aromatic hydrocarbons, e.g. methylbenzene, dimethylbenzene mixtures, substituted naphthalenes; alcohols and glycols and their ethers and esters, e.g. ethanol, ethylene glycol, ethylene glycol monomethyl or monoethyl ether; ketones e.g. 2-propanone, cyclohexanone and the like; strongly polar solvents; e.g. N-methyl-2-pyrrolidone, dimethyl sulfoxide or dimethylformamide; vegetable oils or epoxidised vegetable oils such as epoxidised coconut oil or soybean oil, and mixtures thereof. Solutions can be prepared in the usual way, if necessary, with assistance of solution promotors. Other liquid forms which can be used consist of emulsions, dispersions or suspensions of the active compound in water or suitable inert diluents, or also concentrates for preparing such emulsions, dispersions or suspensions which can be directly adjusted to the required concentration. For this purpose, the active ingredient is, for example, mixed with a dispersing, suspending or emulsifying agent. The active component can also be dissolved or dispersed in a suitable inert solvent and mixed simultaneously or subsequently with a dispersing or emulsifying agent. It is also possible to use semi-solid carrier substances of cream, ointment, paste or waxlike nature, into which the active ingredient can be incorporated, if necessary, with the aid of solution promotors and/or emulsifiers. Vaseline, petroleum wax, liquid paraffin, silicone oil and other cream-bases are examples of semi-solid carrier substances. Furthermore, it is possible for the active ingredient to be used in the form of aerosols. For this purpose the active ingredient is dissolved or dispersed in a voictile liquid suitable for use as a propellant, for example, chlorinated and/or fluorinated derivatives of methane and ethane and mixtures thereof, or compressed air. In this way solutions under pressure are obtained which, when sprayed, yield aerosols that are particularly suitable for controlling or combatting bacteria and/or fouling organisms, e.g. in closed chambers and storage rooms. For the latter

Besides the compounds of formula (I) and the carrier, appropriate formulations often

purpose also smoke generators containing the active ingredient can be used.

15

20

25

30

35

comprise other adjuvants conventionally employed in the art of formulation. These depend on specific applications and the user's preference. Such adjuvants are, for example, organic binding agents (e.g. chemically drying organic binder-forming polymers such as alkyd resins or physically drying organic binder-forming solids by solvent evaporation); insecticides such as, for example, chlorinated hydrocarbons, e.g. endosulfan, organophosphates, e.g. chloropyriphos, pyrethroids, e.g. permethrin and the like; additional fungicides and bactericides such as alcohols, e.g. ethanol, 2,3,3-triiodallyl alcohol; aldehydes, e.g. formaldehyde, glutaraldehyde; formaldehyde releasing compounds, e.g. 2-bromo-2-nitro-propane-1,3-diol (bronopol), 2-bromo-2-nitropropan-1-ol; reaction products of amines and formaldehyde, e.g. triazines, 3,5-dimethyltetrahydro-1,3,5-2H-thiadiazine-2-thione; reaction products of amides and formaldehyde, e.g. 1-hydroxymethyl-2-thiono-1:2-dihydro-benzothiazol-Nhydroxymethylbenzothiazolinthione; phenols, e.g. 2-phenylphenol, pentachlorophenol; organic acids, e.g. propionic acid, benzoic acid, salicylic acid, naphthenic acid copper salts; inorganic acids, e.g. boric acid; amides, e.g. 2,5-dimethyl-N-cyclohexyl-Nmethoxy-furan-3-carbonamide; carbamates, e.g. 3-iodopropargyl-N-butylcarbamate (IPBC), methyl-N-benzinidazol-2-ylcarbamate (Carbendazim), methyl-N-(1butylcarbamoyl)benzimidazol-2-ylcarbamate (benomyl), zinc dimethyldithiocarbamate, zinc ethylenebisdithiocarbamate, bis-(dimethylthiocarbamoyl)disulphide; pyridine derivatives, e.g. 2-mercapto-pyridine-N-oxide, 2-chloro-6-(trichloromethyl)pyridine, 2,3,5,6-tetrachloro-4-(methylsulphonyl)pyridine, copper 8-hydroxyquinoline, 1-ethyl-1,4-dihydro-7-methyl-4-oxo-1,8-naphthyridine-3-carboxylic acid; azoles, e.g. tebuconazole, propiconazole, azaconazole, imazalil; heterocyclic compounds, e.g. 2methyl-3(2H)-isothiazolone, 5-chloro-2-methyl-3(2H)-isothiazolone, 2-n-octyl-4isothiazolin-3-one, 4,5-dichloro-2-(n-octyl)-4-isothiazolin-3-one, 1,2-benzisothiazolin-3-one, 2-methyl-4,5-trimethylene-4-isothiazolin-3-one, 2-(4-thiazolyl)-benzimidazole, 2mercaptobenzothiazole, 2-(thiocyanomethylthio)benzthiazole; N-haloalkylthio compounds, e.g. N-trichloromethylthiophthalimide, folpet, N-trichloromethylthio-4cyclohexane-1,2-dicarboximide, captan, N-1,1,2,2-tetrachloroethylthio-4-cyclohexene-1,2-dicarboximide, captafol, dichlofluanide, tolylfluanide; compounds with activated halogen groups, e.g. chlorothalonil; surface active agents, e.g. guanidines and biguanides; organometallic compounds, e.g. bis(tri-n-butyltin-oxide, tributyltin esters, tributyltin naphthenate, tributyltin linoleate, tributyltin benzoate, tributyltin fluoride; various compounds, e.g. pimaricine, tridemorph, methylene bisthiocyanate, tolyl sulfone, dicyanobutane; metal salts, e.g. chrome-copper-arsenic; active natural products, e.g. streptomycin; auxiliary solvents such as ethylglycol acetate and

methoxypropylacetate; processing additives; fixatives such as carboxymethyl-cellulose,

polyvinyl alcohol, paraffin; plasticizers such as benzoic acid esters and phthalates, e.g. dibutyl phthalate, dioctyl phthalate, diocdecyl phthalate; UV-stabilizers or stability enhancers; dyes; color pigments; siccatives such as cobalt octoate, lead octoate and cobalt naphthenate; corrosion inhibitors; antisettling agents; anti-skinning agents such as methyl ethyl ketoxime; antifoaming agents and the like. Generally, the adjuvants are not essential to the practice of the present invention but are included in particular formulations, especially in coating formulations to optimize overall effectiveness and ease of application. They can be used therein in the conventional amounts.

The antibacterial and/or antifouling compositions which are employed in the method of the invention can contain from 0.001% to 95% of the active ingredient by weight based on the total weight of the composition. Ready-to-use compositions such as paints preferably contain from 0.5% to 20%, in particular from 1 to 10% by weight of the active ingredient. Antifouling paint compositions on the other hand can contain from 10 up to 75%, in particular from 20 to 70% of the active ingredient of formula (I) by weight based on the total weight of the dry mass of said composition (i.e. up to 50%, in particular from 5 to 25% of the active ingredient by weight based on the total weight of the antifouling composition). Preferred compositions are composed in particular of the following constituents (all percentages are by weight):

Emulsifiable concentrates

active ingredient: 1 t

1 to 20%, preferably 5 to 10%

surfactant:

5 to 30%, preferably 10 to 20%

liquid carrier:

50 to 94%, preferably 70 to 85%

25

20

Dusts

active ingredient: 0.1 to 10%, preferably 0.1 to 1%

solid carrier:

99.9 to 90%, preferably 99.9 to 99%

30 <u>Suspension concentrates</u>

active ingredient: 5 to 75%, preferably 10 to 50%

water: 94 to 25%, preferably 88 to 30%

surfactant: 1 to 40%, preferably 2 to 30%

35 Granulates

active ingredient 0.5 to 30%, preferably 3 to 15%

solid carrier: 99.5 to 70%, preferably 97 to 85%

The following examples are not intended to limit, but to illustrate the scope of the

invention.

A. Biological Examples

Example 1: Efficacy against Bacteria and Yeasts.

Test solutions were prepared by dissolving the compounds shown in Tables 1-4 in 50% ethanol and further diluting with sterile distilled water. These test solutions were pipetted into Petri dishes and mixed with warm tryptose agar to reach an active ingredient concentration of 100 ppm. After cooling, the medium was inoculated with the following yeasts or bacteria:

10	Debaryomyces hansenii (yeast)	(A)
	Pseudomonas alcaligenes (gram neg)	(B)
	Bacillus cereus mycoides (gram pos)	(C)
	Pseudomonas aeruginosa (gram neg)	(D)
	Flavobacterium sp. (gram neg)	(E)
15	Streptomyces albus (gram pos)	(F)
	Enterobacter aerogenes (gram neg)	(G)
	Escherichia coli (gram neg)	(H)

After sufficient growth of the untreated cultures, the compounds were evaluated using the following rating system:

0 = growth equal to control.

1 = inhibition of growth by the compound.

2 = no growth under the influence of the compound.

25

The scores measured for antibacterial and antifouling efficacy of the compounds of this Extention are listed in Tables 1-4. The sign '-' signifies the compound was not tested.

Table 1

30

		Compounds				Bac	teria			
Co. no.	n	R	Α	В	С	D	Е	F	G	Н
1	1	4-chlcrophenyl	2	1	2	0	2	2	0	2
2	2	2,4-dichlorophenyl	2	0	2	0	2	0	G	. 0
3	1	3-nitrophenyl	2	2	2	1	2	2	1	2

										
		Compounds		 	Γ	Bac	teria	Γ	Υ	
4	1	3,4-dichlorophenyl	2	1	2	0	2	2	0	2
5	2	2-methylphenyl	2	0	2	0	2	2	0	1
6	1	3-fluorophenyl	2	1	2	0	2	2	0	2
7	1	2-furanyl	2	1	2	0	2	0	0	0
8	1	2-thienyl	2	2	2	1	2	2	2	2
9	1	3-methoxyphenyl	0	0	0	0	0	0	0	0
10	1	4-methylphenyl	2	1	2	1	2	2	0	2
11	2	4-methylphenyl	2	1	1	1	2	1	0	0
12	2	2-furanyl	0	0	0	0	0	0	0	0
13	1	3-trifluoromethyl phenyl	2	0	2	0	2	2	0	2
14	1	4-ethanonephenyl	2	1	2	1	2	2	0	2
15	1	2,6-dichlorophenyl	1	0	1	0	0	0	0	0
16	2	2,6-dichlorophenyl	2	0	2	0	0	0	0	0
17	2	phenyl	0	0	0	0	0	0	0	0
18	2	4-chlorophenyl	_	1	2	0	2	2	0	0
19	2	3,5-dichlorophenyl	-	0	2	0	2	2	0	0
20	1	4-butoxyphenyl	0	0	0	0	0	0	0	0
21	1	3,5-dichlorophenyl	-	2	2	0	2	2	0	0
22	1	4-benzoic acid ethyl ester	-	1	0	0	2	2	0	0
23	2	3-chlorophenyl	0	J	0	0	0	0	0	0
24	2	4-trifluoromethyl phenyl	-	0	2	0	2	2	2	0
25	1	4-trifluoromethyl phenyl	-	1	2	0	2	2	0	0
26	1	3-benzoic acid, methyl ester	-	0	2	0	2	2	0	0
27	2	3-bromophenyl	-	1	2	0	2	2	0	2
28	1	4-ethoxyphenyl	-	0	0	0	2	2	0	0

Table 2

$$\begin{array}{c|c}
R^1 & O \\
S & X \\
\downarrow & \downarrow \\
[O]_n & R^2 & R^3
\end{array}$$

Co. No.	R ¹	R ²	R ³	R ⁴	X	n	M.P. (° C)
29	Н	H	н	CO ₂ CH ₃	0	0	85-89
30	H	H	Н	CO ₂ CH ₃	0	2	126-129
31	Н	H	Н	CO ₂ CH ₃	0	1	118-119
32	Н	CH ₃	Н	Н	S	0	oil
33	Н	CH ₃	Н	Н	S	1	73-75
34	Н	H	Н	Н	S	2	99-101
35	H	H	Н	Br	S	0	82-83
36	Н	H	Н	Br	S	1	113-114
37	Н	CH ₃	Н	Н	S	2	60-62
38	H	H	Н	Br	s	2	118-119
39	H	H	CO ₂ CH ₃	CH ₃	0	0	87-88
40	H	H	Br	Н	S	0	74-75
41	Н	Н	Br	Н	S	1	169-173
42	H	H	Br	Н	S	2	126-127
43	H	H	CO ₂ CH ₃	CH ₃	0	2	156-157
44	H	H	CO ₂ CH ₃	CH ₃	0	1	147-148
45	H	H	CH ₃	CO ₂ CH ₃	S	1	150-152
46	H	Н	CH ₃	CO ₂ CH ₃	S	2	125-126
47	H	Н	Н	CH ₃	s	0	62-63
48	Н	H	Н	CH ₃	s	1	109-111
49	H	H	H	CH ₃	S	2	101-102
50	CH ₃	H	Н	Н	S	1	114-115
51	CH ₃	H	Н	Н	S	2	147-148
52	CH ₃	H	Н	H	S	0	70-72
53	H	H	Н	CO ₂ CH ₂ CH ₃	S	0	68-69
54	H	H	H	CO ₂ CH ₂ CH ₃	S	1	109-110
55	H	H	Н	CO ₂ CH ₂ CH ₃	S	2	123-124
56	H	H	Н	CN	S	0	136-137
57	H	Н	H	CN	S	1	160-162

Co. No.	R ¹	R ²	R ³	R ⁴	X	n	M.P. (° C)
58	Н	Н	Н	CN	S	2	153-155
59	Н	Н	Н	Cl	S	0	74-77
60	H	Н	Н	Cl	S	1	102
61	Н	H	Н	Cl	S	2	113-114
62	H	Н	H	CHO	S	0	48-49
63	Н	Н	Н	NO ₂	S	0	162-163
64	Н	Н	Н	NO ₂	S	1	186-188
65	H	Н	Н	NO ₂	S	2	160-161
66	H	Н	Н	CH=NOCH ₃	S	2	168-170
67	Н	Н	Н	C ₆ H ₅	S	0	100-103
68	Н	Н	Н	C ₆ H ₅	S	1	144-147
69	Н	Н	Н	C ₆ H ₅	S	2	95-98
70	H	Н	NO ₂	C ₆ H ₅	S	0	140-145
71	Н	Н	CH ₃	Br	S	0	oil
72	H	Н	CH ₃	Br	S	1	100-104
73	H	H	Br	CH ₃	S	0	64-67
74	H	Н	COOH	CH ₃	О	0	
75	H	H	CONHC6H5	CH ₃	0	0	
76	H	Н	CONHC6H5	CH ₃	0	0	
77	H	Н	CONHC6H5	CH ₃	0	0	

Table 2a

5

Co. No.	R ²	n	M.P. (° C)
78	Н	2	102-104
79	ਸ	1	106-107

Table 3

$$\begin{array}{c|c}
O & N \\
S & Y \\
\downarrow & Y
\end{array}$$

$$\begin{array}{c|c}
\downarrow & X \\
\downarrow & Y
\end{array}$$

$$\begin{array}{c|c}
\downarrow & Y
\end{array}$$

Co. No.	R"	X	Y	n	M.P.(°C)
80	Н	O	N	2	255
81	Н	О	N	1.	190-191
82	Н	О	N	0	143-144
83	Н	S	N	2	226-227
84	Н	S	N	0	150-151
85	Н	S	N	1	192-195
86	Н	S	CH	0	132-134
87	H	S	CH	1	140-142
88	H	S	CH	2	150-154
89	CH ₃	0	N	1	209-210
90	CH ₃	О	N	2	215-216
91	Н	S	C-OCH(CH ₃) ₂	1	oil

5 Table 4

Co. No.	R8	R ⁹	R ¹⁰	n	M.P.(°C)
92	Н	F	H	2	136-138
93	Н	F	Н	1	132-133
94	F	F	Н	2	106-108
95	F	F	H	1	128-130
96	F	F	Н	0	63-65
97	CF ₃	H	CF ₃	1	110-113
98	CF ₃	Н	CF ₃	0	44-48
99	CF ₃	H	CF ₃	2	76-78
100	F	H	Ŀ	0	103-104

Co. No.	R ⁸	R ⁹	R ¹⁰	n	M.P.(°C)
101	F	Н	F	2	108-110
102	F	Н	F	1	138-139
103	CO ₂ CH(CH ₃) ₂	Cl	H	0	oil
104	CO ₂ CH(CH ₃) ₂	Cl	H	1	127-129
105	CO ₂ CH(CH ₃) ₂	Cl	H	2	82-83
106	Н	CH=NOCH ₃	H	1	85-87
107	Н	CH=NOCH ₃	Н	2	104-106

Example 2: Efficacy against Fresh-water algae

9 ml of Bold's algal broth containing an appropriate concentration of test compound, was inoculated in a 5.5 cm diameter plastic Petri dish with 1 ml of a two week old stock culture of one of three species of green algae (Chlamydomonas dysosmos, Chlorella vulgaris or Ulothrix confervicola) or the blue-green bacterium Anabaena cylindrica. The dishes were incubated in a climate room under a photosynthetically active radiation level of 40 µmole.m⁻².sec⁻¹ at 20°C during the day (16 h) and 18°C at night (8 h). Evaluation was performed after 14 days by visually estimating the percentage of algal growth as 10 compared to controls. Results are expressed as minimum test concentration (in ppm) giving 90% mortality.

		Compounds	Concentration (ppm)				
Co. no.	n	R	Chlamydomonas	Chlorella	Ulothrix	Anabaena	
			dysosmos	vulgaris	confervicola	cylindrica	
4	1	3,4-dichlorophenyl	2.5	10	2.5	2.5	
8	1	2-thienyl	2.5	5	1	2.5	
18	2	4-chlorophenyl	2.5	10	5	2.5	
19	2	3,5-dichlorophenyl	5	10	2.5	2.5	
21	1	3,5-dichlorophenyl	1	5	1	2.5	
25	1	4-trifluoromethyl phenyl	2.5	10	2.5	5	

Example 3: Efficacy against Marine algae 15

9 ml c' Provasoli ASP-2 (Artificial Seawater-2) medium containing an appropriate concentration of test compound, was inoculated in a 5.5 cm diameter plastic Petri dish with 1 ml of a two weeks old stock culture of the diatom Phaeodactylum tricornutum or the unicellar red alga Porphyridium sp. The dishes were incubated in a climate room

under a photosynthetically active radiation level of 40 μ mole.m⁻².sec⁻¹ at 20°C during the day (16 h) and 18°C at night (8 h). Evaluation was performed after 14 days by visually estimating the percentage of algal growth as compared to controls. Compounds 1, 2, 3, 4, 5, 14, 15, 16, 18, 19, 21, 25, 27 caused 90% mortality at

5 concentration levels equal to or lower than 1 ppm.

Example 4: Efficacy against Artemia

Into 1 ml of artificial sea-water containing different amounts of the test compound, approximately 15 *Artemia* Instar II larvae were added. After 24 hours of static

- incubation with continuous illumination the test was evaluated.

 Compounds 2, 4, 5, 11, 13, 18, 19 caused 100% mortality at concentration levels equal to or lower than 10 ppm.
 - B. Composition examples (all percentages are by weight)
- 15 <u>Example 5</u>: Composition examples for solid compounds of formula (I)
 - a) Emulsifiable concentrates: emulsions of any concentration could be obtained from these concentrates by dilution with water.

		a)	b)
	compound of formula (I)	10%	1%
20	octylphenol polyethylene glycol ether		
	(4-5 moles of ethylene oxide)	3%	3%
	calcium dodecylbenzenesulfonate	3%	3%
	castor oil polyglycol ether		
	(36 moles of ethylene oxide)	4%	4%
25	cyclohexanone	30%	10%
	dimethylbenzene mixture	50%	79%

	b) Dusts: were obtained by mixing the	active ingredient wi	th the carriers, and	grinding
	the mixture in a suitable mill.	a)	b)	
30	compound of formula ()	0.1%	1%	
	talcum	99.9%	-	
	kaolin	-	99%	

c) Suspension concentrates from which suspensions of any desired concentration could be obtained by dilution with water were obtained by intimately mixing finely ground active ingredient with the adjuvants.

a)

b)

compound of formula (I)

ethylene glycol

nonylphenol polyethylene glycol ether

	. ~	
	. ,	
•		-

(15 moles of ethylene oxide)	6%	1%
sodium lignosulfate	10%	5%
carboxymethylcellulose	1%	1%
37% aqueous formaldehyde solution	0.2%	0.2%
silicone oil in the form of a 75%		
aqueous emulsion	0.8%	0.8%
water	32%	77%

Example 6: Composition examples for liquid active ingredients of formula (I)

a) Emulsifiable concentrates: emulsions of any concentration could be obtained from these concentrates by dilution with water.

		a)	b)	c)
	compound of formula (I)	20%	40%	50%
	calcium dodecylbenzenesulfonate	5%	8%	5.8%
15	castor oil polyethylene glycol ether			
	(36 moles of ethylene oxide)	5%	-	-
	tributylphenol polyethylene glycol eth	ner		
	(30 moles of ethylene oxide)	-	12%	4.2%
	cyclohexanone	-	15%	20%
20	dimethylbenzene mixture	70%	25%	20%

b) Solutions suitable for application in the form of microdrops.

			•		
		a)	b)	c)	d)
	compounds of formula (I)	80%	10%	5%	95%
25	ethylene glycol monoethyl ether	20%	-	-	-
	polyethylene glycol (MG 400)	-	70%	-	-
	N-methyl-2-pyrrolidone	-	20%	-	-
	epoxidised coconut oil	-	-	1%	5%
	petroleum distillate (boiling range				
30	160-190°C)	-	-	94%	-

c) Granulates: prepared by dissolving the active ingredient in dichloromethane, spraying the solution onto the carrier, and subsequently evaporating the solvent.

		a)	b)
35	compound of formula (I)	5%	10%
	kaolin	94%	-
	highly dispersed silicic acid	1%	-
	attapulgite	-	90%

d) Dusts: were obtained by intimately mixing the carriers with the active ingredient.

		a)	b)
	compound of formula (I)	2%	5%
5	highly dispersed silicic acid	1%	5%
	talcum	97%	-
	kaolin	-	90%

Example 7: Composition examples for paints

10	a)	Compound of formula (I)	6.0 %
		Titanium dioxide	17.1 %
		Whiting	9.7 %
		Talc	13.2 %
		Calgon	0.1 %
15		Hydroxyethylcellulose (3% solution in water)	12.5 %
		Co-solvent	1.2 %
		Minor additives	0.4 %
		Water	27.7 %
20		Vinyl acetate/versatate copolymer emulsion	12.1 %
	b)	Compound of formula (I)	1.0 %
		Titanium dioxide	26.4 %
		Soya alkyd resin	44.0 %
25		White spirit	27.5 %
		Cobalt octoate (8%)	0.3 %
		Lead octoate (33%)	0.7 %
		Methyl ethyl ketoxime	0.1 %

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of controlling bacteria and fouling organisms, said method comprising administering to said bacteria or fouling organisms, or to the locus thereof, an effective antibacterial or antifouling amount of a compound having the formula

$$R^1 \xrightarrow{O_N} R$$
 (D)

wherein n is 0, 1 or 2; R¹ is hydrogen, C¹-4alkyl or benzyl; and R represents

(a) phenyl; phenyl substituted with 1 to 3 substituents independently selected from hydroxyl, halo, C¹-12alkyl, C⁵-6cycloalkyl, trihalomethyl, phenyl, C¹-5alkoxy, C¹-5alkylthio, tetrahydropyranyloxy, phenoxy, C¹-4alkylcarbonyl, phenylcarbonyl, C¹-4alkylsulfinyl, C¹-4alkylsulfonyl, carboxy or its alkali metal salt, C¹-4alkyloxy-carbonyl, C¹-4alkylaminocarbonyl, phenylaminocarbonyl, tolylaminocarbonyl, morpholinocarbonyl, amino, nitro, cyano, dioxolanyl or C¹-4alkyloxyiminomethyl; naphthyl; pyridinyl; thienyl; furanyl; or thienyl or furanyl substituted with one to three substituents independently selected from C¹-4alkyl, C¹-4alkyloxy, C¹-4alkylthio, halo, cyano, formyl, acetyl, benzoyl, nitro, C¹-4alkyloxycarbonyl, phenyl, phenylaminocarbonyl and C¹-4alkyloxyiminomethyl; or R represents a radical of formula

wherein X is oxygen or sulfur; Y is nitrogen, CH or $C(C_{1-4}alkyloxy)$; and R" is hydrogen or $C_{1-4}alkyl$.

- 2. A method acc reling to claim 1 of protecting non-living materials other than wood, and the objects made of or covered by said non-living materials, against bacteria and fouling organisms, said method comprising applying to the surface or incorporating into said materials or objects an effective antibacterial or antifouling amount of a compound of formula (I).
- 3. A method according to claim 2 wherein the compound of formula (I) is 5,6-dihydro-3-(2-thienyl)-1,4,2-oxathiazine, 4-oxide or 3-(4-chlorophenyl)-5,6-dihydro-1,4,2-



5

10

15

20

25

30

oxathiazine, 4,4-dioxide.

- 4. A method according to claim 2 wherein the non-living material is an adherent coating material.
- 5. A method according to claim 4 wherein the adherent coating material is paint, antifouling paint, varnish, lacquer, finish or whitewash.
- 6. A method according to claim 4 to 5 wherein the adherent coating material is conserved in a storage container or wherein the coating material has been applied as a film to a substrate.
- 7. A method according to claim 2 for protecting an underwater object by applying to said object an antifouling composition comprising an effective antifouling amount of a compound of formula (I) as defined in claim 1.
- 8. A method according to claim 7 wherein the underwater object is a shiphull, harbour installation, drying dock, sluice gate, lock, mooring mast, buoy, drilling platform, bridge, pipeline, fishing net, cable or any other object in constant or frequent contact with water.
- 9. A method according to claim 2, wherein the compound of formula (I) is applied in the form of a composition comprising the compound of formula (I) and a suitable carrier, the amount of the compound of formula (I) ranging from 0.001% to 95% by weight based on the total weight of the composition.
- 20 10. A coating composition comprising:
 - (a) as active ingredient a compound of formula (I) as defined in claim 1, and
 - (b) a polymer or copolymer or resin.



i5

- 11. A coating composition according to claim 10 wherein the polymer or copolymer is derived from such monomers as dialkyl siloxanes, (meth)acrylic acid, (meth) acrylic acid esters, vinyl and allyl alcohols and derived esters, maleic acid, styrene, vinylchloride, butadiene, acrylamide or acrylonitride.
- 12. A coating composition according to claim 10 or 11 wherein the resin is selected from alkyd resins, polyurethanes, epoxy resins, phenolic resins or urea-formaldehyde resins.
 - 13. A coating composition according to any one of claims 10 to 12 further comprising one or more additives selected from the group consisting of water-repelling agents; surface slipping agents; organic binding agents; insecticides; fungicides; bactericides; auxiliary solvents; processing additives; fixatives; plasticizers; UV-stabilizers or stability enhancers; dyes; color pigments; siccatives; corrosion inhibitors; antisettling agents; anti-skinning agents; and antifoaming agents.
- 14. A composition according to any one of claims 10 to 13 in the form of an
 antifouling paint composition comprising from 10% up to 75% by weight of the active ingredient based on the total weight of the dry mass of said antifouling paint composition.
 - 15. A method of controlling bacteria and fouling organisms, which method is substantially as herein described with reference to any one of the Examples.
- 20 16. A coating composition as claimed in claim 10 substantially as herein described with references to any one of the Examples.

DATED this 13th Day of May 1997 JANSSEN PHARMACEUTICA N.V.

Attorney: RUTH M. CLARKSON
Fellow Institute of Patent Attorneys of Australia
of SHELSTON WATERS

INTERNATIONAL SEARCH REPORT

Inten Aal Application No
PCT/EP 94/02784

		1 , 2
A. CLASS IPC 6	IFICATION OF SUBJECT MATTER A01N43/88	
	to International Patent Classification (IPC) or to both national class	ification and IPC
	S SEARCHED locumentation searched (classification system followed by classification system followed by class	Non-amelia (a)
IPC 6	A01N	uon symbols)
Documenta	tion searched other than minimum documentation to the extent that	such documents are included in the fields searched
Electronic	data base consulte I during the international search (name of data be	ase and, where practical, search terms used)
C. DOCUN	MENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the	relevant passages Relevant to claim No.
A	EP,A,O 104 940 (UNIROYAL) 4 Apri & US,A,4 569 690 (ID) cited in the application	1 1984
Fur	ther documents are listed in the continuation of box C.	Y Patent family members are listed in annex.
'A' docur consi 'E' carlier filing 'L' docum which citativ 'O' docur other	nent defining the general state of the art which is not dered to be of particular relevance. I document but published on or after the international date described by the doubts on priority claim(s) or nis cited to establish the publication date of another on or other special reason (as specified) ment referring to an oral disclosure, use, exhibition or means the published prior to the international filing date but than the priority date claimed	 "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family
j	e actual completion of the international search	Date of mailing of the international search report
	November 1994	1 6. 11. 94
Name and	mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax (+ 31-70) 340-3016	Authonzed officer Decorte, D

INTERNATIONAL SEARCH REPORT

Inten nal Application No PCT/EP 94/02784

Patent document cited in search report	Publication date	Patent family niember(s)	Publication date
EP-A-0104940	04-04-84	AU-B- 544881 AU-A- 1961883 CA-A- 1273921 GB-A,B 2127817 JP-A- 59080670 US-A- 4569690 US-A- 4675044	20-06-85 05-04-84 11-09-90 18-04-84 10-05-84 11-02-86 23-06-87
US-A-4569690	11-02-86	AU-B- 544881 AU-A- 1961883 CA-A- 1273921 EP-A- 0104940 GB-A,B 2127817 JP-A- 59080670 US-A- 4675044	20-06-85 05-04-84 11-09-90 04-04-84 18-04-84 10-05-84 23-06-87