




US 20160242595A1

(19) **United States**(12) **Patent Application Publication**
Caswell(10) **Pub. No.: US 2016/0242595 A1**(43) **Pub. Date: Aug. 25, 2016**(54) **FLUID MIXING APPARATUS AND METHODS**(71) Applicant: **ROASTING PLANT, INC.**, New York,
NY (US)(72) Inventor: **Michael R. Caswell**, New York, NY
(US)(21) Appl. No.: **14/857,401**(22) Filed: **Sep. 17, 2015****Related U.S. Application Data**(62) Division of application No. 11/699,979, filed on Jan.
30, 2007, now Pat. No. 9,167,936.**Publication Classification**(51) **Int. Cl.***A47J 31/44* (2006.01)*A23F 5/24* (2006.01)*A23C 9/156* (2006.01)(52) **U.S. Cl.**CPC *A47J 31/4496* (2013.01); *A23C 9/156*
(2013.01); *A23F 5/246* (2013.01); *A47J*
31/4489 (2013.01)(57) **ABSTRACT**

Apparatus and methods are provided for making a beverage or providing a liquid. First and second liquids may be mixed to form a mixed liquid. The mixed liquid may be passed through a frothing head and/or may be combined with a coffee product and optionally dispensed into a cup. Examples of first and second liquids can include, but are not limited to various dairy products, enzymes and flavoring liquids. According to one example implementation, a first liquid is a reduced fat milk, such as skim milk, and a second liquid is whole milk, thereby enabling the creation of dairy product varieties including one percent and two percent milk to be created by the appropriate mixture combination of the skim milk and whole milk.






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6

FLUID MIXING APPARATUS AND METHODS

FIELD OF THE INVENTION

[0001] This invention relates broadly to the beverage industry. More particularly, this invention relates to apparatus and methods for the mixing of multiple liquids.

BACKGROUND

[0002] The production of beverage milks combines the operations of clarification, separation for the production of lower fat milks, pasteurization, and homogenization. While the fat content of most raw milk is 4% or higher, the fat content in most beverage milks has been reduced to 3.4%. Lower fat alternatives, such as 2% fat, 1% fat, or skim milk (<0.1% fat) are also available in most markets. These products are either produced by partially skimming the whole milk, or by completely skimming it and then adding an appropriate amount of cream back to achieve the desired final fat content.

[0003] Milk is a major ingredient in espresso and cocoa-based gourmet beverages, specifically cappuccino, mocha, hot cocoa, and latte beverages, both hot and iced. One method for producing cappuccino and latte beverages is through the use of super-automated brewing equipment. These machines come equipped as two-step or one-step machines, referring to the number of steps required by the operator to produce the milk/espresso beverage. Two-step machines require the operator to first hand steam the milk component and then combine the milk with espresso that is produced automatically by the machine or with cocoa. One-step machines automatically steam and combine the milk component with automatically produced espresso.

[0004] A major limitation of existing available one-step machines is the variety of milk that is available to the consumer. Machines currently available can only handle one milk variety due to limitations in milk storage, plumbing, and recipe programming capacity.

[0005] In the North American market in particular this creates a problem and major limitation for the commercial viability of these one-step machines because the educated coffee consumer has become accustomed to choosing between, skim, 1%, 2%, and whole (3.4%) milk. Retailers typically steam milk by hand in order to offer this variety of milk to their customers. This results in slower customer service, product inconsistency and more milk waste.

SUMMARY

[0006] Various embodiments of the present invention can address some of the deficiencies of the art and are usable with many types of brewing equipment. Examples of the present invention may be used in a wide variety of applications to provide an ability to automatically mix fluids, including dairy products, in order to provide a desired fluid as an additive to a beverage.

[0007] Various embodiments of the invention may provide methods or apparatus for providing a beverage and/or addition to a beverage. According to an illustrative embodiment of the invention, an apparatus provides a liquid. In this embodiment, the apparatus includes a water input; a first liquid input in fluid communication with a first liquid storage; a second liquid input in fluid communication with a second liquid storage; a mixing chamber in fluid communication with the first liquid input and second liquid input and adapted to pro-

vide a mixture of the first liquid and the second liquid; and a frothing head in fluid communication with the mixing chamber, the frothing head adapted to receive the mixture; wherein the water input is in fluid communication with a dispenser and the dispenser and the frothing head are configured to output into a liquid container.

[0008] In another illustrative embodiment of the invention, an apparatus for providing a liquid includes a frothing head; a first liquid pump having a first output coupled to the frothing head and having a first input coupled to a first refrigerated liquid container; and a second liquid pump having a second output coupled to the frothing head and having a second input coupled to a second refrigerated liquid container.

[0009] According to one illustrative embodiment of the invention, an apparatus for providing a beverage includes a brewing chamber configured to receive coffee grounds and water and to output coffee; a mixing chamber in fluid communication with a first liquid input and a second liquid input and adapted to output a mixture of the first liquid and the second liquid; and a beverage container region having at least one element defining a border of the region, wherein the mixing chamber is in fluid communication with the beverage container region to dispense the mixture into the beverage container region and wherein the brewing chamber is in fluid communication with the beverage container region to dispense the coffee into the beverage container region.

[0010] According to one illustrative embodiment of the invention, a method of making a beverage includes the acts of obtaining a first liquid dairy product; obtaining a second liquid dairy product; receiving an instruction to specify a mixture of the first liquid dairy product and the second liquid dairy product; automatically mixing the first liquid dairy product and the second liquid dairy product to form a mixed dairy product; dispensing the mixed dairy product into a cup; and dispensing a coffee product into the cup.

[0011] A method of making a beverage includes receiving an instruction to specify a mixture of a first liquid dairy product and an enzyme; mixing the first liquid dairy product and the enzyme according to the instruction; dispensing the mixed first liquid dairy product and the enzyme into a cup; and dispensing a coffee product into the cup.

[0012] A further method of making a beverage according to another illustrative embodiment of the invention includes receiving an instruction to specify a mixture of a first liquid dairy product and a flavoring liquid; mixing the first liquid dairy product and the flavoring liquid according to the instruction; dispensing the mixed first liquid dairy product and the flavoring liquid into a cup; and dispensing a coffee product into the cup.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a schematic illustration of a first embodiment of an apparatus for providing a liquid according to an embodiment of the invention.

[0014] FIG. 2 is a schematic illustration of an apparatus for providing a liquid according to a further illustrative embodiment of the invention.

[0015] FIG. 3 illustrates an apparatus for providing a beverage according to a further illustrative embodiment of the invention.

[0016] FIGS. 4 through 6 provide example flowchart illustrations of various methods of making a beverage according to further example embodiments of the invention.

DETAILED DESCRIPTION

[0017] According to various embodiments of this invention, methods and devices are provided for making a beverage and/or providing a liquid. First and second liquids may be mixed to form a mixed liquid. The mixed liquid may be passed through a frothing head and/or may be combined with a coffee product and optionally dispensed into a cup. Examples of first and second liquids can include, but are not limited to various dairy products, enzymes and flavoring liquids. According to an example implementation, a first liquid is a reduced fat milk, such as skim milk, and a second liquid is whole milk, thereby enabling the creation of dairy product varieties including one percent and two percent milk to be created by the appropriate mixture combination of the skim milk and whole milk.

[0018] An illustrative embodiment of the invention is provided in FIG. 1. The apparatus **100** for providing liquid includes a mixing chamber **110** having a first liquid input **120** and a second liquid input **130**. The first liquid input **120** is in fluid communication with a first liquid storage **140** and the second liquid input **130** is in communication with a second liquid storage **150**. The mixing chamber **110** is configured to output a mixture of the first liquid and the second liquid. It is understood that the output of the mixing chamber **110** may not be fully mixed so as to be uniform mixture of the first liquid and second liquid, although further mixture of the fluids may occur in a frothing head **160** and/or a liquid container **200**. Alternatively, the mixing chamber **110** may provide a thoroughly mixed output.

[0019] The output of the mixing chamber **110** is coupled to the frothing head **160** that is configured to froth the output of the mixing chamber. Frothing of the output may be performed in a wide variety of ways known in the art, including the injection of air into the fluid passing through the frothing head. Optionally, a heating element **170** may be provided proximate to the frothing head to heat the output of the mixing chamber **110**. A water input **180** is also provided with the apparatus **100**. The water input **180** is in fluid communication with a dispenser **190**. Both the dispenser **190** and the frothing head **160** are configured to output into the liquid container **200**. The invention can be used with a wide variety of liquid containers **200**, such as for example, a coffee mug, a pitcher, a vat and/or a bucket.

[0020] Optionally, a brewing chamber **185** may be provided in fluid communication with the water input **180** and the dispenser **190**. The brewing chamber **185** may be used to brew a beverage such as coffee. Brewing methods can include, but are not limited to, percolation, French press, espresso, drip, cold and vacuum brewing.

[0021] The first liquid storage **140** and second liquid storage **150** may be refrigerated and may be used to store a wide variety of liquids. Examples of liquids can include, but are not limited to dairy products such as reduced fat milk, skim milk, one percent milk, two percent milk, whole milk and heavy cream. Other examples of fluids can include a flavorizing liquid that can be used to provide a flavor to the output of the mixing chamber **110**. Another example of a fluid for use in the first liquid storage **140** or second liquid storage **150** is an enzyme.

[0022] Examples of enzymes can include, but are not limited to, enzymes to enable digestion of milk by a lactose-intolerant person. In one example, the enzyme can break down at least some of the lactose in the milk to create a digestible sugar, as is understood in the art.

[0023] Various embodiments of the invention can provide a liquid mixing capability that can enable the delivery of any milk fat percentage in any size beverage, by the cup, and on-demand, including while utilizing one-step super automated brewing equipment, such as, but not limited to, the Egro 50 Series super-automated brewing system. This milk handling strategy can be provided with an ability to store the milk in connection with the automated brewing equipment or may utilize a separate milk storage system, such as a separate refrigerator.

[0024] By utilizing two milks, such as, for example a reduced fat milk, such as, for example skim (<0.1% fat), and whole (3.4% fat), and combining them in various proportions as they enter the one or more frothing heads, the creation of unlimited permutations of delivered milk fat content is provided, in any beverage size, to the final beverage cup.

[0025] According to a second illustrative embodiment of the invention, an apparatus **300** may provide a liquid. The apparatus **300** is illustrated by way of example in FIG. 2. The apparatus **300** includes a first liquid pump **310** and a second liquid pump **320**. Each of the liquid pumps **310**, **320** is configured to have a liquid input coupled to a refrigerated liquid container. The first pump **310** has a liquid input coupled to a first refrigerated liquid container **330**, while the second pump **320** has a input coupled to a second refrigerated liquid container **340**. A controller **350** is provided to control the timing and rate of operation of each of the pumps **310**, **320**. The pumps **310**, **320** are configured to output to a frothing head **360**. By use of the controller **350**, the first pump **310** and/or second pump **320** may be activated to provide a desired mixture of a liquid contained in the first refrigerated liquid container **330** and the liquid contained in the second refrigerated liquid container **340**. According to one example implementation of the invention, skim milk may be located in the first refrigerated liquid container **330** and whole milk may be located in the second refrigerated liquid container **340**. In another example implementation of the invention, a dairy product may be located in the first refrigerated liquid container **330** and an enzyme may be located in the second refrigerated liquid container **340**.

[0026] By enabling the independent but simultaneous control of each pump **310**, **320**, milk can be combined in a range from 100% of a first fluid, such as skim milk to 100% of a second fluid, such as whole milk, or any mixture of the two. By way of illustration, if a customer orders a whole milk latte, the recipe can include instructions to activate only the pump connected to the liquid container having whole milk, thereby delivering 100% whole milk to the frothing head(s) and, eventually, beverage cup. If the customer orders a 2% milk latte, then the recipe instructions will include signals to drive both pumps **310**, **320** in a manner that delivers the appropriate percentage of each milk so that when combined at the frothing head(s) the resulting steamed or cold milk contains 2% milk fat.

[0027] For 1% milk orders the recipes would specify 29% by volume whole milk, and 71% by volume nonfat milk, yielding 1% milk fat content in the cup. Similarly the system could deliver milk at 0.5%, 1.5%, or 2.5% or any other % in between 0% and 3.4% by programming the appropriate ratio. Also, should a higher milk fat content be desired the whole milk ingredient could be replace by half & half, light cream, heavy cream etc. and the associated milk fat % would be calculated in order to deliver the correct final milk fat content (4, 5, 6% etc.) in the beverage. For skim milk orders, the

recipe will include instructions to activate only the pump connected to the liquid container having skim milk, thereby delivering 100% skim milk to the frothing head(s) and beverage cup.

[0028] According to a third example embodiment of the invention, an apparatus 400 for providing a beverage may be provided as illustrated by way of example in FIG. 3. A brewing chamber 410 is configured to receive coffee grounds and water and to output coffee. A mixing chamber 420 is in fluid communication with a first liquid input 422 and a second liquid input 424 and can output a mixture of the first liquid and second liquid. A beverage container region 430 is also provided having at least one element 432 defining a border of the region 430. The mixing chamber 420 is in fluid communication with the beverage container region 430 to dispense a mixture of the first liquid and second liquid into the beverage container region 430. The brewing chamber 410 is in fluid communication with the beverage container region 430 to dispense the coffee into the beverage container region 430.

[0029] Optionally, a coffee bean grinder 440 may be provided to grind coffee beans and provide the coffee grounds to the brewing chamber 410. Also optionally, a first and/or second refrigerated liquid storage 450, 460 may be provided in fluid communication with the first liquid input 422 and second liquid input 424, respectively, of the mixing chamber 420. Optionally, a frothing head 470 may be provided in fluid communication with the mixing chamber 420 and the beverage container region 430 so as to froth an output of the mixing chamber 420. Optionally, an input device 480 may be provided to receive an instruction to specify a desired mixture of the first liquid and second liquid.

[0030] A wide variety of fluids may be stored in the first and second refrigerated liquid storage 450, 460. Examples include, but are not limited to skim milk, one percent milk, two percent milk, whole milk, heavy cream, an enzyme and a flavoring liquid. According to an example implementation of the invention, the input device 480 may receive an instruction to mix two percent milk. The first refrigerated liquid storage 450 may have skim milk located therein, and the second refrigerated liquid storage 460 may have whole milk located therein. By an appropriate mixture of the skim milk and whole milk, the desired two percent milk may be mixed by the mixing chamber 420 and therefore output to the beverage container region 430.

[0031] An element 432 of the beverage container region 430 may include a sidewall, base plate, top plate, one or more posts and/or a marking so as to define at least a portion of a border of the beverage container region 430. The beverage container region 430 is intended to receive and optionally store a beverage container, thereby locating the beverage container 490, such as a coffee cup, to receive the output of the brewing chamber 410 and mixing chamber 420, optionally through the frothing head 470.

[0032] By way of example, in operation, if the input device 480 receives instructions for a 16 oz latte beverage, the recipe could specify 2 oz of espresso, and 14 oz of milk. In order to deliver 14 oz of 2% milk, the recipe could specify the delivery of 8.24 oz (59% by volume) whole milk and 5.76 oz (41% by volume) skim. For larger and smaller 2% milk drinks, the milk volumes would be adjusted utilizing the 59/41% ratio.

[0033] According to a further example embodiment of the invention, a method of making a beverage is provided as illustrated by way of example in FIG. 4. The method 500 includes obtaining 510 a first liquid dairy product and obtain-

ing 520 a second liquid dairy product. Examples of liquid dairy products include, but are not limited to reduced fat milk, skim milk, one percent milk, two percent milk, whole milk and heavy cream. An instruction is received 530 to specify a mixture of the first liquid dairy product and the second liquid dairy product. The first liquid dairy product and second liquid dairy product are automatically mixed 540 to form a mixed dairy product. The mixed dairy product is dispensed 550 into a cup. The coffee product is also dispensed 560 into the cup. Optionally, the mixed dairy product may be heated prior to dispensing 550 the mixed dairy product into the cup. Optionally, steam may be injected into the mixed dairy product prior to dispensing 550 the mixed dairy product into the cup.

[0034] A further example embodiment of the invention is a method 600 of making a beverage as illustrated by way of example in FIG. 5. The method includes receiving 610 an instruction to specify a mixture of a first liquid dairy product and an enzyme. The first liquid dairy product and enzyme are mixed 620 according to the instruction. The mixed first liquid dairy product and the enzyme are dispensed 630 into a cup. Also, a coffee produce is dispensed 640 into the cup. Optionally, a second liquid dairy product may be mixed with the first liquid dairy product and/or the enzyme. In such a case, dispensing 630 the mixed first liquid dairy product and the enzyme into the cup also includes dispensing the mixed second liquid dairy product.

[0035] According to a further exemplary embodiment of the invention, a method 700 is provided by way of example in FIG. 6. The method 700 is a method of making a beverage and includes receiving 710 an instruction to specify a mixture of a first liquid dairy product and a flavoring liquid. The first liquid dairy product and the flavoring liquid are mixed 720 according to the instruction. The mixed first liquid dairy product and the flavoring liquid are dispensed 730 into a cup. Also, a coffee product is dispensed 740 into the cup. Optionally, a second liquid dairy product may be mixed with the first liquid dairy product and/or the flavoring liquid. In such an implementation, dispensing 730 the mixed first liquid dairy product and the flavoring liquid into the cup also includes dispensing the mixed second liquid dairy product.

[0036] The illustrative embodiments, implementations and examples herein are meant to be illustrative and not limiting. The present invention has been described by way of example, and modifications and variations of the exemplary embodiments will suggest themselves to skilled artisans in this field without departing from the spirit of the invention. Features and characteristics of the above-described embodiments may be used in combination. The preferred embodiments are merely illustrative and should not be considered restrictive in any way.

1. An apparatus for providing a liquid, comprising: a water input;
 - a first liquid input in fluid communication with a first liquid storage;
 - a second liquid input in fluid communication with a second liquid storage;
 - a mixing chamber in fluid communication with the first liquid input and second liquid input and adapted to provide a mixture of the first liquid and the second liquid; and
 - a frothing head in fluid communication with the mixing chamber, the frothing head adapted to receive the mixture;

wherein the water input is in fluid communication with a dispenser and the dispenser and the frothing head are configured to output into a liquid container.

2. The apparatus of claim 1, further comprising an input device to receive an instruction to specify the mixture of the first liquid and the second liquid.

3. The apparatus of claim 1, wherein the first liquid storage is a refrigerated liquid storage.

4. The apparatus of claim 1, further comprising skim milk in the first liquid storage.

5. The apparatus of claim 1, further comprising whole milk in the first liquid storage.

6. The apparatus of claim 1, further comprising an enzyme in the first liquid storage and a dairy product in the second liquid storage.

7. The apparatus of claim 1, further comprising a flavoring liquid in the first liquid storage.

8. The apparatus of claim 1, further comprising a heating element proximate to the frothing head to heat the mixture.

9. The apparatus of claim 1, further comprising a brewing chamber in fluid communication with the water input and the dispenser.

10. An apparatus for providing a liquid, comprising: a frothing head;

a first liquid pump having a first output coupled to the frothing head and having a first input coupled to a first refrigerated liquid container; and

a second liquid pump having a second output coupled to the frothing head and having a second input coupled to a second refrigerated liquid container.

11. The apparatus of claim 10, further comprising a controller to activate the first liquid pump and the second liquid pump so as to provide, at the frothing head, a desired mixture of a first liquid contained in the first refrigerated liquid container and a second liquid contained in the second refrigerated liquid container.

12. The apparatus of claim 11, wherein the first liquid is skim milk and the second liquid is whole milk.

13. The apparatus of claim 11, wherein the first liquid is a dairy product and the second liquid is an enzyme.

14.-23. (canceled)

24. A method of making a beverage, the method comprising:

obtaining a first liquid dairy product;

obtaining a second liquid dairy product;

receiving an instruction to specify a mixture of the first liquid dairy product and the second liquid dairy product;

automatically mixing the first liquid dairy product and the second liquid dairy product to form a mixed dairy product;

dispensing the mixed dairy product into a cup; and
dispensing a coffee product into the cup.

25. The method of claim 24, further comprising heating the mixed dairy product prior to the act of dispensing the mixed dairy product.

26. The method of claim 24, further comprising injecting steam into the mixed dairy product prior to the act of dispensing the mixed dairy product.

27. The method of claim 24, wherein, in the act of obtaining a first liquid dairy product, the first liquid dairy product is skim milk; and in the act of obtaining a second liquid dairy product, the second liquid dairy product is whole milk.

28. A method of making a beverage, the method comprising:

receiving an instruction to specify a mixture of a first liquid dairy product and an enzyme;

mixing the first liquid dairy product and the enzyme according to the instruction;

dispensing the mixed first liquid dairy product and the enzyme into a cup; and

dispensing a coffee product into the cup.

29. The method of claim 28, further comprising:

mixing a second liquid dairy product with at least one of the group of the first liquid dairy product and the enzyme; and

wherein the act of dispensing the mixed first liquid dairy product and the enzyme into a cup also includes dispensing the mixed second liquid dairy product.

30. A method of making a beverage, the method comprising:

receiving an instruction to specify a mixture of a first liquid dairy product and a flavoring liquid;

mixing the first liquid dairy product and the flavoring liquid according to the instruction;

dispensing the mixed first liquid dairy product and the flavoring liquid into a cup; and

dispensing a coffee product into the cup.

31. The method of claim 30, further comprising:

mixing a second liquid dairy product with at least one of the group of the first liquid dairy product and the flavoring liquid; and

wherein the act of dispensing the mixed first liquid dairy product and the flavoring liquid into a cup also includes dispensing the mixed second liquid dairy product.

* * * * *