

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
13 February 2003 (13.02.2003)

PCT

(10) International Publication Number  
WO 03/012003 A1

- (51) International Patent Classification<sup>7</sup>: C09K 7/02
- (21) International Application Number: PCT/US02/19497
- (22) International Filing Date: 20 June 2002 (20.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/307,805 25 July 2001 (25.07.2001) US  
10/010,188 6 December 2001 (06.12.2001) US
- (71) Applicant: **M-I L.L.C.** [US/US]; 5950 North Course Drive, Houston, TX 77072-1626 (US).
- (72) Inventors: **KIPPIE, David, P.**; 3610 Pedernales Trails Lane, Katy, TX 77450 (US). **HORTON, Robert, L.**; 1103 Springdale Court, Sugarland, TX 77479 (US). **FOXENBERG, William, E.**; 4385 Harvest Lane, Houston, TX 77004 (US).
- (74) Agents: **ROSENTHAL, Alan** et al.; 1221 McKinney Street, Suite 2800, Houston, TX 77010 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 03/012003 A1

(54) Title: HIGH DENSITY THERMALLY STABLE WELL FLUIDS

(57) Abstract: High density, thermally stable, brine-based well fluids and methods of using the same are disclosed. In one embodiment a well fluid including water and a salt, the salt including at least one formate salt, wherein the weight-to-volume ratio of the well fluid is within the range of at least 120 % to about 400 % is disclosed. In another embodiment, a well fluid including water, a viscosifying agent, and a salt, the salt including at least one formate salt, wherein the weight-to-volume ratio of the well fluid is within the range of at least 120 % to about 400 % is disclosed. A method of treating a well using a well fluid, wherein the well fluid includes water and a salt, the salt including at least one formate salt, wherein the weight-to-volume ratio of the well fluid is within the range of at least 120 % to about 400 % is also disclosed.

## High Density Thermally Stable Well Fluids

### Cross-Reference to Related Applications

- [0001] This application claims the benefit of U.S. Provisional Application No. 60/307,805 filed on July 25, 2001.

### Background of Invention

#### Field of the Invention

- [0002] The invention relates generally to well drilling and completion fluids. More specifically, the present invention relates to high density, thermally stable, brine-based well fluids.

#### Background Art

- [0003] When drilling or completing wells in earth formations, various fluids typically are used in the well for a variety of reasons. The fluid often is water-based. For the purposes herein, such fluid will be referred to as "well fluid." Common uses for well fluids include: lubrication and cooling of drill bit cutting surfaces while drilling generally or drilling-in (*i.e.*, drilling in a targeted petroliferous formation), transportation of "cuttings" (pieces of formation dislodged by the cutting action of the teeth on a drill bit) to the surface, controlling formation fluid pressure to prevent blowouts, maintaining well stability, suspending solids in the well, minimizing fluid loss into and stabilizing the formation through which the well is being drilled, fracturing the formation in the vicinity of the well, displacing the fluid within the well with another fluid, cleaning the well, testing the well, fluid used for implacing a packer, abandoning the well or preparing the well for abandonment, and otherwise treating the well or the formation.
- [0004] One issue that arises in drilling operations relates to the thermal stability of the well fluids. Temperatures in subsurface formations generally rise

approximately 0.5-1 °C (gradient varies with location) per hundred feet of depth. Many well fluids contain additives that may undergo severe chemical degradation in the presence of elevated temperatures, which may lead to a variety of problems.

[0005] Brines (such as, for example, aqueous CaBr<sub>2</sub>) commonly are used as well fluids because of their wide density range and the fact that brines are typically substantially free of suspended solids. In addition, brines are often used in order to achieve a suitable density for use in well-drilling operations. Typically, the brines comprise halide salts of mono- or divalent cations, such as sodium, potassium, calcium, and zinc. Chloride-based brines of this type have been used in the petroleum industry for over 50 years; and bromide-based brines, for at least 25 years; but formate-based brines have only been widely used in the industry relatively recently (roughly the past ten years). One additional advantage of using brines is that brines typically do not damage certain types of downhole formations; and for formations that are found to interact adversely with one type of brine, often there is another type of brine available with which that formation will not interact adversely.

[0006] A variety of compounds are typically added to brine-based well fluids. For example, a brine-based well fluid may also include viscosifiers, corrosion inhibitors, lubricants, pH control additives, surfactants, solvents, and/or weighting agents, among other additives. Some typical brine-based well fluid viscosifying additives include natural polymers and derivatives thereof such as xanthan gum and hydroxyethyl cellulose (HEC). In addition, a wide variety of polysaccharides and polysaccharide derivatives may be used, as is well known in the art.

[0007] Some synthetic polymer and oligomer additives such as poly(ethylene glycol)(PEG), poly(diallyl amine), poly(acrylamide), poly(aminomethylpropylsulfonate[AMPS]), poly(acrylonitrile), poly(vinyl acetate), poly(vinyl alcohol), poly(vinyl amine), poly(vinyl sulfonate),

poly(styryl sulfonate), poly(acrylate), poly(methyl acrylate), poly(methacrylate), poly(methyl methacrylate), poly(vinylpyrrolidone), poly(vinyl lactam), and co-, ter-, and quater-polymers of the following comonomers: ethylene, butadiene, isoprene, styrene, divinylbenzene, divinyl amine, 1,4-pentadiene-3-one (divinyl ketone), 1,6-heptadiene-4-one (diallyl ketone), diallyl amine, ethylene glycol, acrylamide, AMPS, acrylonitrile, vinyl acetate, vinyl alcohol, vinyl amine, vinyl sulfonate, styryl sulfonate, acrylate, methyl acrylate, methacrylate, methyl methacrylate, vinylpyrrolidone, and vinyl lactam are also often used as viscosifiers.

[0008] One example of how a brine-based well fluid may be used in combination with the above listed polymers and oligomers is set forth below. When drilling progresses to the depth of penetrating a hydrocarbon bearing formation, special care may be required to maintain the stability of the wellbore. Examples of formations in which stability problems often arise include highly permeable and/or poorly consolidated formations. In these types of formations, a drilling technique known as "under-reaming" may be used. In under-reaming, the wellbore is drilled to penetrate the hydrocarbon bearing zone using conventional techniques. A casing generally is set in the wellbore to a point just above the hydrocarbon bearing zone. The hydrocarbon bearing zone then may be re-drilled, for example, using an expandable under-reamer that increases the diameter of the already- drilled wellbore below the casing.

[0009] Under-reaming is usually performed using special "clean" drilling fluids. Typical drilling fluids used in under-reaming are expensive, aqueous, dense brines that are viscosified with a gelling and/or cross-linked polymer to aid in the removal of formation cuttings. The high permeability of the target formation, however, may allow large quantities of the drilling fluid to be lost into the formation. Once the drilling fluid is lost into the formation, it becomes difficult to remove. Calcium and zinc bromide brines can form highly stable, acid insoluble compounds when reacted with the formation or substances

contained therein. This reaction may reduce the permeability of the formation to any subsequent out-flow of targeted hydrocarbons. One of the most effective ways to prevent such damage to the formation is to limit fluid loss into the formation.

[0010] Thus, providing effective fluid loss control is highly desirable to prevent damaging the formation in, for example, completion, drilling, drill-in, displacement, hydraulic fracturing, work-over, packer fluid implacement or maintenance, well treating, or testing operations. Techniques that have been developed to control fluid loss include the use of fluid loss "pills." Significant research has been directed to determining suitable materials for the fluid loss pills, as well as controlling and improving the properties of the fluid loss pills. Typically, fluid loss pills work by enhancing filter-cake buildup on the face of the formation to inhibit fluid flow from the wellbore into the formation.

[0011] Because of the high temperatures, high shear (caused by the pumping and placement), high pressures, and low pH to which well fluids are often exposed (*i.e.*, "stress conditions"), the above described polymeric additives used to form fluid loss pills, and to viscosify the well fluids, tend to degrade rather quickly. In addition, even in well fluids without these polymeric additives, other chemical species present in the well fluid may decompose or undergo undesirable reactions. Brine-based well fluids, therefore, are used for a variety of applications in well drilling, both with and without polymeric additives. Increasing the thermal stability of brine-based well fluids, therefore, is a significant concern.

[0012] U.S. Patent No. 4,900,457 (the '457 patent) describes one method of raising the thermal stability of these well fluids. In particular, the '457 patent discloses an aqueous polysaccharide composition comprising 0.03 to 5% weight per volume (w/v) of a water-soluble polysaccharide, 5 to 120% w/v of at least one salt of at least one mono- or divalent cation, wherein at least 0.05% w/v, based on the composition of the at least one salt is formate, the balance of

the salt, if any, being at least one halide. Further, the '457 patent states that the most preferable amount of formate is 10% w/v.

[0013] High density, brine-based well fluids have become increasingly important for a variety of applications, such as well completion. Along with having high densities, these brine-based well fluids must also be thermally stable. What is needed, therefore, are high density, thermally stable, brine-based well fluids for use in a variety of applications.

### **Summary of Invention**

[0014] In one aspect, the present invention relates to a high density, thermally stable well fluid, wherein the well fluid includes water and a salt, wherein the salt includes at least one formate salt, and wherein a weight-to-volume ratio of the salt in the well fluid is within the range of at least 120% to about 400%.

[0015] In another aspect, the present invention relates to a high density, thermally stable well fluid, wherein the well fluid includes water, a viscosifying agent, and a salt, the salt including at least one formate salt, wherein the weight-to-volume ratio of the salt in the well fluid is within the range of at least 120% to about 400%.

[0016] In another aspect, the present invention relates to a method of treating a well which includes injecting a well treating fluid into the well, wherein the well treating fluid includes water and a salt, the salt including at least one formate salt, wherein the weight-to-volume ratio of the salt contained in the well fluid is within the range of at least 120% to about 400%.

[0017] Other aspects and advantages of the invention will be apparent from the following description and the appended claims.

### **Detailed Description**

[0018] In general, the present invention relates to compositions and methods of using high density, thermally stable well fluids (such as kill fluids, or fluid loss

control pills, for example) that can sustain stress conditions for extended periods of time without significant fluid loss or loss of desirable rheological properties. The stress conditions may include, for example, exposure to high shear in pumping and placement, exposure to oxidizing breakers (including oxygen dissolved in the fluid), exposure to brines having high divalent cation content, high temperatures, high differential pressures, low pH, extended times, and a combination of two or more of such stress conditions. These fluids are advantageously used in or in connection with drilling, drill-in, displacement, completion, hydraulic fracturing, work-over, packer fluid emplacement or maintenance, well treating, testing, or abandonment.

[0019] More specifically, the present invention relates to high density, thermally stable, brine based well fluids and methods of using the same. Those skilled in the art will appreciate that 1% w/v (one percent weight-to-volume ratio) corresponds to a concentration of  $10 \text{ kg/m}^3$  (10 g/l) of composition. Thus, as defined, the weight-to-volume ratio represents the grams of solute (salt) in the liters of solution, and it includes salt that may be either dissolved or suspended in the solution at room temperature, inasmuch as said suspended salt may become soluble at a higher temperature. In particular, the present invention discloses formate-containing well fluids having a weight-to-volume ratio of greater than 120% to approximately 400%. The present invention comprises compositions having only formate as the anionic component of the brine, as well as mixed salt systems. "Effective," as used throughout the specification, simply means an amount sufficient to raise the temperature stability of a given well fluid by a measurable amount.

[0020] To test compositions of various embodiments of the invention, fluid loss properties of the compositions described below were determined as follows. Fluid loss tests of durations ranging from 30 seconds to 48 hours were performed in an API standard high pressure high temperature (HPHT) apparatus (Ref.: API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper). The testing temperature used in obtaining the below

readings was predetermined, such as, for example, in accordance with a bottom-hole temperature at which the fluid will be used in the field.

[0021] The HPHT apparatus was operated at 500 psig differential pressure, using, for example, a nominally 65 milliDarcy Aloxite disc (HPHT cell). In general, for the fluid lost tests, a 500 mL HPHT cell is loaded into the HPHT apparatus, which is then pressurized and heated to a predetermined temperature. A discharge valve located on the HPHT apparatus is then opened, and a filtrate volume is measured with respect to time. No limitation on the scope of the present invention is intended by the discussion of the above testing method. Moreover, no limitation should be placed on the scope of the invention by the discussion of use of such fluids as fluid loss control pills. For example, it is expressly within the scope of the present invention that the compositions described below may be used as any type of well fluid.

[0022] In one embodiment of the invention, a mixture, termed "formulation 1," was prepared in the following manner. A mixture of 141.68 mL of 17.3 pounds per gallon (ppg) cesium formate and 148.79 mL of 13.1 ppg potassium formate was prepared by adding to the brines a dry reagent comprising 2 grams of xanthan gum (a biopolymer) and 10 grams of potassium carbonate as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. 100 grams of sodium bromide was then added as a dry reagent to the mixture. Next, 45 grams of calcium carbonate was added as a dry reagent. The weight-to-volume ratio of salt in the resulting composition was determined to be 174.44%.

[0023] Significantly, at room temperature, not all of the sodium bromide remains in solution. However, once the temperature of the solution is raised above room temperature (but well below the operating temperature in a typical well), the sodium bromide is dissolved, leaving only an aqueous phase.

[0024] Formulation 1 was then hot rolled in an oven at 250 °F for approximately 1 hour. After hot rolling, formulation 1 was placed in a standard

HPHT fluid loss cell (as described above). A fluid loss test was then conducted at 400 °F according to API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper. Fluid loss was measured at 30 seconds, 1 hour, 2 hours, 3 hours, and 4.5 hours. Blowout (*i.e.*, loss of fluid control) occurred after 4.5 hours.

[0025] In another embodiment, a mixture, termed “formulation 2,” was prepared in the following manner. To 247.45 mL of 13.1 ppg potassium formate brine solution was added, with stirring, a dry reagent comprising 2 grams of scleroglucan (a biopolymer) was mixed with 10 grams of potassium carbonate as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. 175 grams of sodium bromide was then added as a dry reagent to the mixture. Next, 100 grams of calcium carbonate was added as a dry reagent. The dry reagent mixture. The weight-to-volume ratio of salt in the resulting composition was determined to be 187.12%.

[0026] Formulation 2 was then hot rolled in an oven at 250 °F for approximately 1 hour. After hot rolling, formulation 2 was placed in a standard HPHT (as described above) fluid loss cell. A fluid loss test was then conducted at 400 °F according to API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper. Fluid loss was measured at 30 seconds, 1 hour, 2 hours, 3 hours, 4.5 hours, and 8.75 hours. No blowout (*i.e.*, loss of fluid control) occurred during the testing of formulation 2.

[0027] For comparison, a mixture, “comparison 1,” was prepared in the following manner. A dry reagent comprising 0.75 grams of xanthan gum (a biopolymer) was mixed with 6 grams of modified starch as a dry reagent. Next, 35 grams of calcium carbonate was added as a dry reagent. The dry reagent mixture was then added, with stirring, to 311.15 mL of 12.8 ppg potassium formate brine solution. The weight-to-volume ratio of salt in the resulting composition was determined to be 117.0%. The density of the aqueous phase was found to be approximately 13.1 ppg.

[0028] Comparison 1 was then hot rolled in an oven at 250 °F for approximately 1 hour. After hot rolling, comparison 1 was placed in a standard HPHT (as described above) fluid loss cell. A fluid loss test was then conducted at 400 °F according to API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper. Fluid loss was measured at 30 seconds, 1 hour, 2 hours, 3 hours, 4.5 hours, and 8.75 hours.

Formulation	30 sec fluid loss (mL)	1 hr fluid loss (mL)	2 hr fluid loss (mL)	3 hr fluid loss (mL)	4.5 hr fluid loss (mL)	8.75 hr fluid loss (mL)
1	10	12	12.5	58	Blowout	-----
2	10	24	40	45	57	57
Comparison 1	50	blowout (occurred by 30 min)				

**Table 1: Fluid Loss Over Time**

[0029] From the above results, formulations 1 and 2 increase a thermal stability of the well fluid with respect to fluid loss. Typically, useful ranges of temperatures (*i.e.*, the temperature range in which the polymer provides additional viscosity) for scleroglucan and xanthan gum are about 225 °F - 275 °F. In the above examples, however, the useful temperature range of the well fluid has been extended significantly.

[0030] In another embodiment, a mixture, termed "formulation 3," was prepared in the following manner. A dry reagent comprising 2 grams of scleroglucan (a biopolymer), as a dry reagent, was mixed with 23.6 grams of cesium carbonate (as compared with potassium carbonate of the previous two formulations) as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. 361.9 grams of cesium bromide was then added as a dry reagent to the mixture. Next, 100 grams of calcium carbonate

was added as a dry reagent. The dry reagent mixture was then added, with stirring, to 247.45 mL of 19.2 ppg cesium formate brine solution. The weight-to-volume ratio of salt in the resulting composition was determined to be 360.33%.

[0031] In another embodiment, a mixture, termed "formulation 4," was prepared in the following manner. A mixture of 141.68 mL of 17.3 ppg cesium formate and 148.79 mL of 13.1 ppg potassium formate was prepared. To this mixture was added, with stirring, dry reagent comprising 2 grams of xanthan gum (a biopolymer) and 10 grams of potassium carbonate as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. 30.46 grams of sodium bromide was then added as a dry reagent to the mixture. Next, 45 grams of calcium carbonate was added as a dry reagent.

[0032] The weight-to-volume ratio of salt in the resulting composition was determined to be 155.91%. At room temperature, all of the potassium carbonate and sodium bromide remains in solution. The density of the aqueous phase at 70 °F is approximately 15.4 ppg.

[0033] In another embodiment, a mixture, termed "formulation 5," was prepared in the following manner. To 247.45 mL of 13.1 ppg potassium formate brine solution was added, with stirring, a dry reagent comprising 2 grams of scleroglucan (a biopolymer), as a dry reagent, and 5 grams of potassium carbonate as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. Four grams of sodium bromide was then added as a dry reagent to the mixture. Next, 100 grams of calcium carbonate was added as a dry reagent. The weight-to-volume ratio of salt in the resulting composition was determined to be 165.27%. At room temperature, all of the potassium carbonate and sodium bromide remains in solution.

[0034] In another embodiment, a mixture, termed "formulation 6," was prepared in the following manner. A dry reagent comprising 2 grams of scleroglucan (a biopolymer), was mixed with 23.6 grams of cesium carbonate

(as compared with potassium carbonate of the previous two formulations) as a dry reagent. To this mixture, 10 grams of modified starch was then added as a dry reagent. 7.24 grams of cesium bromide was then added as a dry reagent to the mixture. Next, 100 grams of calcium carbonate was added as a dry reagent. The dry reagent mixture was then added, with stirring, to 247.45 mL of 19.2 ppg cesium formate brine solution. The weight-to-volume ratio of salt in the resulting composition was determined to be 230.42%. At room temperature, all of the cesium carbonate and cesium bromide remains in solution.

[0035] In another embodiment, a mixture, termed "formulation 7," was prepared in the following manner. A dry reagent comprising 0.75 grams of xanthan gum (a biopolymer) was mixed with 6 grams of modified starch as a dry reagent. 361.9 grams of cesium bromide was then added as a dry reagent to the mixture. Next, 35 grams of calcium carbonate was added as a dry reagent. The dry reagent mixture was then added, with stirring, to 311.15 mL of 19.5 ppg cesium formate brine solution (84.4 wt% cesium formate). The weight-to-volume ratio of salt in the resulting composition was determined to be 298.15%. At room temperature, all of the cesium bromide remains in solution.

[0036] In another embodiment, a mixture, termed "formulation 8," was prepared in the following manner. To 311.15 mL of 12.8 ppg potassium formate brine solution was added, with stirring, a dry reagent comprising 0.75 grams of xanthan gum (a biopolymer) and 6 grams of modified starch as a dry reagent. 70.0 grams of cesium bromide was then added as a dry reagent to the mixture. Next, 35 grams of calcium carbonate was added as a dry reagent. The weight-to-volume ratio of salt in the resulting composition was determined to be 133.87%. At room temperature, not all of the sodium bromide remains in solution; but at about 200°F, all of the sodium bromide does go into solution.

[0037] Formulation 8 was then hot rolled in an oven at 250 °F for approximately 1 hour. After hot rolling, formulation 8 was placed in a standard

HPHT (as described above) fluid loss cell. A fluid loss test was then conducted at 400 °F according to API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper. Fluid loss was measured at 30 seconds, 30 minutes, 1 hour, and 1.5 hours.

[0038] For comparison, a mixture, "comparison 2," was prepared in the following manner. To 311.15 mL of 12.8 ppg potassium formate brine solution was added, with stirring, a dry reagent comprising 0.75 grams of xanthan gum (a biopolymer) and 6 grams of modified starch as a dry reagent. Next, 35 grams of calcium carbonate was added as a dry reagent. The weight-to-volume ratio of salt in the resulting composition was determined to be 117.0%. The density of the aqueous phase was found to be approximately 13.1 ppg.

[0039] Comparison 2 was then hot rolled in an oven at 250 °F for approximately 1 hour. After hot rolling, comparison 2 was placed in a standard HPHT (as described above) fluid loss cell. A fluid loss test was then conducted at 400 °F according to API 13-B1 with one modification: substituting an Aloxite or ceramic disk for paper. Fluid loss was measured at 30 seconds, 30 minutes, 1 hour, and 1.5 hours.

[0040] The results are summarized below.

Formulation	30 sec fluid loss (mL)	30 min fluid loss (mL)	1 hr fluid loss (mL)	1.5 hr fluid loss (mL)
8	5	6	10	blowout
Comparison 2	50	blowout	---	---

**Table 2: Fluid Loss Over Time**

[0041] From the above results, formulation 8 provides significant thermal stability to the well fluid. Typically, useful ranges of temperatures (*i.e.*, the temperature range in which the polymer provides additional viscosity) for sceroglucan and xanthan gum are about 225 °F - 275 °F. In the above example,

however, the useful temperature range of the well fluid has been extended significantly.

[0042] While the above embodiments describe particular compositions and a particular use (*i.e.*, as a fluid loss control pill), it is expressly within the scope of the present invention that high density, thermally stable well fluids such as those described above may be used for a variety of purposes within the context of well drilling, whether or not a particular well fluid contains a polymer. Additionally, while reference has been made to particular salts, it is expressly within the scope of the present invention that other mixtures of salts may be used in conjunction with the above described formates. For example, it will be clear to one of ordinary skill in the art that other salts may be used, such as  $\text{CaBr}_2$ ,  $\text{ZnCl}_2$ ,  $\text{CaBr}_2$ ,  $\text{ZnBr}_2$ ,  $\text{NaCl}$ ,  $\text{KCl}$ ,  $\text{NH}_4\text{Cl}$ ,  $\text{MgCl}_2$ , seawater,  $\text{Na}_2\text{S}_2\text{O}_3$ , and combinations thereof. Further, it is expressly within the scope of the present invention that combinations of formate salts may be used. For example, potassium and cesium formates may be used alone or in combination. Other formate salts may be used in combination as well.

[0043] Further, while the above embodiments describe a particular order of addition of the reagents, no restriction on scope is intended thereby. Further, while the above embodiments describe particular weight to volume ratios of salt, it is expressly within the scope of the present invention that a range of weight-to-volume ratio of salt between greater than 120% to about 400% may be used. Preferably, the weight-to-volume ratio of salt is about 150% to 350%. More preferably, the weight-to-volume ratio of salt is about 180% to 300%.

[0044] While the invention has been described with respect to a limited number of embodiments, those skilled in the art, having benefit of this disclosure, will appreciate that other embodiments can be devised which do not depart from the scope of the invention as disclosed herein. Accordingly, the scope of the invention should be limited only by the attached claims.

## Claims

What is claimed is:

- [c 1] A well fluid comprising:  
water; and  
a salt, the salt comprising at least one formate salt, wherein a weight-to-volume ratio of the salt in the well fluid is within a range of greater than 120% to about 400%.
- [c 2] The well fluid of claim 1, wherein the at least one formate salt comprises cesium formate or a mixture of potassium formate and cesium formate.
- [c 3] The well fluid of claim 2, further comprising a halide salt.
- [c 4] The well fluid of claim 2, further comprising sodium bromide.
- [c 5] The well fluid of claim 1, wherein the at least one formate salt comprises potassium formate.
- [c 6] The well fluid of claim 5, further comprising a halide salt.
- [c 7] The well fluid of claim 5, further comprising sodium bromide.
- [c 8] The well fluid of claim 1, wherein the at least one formate salt comprises cesium formate.
- [c 9] The well fluid of claim 1, wherein the weight-to-volume ratio of the total salt content is within a range of about 150% to 350%.
- [c 10] The well fluid of claim 1, wherein the weight-to-volume ratio of the total salt content is within a range of about 180% to 300%.
- [c 11] A well fluid comprising:  
water;  
a viscosifying agent; and

a salt, the salt comprising at least one formate salt, wherein a weight-to-volume ratio of the salt content in the well fluid is within the range of greater than 120% to about 400%.

[c 12] The well fluid of claim 11, wherein the at least one formate salt comprises cesium formate or a mixture of potassium formate and cesium formate.

[c 13] The well fluid of claim 12, further comprising a halide salt.

[c 14] The well fluid of claim 12, further comprising sodium bromide.

[c 15] The well fluid of claim 11, wherein the at least one formate salt comprises potassium formate.

[c 16] The well fluid of claim 15, further comprising a halide salt.

[c 17] The well fluid of claim 15, further comprising sodium bromide.

[c 18] The well fluid of claim 11, wherein the at least one formate salt comprises cesium formate.

[c 19] The well fluid of claim 11, wherein the weight-to-volume ratio of the total salt content is within a range of about 150% to 350%.

[c 20] The well fluid of claim 11, wherein the weight-to-volume ratio of the total salt content is within a range of about 180% to 300%.

[c 21] A method of treating a well comprising:

injecting a well treating fluid into the well, wherein the well treating fluid comprises water and a salt, the salt comprising at least one formate salt, wherein the salt content in the well fluid is within the range of at least 120% to about 400%.

[c 22] The method of claim 21, wherein the at least one formate salt comprises cesium formate or a mixture of potassium formate and cesium formate.

- [c 23] The method of claim 22, further comprising a halide salt.
- [c 24] The method of claim 22, further comprising sodium bromide.
- [c 25] The method of claim 21, wherein the at least one formate salt comprises potassium formate.
- [c 26] The method of claim 25, further comprising a halide salt.
- [c 27] The method of claim 25, further comprising sodium bromide.
- [c 28] The method of claim 21, wherein the at least one formate salt comprises cesium formate.
- [c 29] The method of claim 21, wherein the weight-to-volume ratio of the total salt content is within a range of about 150% to 350%.
- [c 30] The method of claim 21, wherein the weight-to-volume ratio of the total salt content is within a range of about 180% to 300%.
- [c 31] A method of treating a well comprising:  
injecting a well treating fluid into the well, wherein the well treating fluid comprises water, a viscosifying agent, and a salt, the salt comprising at least one formate salt, wherein the salt content in the well fluid is within the range of at least 120% to about 400%.
- [c 32] The method of claim 31, wherein the at least one formate salt comprises cesium formate or a mixture of potassium formate and cesium formate.
- [c 33] The method of claim 32, further comprising a halide salt.
- [c 34] The method of claim 32, further comprising sodium bromide.
- [c 35] The method of claim 31, wherein the at least one formate salt comprises potassium formate.

- [c 36] The method of claim 35, further comprising a halide salt.
- [c 37] The method of claim 35, further comprising sodium bromide.
- [c 38] The method of claim 31, wherein the at least one formate salt comprises cesium formate.
- [c 39] The method of claim 31, wherein the weight-to-volume ratio of the total salt content is within a range of about 150% to 350%.
- [c 40] The method of claim 31, wherein the weight-to-volume ratio of the total salt content is within a range of about 180% to 300%.

INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 02/19497

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 C09K7/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category <sup>o</sup>	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 804 535 A (CASHION-JAMES P ET AL) 8 September 1998 (1998-09-08)  column 2, line 37 - line 65 column 6, line 5 - line 52; claims 1-4,9,11,12  ---  -/--	1-3,5,6, 8,11-13, 15,16, 18, 21-23, 25,26, 28, 31-33, 35,36,38

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

<sup>o</sup> Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the International filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*G\* document member of the same patent family

Date of the actual completion of the international search

12 November 2002

Date of mailing of the international search report

20/11/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Boulon, A

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 02/19497

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 572 113 A (BP CHEM INT LTD) 1 December 1993 (1993-12-01)  page 2, line 1 - line 41; examples 1,2 -----	1, 2, 5, 8, 11, 12, 15, 18, 21, 22, 25, 28
X	WO 97 26311 A (GREAT LAKES CHEMICAL CORP) 24 July 1997 (1997-07-24)  page 1, line 9 - line 17 page 3, line 10 - line 24 page 13, line 10 - page 15, line 19 page 17, line 12 - line 28 page 20, line 16 -----	1, 5-7, 11, 15-17, 21, 25-27, 31, 35-37

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/19497

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5804535	A	08-09-1998	AU 736402 B2	26-07-2001
			AU 6480998 A	10-12-1998
			CA 2239585 A1	09-12-1998
			EP 0884369 A1	16-12-1998
			NO 982638 A	10-12-1998
EP 0572113	A	01-12-1993	DE 69300541 D1	02-11-1995
			DE 69300541 T2	21-03-1996
			EP 0572113 A1	01-12-1993
			NO 931495 A	30-11-1993
WO 9726311	A	24-07-1997	EP 0874878 A1	04-11-1998
			NO 983242 A	15-09-1998
			WO 9726311 A1	24-07-1997
			US 6100222 A	08-08-2000