

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2010271274 B2

(54) Title
Single operator device for delivering an ocular implant

(51) International Patent Classification(s)
A61B 18/18 (2006.01)

(21) Application No: **2010271274** (22) Date of Filing: **2010.07.09**

(87) WIPO No: **WO11/006078**

(30) Priority Data

(31) Number **61/224,156** (32) Date **2009.07.09** (33) Country **US**

(43) Publication Date: **2011.01.13**
(44) Accepted Journal Date: **2015.05.21**

(71) Applicant(s)
Ivantis, Inc.

(72) Inventor(s)
Wardle, John;Schieber, Andrew T.

(74) Agent / Attorney
Davies Collison Cave, PO Box 2219 BUSINESS CENTRE, MILTON, QLD, 4064

(56) Related Art
US 2007/0191863 A1
US 2009/0132040 A1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(10) International Publication Number
WO 2011/006078 A1

(51) International Patent Classification:
A61B 18/18 (2006.01)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:
PCT/US2010/041544

(22) International Filing Date:
9 July 2010 (09.07.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/224,156 9 July 2009 (09.07.2009) US

(71) Applicant (for all designated States except US): IVANTIS, INC. [US/US]; 13766 Alton Parkway, Suite 150, Irvine, CA 92618 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WARDLE, John [US/US]; 13766 Alton Parkway, Suite 150, Irvine, CA 92618 (US). SCHIEBER, Andrew T. [US/US]; 13766 Alton Parkway, Suite 150, Irvine, CA 92618 (US).

(74) Agents: THOMAS, Justin et al.; Shay Glenn LLP, 2755 Campus Drive, Suite 210, San Mateo, CA 94403 (US).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))



WO 2011/006078 A1

(54) Title: SINGLE OPERATOR DEVICE FOR DELIVERING AN OCULAR IMPLANT

(57) **Abstract:** An ocular implant delivery system is provided with a number of features. In some embodiments, the delivery system comprises a rotation mechanism configured to rotate and orient a cannula of the system, and an advancement mechanism configured to advance and retract an ocular implant through the delivery system and into an eye of a patient. In some embodiments, the cannula is sized and configured to be inserted into Schlemm's canal of the eye. The ocular implant is configured to maintain its orientation within the delivery system as the cannula is rotated. In some embodiments, the ocular implant automatically disengages the delivery system when it is advanced beyond a distal tip of the delivery system. Methods of implanting an ocular implant are also provided.

SINGLE OPERATOR DEVICE FOR DELIVERING AN OCULAR IMPLANT

CROSS REFERENCE TO RELATED APPLICATIONS

5 [0001] This application claims the benefit under 35 U.S.C. 119 of U.S. Provisional Patent Application No. 61/224,156, filed July 9, 2009, titled "Single Operator Device for Delivering an Ocular Implant". This application is herein incorporated by reference in its entirety.

INCORPORATION BY REFERENCE

10 [0002] All publications and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication or patent application was specifically and individually indicated to be incorporated by reference.

FIELD OF THE INVENTION

15 [0003] The present invention relates generally to devices that are implanted within the eye and delivery systems for such devices. More particularly, the present invention relates to delivery system for devices that facilitate the transfer of fluid from within one area of the eye to another area of the eye.

BACKGROUND OF THE INVENTION

20 [0004] According to a draft report by The National Eye Institute (NEI) at The United States National Institutes of Health (NIH), glaucoma is now the leading cause of irreversible blindness worldwide and the second leading cause of blindness, behind cataract, in the world. Thus, the NEI draft report concludes, "it is critical that significant emphasis and resources continue to be devoted to determining the pathophysiology and management of this disease." Glaucoma researchers have found a strong correlation between high intraocular pressure and glaucoma. For this reason, eye care professionals routinely screen patients for glaucoma by measuring intraocular pressure using a device known as a tonometer. Many modern tonometers make this measurement by blowing a sudden puff of air against the outer surface of the eye.

25 [0005] The eye can be conceptualized as a ball filled with fluid. There are two types of fluid inside the eye. The cavity behind the lens is filled with a viscous fluid known as vitreous humor. The cavities in front of the lens are filled with a fluid known as aqueous humor. Whenever a person views an object, he or she is viewing that object through both the vitreous humor and the aqueous humor.

[0006] Whenever a person views an object, he or she is also viewing that object through the cornea and the lens of the eye. In order to be transparent, the cornea and the lens can include no blood vessels. Accordingly, no blood flows through the cornea and the lens to provide nutrition to these tissues and to remove wastes from these tissues. Instead, these functions are performed by the aqueous humor. A continuous flow of aqueous humor through the eye provides nutrition to portions of the eye (e.g., the cornea and the lens) that have no blood vessels. This flow of aqueous humor also removes waste from these tissues.

5 [0007] Aqueous humor is produced by an organ known as the ciliary body. The ciliary body includes epithelial cells that continuously secrete aqueous humor. In a healthy eye, a stream of aqueous humor flows out of the anterior chamber of the eye through the trabecular meshwork and into Schlemm's canal as new aqueous humor is secreted by the epithelial cells of the ciliary body. This excess aqueous humor enters the venous blood stream from Schlemm's canal and is carried along with the venous blood leaving the eye.

10 [0008] When the natural drainage mechanisms of the eye stop functioning properly, the pressure inside the eye begins to rise. Researchers have theorized prolonged exposure to high intraocular pressure causes damage to the optic nerve that transmits sensory information from the eye to the brain. This damage to the optic nerve results in loss of peripheral vision. As glaucoma progresses, more and more of the visual field is lost until the patient is completely blind.

15 [0009] In addition to drug treatments, a variety of surgical treatments for glaucoma have been performed. For example, shunts were implanted to direct aqueous humor from the anterior chamber to the extraocular vein (Lee and Scheppens, "Aqueous-venous shunt and intraocular pressure," *Investigative Ophthalmology* (Feb. 1966)). Other early glaucoma treatment implants led from the anterior chamber to a sub-conjunctival bleb (e.g., US 4,968,296 and US 5,180,362).
20 Still others were shunts leading from the anterior chamber to a point just inside Schlemm's canal (Spiegel et al., "Schlemm's canal implant: a new method to lower intraocular pressure in patients with POAG?" *Ophthalmic Surgery and Lasers* (June 1999); US 6,450,984; US 6,450,984). Delivery and deployment systems for some glaucoma implants are described, e.g., in US 2007/0191863 and US 2007/0010827. Surgical devices for accessing Schlemm's canal are
25 described, e.g., in US 2007/0073275 and US 2006/0149194.

SUMMARY OF THE INVENTION

[00010] In one embodiment, an ocular implant delivery system comprises a housing, a cannula coupled to the housing, the cannula sized and configured for insertion into Schlemm's canal of a human eye, a delivery mechanism disposed on the housing, the delivery mechanism

configured to advance and retract an ocular implant within the cannula, and an orientation mechanism disposed on the housing, the orientation mechanism configured to control rotation of the cannula, wherein the ocular implant maintains its orientation with respect to the cannula when the cannula is rotated.

5 [00011] In some embodiments, the ocular implant delivery system further comprises a push tube slidably disposed within the cannula and coupled to the delivery mechanism. The ocular implant can be coupled to a distal portion of the push tube. In some embodiments, an interlocking finger of the implant is coupled to a finger receptacle on the push tube.

10 [00012] In another embodiment, the ocular implant delivery system further comprises a core shaft disposed within the ocular implant. The core shaft or core cable can be configured to align with an interior diameter of the ocular implant so as to prevent any sharp edges or holes of the implant from engaging tissue during implantation.

15 [00013] In one embodiment of the delivery system, the relative locations of the delivery mechanism and the orientation mechanism on the housing allow control over advancement and retraction of the ocular implant and rotation of the cannula with a single hand.

20 [00014] In another embodiment, the ocular implant is configured to automatically disengage from the ocular implant delivery system when it is advanced beyond a distal tip of the cannula. In some embodiments, the ocular implant is pre-biased to assume an expanded configuration. When the implant is advanced beyond the tip of the cannula, the implant can expand so as to 25 disengage the delivery system (e.g., disengage a push tube).

[00015] In one embodiment, the ocular implant delivery system further comprises a core cable having a locking key, the locking key being configured to engage the ocular implant.

25 [00016] A method of delivering an implant into an eye of a patient is provided, comprising inserting a delivery device into the eye, advancing the implant into the eye through the delivery device, and expanding the implant to disengage the implant from the delivery device.

30 [00017] In some embodiments, the inserting step further comprises inserting a cannula into Schlemm's canal of the eye.

[00018] Another embodiment of the method further comprises the step of adjusting an orientation of the cannula with an orientation mechanism to align the cannula with a curvature of 30 Schlemm's canal.

[00019] In some embodiments of the method, the advancing step and the adjusting step are achieved with a single-hand of a user.

35 [00020] The advancing step of the method can further comprise advancing the implant with a wheel disposed on the delivery device. In another embodiment, the advancing step further comprises advancing the implant into the eye past a distal tip of the delivery device. In an

additional embodiment, the implant automatically expands to disengage itself from the delivery device when it is advanced past the distal tip of the delivery device.

[00021] In some embodiments, the expanding step further comprises expanding the implant to disengage an interlocking component of the implant from an interlocking component of the delivery device. The interlocking component of the delivery device can be an interlocking component of a push tube, for example. In another embodiment, the interlocking component of the delivery device can be an interlocking component of a core cable.

[00022] In some embodiments of the method, the advancing step further comprises advancing the implant into the eye with a push tube.

10 **[00023]** Alternatively, the advancing step can further comprise advancing the implant into the eye with a core cable. In one embodiment, the method can further comprise removing the core cable from the implant after expanding the implant.

[00024] In another embodiment, the implant is inserted into a suprachoroidal space.

15 **[00025]** Another method of implanting an ocular implant into Schlemm's canal of an eye is provided, comprising rotating an orientation mechanism of a delivery device to align a cannula with Schlemm's canal, advancing the cannula through a corneal incision and into the eye, piercing Schlemm's canal with the cannula, controlling an advancement mechanism of the delivery system with a first hand to advance the ocular implant from the delivery system into Schlemm's canal, holding a gonioscope with a second hand during the controlling step to visualize implantation of 20 the ocular implant into Schlemm's canal, and automatically disengaging the ocular implant from the delivery system when the ocular implant is advanced beyond a distal tip of the cannula.

[00026] In some embodiments, the method further comprises expanding the ocular implant in the eye to disengage the ocular implant from the delivery system.

[00026A] Typically an ocular implant delivery system, comprising:

25 a housing;
a cannula rotatably coupled to the housing, the cannula sized and configured for insertion into Schlemm's canal of a human eye;
an ocular implant disposed in the cannula;

30 a delivery mechanism disposed on the housing, the delivery mechanism configured to advance and retract the ocular implant within the cannula; and

an orientation mechanism disposed on the housing, the orientation mechanism configured to control rotation of the cannula with respect to the housing while maintaining the orientation of the ocular implant with respect to the cannula during cannula rotation.

2010271274 28 Apr 2015

[00026B] Typically, the ocular implant delivery system further comprising a push tube slidably disposed within the cannula and coupled to the delivery mechanism.

[00026C] Typically, the ocular implant delivery system wherein the ocular implant is coupled to a distal portion of the push tube.

5 **[00026D]** Typically, the ocular implant delivery system wherein the relative locations of the delivery mechanism and the orientation mechanism on the housing allow control over advancement and retraction of the ocular implant and rotation of the cannula with a single hand.

[00026E] Typically, the ocular implant delivery system further comprising a core cable disposed within the ocular implant.

10 **[00026F]** Typically, the ocular implant delivery system wherein the ocular implant is configured to automatically disengage from the ocular implant delivery system when it is advanced beyond a distal tip of the cannula.

[00026G] Typically, the ocular implant delivery system wherein the ocular implant is pre-biased to assume an expanded configuration.

15 **[00026H]** Typically, the ocular implant delivery system further comprising a core cable having a locking key, the locking key being configured to engage the ocular implant.

[00026I] Typically, the ocular implant delivery system wherein the ocular implant is pre-biased to assume an expanded configuration.

BRIEF DESCRIPTION OF THE DRAWINGS

20 **[00027]** The novel features of the invention are set forth with particularity in the claims that follow. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings of which:

[00028] Fig. 1 is a schematic drawing of a human eye.

25 **[00029]** Fig. 2 is a close-up view of the eye showing Schlemm's canal.

[00030] Fig. 3 is a delivery device for implanting an ocular implant in an eye.

[00031] Figs. 4-5 are close-up views of a portion of the delivery device.

- [00032] Fig. 6 is a cutaway side view of the delivery device.
- [00033] Fig. 7 is a close-up cutaway side view of the delivery device.
- [00034] Fig. 8 is an exploded view showing the internal features of the delivery device.
- [00035] Figs. 9-11 are close-up views of some internal features of the delivery device.
- [00036] Figs. 12-13 are cutaway side views of the delivery device.
- [00037] Fig. 14 is a close-up cutaway side view of a portion of the delivery device.
- [00038] Figs. 15-17 illustrate one embodiment of detaching an ocular implant from the delivery device.
- [00039] Figs. 18-19 illustrate another embodiment of detaching an ocular implant from the delivery device.
- [00040] Figs. 20-22 illustrate a method for implanting an ocular device in an eye of a patient.

DETAILED DESCRIPTION OF THE INVENTION

- 5 [00041] The following detailed description should be read with reference to the drawings, in which like elements in different drawings are numbered identically. The drawings, which are not necessarily to scale, depict exemplary embodiments and are not intended to limit the scope of the invention. Examples of constructions, materials, dimensions, and manufacturing processes are provided for selected elements. All other elements employ that which is known to those of skill
- 10 in the field of the invention. Those skilled in the art will recognize that many of the examples provided have suitable alternatives that can be utilized.
- [00042] The devices, systems, and methods described herein may aid in the treatment of glaucoma. The implantable ocular devices described herein may be inserted into Schlemm's canal, the trabecular meshwork, the suprachoroidal space, and/or the anterior chamber of the eye
- 15 to facilitate the outflow of aqueous humor from the anterior chamber. When in place within the eye, the implantable devices can support trabecular meshwork tissue and/or Schlemm's canal tissue, and can provide for improved communication between the anterior chamber and Schlemm's canal (via the trabecular meshwork), between pockets or compartments along Schlemm's canal, and/or the suprachoroidal space.
- 20 [00043] The systems described herein may include delivery devices for delivering implantable devices into Schlemm's canal, the trabecular meshwork, the suprachoroidal space, and/or the anterior chamber of the eye. The delivery devices described herein may be configured to advance, retract, and deploy the implantable device precisely and predictably by a single physician or surgeon using the motion of a single finger. The delivery device may selectively

engage the implantable device allowing the device to be advanced and retracted before implantation within the eye. The delivery devices described herein may also be configured to rotate a bent portion of the delivery device to align with the curvature of the iris of the eye.

[00044] Fig. 1 is a schematic view showing a portion of an eye 20. A reflection on the outer surface of the cornea 22 of the eye is visible in Fig. 1. Cornea 22 encloses an anterior chamber 24 of eye. The iris 26 of the eye is visible through the cornea and anterior chamber. Anterior chamber 24 is filled with aqueous humor which helps maintain the generally hemispherical shape of the cornea. The structures that drain aqueous humor from anterior chamber 24 include Schlemm's canal 30 and a large number of veins 28.

10 [00045] In Fig. 1, Schlemm's canal 30 can be seen encircling iris 26. Aqueous humor exits anterior chamber 24 and enters Schlemm's canal 30 by flowing through a trabecular mesh 32. Aqueous humor exits Schlemm's canal 30 by flowing through a number of outlets called collector channels 40. After leaving Schlemm's canal 30, aqueous humor travels through veins 28 and is absorbed into the blood stream.

15 [00046] Fig. 2 is an enlarged schematic view of a portion of eye 20 shown in the previous figure. The flow of aqueous humor in eye 20 is illustrated using arrows in Fig. 2. In Fig. 2, aqueous humor flowing through trabecular mesh 32 and into Schlemm's canal 30 is represented by a number of lateral flow arrows 34. The flow of aqueous humor along the length of Schlemm's canal is illustrated using a number of axial flow arrows 36.

20 [00047] Fig. 3 illustrates a single operator delivery device 100 configured to deliver an ocular implant into the eye of a patient, such as into Schlemm's canal, the trabecular meshwork, the suprachoroidal space, and/or the anterior chamber of the eye. The ocular implant to be implanted can include any ocular implant described in US Appln. Nos. 11/860,318, 11/943,289, 12/236,254, 12/398,847, and US Provisional Patent Appln. Nos. 61/033,746, 61/120,222, and 25 61/120,295.

[00048] Referring to Fig. 3, delivery device 100 can include housing 102, rotatable sleeve 104, tracking wheel 106, cannula 108, and end cap 110. The delivery device shown in Fig. 3 is configured to be gripped with one hand while providing control of rotation and orientation of the cannula (via the rotatable sleeve 104) in addition to control over advancement, retraction, and 30 deployment of the ocular implant (via the tracking wheel 106), all while gripping the delivery device with the same hand. In general, the tracking wheel is a delivery mechanism configured for advancement and retraction of the ocular implant and the rotatable sleeve is an orientation mechanism configured to control rotation and orientation of the cannula. The housing of delivery device 100—in particular, the relative location of the movable control elements within 35 the housing—results in an ideal ergonomic relationship of the finger-operated control elements

relative to the hand-stabilized housing. This design provides a configuration that will allow a user, such as a physician, to stabilize and orient the delivery device while simultaneously allowing the middle or index finger to move independently and perform the implantation of an ocular implant. This one-handed operation leaves the physician's other hand free for other uses, 5 such as holding a gonioscope.

[00049] Figs. 4-5 show a close-up view of rotatable sleeve 104 and cannula 108. In some embodiments, the cannula can have a curved or bent distal portion 114 configured to aid with implantation of an ocular implant into the eye, such as into Schlemm's canal. The bent distal portion of the cannula may have a pre-formed bend or curvature that is sized and configured to 10 align with and be implanted in the natural curvature of Schlemm's canal. The cannula may also have a sharpened or beveled tip, for example, to cut into and through tissue. As shown, cannula can mount to a hub 112. The hub can attach to the rotatable sleeve in a number of ways, such as by a pin 116 or by an adhesive. By coupling the rotatable sleeve 104 to the cannula 108 and hub 112, rotation of the rotatable sleeve (such as by a physician) can change the orientation of the 15 cannula with respect to the housing 102. For example, Fig. 4 shows the cannula in a first orientation, and Fig. 5 shows the cannula in a second orientation after rotation of the rotatable sleeve. The rotatable sleeve 104 may also include gripping features, such as grooves (as shown), a rubber coating, or other frictional surfaces on the rotatable sleeve.

[00050] During implantation of an ocular implant, correct alignment between the cannula and 20 iris is necessary to ensure that the ocular implant is advanced at the correct trajectory relative to Schlemm's canal or other anatomy in the eye into which the ocular implant is to be implanted. Changing the orientation of the cannula with respect to the housing allows the delivery device 100 to be adjusted to accommodate individual anatomical variables, individual physician holding 25 position preferences, and right/left handed users. The delivery device is configured in a manner that keeps the ocular implant aligned within the delivery device during rotation. All components are keyed together to ensure that the implant and cannula rotate as a single body while simultaneously allowing linear movement (i.e., advancement and retraction) of the ocular implant. For example, in some embodiments of an ocular implant, certain features of the 30 implant, such as openings in the implant, are configured to be aligned with specific anatomy, such as collector channels of Schlemm's canal. Since the delivery device described herein keeps the ocular implant aligned with a pre-determined curvature of the cannula, a physician can ensure the proper orientation of the implant once it's been delivered to Schlemm's canal.

[00051] Fig. 6 is a cutaway view of the delivery device 100 showing the device's internal features, including tracking wheel 106, idler gear 118, and rotating rack gear 120. Tracking 35 wheel 106 and idler gear 118 are rotatably mounted to the housing 102. Gears on the tracking

wheel engage with gears on the idler gear 118, which in turn engage with gears on the rotating rack gear 120 to move the rack gear proximally and distally within the delivery device. The idler gear 118 is included in the device so that rotation of the tracking wheel 106 in the distal direction will cause the rack gear to move distally, and rotation of the tracking wheel in the proximal direction will cause the rack gear to move proximally. In addition, the rotating rack gear 120 is configured to rotate with rotatable sleeve 104 while maintaining the ability to move linearly in the distal and proximal directions before, during, and after rotation.

5 [00052] Fig. 7 is a close-up view of the internal features of the delivery device near the rotatable sleeve 104, including hub 112, pin 116, ocular implant 122, push tube 124, and O-ring 10 126. The ocular implant and push tube can be any ocular implant and push tube as described in the US Patent Applications and Provisional Patent Applications reference above. As shown in Fig. 7, the ocular implant can be positioned partially within cannula 108 and can abut push tube 124 in the delivery device. The O-ring can provide tension and resistance to the rotatable sleeve for tactile feedback during rotation and can prevent the sleeve from being moved from the 15 desired orientation.

[00053] Figs. 8-11 are exploded views of the internal features of delivery device 100, including housing 102, tracking wheel 106, cannula 108, end cap 110, hub 112, idler gear 118, rotating rack gear 120, push tube 124, slot 128, transport tube 130, interlocking finger connector 132, finger receptacle 134, and core cable or core shaft 136. As shown in Fig. 8, transport tube 20 130 is connected to hub 112 and is sized to slidably carry an ocular implant and push tube 124 therein. A proximal portion of the transport tube (as shown in Fig. 9) can include a hexagonal sleeve sized to fit within a hexagonal through-hole in the rotating rack gear 120 (as shown in Fig. 11).

25 [00054] As described herein and in the above referenced applications, push tube 124 and the ocular implant can be sized and configured to slide within transport tube 130 and a cannula. The push tube 124 can have a diameter corresponding to the diameter of the ocular implant, so that distal movement of the push tube can push against and cause distal movement of the ocular implant within the delivery system and into the patient.

[00055] Furthermore, the delivery device can also include a core cable 136 sized to slide 30 within the ocular implant and push tube 124. Referring to Figs. 8 and 11, the core cable 136 can be coupled to the rotating rack gear 120. As described in the above referenced applications, the core cable can be positioned within an internal diameter of the ocular implant during delivery of the implant so as to block and prevent any sharp edges or holes in the implant (such as the edges of fluid inlets and outlets in the implant) from cutting or damaging tissue within the patient

during implantation. Additionally, the core can have a distal radius adapted to dilate Schlemm's canal as the implant is inserted into the patient.

[00056] As shown in Figs. 10-11, a proximal portion of the core cable can include interlocking finger receptacles 134 adapted to engage and join interlocking fingers 132 on a 5 proximal portion of the push tube. The interlocking fingers 132 can be pre-biased to assume an expanded or outward configuration. For example, the interlocking fingers 132 can be formed from stainless steel or from a shape memory material such as Nitinol. In some embodiments, the interlocking finger receptacles and the interlocking fingers are cut from hypotubes having the same diameter. When the fingers are compressed, such as within transport tube 130, they can 10 engage the interlocking finger receptacles to join the push tube and core cable together, and allow the push tube and core cable to move together through the transport tube 130 and delivery system as the rotating rack gear is moved distally and proximally.

[00057] Figs. 12-13 illustrate how rotation of the tracking wheel 106 causes the movement of idler gear 118, rotating rack gear 120, ocular implant, push tube 124, and core cable 136, thereby 15 enabling one-handed operation through one-fingered advancement of the implant, release of the implant and retraction of the delivery mechanism. In Fig. 12, delivery device 100 is shown prior to deployment of the ocular implant into the patient, with rotating rack gear 120 positioned proximally within slot 128 in housing 102. Fig. 13 shows the delivery device fully deployed, with the rotating rack gear positioned distally in slot 128 and touching hub 112. To move the 20 rotating rack gear 120 from the proximal position shown in Fig. 12, to the distal position shown in Fig. 13, the tracking wheel 106 can be rotated distally (e.g., in a counter-clockwise direction as shown by the arrows in Fig. 13), which causes idler gear 118 to rotate in a proximal direction, which in turn causes the rotating rack gear 120 to move distally towards hub 112. Similarly, the rotating rack gear can be returned to the proximal position within housing 102 by rotating 25 tracking wheel 106 in a proximal direction. In another embodiment, the idler gear can be eliminated from the delivery device, which would cause distal movement of the tracking wheel to move the rack gear proximally.

[00058] As the rotating rack gear 120 moves distally from the proximal position in Fig. 12 to the distal position in Fig. 13, the rack gear causes push tube 124, core cable 136, and the ocular 30 implant (not shown) to move distally within transport tube 130. When the rack gear is in the distal position as shown in Fig. 13, the ocular implant is pushed completely out of cannula 108 and into the patient. In some embodiments, the rack gear need not be fully advanced in the distal-most position to push the implant out of the cannula.

[00059] Additionally, when the rack gear is in the distal-most position, the interlocking 35 fingers 132 (shown in Fig. 14) of the push tube 124 and the interlocking finger receptacles 134

(show in Fig. 14) of the core cable 136 are positioned in an opening 138 in hub 112, as shown in Fig. 14. The opening 138 can have a larger inner diameter than the transport tube 130. The transport tube 130 can terminate at the opening 138, so when the interlocking fingers enter the opening and are no longer constrained by the inner walls of the transport tube, the interlocking 5 fingers 132 are allowed to automatically expand outward to assume their pre-biased configuration, thereby disengaging the push tube 124 from the finger receptacles 134 of the core cable 136. With the core cable detached from the push tube, proximal movement of the rack gear (such as by rotating the tracking wheel in a proximal direction) can remove the core cable 10 proximally from the push tube and ocular implant, thereby removing the core cable from the implant and leaving the implant in the patient. The push tube is allowed to remain at the distal-most position to abut the ocular implant and keep the implant in place as the core cable is removed.

[00060] It should be understood that the advancement and retraction of the ocular implant are not limited to the tracking wheel described herein. For example, in some embodiments, the 15 housing may include buttons and a motor for electronically driving the wheel to advance and retract the implant.

[00061] Figs. 15-17 illustrate an embodiment of a device and method for selectively coupling an ocular implant 122 to a push tube 124 in a delivery device 100. Fig. 15 is a top down view of push tube 124 and ocular implant 122 positioned within cannula 108 of delivery device 100. The 20 push tube and ocular implant can include an interlocking component 140, similar to the interlocking fingers and interlocking finger receptacles described above. For example, the push tube may include an interlocking finger and the ocular implant may include an interlocking finger receptacle, or vice versa. Any variety of interlocking shapes may be used. Fig. 16 is a side view of the push tube and ocular implant shown in Fig. 15. Fig. 16 shows the ocular 25 implant further comprising a slit or plurality of slits 142. The ocular implant can be pre-biased to assume an expanded configuration. When the implant is compressed, such as within the cannula or the transport tube described above, the interlocking component 140 will compress and cause the implant to engage and lock with the push tube. However, when the ocular implant is pushed distally beyond the distal tip of the cannula 108, as shown in Fig. 17, the implant can assume its 30 pre-biased configuration, causing the implant to automatically expand along the slits and detach from the push tube to be released in the patient. The expanded portion of the implant also provides for a larger opening to prevent clogging when implanted inside a patient.

[00062] Figs. 18-19 illustrate an alternative embodiment of the delivery system 100 that does not include a push tube, but rather uses a locking key 144 coupled to the core cable 136 to 35 advance, retract, and deliver the ocular implant into a patient. As shown in Fig. 18, core cable

136 can be disposed within the ocular implant 122 and cannula 108 of delivery system 100. Locking key 144 can be disposed on the core cable and can engage window 146 in the ocular implant. As described above, the implant can be pre-biased to assume an expanded configuration when the implant is not constrained (e.g., such as when the implant is not constrained within a cannula). When the implant is compressed, such as within the cannula or the transport tube described above, the locking key 144 will engage window 146 to couple the core cable to the implant. However, when the ocular implant is pushed distally beyond the distal tip of the cannula 108, as shown in Fig. 19, the implant can assume its pre-biased configuration, causing the implant to expand and detach from the core cable.

5 10 [00063] The delivery devices described herein are configured to advance and retract an ocular implant and deliver the implant into the eye of a patient by a physician using a single hand. A physician typically has only one hand available to perform the implantation as the other hand is used to simultaneously hold and stabilize a gonioscope for visualization of the implantation procedure. Physicians typically use their feet during the procedure to adjust the image through 15 the surgical microscope, making a foot-operated system impractical.

10 20 [00064] As described above, advancement and retraction of the implant can be controlled with a tracking wheel 106, and orientation of the implant in the patient can be controlled by changing the orientation of the cannula, hub, implant, push tube, and core cable by rotating the rotatable sleeve 104. When the ocular implant is advanced distally beyond the distal tip of cannula 108, the implant can automatically expand to a pre-biased configuration to disengage the push tube and remain within the patient in the desired location within the eye. As described above, it may be necessary to remove a core cable from within the implant by retracting the rotating rack gear in the proximal direction before fully implanting the ocular implant in the patient.

25 [00065] Figs 20-22 illustrate a method for delivering an ocular implant into a patient. The ocular implant may be inserted into Schlemm's canal, the trabecular meshwork, the suprachoroidal space, and/or the anterior chamber to facilitate the outflow of aqueous humor from the anterior chamber. This flow of aqueous humor can include axial flow along Schlemm's canal, flow from the anterior chamber into Schlemm's canal, flow leaving Schlemm's canal via outlets communicating with Schlemm's canal, or flow into the suprachoroidal space. When 30 implanted within the eye, the ocular implant will support trabecular mesh tissue and Schlemm's canal tissue and will provide for improved communication between the anterior chamber and Schlemm's canal (via the trabecular meshwork), between pockets or compartments along Schlemm's canal, or between the anterior chamber and the suprachoroidal space.

35 [00066] Fig. 20 is a view showing a portion of the face and eye 20. Cannula 108 extends through a cornea of eye 20 so that the distal end of cannula 108 is disposed in the anterior

chamber of the eye. With reference to Fig. 20, it will be appreciated that the distal tip of cannula 108 is positioned near the trabecular mesh and Schlemm's canal 32 of the eye. The orientation of the cannula to the eye can be adjusted by rotating the rotatable sleeve described above with reference to Figs. 3-7.

5 [00067] Fig. 21 is a further enlarged view illustrating a portion of eye 20 shown in the previous figure. In the embodiment of Fig. 21, the distal tip of cannula 108 has pierced through trabecular mesh 32. The distal tip of cannula 108 has also pierced the wall of Schlemm's canal 30 and a distal opening of cannula 108 is disposed in fluid communication with Schlemm's canal. In some embodiments, cannula 108 is curved to achieve substantially tangential entry into 10 Schlemm's canal.

[00068] Fig. 22 is an additional view of eye 20 shown in the previous figure. In the embodiment of Fig. 22, an ocular implant 122 has been advanced through the cannula and into Schlemm's canal of the eye. Fig. 22 illustrates a core cable 124 disposed within the implant 122, and push tube (not shown) abutting a proximal portion of the ocular implant within the cannula 15 108, as described above. The ocular implant can be advanced through the delivery system and into the eye with the delivery device 100 described herein, such as by rotating tracking wheel 106 to advance the push tube, core cable, and implant through the delivery system and into the eye, as described above with reference to Figs. 3, 6, and 12-13.

[00069] Once the implant is positioned within Schlemm's canal (or alternatively within the 20 suprachoroidal space or other anatomy of the eye), the implant can be advanced beyond a distal portion of the cannula to allow the implant to detach from the push tube and core cable (as described above and shown in reference to Figs. 14-19). The core cable can also be configured to automatically detach from the push tube, and the core cable can then be retracted from the ocular implant while the push tube is allowed to abut the implant to keep the implant in place. 25 Once the implant is within the eye of the patient, the delivery system can be removed from the patient leaving only the implant behind.

[00070] In another embodiment that does not utilize a push tube, as described above and referenced in Figs. 18-19, the implant can be advanced beyond a distal portion of the cannula to allow the implant to detach from the a locking key of the core cable. The core cable can then be 30 removed from the ocular implant. Once the implant is within the eye of the patient, the delivery system can be removed from the patient leaving only the implant behind.

[00071] As for additional details pertinent to the present invention, materials and manufacturing techniques may be employed as within the level of those with skill in the relevant art. The same may hold true with respect to method-based aspects of the invention in terms of 35 additional acts commonly or logically employed. Also, it is contemplated that any optional

feature of the inventive variations described may be set forth and claimed independently, or in combination with any one or more of the features described herein. Likewise, reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in the appended claims, the singular forms "a," "and," "said," and "the" include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as "solely," "only" and the like in connection with the recitation of claim elements, or use of a "negative" limitation. Unless defined otherwise herein, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. The breadth of the present invention is not to be limited by the subject specification, but rather only by the plain meaning of the claim terms employed.

[00072] Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

[00073] The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

2010271274 28 Apr 2015


THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An ocular implant delivery system, comprising:
 - a housing;
 - a cannula rotatably coupled to the housing, the cannula sized and configured for insertion into Schlemm's canal of a human eye;
 - an ocular implant disposed in the cannula;
 - a delivery mechanism disposed on the housing, the delivery mechanism configured to advance and retract an ocular implant within the cannula; and
 - an orientation mechanism disposed on the housing, the orientation mechanism configured to control rotation of the cannula with respect to the housing while maintaining the orientation of the ocular implant with respect to the cannula during cannula rotation.
2. The ocular implant delivery system of claim 1 further comprising a push tube slidably disposed within the cannula and coupled to the delivery mechanism.
3. The ocular implant delivery system of claim 2 wherein the ocular implant is coupled to a distal portion of the push tube.
4. The ocular implant delivery system of claim 1 wherein the relative locations of the delivery mechanism and the orientation mechanism on the housing allow control over advancement and retraction of the ocular implant and rotation of the cannula with a single hand.
5. The ocular implant delivery system of claim 1 further comprising a core cable disposed within the ocular implant.
6. The ocular implant delivery system of claim 1 wherein the ocular implant is configured to automatically disengage from the ocular implant delivery system when it is advanced beyond a distal tip of the cannula.
7. The ocular implant delivery system of claim 6 wherein the ocular implant is pre-biased to assume an expanded configuration.


8. The ocular implant delivery system of claim 1 further comprising a core cable having a locking key, the locking key being configured to engage the ocular implant.

9. The ocular implant delivery system of claim 8 wherein the ocular implant is pre-biased to assume an expanded configuration.




1/12

**FIG. 1**



2/12

**FIG. 2**


3/12

**FIG. 3****FIG. 4****FIG. 5**



4/12






5/12




**FIG. 8**

HEXAGONAL SLEEVE


**FIG. 9****FIG. 10****FIG. 11**

**FIG. 12****FIG. 13****FIG. 14**


7/12

FIG. 15**FIG. 16****FIG. 17**


8/12

**FIG. 18**


9/12

**FIG. 19**


10/12

**FIG. 20**

11/12

**FIG. 21**

12/12

**FIG. 22**