




(86) Date de dépôt PCT/PCT Filing Date: 2014/03/14  
(87) Date publication PCT/PCT Publication Date: 2014/10/16  
(45) Date de délivrance/Issue Date: 2021/03/23  
(85) Entrée phase nationale/National Entry: 2015/09/10  
(86) N° demande PCT/PCT Application No.: IB 2014/001421  
(87) N° publication PCT/PCT Publication No.: 2014/167420  
(30) Priorité/Priority: 2013/03/15 (US61/788,370)

(51) Cl.Int./Int.Cl. *D04H 1/00* (2006.01),  
*B29C 70/38* (2006.01), *D04H 1/58* (2012.01),  
*D04H 1/70* (2012.01)  
(72) Inventeurs/Inventors:  
GILOH, TAMAR, GB;  
GILOH, EHUD, GB;  
MELAMED, REUVEN, IL  
(73) Propriétaire/Owner:  
TAMICARE LTD., GB  
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : APPAREIL PERMETTANT DE PRODUIRE UN PRODUIT NON TISSE DANS UN ENVIRONNEMENT NON INDUSTRIEL

(54) Title: AN APPARATUS FOR PRODUCING A NONWOVEN PRODUCT IN A NON-INDUSTRIAL ENVIRONMENT



(57) **Abrégé/Abstract:**

An apparatus for producing a non-woven product is disclosed. The apparatus is located substantially within an enclosure and includes a mold or former and at least two moveable material application heads. A controller controls various elements located within or connected to the enclosure. The footprint of the enclosure is smaller than 2m x 2m.

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(10) International Publication Number  
**WO 2014/167420 A3**

(43) International Publication Date  
16 October 2014 (16.10.2014)

## (51) International Patent Classification:

**D04H 1/00** (2006.01) **D01G 25/00** (2006.01)  
**D04H 1/58** (2012.01) **B29C 70/38** (2006.01)  
**D04H 1/70** (2012.01) **B29C 67/00** (2006.01)  
**D01G 21/00** (2006.01)

## (21) International Application Number:

PCT/IB2014/001421

## (22) International Filing Date:

14 March 2014 (14.03.2014)

## (25) Filing Language:

English

## (26) Publication Language:

English

## (30) Priority Data:

61/788,370 15 March 2013 (15.03.2013) US

(71) Applicant: **TAMICARE LTD.** [GB/GB]; Unit 4, Broadfield Business Park, Pilsworth Road, Heywood OL10 2TA (GB).

(72) Inventors: **GILOH, Tamar**; Unit 4, Broadfield Business Park, Pilsworth Road, Heywood OL10 2TA (GB). **GILOH, Ehud**; Unit 4, Broadfield Business Park, Pilsworth Road, Heywood OL10 2TA (GB). **MELAMED, Reuven**; 30900 Zikhron Ya'akov (IL).

(74) Agents: **LANE, Cathal, Michael** et al.; TOMKINS & CO., 5 Dartmouth Road, DUBLIN 6 (IE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

## Published:

— with international search report (Art. 21(3))

## (88) Date of publication of the international search report:

24 December 2014

(54) Title: AN APPARATUS FOR PRODUCING A NONWOVEN PRODUCT IN A NON-INDUSTRIAL ENVIRONMENT




Figure 1

(57) Abstract: An apparatus for producing a non-woven product is disclosed. The apparatus is located substantially within an enclosure and includes a mold or former and at least two moveable material application heads. A controller controls various elements located within or connected to the enclosure. The footprint of the enclosure is smaller than 2m x 2m.

## **AN APPARATUS FOR PRODUCING A NONWOVEN PRODUCT IN A NON-INDUSTRIAL ENVIRONMENT**

### **Background**

[0001] A small scale printer for 3D product printing is relatively new but a well known process. It features a very desired customization level for products and easy access to producing products "at home" with its added convenience and independency. The nonwoven industry usually employs full scale, very large machines for regular production of nonwoven disposable products such as diapers, etc. The massive quantities of products used by individuals and the different desired and required specs create the need for a small scale production system, for home usage and for institutional usage (hospitals, home-care, children garden, army, space ship etc.). There is also a growing interest in the field of home printing, and the possibility of printing cloths for regular daily use is something people are looking for.

### **Summary**

[0002] This application discloses producing a nonwoven article at a non-industrial environment. The main difference in the production method of this invention to the method currently used in industrial production lines for nonwoven products is in that the invention introduces a neat aesthetic small footprint enclosed apparatus where products are produced typically in a relatively small output without departing outside the limited boundaries of the SOHO (Small Office Home Office) scale enclosure.

[0003] The apparatus incorporates different static and moving parts for the application of product materials, such as polymers in a liquid and loose textile fibers, and the production is executed mainly one step at a time and the different material application units do not work simultaneously, but generally one after the other sequentially.

[0004] In one embodiment, an apparatus for small scale production of nonwoven products is disclosed. The apparatus includes an enclosure, a former located within the enclosure, a controller mounted to the enclosure, at least two moveable appliance heads located within the enclosure, the at least two moveable appliance heads being

controlled by the controller, at least one container for polymers mounted to the enclosure and connected to one of the moveable appliance heads, at least one container for fibers mounted to the enclosure and connected to the other moveable appliance heads, and a curing system. The footprint of the enclosure is smaller than 2m x 2m.

[0005] In one aspect, the footprint of the enclosure is smaller than 1.5m x 1.5m.

[0006] In another aspect, the footprint of the enclosure is smaller than 1m x 1m.

[0007] In another aspect, the former is fixed in place.

[0008] In another aspect, the former is motorized and moving, and wherein the movement of the former does not exceed the size of the enclosure.

[0009] In another aspect, the at least one moveable appliance head comprises a spray nozzle.

[0010] In another aspect, the at least one moveable appliance head comprises a fiber flocking unit.

[0011] In another aspect, the former can be removed from the apparatus.

[0012] In another aspect, the enclosure further comprises a set of fiber cartridges.

[0013] In another aspect, the enclosure further comprises a user interface.

[0014] In another aspect, the at least two moveable appliance heads are mounted on the same a moveable arm or mechanism.

[0015] In another aspect, the one moveable appliance head is mounted on one moveable arm or mechanism, and another moveable appliance head is mounted on a second moveable arm or mechanism.

### **Description of the Drawing**

[0016] Figure 1 shows a top view of an example apparatus of the present application.

[0017] Figure 2 is a block diagram of one embodiment of the apparatus.

### **Description**

[0018] An apparatus for producing nonwoven products in a non-industrial environment is disclosed, the apparatus comprising a mold on which the product materials are layered and built (or printed, in an additive manufacturing process), layer by layer. Primarily, polymers in a latex form (suspension or emulsion) and loose textile fibers are applied in a desired sequence and at specific zones on top of

the mold surface, according to the product structure and specifications, and cured (by polymerization of the polymer) to create a non-woven fabric and product. A motorized moving 'appliance' head/s is used for applying different liquid based materials and polymers, motorized movable fibers flocking head/s or unit/s, polymer curing system heating or drying elements or water evaporation system, material storage containers, etc.

[0019] In this application the term 'mold' or 'mould' is interchangeable with the term 'former' and with the term 'production surface'.

[0020] In this application the term 'appliance head' is interchangeable with the term 'material application unit or gun'.

[0021] The apparatus is a contained structure having substantially all of its components and parts located within a single enclosure, with aesthetics similar to a SOHO paper printer or 3D printer, creating a pleasant, appealing and user friendly machine and gadget.

[0022] Referring to Figure 1, an enclosure 100 is provided. The enclosure 100 contains at least one former, production surface, or mold 102, and the fabric film created on top of the mold substantially conforms to the shape of the mold so that a shape of the mold largely define the shape of final product made by the apparatus. The former 102 includes an outer surface 101. The enclosure also includes a controller 200 incorporated therein for controlling various elements located within or connected to the enclosure.

[0023] The enclosure 100 further includes at least one moveable material application head or unit in the form of a liquid polymer spray nozzle 104. The movable spray nozzle 104 may be mounted on a motorized moving arm 111. The moving arm 111 may be any moving arm as know in the art, such as but not limited to XY table, XYZ system or any other suitable moving mechanism. The moving arm 111 is operated by the controller 200, moving the material application head 104 alongside the outer surface 101 of the former 102 in correlation with data received by the controller 103. The moving arm(s) or mechanism 111 is designed to move the material application

heads ('printing' heads) 104, 105 according to the desired location and trajectory, alongside the surface 101 of the mold 102.

[0024] A suitable spray nozzle 104 or sprayer system may include, without limitation, air assisted based, airless based, electrostatic-based sprayers. The spray nozzle or sprayer system may further include spray guns, compressors, pressure tanks, pressure regulators, feeding pipes and other components known in the art for spraying liquid polymers, elastomers such as latex, and other like materials.

[0025] The spray nozzle 104 may include a variety of controllable parameters. Examples of the parameters include, but are not limited to, amount of liquid material delivered as a function of time, fan pattern, direction, controlled material atomization, and spray gun activation. The parameters for spray operation may be set automatically or manually. If set automatically, the parameters may be determined by accessing the memory which stores the parameters for operation of the sprayer. Based on this determination, the memory may be accessed to set the parameters for the sprayer based on the aspects of the product so that further operation steps such as additional spraying of product material bands or layers at specific regions of the initial product for thickening or reinforcement may be performed.

[0026] The enclosure also includes another material application head in the form of a fiber flocking unit 105, the flocking unit also being operated by the controller 200. The fiber flocking unit 105 is located within the enclosure 100 and is mounted on a second motorized, movable arm or mechanism 112, or on the same movable arm or mechanism, 111.

[0027] The enclosure also includes at least one container 106 for holding polymer and in connection with the spray nozzle 104. The container 106 may be connected to a pump and/or to the spray nozzle 104 by tubing for example. Other connection means are also possible. The polymers are sprayed onto the mold 102 through the spray nozzle 104. The enclosure 100 may further include at least one container 107 for containing loose fibers to be flocked. The container 107 is connected to the fiber flocking unit 105, such as by tubing for example. Other connection means are also possible. The loose fibers are flocked onto the mold 102 by the fiber flocking unit

105. The polymer and/or the loose fiber containers 106 and 107 may be replaceable cartridges. Although the apparatus is substantially enclosed, the material storage containers 106 and 107 may be located within the enclosure, slightly outside or partly outside of it, or underneath it to allow for easy replacement and handling.

[0028] The enclosure 100 may also include a curing system 108 for curing the polymers on the mold 102. The curing system 108 may be located within the enclosure 100. The curing system 108 may be induced by heat using UV or incandescent light or a heating coil, blowing hot air, or through a chemical reaction, or by suitable IR radiation or by any other suitable method.

[0029] In another embodiment, the enclosure 100 may contain a set of fiber cartridges 109, as a replacement for containers 106 and/or 107, and each cartridge may contain fibers of different nature, length, width (Decitex), and color.

[0030] Examples of fiber materials may be viscose, cotton, polyamide, polyester, silk, wool, or any other suitable fiber.

[0031] Referring to Figure 2, a representative block diagram of the system is shown. The controller 200 controls the operation of the system. Examples of a controller include, but are not limited to, a computer, a terminal, a workstation, or some other electronic device capable of controlling the operation of the moveable arms 111 and the former 102. The moveable arms 111 each include at least one motor 206 for moving components connected to the arms, i.e., the spray nozzle 104 and the flocking unit 105. The controller 200 includes a processor 202 and a memory 204. The processor 202 may comprise a microprocessor, a microcontroller, or any device which performs arithmetic, logic or control operations. The memory 204 may include any suitable memory device such as non-volatile memory devices such as a ROM, or magnetic or optical memory. The memory 204 may also include volatile memory devices such as a RAM device. Software may be included for the controller 200 to control components within the system, such as the arms 111, the flocking unit 105, and former 102.

[0032] The apparatus may also comprise other components such as pumps, pressure regulators, a high voltage generator for electrostatic fibers flocking or for electrostatic liquid polymer spraying, brushes, an adhesive or hot melt applicator and a seaming tool to close a flat product into a sleeve shaped or partially sleeved product, and additional material/s or object/s applicator, 105a such as sanitary pad applicator, a nonwoven sheets applicator, a decoration applicator, perfume or other liquids applicators, those material/s or object/s applicators may be movable in a controlled manner by the controller to apply the material/s or object/s at any desired location or zone of the former surface. The apparatus may also include a vision system, a numeric printer, a counter. These components may be attached to or contained within the enclosure 100. A user interface 110 may also be mounted on the enclosure 100. The user interface operates the controller 200. The user interface 110 may include push-buttons or a keyboard, and a display.

[0033] The footprint of the enclosure 100 is preferably smaller than approximately 2m x 2m, and even more preferably smaller than approximately 1.5m x 1.5m or even more preferably smaller than approximately 1m x 1m.

[0034] The apparatus may produce the products according to a pre-set program, hence facilitating operation by a non-skilled operator. Design and production data and commands are generated by electronic media and may be transmitted to the apparatus via a digital interface.

[0035] In one embodiment, the former 102 may be fixed in place. In another embodiment, the former 102 may be motorized and moving during production to improve production process speed, efficiency or accuracy. However, the movement of the former 102 shall not generally exceed the size of the enclosure 100 or cause the former to depart from the enclosure.

[0036] In another embodiment, the material application heads 104, 105, 105a may be substantially static during the manufacturing process, so that at least most of the necessary relative movements, between the materials application heads 104, 105, 105a (any material application device within the enclosure) and the former are performed by movements of the former 102.



[0037] In yet another embodiment, some of the relative movements between the materials application heads and the former 102 are performed by movement of at least some of the material applications heads, and some relative movements are performed by moving of the former.

[0038] In yet another embodiment, the former 102 may be removed, manually or automatically, from the apparatus, after the product is substantially created, allowing convenient removal of the finished product from the former.

[0039] The apparatus of the present application may be used to produce products such as lingerie, sportswear, swimwear, sanitary napkins, diapers, medical dressing, cosmetic masks, sanitary underwear or any other desired garment or product. The apparatus may be also used to produce regular nonwoven clothing, such as underwear, tights, shirts, sportswear etc. The products produced in the apparatus may include the technology and materials introduced by TamiCare ltd in, for instance, U.S. Patent nos. 7,354,424; 7,901,740; 7,700,030; and 8,323,764; U.S. Pub. Patent application nos. 2009/0131902, but are not limited to this technology and products only.

[0040] The apparatus may also comprise a unit for adding on an absorbent device such as a hygiene pad. See, for instance, U.S. Design patent no. D595,844 and U.S. Patent publication no. 2010/0106124.

We claim:

1. An apparatus for small scale production of nonwoven products, the apparatus comprising:

an enclosure;

a former located within the enclosure;

a controller mounted to the enclosure;

at least two moveable appliance heads located within the enclosure, the at least two moveable appliance heads being controlled by the controller ;

at least one container for polymers mounted to the enclosure and connected to one of the at least two moveable appliance heads, wherein said one of the at least two moveable appliance heads comprises a spray nozzle for spraying said polymers;

at least one container for fibers mounted to the enclosure and connected to the other of the at least two moveable appliance heads, wherein said other of the at least two moveable appliance heads comprises a fiber flocking unit; and

a curing system;

wherein the footprint of the enclosure is smaller than 2m x 2m.

2. The apparatus according to claim 1 wherein the footprint of the enclosure is smaller than 1.5m x 1.5m.

3. The apparatus according to claim 1 wherein the footprint of the enclosure is smaller than 1m x 1m.

4. The apparatus according to any one of claims 1 to 3, wherein the former is fixed in place.

5. The apparatus according to any one of claims 1 to 3, wherein the former is motorized and moving, and wherein the movement of the former does not exceed the size of the enclosure.

6. The apparatus according to any one of claims 1 to 5, wherein the former is removeable from the apparatus.

7. The apparatus according to any one of claims 1 to 6, wherein the enclosure further comprises a set of fiber cartridges.

8. The apparatus according to any one of claims 1 to 7, wherein the enclosure further comprises a user interface.

9. The apparatus according to any one of claims 1 to 8, wherein the at least two moveable appliance heads are mounted on a moveable arm or mechanism.

10. The apparatus according to any one of claims 1 to 9 wherein said one of the at least two moveable appliance heads is mounted on one moveable arm or mechanism, and said other of the at least two moveable appliance heads is mounted on a second moveable arm or mechanism.

1/2




Figure 1

2/2




Figure 2

