



(51) International Patent Classification:

B01J 23/46 (2006.01) F01N 3/10 (2006.01)
B01D 53/94 (2006.01) F01N 3/035 (2006.01)

(21) International Application Number:

PCT/EP2019/078194

(22) International Filing Date:

17 October 2019 (17.10.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

18201092.6 18 October 2018 (18.10.2018) EP

(71) Applicant: UMICORE AG & CO. KG [DE/DE]; Rodenbacher Chaussee 4, 63457 Hanau-Wolfgang (DE).

(72) Inventors: SCHOENHABER, Jan; Heinrich-Fuhr-Str. 19, 64287 Darmstadt (DE). RICHTER, Joerg-Michael; Dietrich-Bonhoeffer-Weg 51, 60389 Frankfurt (DE). BRAUN, Carolin; Bahnstraße 74, 63225 Langen (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- with amended claims (Art. 19(1))

(54) Title: EXHAUST GAS PURIFICATION SYSTEM FOR A GASOLINE ENGINE

(57) Abstract: Subject of the invention is an exhaust gas purification system for a gasoline engine, comprising in consecutive order the following devices: • a first three-way-catalyst (TWC1), a gasoline particulate filter (GPF) and a second three-way-catalyst (TWC2), • wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF, wherein the WCL is determined in g/l of the volume of the device. Also disclosed are methods in which the system is used and uses of the system.



Exhaust gas purification system for a gasoline engine

The invention relates to an exhaust gas purification system for a gasoline engine, comprising in consecutive order a first three-way-catalyst, a gasoline particulate filter and
5 a second three-way-catalyst. The invention also relates to methods and uses thereof.

State of the art

Exhaust gas from gasoline engines comprises pollutants which have to be removed before the exhaust gas is released into the environment. The most relevant pollutants in
10 this regard are nitrogen oxides (NO_x), hydrocarbons (HC or THC), carbon monoxide (CO) and particulate matter, especially soot. Other pollutants comprise sulfur oxides (SO_x) and volatile organic compounds (VOC). Such gaseous pollutants are removed from the exhaust gas by catalyst system and devices located downstream of the engine. Typically, such systems comprise a three-way catalyst (TWC), which is capable of removing nitric
15 oxides, hydrocarbons and carbon monoxide.

In recent years, there has been increasing attention on the removal of particulate matter, and especially soot, from exhaust gas from gasoline engines. For many years, soot particles were only removed from diesel engine exhaust gas. However, there is growing
20 evidence that also fine soot particles from gasoline engines can impair health. Therefore, there is a strong tendency to equip exhaust gas purification systems for gasoline engines with gasoline particulate filters (GPF). The GPF should efficiently reduce the particle mass (PM) and the particle number (PN) of the exhaust gas. In the European Union, the standard EURO 6 dated September 2014 defines for the first time maximum levels for
25 particulate matter of gasoline engines of passenger vehicles.

Presently, there are increasing demands by public authorities on manufacturers of vehicles and gasoline engines to improve exhaust gas purity. There is a worldwide trend towards lower legal thresholds for emission levels of such pollutants. Moreover, the
30 European Union plans to introduce obligatory tests for vehicles under real conditions with portable emissions measurement systems under the designation Real Driving Emissions

(RDE). Such demands exert high pressure on manufacturers to provide exhaust gas purification systems which fulfill all legal standards. In this regard, it is a known problem that the amount and ratio of exhaust gas pollutants can vary significantly depending on the operation conditions of the engine. Vehicle exhaust gas purification systems should be efficient under conditions as different as urban traffic, long-distance traffic, low or high velocity, cold or hot environment, and cautious or offensive driving.

It is another problem that a gasoline engine should have low fuel consumption in order to keep carbon dioxide emissions low. Carbon dioxide is considered to be the main cause of the greenhouse effect and global warming. Thus, attempts to increase exhaust gas purity should not negatively affect the performance of the gasoline engine.

It is a general problem that when a catalyst device, such as a TWC, is combined with a GPF in purifying exhaust gas from a gasoline engine, it is difficult to achieve an efficient depletion of all relevant pollutants whilst maintaining a high performance of the gasoline engine. The reason is that three different properties of the exhaust gas purification system, which are at least in part antagonistic, have to be brought into accordance with each other. Accordingly, the system should have high catalytic activity, high filtration efficiency and low pressure drop. High filtration efficiency is required for efficient removal of particles. High catalytic activity is required for efficient depletion of gaseous pollutants, such as HC, NO_x and CO. Low pressure drop is required for maintaining a high engine performance. In contrast, an increasing pressure drop tends to reduce the efficiency of the engine, which leads to higher fuel consumption and carbon dioxide emission.

It is a general problem that a GPF and catalytic devices require high temperatures for efficient operation. Therefore, they have to be operated close to the engine, which leads to dimensional limitations of the overall exhaust gas purification system. In order to increase the filtration efficiency or catalytic activity of an exhaust gas purification system, more catalyst material and filtration means are required. In the limited space of the catalytic system, this is generally associated with an increase of pressure drop in the GPF and in catalytic devices. The reason is that the exhaust gas is attenuated when passing filtering material and porous coatings in such devices. Consequently, the efficiency of the gasoline engine has to be reduced and more carbon dioxide is emitted for achieving a comparable performance. On the other hand, if the pressure drop is kept low, it is difficult

to achieve a good filtration efficiency and high catalytic activity in the limited space of the exhaust gas purification system.

Various attempts have been made in the prior art to provide gasoline engine purification systems, which overcome the above-mentioned problems. For example, various catalytic devices and gasoline particulate filters have been described, which are equipped with specific catalysts or combination of catalysts. In this regard, catalysts can be provided with special combinations of metals or catalyst layers. Other solutions focus on the internal structure or specific physical properties of such devices.

Further, exhaust gas purification systems with special arrangements of multiple devices have been proposed for increased efficiency. For example, DE 10 2015 212 514 A1 suggests a combination of two consecutive TWC and a GPF located downstream of the second TWC. WO 2010/052055 A1 also discloses a combination of a first TWC, a second downstream TWC and a GPF further downstream. It is a problem of such systems that when the terminal GPF is regenerated and the stored soot is burned, new pollutants such as CO and HC can be formed and emitted into the environment. It is another problem that the terminal GPF is located relatively far from the engine. Therefore, it cannot be heated rapidly and efficiently by the engine exhaust gas to achieve the optimal process temperature. Moreover, it is difficult to achieve the high regeneration temperature required for efficient soot burning, so an active regeneration has to be triggered. Generally, operation of a GPF at a low, non-optimal temperature reduces the efficiency and increases the amounts of residual pollutants. Therefore, the performance of such systems could still be improved.

WO 2017/004414 A1 discloses various systems for purifying exhaust gas from gasoline engines comprising N₂O removal catalysts. For example, an upstream TWC is coupled with downstream devices, such as a GPF and the N₂O removal catalyst. However, the terminal catalytic device is for N₂O removal and cannot efficiently remove pollutants formed in the upstream GPF, such as CO and CH. The data provided in the document also indicates that the overall performance could still be improved.

WO 2010/096641 A1 also discloses a combination of an upstream TWC which is close-coupled to a gasoline engine, a downstream particulate matter control device and a

downstream NO_x control system. However, the terminal catalytic device focusses on NO_x removal and cannot efficiently remove the most relevant pollutants from the upstream GPF, for example those which are formed during regeneration of the GPF. Overall, the performance of the system could still be improved.

5

Overall, there is a continuous need for providing exhaust gas purification systems for gasoline engines, which overcome the above-mentioned problems.

Problem underlying the invention

10 It is a problem underlying the invention to provide an exhaust gas purification system for gasoline engines which overcome the above-mentioned problems.

Specifically, an exhaust gas purification system for gasoline engines shall be provided, which efficiently removes the relevant pollutants, and especially NO_x, hydrocarbons (HC),
15 carbon monoxide and particulate matter, especially soot. The filtration efficiency for soot should be high with regard to particle mass as well as particle number. At the same time, the pressure drop of the system should be low, such that the engine can maintain a high performance and carbon dioxide emissions will not increase.

20 It is a special problem to provide an exhaust gas purification system for gasoline engines, which is efficient under various different operation conditions. Therefore, the level of pollutants shall be low also under RDE conditions.

Further, routine monitoring of the system by on board diagnosis (OBD system) should be
25 convenient and provide appropriate results.

It is a further problem underlying the invention to provide a system which has high purification efficiency, but is relatively simple and usable in standard automobile applications. The system should be relatively compact, stable and convenient to
30 manufacture and use.

Disclosure of the invention

Surprisingly, it was found that the problem underlying the invention is solved by an exhaust gas purification system according to the claims. Further embodiments of the invention are outlined throughout the description.

Subject of the invention is an exhaust gas purification system for a gasoline engine,
5 comprising in consecutive order the following devices:

a first three-way-catalyst (TWC1), a gasoline particulate filter (GPF) and a second three-way-catalyst (TWC2),

wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF, wherein the WCL is determined in g/l of the volume of the device.

10 The invention relates to an exhaust gas purification system for a gasoline engine. A gasoline engine is a combustion engine, which uses petrol (gasoline) as fuel. A gasoline engine is different from a diesel engine, which does not use spark ignition. Generally, exhaust gas emitted from gasoline engines has a different composition than exhaust gas from diesel engines and requires different exhaust gas purification systems.

15 Preferably, the engine uses gasoline direct injection (GDI), also known as petrol direct injection, because these engines are known for their improved fuel efficiency. Typically, the exhaust gas from such an engine comprises a relatively high number of relatively small soot particles. Especially for such an engine, it can be advantageous that the system is capable of efficient removal of soot particles.

20 The purification system comprises the three devices as outlined above. Typically, the devices are different units, which can be provided in separate housings. The devices can be connected by connection means, such as tubes and/or plugs. The three devices are arranged in consecutive order, such that the TWC1 is located upstream from the GPF, which is located upstream from the TWC2. The TWC1 is positioned downstream from the
25 gasoline engine. As used herein, the terms "upstream" and "downstream" refer to the directions of the flow of the engine exhaust gas stream from the engine towards the exhaust pipe, with the engine in an upstream location and the exhaust pipe downstream.

The exhaust gas purification system comprises at least the three purification devices TWC1, GPF and TWC2. In a preferred embodiment, the system does not comprise other
30 purification devices, especially not additional catalytic devices. More preferably, the system does not comprise another TWC, another GPF and/or another pollutant removal

device, such as a separate NO_x removal device or the like. According to the invention, it was found that efficient exhaust gas purification is possible only with the three devices in the order described herein.

5 In another embodiment, the system comprises additional devices which participate in pollutant removal. In one embodiment, at least one additional catalyst device may be present. In another embodiment, at least one additional non-catalytic device may be present.

A TWC comprises a three way catalyst coating which is coated on a flow-through substrate. The term "three-way" refers to the function of three-way conversion, where
10 hydrocarbons, carbon monoxide, and nitrogen oxides are substantially simultaneously converted. Three-way-catalysts (TWC) are known and widely used in the art. A gasoline engine typically operates under near stoichiometric reaction conditions that oscillate or are perturbed slightly between fuel-rich and fuel-lean air to fuel ratios (A/F ratios) ($\lambda = 1 \pm \sim 0.01$), at perturbation frequencies of 0.5 Hz to 2 Hz. This mode of operation is also
15 referred to as "perturbated stoichiometric" reaction conditions. TWC catalysts include oxygen storage materials (OSM) such as ceria that have multi-valent states which allows oxygen to be held and released under varying air to fuel ratios. Under rich conditions, when NO_x is being reduced, the oxygen storage capacity (OSC) provides a small amount of oxygen to consume unreacted CO and HC. Likewise, under lean conditions when CO
20 and HC are being oxidized, the OSM reacts with excess oxygen and/or NO_x. As a result, even in the presence of an atmosphere that oscillates between fuel-rich and fuel-lean air to fuel ratios, there is conversion of HC, CO, and NO_x all at the same (or at essentially all the same) time. Typically, a TWC catalyst comprises one or more platinum group metals such as palladium and/or rhodium and optionally platinum; an oxygen storage component;
25 and optionally promoters and/or stabilizers. Under rich conditions, TWC catalysts may generate ammonia.

The term "platinum group metal" refers to the six platinum-group metals ruthenium, rhodium, palladium, osmium, iridium, and platinum.

A "gasoline particulate filter" (GPF) is a device for removing particulate matter, especially
30 soot, from exhaust gas. The GPF is a wall-flow filter. In such a device, the exhaust gas passes the filter walls inside the device, whereas the particles are not capable of passing the filter walls and accumulate inside the device. Typically, the filters comprise multiple

parallel gas-flow channels. A plurality of first channels is open at the upstream side from which the exhaust gas streams into the channels, and closed at the opposite end in flow direction. The exhaust gas enters the first channels, passes the filter walls and enters adjacent second channels, whereas the particles remain trapped in the first channels. The second channels are closed at the upstream end and open at the opposite end downstream in flow direction, such that the exhaust gas exits the GPF.

Typically, the GPF comprises a catalytically active coating, typically a TWC coating. Thereby, the overall catalytic efficiency of the overall system can be enhanced and the performance can be increased. Typically, inner surfaces of the GPF, preferably all inner surfaces, are coated with a catalyst coating. Thus, inner walls of the filter channels or at least portions thereof comprise a catalyst coating, such that the exhaust gas which passes the filter walls also flows through the porous catalyst coating. Typically, the catalytic coating is located inside the porous filter walls, or onto the filter walls, or both, inside and onto the filter walls. Thereby, the GPF can filter off particles, and at the same time removes gaseous pollutants by catalytic chemical reaction. The catalyst may also support removal of particles, especially during regeneration.

A "wash coat" (WC) is a thin, adherent coating of a catalytic or other material applied to a carrier substrate. The carrier substrate can be a honeycomb flow through monolith substrate or a filter substrate, which is sufficiently porous to permit the passage of the gas stream being treated. A "wash coat layer" is defined as a coating that comprises support particles. A catalyzed wash coat comprises additional catalytic components. The wash coats of the TWC1 and TWC2 of the system are catalytic washcoats. Further, it is preferred that the GPF comprises a catalytic washcoat.

According to this application, the wash coat load is determined in g/l, wherein the weight in gram corresponds to all solids in the wash coat, whereas the volume is the total volume of the device, and not only the void volume of the device in the channels.

A "carrier" is a support, typically a monolithic substrate, examples of which include, but are not limited to, honeycomb flow-through substrates for the TWC and wall-flow filter substrates for the GPF. A "monolithic substrate" is a unitary structure that is homogeneous and continuous and has not been formed by affixing separate substrate pieces together. Typically, the carrier is coated with a wash coat comprising the catalyst.

An "OSM" refers to an oxygen storage material, which is an entity that has multivalent oxidation states and can actively react with oxidants such as oxygen or nitric oxide (NO₂) under oxidative conditions, or reacts with reductants such as carbon monoxide (CO) or hydrogen under reduction conditions. Examples of suitable oxygen storage materials include ceria or praseodymia. Delivery of an OSM to the wash coat layer can be achieved by the use of, for example, mixed oxides. For example, ceria can be delivered as an oxide of cerium and/or zirconium and mixtures thereof, and/or a mixed oxide of cerium, zirconium, and further dopants like rare earth elements, like Nd, Pr or Y.

As used herein, the "volume" of a device, such as a TWC or GPF, is the total volume of the device defined by its outer dimensions. Thus, the volume is not only the void volume within the channels or within the porous structure of the device.

Preferably, the OSC is determined in fresh condition. The presence or absence of oxygen storage capacity (OSC) can be determined by a jump test. Thereby, the OSC in mg/L of a catalyst or system that is located between two λ -sensors is calculated by the time offset of the two sensor signals that is occurring after air-to-fuel ratio jumps (e.g. between λ 0.95-1.05; see for example "Autoabgaskatalysatoren, Grundlagen – Herstellung – Entwicklung – Recycling – Ökologie", Christian Hagelüken, 2nd ed. 2005, page 62). The catalyst is in fresh condition when it is put into use after manufacture.

Typically, the catalytic performance changes during operation and its performance may decrease. This phenomenon is known as aging. Thus, it is preferred that the general catalyst performance is determined in aged condition, as it is required by legislation.

According to the invention, the system comprises a TWC1, a GPF and a TWC2 in consecutive order. Such an arrangement of these three devices confers various advantages to the inventive system.

It is an advantage of the system that the GPF can be positioned relatively close to the engine. Generally, GPFs require a relatively high temperature for optimal performance and efficient regeneration. When the engine is started, the GPF is heated by the exhaust gas stream. When the GPF is located close to the engine, it is heated faster and achieves the high, optimal operation temperature earlier. The time window in which the filter is not operated efficiently is relatively small. In conventional systems, in which the GPF is a terminal device and/or located further away from the engine, more time is required for

achieving the operation temperature for efficient three-way catalyst activity and soot oxidation.

Moreover, a GPF must be regenerated actively at defined time intervals if it is located too far from the engine and therefore does not reach the temperature that is required for soot burning. During regeneration, accumulated soot is burned at high temperature. If the required temperature cannot be reached, the soot may not be burned completely and undesired side products, such as CO and hydrocarbons, can be formed in the regeneration process. Therefore, it is advantageous for efficient regeneration that the GPF is located relatively close to the engine.

It is another advantage of the system that the partially purified exhaust gas, which is released from the GPF, can be subjected to further purification by the downstream second TWC (TWC2). In known systems, the GPF is often the terminal purification device for final removal of particles from pre-purified exhaust gas. When the GPF is regenerated, the soot is oxidized and impurities, such as carbon monoxide (CO) or hydrocarbons (CH), can be formed. With a conventional system comprising a terminal GPF, pollutants formed during regeneration are released into the environment. According to the invention, the pre-purified exhaust gas from the GPF is subjected to downstream purification in the TWC2. Thereby, residual impurities which pass the GPF or which are formed in the GPF can be removed or at least significantly reduced. The terminal TWC2 can ensure a final catalytic purification, which can function as a finishing step in the overall purification process.

It is a further advantage of the system that the TWC2 is located at a position distant from the engine. It is a known problem in the technical field that catalytic devices, such as TWCs, undergo aging during use. Aging means that the activity and performance of the catalyst changes over lifetime, and usually tends to decrease. Generally, aging occurs more rapidly at high temperature. In the inventive system, the TWC2 is positioned relatively far from the engine, which has the consequence that less heat is transferred to the TWC2 than to the upstream devices during use. Therefore, the aging process of the TWC2 is comparably slow and the catalyst can maintain its efficiency and performance for a prolonged time. This can be advantageous for long-time use, especially when emissions are monitored under RDE conditions. On the other hand, since the TWC2 is only the final catalyst for removing residual pollutants from the pre-purified exhaust gas, it can be acceptable that its performance may not be optimal at certain time intervals due to its position relatively far from the engine. The terminal downstream TWC2 can still efficiently

clean up the relatively small amounts of residual pollutants, even at times when its temperature should not be as high as required for optimal function.

Overall, the system with the special arrangement of the TWC1, GPF and TWC2 allows highly efficient removal of gaseous and particulate pollutants from gasoline engine exhaust gas during standard use and for a prolonged time.

In a preferred embodiment, the platinum-group metal concentration (PGM) of the GPF is at least 40% greater than the PGM of the TWC2. According to the present application, the PGM is determined in g/ft³ of the volume of the device. It can be advantageous that an efficient overall purification can be achieved with the inventive system, although the PGM, and thus concomitant catalytic efficiency based on platinum group metals, of the second TWC (TWC2) can be relatively low. In this regard, the terminal TWC2 can efficiently remove the residual pollutants from the pre-purified exhaust gas from the GPF, although the amount of precious metal in the TWC2 is relatively low. Overall, an efficient purification of the exhaust gas can be achieved with a relatively moderate total amount of precious metal in the system. This is advantageous for practical applications, because the precious metals are the main cause that catalyst systems are very expensive.

Generally, it is preferred that the GPF comprises a catalyst coating, preferably a TWC coating. This can be advantageous, because the GPF can then support the removal of gaseous pollutants by the system. Thereby, the limited space in the system can be used more efficiently compared to a GPF without a catalyst coating. Further, the catalyst coating can support oxidation of particles.

In a preferred embodiment, the ratio of the platinum-group metal concentration (PGM) of the TWC1 to the PGM of the GPF is from 1.1 to 10, preferably from 1.25 to 9, more preferably from 1.45 to 5, wherein the PGM is determined in g/ft³ of the volume of the device. This can be advantageous, because the TWC1 is located closer to the gasoline engine than the GPF. Thus, the TWC1 can reach the high temperature required for optimal catalytic performance more rapidly and for longer time periods. Due to the higher temperature, the catalytic performance of the TWC1 can be higher than that of the GPF especially under non-optimal operating conditions. For this reason, it can be advantageous to equip the TWC1 with a higher catalyst concentration than the GPF, such that a large portion of the gaseous pollutants is already removed in the TWC1.

Further, it can be advantageous that the platinum-group metal concentration (PGM) of the GPF is lower than in the TWC1, because the GPF has to be equipped with less wash coat. As a result, the pressure drop in the GPF can be kept relatively low. Since the exhaust gas stream has to pass the filter walls in the GPF, control of the pressure drop is important, such that the performance of the engine is not impaired. Overall, due to the optimal distribution of PGM between the devices of the system, the overall amount of precious metals in the system can be kept relatively low, whilst a high exhaust gas purification efficiency and high engine performance is achieved.

In a preferred embodiment, the platinum-group metal concentration (PGM) of the TWC1 is at least 40% greater than the PGM of the GPF, wherein the PGM is determined in g/ft³ of the volume of the device. In this embodiment, especially under non-optimal operating conditions, it can be advantageous that the catalytic performance of the TWC1 can be adjusted relatively high, whereas the pressure drop of the GPF can be kept relatively low such that a good engine performance can be maintained.

In a preferred embodiment, the platinum-group metal concentration (PGM) of the TWC1 is greater than the sum of the PGM of the GPF and TWC2, wherein the PGM is determined in g/ft³ of the volume of the device. When the PGM of the TWC1 is adjusted accordingly, the overall system can especially have a high catalytic efficiency under non-optimal conditions. Since the TWC1 is located closer to the engine than the GPF and TWC2, it can reach its optimal high operating temperature more rapidly and for longer time periods, and has a higher relative catalytic performance. Therefore, it can be advantageous that a relatively high portion of the overall catalytic activity of the total system is concentrated in the TWC1, whilst a significantly lower portion of the catalytic activity is located in the GPF and TWC2. Overall, this can be acceptable, because the GPF is in contact with the pre-purified exhaust gas from the TWC1, which comprises significantly less gaseous pollutants than the original exhaust gas. Moreover, the TWC2 is only in contact with the pre-purified exhaust gas from the GPF, which only comprises residual, relatively small amounts of gaseous pollutants. Overall, a system can be provided in which the PGM is distributed between the three devices, such that gaseous and particulate pollutants are efficiently removed whilst the pressure drop is kept low and engine performance is maintained.

In a preferred embodiment, the total amount of platinum-group metal of the TWC1 is from 1 g to 15 g, preferably from 2 g to 10 g. In a preferred embodiment, the total amount of

platinum-group metal of the GPF is from 0 g to 5 g, preferably from 0.05 g to 5g, more preferably from 1 g to 3 g. In a preferred embodiment, the total amount of platinum-group metal of the TWC2 is from 0.1 g to 2 g, preferably from 0.2 g to 1.5 g. Overall, an efficient removal of pollutants with minimum PGM costs can be achieved with the system when the
5 total amount of platinum group metal is adjusted and distributed accordingly.

In a preferred embodiment, the TWC1 comprises palladium and/or rhodium. In a preferred embodiment, the GPF comprises palladium, platinum, rhodium or mixtures thereof. Rhodium is especially efficient in removing NO_x, whereas palladium is especially efficient in removing CO. Therefore, the use of these metals in these devices can be
10 advantageous for efficient overall removal of pollutants from the exhaust gas.

In a preferred embodiment, the percentage of rhodium of the total amount of platinum-group metal of the GPF is at least 10 wt.%, more preferably at least 20 wt.%. This can be advantageous for efficiently removing NO_x in the GPF.

In a preferred embodiment, the TWC2 comprises rhodium. In a preferred embodiment, the
15 percentage of rhodium of the total amount of platinum-group metal of the TWC2 is at least 15 wt.%, more preferably at least 25 wt.%. It can be advantageous that the TWC2 comprises rhodium in such amounts in order to remove NO_x, but also other impurities, such as CO, from the pre-purified exhaust gas, which is emitted from or not converted by the GPF.

In a preferred embodiment, the TWC2 does not comprise platinum. It can be
20 advantageous that the use of expensive platinum can be avoided in the TWC2, whilst an overall efficient removal of pollutants can be achieved.

According to the invention, the wash coat load (WCL) of the TWC2 is greater than the
25 WCL of the GPF, wherein the WCL is determined in g/l of the volume of the device.

Generally, a high WCL in the GPF can lead to a high pressure drop, because the exhaust gas has to pass the inner filter walls of the GPF and the catalytic wash coat on the filter walls. According to the invention, it can be advantageous that the WCL of the GPF is relatively low, because the pressure drop of the GPF, and therefore of the whole exhaust
30 gas purification system, can be kept low. In contrast, the exhaust gas usually does not traverse the filter walls of a three way catalyst device. Thus, additional wash coat in the

TWC2 will generally not provide a comparable decrease of pressure drop as in the GPF. However, it is preferred that the GPF is provided with a wash coat having catalytic activity. Overall, an efficient overall system can be provided having high catalytic efficiency and low pressure drop.

- 5 Further, a significant WCL of the TWC2 can be advantageous, because it can provide an efficient removal of all residual pollutants from the pre-purified exhaust gas not converted by or emitted from the GPF, especially when the GPF is regenerated. Thus, the overall system can provide an efficient removal of pollutants.

10 Even further, the TWC2 is located relatively far from the gasoline engine. Thus, the TWC2 is subjected to and frequently operated at lower temperatures than the other upstream devices. Consequently, the TWC2 is less affected by aging and concomitant deterioration of catalyst performance. Thus, since the catalytic efficiency of the TWC2 can be relatively stable, it can be advantageous to provide the TWC2 with a relatively high amount of wash coat.

- 15 In a preferred embodiment, the wash coat load (WCL) of the TWC2 is from 100 g/l to 300 g/l, preferably from 150 g/l to 280 g/l, more preferably from 175 g/l to 260 g/l. When the WCL of the TWC2 is adjusted accordingly, a relatively good overall removal of pollutants with the catalytic system is possible. Overall, the catalyst is used efficiently, because the TWC2 is located far away from the engine and less affected by aging than
20 the GPF or TWC1. Further, such amounts of wash coat are suitable for providing an effective finishing of the pre-purified exhaust gas emitted from the GPF, whereby residual pollutants are removed.

In a preferred embodiment, the wash coat load (WCL) of the GPF is from 0 g/l to 150 g/l, preferably from 30 g/l to 130 g/l, more preferably from 50 g/l to 110 g/l. When adapting the
25 WCL of the GPF in such relatively low ranges, the pressure drop can be adjusted to be low. Further, the overall amount of catalyst in the system can be kept relatively low. The GPF, which is coated with a relatively low amount of wash coat, can efficiently remove residual pollutants from the TWC1, which comprises a relatively high WCL.

In a preferred embodiment, the wash coat load (WCL) of the TWC1 is from 150 g/l to
30 350 g/l, preferably from 180 g/l to 310 g/l, more preferably from 200 g/l to 280 g/l. When the WCL of the TWC1 is used in such relatively high amounts, a good combination of high catalytic performance of the TWC1 with efficient removal of residual pollutants by the GPF

and TWC2 is provided. It is also advantageous that the WCL of the TWC1 is adjusted within these relatively high ranges, because the TWC1 is located closest to the gasoline engine. Thus, it is heated more rapidly than the downstream devices and achieves the high optimal operation temperature more often and for longer time periods. Further, a high
5 WCL typically confers higher aging stability to the TWC1, which is especially advantageous when the TWC1 is closed coupled to the engine and thus operated at higher temperatures. Therefore, a relatively high wash coat load of the TWC1 can be advantageous for an effective initial and also total removal of pollutants. Overall, by adapting the WCL of the devices accordingly, an efficient use of total catalyst can be
10 adjusted.

Further, a relatively high catalytic efficiency of the TWC1 can be advantageous for diagnosis capability. Especially during on-board diagnosis, the catalytic performance is commonly carried out by monitoring the first catalytic device in the system. When the wash coat load and catalytic performance of the TWC1 is relatively high, on-board
15 diagnosis can provide relatively good results in approximation when monitoring only the TWC1. Thereby, a relatively good correlation of the diagnosis result with real driving emissions is possible.

In a preferred embodiment, the wash coat load (WCL) of the TWC1 is greater than the WCL of the TWC2, wherein the WCL is determined in g/l of the volume of the device. This
20 can be advantageous, because the upstream TWC1, which is located close to the gasoline engine, can be operated more efficiently and more often at a high temperature and achieves a greater catalytic efficiency at high operation temperature. Since the TWC2 only removes residual pollutants, it is appropriate that the WCL is lower than of the TWC1. However, it can be advantageous that a downstream TWC2 is present, which removes
25 pollutants from the TWC1 and GPF, and which is less affected by aging than the TWC1. In the overall system, it can be advantageous that on-board diagnosis can be performed with the TWC1 and provides a reasonable correlation to total emissions. Overall, the TWC1 and TWC2 complement each other in the system and provide, together with the GPF between them, an unexpected combination of high filtration efficiency, high catalytic
30 efficiency and low pressure drop.

In one embodiment, the wash coat of the TWC1 is the same as for the TWC2. This means that the oxides comprised and concentrations thereof are the same in both wash coats. In another embodiment, the TWC1 and TWC2 comprise different wash coats.

TWC catalysts include oxygen storage materials (OSM) such as ceria that have multi-valent states which allows oxygen to be held and released under varying air to fuel ratios. Under rich conditions, when NO_x is being reduced, the OSM provides a small amount of oxygen to consume unreacted CO and HC. Likewise, under lean conditions when CO and HC are being oxidized, the OSM reacts with excess oxygen and/or NO_x . As a result, even in the presence of an atmosphere that oscillates between fuel-rich and fuel-lean air to fuel ratios, there is conversion of HC, CO, and NO_x all at the same (or at essentially all the same) time.

In a preferred embodiment, the oxygen storage capacity (OSC) of the GPF is higher than the OSC of the TWC2, wherein the OSC is determined in mg/l of the volume of the device in fresh state. This can be advantageous, because the GPF is located closer to the gasoline engine. Therefore, the GPF reaches the required high temperature for optimal performance more rapidly and for longer time intervals than the TWC2. The relatively high OSC in the GPF can support and mediate the relatively efficient catalytic reaction in the GPF. In contrast, a relatively low OSC in the terminal TWC2, which is located further away from the engine and does not achieve a high temperature as readily, can nonetheless be sufficient for removing the relative small amounts of residual pollutants, which are emitted from the GPF. Overall, the distribution of the OSC in the system provides an efficient overall removal of pollutants.

Further, a relatively high OSC of the GPF compared to the TWC2 can be advantageous when the engine is operated alternately under rich operation conditions with $\lambda < 1$ and lean operation conditions with $\lambda > 1$ for short intervals of time. Such an operation mode is known as wobbling or as wobble operation. In a wobbling mode, a high OSC can be advantageous, because oxygen can be efficiently stored under lean operation conditions and released under rich operation conditions. Accordingly, a higher OSC in the GPF supports an efficient overall removal of pollutants under such conditions. In contrast, a high OSC of the TWC2 is less relevant for operation under wobble conditions, because the major portion of the pollutants was already removed in the TWC1 and GPF, such that the absolute concentrations of the residual pollutants which enter the TWC2 are comparably low.

In a preferred embodiment, the oxygen storage capacity (OSC) of the TWC1 is higher than the OSC of the GPF, wherein the OSC is determined in mg/l of the volume of the device in fresh state. In a preferred embodiment, the OSC of the TWC1 is at least 40% greater than the OSC of the GPF. A higher OSC of the TWC1 can be advantageous, because it can support a relatively high catalytic efficiency of the TWC1. The TWC1 is located closest to the gasoline engine and thus is operated more frequently at optimal high temperature than the downstream GPF, and especially than the even more remote TWC2. Therefore, an efficient catalytic reaction can occur more easily and more frequently in the TWC1 than in the downstream devices. In the overall system, it can be generally advantageous if a relatively high catalytic turnover is mediated by the TWC1. Then, residual pollutants emitted from the TWC1 can be removed by the downstream devices, which can have a lower OSC.

Moreover, a relatively high OSC of the TWC1 can be advantageous when the engine is operated alternately under rich operation conditions with $\lambda < 1$ and lean operation conditions with $\lambda > 1$ for short intervals of time. Such an operation mode is known as wobbling or as wobble operation. In a wobbling mode, a high OSC can be advantageous, because oxygen can be efficiently stored under lean operation conditions and released into the reaction under rich operation conditions. Accordingly, a high OSC in the TWC1 supports an efficient overall removal of pollutants under such conditions. In contrast, a high OSC of the GPF is less relevant for operation under wobble conditions, because the major portion of the pollutants was already removed in the TWC1, such that the absolute concentrations of the pollutants are comparably low in the GPF.

Even further, a high OSC in the TWC1 can be advantageous for efficient removal of NO_x under lean operation conditions. A TWC1 having a high OSC can bind a large amount of oxygen under lean operation conditions. If the OSC would be too low, too much unbound oxygen can be present under lean conditions, and the reduction of NO_x to N_2 can be impaired.

Further, a high OSC of the TWC1 can be advantageous for diagnosis capability. Especially on-board diagnosis is commonly carried out with the first catalytic device. When the upstream TWC1 has a high OSC, the result of on-board diagnosis at the TWC1 will provide a reasonable indication of final emissions or real driving emissions (RDE).

In a preferred embodiment, the oxygen storage capacity (OSC) of the TWC1 in fresh state is from 400 mg to 1250 mg, preferably from 500 mg to 900 mg. This can be advantageous, because a high catalytic efficiency can be achieved at the TWC1 when the OSC is adjusted accordingly. As outlined above, this can be advantageous for overall catalytic efficiency, operation in the wobbling mode and diagnosis capability.

In a preferred embodiment, the ratio $V_{\text{cat}} / V_{\text{eng}}$ is at least 1, wherein V_{cat} is the total catalyst volume of all devices and V_{eng} is the engine displacement of the gasoline engine. Thus, the total catalyst volume is at least the sum of the volumes of the TWC1, TWC2 and GPF. As used herein, the catalyst volume of a device is the overall volume, and not only the internal void volume. A ratio of 1 or more is advantageous, because a relatively high catalyst volume of all devices can provide a high catalytic performance. The volume of the engine can approximately be correlated to the amount of exhaust gas emitted during operation. If the total catalyst volume would be smaller than the engine volume, the efficiency of the exhaust gas purification system can be too low, especially under high mass flows that are observed under real driving conditions. In order to achieve a high catalytic efficiency, a relatively high catalyst concentration may then have to be provided in the catalytic devices, which could lead to an undesired increase of the pressure drop.

In a preferred embodiment, the ratio $V_{\text{cat}} / V_{\text{eng}}$ is from 1 to 5, preferably from 1.1 to 4, more preferably from 1.2 to 3.5. If the catalyst volume would be higher, the heat transfer from the gasoline engine to the catalytic devices could become insufficient. Generally, an efficient heat transfer from the gasoline engine to the downstream catalytic devices is required, such that the devices can attain the optimal high operation temperature. Typically, such catalytic devices are operated at a temperature of several hundred degrees Celsius for an optimal performance and catalytic conversion. If the temperature is below the optimal temperature, the catalytic turnover can be decreased. Further, a compact integration of the catalytic system into a vehicle is difficult, when the total catalytic volume is too high.

In a preferred embodiment, the volume of the TWC1 (V_{TWC1}) is from 20% to 50%, preferably from 30% to 40%, of the total catalyst volume V_{cat} . In this embodiment, it is preferred that the volume of the TWC1 is larger than the volume of the TWC2. Overall, a relatively high volume of the TWC1 can be advantageous, because the TWC1 can be

provided with a relatively high catalytic efficiency. Accordingly, a major portion of the gaseous pollutants from the gasoline engine can be removed in the TWC1, which is located relatively close to the engine and attains a relatively high temperature more easily and frequently. This is especially advantageous for efficient removal of pollutants under
5 dynamic driving conditions, for example in urban traffic or after a cold start of the engine. Further, diagnosis capability, especially for on-board diagnosis of catalytic efficiency, is usually carried out at the upstream device, in this case the TWC1. Therefore, a high efficiency of the TWC1 allows relatively good monitoring of the overall catalytic efficiency.

In a preferred embodiment, the volume of the GPF (V_{GPF}) is from 30% to 60%, preferably
10 from 40% to 55%, of the total catalyst volume V_{cat} . In a specific embodiment, the total volume of the GPF is larger than the total volume of the TWC1 and/or of the TWC2. A relatively high volume of the GPF can be advantageous, because a relatively high volume can be associated with a relatively low pressure drop. If the volume of the GPF would be too low, the pressure drop could increase, which could yield to inefficient operation of the
15 engine and increased carbon dioxide emissions. A relatively high volume of the GPF can be especially advantageous, if the GPF is a catalytic GPF, which is provided with a catalyst wash coat, preferably a TWC washcoat, which reduces the void volume in the device through which the exhaust gas can flow. A relatively high volume of the GPF can also be advantageous for efficient storage of particles and for efficient regeneration, when
20 accumulated soot particles are removed under oxidizing conditions.

In a preferred embodiment, the volume of the TWC2 (V_{TWC2}) is from 10% to 40%, preferably from 15% to 35%, of the total catalyst volume V_{cat} . A lower volume of the TWC2, when compared to the TWC1 and/or GPF, can be advantageous, because removal of residual pollutants from the GPF may require less catalyst and thus catalyst
25 volume in the TWC2. Therefore, an efficient overall system can be provided at relatively low costs and with favourable distribution of catalyst throughout the three devices.

In a preferred embodiment, the ratio of the smallest diameter of the GPF to the length of the GPF is from 0.7 to 3, preferably from 0.75 to 1.6. When the dimensions of the GPF are adjusted accordingly, a relatively efficient particle filtration and catalyst performance could
30 be achieved while maintaining a relatively low backpressure.

In a highly preferred embodiment, the system comprises a turbocharger positioned upstream from the TWC1. A turbocharger is a turbine-driven forced induction device that

increases an internal combustion engine's efficiency and power output by forcing extra air into the combustion chamber. Therefore, a more efficient exhaust gas purification system can be required if a turbocharger is present. The highly efficient inventive catalytic system is especially suitable for purifying exhaust gas from a gasoline engine and a turbocharger.

5 Preferably, the turbocharger is the only additional device between the gasoline engine and the TWC1.

Preferably, the distance from the outlet surface of the turbocharger to the inlet surface of the TWC1 is from 1 cm to 40 cm, preferably from 2 cm to 30 cm, more preferably from 2 cm to 20 cm. Preferably, the distance is less than 10 cm or less than 5 cm. When the
10 dimensions of the turbocharger and TWC1 are adapted accordingly, a close-coupled operation of the TWC1 with the gasoline engine is possible. Then, heat can be transferred more rapidly and efficiently from the engine to the TWC1 and downstream catalyst devices. This can be advantageous, because the catalytic reaction in the TWC1 and downstream devices is generally more efficient at high temperature. Further, rapid heat
15 transfer supports an efficient catalytic reaction after cold-start and under dynamic driving conditions, for example in urban traffic. Moreover, a close-coupled system can be integrated directly in the space behind the gasoline engine. Accordingly, it is not necessary to integrate the TWC1, or downstream catalytic devices which are also close-coupled, into the underbody of a vehicle. Thereby, a compact integrated catalyst system
20 can be provided. Further, close-coupling of the TWC1 and the GPF to the engine generally can also provide a higher catalytic efficiency of the GPF and more efficient regeneration of the GPF.

In a preferred embodiment, the distance of the outlet surface of the TWC1 to the inlet surface of the GPF is from 1 cm to 60 cm, preferably from 2 cm to 50 cm, more preferably
25 from 3 cm to 40 cm. Preferably, the distance is less than 20 cm or less than 10 cm. When keeping the distance between the TWC1 and GPF relatively short, a close-coupled connection of the GPF with the gasoline engine is possible. Thereby, heat can be transferred more efficiently and rapidly into the GPF, but also the downstream TWC2. Further, the GPF can be integrated more compactly into a vehicle. Further, the catalyst
30 system can be regenerated more efficiently at high temperature and can have a higher catalytic turnover.

In a preferred embodiment, the distance of the outlet surface of the GPF to the inlet surface of the TWC2 is from 0 cm to 120 cm, preferably from 1 cm to 110 cm, more

preferably from 2 cm to 100 cm. Preferably, the distance is less than 20 cm or less than 10 cm. Thereby, a close-coupled system is obtainable with additional advantages as described above. Overall, it is preferred that all devices of the system are close-coupled to each other and to the gasoline engine.

- 5 In a preferred embodiment, the TWC1 comprises at least two different wash coat layers. In a further preferred embodiment, the TWC2 comprises one or two different wash coat layers. Preferably, the wash coat layers are laid over each other. In a preferred embodiment, different wash coat layers can be located at different surfaces of the porous walls of the GPF. When combining different wash coat layers, catalytic coatings can be
10 combined which have different catalytic efficiency, resulting in an overall system which is effective in removing different fractions of pollutants.

- In a further embodiment, the catalytic efficiency of the TWC1 is greater than that of the GPF with regard to removal of NO_x, CO and/or hydrocarbons, when performance of the GPF is determined under the same conditions as for the TWC1. This means that the
15 performance of the GPF is determined without the upstream TWC1. This can be advantageous, because the TWC1 is closer to the engine and can be operated more efficiently at a higher temperature. Further, a high wash coat load in the TWC1 affects pressure drop less significantly than high wash coat load in the GPF, because the exhaust gas in the TWC1 does not have to traverse monolith filter walls.

- 20 In a further embodiment, the catalytic performance of the GPF is greater than that of the TWC2 with regard to removal of NO_x, CO and/or hydrocarbons, when performance of the TWC2 is determined under the same conditions as for the GPF. This means that the performances of the GPF and TWC2 are determined without further upstream exhaust gas purification devices. This can be advantageous, because the levels of gaseous
25 pollutants in the GPF can be higher than in the pre-purified exhaust gas which enters the TWC2. Accordingly, relatively efficient removal of pollutants in the GPF can be combined with final removal of residual pollutants in the TWC2. Overall, a system can be provided with effective combination and adaptation of filtration efficiency, TWC efficiency and low pressure drop in the three devices, with a highly efficient distribution of the catalytic
30 material throughout the catalyst system.

Preferably, the purified exhaust gas emitted from the TWC2 comprises the following levels of pollutants (in mg/km):

CO: less than 1000, preferably less than 500, more preferably less than 300

THC: less than 100, preferably less than 50, more preferably less than 30

NO_x: less than 60, preferably less than 40, more preferably less than 30

PM: less than 0.005, preferably less than 0.002, more preferably less than 0.001

- 5 Preferably, the particle number (PN) is less than 6×10^{11} , preferably less than 5×10^{11} .

Preferably, these pollutant levels are determined according to the standard tests defined in EURO6, test cycle WLTP (see EU commission regulation 2007/715 and 2008/692 and regulations based thereon 2017/1151, 2017/134).

- 10 Subject of the invention is also a method for purifying exhaust gas emitted from a gasoline engine, comprising the steps of:

(a) providing a gasoline engine and an exhaust gas purification system of the invention, and

- 15 (b) passing exhaust gas emitted from the gasoline engine through the system, such that the exhaust gas is purified by the system.

As outlined above, method uses the exhaust gas purification system as described above, which is suitable for gasoline engines. It is adapted to the specific exhaust gas and pollutants emitted from gasoline engines, which is different than exhaust gas from diesel engines.

- 20 Subject of the invention is also the use of the inventive exhaust gas purification system for purifying exhaust gas from a gasoline engine.

The invention comprises the following embodiments:

1. An exhaust gas purification system for a gasoline engine, comprising in consecutive order the following devices:

a first three-way-catalyst (TWC1), a gasoline particulate filter (GPF) and a second
5 three-way-catalyst (TWC2),

wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF,
wherein the WCL is determined in g/l of the volume of the device.

2. The system according to the preceding embodiment, wherein the platinum-group metal concentration (PGM) of the GPF is at least 40% greater than the PGM of the
10 TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.

3. The system according to at least one of the preceding embodiments, wherein the ratio of the platinum-group metal concentration (PGM) of the TWC1 to the PGM of the GPF is from 1.1 to 10, preferably from 1.25 to 9, more preferably from 1.45 to 5, wherein the PGM is determined in g/ft³ of the volume of the device.

4. The system according to at least one of the preceding embodiments, wherein the platinum-group metal concentration (PGM) of the TWC1 is at least 40% greater than the PGM of the GPF, wherein the PGM is determined in g/ft³ of the volume of the device.

5. The system according to at least one of the preceding embodiments, wherein the
20 platinum-group metal concentration (PGM) of the TWC1 is greater than the sum of the PGM of the GPF and TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.

6. The system according to at least one of the preceding embodiments, wherein the total amount of platinum-group metal of the TWC1 is from 1 g to 15 g.

7. The system according to at least one of the preceding embodiments, wherein the total amount of platinum-group metal of the GPF is from 0 g to 5 g, preferably from 0.05 g to 5g.

8. The system according to at least one of the preceding embodiments, wherein the total amount of platinum-group metal of the TWC2 is from 0.1 g to 2 g.

9. The system according to at least one of the preceding embodiments, wherein the TWC1 comprises palladium and/or rhodium.
10. The system according to at least one of the preceding embodiments, wherein the GPF comprises palladium, platinum, rhodium or mixtures thereof.
- 5 11. The system according to at least one of the preceding embodiments, wherein the percentage of rhodium of the total amount of platinum-group metal of the GPF is at least 10 wt.%.
12. The system according to at least one of the preceding embodiments, wherein the TWC2 comprises rhodium.
- 10 13. The system according to at least one of the preceding embodiments, wherein the percentage of rhodium of the total amount of platinum-group metal of the TWC2 is at least 15 wt.%.
14. The system according to at least one of the preceding embodiments, wherein the TWC2 does not comprise platinum.
- 15 15. The system according to at least one of the preceding embodiments, wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF, wherein the WCL is determined in g/l of the volume of the device.
16. The system according to at least one of the preceding embodiments, wherein the wash coat load (WCL) of the TWC2 is from 100 g/l to 300 g/l, preferably from 150 g/l
20 to 280 g/l, more preferably from 175 g/l to 260 g/l.
17. The system according to at least one of the preceding embodiments, wherein the wash coat load (WCL) of the GPF is from 0 g/l to 150 g/l, preferably from 30 g/l to 130 g/l, more preferably from 50 g/l to 110 g/l.
18. The system according to at least one of the preceding embodiments, wherein the
25 wash coat load (WCL) of the TWC1 is from 150 g/l to 350 g/l, preferably from 180 g/l to 310 g/l, more preferably from 200 g/l to 280 g/l.
19. The system according to at least one of the preceding embodiments, wherein the wash coat load (WCL) of the TWC1 is greater than the WCL of the TWC2, wherein the WCL is determined in g/l of the volume of the device.

20. The system according to at least one of the preceding embodiments, wherein the oxygen storage capacity (OSC) of the GPF is greater than the OSC of the TWC2, wherein the OSC is determined in mg/l of the volume of the device.
21. The system according to at least one of the preceding embodiments, wherein the oxygen storage capacity (OSC) of the TWC1 is greater than the OSC of the GPF, wherein the OSC is determined in mg/l of the volume of the device.
22. The system according to at least one of the preceding embodiments, wherein the oxygen storage capacity (OSC) of the TWC1 is from 400 mg to 1250 mg, preferably from 500 mg to 900 mg.
23. The system according to at least one of the preceding embodiments, wherein the ratio $V_{\text{cat}} / V_{\text{eng}}$ is at least 1, wherein V_{cat} is the total catalyst volume of all devices and V_{eng} is the engine displacement of the gasoline engine.
24. The system according to at least one of the preceding embodiments, wherein the ratio $V_{\text{cat}} / V_{\text{eng}}$ is from 1 to 5, preferably from 1.1 to 4, more preferably from 1.2 to 3.5.
25. The system according to at least one of the preceding embodiments, wherein the volume of the TWC1 (V_{TWC1}) is from 20% to 50% of the total catalyst volume V_{cat} , preferably from 30% to 40%.
26. The system according to at least one of the preceding embodiments, wherein the volume of the GPF (V_{GPF}) is from 30% to 60% of the total catalyst volume V_{cat} , preferably from 40% to 55%.
27. The system according to at least one of the preceding embodiments, wherein the volume of the TWC2 (V_{TWC2}) is from 10% to 40% of the total catalyst volume V_{cat} , preferably from 15% to 35%.
28. The system according to at least one of the preceding embodiments, wherein the ratio of the smallest diameter of the GPF to the length of the GPF is from 0.7 to 3, preferably from 0.75 to 1.6.
29. The system according to at least one of the preceding embodiments, wherein the system comprising a turbocharger positioned upstream of the TWC1, wherein the distance of the outlet surface of the turbocharger to the inlet surface of the TWC1 is from 1 cm to 40 cm, preferably from 2 cm to 30 cm, more preferably from 2 cm to 20 cm.

30. The system according to at least one of the preceding embodiments, wherein the distance of the outlet surface of the TWC1 to the inlet surface of the GPF is from 1 cm to 60 cm, preferably from 2 cm to 50 cm, more preferably from 3 cm to 40 cm.
31. The system according to at least one of the preceding embodiments, wherein the distance of the outlet surface of the GPF to the inlet surface of the TWC2 is from 0 cm to 120 cm, preferably from 1 cm to 110 cm, more preferably from 2 cm to 100 cm.
32. The system according to at least one of the preceding embodiments, wherein the TWC1 comprises at least two different wash coat layers.
33. The system according to at least one of the preceding embodiments, wherein the TWC2 comprises one or two different wash coat layers.
34. The system according to at least one of the preceding embodiments, wherein the catalytic performance of the TWC1 is greater than that of the GPF with regard to removal of NO_x, CO and/or hydrocarbons, when performance of the GPF is determined under the same conditions as for the TWC1.
35. The system according to at least one of the preceding embodiments, wherein the catalytic performance of the GPF is greater than that of the TWC2 with regard to removal of NO_x, CO and/or hydrocarbons, when performance of the TWC2 is determined under the same conditions as for the GPF.
36. A method for purifying exhaust gas emitted from a gasoline engine, comprising the steps of:
- (a) providing a gasoline engine and an exhaust gas purification system of any of the preceding embodiments, and
 - (b) passing exhaust gas emitted from the gasoline engine through the system, such that the exhaust gas is purified in the system.
37. Use of an exhaust gas purification system of any of the preceding embodiments for purifying exhaust gas from a gasoline engine.

CLAIMS

1. An exhaust gas purification system for a gasoline engine, comprising in consecutive
5 order the following devices:

a first three-way-catalyst (TWC1), a gasoline particulate filter (GPF) and a second
three-way-catalyst (TWC2),

wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF,
wherein the WCL is determined in g/l of the volume of the device.
- 10 2. The system according to at least one of the preceding claims, wherein the platinum-
group metal concentration (PGM) of the GPF is at least 40% greater than the PGM of
the TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.
3. The system according to at least one of the preceding claims, wherein the ratio of the
platinum-group metal concentration (PGM) of the TWC1 to the PGM of the GPF is
15 from 1.1 to 10, preferably from 1.25 to 9, more preferably from 1.45 to 5, wherein the
PGM is determined in g/ft³ of the volume of the device.
4. The system according to at least one of the preceding claims, wherein the platinum-
group metal concentration (PGM) of the TWC1 is at least 40% greater than the PGM
of the GPF, wherein the PGM is determined in g/ft³ of the volume of the device.
- 20 5. The system according to at least one of the preceding claims, wherein the total
amount of platinum-group metal of the TWC2 is from 0.1 g to 2 g.
6. The system according to at least one of the preceding claims, wherein the GPF
comprises palladium, platinum, rhodium or mixtures thereof.
7. The system according to at least one of the preceding claims, wherein the percentage
25 of rhodium of the total amount of platinum-group metal of the GPF is at least 10 wt.%.
8. The system according to at least one of the preceding claims, wherein the TWC2
comprises rhodium,

wherein preferably the percentage of rhodium of the total amount of platinum-group
metal of the TWC2 is at least 15 wt.%.

9. The system according to at least one of the preceding claims, wherein the platinum-group metal concentration (PGM) of the TWC1 is greater than the sum of the PGM of the GPF and TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.

5 10. The system according to at least one of the preceding claims, wherein the wash coat load (WCL) of the TWC2 is from 100 g/l to 300 g/l, preferably from 150 g/l to 280 g/l, more preferably from 175 g/l to 260 g/l.

11. The system according to at least one of the preceding claims, wherein the wash coat load (WCL) of the GPF is from 0 g/l to 150 g/l, preferably from 30 g/l to 130 g/l, more
10 preferably from 50 g/l to 110 g/l, and/or

wherein the wash coat load (WCL) of the TWC1 is from 150 g/l to 350 g/l, preferably from 180 g/l to 310 g/l, more preferably from 200 g/l to 280 g/l.

12. The system according to at least one of the preceding claims, wherein the wash coat load (WCL) of the TWC1 is greater than the WCL of the TWC2, wherein the WCL is
15 determined in g/l of the volume of the device.

13. The system according to at least one of the preceding claims, wherein the oxygen storage capacity (OSC) of the GPF is greater than the OSC of the TWC2, wherein the OSC is determined in mg/l of the volume of the device.

14. The system according to at least one of the preceding claims, wherein the oxygen
20 storage capacity (OSC) of the TWC1 is greater than the OSC of the GPF, wherein the OSC is determined in mg/l of the volume of the device.

15. The system according to at least one of the preceding claims, wherein the oxygen storage capacity (OSC) of the TWC1 is from 400 mg to 1250 mg, preferably from 500 mg to 900 mg.

25

AMENDED CLAIMS
received by the International Bureau
on 06 February 2020 (06.02.2020)

1. An exhaust gas purification system for a gasoline engine, comprising in consecutive
5 order the following devices:
a first three-way-catalyst (TWC1), a gasoline particulate filter (GPF) and a second three-
way-catalyst (TWC2),
wherein the wash coat load (WCL) of the TWC2 is greater than the WCL of the GPF,
wherein the WCL is determined in g/l of the volume of the device, and
10 wherein the wash coat load (WCL) of the TWC1 is greater than the WCL of the TWC2,
wherein the WCL is determined in g/l of the volume of the device.
2. The system according to at least one of the preceding claims, wherein the platinum-
group metal concentration (PGM) of the GPF is at least 40% greater than the PGM of
the TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.
- 15 3. The system according to at least one of the preceding claims, wherein the ratio of the
platinum-group metal concentration (PGM) of the TWC1 to the PGM of the GPF is from
1.1 to 10, preferably from 1.25 to 9, more preferably from 1.45 to 5, wherein the PGM is
determined in g/ft³ of the volume of the device.
4. The system according to at least one of the preceding claims, wherein the platinum-
20 group metal concentration (PGM) of the TWC1 is at least 40% greater than the PGM of
the GPF, wherein the PGM is determined in g/ft³ of the volume of the device.
5. The system according to at least one of the preceding claims, wherein the total amount
of platinum-group metal of the TWC2 is from 0.1 g to 2 g.
6. The system according to at least one of the preceding claims, wherein the GPF
25 comprises palladium, platinum, rhodium or mixtures thereof.
7. The system according to at least one of the preceding claims, wherein the percentage
of rhodium of the total amount of platinum-group metal of the GPF is at least 10 wt.%.

8. The system according to at least one of the preceding claims, wherein the TWC2 comprises rhodium,

wherein preferably the percentage of rhodium of the total amount of platinum-group metal of the TWC2 is at least 15 wt.%.

5 9. The system according to at least one of the preceding claims, wherein the platinum-group metal concentration (PGM) of the TWC1 is greater than the sum of the PGM of the GPF and TWC2, wherein the PGM is determined in g/ft³ of the volume of the device.

10. The system according to at least one of the preceding claims, wherein the wash coat load (WCL) of the TWC2 is from 100 g/l to 300 g/l, preferably from 150 g/l to 280 g/l,
10 more preferably from 175 g/l to 260 g/l.

11. The system according to at least one of the preceding claims, wherein the wash coat load (WCL) of the GPF is from 0 g/l to 150 g/l, preferably from 30 g/l to 130 g/l, more preferably from 50 g/l to 110 g/l, and/or

wherein the wash coat load (WCL) of the TWC1 is from 150 g/l to 350 g/l, preferably
15 from 180 g/l to 310 g/l, more preferably from 200 g/l to 280 g/l.

12. The system according to at least one of the preceding claims, wherein the oxygen storage capacity (OSC) of the GPF is greater than the OSC of the TWC2, wherein the OSC is determined in mg/l of the volume of the device.

13. The system according to at least one of the preceding claims, wherein the oxygen
20 storage capacity (OSC) of the TWC1 is greater than the OSC of the GPF, wherein the OSC is determined in mg/l of the volume of the device.

14. The system according to at least one of the preceding claims, wherein the oxygen storage capacity (OSC) of the TWC1 is from 400 mg to 1250 mg, preferably from 500 mg to 900 mg.

25

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2019/078194

A. CLASSIFICATION OF SUBJECT MATTER

INV. B01J23/46 B01D53/94 F01N3/10 F01N3/035
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B01J B01D F01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 10 2013 018208 A1 (GM GLOBAL TECH OPERATIONS INC [US]) 30 April 2015 (2015-04-30) paragraphs [0001], [0005], [0008], [0011], [0019] - [0022] figure 1	1,4-6, 8-12,14, 15
X	JP 2010 048131 A (TOYOTA MOTOR CORP) 4 March 2010 (2010-03-04) paragraphs [0012], [0021] - [0024], [0036], [0040], [0107] - [0122] figures 1,2,7 ----- -/--	1,4-6, 8-12,14, 15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

13 December 2019

Date of mailing of the international search report

02/01/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Hackenberg, Stefan

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2019/078194

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2010/011749 A1 (FUJIWARA TAKAHIKO [JP] ET AL) 21 January 2010 (2010-01-21) paragraphs [0007] - [0010], [0019], [0021], [0072] - [0076], [0083], [0093] figure 1 -----	1-11,13, 15
A	JP 2015 025434 A (MITSUBISHI MOTORS CORP) 5 February 2015 (2015-02-05) paragraphs [0020] - [0025] figures 1,2 -----	1-15
A	US 2010/192543 A1 (FUJIWARA TAKAHIKO [JP] ET AL) 5 August 2010 (2010-08-05) paragraphs [0008], [0011], [0016], [0025] - [0028], [0034] figure 1 -----	1-15
A	DE 10 2010 046762 A1 (FORD GLOBAL TECH LLC [US]) 31 March 2011 (2011-03-31) paragraphs [0005], [0029], [0041], [0047], [0053], [0063] page 2c -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2019/078194

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 102013018208 A1	30-04-2015	NONE	
JP 2010048131 A	04-03-2010	JP 4893711 B2 JP 2010048131 A	07-03-2012 04-03-2010
US 2010011749 A1	21-01-2010	CN 101617106 A DE 112008000369 T5 JP 4710846 B2 JP 2008202523 A US 2010011749 A1 WO 2008102793 A1	30-12-2009 18-02-2010 29-06-2011 04-09-2008 21-01-2010 28-08-2008
JP 2015025434 A	05-02-2015	JP 6197993 B2 JP 2015025434 A	20-09-2017 05-02-2015
US 2010192543 A1	05-08-2010	CN 101868607 A EP 2217798 A2 JP 5061861 B2 JP 2009127458 A US 2010192543 A1 WO 2009066554 A2	20-10-2010 18-08-2010 31-10-2012 11-06-2009 05-08-2010 28-05-2009
DE 102010046762 A1	31-03-2011	CN 202039925 U DE 102010046762 A1 US 2011072784 A1	16-11-2011 31-03-2011 31-03-2011