



US 20050201880A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0201880 A1****Gentilin**(43) **Pub. Date:****Sep. 15, 2005**(54) **POSITIVE-DISPLACEMENT
RECIPROCATING COMPRESSOR****Publication Classification**(76) **Inventor:** **Giampaolo Gentilin, Trissino (VI) (IT)**(51) **Int. Cl.⁷** **F04B 1/12; F04B 17/00**(52) **U.S. Cl.** **417/521; 417/415**

Correspondence Address:

DYKEMA GOSSETT PLLC**FRANKLIN SQUARE, THIRD FLOOR WEST****1300 I STREET, NW****WASHINGTON, DC 20005 (US)**


(57)


ABSTRACT

A positive-displacement reciprocating compressor, comprising a plunger slidingly coupled inside a cylinder, in which a compression chamber is obtained, and operatively connected to driving means which put it in motion inside the cylinder. The driving means comprise a motor having the rotation shaft coupled with eccentric means mechanically connected to the plunger and able to impose longitudinal displacements to the plunger according to an orthogonal direction with respect to the rotation axis of the shaft.

(21) **Appl. No.:** **11/061,644**(22) **Filed:** **Feb. 22, 2005**(30) **Foreign Application Priority Data**

Mar. 12, 2004 (IT) VI2004A000051








FIG. 4






FIG. 5






FIG. 8




FIG. 9




FIG. 10





FIG.11

FIG.12






FIG.14

POSITIVE-DISPLACEMENT RECIPROCATING COMPRESSOR

BACKGROUND OF THE INVENTION

[0001] The present invention is about a positive-displacement reciprocating compressor, suitable for being used in several applications, like for instance to feed spray guns or in tools of compressed air type, for performing blowing operations in machine shops, or other.

[0002] It is known that, to produce the compressed air required for performing operations like the painting of industrial products, for instance automobiles or earthmovers, positive-displacement reciprocating compressors are used, which compress variable air flow rates according to the use requirements.

[0003] Said compressors generally comprise a piston, or plunger, which, sliding inside a cylinder, compresses the air sucked from the surrounding environment for supplying it to one or more users at a higher pressure.

[0004] The piston performs a reciprocating motion inside the cylinder, according to an operation known for the man skilled in the art.

[0005] The movement of the piston is obtained through the so called "oscillating piston" mechanism, it too well known for the persons skilled in the art.

[0006] The compressed air produced by the compressor is usually stored in a tank for a subsequent utilization.

[0007] However, said compressors have some acknowledged inconveniences.

[0008] A first inconvenience is due to the fact that, for the intrinsic features of the "oscillating piston" mechanism, the sealing elements or gaskets coupled with said piston undergo stresses that cause a rather considerable wear degree.

[0009] This is due to the continuous irregular oscillation of the piston inside the cylinder, which causes an excessive rubbing of the sealing elements against the cylinder inner walls.

[0010] Consequently, maintenance or replacement interventions of the sealing elements are required, with the inevitable material and labour costs this involves.

[0011] A second inconvenience is due to the fact that, in order to limit the sealing elements wear, the oscillating piston performs an incomplete stroke inside the cylinder.

[0012] As a result, there is a lower production of compressed air, and thus lower efficiencies of the compressor with respect to the possible and expected ones.

[0013] A further inconvenience of the aforementioned compressors is due to their high constructional complexity.

[0014] Another inconvenience is due to the fact that the compressors according to the prior art described hereinbefore are not able to produce a continuous flow of compressed air when operated.

[0015] As is well known, this fact leads to undesired operative conditions, in which the compressed air exits

intermittently from the compressor and the operation that it has to perform is performed in an imprecise and inadequate way.

[0016] To overcome the latter inconvenience, the compressors of known type are provided with a storage tank in which the compressed air is stored before being used.

[0017] The capacity of the tanks nowadays available on the market ranges from 25 to about 5000 litres, and thus there are several types of use, varying from hobbies to industrial utilization.

[0018] Only after the complete loading of these tanks, the compressed air is stably and readily available to the users.

[0019] The compressed air flow supplied by the compressor is thus made continuous and the optimal operative conditions to correctly perform the workings are obtained in use.

[0020] However, this solution of known type too has a first inconvenience due to the fact that the tanks considerably increase the overall dimensions of the compressors, this aspect being of particular relevance in those applications in which practical and easy manoeuvrability and handling of the compressor are required.

[0021] Another inconvenience is due to the danger related to the presence of the tank.

[0022] A further inconvenience is due to the need to produce more compressed air than that actually required at every use.

[0023] Indeed, when the compressor is stopped, it is required to refill the tank with its nominal flow rate to make efficient its subsequent use.

[0024] This involves an additional series of operations and an energy loss which could be avoided.

[0025] Not the least inconvenience is due to the fact that the arrangement of the tank further complicates the constructional shape of the compressors.

SUMMARY OF THE INVENTION

[0026] The present invention intends to overcome the aforementioned inconveniences.

[0027] In particular, the main object of the invention is to provide for a compressor in which the piston motion causes a lower wear degree of the sealing elements associated therewith with respect to that of equivalent known compressors.

[0028] It is a second object to improve the efficiency of positive-displacement compressors with respect to the prior art.

[0029] It is a further object of the invention to supply a continuous flow rate of stable compressed air to the users, simplifying the constructional shape of the compressor with respect to the known ones.

[0030] Said objects are obtained by a positive-displacement reciprocating compressor which, according to the content of the main claim, comprises at least a plunger, slidably coupled inside a cylinder in which a compression chamber is obtained, and operatively connected to driving means able to put it in motion in said cylinder, and it is

characterized in that said driving means comprise a motor having the rotation shaft coupled with eccentric means mechanically connected to said plunger and able to impose longitudinal displacements to said plunger according to an orthogonal direction with respect to the rotation axis of said shaft.

[0031] According to a preferred executive embodiment of the invention, the compressor comprises a shaped basement, which supports said piston and in which a collection chamber of the compressed air is obtained, said chamber being provided with at least an inlet for said compressed air in communication with said compression chamber of said cylinder, and at least an outlet for said compressed air in communication with the utilization.

[0032] Advantageously, the plunger motion inside the cylinder is an axial motion, being fully guided along the longitudinal axis of the cylinder in which it is contained.

[0033] This results in a minimum wear of the sealing elements interposed between the piston and the respective cylinder, increasing the working life of said elements with respect to what happens in the compressors of known type.

[0034] More advantageously, the axial movement allows the plunger to reach the end of stroke inside the cylinder, increasing the compressed air production and consequently the efficiency of the compressor with respect to the prior art ones.

[0035] Still advantageously, the compressor of the invention produces in use a more continuous compressed air flow with respect to the prior art, without requiring a tank of proper capacity coupled with the compressor.

[0036] Such aspect is furthermore improved by the arrangement of the collection chamber which, although generally being of reduced size, contributes to produce in use an almost continuous air flow rate.

[0037] As it will be better explained hereinafter, the collection chamber compensates, both at the switching on and in operative conditions, even the minimum compressed air supply intermittence.

[0038] Moreover, the collection chamber is rapidly refilled when the compressor is not operated: indeed, it is estimated that very few seconds are required to perform such operation.

[0039] In this way, the energy consumptions, related to the refill of stable compressed air inside the tank once the utilization is finished to be found in the compressors of known type with which the invention is comparable, are substantially eliminated.

[0040] All this is obtained without requiring storage tanks, as happens, on the other hand, in the prior art.

[0041] In this way, the overall dimensions and the constructional complexity of the compressor are considerably reduced with respect to the prior art.

[0042] Moreover, the handling, transport and arrangement of the compressor are improved in any situation.

[0043] Furthermore, in an advantageous way, the danger of the compressors is reduced with respect to those provided with a tank.

BRIEF DESCRIPTION OF THE DRAWINGS

[0044] The aforesaid objects and advantages, and others better specified in the following description, will be better highlighted in the description of a preferred executive embodiment of the invention, given in an explanatory and not limiting way, with reference to the figures of the annexed drawings, wherein:

[0045] **FIG. 1** is a partial sectional axonometric view of the compressor of the invention;

[0046] **FIG. 2** is an axonometric view of a first detail of **FIG. 1**;

[0047] **FIG. 3** is a partial sectional axonometric view of a second detail of **FIG. 1**;

[0048] **FIG. 4** is an axonometric view of a third detail of **FIG. 1**;

[0049] **FIG. 5** is an axonometric view of a detail of **FIG. 4**;

[0050] **FIG. 6** is an axonometric view of a fourth detail of **FIG. 1**;

[0051] **FIG. 7** is a bottom axonometric view of a detail of **FIG. 6**;

[0052] **FIG. 8** is a partial sectional axonometric view of a fifth detail of **FIG. 1**, without eccentric means;

[0053] **FIG. 9** is an axonometric view of a detail of **FIG. 8** in an operative condition, i.e. during the compression stroke;

[0054] **FIG. 10** is an axonometric view of the detail of **FIG. 9** in another operative condition, i.e. during the induction stroke;

[0055] **FIG. 11** is an axonometric view of a different embodiment of the detail of **FIG. 3**;

[0056] **FIG. 12** is an axonometric view of a first detail of **FIG. 11**;

[0057] **FIG. 13** is an exploded axonometric view of a second detail of **FIG. 11**; and

[0058] **FIG. 14** is an axonometric view of a different executive embodiment of **FIG. 1**.

DESCRIPTION OF THE INVENTION

[0059] The positive-displacement reciprocating compressor of the invention is shown in **FIG. 1**, where it is generally indicated with numeral 1.

[0060] One can see that it comprises four plungers, indicated with numerals 2, 3, 4 and 5, slidably coupled inside correspondent cylinders, indicated with numerals 6, 7, 8 and 9, in which a compression chamber is obtained, visible for the cylinders 8 and 9 only, where it is indicated with numerals 8a and 9a.

[0061] The plungers 2, 3, 4 and 5 are operatively connected to driving means, generally indicated with numeral 10, used to put them in motion in the respective cylinders 6, 7, 8 and 9.

[0062] According to the invention, the driving means 10 comprise a motor 11 having the rotation shaft 12 coupled with eccentric means, generally indicated with numeral 13,

mechanically connected to the plungers **2, 3, 4, 5** and able to impose them longitudinal displacements according to an orthogonal direction with respect to the rotation axis **Y** of the shaft **12**.

[0063] In **FIG. 1** it is further evidenced that the positive-displacement compressor **1** comprises a shaped basement **31** which supports the plungers **2, 3, 4** and **5**.

[0064] As shown in **FIG. 2**, the eccentric means **13** consist of a substantially longitudinally developed rotating body, in which a tubular portion **14** is obtained on one side, for the coupling to the shaft **12** according to systems well known for a man skilled in the art, like for instance a key coupling.

[0065] On the opposite side of the rotating body, an eccentric pin **15** is obtained, provided with contrast means, generally indicated with numeral **16**, which, in this specific case and as better explained hereinafter, are arranged to cooperate with a profile **17, 18**, visible starting from **FIG. 3**, obtained in a respective bracket **19, 20** which supports a pair of the plungers **2, 4** and **3, 5**.

[0066] According to further executive embodiments of the invention, not shown in the drawings, the positive-displacement compressor could comprise a different number of plungers, as well as of the corresponding cylinders, said number varying with continuity from one to a higher number and being set by the manufacturer, depending upon the compressed air flow rate that has to be made available to the user and the constructional feasibility.

[0067] Therefore, different executive embodiments of the compressor of the invention can exist, comprising a plunger supported by a bracket, or a pair of mutually opposed and coaxial plungers supported by a single bracket, or still a pair of plungers mutually staggered at a right angle, supported by a respective bracket, and so on.

[0068] Still in **FIG. 2** one can see that the rotating body is externally provided with a shaped sleeve **21**, coaxial with the tubular portion **14**, used to balance the weight of said tubular portion **14** with respect to the eccentric pin **15** during the rotation of the rotating body.

[0069] **FIG. 3** shows in detail that the first bracket **19** has the profile **17** and supports a first pair of mutually opposed and coaxial plungers **2, 4**, while the second bracket **20** has the profile **18** and supports a second pair of mutually opposed and coaxial plungers **3, 5**.

[0070] The contrast means **16** comprise a pair of cams **22, 23** mounted one above the other, coaxial to each other and to the eccentric pin **15**.

[0071] The first cam **22** cooperates with the profile **17** of the first bracket **19**, while the second cam **23** cooperates with the profile **18** of the second bracket **20**.

[0072] As one can see in **FIG. 3**, and better in **FIG. 4**, the profile **17, 18** which houses the contrast means **16** preferably but not necessarily consists of a through opening, but this constructional expedient is not binding with respect to the present invention, because the profile can have any kind of shape.

[0073] The first bracket **19** and the second bracket **20** are mutually orthogonally disposed and they slide one above the other to define a so called "star" constructional shape, well visible in **FIGS. 3** and **4**.

[0074] The longitudinal axis Z_1, Z_2 , defined by the first and the second pair of plungers **2, 4** and **3, 5** respectively, lies on the sliding plane between the first bracket **19** and the second bracket **20**, to dispose the centre of each plunger **2, 3, 4, 5** on the same virtual circumference, indicated with **C** in **FIG. 3**.

[0075] **FIG. 4** shows that each profile **17, 18** has a pair of mutually facing wearproof inserts **24, 25** and **26, 27**, applied to the lateral edge **17a, 18a** of said profile **17, 18**.

[0076] In this case, said wearproof inserts **24, 25, 26, 27** are made of lapped steel, but, in other embodiments, they can be of a suitable material for this kind of component, like for instance Teflon.

[0077] The utilization of the above mentioned materials allows a proper contact between the contrast means **16** and the lateral edge **17a, 18a** of each profile **17, 18** during the rotation of the rotating body, this aspect giving a good durability to the mechanical elements in reciprocal motion.

[0078] In **FIG. 5** one can see that the plunger **5** is provided with a perimetral sealing element **28**, protruding from the lateral edge **5a** of the plunger **5** and maintained steady in position by a covering disk **29** mounted in a depression obtained on the outer wall of the plunger **5**.

[0079] The covering disk **29** is made integral with the plunger **5** through first fastening means, generally indicated with numeral **30** and of well known type, for example screws.

[0080] It is intended that what mentioned hereinbefore for the plunger **5** with reference to **FIG. 5** is valid also for the other plungers **2, 3** and **4** belonging to the positive-displacement compressor **1**.

[0081] As shown in **FIG. 6**, according to the preferred executive embodiment of the invention described hereby, the compressor **1** comprises a collection chamber **32** for the compressed air, obtained in the aforementioned shaped basement **31** and provided with four compressed air inlets, of which only two, indicated with numerals **33** and **34**, are visible.

[0082] The collection chamber **32** communicates with the compression chamber, of the kind previously indicated with numerals **8a, 9a** in **FIG. 1**, belonging to each of the cylinders **6, 7, 8, 9**.

[0083] The collection chamber **32** is furthermore provided with a compressed air outlet, not shown in the annexed drawings, in communication with the outside and preferably having an annular shaped profile.

[0084] Each inlet is provided with a valve **35** consisting of a steel made annular foil, whose shape evidently follows the shape of the collection chamber **32**, thus being the only valve for each inlet.

[0085] Moreover, in operative conditions, as it will be better explained hereinafter, the valve **35** is opened at one of the plungers **2, 3, 4, 5** involved in the compression in that instant, while it is closed at one of the same plungers **2, 3, 4, 5**, opposed to the previous one, which is sucking air in the same instant.

[0086] The shaped basement **31** is provided with a closure cap **36**, applied thereon through connection means not

shown in the drawings and of type known per se, for instance screws, which closes the collection chamber 32.

[0087] The arrangement and the shape of the collection chamber 32 are rather useful and effective for providing, in use, even more stable compressed air in a continuous way.

[0088] Indeed, if the sequential movement of the plungers 2, 3, 4, 5 provides for an almost optimal compressed air flow on one side, at least more continuous with respect to equivalent compressors of known type, an even minimum intermittence at the compressed air outlet remains on the other side, said intermittence being compensated in an optimal way by the collection chamber 32.

[0089] As it will be explained hereinafter, the combination of the plungers 2, 3, 4, 5 action with the collection chamber 32 provides, in use, for optimal operative conditions of the compressor 1, because the air flow rate is continuous, fluid and stable.

[0090] FIG. 8 shows that the compressor 1 comprises four heads, generally indicated with numerals 37, 38, 39 and 40, each externally applied to a portion of the shaped basement 31 through second fastening means, generally indicated with numeral 41, to be disposed to cover the respective cylinders 6, 7, 8 and 9.

[0091] Each head 37, 38, 39 and 40 has two through holes, partially visible in FIG. 8 for the heads 39 and 40, where they are indicated with numerals 42 and 44 respectively, and predisposed for sucking the air to be compressed inside the cylinders 6, 7, 8 and 9.

[0092] The subsequent FIGS. 9, 10 precisely show this particular constructional detail, with reference to the head 40 only, being intended that the other heads 37, 38 and 39 too are provided with the same characteristics.

[0093] In the aforementioned Figures, the two through holes, through which the air to be compressed is sucked, are indicated with numerals 42 and 43.

[0094] The compressor 1 comprises a flexible thin blade 45, preferably made of steel, coupled with the inner wall 40a of the head 40, the inner wall 40a being turned toward the corresponding cylinder 9.

[0095] The flexible thin blade 45 is blocked at the ends 45a, 45b by placing the peripheral edge 9b of the cylinder 9 close to the head 40.

[0096] The flexible thin blade 45 is disposed near the through holes 42, 43, to close them during the compression stroke and to open them during the induction stroke.

[0097] For this purpose, the flexible thin blade 45 is provided at the ends 45a, 45b with a pair of slots which are coupled with a respective pin applied to the inner wall 40a of the head 40.

[0098] During the induction stroke, the flexible thin blade 45 is bent toward the interior of the cylinder 9, substantially detaching from the inner wall 40a of the head 40 for most part of its length and remaining coupled therewith at the ends 45a, 45b only.

[0099] This is allowed because the slots obtained at the ends 45a, 45b of the flexible thin blade 45 slidably hold the respective pins for a portion sufficient to uncouple said thin

blade 45 from the inner wall 40a of the head 40, thus allowing the air to enter the cylinder 9.

[0100] It is evident that such an air suction system is very simple to manufacture, since it does not require those fastening means usually employed in the prior art to mutually couple this kind of constructional details of the compressor.

[0101] In FIG. 11 an example of a different executive embodiment of the invention is shown, in which the positive-displacement reciprocating compressor is different from that previously described because the contrast means, generally indicated with numeral 105, coupled with the eccentric pin 104 of the eccentric means 100, said eccentric pin 104 being better visible in FIG. 12, cooperate with a connecting rod 106 fastened to a lower bracket 107 and an upper bracket 108 which support a pair of mutually opposed and coaxial plungers 101, 102.

[0102] The lower bracket 107 and the upper bracket 108 are mutually parallel and spaced, coupled with the plungers 101, 102 at their peripheral edge 101a, 102a.

[0103] FIG. 13 shows that the head 106a of the connecting rod 106 is engaged with a through opening 109 obtained on the lower bracket 107, while the small end 106b of the connecting rod 106 is coupled with a pin 110, connected to the lower bracket 107 and the upper bracket 108, through the interposition of a ball bearing 111.

[0104] Therefore, in this case, the rotation movement of the shaft 103 and the eccentric pin 104 associated therewith is transformed in a reciprocating rectilinear movement of the plungers 101, 102 through a mechanism known in technical language as "crank-handle connecting-rod assembly".

[0105] The subsequent FIG. 14 shows another embodiment of the invention, in which the positive-displacement compressor, generally indicated with numeral 200, comprises handle means 203 available to the user, joined to the shaped basement 202.

[0106] In the compressor 200, the collection chamber 204 of the compressed air consists of a tubular structure which externally limits and protects the driving means 201 and the shaped basement 202.

[0107] In this case, the compressor 200 also comprises two wheels, joined to the shaped basement 202, only one of said wheels, indicated with numeral 205, being visible in the figures, for its practical handling by the user.

[0108] Operatively, the driving means 10 put in motion the eccentric means 13 coupled with the bracket 19, 20, on which the plungers 2, 4 and 3, 5 are mounted in pairs and mutually opposed.

[0109] Now it is assumed, for instance, that the eccentric means 13 initially put in motion the plunger 2 inside the profile 17 of the bracket 19, said plunger performing in such way the air compression stroke in the cylinder 6.

[0110] Then the plunger 4, diametrically opposed and integral with the plunger 2, simultaneously starts the induction stroke, sucking air inside the cylinder 8.

[0111] The latter stroke is allowed by the fact that the flexible thin blade, not visible but of the type indicated with numeral 45, is almost fully moved away from the inner wall

of the head **39** during the induction stroke, letting the air enter through the two through holes, only one of which being visible and indicated with numeral **44**.

[0112] The plunger **3**, adjacent to the plunger **2** and disposed with its longitudinal axis Z_2 orthogonal to the longitudinal axis Z_1 of said plunger **2**, because of the movement of the eccentric means **13** inside the profile **18** of the bracket **20**, starts to compress small air flow rates inside the cylinder **7** even before the plunger **2** has completed its compression stroke in the cylinder **6**.

[0113] Similarly to what explained hereinbefore for the plunger **4**, while the plunger **3** starts to compress air, the plunger **5**, integral therewith and diametrically opposed, sucks a small air quantity inside the cylinder **9**. In this way, when the plunger **2** has finished its compression action, the plunger **3** adjacent therewith has already started to compress its own air quantity.

[0114] In a sequential and uninterrupted manner, the eccentric means **13** will subsequently put in motion the plungers **4** and **5** so that they will contribute to produce compressed air.

[0115] It is evident that, while the plungers **4**, **5** will compress air, although in a different quantity one respect to the other, the plungers **2** and **3** respectively opposed thereto will suck air in their turn, always according to different flow rates.

[0116] The operation described hereinbefore will continue indefinitely according to the need, with the plungers **2**, **3**, **4**, **5** motion regulated by the rotation speed of the motor **11** shaft **12**.

[0117] The operation of the positive-displacement reciprocating compressor shown in FIGS. **11** to **13**, is almost equivalent with respect to that previously explained for the compressor **1**, with the only exception that the longitudinal motion of the plungers **101**, **102** is obtained through a mechanism known as "crank-handle connecting-rod assembly".

[0118] It is thus assured a continuous production of compressed air, without idle times, which considerably reduces, in use, the intermittence in the compressed air delivery, this aspect, as well known, causing inadequate and undesired operative conditions.

[0119] This is obtained through the axial operation of the plungers **2**, **3**, **4**, **5** or **101**, **102** by the driving means **10**, considerably reducing, with respect to known compressors, the wear of the sealing elements of the type indicated with numeral **28**, interposed between the plungers **2**, **3**, **4**, **5** or **101**, **102** and the respective cylinders **6**, **7**, **8**, **9**.

[0120] Consequently, the plungers **2**, **3**, **4**, **5** or **101**, **102** are allowed to move until their end of stroke, this aspect being instead prevented in the oscillating piston system compressors by the excessive wear of the sealing elements in the same conditions.

[0121] It is thus achieved the object to produce greater air flow rates with the same constructional solutions, increasing by extension the efficiency of the compressor with respect to the equivalent prior art.

[0122] Moreover, the lower wear of the sealing elements leads to less frequent repairing, maintenance or replacement

interventions with respect to the prior art, with the evident advantages in terms of costs that this involves.

[0123] It is important to note that the above is obtained with a compressor of simple design and compact size that lead to extremely practical use conditions, in some applications.

[0124] Furthermore, the compressor of the invention supplies, in use, the actually required compressed air flow rate, without needing to maintain it working to restore the nominal capacity of a compressed air storage tank, as happens instead in the prior art.

[0125] The compressed air produced by each plunger **2**, **3**, **4**, **5** is thus sent from the respective compression chamber to the collection chamber **32**, and from here to its use destination.

[0126] The collection chamber **32** does not have a considerable size, but it is able to compensate temporary anomalies which can occur during the compressor **1** operation, especially in the initial phases.

[0127] Furthermore, the air inside the collection chamber is refilled in few seconds, depending on the compressor size, said air being thus stable and making the compressor immediately ready to be used in its subsequent switching on.

[0128] It is thus evident that, once finished the use of the positive-displacement compressor, few energy is sufficient to restore its ideal conditions for a subsequent use, lower, in any case, than the energy required by the known compressors provided with tank.

[0129] A number of other advantages with respect to the known compressors is related to the presence of the collection chamber **32**.

[0130] First of all, the compressor of the invention assures stable and continuous compressed air flows even without requiring to provide for a compressed air storage tank, which is typical of the equivalent known embodiments.

[0131] Consequently, the constructional complexity and the overall dimensions of the positive-displacement compressor are further reduced, the latter aspect leading to better handling and transport conditions in any situation.

[0132] The fact that the removal of the tank provides for greater safety conditions, because explosion dangers are reduced, has to be considered too.

[0133] Obviously, the manufacturer could modify the plungers diameters to set the compressed air flow rate produced according to the customers' requirements and the operative conditions.

[0134] However, this is independent of the fact that the positive-displacement compressor of the invention provides for continuous and stable flow rate conditions for any application.

[0135] It is still evident that the compressor of the invention could be provided with feet and handles which make easy its transport and positioning even in standing position, this fact not being allowed at present by the compressors provided with tanks.

[0136] Therefore, on the basis of the aforesaid description, it should be understood that the positive-displacement recip-

reciprocating compressor of the invention achieves all the aforementioned objects and advantages.

[0137] Modifications and variations to the positive-displacement compressor of the invention could be introduced in the executive stage, consisting for instance in a different number of plungers moved by driving means to obtain the desired air flow rates.

[0138] It is evident that this could be made according to the use condition, contemporarily acting on the diameter of the plungers.

[0139] Otherwise, to obtain an ideal flow, the manufacturer could indefinitely increase the number of plungers.

[0140] Furthermore, the arrangement of the compression chamber with respect to the plungers could be different from that described hereinafter; for instance, it could be positioned between the pistons, and not below them.

[0141] All the described and cited embodiments, but not shown in the annexed figures of drawings, if they fall within the scope of protection of the following claims, should be intended as protected by the present patent.

1. A positive-displacement reciprocating compressor, comprising at least a plunger slidably coupled inside a cylinder, in which a compression chamber is obtained, and operatively connected to driving means able to put it in motion in said cylinder, wherein said driving means comprise a motor having the rotation shaft coupled with eccentric means mechanically connected to said plunger and able to impose longitudinal displacements to said plunger according to an orthogonal direction with respect to the rotation axis of said shaft.

2. The compressor according to claim 1, wherein said eccentric means consist of a substantially longitudinally developed rotating body, in which a tubular portion coupling to said shaft, on one side, and an eccentric pin, on the other side, are obtained.

3. The compressor according to claim 2, wherein said eccentric pin is provided with contrast means able to cooperate with a profile obtained in a bracket which supports said plunger.

4. The compressor according to claim 2, wherein said eccentric pin is coupled with contrast means able to cooperate with a connecting rod, fastened to a lower bracket, and an upper bracket, which support said plunger.

5. The compressor according to claim 2, wherein said rotating body is externally provided with a shaped sleeve, coaxial with said tubular portion, able to balance the weight of said tubular portion with respect to said eccentric pin during the rotation of said rotating body.

6. The compressor according to claim 3, wherein it comprises a plunger supported by said bracket.

7. The compressor according to claim 3, wherein it comprises a pair of mutually opposed and coaxial plungers supported by said bracket.

8. The compressor according to claim 2, wherein it comprises a first pair of mutually opposed and coaxial plungers, supported by a first bracket, and a second pair of mutually opposed and coaxial plungers, supported by a second bracket, said brackets being mutually orthogonally disposed and sliding one above the other.

9. The compressor according to claim 8, wherein the longitudinal axis, defined by each of said plungers, lies on

the sliding plane between said first bracket and said second bracket to dispose the centre of each of said plungers on the same virtual circumference.

10. The compressor according to claim 9, wherein said contrast means comprise a pair of cams mounted one above the other, coaxial to each other and to said eccentric pin, the first cam cooperating with said profile obtained in said first bracket, and the second cam cooperating with said profile obtained in said second bracket.

11. The compressor according to claim 3, wherein said profile consists of an opening able to house said contrast means.

12. The compressor according to claim 4, wherein the head of said connecting rod is engaged with an opening obtained on said lower bracket, and the small end of said connecting rod is coupled with a pin through the interposition of a ball bearing.

13. The compressor according to claim 11, wherein said opening is a through opening.

14. The compressor according to claim 3, wherein said profile has a pair of mutually facing wearproof inserts applied to the lateral edge of said profile.

15. The compressor according to claim 4, wherein it comprises a pair of mutually opposed and coaxial plungers, supported by said lower bracket and said upper bracket, said brackets being mutually parallel and spaced and coupled with said plunger at the peripheral edge of said plunger.

16. The compressor according to claim 1, wherein said plunger is provided with a perimetral sealing element, protruding from the lateral edge of said plunger and maintained steady in position by a covering disk mounted in a depression obtained on the outer wall of said plunger.

17. The compressor according to claim 16, wherein said covering disk is made integral with said plunger through first fastening means.

18. The compressor according to claim 1, wherein it comprises a shaped basement which supports said plunger.

19. The compressor according to claim 18, wherein it comprises a collection chamber for the compressed air, provided with at least an inlet for said compressed air in communication with said compression chamber of said cylinder and with at least an outlet for said compressed air in communication with the outside.

20. The compressor according to claim 19, wherein said collection chamber is obtained in said shaped basement.

21. The compressor according to claim 19, wherein said collection chamber consists of a tubular structure which externally limits said driving means and said shaped basement.

22. The compressor according to claim 19, wherein said inlet is provided with a valve opened during the compression stroke and closed during the induction stroke.

23. The compressor according to claim 20, wherein said collection chamber has an annular shaped profile.

24. The compressor according to claim 20, wherein said shaped basement is provided with a closure cap of said collection chamber.

25. The compressor according to claim 22, wherein said valve is an annular foil.

26. The compressor according to claim 18, wherein it comprises at least a head, externally applied to said basement through second fastening means, to be disposed to cover said cylinder.

27. The compressor according to claim 26, wherein said head has at least a through hole for sucking said air to be compressed in said cylinder.

28. The compressor according to claim 27, wherein it comprises a flexible thin blade, coupled with the inner wall of said head, said inner wall being turned toward said cylinder and said flexible thin blade being blocked at the ends by placing the peripheral edge of said cylinder close to said head.

29. The compressor according to claim 28, wherein said thin blade is disposed near said through hole, to close it during the compression stroke and to open it during the induction stroke.

30. The compressor according to claim 14, wherein said wearproof inserts are made of lapped steel.

31. The compressor according to claim 14, wherein said wearproof inserts are made of Teflon.

32. The compressor according to claim 1, wherein it comprises at least two wheels for its handling, joined to said shaped basement.

33. The compressor according to claim 1, wherein it comprises comprising handle means available to the user, joined to said shaped basement.

34. The compressor according to what substantially described and shown.

* * * * *