

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 February 2006 (23.02.2006)

PCT

(10) International Publication Number
WO 2006/020317 A2

(51) International Patent Classification:
A47L 13/22 (2006.01) A46B 11/00 (2006.01)

Kent BR7 5PH (GB). DESSON, G. Scoot [US/US]; 17
Ray Court, Bedminster, NJ 07921 (US).

(21) International Application Number:
PCT/US2005/025715

(74) Agent: MONTANA, Mark, A.; Norris McLaughlin &
Marcus, P.A., 721 Route 202-206, 2nd Floor, Bridgewater,
NJ 08807 (US).

(22) International Filing Date: 18 July 2005 (18.07.2005)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ,
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,
SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/903,137 30 July 2004 (30.07.2004) US

(71) Applicant (*for all designated States except US*): HCT
LIMITED [CN/CN]; Unit 3, 23/F Lippo House, Cause-
way Bay Plaza 2, 463 Lockhart Road, Hong Kong (CN).

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): THORPE, Richard,
Christopher [GB/GB]; #2 Camden Close, Chislehurst,

[Continued on next page]

(54) Title: TWIST UP PEN TYPE DISPENSER WITH BRUSH APPLICATOR

(57) Abstract: The invention pertains to
a twist up pen type dispenser comprising a
brush applicator that is capable of receiving
material from a reservoir.



WO 2006/020317 A2



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

Published:

— *without international search report and to be republished upon receipt of that report*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

~~TWIST UP PEN TYPE DISPENSER WITH BRUSH APPLICATOR~~**BACKGROUND OF THE INVENTION**

[0001] The invention pertains to a twist up pen type dispenser comprising a brush applicator that is capable of receiving material from a reservoir. In an embodiment of the invention, the brush applicator of the twist up pen type dispenser has a plurality of protrusions for brushing teeth.

SUMMARY OF THE INVENTION

[0002] The twist up pen type dispenser with brush applicator comprises a body having an annular space, an end cap, a nozzle section having a nozzle section body and a nozzle element, a brush applicator and a cover. Material, such as a dentifrice composition, can be stored in the annular space. The brush applicator comprises a pinhole which is capable of being engaged with the nozzle, particularly a nozzle opening at the tip of the nozzle. The cover, which can be releasably secured and thus removable has a cover protrusion. When the cap is secured, the cover protrusion is engaged with the pinhole and/or the nozzle opening to seal or substantially seal the material from the external environment.

[0003] Mechanical means within the dispenser may be applied to move the material from the annular space through the nozzle and deposit the material on the brush applicator through the pinhole. Because the cover protrusion seals or the substantially seals the material from the external environment, the material is isolated from any deleterious affects that the environment may have on the material, such as spoilage, drying, hardening and the like.

[0004] The engagement of the cover protrusion with the nozzle opening and/or the pinhole also prevents material from flowing out of the twist up pen type dispenser with brush applicator while not in use, thus making the device particularly

~~portable especially for less viscous materials, such as a tooth cleaning gel or eyeliner.~~

[0005] In an embodiment of the invention, the twist up pen type dispenser with brush applicator has a dentifrice composition contained in the annular space and the brush applicator has one or more brush protrusions for brushing human or animal teeth. Dentifrice compositions that may be used in this embodiment include tooth gel, tooth paste, mouthwashes, mouth rinses, tooth whiteners and combinations thereof. This embodiment provides a handy portable tooth brush having a relatively narrow body that can be easily stored in smaller bags, such as a handbag, pouch, fanny pack, backpack and the like, without the material spoiling, hardening, drying out, or flowing out of the twist up pen type dispenser with brush applicator while the device is not being used.

DETAILED DESCRIPTION OF THE DRAWINGS

[0006] **Fig. 1** is a perspective drawing of a person using the twist up pen type dispenser with brush applicator for brushing teeth.

[0007] **Fig. 2** is a side elevational view of the twist up pen type dispenser with brush applicator showing the cover in a closed position covering the brush applicator.

[0008] **Fig. 3** is a side elevational view of the twist up pen type dispenser with brush applicator showing the cover in an open position.

[0009] **Fig. 4** is a cross sectional view of the twist up pen type dispenser with brush applicator showing a cap in a closed position covering the brush applicator.

[0010] **Fig. 5** is a cross sectional view of the twist up pen type dispenser with brush applicator showing the cap in an open position.

~~PCT/US2005/025715~~
 [0011] **Fig. 6** is a front view of the brush applicator engaged with the nozzle section.

[0012] **Fig. 7** is a cross sectional view of the brush applicator engaged with the nozzle section with material in the nozzle.

[0013] **Fig. 8** is a cross sectional view of the brush applicator engaged with the nozzle section with material in the nozzle and on the brush applicator top surface.

DETAILED DESCRIPTION OF THE INVENTION


[0014] As shown in **Figs. 2-5**, the twist up pen type dispenser with brush applicator **1** comprises a body **2**, preferably substantially in the shape of a cylinder, having a top **3**, a bottom **4**, an outer surface **5** and an inner surface **6** which defines an annular space **7**. As shown in **Figs. 4 and 5**, material **8** may be within the annular space **7**, which functions as a reservoir for the material **8** within the twist up pen type dispenser with brush applicator **1**. The material **8** may be a dentifrice, such as tooth gel, tooth paste, mouthwash, mouth rinse, tooth whitener and combinations thereof, cosmetics, such as mascara and eyeliner, hair colorants such as darkeners, like darkeners for facial hair such as moustaches, dyes or similar materials, or skin treatment compositions, combinations thereof, and the like.

[0015] Again referring to **Figs 2-5**, the twist up pen type dispenser with brush applicator **1** further comprises an end cap **9**, preferably substantially in the shape of the cylinder, having a continuous lateral side **10** with an outer surface **11** and an inner surface **12**, an end cap top **13** having an end cap opening **14** and an end cap bottom **15** with an outer surface **16** and an inner surface **17**, the end cap having a cavity **18** defined by the inner surface **12** of the continuous lateral side **10** and the inner surface **17** of the end cap bottom **15**. The end cap top **13** is adjacent

to the bottom 4 of the body 2 with the end cap opening 14 and cavity 18 about aligned with the annular opening 7 of the body 2. As shown in **Figs. 2-5**, the outer surface 11 of the end cap 9 may have a continuous protrusion 111 at about the end cap top 13. Also, the inner surface 17 of the end cap 9 may have a plurality of sequential and adjacent polygonal surfaces 19, such as rectangular surfaces. As shown in **Figs. 4 and 5**, the polygonal surfaces may protrude within the annular opening 7 being opposite the inner surface 6 of the body 2 at about the bottom 4 of the body 2. The end cap is preferably capable of rotation. The end cap and/or body may be made of clear or opaque plastic material which permits portability without risk of breakage and allows a user to see the amount of material 8 remaining in the annular space 7.

[0016] The twist up pen type dispenser with brush applicator 1 further comprises means 21 for moving the material 8 from the annular space 7 to a brush applicator 20. As shown in the embodiment depicted in **Figs. 2-5**, the means 21 comprises a driving rod 22, a compression spring 23, a ratchet wheel 24, a securing seat 25, a piston rod 26 and a piston 27. As shown in **Figs. 4 and 5**, the driving rod 22 has a top 28, bottom 29, an inner surface 30 and an outer surface 31. The bottom 29 of the driving rod 22 is inserted into the end cap bottom and is held into place by the polygonal surfaces 19 such that as the end cap rotates the driving rod is driven to rotate which causes the piston rod 26 and piston 27 to move through the annular space 7.

[0017] As shown in the drawings, particularly **Figs. 2-5**, a continuous shelf 33 is located on the inner surface 6 of the body proximate to the bottom 4 of the body 2. The ratchet wheel 24 has a top 34 and a bottom 35 and comprises a plurality (e.g. a ring) of teeth 36 at the top 34. The compression spring 24 is mounted to the

The outer surface of the driving rod between the bottom **35** of the ratchet wheel and the continuous shelf **33** and facilitates movement of the ratchet wheel **24**.

[0018] The securing seat **34** is above the ratchet wheel. The securing seat **34** has a top **35** and a bottom **36** and there are a plurality of teeth **33** (e.g. a ring of teeth) at the bottom **36** of the securing seat. The seat further has a circumferential edge **37** which is provided with securing engagement edge **38** of polygonal shape on the inner surface of the body for mounting within the annular opening **7** of the body **2**. The securing seat **34** further comprises a hole **39** at about the center running from the top **35** to the bottom allowing the piston rod **26** to pass through. As shown in **Figs. 2-5**, the top **35** of the securing seat **34** may be smaller in dimension, e.g., have a smaller diameter in the axial direction than the bottom **36** of the securing seat **34**.


[0019] The piston rod **26** is threaded with screw threads **40** for mounting to the inner surface **30** of the driving rod **22**. The inner surface **30** of the driving rod **22** may also have screw threads **45**. The piston rod is secured at the top of the piston rod to the piston **27**. As shown in **Figs. 4 and 5**, the top of the piston rod **26** is provided with an engaging block **46** having a continuous outer protrusion **47** and a center protrusion **147** to engage with the piston **27**. The continuous outer protrusion **47** is proximate to the outer edge of the engaging block **46** and the center protrusion **147** corresponds to the piston rod **26**.

[0020] The piston **27** is located in the annular space **7** of the body **2**. The bottom **48** of the piston interfaces with the engaging block **46** and, as shown in **Figs. 4 and 5** the continuous outer protrusion **47** and center protrusion **147** protrude within the piston **27** thus securing the piston **27** to the engaging block **46** and thus the piston rod **26**. The piston may be any geometric shape, such as a disc with a flat top

~~PCT/US2005/025715~~
 and bottom, but is shown in Figs. 4 and 5 as having a conical shape, such as a crown top. The conical shape maximizes removal of the material 8 from the annular opening 7. The piston 27 may be made from silicone or similar type plastic material.

[0021] Referring to Figs. 2-5, when the end cap 10 rotates counterclockwise, the driving rod 22 will drive the ratchet wheel 36 to rotate counterclockwise. At the same time, the piston 27 will move upward within the annular space 7 as a result of the piston rod 26 being driven by the driving rod 22. The material 8 is on the top of the piston 27 and is squeezed upwards to the nozzle section 48. When the ratchet wheel 24 rotates counterclockwise, the teeth 33 will not move for the reason that the securing seat 34 is secured to the body 2. The sloping face of the teeth 36 of the ratchet wheel 24 will move along the corresponding sloping face of the teeth 33 of the securing seat 34 so that the ratchet wheel 24 will be lowered and compress the compression spring 23 until the teeth 36 of the ratchet wheel 24 are moved to the teeth 33 of the securing seat 34 (i.e., the sloping face of the teeth 36 of the ratchet wheel 24 are engaged with the sloping face of the teeth 33 of the securing seat 34 displaced by one tooth 33 section in the counterclockwise direction). At this instance, the ratchet wheel 24 will restore to its original position by the spring force of the compression spring 26.

[0022] In the original position, the teeth 36 of the ratchet wheel 24 are mutually opposed to the teeth 33 of the securing seat 34, such that the teeth are mutually engaging, so that reverse direction (e.g., clockwise direction) of the ratchet wheel will not be possible. The piston 27 defines the lower edge of the material 8 within the annular space 7. Because reverse direction of the ratchet wheel is not possible, the piston 27 is effectively unidirectional and thus the material will always move toward the top 3 of the body 2. This precludes material 8 and, in part,

 prevents material **8**, from entering portions of the annular space **7** behind the advancement of the piston **27** and contacting the other elements of the means for moving the material. This aspect of the invention facilitates the function of the device.

[0023] U.S. Patent No. 6,474,891 describes a material-extracting device for a pen type make up dispenser. This material-extracting device can be used with the twist up pen type dispenser with brush applicator as described herein. U.S. Patent No. 6,747,891 is incorporated herein in its entirety by reference.

[0024] The twist up pen type dispenser with brush applicator **1** further comprises a nozzle section **48**. As shown in **Figs. 2-5**, the nozzle section comprises a nozzle section body **49** and a nozzle element **50**. The nozzle section body is generally cylindrical having a nozzle section body bottom **51**, nozzle section body top **52**, a nozzle section body outer surface **53** and a nozzle section body inner surface **54** and is adjacent to the top **30** of the body **2**. The nozzle section further comprises a sheath **55** having a bottom plate **56**, a middle wall **57** and a top wall **58**. The top wall **58** of the sheath **55** is adjacent to the nozzle section body top **52** and protrudes inwards from the nozzle section body top **52** adjacent to the middle wall **57** which is opposed to the nozzle section body inner surface **54**. The middle wall **57** terminates at the bottom plate **56** which protrudes from the nozzle section body inner surface, preferably at an angle of about 90 °, at some point between the nozzle section body bottom **51** and nozzle section body top **52**. As shown in **Figs. 2-3**, the nozzle section body outer surface **53** near the nozzle section body bottom **51** may have one or more protrusions **78** for engaging the cover **77**.

[0025] As shown in **Figs 2-5**, the nozzle element **50** comprises a base section **59**, nozzle mid section **60** and a tip **61**. The base section **59** is cylindrical

and has a base section outer wall **62** that has a plurality of protrusions which secure the nozzle element to the nozzle section body. The nozzle section body **49** is either attached to the body **2** or is integral with the body **2**. The nozzle element base section **59** has a base section inner surface **159** which may be tapered that defines all or part of a nozzle annular space **63** that is continuous through the base section **59**, mid section **60** and tip **61**. The nozzle mid section **60** has an outer wall **64** that may have one or more protrusions **65** for engaging the brush applicator **20** and a mid section inner surface **160** which may be tapered that defines all or part of a nozzle part annular space **63**. The tip **61** is a tapered element having an nozzle opening **66** at the end opposite the mid section **60**. The tip has a tip inner surface **161** which may be tapered that defines all or part of a nozzle part annular space **63**.

[0026] The twist up pen type dispenser with brush applicator **1** further comprises the brush applicator **20**, which is shown in the drawings and in particular **Figs. 6-8**. The brush applicator **20** comprises a brush applicator base **67** which is generally a cylindrical sleeve **120** having a hollow inner section for engaging the nozzle section **48**, and a brush applicator top **68**. The brush applicator base **67** has an outer surface **69** and an inner surface **70** with the inner surface **70** defining the sleeve. The sleeve is capable of engaging the outer wall **64** of the nozzle mid section **61** and the top wall **58** of the sheath **55** such that the brush applicator can be secured to or releasably secured to the nozzle element. The bottom of the brush applicator base **67** has an opening defined by the inner surface **70**. The brush applicator top **68** may be angled and has a brush applicator top surface **168** having one or more brush protrusions **71** and a pinhole **72**. As shown in **Figs. 6-8**, when the brush applicator **20** is releasably secured to the nozzle, the nozzle opening **66** is

~~PCT/US2005/025715~~
engaged with the pinhole **72**. The brush applicator **20** may be a single piece made of silicone, such as injection molded silicone, or similar type material.


[0027] As shown in **Figs. 2-4**, the twist up pen type dispenser with brush applicator **1** also comprises a cover **77**, preferably substantially in the shape of a cylinder, having a cover outer surface **73**, a cover inner surface **74** and a cover top **75** with an inner and outer surface. The cover has a cover opening **76** at the end opposite the cover top **75**. The cover inner surface **74** and the inner surface of the cover top defines a cavity so that the cover can be placed over the nozzle element and brush applicator with the cover inner surface **74** engaging the nozzle section body outer surface **53**, such as the one or more protrusions **78** near the nozzle section body bottom **51**. In this manner the cover can be replaceably secured to the twist up pen type dispenser with brush applicator.

[0028] As shown in **Figs 2-4**, the cover further comprises a cover protrusion **79** emanating from the inner surface of the cover top **75**, generally from about the center of the inner surface of the cover. The protrusion **79** may be tapered and has a protrusion tip **80** at the end opposite the cover top **75**. When the cover is releasably secured to the twist up pen type dispenser with brush applicator **1**, the protrusion tip **80** is engaged with the pinhole **72** and/or the nozzle opening **66**. As such, the engagement of the nozzle opening, pinhole and cover protrusion effectively seals the material from the external environment when the twist up pen type dispenser with brush applicator **1** is not in use. The cover top **75** may further comprise one or more holes (not shown) to allow ambient air onto the brush applicator. The cover may be made of a clear plastic material.

[0029] The material **8** in the twist up pen type dispenser with brush applicator **1** is stored for use in the annular space **7** of the body **2**. When a person

desires to use the twist up pen type dispenser with brush applicator, the user removes the cover **78** and rotates the end cap **10** thereby causing the driving rod **22** to drive the ratchet wheel **36** to rotate thus moving the piston **27** upward within the annular opening **7** as a result of the piston rod **26** being driven by the driving rod **22** thereby forcing some or all of the material **8** from the annular space **7** to the nozzle section **48**. The pressure caused by the piston on the material **8** forces the material **8** through the nozzle part annular space **63** to the nozzle opening **66** and through the nozzle opening and pinhole **72** thereby depositing the material on the brush applicator top **68**, as shown on **Figs. 7 and 8**. When sufficient material is on the brush applicator top, the user simply stops rotating the end cap **10**. After use, the user replaces the cover **78** on the twist up pen type dispenser with brush applicator **1** which, as discussed above, seals the material from the external environment.

[0030] In an embodiment of the invention, as shown in **Fig. 1**, the twist up pen type dispenser with brush applicator **1** is used as a portable tooth brush. Although the twist up pen type dispenser with brush application **1** is shown in **Fig. 1** as a toothbrush, it should be understood that this is a depiction of one of many uses or embodiments for the twist up pen type dispenser with brush applicator. Another use, for example, can be as an applicator for darkening facial hair, such as a moustache, wherein the material **8** is hair darkener and can be applied to the moustache by depositing the hair darkener on the brush applicator top and then engaging the brush applicator top with the moustache, such as stroking the brush protrusions through the moustache hairs.



CLAIMS

We claim:

1. A dispenser comprising a body with an annular space having material stored within the annular space, a brush applicator having a pinhole and a cover having a protrusion wherein the protrusion is capable of engaging at least the pinhole to seal the material from the external environment.
2. The dispenser of Claim 1 wherein the material is selected from the group consisting of tooth gel, tooth paste, mouthwash, tooth whitener, mouth rinse and combinations thereof.
3. A dispenser comprising
 - a) a body comprising a top, a bottom, an outer surface and an inner surface which defines an annular space;
 - b) an end cap comprising a continuous lateral side with an outer surface and an inner surface, an end cap top having an end cap opening and an end cap bottom with an outer surface and an inner surface, the end cap having a cavity defined by the inner surface of the continuous lateral side and the inner surface of the end cap bottom wherein the end cap top is adjacent to the bottom of the body and the end cap is capable of rotation;
 - c) a nozzle section comprising
 - i) a nozzle section body with a nozzle section body bottom, nozzle section body top, a nozzle section body outer surface and a nozzle section body inner surface wherein the nozzle section body is adjacent to the top of the body; and

- ii) a nozzle element having a base section with a base section inner surface, a nozzle mid section with a mid section inner surface and a tip with a tip opening and a tip inner surface wherein the base section inner surface, mid section inner surface and tip inner surface define a nozzle annular space;
- d) a brush applicator comprising a brush applicator base and a brush applicator top wherein
- i) the brush applicator base has an outer surface and an inner surface which defines a sleeve;
 - ii) the brush applicator base further has an opening defined by the brush applicator inner surface;
 - iii) the brush applicator top has a brush applicator top surface having one or more brush protrusions and a pinhole; and
 - iv) the brush applicator is capable of being secured to or releasably secured to the dispenser such that the pinhole is engaged with the tip of the nozzle element at the nozzle opening;
- e) a cover comprising a cover outer surface, a cover inner surface and a cover top with an inner surface and an outer surface wherein
- i) the cover inner surface and inner surface of the cover top define a cavity;
 - ii) the cover further comprises a cover opening at the end of the cover opposite the cover top;
 - iii) the inner surface of the cover top comprises a cover protrusion emanating from the cover inner surface into the cavity wherein the cover is capable of being releasably secured over the brush

~~PCT/US2005/025715~~
applicator with the cover protrusion engaged with the pinhole,
nozzle opening or combinations thereof; and

- f) a means for moving material from the annular space to the brush applicator.
4. The dispenser of Claim 3 wherein the means for moving material comprises
- a) a driving rod comprising a top, a bottom, an inner surface and an outer surface wherein the bottom is inserted into the cavity of the end cap and secured to the end cap;
 - b) a piston rod comprising screw threads and an engaging block wherein the screw threads are mounted to the inner surface of the driving rod;
 - c) a ratchet wheel and a securing seat having mutually engaging teeth;
 - d) a piston located in the annular space which interfaces with the engaging block; and
 - e) a compression spring.
5. The dispenser of Claim 4 wherein the inner surface of the body comprises a continuous shelf and the compression spring is mounted to the outer surface of the driving rod between the ratchet wheel and the continuous shelf.
6. The dispenser of Claim 4 wherein driving rod is secured to the end cap by polygonal surfaces on the inner surface of the end cap.
7. The dispenser of Claim 4 wherein the inner surface of the driving rod has screw threads.
8. The dispenser of Claim 4 wherein the piston rod has a continuous outer protrusion and a center protrusion for engaging the piston.

9. The dispenser of Claim 4 wherein the securing seat is mounted to the body within the annular space by a securing engagement edge on the inner surface of the body.
10. The dispenser of Claim 4 wherein the piston is silicone.
11. The dispenser of Claim 3 wherein the body, the end cap and the cover are substantially in the shape of a cylinder.
12. The dispenser of Claim 3 wherein the outer surface of the end cap has a continuous protrusion at about the end cap top.
13. The dispenser of Claim 3 wherein the end cap is made of clear or opaque plastic material.
14. The dispenser of Claim 3 wherein the body is made of clear or opaque plastic material.
15. The dispenser of Claim 3 wherein the nozzle section further comprises a sheath having a bottom plate, a middle wall and a top wall wherein the top wall is adjacent to the nozzle section body top and protrudes inwards from the nozzle section body top adjacent to the middle wall, the middle wall is opposed to the nozzle section body inner surface and terminates at the bottom plate which protrudes from the nozzle section body inner surface at some point between the nozzle section body bottom and the nozzle section body top.
16. The dispenser of Claim 3 wherein the nozzle section body bottom comprises one or more protrusions.
17. The dispenser of Claim 3 wherein the base section of the nozzle element has a base section outer wall with a plurality of protrusions.
18. The dispenser of Claim 3 wherein the brush applicator top is angled.
19. The dispenser of Claim 3 wherein the brush applicator is silicone.

20. The dispenser of Claim 3 wherein the cover top comprises one or more holes.

21. The dispenser of Claim 3 wherein the material is selected from the group consisting of tooth gel, tooth paste, mouthwash, tooth whitener, mouth rinse and combinations thereof.

22. The dispenser of Claim 3 which is a portable toothbrush.



23. The dispenser of Claim 3 wherein the material is selected from the group consisting of a cosmetic, a hair treatment composition, a skin treatment composition and combinations thereof.

1/4



FIG. 1





FIG. 3



3/4

FIG. 4**FIG. 5**

4/4

FIG. 6**FIG. 7****FIG. 8**