



(22) **Date de dépôt/Filing Date:** 2014/06/13

(41) **Mise à la disp. pub./Open to Public Insp.:** 2015/01/03

(45) **Date de délivrance/Issue Date:** 2016/11/29

(30) **Priorité/Priority:** 2013/07/03 (EP13174862.6)

(51) **Cl.Int./Int.Cl.** *F23J 15/02* (2006.01),
F23J 15/04 (2006.01)


(72) **Inventeurs/Inventors:**
NILSSON, LARS, SE;
GRUBBSTROM, JOERGEN PER-OLOF, SE

(73) **Propriétaire/Owner:**
GENERAL ELECTRIC TECHNOLOGY GMBH, CH

(74) **Agent:** CRAIG WILSON AND COMPANY

(54) **Titre : SYSTEME DE TRAITEMENT ET PROCEDE POUR UN GAZ D'EVACUATION ISSU D'UN PROCEDE DE COMBUSTION**

(54) **Title: TREATMENT SYSTEM AND METHOD FOR A FLUE GAS FROM A COMBUSTION PROCESS**



(57) **Abrégé/Abstract:**

The treatment system (2) for a flue gas from a combustion process comprises a condenser (4), a compressor (5) for compressing the flue gas deprived of moisture at the condenser (4), a NO₂ scrubber column (6) supplied with the compressed flue gas from the compressor (5), a liquid supply line (7) for supplying liquid condensed at the condenser (4) to the NO₂ scrubber column (6), a liquid recirculation line (8) for recirculating liquid from the NO₂ scrubber column (6) to the condenser (4).



ABSTRACT

The treatment system (2) for a flue gas from a combustion process comprises a condenser (4), a compressor (5) for compressing the flue gas deprived of moisture at the condenser (4), a NO₂ scrubber column (6) supplied with
5 the condensed flue gas from the compressor (5), a liquid supply line (7) for supplying liquid condensed at the condenser (4) to the NO₂ scrubber column (6), a liquid recirculation line (8) for recirculating liquid from the
10 NO₂ scrubber column (6) to the condenser (4).

(figure 2)

TREATMENT SYSTEM AND METHOD FOR A FLUE GAS FROM A
COMBUSTION PROCESS

TECHNICAL FIELD

5 The present invention relates to a treatment system
and method for a flue gas from a combustion process.

 The combustion process occurs for example in a boiler
of a power plant, preferably an oxyfired boiler (i.e. a
boiler supplied with oxygen instead of air).

10

BACKGROUND

 EP 2 365 866 discloses a system for treatment of flue
gas for removing NO_x and SO₂ comprising a compressor and a
wet scrubber wherein the flue gas is transported counter
15 currently to a wash medium. In addition, between the
compressor and the wet scrubber, a basic additive is
supplied to limit the acidity of the water coming from the
wet scrubber and thus protect the plant.

 WO 2011/140 054 discloses a system for treatment of
20 flue gas including a condenser to remove water from the
flue gas, a compressor and a wet scrubber column for NO_x
removal. In addition, the water gathered at the condenser
(this is waste water) is supplied from the condenser to the
wet scrubber. According to WO 2011/140 054, after having
25 passed through the wet scrubber, the water is collected as
acid water and is disposed.

 This system requires a large amount of water and, in

79291-241

2

addition generates a large amount of acid water at the wet scrubber. The present invention proposes a way to overcome these drawbacks.

SUMMARY

5 An aspect of the present invention includes providing a system and a method by which the water demand can be reduced.

Another aspect of the present invention includes providing a system and a method by which the acid water amount produced at the wet scrubber can be drastically reduced or
10 completely eliminated.

According to a further aspect, there is provided a treatment system for a flue gas from a combustion process comprising a condenser, a compressor for compressing the flue gas deprived of moisture at the condenser, a NO₂ scrubber
15 column supplied with the compressed flue gas from the compressor, a liquid supply line for supplying at least a part of liquid condensed at the condenser to the NO₂ scrubber column, and a liquid recirculation line for recirculating at least a part of the liquid from the NO₂ scrubber column to the
20 condenser.

There is also provided a treatment method for a flue gas from a combustion process comprising passing the flue gas through a condenser to condensate moisture contained therein, compressing the flue gas deprived of moisture at the condenser,
25 passing the compressed flue gas through a NO₂ scrubber column to remove NO₂, supplying at least a part of liquid condensed at the condenser to the NO₂ scrubber column through a liquid supply line, and recirculating

79291-241

2a

at least a part of the liquid from the NO₂ scrubber column to the condenser.

These and further aspects are disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Further characteristics and advantages will be more apparent from the description of a preferred but non-exclusive embodiment of the system and method, illustrated by way of non-limiting example in the accompanying drawings, in which:

10 Figure 1 is a schematic view of a system for flue gas treatment; and

Figure 2 is a schematic view of a system in an embodiment of the invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Figure 1 shows an example of a system for a flue gas treatment.

5 Reference 1 indicates a boiler such as preferably an oxyfired boiler (i.e. a boiler supplied with oxygen and usually also with recirculated flue gas) and a fuel such as coal, oil or gas. The boiler 1 generates flue gas that is directed to the flue gas treatment system 2.

10 The flue gas treatment system 2 can have different components and the components can be differently positioned one with respect to the other, but usually the system 2 includes a filter or electrostatic precipitator for dust removal, a SO₂ scrubber, a diverter connected to a
15 recirculation line for supplying a portion of the flue gas back to the boiler 1 (this recirculated gas is mixed with the oxygen) and/or other components. These components are generally identified by the reference 3.

 The system also includes a condenser 4 for liquid
20 removal. The condenser 4 can be of the type having liquid falling for the top and gas rising from the bottom thereof. The amount of liquid can be up to 40% by volume of the flue gas, thus the amount of liquid that is collected at the condenser 4 can be large.

25 Downstream of the condenser 4, the system 2 includes a compressor 5 for compressing the flue gas deprived of

liquid at the condenser 4. The compressor 5 is usually a multi stage compressor.

The system 2 then includes a NO₂ scrubber column 6, which is supplied with the compressed flue gas from the compressor 5, and a liquid supply line 7 for supplying a part of the liquid condensed at the condenser 4 to the NO₂ scrubber column 6 (this liquid includes mainly water but it can also include other components). Also the NO₂ scrubber column 6 is preferably of the type having liquid falling for the top and gas rising from the bottom thereof.

In addition, the system 2 also comprises a liquid recirculation line 8 for recirculating liquid from the NO₂ scrubber column 6 back to the condenser 4.

On the liquid supply line 7 a feed pump 9a and usually a recirculation pump 9b are provided.

The feed pump 9a recirculates the liquid from the condenser 4 to the NO₂ scrubber 6 and the recirculation pump 9b recirculates the liquid from the outlet of the NO₂ scrubber to the inlet of the NO₂ scrubber through the line 9c, in case of low liquid flow from the feed pump 9a.

The system also has a main flow recirculation 20, for recirculating liquid from the outlet of the condenser 4 back to the inlet of the condenser 4.

Preferably the main flow recirculation 20 and the recirculation line 8 merge in a return line 22 that is connected to the inlet of the condenser 4.

No fresh water (or only limited amount of fresh water) needs to be supplied to the condenser 4, as the liquid supplied to the condenser 4 is extracted from the flue gas itself.

5 A supply 21 for reagents, such as for pH control reagents can be provided at the return line 22.

In addition, a pump 10 is preferably provided on the return line 22, to help liquid circulation and a heat exchanger 11 is also preferably provided on the return line
10 22, to cool the liquid that must be supplied to the condenser 4. Alternatively or in addition to the heat exchanger 11 on the return line 22, a heat exchanger can also be provided on the main flow recirculation 20.

The heat exchanger 11 can be of any type according to
15 the cooling capacity needed and the cooling medium available; for example as cooling medium one or more of the following can be used: water (that preferably does not come into contact with the water to be cooled), air, etc.

Advantageously a controller 13 for the heat exchanger
20 11 is provided.

The controller 13 can regulate the flue gas temperature at the outlet of the condenser 4 by regulating the heat exchanger 11 on the basis of a target temperature for the flue gas at the outlet of the condenser 4.

25 For example, the controller 13 can regulate the liquid temperature at the outlet of the heat exchanger 11 on the

basis of a measured temperature of the flue gas (via a sensor 50) and a target temperature for the flue gas at the outlet of the condenser 4. The target temperature is defined in advance and depends on the environment and
5 operating conditions and on the cooling fluid available.

A controller 17 for controlling the feed pump 9a is also provided; the controller 17 can regulate the feed pump 9a on the basis of at least a feature of the liquid supplied to the NO₂ scrubber column 6 via the supply line
10 7.

Different kinds of sensors can be provided to detect the features of the liquid, but preferably a sensor 19 for the pH of the liquid is provided on the liquid supply line 7. The sensor 19 is connected to the controller 17 for
15 controlling the feed pump 9a.

The controller 17 controls the feed pump 9a in order to keep the pH of the liquid supplied to the NO₂ scrubber column in the range 5.5-7 and preferably 6-7.

In addition, another sensor 40 preferably for the pH
20 of the liquid can be provided on the return line 22; the sensor 40 is connected to a controller 42 that is in turn connected to and controls the supply 21 for reagents, such as a pH control reagent.

The controllers 13 and/or 17 and/or 42 can be local or
25 centralised controllers, for example those controllers 13, 17, 42 are separate controllers or one single control unit

that implements all control functions or they can be embedded in one of the machines such as heat exchanger 11, pump 9a, supply 21.

Downstream of the NO₂ scrubber column 6 the system 2
5 has a dehydration device 25 for moisture removal, and a CO₂ separation system 26, to separate CO₂ that is supplied to a sequestration unit 27 from other gas that is vented at 28.

The system 2 also comprises a heat exchanger 52 for cooling the liquid supplied to the NO₂ scrubber column 6.
10 The heat exchanger 52 is preferably on the liquid supply line 7.

The operation of the system is apparent from that described and illustrated and is substantially the following.

15 The flue gas generated at the boiler 1 is treated in different ways at 3 (when these treatments are provided).

Then the flue gas is supplied to the condenser 4 where moisture is condensed; the flue gas deprived of moisture is thus compressed at the compressor 5 (as a side effect this
20 enhances conversion of NO into NO₂) and thus it is supplied to the bottom of the NO₂ scrubber column 6.

The liquid collected at the bottom of the condenser 4 is partly supplied to the inlet of the condenser 4 via the main flow recirculation 20 and it is partly supplied via
25 the supply line 7 to the top of the NO₂ scrubber column 6. The liquid supplied to the NO₂ scrubber column 6 washes in

counter flow the flue gas and removes NO₂ (and NO that keeps converting into NO₂) with high efficiency.

Liquid is collected at the bottom of the NO₂ scrubber column 6. From the NO₂ scrubber column 6 the liquid is
5 supplied via the recirculation line 8 and main flow recirculation and through the pump 10 to the heat exchanger 11 and thus to the inlet of the condenser 4.

The sensor 19 measures the pH of the liquid in the supply line 7 and supplies the information on the pH to the
10 controller 17. The controller 17 regulates the feed pump 9a such that the pH of the liquid in the supply line 7 is in the target range, i.e. between 5.5-7 and preferably 6-7. In other words, the regulation of the pump 9a is such that the acidity of the liquid at the NO₂ scrubber column 6 is
15 limited by dilution.

This pH value allows operation of the system with a limited risk of corrosion and damage to the plant and its components caused by the acidity of the liquid.

In addition, the pH of the liquid is also measured by
20 the sensor 40 close to the inlet of the liquid into the condenser 4; this information of the pH is supplied to the supply 21 through which a pH control reagent is supplied into the return line 22 for controlling and adjusting the pH of the liquid supplied into the condenser 4.

25 In addition a control valve 15 is provided connected to the bottom of the condenser 4 and to a liquid waste line

16.

The control valve 15 is used to dispose liquid and regulate the liquid amount at the bottom of the condenser 4; the liquid disposed via the waste line 16 has a pH around 7 and can be easily discharged. Anyhow, an additional supply 29 can be provided at the waste line 16 in order to supply an additive to regulate the pH according to the desired pH at the waste line 16.

The flue gas from the NO₂ scrubber column 6 is then dehydrated at 26; thus at the CO₂ separation system CO₂ is separated from other gas and is sequestered in 27 and other gas (for example oxygen, argon, nitrogen) are vented at 28.

The present invention also relates to treatment method for a flue gas from a combustion process. The method comprises:

passing the flue gas through a condenser 4 to condensate the moisture contained therein,

compressing the flue gas deprived of moisture at a condenser 4,

passing the compressed flue gas through a NO₂ scrubber column 6 to remove NO₂,

supplying at least a part of the liquid condensed at the condenser 4 to the NO₂ scrubber column 6,

recirculating at least a part of the liquid from the NO₂ scrubber column 6 to the condenser 4.

The method also includes regulating the flue gas temperature at the outlet of the condenser 4 by regulating the heat exchanger 11 on the basis of a target temperature for the flue gas at the outlet of the condenser 4.

5 In particular, according to the method the supplying of at least a part of the liquid condensed at the condenser 4 to the NO₂ scrubber column 6 is regulated on the basis of at least a feature of the liquid supplied to the NO₂ scrubber column 6. For example the at least a feature of
10 the liquid supplied to the NO₂ scrubber column 6 is the pH. Preferably the feeding is regulated in order to keep the pH of the liquid supplied to the NO₂ scrubber column 6 in the range 5.5-7 and preferably 6-7.

The method also includes cooling the liquid supplied
15 to the NO₂ scrubber column 6. Cooling preferably includes cooling the liquid supplied through the liquid supply line 7.

Naturally the features described may be independently provided from one another.

20 In practice the materials used and the dimensions can be chosen at will according to requirements and to the state of the art.

REFERENCE NUMBERS

- 1 boiler
- 2 flue gas treatment system
- 3 components
- 5 4 condenser
- 5 compressor
- 6 NO₂ scrubber column
- 7 liquid supply line
- 8 liquid recirculation line
- 10 9a feed pump
- 9b recirculation pump
- 9c line
- 10 pump
- 11 heat exchanger
- 15 13 controller
- 15 control valve
- 16 liquid waste line
- 17 controller
- 19 sensor
- 20 20 main flow recirculation
- 21 supply
- 22 return line
- 25 dehydration device
- 26 CO₂ separation system
- 25 27 sequestration unit
- 28 venting

- 29 additional supply
- 40 sensor
- 42 controller
- 50 sensor
- 5 52 heat exchanger

79291-241

13

CLAIMS:

1. A treatment system for a flue gas from a combustion process comprising

a condenser,

5 a compressor for compressing the flue gas deprived of moisture at the condenser,

a NO₂ scrubber column supplied with the compressed flue gas from the compressor,

a liquid supply line for supplying at least a part of liquid
10 condensed at the condenser to the NO₂ scrubber column, and

a liquid recirculation line for recirculating at least a part of the liquid from the NO₂ scrubber column to the condenser.
2. The system according to claim 1, further comprising

a feed pump for supplying liquid to the NO₂ scrubber column,
15 and

a controller for regulating the feed pump on the basis of at least a feature of the liquid supplied to the NO₂ scrubber column.
3. The system according to claim 2, further comprising
20 at least a sensor for the pH of the liquid supplied to the NO₂ scrubber column.
4. The system according to claim 3, wherein the controller controls the feed pump in order to keep the pH of

79291-241

14

the liquid supplied to the NO₂ scrubber column in the range 5.5-7.

5. The system according to claim 3, wherein the controller controls the feed pump in order to keep the pH of
5 the liquid supplied to the NO₂ scrubber column in the range 6-7.

6. The system according to claim 1, further comprising a heat exchanger for cooling the liquid supplied to the NO₂ scrubber column.

10 7. The system according to claim 6, wherein the heat exchanger is on the liquid supply line.

8. A treatment method for a flue gas from a combustion process comprising

15 passing the flue gas through a condenser to condensate moisture contained therein,

compressing the flue gas deprived of moisture at the condenser,

passing the compressed flue gas through a NO₂ scrubber column to remove NO₂,

20 supplying at least a part of liquid condensed at the condenser to the NO₂ scrubber column through a liquid supply line, and recirculating at least a part of the liquid from the NO₂ scrubber column to the condenser.

9. The method according to claim 8, further comprising regulating the supplying of at least a part of the liquid
25 condensed at the condenser to the NO₂ scrubber column on the

79291-241

15

basis of at least a feature of the liquid supplied to the NO₂ scrubber column.

10. The method according to claim 9, wherein the at least a feature of the liquid supplied to the NO₂ scrubber column is
5 the pH.

11. The method according to claim 10, further comprising regulating the feeding in order to keep the pH of the liquid supplied to the NO₂ scrubber column in the range 5.5-7.

12. The method according to claim 10, further comprising
10 regulating the feeding in order to keep the pH of the liquid supplied to the NO₂ scrubber column in the range 6-7.

13. The method according to claim 8, further comprising cooling the liquid supplied to the NO₂ scrubber column.

14. The method according to claim 13, further comprising
15 cooling the liquid supplied through the liquid supply line.

Fig. 1




Fig. 2

