




(86) Date de dépôt PCT/PCT Filing Date: 2001/11/29
(87) Date publication PCT/PCT Publication Date: 2002/07/25
(45) Date de délivrance/Issue Date: 2006/06/27
(85) Entrée phase nationale/National Entry: 2003/07/15
(86) N° demande PCT/PCT Application No.: US 2001/045239
(87) N° publication PCT/PCT Publication No.: 2002/058436
(30) Priorité/Priority: 2001/01/19 (US09/765,851)

(51) Cl.Int./Int.Cl. *H05B 6/80* (2006.01),
B65D 81/34 (2006.01)
(72) Inventeurs/Inventors:
ZENG, NEILSON, CA;
LAI, LAURENCE M. C., CA;
RUSSELL, ANTHONY, CA
(73) Propriétaire/Owner:
GRAPHIC PACKAGING INTERNATIONAL, INC., US
(74) Agent: BLAKE, CASSELS & GRAYDON LLP

(54) Titre : **MATERIAUX D'EMBALLAGE METALLIQUES TOLERANT LES MAUVAISES UTILISATIONS POUR CUISSON
PAR MICRO-ONDES**

(54) Title: **ABUSE-TOLERANT METALLIC PACKAGING MATERIALS FOR MICROWAVE COOKING**



(57) **Abrégé/Abstract:**

An abuse-tolerant microwave food packaging material includes repeated sets of metallic foil or high optical density evaporated material segments (22, 30) disposed on a substrate. Each set of metallic segments (22, 30) is arranged to define a perimeter (24, 32) having a length equal to a predetermined fraction of the operating or effective wavelength of an operating microwave oven. The repeated sets of segments (22, 30) act both as a shield to microwave energy and as focusing elements for microwave energy when used in conjunction with food products, while remaining electrically safe in the absence of the food products.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
25 July 2002 (25.07.2002)

PCT

(10) International Publication Number
WO 02/058436 A1(51) International Patent Classification⁷: **H05B 6/80**(74) Agents: **POLUMBUS, Gary et al.**; DORSEY & WHITNEY LLP, 370 Seventeenth Street, Suite 4700, Denver, CO 80202 (US).

(21) International Application Number: PCT/US01/45239


(22) International Filing Date:
29 November 2001 (29.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/765,851 19 January 2001 (19.01.2001) US(71) Applicant: **GRAPHIC PACKAGING CORPORATION** [US/US]; Suite 250, 14062 Denver West Parkway, Golden, CO 80401 (US).(72) Inventors: **ZENG, Neilson**; 180 Edmonton Drive, North York, Ontario M2J 3X5 (CA). **LAI, Laurence, M.C.**; 887 The Greenway, Mississauga, Ontario L5G 1P7 (CA). **RUSSELL, Anthony**; 13645 RR 2, Rockwood, Ontario N0B 2K0 (CA).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**Declarations under Rule 4.17:**— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations**[Continued on next page]*

(54) Title: ABUSE-TOLERANT METALLIC PACKAGING MATERIALS FOR MICROWAVE COOKING



(57) Abstract: An abuse-tolerant microwave food packaging material includes repeated sets of metallic foil or high optical density evaporated material segments (22, 30) disposed on a substrate. Each set of metallic segments (22, 30) is arranged to define a perimeter (24, 32) having a length equal to a predetermined fraction of the operating or effective wavelength of an operating microwave oven. The repeated sets of segments (22, 30) act both as a shield to microwave energy and as focusing elements for microwave energy when used in conjunction with food products, while remaining electrically safe in the absence of the food products.

**WO 02/058436 A1**

WO 02/058436 A1



- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*
- *entirely in electronic form (except for this front page) and available upon request from the International Bureau*

ABUSE-TOLERANT METALLIC PACKAGING MATERIALS FOR MICROWAVE COOKING

5

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of the filing date of U.S. Patent No. 6,433,322 filed 19 January 2001, which is a continuation-in-part of U.S. Patent No. 6,204,492 filed 20 September 1999.

BACKGROUND OF THE INVENTION

1) Field of the Invention

15 The present invention relates to an improved microwave-interactive cooking package. In particular, the present invention relates to high efficiency, safe and abuse-tolerant susceptor and foil materials for packaging and cooking microwavable food.

2) Description of the Related Art

20 Although microwave ovens have become extremely popular, they are still seen as having less than ideal cooking characteristics. For example, food cooked in a microwave oven generally does not exhibit the texture, browning, or crispness that are acquired when food is cooked in a conventional oven.

A good deal of work has been done in creating materials or utensils that permit food to be cooked in a microwave oven to obtain cooking results similar to that of conventional
25 ovens. The most popular device being used at present is a plain, susceptor material, which is an extremely thin (generally 60 to 100 Å) metallized film that heats under the influence of a microwave field. Various plain susceptors (typically aluminum, but many variants exist) and various patterned susceptors (including square matrix, "shower flower," hexagonal, slot matrix and "fuse" structures) are generally safe for microwave cooking. However, susceptors
30 do not have a strong ability to modify a non-uniform microwave heating pattern in food through shielding and redistributing microwave power. The quasi-continuous electrical nature of these materials prevents large induced currents (so limiting their power reflection capabilities) or high electromagnetic (E-field) strengths along their boundaries or edges. Therefore their ability to obtain uniform cooking results in a microwave oven is quite limited.

Electrically “thick” metallic materials (e.g., foil materials) have also been used for enhancing the shielding and heating of food cooked in a microwave oven. Foil materials are much thicker layers of metal than the thin, metallized films of susceptors. Foil materials, also often aluminum, are quite effective in the prevention of local overheating or hot spots in food cooked in a microwave by redistributing the heating effect and creating surface browning and crisping in the food cooked with microwave energy. However, many designs fail to meet the normal consumer safety requirements by either causing fires, or creating arcing as a result of improper design or misuse of the material.

The reason for such safety problems is that any bulk metallic substance can carry very high induced electric currents in opposition to an applied high electromagnetic field under microwave oven cooking. This results in the potential for very high induced electromagnetic field strengths across any current discontinuity (e.g., across open circuit joints or between the package and the wall of the oven). The larger the size of the bulk metallic materials used in the package, the higher the potential induced current and induced voltage generated along the periphery of the metallic substance metal. The applied E-field strength in a domestic microwave oven might be as high as 15kV/m under no load or light load operation. The threat of voltage breakdown in the substrates of food packages as well as the threat of overheating due to localized high current density may cause various safety failures. These concerns limit the commercialization of bulk foil materials in food packaging.

Commonly owned Canadian Patent No. 2196154 offers a means of avoiding abuse risks with aluminum foil patterns. The structure disclosed addresses the problems associated with bulk foil materials by reducing the physical size of each metallic element in the material. Neither voltage breakdown, nor current overheat will occur with this structure in most microwave ovens, even under abuse cooking conditions. Abuse cooking conditions can include any use of a material contrary to its intended purpose including cooking with cut or folded material, or cooking without the intended food load on the material. In addition, the heating effectiveness of these metallic materials is maximized through dielectric loading of the gaps between each small element that causes the foil pattern to act as a resonant loop (albeit at a much lower Q-factor (quality factor) than the solid loop). These foil patterns were effective for surface heating. However, it was not recognized that a properly designed metallic strip pattern could also act to effectively shield microwave energy to further promote uniform cooking.

Commonly owned U.S. Patent No. 6,133,560 approaches the problem differently by creating low Q-factor resonant circuits by patterning a susceptor substrate. The low Q-factor

operation described in U.S. Patent No. 6,133,560 provides only a limited degree of power balancing.

SUMMARY OF THE INVENTION

5 The present invention relates to an abuse-tolerant microwave packaging material which both shields food from microwave energy to control the occurrence of localized overheating in food cooked in a microwave, and focuses microwave energy to an adjacent food surface.

10 Abuse-tolerant packaging according to the present invention includes one or more sets of continuously repeated microwave-interactive metallic segments disposed on a microwave-safe substrate. Each set of metallic segments defines a perimeter equal to a predetermined fraction of the effective wavelength in an operating microwave oven. Methodologies for choosing such predetermined fractional wavelengths are discussed in U.S. Patent No. 5,910,268, which is incorporated herein by reference. The metallic segments can be foil
15 segments, or may be segments of a high optical density evaporated material deposited on the substrate. The terms "fraction" or "fractional" as used herein are meant in their broadest sense as the numerical representation of the quotient of two numbers, i.e., the terms include values of greater than, equal to, and less than one (1).

20 In a first embodiment, the length of the perimeter defined by a first set of metallic segments is preferably approximately equal to an integer multiple of the effective wavelength of microwaves in an operating microwave oven, such that the length of the perimeter is resonant with the effective wavelength. In a second embodiment, the length of the perimeter defined by the metallic segments is approximately equal to an integer multiple of one-half the effective wavelength of microwaves in an operating microwave oven, such that the length of
25 the second perimeter is quasi-resonant with the effective wavelength.

 Each segment in the first set is spaced from adjacent segments so as to create a (DC) electrical discontinuity between the segments. Preferably, each first set of metallic segments defines a five-lobed flower shape. The five-lobed flower shape promotes uniform distribution of microwave energy to adjacent food by distributing energy from its perimeter
30 to its center.

 Preferably, abuse-tolerant packaging according to the present invention includes a repeated second set of spaced metallic segments that enclose each first set of metallic segments and define a second perimeter. In the first embodiment, this second perimeter preferably has a length approximately equal to an integer multiple of the effective wavelength

- 4 -

5 of microwaves in an operating microwave oven, such that the length of the second perimeter is resonant with the effective wavelength. In the second embodiment, this second perimeter preferably has a length approximately equal to an integer multiple of one-half the effective wavelength of microwaves in an operating microwave oven, such that the length of the second perimeter is quasi-resonant with the effective wavelength.

10

A third embodiment of abuse-tolerant packaging according to the present invention includes, in addition to the second set of metallic segments, a repeated third set of spaced metallic segments that enclose each second set of metallic segments and define a perimeter approximately equal to another predetermined fraction of the effective wavelength of

15

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a detail view of a portion of a sheet of abuse-tolerant microwave
20 packaging material incorporating a repeated pattern of reflective segments according to a first embodiment of the present invention.

Figure 2 is a sectional view of abuse-tolerant microwave packaging material according to the present invention.

Figure 3 is a detail view of a portion of a sheet of abuse-tolerant microwave
25 packaging material incorporating a repeated pattern of reflective segments according to a second embodiment of the present invention.

Figure 4 is a detail view of a portion of a sheet of abuse-tolerant microwave packaging material incorporating a repeated pattern of reflective segments according to a third embodiment of the present invention.

30 Figure 5 is a detail view of a portion of a sheet of abuse-tolerant microwave packaging material according to the third embodiment of the present invention.

Figure 6 is a plan view of a baking disk with a quasi-shielding wall according to a fourth embodiment of the present invention.

- 4a -

5

DETAILED DESCRIPTION OF THE INVENTION

For a better understanding of the invention, the following detailed description refers to the accompanying drawings, wherein preferred exemplary embodiments of the present invention are illustrated and described.

10

The present invention relates to an abuse-tolerant, high heating-efficiency metallic material used in microwave packaging materials. This abuse-tolerant material redistributes incident microwave energy so as to increase reflection of microwave energy while maintaining high microwave energy absorption. A repeated pattern of metallic foil segments can shield microwave energy almost as effectively as a continuous bulk foil material while still absorbing and focusing microwave energy on an adjacent food surface. The metallic

segments can be made of foil or high optical density evaporated materials deposited on a substrate. High optical density materials include evaporated metallic films that have an optical density greater than one (optical density being derived from the ratio of light reflected to light transmitted). High optical density materials generally have a shiny appearance, whereas thinner metallic materials, such as susceptor films have a flat, opaque appearance. Preferably, the metallic segments are foil segments.

The segmented foil (or high optical density material) structure prevents large induced currents from building at the edges of the material or around tears or cuts in the material, thus diminishing the occurrences of arcing, charring, or fires caused by large induced currents and voltages. The present invention includes a repeated pattern of small metallic segments, wherein each segment acts as a heating element when under the influence of microwave energy. In the absence of a dielectric load (i.e., food), this energy generates only a small induced current in each element and hence a very low electric field strength close to its surface.

Preferably, the power reflection of the abuse-tolerant material is increased by combining the material in accordance with the present invention with a layer of conventional susceptor film. In this configuration, a high surface heating environment is created through the additional excitement of the susceptor film due to the composite action of food contacting the small metallic segments. When the food contacts the metallic segments of the abuse-tolerant material according to the present invention, the quasi-resonant characteristic of perimeters defined by the metallic segments can stimulate stronger and more uniform cooking. Unlike a full sheet of plain susceptor material, the present invention can stimulate uniform heating between the edge and center portion of a sheet of the abuse-tolerant metallic material to achieve a more uniform heating effect. The average width and perimeter of the pattern of metallic segments will determine the effective heating strength of the pattern and the degree of abuse tolerance of the pattern. However, the power transmittance directly toward the food load through an abuse-tolerant metallic material according to the present invention is dramatically decreased, which leads to a quasi-shielding functionality. In the absence of food contacting the material, according to the present invention, the array effect of the small metallic segments still maintains a generally transparent characteristic with respect to microwave power radiation. Thus, the chances of arcing or burning when the material is unloaded or improperly loaded are diminished.

Preferably, each metallic segment has an area less than 5 mm^2 and the gap between each small metallic strip is larger than 1 mm. Metallic segments of such size and

arrangement reduce the threat of arcing that exists under no load conditions in average microwave ovens. When, for example, food, a glass tray, or a layer of plain susceptor film contacts the metallic segments, the capacitance between adjacent metallic segments will be raised as each of these substances has a dielectric constant much larger than a typical
5 substrate on which the small metal segments are located. Of these materials, food has the highest dielectric constant (often by an order of magnitude). This creates a continuity effect of connected metallic segments which then work as a low Q-factor resonate loop, power transmission line, or power reflection sheet with the same function of many designs that would otherwise be unable to withstand abuse conditions. On the other hand, the pattern is
10 detuned from the resonant characteristic in the absence of food. This selectively tuned effect substantially equalizes the heating capability over a fairly large packaging material surface including areas with and without food.

Note, the effective wavelength λ_{eff} of microwaves in a dielectric material (e.g., food
15 products) is calculated by the formula $\lambda_{eff} = \frac{\lambda_0}{\sqrt{\epsilon}}$, where λ_0 is the wavelength of microwaves in air and ϵ is the dielectric constant of the dielectric material. According to the present invention, the perimeter of each set of metallic segments is preferably a predetermined fraction of the effective wavelength of microwaves in an operating microwave oven. The predetermined fraction is selected based on the properties of the food to be
20 cooked, including the dielectric constant of the food and the amount of bulk heating desired for the intended food. For example, a perimeter of a set of segments can be selected to be equal to predetermined fractions or multiples of the effective microwave wavelength for a particular food product. Furthermore, a resonant fraction or multiple of the microwave wavelength is selected when the microwave packaging material is to be used to cook a food
25 requiring strong heating, and a smaller, high density, nested perimeter of a quasi-resonant, fractional wavelength is selected when the microwave packaging material is used to cook food requiring less heating, but more shielding. Therefore, the benefit of concentric but slightly dissimilar perimeters is to provide good overall cooking performance across a greater range of food properties (e.g., from frozen to thawed food products).

30 Turning to the drawing figures, Figures 1, 3, and 4 show three respective embodiments of patterns of metallic foil segments according to the present invention. In a first embodiment in accordance with the present invention shown in Figure 1, a first set of spaced bent metallic segments 22 define a first perimeter, or loop, 24. According to the

present invention, the length of the first perimeter 24 is preferably approximately equal to an integer multiple of the effective wavelength of microwaves in a microwave oven, such that the length of the first perimeter 24 is resonant with the effective wavelength. The length of the first perimeter 24 of the first set of metallic segments 22 may be other fractions of the effective wavelength depending upon the food product and the desired cooking result. In a preferred first embodiment, the first perimeter 24 is approximately equal to one full effective wavelength of microwaves in an operating microwave oven.

Preferably the first set of metallic segments 22 are arranged to define a five-lobed flower shape as the first perimeter 24, as seen in each of the respective embodiments shown in Figures 1, 3, and 4. The five-lobed flower arrangement promotes the even distribution of microwave energy to adjacent food. Metallic segments 22 defining other shapes for the first perimeter or loop 24 such as circles, ovals, and other curvilinear shapes, preferably symmetrical curvilinear shapes, triangles, squares, rectangles, and polygonal shapes, preferably right polygons, and even more preferably equilateral polygonal shapes, are within the scope of the present invention.

As used herein the term "symmetrical curvilinear shape" means a closed curvilinear shape that can be divided in half such that the two halves are symmetrical about an axis dividing them. As used herein, the term "right polygon" means a polygon that can be divided in half such that the two halves are symmetrical about an axis dividing them. Equilateral polygons would therefore be a subset of right polygons. It should be remembered that all of these shapes, which are closed by definition, are merely patterns that the sets of metallic segments follow, but the metallic segments themselves are not connected and are therefore not closed.

Preferably, each first set of metallic segments 22 is accompanied by an enclosing second set of straight metallic segments 30. The second set of metallic segments 30 also preferably defines a second perimeter 32 preferably having a length approximately equal to an integer multiple of the effective wavelength of microwaves in an operating microwave oven, such that the length of the second perimeter 32 is resonant with the effective wavelength. The length of the second perimeter 32 of the second set of metallic segments 30 may be other fractions of the effective wavelength depending upon the food product and the desired cooking result.

The first and second sets of metallic segments 22, 30 are arranged to define a pattern (only partially shown in Figure 1, but fully shown in Figure 5, which is described later), which is continuously repeated to create a desired quasi-shielding effect. Preferably, the

second set of metallic segments 30 (the outer set of segments in the first embodiment) define a hexagonal second perimeter 32, a shape that allows each second set of metallic segments 30 to be nested with adjacent second sets of metallic segments 30. Nested arrays of resonant hexagonal loops are described in commonly owned U.S. Patent No. 6,133,560 and are discussed in more detail in reference to Figure 5. The hexagon is an excellent basic polygon to select due to its ability to nest perfectly along with its high degree of cylindrical symmetry.

Other shapes that can be used to define the second perimeter 32, and that are within the scope of this invention, include circles, ovals, and other curvilinear shapes, preferably symmetrical curvilinear shapes, triangles, squares, rectangles, and other polygonal shapes, preferably right polygonal shapes, and even more preferably equilateral polygonal shapes. These shapes are preferably configured in arrays such that they are similarly capable of nesting. In addition, the arrays of shapes defining the second perimeter 32 need not be repetitive of a single shape, but instead can be combinations of various shapes, preferably capable of nesting. For example, an array of shapes defining the second perimeter 32 might be an array of nested hexagons and polygons, as in the patchwork of a soccer ball.

The first and second sets of metallic segments 22, 30 are preferably formed on a microwave transparent substrate 34, as shown in Figure 2, by conventional techniques known in the art. One technique involves selective demetalization of aluminum having a foil thickness and which has been laminated to a polymeric film. Such demetalizing procedures are described in commonly assigned U.S. Patent Nos. 4,398,994, 4,552,614, 5,310,976, 5,266,386 and 5,340,436. Alternatively, metallic segments may be formed on a susceptor film (i.e., a metallized polymeric film) using the same techniques. Segments of high optical density evaporated materials can be produced by similar etching techniques or by evaporating the material onto a masked surface to achieve the desired pattern. Both techniques are well known in the art. Figure 2 shows a schematic sectional view of metallic segments 30 formed on a substrate 34 and including a susceptor film 36 having a metallized layer 37 and a polymer layer 39 to form a microwave packaging material 38 according to the present invention.

In a second embodiment shown in Figure 3, a first set of bent metallic segments 40 define a first perimeter 42, preferably having a length equal to an integer multiple of one-half an effective wavelength (i.e., 0.5λ , 1λ , 1.5λ , etc.) of microwaves in an operating microwave oven. Like the first embodiment, the first perimeter 42 preferably defines a multi-lobed shape in order to evenly distribute microwave energy. Also as in the first embodiment, the first perimeter 42 may define various other shapes as described above. The smaller, more

densely nested, first perimeter 42 pattern shown in Figure 3 has a higher reflection effect under light or no loading than the larger first perimeter 24 pattern shown in Figure 1, at the expense of a proportionate amount of microwave energy absorption and heating power. A second set of metallic segments 44 encloses the first set of metallic segments 40 in the second embodiment, and defines a second perimeter 46, preferably of a length approximately equal to an integer multiple of one-half the effective wavelength of microwaves in an operating microwave oven. Preferably, the second set of metallic segments 44 are arranged in a nested configuration and define a hexagonal second perimeter. Again, the second perimeter 46 may be configured in many other arrays of shapes and combinations thereof as described above with reference to the first embodiment.

A third embodiment of a pattern of metallic segments, in accordance with the present invention, is shown in Figure 4. The third embodiment includes a third set of metallic segments 60 in addition to first and second sets of metallic segments 62, 64 defining first and second perimeters 63, 65 similar to those in the first embodiment. The third set of metallic segments 60 encloses the second set of metallic segments 64 and defines a third perimeter 68. Preferably, in the pattern according to the third embodiment shown in Figures 4 and 5, the second set of metallic segments 64 defines the second perimeter 65 with a length approximately equal to an integer multiple of the effective wavelength of microwaves in an operating microwave oven, such that the length of the second perimeter 65 is resonant with the effective wavelength. The third set of metallic segments 60 then defines the third perimeter 68, preferably with a similar, but deliberately altered, perimeter length approximately equal to a predetermined fraction of the effective wavelength of microwaves in an operating microwave oven.

Preferably the third set of metallic segments 60 defines a hexagonal third perimeter 68. However, other shapes can be used to define the third perimeter 68 and include circles, ovals, and other curvilinear shapes, preferably symmetrical curvilinear shapes, triangles, squares, rectangles, and other polygonal shapes, preferably right polygonal shapes, and even more preferably equilateral polygonal shapes. These shapes are preferably configured in arrays such that they are similarly capable of nesting. In addition, the arrays of shapes defining the third perimeter 68 need not be repetitive of a single shape, but instead can be combinations of various shapes, preferably capable of nesting. For example, an array of shapes defining the second perimeter might be an array of nested hexagons and polygons, as in the patchwork of a soccer ball.

In the third embodiment, additional metallic segments 70a, 70b, and 70c are preferably included within each lobe 72 (70a), between each lobe 72 (70b), and at a center 74 (70c) of the five-lobed flower shape defined by the first set of metallic segments 62. The additional metallic segments 70a and 70b that are arranged between and within the lobes 72
5 are preferably triangular shaped with vertices pointing in the direction of the center 74 of the flower shape. The additional segments 70a, 70b, and 70c further enhance the even distribution of microwave energy, in particular from the edges of the perimeter to the center of the perimeter.

Similar to the first embodiment, first and second sets of metallic segments 40, 44 in
10 the second embodiment, and first, second, and third sets of metallic segments 62, 64, 60 in the third embodiment are preferably formed on a microwave transparent substrate in the same manner as discussed herein with reference to Figure 2. An example of a sheet of microwave packaging material according to the present 30 invention is shown in Figure 5. A pattern according to the third embodiment shown in Figure 4 is repeated on a substrate 76 which may
15 be microwave transparent (e.g., paperboard), or include a susceptor film. Preferably, the third set of metallic segments 60 is repeated with the first and second sets of metallic segments 62, 64 in a nested array 78 best seen in Figure 5. A nested array 78 is an arrangement wherein each of the metallic segments in an outer set of metallic segments is shared by adjacent sets of metallic segments (i.e., one strip of metallic segments divides one
20 first or second set of segments from another first or second set). The nested array 78 contributes to the continuity of the overall pattern and therefore to the quasi-shielding effect of the present invention. Furthermore, outer sets of metallic segments are preferably arranged to define a hexagonal shape to better facilitate a nested array 78 of sets of metallic segments.

25 Further advantages and features of the present invention are discussed in the context of the following examples.


EXAMPLE 1

In Example 1, the power Reflection/Absorption/Transmission (RAT) characteristics
30 of plain susceptor paper and arrays of metallic segments formed on susceptor paper according to the present invention are compared. The metallic segments were arranged in a nested pattern according to the second and third embodiments shown in Figures 3 and 4. Both were measured using a microwave Network Analyzer (NWA), which is an instrument commonly used in the art for measuring microwave device characteristics at low power levels. Tests

were also conducted in a high power test set with a wave guide type WR430 under open load operation. The table and graph below show that a susceptor including a nested segmented foil pattern as shown in Figure 3 performed at a higher power reflection capacity than the plain susceptor at an E-field strength of 6 kV/m under an open load. The power reflection for a plain susceptor reaches 54% at low E-field strength radiation and 16% at high E-field strength radiation. Power reflection of a susceptor laminated to arrays of metallic segments according to the present invention susceptor provides 77% reflection at low E-field radiation and 34% at high E-field radiation. The table and graph demonstrate that a microwave packaging material including a repeated pattern of metallic segments according to the present invention has much improved shielding characteristics compared to plain susceptor material.

Applied Electric Field (kV/m)	Plain Suceptor Transmission	Reflection	Absorption	Present Invention Transmission	Reflection	Absorption
0.0	6%	54%	40%	1%	77%	21%
3.9	14%	46%	40%	4%	68%	28%
5.6	50%	16%	34%	40%	37%	26%
6.8	57%	15%	29%	45%	33%	21%
7.9	66%	14%	21%	69%	21%	11%
8.8	65%	13%	22%	67%	20%	14%
9.6	66%	12%	22%	67%	19%	14%


Reflection Characteristics



EXAMPLE 2

Example 2 shows RAT performance of the third embodiment of the present invention (Figures 4 and 5) laminated on a susceptor. The measurements were taken with a layer of pastry in contact with the packaging material according to the present invention. The quasi-resonance and power reflection effect occurs when the food is in contact with the metallic segments so as to complete the segmented pattern. The test showed the power reflection of the present invention to be between 73% to 79%. (It is assumed that plain bulk metallic foil has a power reflection of 100%.) This test demonstrates that the present invention can be used as a quasi-shielding material in microwave food packaging. The benefit of the present invention is that, unlike bulk metallic foil, it is abuse-tolerant and safe for microwave oven cooking, yet still has much of the shielding effect of bulk metallic foil when loaded with food (even under the very high stress conditions of this test).


Applied Electric Field (kV/m)	Present Invention Transmission	Reflection	Absorption
0.0	1%	79%	20%
3.9	4%	70%	26%
5.6	4%	73%	23%
6.8	4%	86%	10%
7.9	4%	82%	15%
8.8	12%	87%	1%
9.6	21%	78%	1%



EXAMPLE 3


Example 3 shows the stability of the power reflection performance of both a plain susceptor and the microwave packaging material according to the third embodiment (Figures 4 and 5) of the present invention laminated to a susceptor under increasing E-field strengths in open load operation. RAT characteristic data of each material was measured after two minutes of continuous radiation in each level of E-field strength. The test showed that the metallic segment/susceptor laminate material is also more durable than the plain susceptor. While not wishing to be bound by one particular theory, the inventors presently believe that the increased durability of the present invention results from the metallic segments imparting mechanical stability to the polymer layer commonly included in susceptor films.

Packaging	E-Field Strength	Reflection	Transmission	Absorption	Film Appearance
Plain Susceptor or PaperBoard	0	63%	4%	33%	no crack
Plain Susceptor or PaperBoard	5	19%	52%	28%	visible crack
Plain Susceptor or PaperBoard	10	9%	80%	11%	crack
Present Invention	0	77%	9%	14%	no crack
Present Invention	5	36%	50%	14%	no crack
Present Invention	10	11%	75%	14%	slight cracked lines



EXAMPLE 4

Temperature profiles of frozen chicken heated using sleeves of a patterned metallic segment/susceptor laminate according to the present invention are shown in the graph below. Three fiber-optic temperature probes were placed at different portions of frozen chicken to monitor the cooking temperature. The test results indicated that the patterned metallic segments included with a susceptor sleeve deliver a high surface temperature that causes good surface crisping of the chicken. Note that the center of the chicken heated after the surface and tip of the chicken were heated. This is close to the heating characteristics that would be observed in a conventional oven. The chicken cooked using microwave packaging according to the present invention achieved comparable results to a chicken cooked in a conventional oven. The chicken had a browned, crisped surface and the meat retained its juices.

Frozen Chicken Thigh (177 g) in Breadcrumbs**EXAMPLE 5**

A combined patterned metallic segment and susceptor lid according to the present invention as seen in Figure 5 was used for microwave baking of a 28 oz. frozen fruit pie. It takes approximately 15 minutes in a 900 watt power output microwave oven to bake such a pie. The lid of this cooking package used the patterned metallic segment and susceptor sheet

with periodical array of the basic structure as shown in Figures 4 and 5. Both the lid and tray are abuse-tolerant and 10 safe for operation in a microwave oven. Testing showed this lid generated an even baking over the top surface. The lid can be exposed to an E-field strength as high as 15 kV/m unloaded by food without any risk of charring, arcing, or fire in the
5 packaging or paper substrate tray.

EXAMPLE 6

In another experiment, the baking results for raw pizza dough using two kinds of reflective walls were compared. One wall was made with an aluminum foil sheet and the
10 other was made from a packaging material according to the present invention. The quasi-shielding wall according to the present invention is shown in Figure 6. A 7 μ m thick aluminum foil was used in both wall structures (i.e., the metallic segments of the packaging material according to the present invention are 7 μ m thick). Fairly similar baking performance was achieved in both pizzas. Thus the packaging material according to the
15 present invention achieved the same good results as the less safe bulk foil.

The present invention can be used in several formats such as in baking lids, trays, and disks, with or without a laminated layer of susceptor film. In general, a susceptor laminated with the present invention is able to generate higher reflection of radiation power than a plain
20 susceptor at the same level of input microwave power. The present invention can be treated as an effective quasi-shielding material for various microwave food-packaging applications.

The present invention has been described with reference to a preferred embodiment. However, it will be readily apparent to those skilled in the art that it is possible to embody the invention in specific forms other than as described above without departing from the spirit of the invention. The preferred embodiment is illustrative and should not be considered
25 restrictive in any way. The scope of the invention is given by the appended claims, rather than the preceding description, and all variations and equivalents that fall within the range of the claims are intended to be embraced therein.

CLAIMS

What is claimed is:

1. An abuse-tolerant microwave packaging material comprising a plurality of a
5 first set of segments formed of a microwave energy reflective material, the first sets of
segments supported on a substrate in a repeated pattern, wherein each first set of segments
defines a first perimeter having a length approximately equal to a first predetermined fraction
of an effective wavelength of microwaves in an operating microwave oven, wherein each
10 segment in each first set of segments is spaced apart from adjacent segments, and wherein the
first perimeter comprises at least one shape selected from the group of shapes comprising: a
circle, an oval, a curvilinear shape, a symmetrical curvilinear shape, a triangle, a square, a
rectangle, a polygon, a right polygon, and an equilateral polygon.
2. An abuse-tolerant microwave packaging material as described in claim 1
15 further comprising a plurality of a second set of segments formed of a microwave energy
reflective material, the second sets of segments supported on the substrate in a repeated
pattern, wherein each second set of segments defines a second perimeter enclosing at least
one of the first sets of segments, the second perimeter having a length approximately equal to
a second predetermined fraction of the effective wavelength of microwaves in the operating
20 microwave oven, wherein each segment of each second set of segments is spaced apart from
adjacent segments, and wherein the second perimeter comprises at least one shape selected
from the group of shapes comprising: a circle, an oval, a curvilinear shape, a symmetrical
curvilinear shape, a triangle, a square, a rectangle, a polygon, a right polygon, and an
equilateral polygon.
3. An abuse-tolerant microwave packaging material as described in claim 2
25 further comprising a plurality of a third set of segments formed of a microwave energy
reflective material, the third sets of segments supported on the substrate in a repeated pattern,
wherein each third set of segments defines a third perimeter enclosing at least one of the
repeated second sets of segments, the third perimeter having a length approximately equal to
a third predetermined fraction of the effective wavelength of microwaves in the operating
30 microwave oven, wherein each segment of each third set of segments is spaced apart from
adjacent segments, and wherein the third perimeter comprises at least one shape selected
from the group of shapes comprising: a circle, an oval, a curvilinear shape, a symmetrical
curvilinear shape, a triangle, a square, a rectangle, a polygon, a right polygon, and an
equilateral polygon.

4. The abuse-tolerant microwave packaging material of claim 2, wherein each of the second sets of segments is nested with adjacent second sets of segments.

5. The abuse-tolerant microwave packaging material of claim 3, wherein each of the third sets of segments is nested with adjacent third sets of segments.

5 6. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein each segment has an area less than 5 mm^2 .

7. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein the substrate includes a susceptor film.

8. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein
10 the substrate is microwave transparent.

9. The abuse-tolerant microwave packaging material of claim 8, wherein the substrate is a paper based material.

10. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein the microwave energy reflective material comprises a metal material comprised of at least
15 one of the following: metal foil and a deposition of a high optical density evaporated material on the substrate.

11. The abuse-tolerant microwave packaging material of claim 10, wherein the metal material comprises aluminum.

12. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein
20 the equilateral polygon is a hexagon.

13. The abuse-tolerant microwave packaging material of claim 1, 1, or 2, wherein the first predetermined fraction of the effective wavelength is an integer multiple of the effective wavelength, such that the length of the first perimeter is resonant with the effective wavelength.


25 14. The abuse-tolerant microwave packaging material of claim 1, 2, or 3, wherein the first predetermined fraction of the effective wavelength is an integer multiple of one-half the effective wavelength, such that the length of the first perimeter is quasi-resonant with the effective wavelength.

15. The abuse-tolerant microwave packaging material of claim 2 or 3, wherein the
30 second predetermined fraction of the effective wavelength is an integer multiple of the effective wavelength, such that the length of the second perimeter is resonant with the effective wavelength.



16. The abuse-tolerant microwave packaging material of claim 2 or 3, wherein the second predetermined fraction of the effective wavelength is an integer multiple of one-half

the effective wavelength, such that the length of the second perimeter is quasi-resonant with the effective wavelength.


1/5

**Fig. 1**


2/5

**Fig. 2****Fig. 3**


3/5

**Fig. 4**

4/5

**Fig. 5**

5/5

**Fig. 6**

