

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
24 July 2008 (24.07.2008)

PCT

(10) International Publication Number
WO 2008/087181 A1

(51) International Patent Classification:

F03D 1/00 (2006.01) *E02D 27/42* (2006.01)
F03D 11/04 (2006.01) *E04H 12/28* (2006.01)

(21) International Application Number:

PCT/EP2008/050491

(22) International Filing Date: 17 January 2008 (17.01.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

07100768.6 18 January 2007 (18.01.2007) EP

(71) Applicant (for all designated States except US):
ECOTECNIA ENERGÍAS RENOVABLES, S. L.
[ES/ES]; C. Roc Boronat, 78, E-08005 Barcelona (ES).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PUIGCORBÉ PUNZANO, Jordi** [ES/ES]; Ecotecnia Energías Renovables, S. L., C. Roc Boronat, 78, E-08005 Barcelona (ES). **ELKOROBEREZIBAR MARKIEGI, Enrique** [ES/ES]; LKS Ingeniería, Paseo José M^a Arizmendiarrieta, 5, 4^o, E-20500 Arrasate (guipuzkoa) (ES).

(74) Agent: **BARLOCCI, Anna**; ZBM Patents, S. L., Balmes, 114 4^o, E-08008 Barcelona (ES).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

- with international search report

[Continued on next page]

(54) Title: JOINING DEVICE FOR HYBRID WIND TURBINE TOWERS



WO 2008/087181 A1

(57) Abstract: A joining device (8) for hybrid wind turbine towers (5) intended for the fixation of a metal portion (6) of a wind turbine tower (5) to a concrete portion (7) of said wind turbine (1) which comprises a metal body (9) having a generally tubular configuration that is suitable to be fixed to the metal portion (6) of the tower (5) which in use is adjacent to the concrete portion (7), and suitable for being at least partially embedded into said concrete portion (7), said metal body (9) being provided with a number of anchoring openings (11) adapted such that the material of the concrete portion (7) passes therethrough. A hybrid 10 wind turbine tower (5) comprises such a joining device (8) provided between one metal portion (6) and one concrete portion (7).



- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Joining device for hybrid wind turbine towers

Field of the invention

5 The present invention relates to a joining device for hybrid wind turbine towers that is intended for the fixation of a metal portion of a wind turbine tower to a concrete portion of the wind turbine.

The invention further relates to a hybrid wind turbine tower that comprises at 10 least a metal portion and at least a concrete portion and which is further provided with said joining device between said metal/concrete portions.

Background of the invention

15 The technological evolution in wind power generation is involving increasingly larger and more powerful machines which, in conjunction with taller towers, increase the output power generated by the wind. The development of taller towers has to be done according to different rules related to design criteria such as load, material strength and dynamic behavior as well as construction, 20 transportation and installation conditions.

Up to 80 m, towers for wind power applications have been made basically using steel tubular sections. Taller towers involving high loads require more 25 resistant structures. Due to transportation problems, bottom diameters larger than 4.5 m are not possible. This requires the steel plate thickness to be increased up to values that make the tower cost to be increased.

The use of concrete for constructing certain parts of wind turbines towers (particularly at the bottom of the tower) is a prominent alternative. Preliminary 30 cost investigations have clearly shown that an improvement in tower costs can be achieved by substituting steel bottom portions by concrete bottom portions, specially in tower heights above 80 m. Moreover, despite the material used in the construction, the design of the concrete portions has to be carried out in accordance with the same rules that for steel portions, that is, loads, strength 35 and mainly dynamic behavior. In order to complain with the dynamic behavior,

thin-walled concrete portions have to be designed. Nevertheless, such a thin-walled concrete portion design leads to extra complexity in tower design.

Shear strength connections, such as shear studs or the like, are in general not 5 valid in such applications due to geometrical complexity in its construction (steel reinforcement layout) and due to dimensional limitations of the tower wall.

WO2005015013 discloses a tower for a wind turbine comprising a concrete 10 tower segment and a steel tower segment having an end portion embedded into the concrete tower segment. The steel tower segment within its embedded end portion comprises anchoring elements. Said anchoring elements project radially from an inner or an outer surface or both inner and outer surfaces of the wall of the steel tower segment. This however does not overcome the 15 above mentioned problem of an easy steel-concrete integration in concrete thin-walled towers in wind turbine applications. This is because a very large concrete wall thickness is needed in the tower design disclosed in this document for withstanding horizontal load components resulting from such protruding elements.

20

Description of the invention

It is an object of the present invention to provide a joining device for hybrid wind turbine towers having an easy integration with concrete thin-walled 25 towers and providing transmission of axial loads between steel and concrete portions of the tower, thus avoiding geometric stress concentrations.

According to a first aspect, the invention provides a joining device for a hybrid wind turbine tower. The wind turbine has a metal portion and a concrete 30 portion. The joining device of the invention is suitable for effectively and reliably fixing said metal portion to said concrete portion in a simple way.

For this purpose, the joining device of the invention comprises a metal body that is intended for being at least partially embedded in the concrete portion 35 and fixed to the metal portion of the tower which in use is adjacent to the

concrete portion.

This metal body has a generally tubular configuration that may be cylindrical or polygonal in shape. In some cases, the metal body could have a frusto conical 5 geometry in combination with said metal body shapes.

The metal body is provided with a number of anchoring openings that are adapted such that the material of the concrete portion passes therethrough.

10 These anchoring openings may have variable dimensions according to requirements. They may be arranged at a defined spatial distribution in order to control and accommodate the shear strength resulting in the metal portion and the concrete portion of the tower in use, that is, when the tower structure is finally assembled and operative.

15

The metal body is provided with a connecting edge at one end thereof that is adapted to connect the metal body to the metal portion of the tower. This connecting edge comprises a L or T shaped flange welded to the metal body.

20 In one embodiment, said anchoring openings in the metal body are formed in the tubular wall thereof, but they may be formed elsewhere according to requirements.

In a further embodiment of the invention, the metal body of the device of the 25 present invention includes a number of plates projecting therefrom. These plates may be arranged at an outer portion of the metal body, that is, projecting outwards therefrom and/or arranged at an inner portion of the metal body, that is, projecting inwards therefrom. Plates may extend substantially along the length of the metal body but, in general, plate length will depend on 30 the number of anchoring openings formed therein.

Alternative or additionally, the anchoring openings may be formed in said plates so that the material of the concrete portion passes therethrough.

35 These anchoring openings (whether they are formed in the tubular wall and/or

the plates of the metal body) may be of different shapes and configuration according to requirements. For example, at least some of said openings may be circular or elliptical in shape. Openings may be alternatively drop-shaped.

5 In any case, said anchoring openings may have a size decreasing (or increasing) in a direction towards the top of the tower and/or at least some of them may widen from the edge of the plate in a direction towards the metal body. With this decreasing (or decreasing) size arrangement, the stress distribution would be almost constant along the metal body.

10

Said variations in the size and the arrangement of the anchoring openings in the metal plates, as well as the number of said openings, are according to the mechanical properties (rigidity, ductility and strength) required for the steel-concrete interface.

15

In the joining device of the invention, loads are transmitted to the metal body through the anchoring openings which loads are substantially free of horizontal component, i.e. they are mostly axial loads. It is to be noted that in the embodiment in which the metal body has plates, the plates only serve as a 20 carrier for such anchoring openings.

In a preferred embodiment, the plates project substantially perpendicular to said metal body but it an arrangement in which plates project from the metal body forming an angle thereto is further envisaged.

25

The configuration of the aforescribed joining device may of course be combined with other solutions for hybrid tower applications involving means for fixing the metal/concrete portions of the wind turbine tower, such as anchoring protruding elements or the like.

30

A joining device for fixing a metal portion of a wind turbine tower to a concrete portion of said wind turbine according to the invention has a simple construction that permits an easy and quick assembly with a construction having a high mechanical performance. The joining device of the invention 35 further provides a good axial concrete-steel interface that is suitable for any

hybrid tower structure for a wind turbine. The invention is specially suitable for thin-walled concrete portions in wind turbine towers.

According to a second aspect of the invention there is provided a hybrid wind 5 turbine tower comprising at least a metal portion and at least a concrete portion. Once such portions are all joined to each other, they form the whole tower of a hybrid wind turbine.

The hybrid wind turbine tower of the invention includes the previously 10 described joining device of the invention. The joining device is provided between one metal portion and one concrete portion of the hybrid tower.

Brief description of the drawings

15 *A particular embodiment of a joining device for a hybrid wind turbine tower according to the present invention will be described in the following, only by way of non-limiting example, with reference to the appended drawings, in which:

20 Fig.1 is an overview of a wind turbine with a hybrid tower having a joining device according to the present invention;

Fig. 2 is an elevational view of one embodiment of the joining device of the invention;

25

Fig. 3 is a perspective view of a further embodiment of the joining device of the invention;

30 Figs.4a-4e are plan views showing several embodiments of plates of the metal body having different types of anchoring holes; and

Fig. 5 is an enlarged view in which part of a metal body wall is shown having several metal plates formed therein.

Detailed description of particular embodiments

Figure 1 shows a wind turbine generally indicated at 1. Wind turbine 1 has a nacelle 2 with a rotor 3 carrying blades 4. The nacelle 2 is rotatably mounted at 5 the top of a ninety meter high wind turbine hybrid tower 5.

This hybrid tower 5 comprises a metal portion 6, e.g. made of steel and a concrete portion 7 located below said metal portion 6. Concrete portion 7 is fitted in a foundation 7a. Portions 6, 7 are both connected to each other by a 10 joining device 8, that is provided between the metal portion 6 and one concrete portion 7 of the hybrid tower 5.

Joining device 8 provides a steel-concrete interface and it comprises a metal body 9 having a diameter of, for example, less than 4500 mm (for example 15 4260 mm) for being compatible with road transport. Two different embodiments of this joining device 8 are shown in figs. 2 and 3.

The metal body 9 is intended for being at least partially embedded in the concrete portion 7 when in use and fixed to the metal portion 6 of the hybrid 20 tower 5 as shown in fig. 2. For this purpose, the metal body 9 is provided with a L or T shaped connecting edge 10 at the upper end thereof for connecting the metal body 9 to the metal portion 6 of the tower 5.

The metal body 9 has a generally tubular configuration (see fig. 3). In one 25 embodiment, the tubular metal body 9 may be cylindrical in shape as shown in said figure 3. In other possible embodiments, the metal body 9 can be polygonal. In the embodiment of the metal body 9 shown in figure 2, the metal body 9 has a frusto conical geometry.

30 In both embodiments of the metal body 9 shown in said figures 2 and 3, the metal body 9 is provided with a number of anchoring openings 11 adapted such that the material of the concrete portion 7 passes therethrough.

In use (when the tower structure is assembled and operative), resulting loads 35 in the metal body 9 and the concrete portion 7 are transmitted by the

anchoring openings 11 to the to the metal portion 6 of the tower 5.

In the embodiment of the metal body 9 shown in the figure 2, the metal body 9 has a number of plates 13 projecting therefrom. The plates 13 in the metal 5 body 9 may project outwards from the tubular wall 12 and/or inwards therefrom.

The plates 13 extend along the length of the metal body 9 but in this embodiment they do not completely cover the entire length of the metal body 9 10 as shown in figure 2. Plate length depend on the opening configuration, as explained further on.

The plates 13 may project perpendicular to the metal body 9 but they may project therefrom forming an angle to the metal body 9 as shown in the 15 embodiment of fig, 5 in which pairs of pates 13 project from the tubular wall 12 of the metal body 9 forming an angle to each other and to said wall 12 substantially different from 90°.

The anchoring openings 11 in the metal body 9 may be formed anywhere 20 therein. For example, they may be formed in the tubular wall 13 of the metal body 9, as in the embodiment shown in the figure 3, or they may additionally be formed in the plates 13.

The length of the plates 13, as noted above, depends on the number of 25 anchoring openings 11 formed therein. More particularly, the minimum plate length (plate 13 having circular openings 11) is determined by:

$$L_{\min} \geq \left(\frac{n^{\circ} \phi \cdot t \cdot 6 \cdot f_{ck} \cdot \sqrt{3} \cdot \beta}{2 \cdot a \cdot f_{yk}} \right)$$

where:

30 L_{\min} is the minimum opening length, in mm;
 n° is the number of anchoring openings formed in the plate;
 ϕ is the opening diameter, in mm;
 t is the plate thickness, in mm;

f_{ck} is the characteristic concrete compressive strength, in MPa;
 f_{yk} is the characteristic metal tensile strength of the plates or the metal portion, in MPa;
 β is a coefficient that depends on the type of the plate steel; and
5 a is the welding-neck thickness.

These anchoring openings 11 (whether they are formed in the tubular wall and/or the plates of the metal body) may be of different size, shape and configuration according to requirements for the steel-concrete interface (joining 10 device 8) and the mechanical properties (rigidity, ductility and strength) required therefor.

Openings 11 may be arranged at different defined spatial distributions (for example in vertical rows as in the embodiment depicted in figure 3) which 15 again will depend on the requirements. In the embodiment shown in figure 3, the plates 13 have a series of vertical rows with seventeen circular openings 11.

In one example, at least some of said anchoring openings 11 may be circular 20 as in the embodiment depicted in figures 3, 4c-e, or elliptical as in the embodiment depicted in the figures 2 and 4b. Openings may be alternatively drop-shaped, as shown in the embodiment of fig. 4a.

The size of the anchoring openings 11 may be constant, as in the 25 embodiments depicted in figs. 2, 3, 4a, 4b, 4d or 4e. In other cases it could be interesting the size of the anchoring openings 11 to be decreasing (or increasing), as shown in the embodiment in fig. 4c, from e.g. 12,5 mm (top opening) to 25 mm (bottom opening). In this embodiment, it is preferred that the size of the anchoring openings 11 decreases in a direction towards the top 30 of the tower 5 so that stress distribution is almost constant along the metal body 9.

The centre-to-centre distance of the anchoring openings 11 may be constant, as in the embodiments depicted in figs. 3, 4a, 4b, 4c, and 4d, but it may be 35 varying as shown in the embodiment of fig. 4e. In this particular case, said

centre-to-centre distance of the anchoring openings 11 decreases in a direction towards the top of the tower 5.

In the case of plates 13 having circular openings 11 (figures 3, 4c, 4d, 4e) the 5 minimum opening centre-to-centre distance is determined by:

$$s_{\min} \geq \left(1 + \frac{\sqrt{3}}{2} \cdot 6 \cdot \frac{f_{ck}}{f_{yd}} \cdot \frac{1}{1.25} \right) \cdot \phi$$

where:

10 s_{\min} is the minimum opening centre-to-centre distance, in mm);
 f_{ck} is the characteristic concrete compressive strength, in MPa;
 f_{yk} is the characteristic metal tensile strength of the plates or the metal portion, in MPa; and
 ϕ is the opening diameter in mm.

15 At least some of the anchoring openings 11 may widen from the edge 14 of the corresponding plate 13 in a direction towards the metal body 9, as shown in the embodiment of fig. 4a (incomplete openings). This embodiment is particularly preferred in combination with drop-shaped configuration of the anchoring openings 11 as shown in fig. 4a.

20 The anchoring openings 11 serve the purpose of transmitting loads to the metal body 9 and therefore to the metal portion 6 of the hybrid tower 5. These loads transmitted to the metal body are substantially free of horizontal component, i.e. they are mostly axial loads since no protrusions are used in 25 the configuration of the joining device 8. When a metal body 9 fitted with plates 13 is used, such plates only serve as a carrier for the anchoring openings 11 and no anchoring function is performed by said plates 13.

Claims

1.- Joining device (8) for hybrid wind turbine towers (5) intended for the fixation of a metal portion (6) of a wind turbine tower (5) to a concrete portion (7) of 5 said wind turbine (1), characterized in that said joining device (8) comprises a metal body (9) having a generally tubular configuration that is suitable to be fixed to the metal portion (6) of the tower (5) which in use is adjacent to the concrete portion (7), and suitable for being at least partially embedded into said concrete portion (7), said metal body (9) being provided with a number of 10 anchoring openings (11) adapted such that the material of the concrete portion (7) passes therethrough.

2.- Joining device (8) as claimed in claim 1, wherein said anchoring openings (11) are formed in the tubular wall (12) of the metal body (9).

15

3.- Joining device (8) as claimed in claim 1 or claim 2, wherein said metal body (9) includes a number of plates (13) projecting therefrom.

4.- Joining device (8) as claimed in claim 3, wherein said plates (13) are 20 arranged at an outer portion of the metal body (9).

5.- Joining device (8) as claimed in claim 3 or claim 4, wherein said plates (13) are arranged at an inner portion of the metal body (9).

25 6- Joining device (8) as claimed in any of the claims 3 to 5, wherein said plates (13) are provided with a number of anchoring openings (11) adapted so that material of the concrete portion (7) passes therethrough.

7.- Joining device (8) as claimed in claim 6, wherein at least some of the 30 anchoring openings (11) of the plates (13) are circular or elliptical in shape.

8.- Joining device (8) as claimed in claim 6, wherein said anchoring openings (11) are drop-shaped.

35 9.- Joining device (8) as claimed in claim 7 or claim 8, wherein said anchoring

openings (11) have a size decreasing in a direction towards the top of the tower (5).

10.- Joining device (8) as claimed in claim 7 or claim 8, wherein said anchoring 5 openings (11) have a size increasing in a direction towards the top of the tower (5).

11.- Joining device (8) as claimed in any of the claims 7-10, wherein at least some of said anchoring openings (11) widens from the edge (14) of the plate 10 (13) in a direction towards the metal body (9).

12- Joining device (8) as claimed in any of the preceding claims, wherein said plates (13) project substantially perpendicular to said metal body (9).

15 13- Joining device (8) as claimed in any of the preceding claims, wherein said metal body (9) is cylindrical in shape.

14- Joining device (8) as claimed in any of the claims 1-12 wherein said metal body (9) is polygonal in shape.


20

15- Joining device (8) as claimed in any of the claims 1-13, wherein said metal body (9) is frusto conical in shape.

16- Hybrid wind turbine tower (5) comprising at least a metal portion (6) and at 25 least a concrete portion (7), characterized in that it comprises a joining device (8) according to any of the preceding claims provided between one metal portion (6) and one concrete portion (7).

1.3

FIG.1



2.3

FIG.2





FIG.3



3.3

FIG.4a




FIG.4b




FIG.4c




FIG.4d




FIG.4e





FIG.5



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2008/050491

A. CLASSIFICATION OF SUBJECT MATTER INV. F03D1/00 F03D11/04 E02D27/42 E04H12/28			
According to International Patent Classification (IPC) or to both national classification and IPC			
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) F03D E02D E04H			
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched			
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal			
C. DOCUMENTS CONSIDERED TO BE RELEVANT			
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	
X Y	US 2005/072067 A1 (WOBBEN ALOYS [DE]) 7 April 2005 (2005-04-07) paragraph [0041] – paragraph [0044] abstract; figures 1,2 -----	1,2, 13-16 3-12	
X	DE 72 06 725 U (MENSEBACH W) 8 June 1972 (1972-06-08) page 3 – page 4 figures -----	1,2, 13-15	
X	US 2004/093818 A1 (SIMMONS ROBERT J [US]) 20 May 2004 (2004-05-20) paragraph [0019] paragraph [0029] – paragraph [0030] abstract; figures 2-5 -----	1,2,13, 14 -/-	
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C.		<input checked="" type="checkbox"/> See patent family annex.	
* Special categories of cited documents : *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed			
T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&* document member of the same patent family			
Date of the actual completion of the international search 28 April 2008		Date of mailing of the international search report 16/05/2008	
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer O'Shea, Gearóid	

INTERNATIONAL SEARCH REPORT

International application No PCT/EP2008/050491

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2005/015013 A (GEN ELECTRIC [US]; SEIDEL MARC [DE]) 17 February 2005 (2005-02-17) cited in the application page 6, line 13 – page 8, line 19 abstract; figures -----	1-16
Y	JP 09 195584 A (HITACHI SHIPBUILDING ENG CO) 29 July 1997 (1997-07-29) abstract; figures -----	1-16
A	EP 1 624 137 A (EUROP COMMUNITY REPRESENTED BY [BE]) 8 February 2006 (2006-02-08) paragraph [0035] paragraph [0038] figures -----	1,2,6,16

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2008/050491

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 2005072067	A1 07-04-2005	NO ZA	20041876 A 200403177 A	07-05-2004 27-09-2004
DE 7206725	U	NONE		
US 2004093818	A1 20-05-2004	NONE		
WO 2005015013	A 17-02-2005	AT AU CA CN DE DK EP ES US	354023 T 2003250227 A1 2533806 A1 1788156 A 60311894 T2 1654460 T3 1654460 A1 2280852 T3 2007006541 A1	15-03-2007 25-02-2005 17-02-2005 14-06-2006 22-11-2007 21-05-2007 10-05-2006 16-09-2007 11-01-2007
JP 9195584	A 29-07-1997	NONE		
EP 1624137	A 08-02-2006	NONE		