

(21) Application No: 1215411.8
(22) Date of Filing: 06.10.2008
Date Lodged: 30.08.2012
(30) Priority Data:
(31) 60997787 (32) 04.10.2007 (33) US
(62) Divided from Application No
1210081.4 under section 15(9) of the Patents Act 1977

(51) INT CL:
A61M 1/00 (2006.01)
(56) Documents Cited:
US 20050171495 A1
(58) Field of Search:
INT CL A61M
Other: EPODOC, WPI

(71) Applicant(s):
Dornoch Medical Systems Inc
(Incorporated in the United Kingdom)
4032 W.Riverside St., Riverside 64168,
Massachusetts, United States of America
(72) Inventor(s):
Anthony Martini
Lawrence Guerra
(74) Agent and/or Address for Service:
Marks & Clerk LLP
1 New York Street, MANCHESTER, M1 4HD,
United Kingdom

(54) Title of the Invention: Medical waste fluid collection and disposal system
Abstract Title: Lid assembly for canister

(57) A lid assembly for a canister preferably for use with medical waste system comprising a lid ring 410 adapted to engage an opening of the canister, said lid ring 410 featuring a central opening 416 and a circumferential lip portion 437. An insert 462 positioned within the central opening of the lid, said insert including a aperture 463. A flap 466 attached to said insert 462 and pivotable between a closed position, where the flap 466 covers the aperture 463 of the insert, and an open position where the aperture 433 is not covered. A spring 474 engaging the flap 466 so that the flap 466 is biased in the closed position, and a lid featuring a suction port 486 (a-c). The lid sized to engage the aperture 463 of the insert 462 and the flap 466 so that the flap 466 is in the open position when the lid is positioned within the aperture 463 of the insert 462.




FIG. 19





FIG. 24



2/28




FIG. 2




FIG. 3




FIG. 4




FIG. 5

5/28




FIG. 6





FIG. 7



8
9
10
11




FIG. 9

8/28




FIG. 10




FIG. 11




FIG. 12

11/28




FIG. 13




FIG. 14

12/28




FIG. 15




FIG. 16






FIG. 17A




Revision C
5-31-2007

FIG. 17B



0000



0000




Fig. 18A




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25





FIG. 26







FIG. 28






FIG. 30

MEDICAL WASTE FLUID COLLECTION AND DISPOSAL SYSTEM

CLAIM OF PRIORITY

[0001] This application claims priority from U.S. Provisional Patent Application Serial No. 60/997,787, filed October 4, 2007, currently pending.

BACKGROUND

[0002] The invention relates generally to systems for handling biological fluids and, in particular, to an automated system for collecting waste fluids during medical procedures and safely disposing of the waste fluids.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Fig. 1 is a perspective view of an embodiment of the system of the invention, including a first embodiment of the cart;

[0004] Fig. 2 is an enlarged perspective view of one of the cylinder lids of Fig. 1;

[0005] Fig. 3 is an enlarged perspective view of the station coupler of Fig. 1;

[0006] Fig. 4 is a perspective view of the coupler of Fig. 1 with half of the coupler housing removed;

[0007] Fig. 5 is an enlarged perspective view of the coupler of Fig. 4;

[0008] Fig. 6 is a side elevational view of the coupler of Figs. 3-5 with the handle in a released position;

[0009] Fig. 7 is a partial side elevational view of the coupler of Figs. 3-6 with the handle in a locked position;

[0010] Fig. 8 is a perspective view of the coupler of Fig. 5 in engagement with the socket of the cart receptacle;

[0011] Fig. 9 is a front perspective view of a second embodiment of the cart of the system of the invention;

[0012] Fig. 10 is a sectional view of the cart taken along line 10-10 of Fig. 9;

[0013] Fig. 11 is a partial rear perspective view of the cart of Figs. 9 and 10;

[0014] Fig. 12 is an exploded enlarged perspective view of the valve assembly and valve drive system of the cart of Figs. 9-12;

[0015] Fig. 13 is a bottom perspective view of the valve assembly and valve drive system of Fig. 12 after assembly;

[0016] Fig. 14 is a sectional view of the valve assembly taken along line 14-14 of Fig. 13;

[0017] Fig. 15 is an enlarged exploded view of the lower portion of the cart of Figs. 9-11;

[0018] Fig. 16 is schematic of the cart of Figs. 9-15;

[0019] Fig. 17 is a schematic of an embodiment of the station of the invention;

[0020] Figs. 18A-18C are schematics illustrating configurations of the cart valves of Fig. 16;

[0021] Fig. 19 is an exploded view of the cart lid ring assembly;

[0022] Fig. 20 is an assembled perspective view of the cart lid ring assembly of Fig. 19;

[0023] Fig. 21 is an exploded view of a lid insert assembly in an alternative embodiment of the cart;

[0024] Fig. 22 is an assembled perspective view of the lid insert assembly of Fig. 21 in a closed configuration;

[0025] Fig. 23 is a perspective view of the lid insert assembly of Fig. 22 in an open configuration;

[0026] Fig. 24 is a perspective view of the lid insert assembly of Figs. 21-23 and a portion of the cart of Fig. 9 with a disposable lid being inserted;

[0027] Fig. 25 is a perspective view of the lid insert assembly and portion of the cart of Fig. 24 with the disposable lid fully inserted;

[0028] Fig. 26 is a sectional view of an embodiment of the composite hose of the invention;

[0029] Fig. 27 is a perspective view of a portion of the cart of Fig. 9 with a canister removed to show the canister lighting arrangement;

[0030] Fig. 28 is an exploded enlarged perspective view of an alternative embodiment of the valve assembly and valve drive system of the cart of Figs. 9-12;

[0031] Fig. 29 is a bottom perspective view of the valve assembly and valve drive system of Fig. 28 after assembly but with the drive housing removed;

[0032] Fig. 30 is a bottom perspective view of the valve assembly and valve drive system of Fig. 29 with the drive housing in place.

DESCRIPTION OF EMBODIMENTS

[0033] An embodiment of the system of the present invention is indicated in general at 100 in Fig. 1. The system includes a cart, indicated in general at 102, and an evacuation station, indicated in general at 104.

[0034] The cart features a top plate 108 and a bottom plate 110. Positioned between the top and bottom plates are fluid collection cylinders 112a-112d. While four cylinders are shown in Fig. 1, the cart may feature an alternative number of cylinders, such as two in the case of the alternative embodiment discussed below. The cart also features a bottom cabinet, indicated at 114, that is mounted on casters 116a-116d which offer steering capability for the cart. The casters also

preferably include a brake feature. Such casters are well-known in the art. The top plate 108 features a handle 118. As a result, the cart may be easily pushed to and from an operating room.

[0035] As will be described in greater detail below, each of the cylinders 112a-112d are connected to a vacuum source via flexible tubing 122a-122d and their lids 124a-124d. An enlarged view of one of the lids is provided in Fig. 2, where the lid is indicated in general at 124a. The lid is preferably constructed of molded plastic and is disposable. Flexible tubing 122a of Fig. 1 attaches at one end to vacuum port 126, with the opposite end attaching to a vacuum pump as described below. The vacuum port is provided with a filter, preferably a hydrophobic filter, positioned in compartment 127 (Fig. 2). Normally when in use during a medical procedure, the accessory port 128 is covered by cap 132. A patient out suction tube is connected to the ortho port 133, while a tandem port 134 and an patient port 135 are covered by two of the caps 136a-136d. The lid 124a also includes tubing post 137 for occluded vacuum with the patient tubing. The same applies for the remaining cylinder lids 124b-124d of Fig. 1. As a result, suction is selectively drawn on each cylinder so that fluids may be collected therein during the medical procedure via the suction tubing. The suction and other functions of the cart are controlled via a touch screen 140 of Fig. 1.

[0036] After the cart 102 is used in an operating room procedure, and fluids have been collected in one or more of the cylinders 112a-112d, the patient suction tubing is removed from the cylinder lids and all ports for each cylinder lid to which suction was applied are covered with caps (such as one of the caps 136a-136d of Fig. 2 for lid 124a). The cart is then rolled to a position adjacent to the evacuation station 104 for draining, washing, disinfecting, rinsing and return to a suction collection state, as illustrated in Fig. 1.

[0037] Evacuation station 104 includes a housing 142 that contains a source of disinfection solution, pump, drainage system and other components, which are described below, for draining, washing and disinfecting the cylinders of cart 102. As will be explained in greater detail below, the evacuation station 104 communicates with cart 102 by way of composite hose 144 and coupler 146. As illustrated in Fig. 1, coupler 146 is received within a receptacle 148 of the cart. When the draining, washing and disinfecting of the cart cylinders is complete, the coupler 146 is

removed from the cart receptacle 148 so that the cart may again be rolled to an operating room for use.

[0038] Enlarged and sectional views of the coupler 136 of the system of Fig. 1 are presented in Figs. 3-8. Prior art systems, such as the one illustrated in commonly assigned U.S. Patent No. 7,090,663, require that multiple fluid lines and an electrical line be individually connected between the cart and the evacuation station. The coupler 146 permits a single connection to be made between the cart and station. This simplifies and expedites connecting the cart to, and disconnecting the cart from, the evacuation station.

[0039] As illustrated in Fig. 3, the coupler 146 includes a coupler housing 152, a coupler handle 154 and a coupler nose plate 155. Fig 4 shows the coupler with half of the housing removed. As illustrated in Fig. 4, the coupler features a wash supply line 156 and wash drain line 158. The coupler also features an electrical connector 162, which is positioned in nose plate 155. As will be explained in greater detail below, the electrical connector provides 24V DC power to the cart for powering a cart processor and operation of the valve drive system, sensors, solenoids and touch screen. The connector also permits data transfer between the cart and the evacuation station processors and provides the cart's safety ground plain connection. As illustrated in Figs. 4 and 5, the wash supply and drain lines terminate at one end in wash supply and drain fittings 164 and 166, respectively, both of which are positioned on nose plate 155. Wash supply and drain lines 156 and 158, along with an electrical line featuring one end that terminates in electrical connector 162, are combined in a parallel fashion and housed in composite hose 144 of Fig. 1, which is attached to the evacuation station 104, as will be explained below.

[0040] As illustrated in Figs. 4-8, the coupler also includes a ratchet wheel 172 to which handle 154 is attached. Ratchet wheel 172 pivots about an axis defined by screw 174. In addition, as illustrated in Figs. 6 and 7, the coupler includes a solenoid 176 featuring a ram 178 that is attached in a pivoting fashion by pin 180 to a toggle 182. Toggle 182 pivots about pin 184 and features a top tooth 186a and a bottom tooth 186b. Ratchet wheel 172 includes a top notch 188a (Fig. 6) and a bottom notch 188b (Fig. 7). The top portion of toggle 182 is connected to tension coil spring 192 that urges the toggle to pivot about pin 184 in a counter-clockwise direction.

[0041] As illustrated in Figs. 4 and 6 the coupler also features a hook arm, indicated in general at 194. The hook arm features a hook portion 196 at one end and is pivotally connected at the opposing end via pin 198 to ratchet wheel 172. The hook arm also includes a generally L-shaped slot 202 (see also Figs. 5 and 8) within which pin 204 is received.

[0042] When a user initially inserts the coupler in the receptacle of the cart (indicated at 148 in Fig. 1), the coupler is in the configuration illustrated in Fig. 6 (and Figs. 3 and 4). More specifically, the solenoid 176 is not powered and ram 178 is extended. As a result, the bottom tooth 186b of the toggle is positioned within the bottom slot 188b of the ratchet wheel 172 and handle 154 is locked in the position illustrated. In addition, the hook portion 196 of the hook arm 194 is recessed within the generally square opening 206 of the coupler housing (as illustrated in Figs. 3, 4 and 6) so that it is flush with the top surface of the coupler housing.

[0043] As illustrated in Fig. 6-8, the coupler also features a proximity sensor 208, which is positioned adjacent to the interior surface of the bottom of the coupler housing and detects when metal is near. *The proximity sensor includes a circuit for determining proximity to metal.* As illustrated in Fig. 8, the socket 212 of the cart receptacle (148 in Fig. 1) features a metal strip 214. After the coupler 146 is inserted into the cart receptacle 148, as illustrated in Figs. 1 and 8, the proximity sensor 208 of the coupler detects the presence of the now adjacent metal strip 214 within the socket of the cart receptacle. The proximity sensor then sends a signal to a switch within the coupler that energizes the solenoid 176 with power received from the evacuation station via electrical connector 162 (Figs. 4 and 5).

[0044] When the solenoid 176 is powered, ram 178 is retracted, as illustrated in Figs. 7 and 8. As a result, toggle 182 is pivoted about pin 184 in a clockwise direction so that the bottom tooth 186b of the toggle 182 is removed from the lower notch 188b of ratchet wheel 172. As a result, ratchet wheel 172 is free to pivot and the user may rotate the handle 154 in the direction of arrow 216 of Fig. 6 from a release position (illustrated in Fig. 6) into the lock position shown in Fig. 7. As this occurs, the ratchet wheel 172 rotates in a clockwise direction about screw and pivot axis 174 until the upper tooth 186a of the toggle engages the upper notch 188a of the ratchet wheel 172.

[0045] As the ratchet wheel 172 rotates clockwise, while the user is rotating handle 154, the hook arm is pulled to the right of Fig. 6 by pin 198. As a result, pin 204 travels through the generally L-shaped slot 206 from the position illustrated in Fig. 6 to the position illustrated in Figs. 5 and 8. This causes the hook portion 196 of the hook arm to rise up through opening 206 (Figs. 3 and 6) of the top surface of the coupler housing to the position illustrated in Figs. 5 and 8. As a result, with reference to Fig. 8, the hook portion 196 engages a corresponding notch 220 formed in the socket 212 of the cart receptacle (148 in Fig. 1) so that the coupler cannot be withdrawn from the cart receptacle. In addition, when the hook portion 196 engages the socket 212, it aids in engagement by pulling coupler into the receptacle as the handle is rotated downwards. This provides a mechanical advantage for the insertion of the wash supply and drain fittings 164 and 166 into the corresponding ports, and O-rings, of the socket.

[0046] Due to the engagement of the upper tooth 186a of the toggle with the upper notch 188a of the ratchet wheel, as illustrated in Figs. 4, 7 and 8, the handle 154 of the coupler is locked in the position illustrated in Fig. 7 until the solenoid 176 is de-energized and the ram 178 returns to the original extended position illustrated in Fig. 6 (as the coil spring 192 contracts). The coupler is therefore locked within the socket of the cart receptacle, as illustrated in Figs. 1 and 8, until the solenoid 176 (Figs. 6-8) is de-energized. As illustrated in Figs. 3 and 4, the coupler features an "emergency release" button 222 that de-energizes the solenoid 176 so that the handle 154 may be lifted into the position illustrated in Figs. 3, 4 and 6, and the coupler removed from the cart receptacle.

[0047] An embodiment of the cart of the system featuring two fluid collection canisters is indicated in general at 220 in Figs. 9 and 10. As described previously with reference to the embodiment of the cart of Fig. 1, in this embodiment, the canisters are two cylinders, indicated at 222a and 222b in Figs. 9 and 10, are positioned between a top plate 224 and a bottom plate 226. Circular portions of the bottom plate 226 form the bottoms of the cylinders 222a and 222b. The cylinders are preferably constructed of acrylic and may feature a fluorinated coating for easier cleaning. The cylinders may also be constructed from a variety of alternative materials including, but not limited to, glass and plastic. The cart is mounted on casters 228a-228d and top

plate 224 features a handle 232 so that the cart may be easily pushed to and from an operating room.

[0048] As illustrated in Figs. 9-11, the cart also features a bottom cabinet, indicated at 234, as well as a back cabinet, indicated at 236. As illustrated in Fig. 11, the back cabinet 236 features a door 238 that permits access to its interior.

[0049] As illustrated in Figs. 9-11, a fluid manifold 240 is positioned between cylinders 222a and 222b and extends into the interior of back cabinet 236. As illustrated in Fig. 11, the fluid manifold includes a "wash" tube fitting 242, a "drain" tube fitting 244 and a "vent" tube fitting 246. The "wash" tube fitting (242 in Fig. 11) communicates with a 3-way "wash" valve, illustrated at 250 in Fig. 10, via fluid passage 252, also illustrated in Fig. 10. The "drain" tube fitting (244 in Fig. 11) similarly communicates with a 3-way "drain" valve, illustrated at 254 in Fig. 10, via fluid passage 256, also illustrated in Fig. 10. The "vent" tube fitting (246 in Fig. 11) similarly communicates with a 3-way "vent" valve, illustrated at 258 in Fig. 10, via fluid passage 260, also illustrated in Fig. 10.

[0050] As will be explained in greater detail below, wash tube fitting 242 communicates with the cart receptacle 259 (Fig. 11) via flexible tubing (not shown) so that it may receive water and cleaning and disinfecting solution from, with reference to Fig. 1, the composite hose 144 and coupler 146 of the evacuation station 104. The drain tube fitting 244 similarly communicates with the cart receptacle (259 in Fig. 11) via flexible tubing (not shown) so that it may direct waste fluid to the evacuation station via the coupler and composite hose of the station. Vent tube fitting 246 communicates with the interiors of the cylinders via flexible tubing (not shown) and vent ports formed in the cylinder lids (illustrated at 261a and 261b in Fig. 9).

[0051] As illustrated in Fig. 12, valve 250, drain valve 254, vent valve 258 and a short loop valve 262 (also shown in Fig. 10) are positioned between left and right manifold blocks 264a and 264b. The manifold blocks 264a and 264b feature leading ends 266a and 266b, respectively, which face the front of the cart.

[0052] As illustrated in Fig. 14, which is a sectional view taken from the assembled manifold blocks illustrated in Fig. 13, the wash valve 250 communicates with fluid passages 268a and

268b. The fluid passages 268a and 268b lead to and communicate with cleaning nozzles, which connect to base ports 272a and 272b in Fig. 15. The nozzles, examples of which are illustrated at 273a and 273b in Fig. 1, rotate when water, cleaning and disinfecting solutions are supplied thereto in the manner described below. As a result, the nozzles spray the interior of the cylinders (222a and 222b of Figs. 9 and 10) so that they are cleaned, disinfected and drained.

[0053] In addition, Fig. 14 illustrates that the drain valve 254 communicates with fluid passages 274a and 274b, which terminate into oblong recesses 276a and 276b which, as illustrated in Fig. 15 communicate with correspondingly sized and shaped openings 278a and 278b formed in bottom plate 226. As a result, the drain valve 254 communicates with the interior of each cylinder (222a and 222b in Fig. 9).

[0054] Vent valve 258, as illustrated in Fig. 14 communicates with fluid passages 282a and 282b. As will be explained in greater detail below, the fluid passages communicate with a gas collector, illustrated at 284 in Fig. 10 (and 16), via flexible tubing. Gas collector 284 may be periodically connected to the hospital building ventilation system for venting to the exterior of the building.

[0055] Short loop valve 262, as illustrated in Fig. 14, communicates with fluid passages 286a and 286b. As will be explained in greater detail below, the fluid passages selectively communicate with the supply of water and cleaning and disinfecting solutions from the system station to avoid drips when the station coupler (146 in Fig. 1) is disconnected from the cart.

[0056] Returning to Fig. 12, valves 250, 254, 258 and 262 are controlled via a valve drive system that includes a gear train featuring gears 290a, 290b, 290c and 290d. A main drive gear 292 is connected to gear 290a so that they turn in unison. The main drive gear is engaged by a worm gear 294 which is selectively rotated by an electric drive motor 296. As a result, the configuration of the valves 250, 254, 258 and 262 may be controlled by activation of the electric drive motor 296. As illustrated in Figs. 12 and 13, the gear train, main drive gear, worm gear and electric drive motor are secured to the manifold blocks 264a and 264b by drive housing 298.

[0057] As mentioned previously, valves 250, 254, 258 and 262 are 3-way valves. The configurations of valves 250, 254 and 258 include simultaneously "on" for cylinder 222a only,

simultaneously "on" for cylinder 222b only or simultaneously "off" for both cylinders. When the valves are configured to be "on" for cylinder 222a only, water and cleaning and disinfecting solution are provided to cylinder 222a and drainage and venting are provided for cylinder 222a. When the valves are configured to be "on" for cylinder 222b only, water and cleaning and disinfecting solution are provided to cylinder 222b and drainage and venting are provided for cylinder 222b. When valves 250, 254 and 258 are configured in either one of the two "on" positions, short loop valve 262 is configured in an "off" position. When valves 250, 254 and 258 are each configured in the "off" position, short loop valve 262 is configured in an "on" position, the impact of which will be described below.

[0058] Additional details and operation of the system will now be described with regard to Figs. 16 and 17, which show schematics of the cart and station, respectively, as well as Fig. 18, which illustrates the configurations of the cart valves during evacuation of the cylinders and use in the operating room.

[0059] A schematic of the cart of Figs. 9-15, is illustrated in Fig. 16. As illustrated in Fig. 16, the cart features a vacuum pump 302 that is driven by an electric drive motor 304. When in the operating room, the electric drive motor 304 of the pump receives power via 120V power hookup 307 of Fig. 11. The vacuum pump 302 is also illustrated in Fig. 10 and can feature a variable speed motor (304 in Fig. 16) so that a variety of suction levels may be provided by the cart. As an alternative to a variable speed pump, individual regulating lines may be used to provide variable suction levels. The suction provided by the pump 302 is detected by pressure sensor 305 which, as will be explained below, communicates with the cart processor. As illustrated in Fig. 16, the vacuum pump 302 selectively communicates with cylinder 222a via lines 306, 308, 310 and 312 and valve 314 and/or cylinder 222b via lines 306, 308, 316 and 318 and valve 320. Valves 314 and 320 are also illustrated in Fig. 15 and are positioned within the bottom cabinet 234 of the cart. Lines 312 and 318 of Fig. 16 are actually flexible tubing that connect the vacuum ports of the cylinder lids, illustrated at 322a and 322b in Fig. 9, with valves 314 and 320.

[0060] Suction may therefore be pulled on either cylinder 222a or 222b individually, or suction may be pulled on both cylinders simultaneously, by vacuum pump 302. Exhaust air exiting the

vacuum pump 302 travels through check valve 324, exhaust muffler 326 and particulate filter 328 before venting to the operating room/atmosphere or hospital suction system. Filtration is provided for the pump input via HEPA bio-filter 325 of Fig. 16. As a result, as explained above with regard to Figs. 1 and 2, patient suction lines, illustrated at 333a and 333b in Fig. 16, may be connected to patient ports in the cylinder lids (261a and 261b in Fig. 9) so that waste fluids may be collected in either or both cylinders 222a and 222b during a surgical procedure.

[0061] The cart protects the filter 328 and the HEPA bio-filter 325 by use of a hydrophobic pre- filters in the canister lids, illustrated at 327 and 329 in Fig. 16, and a sensor to detect if filter 328 becomes wet or damaged so that it would be ineffective. This may be done by a sensor that detects pressure differential change in the air flow across the filter.

[0062] As illustrated in Fig. 16, the cart also features a vacuum transfer valve 330 allowing a hospital vacuum system 332 to be used when ultra-low vacuum is required for suction.

[0063] When the cart is wheeled out of the operating room, either or both cylinders 222a and 222b will be at lease partially filled with waste fluid from the surgical procedure. To drain, wash and disinfect the cylinder(s), the cart must be positioned adjacent to the system evacuation station and the station coupler positioned within the cart receptacle, as illustrated for cart 102 and evacuation station 104 of Fig. 1.

[0064] A schematic of an embodiment of the evacuation station is provided in Fig. 17. As illustrated in Fig. 17, the station includes a coupler 334 (also illustrated in Fig. 9) which is coupled to the station by a composite hose (such as illustrated by composite hose 144 of Fig. 1) that includes data link 336, power lines 338, wash supply line 340 and drain line 342, along with corresponding connectors in the coupler 334. The wash drain line 342 communicates with a drain pump 344, which is powered by electric drive motor 346. The outlet of the drain pump communicates with the hospital sewer connection 348. The wash supply line 340 communicates with a supply of bleach 350 and a supply of enzyme 352 via a valve 354, a flushing pump 356 and a chemical injection fitting 358. The chemical injection fitting 358 also receives water from hot water connection 360 and cold water connection 362 through solenoid valves 364 and 366.

[0065] When the coupler 334 (Fig. 17) of the station is inserted into the receptacle 259 (Fig. 16) of the cart, as illustrated in Fig. 9, the power, data, wash supply and drain connectors in the coupler and receptacle engage. Next, the handle of the coupler 368 (Fig. 9) is pivoted down, as described with reference to Figs. 3-8 above. Indeed, the coupler 334 of Figs. 9 and 17 features the same construction as the coupler 146 of Figs. 3-8 and operates in the same fashion.

[0066] As illustrated in Fig. 17, the station features a processor 372, while the cart, as illustrated in Fig. 16, features a processor 374. The processor 374 of the cart communicates with a touch screen 376 (also shown in Figs. 9 and 10), which controls operation of the system both when the cart is connected to the evacuation station, and when the cart is being used in the operating room. When the cart is being used in the operating room, the cart processor and touch screen receive power through the 120V AC hookup 307 of Fig. 11, after it is converted to 24V DC with a power supply on board the cart. With regard to the latter, the cart computer 374, based on user inputs through the touch screen 376, controls operation of valves 314 and 320 of Fig. 16 as well as the speed of vacuum pump drive motor 304 and the configuration of vacuum transfer valve 330 to control the level of vacuum provided for each cylinder.

[0067] With the cart and station connected through coupler 334 and receptacle 259, cart data line 378 (Fig. 16) and station data line 336 (Fig. 17) permit the cart and station processors to communicate so that the user can control both, and therefore the draining, washing and disinfecting operations, via the touch screen 376.

[0068] When the cart and station are connected, the cart processor determines whether or not there is waste fluid in either cylinder 222a or 222b or both. This is accomplished via level transducers 380a and 380b. The transducers preferably take the form of the magnorestrictive liquid level sensors, indicated in general at 380a and 380b in Fig. 15.

[0069] When the cart is being used in surgery to provide suction to a patient, wash valve 250, waste valve 254 and vent valve 258 are closed, while short loop valve 262 is open. This valve configuration is illustrated in Fig. 18C. When the cart processor 374 detects, via the canister liquid level transducers, that either canister 222a and 222b is nearly filled with liquid waste, an audible/audio and/or optical/visual warning is provided to allow operator to change to the other

cylinder. The optical warning may include an illuminated "X" over graphic displays of the canisters on the touch screen 376. The audible warning may include activation of a buzzer, bell or any other audio device which may be positioned in the touch screen housing or otherwise on the cart.

[0070] When the cart is connected to the station, if the cart processor determines that there is liquid waste in cylinder 222a, or liquid waste in both cylinders 222a and 222b, the cart processor energizes electric valve drive motor 296 so that the wash, drain, vent and short loop valves 250, 254, 258 and 262, respectively, are placed in the configuration illustrated in Fig. 18A. The cart processor then communicates to the station processor that the cart is configured to wash cylinder 222a. The cart processor also causes a "draining cycle" indication to be displayed on the cart touch screen 375.

[0071] The station processor 372 then activates drain pump 334 of the station. With reference to Fig. 16, waste liquid from cylinder 222a travels through fluid passage 274a (see also Fig. 14) to waste valve 254 and then through fluid passage 256 (see also Fig. 10) and line 386 to the receptacle 259. With reference to Fig. 17, the waste liquid then travels through coupler 334 through station line 342, through drain pump 344 and then to sewer connection 348 where it is disposed.

[0072] Venting is provided to cylinder 222a via line 387, fluid passage 282a (see also Fig. 14) and vent valve 258. As illustrated in Fig. 16, line 387 communicates with a vent port in the lid of cylinder 222a. Vent valve 258 communicates with collector 284 via fluid passage 260 (see also Fig. 10) and line 389.

[0073] When the liquid level transducer 380a (Fig. 16) detects that there is no more liquid waste in the cylinder 222a, the cart processor causes a "flushing cycle" indication to be displayed on the cart touch screen 376 and sends a signal to the station processor 372 (Fig. 17) indicating that the flushing cycle should begin. With reference to Fig. 17, the station processor activates flushing pump 356 so that a mixture of bleach and enzyme are provided to the chemical injection fitting 358. This mixture is combined with water in the chemical injection fitting 358 so that the resulting disinfecting solution is supplied via line 340 to the coupler 334.

[0074] With reference to Fig. 16, the disinfecting solution travels from the coupler 334 through the receptacle 259, line 388 and fluid passage 252 (see also Fig. 10) to wash valve 250. The disinfecting solution then travels through fluid passage 268a (see also Fig. 14) to rotating nozzle 392a so that the interior of cylinder 222a is flushed with the disinfecting solution. The disinfecting solution combined with the liquid waste remaining in the cylinder 222a travels out of the cylinder through fluid passage 274a and, as during the draining cycle, is directed through the waste valve 254, fluid passage 256, line 386, cart receptacle 259, station coupler 334, line 342, drain pump 344 and final to sewer connection 348 for disposal.

[0075] After a period of time, the station flushing pump 356 is deactivated by the station processor while the station drain pump continues to run so that all of the liquid in cylinder 222a drains. When the liquid level transducer 380a indicates that cylinder 222a is empty, the flushing pump is again activated so that the flushing cycle is repeated. The station and cart processors keep track of the number of flushing cycles and preferably two or three flushing cycles are performed. When the last flushing cycle is performed, the "flushing cycle" indication provided on touch screen 376 is extinguished with both the station flushing and drain pumps deactivated.

[0076] If the liquid level transducer 380b of the cart detects the presence of waste liquid in cylinder 222b, the cart processor the cart processor energizes electric valve drive motor 296 and reconfigures the cart valves into the configuration indicated in Fig. 18B. The above process is then repeated for cylinder 222b.

[0077] In addition to the liquid level transducers 380a and 380b, the cylinders may be optionally provided with sensors that detect the density or other characteristic of the fluid in the cylinders. As a result, the processor, and thus system, may provide an automatic notification that the operator needs to soak a cylinder for deep cleaning in appropriate situations. The system then provides an automatic soak cycle when the operator accepts the notification. Alternatively, the user may manually configure (via the touch screen 376) the system to provide an extended soaking period to dissolve blood clots and the like.

[0078] During the draining and flushing cycles described above, the station processor directs the coupler to maintain the coupler solenoid (176 in Figs. 4 and 6-8) in an energized state so that it cannot be removed from the cart receptacle.

[0079] After the final washing cycle has been completed for either or both of cylinders 222a and 222b, and the cart processor determines there is no more liquid in either cylinder, the cart processor energizes the electric drive motor 296 (Fig. 16) so that the valves 250, 254, 258 and 262 are again placed in the configuration illustrated in Fig. 18C. As described previously, in this configuration, the wash, waste and vent valves 250, 254 and 258 are all closed or "off," however, the short loop valve 262 is open or "on." This causes the cart wash supply line 388 to communicate with the fluid passage 286a (see also Fig. 14) and the inlet of the short loop valve 262. The outlet of the short loop valve 262 communicates with fluid passage 395 (Figs. 10 and 16) and cart drain line 386. The station drain pump continues to run so that any liquid remaining in the wash line 340 and drain line 342 of the station composite hose is completely drained and routed to the station sewer connection 348. This prevents drips from the coupler 334 when it is disengaged from the station receptacle 259.

[0080] As illustrated in Fig. 17, the station features pressure sensor 403 and flow meter 405 in communication with drain line, both of which communicate with the station processor 372. As a result, the processor can detect when the drain pump 344 is functioning and at what flow rate.

[0081] The station may optionally use the pressure sensor 403 and flow meter 405 to detect clogs in the drain line. When a clog is detected, the processor may reverse direction of the drain pump 344 to momentarily cause a back flush to help remove the clog automatically.

[0082] The station also includes flow meter 406, which detects the flow rate of the bleach and enzyme mixture to the chemical injection fitting 358, and flow meter 408, which detects the flow rate of water to the chemical injection fitting. Both flow meters 406 and 408 communicate with the station processor so that it may adjust the speed of the flushing pump 356 so that the proper solution composition is provided to the cart.

[0083] As illustrated in Fig. 10, lid 261a engages a cart lid ring 410. Lid 261b (Fig. 9) engages a similar cart lid ring. As illustrated in Figs. 19 and 20, the cart lid ring 410 is part of a cart lid

ring assembly, one each of which, with reference to Fig. 11, is mounted within the circular openings 412a and 412b formed in cart top plate 224. As illustrated in Fig. 19, a lid alignment member 414 is positioned within the central opening 416 of the cart lid ring 410, with O-ring 418 positioned there between for sealing. A dowel pin 422 is positioned within a bore 424 formed in the cart lid ring 410 and engages a corresponding bore formed in lid alignment member 414. A second O-ring 426 is positioned between the top of a fluid collection cylinder (such as 222a or 222b in Fig. 9) and an interior circumferential ledge 428 formed within the cart lid ring 410. A lid alignment spud 432 is secured to the lid alignment member 414 by threaded engagement with aperture 433. An O-ring 434 is positioned there between.

[0084] The assembled cart lid ring assembly is illustrated in Fig. 20. The cart lid ring 410 includes an exterior circumferential ledge 436 that engages the top of cart top plate when the cart lid ring assembly is mounted to the cart top plate 224 (Fig. 10). The cart lid ring also includes a circumferential lip 437 that is engaged by the lid. The openings 438 and 442 formed in the lid alignment member 414 permit the ports of the lid to communicate with the interior of the fluid collection cylinder. The lid alignment spud 432 engages the cylinder lid accessory port (128 in Fig. 2) so that the remaining lid ports are aligned with openings 438 and 442. The cylinder lid snaps onto the top edge 444 of the cart lid ring, as illustrated in Fig. 10. The top edge or other portion of the cart lid ring 410 or lid alignment member 414 may be provided with an alternative lid alignment and/or locking arrangement which may or may not require a corresponding structure on the cylinder lid.

[0085] The cart lid ring 410 and lid alignment member 414 are both preferably constructed of aluminum or stainless steel, but other materials may alternatively be used.

[0086] In addition to holding the lid, the cart lid ring assembly prevents splash back and is an accessible opening if needed to service or clean the inside of the cylinder. In addition, the lid alignment member 414 provides a support for the lid's main body so that the lid is not supported solely around the circumferential edge of the lid. This prevents any lid failure due to the lid imploding into the cylinder.

[0087] In an alternative embodiment of the cart, the lid alignment member 414 of Figs. 19 and 20 may be replaced by the lid insert assembly, indicated in general at 460 in Figs. 21-23. As illustrated in Fig. 21, the lid insert assembly includes an insert 462 and an O-ring 464 that is positioned between the insert 462 and the cart lid ring 410 (Fig. 19). The insert 462 includes a central aperture 463. A flap 466 is attached to the bottom of the insert 462 via hinge members 468a and 468b and pin 472. A torsion spring 474 urges the flap 466 into the closed configuration, illustrated in Fig. 22, where the central aperture 463 of the insert 462 is covered. The open configuration of the flap 466, against the urging of torsion spring 474, is illustrated in Fig. 23 and leaves the central aperture 463 of the insert 462 uncovered.

[0088] As illustrated in Figs. 24 and 25, a disposable lid, indicated in general at 480, features a cylindrical portion 482 and a head portion, indicated in general at 484, which features suction ports 486a, 486b and 486c and auxiliary port 488, as well as associated caps. The interior of cylindrical portion is hollow and communicates with the suction and auxiliary ports. The head 484 also features tab 490 and an identical tab (not shown) positioned on the opposite side of head 484.

[0089] As illustrated in Figs. 21 and 24, the wall 461 defining central aperture 462 features notches 492a and 492b which communicate with horizontal slots 494a and 494b, respectively, that are also formed in the wall 461.

[0090] To prepare a canister for use in surgery, the cylindrical portion 482 of the disposable lid 480 is moved through the central aperture 463 of the insert 462. As this occurs, the flap 466 of the lid insert assembly swings into the open position illustrated in Fig. 23. This action is aided by arcuate-shaped opening member 495 of Fig. 21, which is engaged by the bottom of the lid cylindrical portion. As the lid is further lowered into the central opening 463, the tabs 490 of the head 484 are aligned with notches 492a and 492b of the insert 462 and the lid 480 is lowered into the position illustrated in Fig. 25. The head 484 is then turned, as indicated by arrow 496 of Fig. 25 so that the tabs 490 of the lid move through horizontal slots 494a and 494b of Figs. 21 and 24. As a result, the disposable lid 480 is secured in place, and suction tubes may be attached to ports 486a-486c.

[0091] After surgery is completed, the disposable lid 480 may be removed from the insert 462 by performing the sequence of the above paragraph in reverse order. After the disposable lid is removed from the insert, the flap 466 moves into the closed configuration of Fig. 22. As a result, the contents of the canister cannot splash out or otherwise escape from the canister as the cart is transported.

[0092] An alternative embodiment of the composite hose 144 of Fig. 1 is presented in Fig. 26 in cross-section. As illustrated in Fig. 26, the composite hose features PVC hoses 502 and 504, which may be used for the wash supply and drain lines of the evacuation station. The power and data lines of the evacuation station are provided by 10 wire 20 AWG cables 506 and 508. A ground wire 510 is also provided. The hoses 502 and 504, cables 506 and 508 and ground wire 510 are surrounded by an EPDM thermoelastic polymer jacket 512.

[0093] The cylinders of the cart may optionally feature lighting that is automatically illuminated when either cylinder, or both, is in use during a medical procedure. With reference to Fig. 9, the lighting may be activated by touch screen 376 or may automatically be activated by the cart processor when the cart is in use during surgery. With reference to Fig. 27, the lighting preferably takes the form of multiple light-emitting diodes 514a-514h that extend vertically behind each canister. The illumination allows the liquid level in each canister to be easily monitored by the operator.

[0094] As illustrated in Figs. 28-30, the valve drive system of the cart may include a chain drive in place of the worm gear arrangement of Fig. 12. More specifically, valves 250, 254, 258 and 262 of Fig. 28 are controlled via a valve drive system that includes a gear train featuring gears 290a, 290b, 290c and 290d. As illustrated in Figs. 28 and 29, a pair of sprockets 520a and 520b are secured to gears 290b and 290d, respectively, by spur gear inserts 522a and 522b. Sprockets 520a and 520b are engaged by a drive chain 524 which is selectively driven by an electric drive motor 526. As a result, the configuration of the valves 250, 254, 258 and 262 may be controlled by activation of the electric drive motor 526. As illustrated in Figs. 28 and 30, the gear train, sprockets, drive chain and electric drive motor are secured to the manifold blocks 264a and 264b by drive housing 528.

[0095] The above system therefore provides a cart that collects fluids in the operating room with an on board vacuum, and also offers automated operation with touch screen menu control. The system also includes a station "coupler" that contains water, waste, and electrical lines in one unit. The coupler automatically engages with a cart when inserted into a "receiver assembly" of the cart and, once engaged with the coupler, the cart automatically cycles through drain, wash, and disinfect cycles. The system is capable of identifying which cart cylinders have fluid in them and drains, washes and disinfects only those cylinders. At the end of the draining, washing and disinfecting, the cart is automatically changed back to operation for the operating room. The system also provides a warning prior to cylinders becoming full during fluid collection in the operation room to allow operator to change to next cylinder if needed.

[0096] While embodiments of the invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made therein without departing from the spirit of the invention.

Preferred aspects and embodiments of the present invention are set out below in the following numbered paragraphs.

1. A coupler for removably connecting a medical waste fluid collection cart to a drainage station comprising:

- a) a housing including a wash supply fitting and a wash drain fitting;
- b) a ratchet pivotably positioned within said housing;
- c) a handle attached to said ratchet and extending out of said housing so that said handle may be moved between a release position and a lock position; and
- d) a hook arm having a proximal end attached to said ratchet and a distal end featuring a hook portion, said hook portion extending out of the housing when the handle is moved into the lock position so that a receptacle is engaged by the hook portion which prevents removal of the coupler from the receptacle until the handle is moved to the release position and the hook portion is retracted into the housing.

2. The coupler of paragraph 1 wherein the receptacle is positioned within the cart.

3. The coupler of paragraph 1 further comprising a composite hose including a wash supply line connected to the wash supply fitting and a wash drain line connected to the wash drain fitting.

4. The coupler of paragraph 3 wherein the housing also includes an electrical connector and the composite hose also includes a data line and a power line in communication with the electrical connector.

5. The coupler of paragraph 1 wherein the proximal end of the hook arm is pivotally attached to the ratchet and wherein the hook arm features a generally L-shaped slot and further comprising a pin positioned in the housing, said pin traversing the L-shaped slot when the handle is moved between the release position and the lock position so that said hook portion extends out of the housing when the handle reaches the lock position.

6. The coupler of paragraph 5 further comprising:

e) a solenoid positioned within the housing and featuring a ram;

f) a toggle pivotally positioned within said housing and pivotally connected to said ram, said toggle including a first tooth and a second tooth;

g) said ratchet including a release slot that is positioned so that the first tooth of the toggle is received therein when the handle is in the release position and a lock slot that is positioned so that the second tooth of the toggle is received therein when the handle is in the lock position; and

h) a proximity sensor positioned in said housing and in communication with said solenoid, said proximity sensor activating said solenoid when the coupler is positioned within the receptacle so that said solenoid moves said ram so that said toggle is pivoted so that the first tooth is removed from the release slot and the second tooth may engage the lock slot.

7. The coupler of paragraph 1 further comprising:

e) a solenoid positioned within the housing and featuring a ram;

f) a toggle pivotally positioned within said housing and pivotally connected to said ram, said toggle including a first tooth and a second tooth;

g) said ratchet including a release slot that is positioned so that the first tooth of the toggle is received therein when the handle is in the release position and the a lock slot that is positioned so that the second tooth of the toggle is received therein when the handle is in the lock position; and

h) a proximity sensor positioned in said housing and in communication with said solenoid, said proximity sensor activating said solenoid when the coupler is positioned within the receptacle so that said solenoid moves said ram so that said toggle is pivoted so that the

first tooth is removed from the release slot and the second tooth may engage the lock slot when the handle is rotated into the lock position.

8. The coupler of paragraph 7 wherein the release slot and the lock slot are two separate slots.

9. The coupler of paragraph 7 further comprising a tension coil spring connected between the housing and the toggle so that said toggle is urged into a position where the first tooth engages the release slot of the ratchet and the second tooth is released from the lock slot of the ratchet.

10. The coupler of paragraph 9 further comprising an emergency release button positioned in said housing, said emergency release button in communication with said solenoid so that when said emergency release button is pressed, said solenoid is deactivated so that said tension coil spring causes the second tooth of said ratchet to be removed from the lock slot so that the handle may be pivoted into the release position to permit removal of the coupler from the receptacle.

11. *The coupler of paragraph 7 further comprising a switch that is in circuit between the proximity sensor and the solenoid, said switch energizing the solenoid when the coupler is positioned within the receptacle.*

12. A station for removably connecting to a medical waste fluid collection cart for draining and washing medical waste fluid containers of the cart comprising:

a) a drain pump;

b) a wash drain line in communication with the drain pump;

c) a flushing pump adapted to communicate with a source of washing liquid;

d) a wash supply line in communication with the flushing pump; and

e) a coupler including:

i. a coupler housing including a wash supply fitting in communication with the wash supply line and a wash drain fitting in communication with the wash drain line;

ii. a ratchet pivotably positioned within said coupler housing;

iii. a handle, attached to said ratchet and extending out of said coupler housing so that said handle may be moved between a release position and a lock position;

iv. a hook arm having a proximal end attached to said ratchet and a distal end featuring a hook portion, said hook portion extending out of the coupler housing when the handle is moved into the lock position so that a receptacle of the cart is engaged by the

hook portion which prevents removal of the coupler from the receptacle of the cart until the handle is moved to the release position and the hook portion is retracted into the coupler housing.

13. The station of paragraph 12 further comprising a station housing containing the drain and flushing pumps and further comprising a composite hose extending between the station housing and the coupler, said composite line including the wash supply line and the wash drain line.

14. The station of paragraph 13 further comprising a processor positioned within the station housing and wherein the coupler housing also includes an electrical connector and the composite hose also includes a data line and a power line in communication with the electrical connector and the processor.

15. The station of paragraph 12 wherein the proximal end of the hook arm is pivotally attached to the ratchet and wherein the hook arm features a generally L-shaped slot and further comprising a pin positioned in the housing, said pin traversing the L-shaped slot when the handle is moved between the release position and the lock position so that said hook portion extends out of the housing when the handle reaches the lock position.

16. The station of paragraph 15 further comprising:

- e) a solenoid positioned within the coupler housing and featuring a ram;
- f) a toggle pivotally positioned within said coupler housing and pivotally connected to said ram, said toggle including a first tooth and a second tooth;
- g) said ratchet including a release slot that is positioned so that the first tooth of the toggle is received therein when the handle is in the release position and a lock slot that is positioned so that the second tooth of the toggle is received therein when the handle is in the lock position; and
- h) a proximity sensor positioned in said coupler housing and in communication with said solenoid, said proximity sensor activating said solenoid when the coupler is positioned within the cart receptacle so that said solenoid moves said ram so that said toggle is pivoted so that the first tooth is removed from the release slot and the second tooth may engage the lock slot.

17. The station of paragraph 12 further comprising:

- e) a solenoid positioned within the coupler housing and featuring a ram;

- f) a toggle pivotally positioned within said coupler housing and pivotally connected to said ram, said toggle including a first tooth and a second tooth;
- g) said ratchet including a release slot that is positioned so that the first tooth of the toggle is received therein when the handle is in the release position and the a lock slot that is positioned so that the second tooth of the toggle is received therein when the handle is in the lock position; and
- h) a proximity sensor positioned in said coupler housing and in communication with said solenoid, said proximity sensor activating said solenoid when the coupler is positioned within the receptacle so that said solenoid moves said ram so that said toggle is pivoted so that the first tooth is removed from the release slot and the second tooth may engage the lock slot when the handle is rotated into the lock position.

18. The station of paragraph 17 wherein the release slot and the lock slot are two separate slots.

19. The station of paragraph 17 further comprising a tension coil spring connected between the housing and the toggle so that said toggle is urged into a position where the first tooth engages the release slot of the ratchet and the second tooth is released from the lock slot of the ratchet.

20. The station of paragraph 19 further comprising an emergency release button positioned in said coupler housing, said emergency release button in communication with said solenoid so that when said emergency release button is pressed, said solenoid is deactivated so that said tension coil spring causes the second tooth of said ratchet to be removed from the lock slot so that the handle may be pivoted into the release position to permit removal of the coupler from the receptacle of the cart.

21. The station of paragraph 17 further comprising a switch that is in circuit between the proximity sensor and the solenoid, said switch energizing the solenoid when the coupler is positioned within the receptacle.

22. The station of paragraph 12 further comprising a station housing containing the drain and flushing pumps and the source of washing liquid, wherein the source of washing liquid includes a supply of bleach and a supply of enzyme.

23. A medical waste fluid collection cart comprising:

- a) a first fluid collection canister and a second fluid collection canister;

- b) a valve assembly selectively in communication with the first and second fluid collection canisters and adapted to communicate with a source of washing liquid, a drain and a vacuum source;
- c) a valve drive system in communication with said valve assembly;
- d) a first liquid level sensor positioned within said first fluid collection canister and a second liquid level sensor positioned within said second fluid collection canister; and
- e) a processor in communication with the first and second liquid level sensors and the valve drive system, said processor configuring the valve assembly via the valve drive system for fluid collection during a medical procedure, draining and flushing based on the liquid levels in the first and second fluid collection canisters detected by the first and second liquid level sensors.

24. The cart of paragraph 23 further comprising a vacuum pump in communication with the processor, said vacuum pump capable of being activated when the valve assembly is configured by the processor for fluid collection during a medical procedure.

25. The cart of paragraph 24 wherein said vacuum pump is a variable speed vacuum pump and further comprising a vacuum line communicating with the vacuum pump and the first and second fluid collection canisters and a pressure sensor positioned within the vacuum line, said pressure communicating with the processor so that said processor controls the vacuum pump speed based on pressure within the vacuum line.

26. The cart of paragraph 24 further comprising an exhaust line in communication with an outlet of the vacuum pump and a filter.

27. The cart of paragraph 23 further comprising lights positioned adjacent said first and second fluid collection canisters, said lights illuminating the first and second fluid collection canisters so that the liquid levels therein may be observed.

28. The cart of paragraph 27 wherein the lights include light-emitting diodes.

29. The cart of paragraph 27 wherein the lights communicate with and are controlled by the processor and are automatically illuminated for a canister that is being used for fluid collection.

30. The cart of paragraph 23 further comprising a touch screen in communication with the processor and permitting an operator to control operation of the cart via the touch screen.

31. The cart of paragraph 30 wherein said touch screen provides a visual indication to the operator that at least one of the fluid collection canisters is nearly full.

32. The cart of paragraph 23 further comprising an audio device in communication with the processor, said audio device providing an audible indication to the operator that at least one of the fluid collection canisters is nearly full.

33. The cart of paragraph 23 wherein said valve drive assembly includes a gear train connected to said valve assembly and an electric drive motor connected to said gear train and said processor.

34. The cart of paragraph 33 wherein the electric drive motor is connected to said gear train by a worm gear.

35. The cart of paragraph 33 wherein the electric drive motor is connected to said gear train by a drive chain and sprockets that are engaged by said drive chain.

36. The cart of paragraph 23 wherein the first and second liquid level sensors are magnorestrictive transducers.

37. The cart of paragraph 23 wherein the valve assembly includes a wash valve adapted to communicate with the source of washing liquid, a drain valve adapted to communicate with the drain and a vent valve, each of which selectively communicate with said fluid collection canisters.

38. The cart of paragraph 37 further comprising a gas collector in communication with the vent valve.

39. The cart of paragraph 37 further comprising a washing liquid supply line in communication with the wash valve and a receptacle and a washing drain line in communication with the drain valve and the receptacle, said receptacle adapted to communicate with the source of washing liquid and the drain.

40. The cart of paragraph 23 further comprising cleaning nozzles positioned within said first and second fluid collection canisters, said cleaning nozzles in communication with said valve assembly so that they may selectively receive washing liquid.

41. The cart of paragraph 40 wherein the nozzles rotate.

42. The cart of paragraph 23 wherein the canisters feature disposable lids having patient ports.

43. The cart of paragraph 23 wherein the canisters are constructed of acrylic and include a fluorinated coating.

44. The cart of paragraph 23 further comprising:

f) a top plate;

g) a bottom plate;

h) first and second cylinders positioned between the top and bottom plate, said first and second cylinders cooperating with the top and bottom plates to define the first and second fluid collection canisters.

45. The cart of paragraph 44 wherein said first and second cylinders are constructed of acrylic and include a fluorinated coating.

46. The cart of paragraph 44 further comprising a cabinet positioned beneath said bottom plate, said cabinet housing the valve assembly and valve drive system.

47. The cart of paragraph 46 further comprising casters positioned on a bottom portion of said cabinet housing and wherein said top plate features a handle.

48. The cart of paragraph 44 wherein the top plate features first and second circular openings and further comprising:

i) first and second cart lid ring assemblies positioned within said first and second circular openings, respectively, each of said first and second cart lid ring assemblies including:

i. a cart lid ring engaging one of the first and second circular openings of the cart top plate, said cart lid ring featuring a central opening and a circumferential lip portion;

ii. a lid alignment member positioned within the central opening of the cart lid ring, said lid alignment member including a lid alignment spud;

iii. a lid removably engaging the lip portion of the cart lid ring, said lid featuring a port that, when engaged by the lid alignment spud of the lid alignment member, is properly positioned on the cart lid ring.

49. The cart of paragraph 48 wherein each cart lid ring assembly further includes:
iv. a lower O-ring positioned between the cart lid ring and the top plate of the cart;
and

v. an upper O-ring positioned between the cart lid ring and the lid alignment member.

50. The cart of paragraph 48 wherein each cart lid ring assembly further includes a dowel pin positioned between the cart lid ring and the lid alignment member.

51. A medical waste fluid collection and disposal system comprising:

a) A medical waste fluid collection cart including:

i. a first fluid collection canister and a second fluid collection canister;
ii. a valve assembly selectively in communication with the first and second fluid collection canisters;

iii. a valve drive system in communication with said valve assembly;

iv. a first liquid level sensor positioned within said first fluid collection canister and a second liquid level sensor positioned within said second fluid collection canister;

v. a cart processor in communication with the first and second liquid level sensors and the valve drive system,

vi. a cart drain line in communication with the valve assembly;

vii. a cart flushing line in communication with the valve assembly;

viii. a cart data line in communication with the cart processor;

b) a station including:

i. a drain pump having an outlet adapted to communicate with a drainage system and an inlet;

ii. a flushing pump having an outlet and an inlet;

iii. a source of washing liquid in communication with the inlet of said flushing pump;

iv. a station processor in communication with the drain pump and the flushing pump;

v. a station drain line in communication with the drain pump inlet;

vi. a station flushing line in communication with the flushing pump outlet; vii. a station data line in communication with the station processor;

c) a coupler for removably coupling the cart and station drain lines, the cart and station flushing lines and the cart and station data lines so that cart and station processors may cooperate in operating the cart valve assembly and the station drain and flushing pumps based on liquid levels in the first and second fluid collection canisters of the cart so that

medical waste fluids may be drained and flushed from the first and second fluid collection canisters.

52. The system of paragraph 51 wherein said cart further includes a cart power line in communication with the cart processor and the coupler and said station includes a station power line in communication with the coupler so that said cart and station power lines are removably coupling so that said cart processor receives power from the station power line.

53. The system of paragraph 51 wherein the cart further comprises a touch screen that communicates with the cart processor, said touch screen permitting a operator to control both the cart and station processors when the cart and station data lines are coupled by the coupler.

54. The system of paragraph 51 wherein the source of washing liquid includes a supply of bleach and a supply of enzyme.

55. The system of paragraph 51 wherein the coupler includes a composite hose including station drain line, the station flushing line and the station data line and a coupler housing including wash supply fitting in communication with the station flushing line, a wash drain fitting in communication with the station drain line and an electrical connector in communication with the station data line.

56. The system of paragraph 55 wherein said cart includes a receptacle in communication with the cart drain line, the cart flushing line and the cart data line, said receptacle sized to receive the coupler housing.

57. The system of paragraph 56 wherein said composite hose also includes a station power line that is in communication with the electrical connector of the coupler housing and wherein said cart includes a cart power line in communication with the cart processor and the receptacle.

58. The system of paragraph 51 wherein the coupler includes a locking mechanism having a locked configuration and a release configuration, said locking mechanism in communication with the station processor and said station processor maintaining the locking mechanism in the locked configuration as medical waste fluids are drained and flushed from the first and second fluid collection canisters.

59. A lid assembly for a canister comprising:

- a) a lid ring adapted to engage an opening of the canister, said lid ring featuring a central opening and a circumferential lip portion;
- b) a lid alignment member positioned within the central opening of the lid ring, said lid alignment member including a lid alignment spud and a slot;
- c) a lid removably engaging the lip portion of the lid ring, said lid featuring an alignment port and a suction port positioned in the lid so that when the alignment port is engaged by the lid alignment spud of the lid alignment member, the suction port is aligned with the slot of the lid alignment member.

60. The lid assembly of paragraph 59 wherein the lid is disposable.

61. The lid assembly of paragraph 60 wherein the lid includes a vacuum port and a filter in communication with the vacuum port.

62. The lid assembly of paragraph 61 wherein the filter is a hydrophobic filter.

63. *The lid assembly of paragraph 59 further comprising:*

- d) a lower O-ring adapted to be positioned between the lid ring and the canister; and
- e) an upper O-ring positioned between the lid ring and the lid alignment member.

64. The lid assembly of paragraph 59 further comprising a dowel pin positioned between the lid ring and the lid alignment member.

65. The lid assembly of paragraph 59 wherein the lid ring and the lid alignment member are two separate pieces.

66. The lid assembly of paragraph 59 wherein the

67. A lid assembly for a canister comprising:

- a) a lid ring adapted to engage an opening of the canister, said lid ring featuring a central opening and a circumferential lip portion;
- b) an insert positioned within the central opening of the lid, said insert including a aperture;
- c) a flap attached to said insert and pivotable between a closed position, where the flap covers the aperture of the insert, and an open position where the aperture is not covered;

d) a spring engaging said flap so that said flap is biased in the closed position; and
e) a lid featuring a suction port, said lid sized to engage the aperture of the insert and the flap so that said flap is in the open position when the lid is positioned within the aperture of the insert.

68. The lid assembly of paragraph 67 further comprising an O-ring adapted to be positioned between the lid ring and the canister.

69. The lid assembly of paragraph 67 wherein the spring is a torsion spring.

70. The lid assembly of paragraph 67 wherein the flap is mounted to a bottom surface of the insert.

72. The lid assembly of paragraph 67 wherein the flap includes an opening member.

73. The lid assembly of paragraph 72 wherein the opening member is arcuate-shaped.

74. The lid assembly of paragraph 67 wherein the lid includes a head portion and a cylindrical portion, wherein the head portion includes the suction port and the cylindrical portion engages the flap when the lid is inserted through the aperture of the insert.

75. The lid assembly of paragraph 74 wherein the head portion includes a tab and the insert includes a wall defining the aperture, said wall featuring a notch which receives the tab when the lid is positioned within the aperture of the insert.

76. The lid assembly of paragraph 75 wherein the wall further includes a horizontal slot in communication with the notch, said horizontal slot receiving the tab of the lid when the lid is rotated about a vertical axis.

77. The lid assembly of paragraph 74 wherein the cylindrical portion is hollow and communicates with the suction port.

78. The lid assembly of paragraph 67 wherein the lid is disposable.

79. The lid assembly of paragraph 78 wherein the lid includes a vacuum port and a filter in communication with the vacuum port.

80. The lid assembly of paragraph 79 wherein the filter is a hydrophobic filter.

81. The lid assembly of paragraph 67 wherein the aperture is located generally in the horizontal center of the insert.

82. A disposable lid for a canister comprising a head portion and a cylindrical portion, said head portion including a suction port and a vacuum port and the cylindrical portion being hollow and in communication with the suction and vacuum ports.

83. The disposable lid of paragraph 82 further comprising a filter in communication with the vacuum port.


84. The disposable lid of paragraph 83 wherein the filter is a hydrophobic filter.

85. The disposable lid of paragraph 82 further comprising a tab mounted on a circumferential edge of the head portion.

CLAIMS:

1. A lid assembly for a canister comprising:
 - a) a lid ring adapted to engage an opening of the canister, said lid ring featuring a central opening and a circumferential lip portion;
 - b) an insert positioned within the central opening of the lid, said insert including an aperture;
 - c) a flap attached to said insert and pivotable between a closed position, where the flap covers the aperture of the insert, and an open position where the aperture is not covered;
 - d) a spring engaging said flap so that said flap is biased in the closed position; and
 - e) a lid featuring a suction port, said lid sized to engage the aperture of the insert and the flap so that said flap is in the open position when the lid is positioned within the aperture of the insert.
2. The lid assembly of claim 1 further comprising an O-ring adapted to be positioned between the lid ring and the canister.
3. The lid assembly of claim 1 wherein the spring is a torsion spring.
4. The lid assembly of claim 1 wherein the flap is mounted to a bottom surface of the insert.
5. The lid assembly of claim 1 wherein the flap includes an opening member.
6. The lid assembly of claim 5 wherein the opening member is arcuate-shaped.
7. The lid assembly of claim 1 wherein the lid includes a head portion and a cylindrical portion, wherein the head portion includes the suction port and the cylindrical portion engages the flap when the lid is inserted through the aperture of the insert.
8. The lid assembly of claim 7 wherein the head portion includes a tab and the insert includes a wall defining the aperture, said wall featuring a notch which receives the tab when the lid is positioned within the aperture of the insert.

9. The lid assembly of claim 8 wherein the wall further includes a horizontal slot in communication with the notch, said horizontal slot receiving the tab of the lid when the lid is rotated about a vertical axis.
10. The lid assembly of claim 7 wherein the cylindrical portion is hollow and communicates with the suction port.
11. The lid assembly of claim 1 wherein the lid is disposable.
12. The lid assembly of claim 11 wherein the lid includes a vacuum port and a filter in communication with the vacuum port.
13. The lid assembly of claim 12 wherein the filter is a hydrophobic filter.
14. The lid assembly of claim 1 wherein the aperture is located generally in the horizontal center of the insert.



Application No: GB1215411.8

Examiner: Dr Matthew Parker

Claims searched: 1-14

Date of search: 13 September 2012

Patents Act 1977: Search Report under Section 17

Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance
X	1-14	US2005/171495 A1 (AUSTIN), see Figure 8

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^X:

Worldwide search of patent documents classified in the following areas of the IPC

A61M

The following online and other databases have been used in the preparation of this search report

EPODOC, WPI

International Classification:

Subclass	Subgroup	Valid From
A61M	0001/00	01/01/2006