




(86) Date de dépôt PCT/PCT Filing Date: 2009/05/27  
(87) Date publication PCT/PCT Publication Date: 2009/12/03  
(45) Date de délivrance/Issue Date: 2018/06/12  
(85) Entrée phase nationale/National Entry: 2010/11/30  
(86) N° demande PCT/PCT Application No.: CN 2009/000596  
(87) N° publication PCT/PCT Publication No.: 2009/143711  
(30) Priorité/Priority: 2008/05/30 (CN200810028408.4)

(51) Cl.Int./Int.Cl. *A45C 7/00* (2006.01)  
(72) Inventeur/Inventor:  
LIN, CHE-WEN, CN  
(73) Propriétaire/Owner:  
LIN, CHE-WEN, CN  
(74) Agent: ADE & COMPANY INC.

(54) Titre : STRUCTURE DE RECEPTION APTE A LA FIXATION POUR ENCEINTE SOUPLE  
(54) Title: COVER-TYPE CONTAINING STRUCTURE FOR FLEXIBLE ENCLOSURES



(57) **Abrégé/Abstract:**

A cover-type containing structure for flexible enclosures mainly includes a front cover sheet, a rear cover sheet, a connection portion and a flexible enclosure. The front cover sheet includes a first joining edge and a cover piece, whereas the rear cover sheet includes a cover assembly corresponding to the cover piece. The connection portion is located between the front cover sheet and the rear cover sheet to connect the two sheets. The flexible enclosure includes a second joining edge and by engaging the first joining edge with the second joining edge, the front cover sheet and the flexible enclosure are fixed. Besides, the containing structure further includes a holding portion. Under a contained state, the holding portion is used to contain smaller objects; whereas, in an unfolded state, in addition to that the flexible enclosure is used to contain larger objects, the holding portion can be used as well to contain smaller objects. In addition to applying to a bag-like product, the containing structure of the present can be also applied to contain other clothing combined with the bag-like product or other flexible enclosure.

**ABSTRACT**

A cover-type containing structure for flexible enclosures mainly includes a front cover sheet, a rear cover sheet, a connection portion and a flexible enclosure. The front cover sheet includes a first joining edge and a cover piece, whereas the rear cover sheet includes a cover assembly corresponding to the cover piece. The connection portion is located between the front cover sheet and the rear cover sheet to connect the two sheets. The flexible enclosure includes a second joining edge and by engaging the first joining edge with the second joining edge, the front cover sheet and the flexible enclosure are fixed. Besides, the containing structure further includes a holding portion. Under a contained state, the holding portion is used to contain smaller objects; whereas, in an unfolded state, in addition to that the flexible enclosure is used to contain larger objects, the holding portion can be used as well to contain smaller objects. In addition to applying to a bag-like product, the containing structure of the present can be also applied to contain other clothing combined with the bag-like product or other flexible enclosure.

## **COVER-TYPE CONTAINING STRUCTURE FOR FLEXIBLE ENCLOSURES**

### **BACKGROUND OF THE INVENTION**

#### **5 a) Field of the Invention**

The present invention relates to a cover-type containing structure for flexible enclosures, and more particular to a multi-functional structure which applies a fastening mode to facilitate a user to quickly contain and access a flexible enclosure, such as a bag or clothing.

#### **10 b) Description of the Prior Art**

In a modern industrial society which is highly developed, a need for most people to carry all kinds of personal belongings in a simpler and handier way has been increased significantly. For example, to reduce use of plastic bags for environmental protection, a person should bring  
15 his or her own recycle shopping bag while shopping in a mall. In addition, to prevent from cold or rain due to temperature change or when a raining season comes, he or she should carry personally a thin overcoat, a windbreaker or all kinds of clothing. However, the existing structures which are designed to provide a user to fold and contain,  
20 whether being applied to the recycle shopping bag, the thin overcoat, the

windbreaker or all kinds of clothing, are not able to achieve the effects of simplicity, quick containing and accessing. Furthermore, as being limited to a product framework, these existing structures are only provided with a single function of containing and not equipped with a  
5 complex function of containing objects and providing a design of a funny appearance at a same time.

Taking the existing recycle shopping bag, the thin overcoat or the windbreaker which is carried personally as an example, a mode of roll-up for containing is usually applied. Referring to FIG. 1, it shows a  
10 schematic view of an ordinary recycle shopping bag in an unfolded state. The recycle shopping bag includes primarily a bag unit 3, a handle 31, a cover piece 300, a male containing piece 304 and a female containing piece 305, wherein the cover piece 300 further includes a fixing end 302 and an open end 303. The cover piece 300 is fixed at an exterior side of  
15 the bag unit 3 by the fixing end 302, the male containing piece 304 is provided at a proper position of the open end 303 and the female containing piece 305 is provided at a position corresponding to an upper side of the male containing piece 304 with a proper distance. Referring to FIG. 2, it shows the ordinary recycle shopping bag which is rolled up.  
20 When containing, the bag unit 3 is first folded to be at a same width with

that of the cover piece 300 and is then rolled up below the open end 303 of the cover piece 300, along with the handle 31. When the bag unit 3 is rolled up to be at a same size of the cover piece 300, the bag unit 3 is next collected by the male containing piece 304 of the open end 303 and the female containing piece 305 is fixed, thereby enabling the bag unit 3  
5 to be fixed below the cover piece 300 after being rolled up.

In addition to the abovementioned recycle shopping bag, the personal thin overcoat or the windbreaker (not shown in the drawings) sold on existing markets also uses the similar roll-up mode and is provided with a single function that only the size can be reduced after roll-  
10 up, without other functions of use. Therefore, it is very imperfect for the user, as the convenience of use and the complex multi-function cannot be provided.

#### SUMMARY OF THE INVENTION

15 One primary aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which uses a fastening mode to facilitate a user to quickly contain and access a flexible enclosure such as a bag or clothing, as well as to provide a complex function of using a smaller holding part and a larger containing space at a same time. The present invention includes primarily a front cover sheet, a rear cover sheet, a connection  
20 portion and a flexible enclosure, wherein the front cover sheet is provided with a first joining edge and a cover piece, the rear cover sheet is provided with a cover assembly

corresponding to the cover piece and the connection portion is provided below the front cover sheet at a position corresponding to the rear cover sheet to connect the two sheets. The flexible enclosure is provided with a second joining edge which is engaged with the corresponding first joining edge of the front cover sheet, thereby fixing the front cover sheet  
5 and the flexible enclosure.

A second aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, wherein an exterior side of the front cover sheet or an inner or exterior side of the rear cover sheet is further provided with a holding portion to provide an additive  
10 function of putting in an object in addition to containing the flexible enclosure. Furthermore, a side wall of the containing structure that is connected with the holding portion can be further provided with a buckle and a belt to facilitate a user to carry as a bag when necessary.

15 A third aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, wherein the second joining edge is partially engaged with the first joining edge and a containing port is formed at a place where the first joining edge is not engaged with the second joining edge. When the unfolded flexible enclosure is accessed, the opened rear cover sheet can be put in the containing space between the front cover sheet  
20 and the flexible enclosure from the containing port.

A fourth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, wherein a side wall is provided between the front cover sheet and the cover piece and the flexible enclosure is provided with a joining portion to connect with the corresponding side wall. The joining portion assumes an annulus-like unit, a radius of which is a little smaller than that of the side wall and an interior of which is formed with the containing space. As the side wall is overlapped and encloses the joining portion and an upper wall of the annulus-like joining portion is abutted toward an upper wall of the side wall, a first containing portion will be formed in an un-abutted space between a lower wall of the joining portion and the side wall, thereby containing the folded rear cover sheet. The inner containing space of the annulus-like joining portion is combined with the front cover sheet to form a second containing portion which further includes a port to connect with the flexible enclosure, thereby allowing the folded flexible enclosure to be contained in the second containing portion from the port.

15

A fifth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a bag unit and is provided with the connection portion connecting the front cover sheet and the rear cover sheet. The connection portion is bended and is latched from top to bottom at an upper rim of a front piece of the flexible enclosure; whereas, the folded flexible enclosure can be contained in the containing space formed between the front cover sheet and the rear cover sheet. As the connection portion is latched between two end parts of a handle at an upper rim of the flexible enclosure, weight of the

20

containing structure and the holding portion is supported by a force a user uses to lift up the two end parts of the handle, thereby preventing the upper rim of the flexible enclosure from suspending and deformation due to the weight of the holding portion. The upper rim of the front piece or a rear piece of the flexible enclosure can be further provided with a lower dent  
5 having a dented size fitting with a width of the connection portion, such that the flexible enclosure and the holding portion can be combined more smoothly, beautifully and stably.

A sixth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a bag unit and is provided with an extension function  
10 of an extension portion to extend and put the holding portion at a bottom in the flexible enclosure, wherein an end of the extension portion is connected to the second joining edge and the other end is connected to the first joining edge. Therefore, when the holding portion is loaded too heavily, the holding portion can be extended and put at the bottom in the flexible enclosure by the extension portion, without causing an opening to suspend and be  
15 deformed as the holding portion which is connected to the opening is too heavy.

A seventh aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a bag unit and is provided with a fork portion between the flexible enclosure and the handle, allowing the front cover sheet and the rear cover  
20 sheet which are smaller in entirety, along with the holding portion, to be connected with the upper rim of the front piece of the flexible enclosure by the connection portion, the first joining edge, the second joining edge and the extension portion. In addition, weight of the front cover sheet, the rear cover sheet, the holding portion and the containing structure is supported by a force a user uses to lift up the handle and the fork portion.

An eighth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a piece of clothing combined with a bag unit carried on a back or at a side and snapped horizontally at a waist of a user. The exterior side of the front cover sheet or the inner or exterior side of the rear cover sheet is further connected with the holding portion to provide the additive function of putting in an object in addition to containing the clothing. A side or a rear of the containing structure that is connected with the holding portion can be further provided with an outer belt to facilitate using as a side pack, a backpack or a waist bag. When the clothing is contained, the outer belt of the rear cover sheet can facilitate carrying the bag unit and the clothing which is contained in the containing space.

A ninth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a piece of clothing combined with a bag unit. The present invention is further provided with plural through-holes for the clothing, allowing plural end parts of an inner belt (single shoulder strap or dual shoulder strap) to pass through the through-holes of the clothing to be engaged with the bag unit. Next, the first joining edge is engaged with the corresponding second joining edge to fix the front cover sheet and the clothing, wherein an upper end and lower end of the inner belt pass through respectively the plural through-holes of the clothing to connect with the upper rim and lower rim of the front cover sheet, such that weight of the bag unit can be supported when a user is wearing the clothing.

A tenth aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a piece of clothing combined with a bag unit. The present invention is provided with a mask unit between the front cover sheet and the rear cover sheet. A side of the mask unit is provided with a connection side to connect with the bag unit. The connection side is located at an upper rim of the mask unit and is connected with the upper rim of the front cover sheet or the first joining edge. In addition, the mask unit is further provided with a sheath piece to sheath and fix the mask unit from top to bottom at an outer periphery of the bag unit, thereby achieving a rain-proofing effect for the bag unit.

10

An eleventh aspect of the present invention is to provide a cover-type containing structure for flexible enclosures, which is applied to a piece of clothing combined with a bag unit. The clothing and the bag unit are loosely or fixedly connected. For the fixed connection mode, the first joining edge and the second joining edge are engaged by gluing, hot pressing or sewing. For the loose connection mode, on the other hand, the first joining edge and the second joining edge are added respectively with a first movable joining piece and a second movable joining piece (such as a zipper, a snap latch or a hook and loop fastener), thereby providing a movable dismantlement function to the clothing and the bag unit. Therefore, when the clothing or the bag unit is damaged or gets dirty, it can be dismantled and replaced for use.

20

A twelfth aspect of the present invention is provide a cover-type containing structure for flexible enclosures, wherein the exterior side of the front cover sheet and the exterior side of the flexible enclosure can be further provided with corresponding textures and patterns to improve a sense of aesthetics or contrast into a different visual effect. When the holding portion is used alone, the front cover sheet and the holding portion will manifest the partial textures or patterns. On the other hand, when the flexible enclosure is unfolded, the front cover sheet and the holding portion can manifest the textures or patterns corresponding to the flexible enclosure, thereby improving a sense of aesthetics, providing a funny appearance and contrasting into a different visual effect.

According to a further aspect of the invention, there is provided a cover-type containing structure for flexible enclosures, comprising:

- a front cover sheet, an edge of which is provided with a cover piece;
- 15 a rear cover sheet, an edge of which is provided with a cover assembly corresponding to the cover piece;
- a connection portion which is provided between the front cover sheet and the rear cover sheet to connect the two sheets;
- a first joining edge which is provided: at the front cover sheet; at the rear cover sheet;
- 20 between the front cover sheet and the rear cover sheet; or at the connection portion; and
- a flexible enclosure which includes a second joining edge, the front cover sheet and the flexible enclosure are connected by engaging the first joining edge with the corresponding second joining edge, wherein the front cover sheet is disposed at various

positions on the flexible enclosure at least including the position close to a center or an edge thereof;

a containing space being formed between the front cover sheet and the rear cover sheet to contain the flexible enclosure in folded condition, and the front cover sheet and the  
5 rear cover sheet being covered by the cover piece and the cover assembly.

To enable a further understanding of the said aspects and the technological methods of the invention herein, the brief description of the drawings below is followed by the detailed description of the preferred

## **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 shows a schematic view of a conventional shopping bag in an unfolded state.

FIG. 2 shows a schematic view of the conventional shopping bag which is  
5 rolled up.

FIG. 3 shows an exploded view of a first embodiment of the present invention in an unfolded state.

FIG. 4 shows a schematic view of the first embodiment of the present invention in a contained state.

10 FIG. 5 shows a schematic view of the first embodiment of the present invention in an unfolded state.

FIGS. 6 to 9 show schematic views of a cross section of the first embodiment of the present invention in the contained and unfolded states.

15 FIG. 10 shows an exploded view of a second embodiment of the present invention in an unfolded state.

FIG. 11 shows a schematic view of the second embodiment of the present invention in a three-dimensional contained state.

FIG. 12 shows a schematic view of the second embodiment of the  
20 present invention in a three-dimensional unfolded state.

FIG. 13 and FIG. 14 show partial schematic views of the second embodiment of the present invention in the unfolded state.

FIGS. 15 to 18 show schematic views of a cross section of the second embodiment of the present invention in the contained and unfolded states.

FIGS. 19 to 23 show schematic views of containing steps of the first and second embodiments of the present invention.

FIG. 24 shows an exploded view of a first implementation of the present invention to a piece of clothing, in an unfolded state.

10 FIG. 25 shows a schematic view of the first implementation of the present invention to the clothing, after containing.

FIG. 26 shows a schematic view of the first implementation of the present invention to the clothing, in a partially unfolded state.

15 FIG. 27 shows a schematic view of the first implementation of the present invention to the clothing, in the unfolded state.

FIG. 28 and FIG. 29 show schematic views of expansion operations of the first implementation of the present invention to the clothing.

FIG. 30 and FIG. 31 show schematic views of the first implementation of the present invention to the clothing, after unfolding.

20 FIG. 32 and FIG. 33 show schematic views of a second implementation of

the present invention to the clothing, in an unfolded state.

FIG. 34 shows a schematic view of a third implementation of the present invention to the clothing, in a partially unfolded state.

FIG. 35 shows an exploded view of a third embodiment of the present invention, in an unfolded state.

FIG. 36 and FIG. 37 show first schematic views of the third embodiment of the present invention, in the unfolded state.

FIGS. 38 to 42 show schematic views of containing steps of the third embodiment of the present invention.

FIG. 43 and FIG. 44 show second schematic views of the third embodiment of the present invention, in the unfolded state.

FIG. 45 shows a third schematic view of the third embodiment of the present invention, in the unfolded state.

FIG. 46 shows a fourth schematic view of the third embodiment of the present invention, in the unfolded state.

FIG. 47 shows a schematic view of a fourth embodiment of the present invention, in a contained state.

FIG. 48 shows a schematic view of the fourth embodiment of the present invention, in an unfolded state.

FIG. 49 shows an exploded view of the fourth embodiment of the present

invention, in the unfolded state.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Referring to FIGS. 3 to 5, a first embodiment of the present invention comprises primarily a front cover sheet 1, a rear cover sheet 2, a connection portion 12 and a flexible enclosure 3, wherein an edge of the front cover sheet 1 is provided with a first joining edge 131 and a cover piece 11. The first joining edge 131 can be also provided at the rear cover sheet 2, between the first cover sheet 1 and the rear cover sheet 2 or at the connection portion 12. An edge of the rear cover sheet 2 is provided with a cover assembly 21 which corresponds to the cover piece 11; whereas, the cover piece 11 and the cover assembly 21 are a single-headed zipper and include a first pull piece 110. The connection portion 12 is provided below the front cover sheet 1 and a corresponding position above the rear cover sheet 2 to connect the two sheets. The flexible enclosure 3 is provided with a second joining edge 331 which is engaged with the first joining edge 131 at the first cover sheet 1 and fixes the front cover sheet 1 on a surface close to a center of the flexible enclosure 3.

An exterior side of the front cover sheet 1 can be further connected with a holding portion 4 by which another additive function of putting in an

object is provided, in addition to containing the flexible enclosure 3. The holding portion 4 is provided with a switching piece 41 and a switching assembly 42 to facilitate a user to open and close the holding portion 4 and access an object therein at any time, wherein the switching mode of the switching piece 41 and the switching assembly 41 includes a zipper, a hook and loop fastener, a snap or a magnetic button. In the present embodiment, in addition to that the exterior side of the front cover sheet 1 can be connected with the holding portion 4, an interior side (as shown in FIGS. 20 to 23 of a second embodiment) or an exterior side (not shown in the drawings) of the rear cover sheet 2 can be further connected with the holding portion 4. As the structures are roughly the same, further description is not provided. In the present embodiment, a side of the rear cover sheet 2 corresponding to the flexible enclosure 3 can be further provided with a fixing piece 22 and a fixing assembly 32 to fix the rear cover sheet 2 on a surface of the flexible enclosure 3, such that the rear cover sheet 2 will not suspend from the surface of the flexible enclosure 3 and swing. The fixing piece 22 and the fixing assembly 32 include a zipper, a hook and loop fastener, snap latch or a magnetic button.

As shown in FIGS. 6 to 9, as the second joining edge 331 and the first

joining edge 131 are engaged partially and a containing port 301 is formed at a place where the two edges are not engaged, when accessing the unfolded flexible enclosure 3, the rear cover sheet 2 can be put in a containing space 30 between the front cover sheet 1 and the flexible enclosure 3 from the containing port 301. On the contrary, after containing the folded flexible enclosure 3, the rear cover sheet 2 can be taken out of the containing port 301 and the rear cover sheet 2 and the front cover sheet 1 can be fixed by a single-headed zipper and the first pull piece 110. Besides, to stably engage the front cover sheet 1 at the flexible enclosure 3 and to allow the rear cover sheet 2 that is contained in the containing port 301 to be latched in the containing space 30 without falling out of the containing port 301, a preferred structure of the present embodiment is that a circumferential length of partially engaging the first joining edge 131 with the second joining edge 331 is set to be at least a half of an entire circumferential length of the front cover sheet 1.

Referring to FIGS. 10 to 12, in addition to the components included by the first embodiment, a second embodiment of the present invention further includes a side wall 13 between the front cover sheet 1 and the cover piece 11, with that the flexible enclosure 3 is provided with a joining portion 33 corresponding to the side wall 13. The joining portion 33

assumes an annulus-like unit, a radius of which is a little smaller than that of the side wall 13 and an interior of which is formed with the containing space 30. The second joining edge 331 is abutted at and connected with the first joining edge 131, allowing the side wall 13 to overlap and  
5 enclose the joining portion 33. When the flexible enclosure 3 is folded and contained in a second containing portion 35 and is closed by the cover piece 11 and the cover assembly 21, the side wall 13 of the containing structure that is connected with the holding portion 4 can be further provided with a buckle 15 and a belt 16 to serve as a backpack  
10 facilitating a user to carry personal belongings. As described above and same as the first embodiment, the holding portion 4 of the present embodiment is provided with the switching piece 41 and the switching assembly 42 to facilitate a user to open and close the holding portion 4 and access an object therein at any time, with that the switching mode  
15 includes a zipper, a hook and loop fastener, a snap latch or a magnetic button.

As shown in FIGS. 13 to 18, as the second joining edge 331 is abutted at a top rim of and connected with the first joining edge 131, an upper wall of the annulus-like joining portion 33 is abutted toward an upper wall of  
20 the side wall 13, forming a first containing portion 14 in an un-abutted

space between a lower wall of the joining portion 33 and the side wall 13 to contain the folded rear cover sheet 2 (or any wall of the annulus-like joining portion 33 is abutted toward any wall of the side wall 13 to form the first containing portion 14 in the un-abutted space). Moreover, the

5 second containing portion 35 is formed after the inner containing space 30 of the annulus-like joining portion 33 has been combined with the front cover sheet 1, and the second containing portion 35 further includes a port 34 to connect with the flexible enclosure 3. Therefore, the folded flexible enclosure 3 can be contained in the second containing portion 35

10 through the port 34. On the other hand, the rear cover sheet 2 is further provided with a fixing piece 22 which is located below the first containing portion 14 and a fixing assembly 32 which is located below the joining part 33. By the fixing piece 22 and the fixing assembly 32, the folded rear cover sheet 2 can be contained in the first containing portion 14 and

15 then fixed, wherein the fixing piece 22 and the fixing assembly 32 are a hook and loop fastener or a snap latch.

As shown in FIGS. 19 to 23, when a user is to fold and contain the flexible enclosure 3 in the second containing portion 35 (FIG. 20), he or she should first put downward the holding portion 4 and the exterior side

20 of the front cover sheet 1. At this time, the flexible enclosure 3 and the

rear cover sheet 2 will face upward and the rear cover sheet 2 will be lifted open. When containing, the flexible enclosure 3 is folded from outside to inside to be located in the containing space 30 between the front cover sheet 1 and the rear cover sheet 2, and the front cover sheet 1 and the rear cover sheet 2 are closed by the cover piece 11 and the cover assembly 21. In the present embodiment, in addition to that the exterior side of the front cover sheet 1 can be connected with the holding portion 4, the interior side or the exterior side (not shown in the drawings) of the rear cover sheet 2 can be further provided with the holding portion 4 which is provided with the switching piece 41 and the switching assembly 42, facilitating a user to open and close the holding portion 4 and access an object therein at any time.

In addition to being applied to the flexible enclosure which includes the recycle shopping bag or other kinds of bags, the containing structure disclosed above can be further applied to implementations of all kinds of clothing, such as a sport shirt, an overcoat and clothes. A first implementation of the present invention is a flexible enclosure 3 (clothing) combined with a bag unit 10, which is a backpack structure including a front cover sheet 1, a rear cover sheet 2, a connection portion 12, an outer belt 16 and a flexible enclosure 3 (clothing), wherein an edge of the

front cover sheet 1 is provided with a first joining edge 131 and a cover piece 11; whereas, the first joining edge 131 is provided at a parallel side of the bag unit 10 corresponding to the flexible enclosure 3 (clothing), at the edge of the front cover sheet 1 in the drawing. An edge of the rear cover sheet 2 is provided with a cover assembly 21 corresponding to the cover piece 11; whereas, the cover piece 11 and the cover assembly 22 can be implemented as a zipper. The connection portion 12 is provided at a corresponding position between sides of the front cover sheet 1 and the rear cover sheet 2 to connect the two sheets. The clothing 3 includes a second joining edge 331 and an inner belt 6, wherein the second joining edge 331 is engaged with the first joining edge 131 of the front cover sheet 1 and fixes the front cover sheet 1 at a rear position of the flexible enclosure 3 (clothing). For the flexible enclosure 3 (clothing) and the bag unit 10, in addition to using a fixed joining mode (gluing, hot pressing or sewing) for the first joining edge 131 and the second joining edge 331, the first joining edge 131 and the second joining edge 331 can be also added respectively with a first movable joining piece 130 and a second movable joining piece 330 (such as a zipper, a snap latch, a magnetic button or a hook and loop fastener), thereby providing the flexible enclosure 3 (clothing) and the bag unit 10 with a movable

dismantlement function that when the flexible enclosure 3 (clothing) or the bag unit 10 is damaged or gets dirty, it can be dismantled and replaced for use.

The flexible enclosure 3 (clothing) can be further opened with plural  
5 through-holes 332, allowing plural end parts of the inner belt 6 (a single shoulder strap or a dual shoulder strap at back) to pass through the through-holes 332 from the interior of the flexible enclosure 3 (clothing) to combine outward with the bag unit 10. Next, the first joining edge 131 is engaged with the corresponding second joining edge 331 to fix the front  
10 cover sheet 1 and the flexible enclosure 3 (clothing), wherein an upper end part and a lower end part of the inner belt 6 pass through the plural through-holes 332 of the flexible enclosure 3 (clothing) and then are connected with the upper rim and the lower rim of the front cover sheet 1, such that weight of the bag unit 10 can be supported when a user is  
15 wearing the flexible enclosure 3 (clothing).

Besides, a mask unit 7 is provided between the front cover sheet 1 and the rear cover sheet 2. A side of the mask unit 7 is provided with a connection side 71 which is connected with the bag unit 10. The connection side 71 is provided at an upper rim of the mask unit 7 and is  
20 connected with the upper rim or the first joining edge 131 of the front

cover sheet 1. In addition, the mask unit 7 is further provided with a sheath piece 72 which can sheath the mask unit 7 from top to bottom at an outer periphery of the bag unit 10, thereby achieving a rain-proofing effect for the bag unit 10.

5 The rear cover sheet 2 is provided with an outer belt 16 which is a dual belt or a single belt at a back (not shown in the drawing) and an upper and lower end of which are provided respectively at an upper side and a lower side of the exterior side of the rear cover sheet 2, allowing a user to carry the bag unit 10 and the flexible enclosure 3 (clothing) which is  
10 contained in the containing space 30 from the outer belt 16 of the rear cover sheet 2, when the flexible enclosure 3 (clothing) is contained. The outer belt 16 is loosely or fixedly connected with the bag unit 10 (which is a prior art and is thus not described further). In the present embodiment, the exterior side of the front cover sheet 1 is connected with a holding  
15 portion 4 to provide an additive function of putting in an object in addition to containing the clothing 3. The holding portion 4 is provided with a switching piece 41 and a switching assembly 42 to facilitate a user to open and close the holding portion 4 and access an object therein at any time, wherein the switching mode of the switching piece 41 and the  
20 switching assembly 42 includes a zipper, a hook and loop fastener, a

snap latch or a magnetic button. In the present embodiment, in addition to that the exterior side of the front cover sheet 1 can be connected with the holding portion 4, the inner side or the exterior side (not shown in the drawing) of the rear cover sheet 2 can be further connected with the holding portion 4. As the structures are roughly the same, no further description is provided.

As shown in FIGS. 25 to 31, the flexible enclosure 3 (clothing) is taken out of the containing space 30 of the bag unit 10 and then worn on a user, wherein the front cover sheet 1 is fixed at a rear side, close to a center, of the flexible enclosure 3 (clothing), and the holding portion 4 is connected at the exterior side of the front cover sheet 1 to allow a user to put in an object. A front side of the flexible enclosure 3 (clothing) is provided with a left and right forepart 334, each of which is further provided with a closing piece 333. After wearing the flexible enclosure 3 (clothing), a user can use the closing pieces 333 to close the left and right foreparts 334.

The rear cover sheet 2 is connected with the front cover sheet 1 from the connection portion 12 and when the rear cover sheet 2 is not yet contained in the containing space 30, it is located below the holding portion 4. As shown in FIG. 29 and FIG. 30, after the rear cover sheet 2

has been contained in the containing space 30, it will be hidden behind the holding portion 4 and lie between the holding portion 4 and the flexible enclosure 3 (clothing). As shown in FIG. 26, when the flexible enclosure 3 (clothing) and the mask unit 7 are not used, the holding

5 portion 4 is first made to face downward and the rear cover sheet 2 is lifted open to expose the containing space 30, facilitating putting the flexible enclosure 3 (clothing) and the mask unit 7 in the containing space 30 after folding. When folding, the mask unit 7 and the flexible enclosure 3 (clothing) can be folded downward and the flexible enclosure

10 3 (clothing) is folded toward a center from four sides. At this time, the mask unit 7 and the flexible enclosure 3 (clothing) will become a rectangle after folding, a little smaller than the front cover sheet 1 and above the front cover sheet 1, to be contained in the containing space 30 and closed by the cover piece (assembly) 11 (21), as shown in FIG. 25.

15 After closing the containing space 30, the flexible enclosure 3 (clothing) is put in the containing space 30 and a user can still open the holding portion 4 from the switching piece (assembly) 41 (42) above the holding portion 4 to put in or access an object. When the flexible enclosure 3 (clothing) is contained, the flexible enclosure 3 (clothing) and the inner

20 belt 6 are closed in the containing space 30 between the rear cover sheet

2 and the front cover sheet 1 by the cover piece 11 and the cover assembly 21 and a user can utilize the outer belt 16 above the rear cover sheet 2 (as shown in FIGS. 29 to 31) and use the holding portion 4 as the bag unit 10.

5 Referring to FIG. 32 and FIG. 33, a second implementation of the present invention is a flexible enclosure 3 (clothing) combined with a bag unit 10, which is a bag unit 10 worn at a side (usually called a side pack). The structures and elements included are all the same as those of the bag unit 10 in the first embodiment, with a primary difference being that  
10 the bag unit 10 is worn at a side or at a front of a human body by a single belt. Therefore, the outer belt 16 (not shown in the drawings) and the inner belt 6 are all connected by the single belt at a left and right end of the bag unit 10. When the flexible enclosure 3 (clothing) is not used, the containing mode is the same as that of the first embodiment where the  
15 flexible enclosure 3 (clothing) and the inner belt 6 are contained in the containing space 30 (not shown in the drawings) after folding, and are closed by the cover piece (assembly) 11 (21). When the flexible enclosure 3 (clothing) is contained, the storage function of the bag unit 10 can be still used. In addition, two sides of the bag unit 10 are provided  
20 respectively with a buckle 15 and an outer belt 16 (not shown in the

drawings) which is movably engaged with the buckle 15, allowing a user to carry on a shoulder.

As shown in FIG. 34, a third embodiment of the present invention is a flexible enclosure 3 (clothing) combined with a bag unit 10, which is transversally fixed at a waist of a user (usually called a waist bag). The structures and elements included are the same as those of the side bag unit 10 in the second embodiment, with a primary difference being that the bag unit 10 is connected to a left and right side by the outer belt 16 and is transversally fixed at a user's waist after engaging a male snap 161 with a female snap 162 at open ends of the outer belt 16. As an inner size of the holding portion 4 of the bag unit 10 of the present embodiment is smaller than that of the bag unit 10 in the abovementioned two embodiments, the inner belt 6 is not needed when the loading is not heavy, such that the weight of the bag unit 10 can be supported when a user is wearing the flexible enclosure 3 (clothing). When the flexible enclosure 3 (clothing) is not used, the containing mode is the same as that of the two abovementioned embodiments where the flexible enclosure 3 (clothing) is contained in the containing space 30 (not shown in the drawing) after folding, and is closed by the cover piece (assembly) 11 (21). When the flexible enclosure 3 (clothing) is contained, the

storage function of the bag unit 10 can be still used. When the clothing 3 is contained, the outer belt 16 which is transversally connected at two sides of the bag unit 10 can be fixed on a waist by a user. Besides, the outer belt 16 is loosely or fixedly connected with the bag unit 10 (which is a prior art and is thus not described further). As shown in FIGS. 35 to 37, a fourth embodiment of the present invention applies primarily the flexible enclosure 3 to a bag unit having a handle 31. A hollow space is formed between two end parts of the handle 31, allowing a user to unfolded the flexible enclosure 3 (bag) from the containing space 30, followed by carrying the handle 31 on a shoulder or with a hand, wherein the flexible enclosure 3 (bag) includes a front piece 38, a rear piece 39 and an opening 40. The difference of the present embodiment from the abovementioned embodiments lies in primarily that the connection portion 12 that connects the front cover sheet 1 and the rear cover sheet 2 is bended and latched from top to bottom at an upper rim of the front piece 38 of the flexible enclosure 3 (bag); whereas, the flexible enclosure 3 (bag) can be contained in the containing space 30 formed between the front cover sheet 1 and the rear cover sheet 2 after folding. As the connection portion 12 is latched between two end parts of the handle 31 at the upper rim of the flexible enclosure 3 (bag), weight of the containing

structure and the holding portion 4 is supported by a force a user uses to lift up two end parts of the handle 31, thereby preventing the upper rim of the opening 40 of the flexible enclosure 3 (bag) from suspending and deformation due to the weight of holding portion 4, wherein the first

5 joining edge 131 of the front cover sheet 1 and the corresponding second joining edge 331 of the rear cover sheet 2 are connected by sewing, gluing or hot pressing in a high frequency (not shown in the drawing). Besides, in addition to that the first joining edge 131 of the present embodiment can be provided at the front cover sheet 1, it can be also

10 provided between the front cover sheet 1 and the rear cover sheet 2 or at the connection portion 12, followed by being connected with the second joining edge 331 (not shown in the drawing). On the other hand, the upper rim of the front piece 38 of the flexible enclosure 3 (bag) is further provided with a switching piece 41 and a switching assembly 42, with the

15 implementation mode being a zipper as shown in the drawing or other splitting element such as a hook and loop fastener, a snap latch or a magnetic button (not shown in the drawing). Moreover, the holding portion 4 is connected with the connection portion 12 that is bended downward and is latched between two end parts of the handle 31 of the

20 front piece 38 of the flexible enclosure 3 (bag), and weight of the holding

portion 4 and the containing structure is supported a force a user uses to lift up two end parts of the handle 31. In addition to that the abovementioned lower dent 37 can be provided at the front piece 38, it can be also selectively configured at the rear piece 39 (not shown in the drawing); whereas, the holding portion 4 can be provided at the exterior side of the rear cover sheet 2 or can be selectively provided at the exterior side of the front cover sheet 1 (not shown in the drawing).

Referring to FIG. 35 and FIG. 36, the first joining edge 131 of the front cover sheet 1 and the second joining edge 331 of the front piece 38 of the flexible enclosure 3 (bag) can latch and fix the connection portion 12 in the lower dent 37 at the upper rim of the front piece 38, allowing the holding portion 4 to be located in the opening 40 of the flexible enclosure 3 (bag) (FIG. 37). Besides, inner sides of the front piece 38 and the rear piece 39 of the flexible enclosure 3 (bag) are further provided respectively with a first positioning assembly 321 and a second positioning assembly 322 to correspond to the fixing piece 22 of the rear cover sheet 2 of the collection space 30. As described above, when the rear cover sheet 2 and the holding portion 4 are located in the opening 40 of the flexible enclosure 3 (bag), the holding portion 4 can be attached at the inner side of the front piece 38 of the flexible enclosure 3 (bag) by a

positioning piece 221 and the first positioning assembly 321 to increase stability.

The advantage of this unique design is that after the flexible enclosure 3 (bag) has been taken out of the containing space 30 and when the flexible enclosure 3 (bag) is unfolded, the front cover sheet 1 will be located at the exterior side of the front piece 38 of the flexible enclosure 3 (bag); whereas, the holding portion 4 which is used to put money, letters of credits or other objects can be closed by the switching piece (assembly) 41 (42) and the holding portion 4 will be located in the opening 40 of the flexible enclosure 3 (bag), thereby preventing the money or objects in the holding portion 4 from lost. As shown in FIG. 35 and FIG. 37 again, a user can also select to position the positioning piece 221 at the second positioning assembly 322 on the exterior side of the rear piece 39 of the flexible enclosure 3 (bag), such that the opening 40 of the flexible enclosure 3 (bag) can be closed and the holding portion 4 can be located at the exterior side of the rear piece 39 of the flexible enclosure 3 (bag) (FIG. 37). When a user carries the handle 31 of the flexible enclosure 3 (bag) on a shoulder or with a hand, the exterior side of the rear piece 39 of the flexible enclosure 3 (bag) can be made to lean toward a side of the user's body, facilitating accessing an object or putting the object in the

holding portion 4 and also preventing the money or object in the holding portion 4 from lost. The abovementioned fixing piece 22 and the corresponding first positioning assembly 321 and second positioning assembly 322 can be implemented as a zipper as shown in the drawings  
5 or as a hook and loop fastener, a snap latch or a magnetic button.

Referring to FIGS. 38 to 42, when the flexible enclosure 3 (bag) is not to be used, the holding portion 4 is first made to face downward and the front cover sheet 1 is lifted open upward to expose the containing space 30, facilitating putting the flexible enclosure 3 (bag) in the containing  
10 space 30 after folding. When folding, the flexible enclosure 3 (bag) can be folded toward the center from the left and right sides, allowing the rear piece 39 to overlap on the front piece 38 from rear to front. In addition, the handle 31 is folded downward and at this time, the flexible enclosure 3 (bag) will become a long strip after folding, with a width a little smaller  
15 than that of the front cover sheet 1 (FIG. 40). Next, the long-strip flexible enclosure 3 (bag) is folded or rolled upward and then contained in the containing space 30, followed by being closed by the cover piece (assembly) 11 (21) (FIG. 41 and FIG. 42). After the containing space 30 has been closed, the flexible enclosure 3 (bag) is put in the containing  
20 space 30 and a user can open the holding port 4 to put in or access an

containing space 30 has been closed, the flexible enclosure 3 (bag) is put in the containing space 30 and a user can open the holding portion 4 to put in or access an object from the switching piece (assembly) 41 (42) above the holding portion 4 (FIG. 42).

Referring to FIG. 43 and FIG. 44, the present embodiment is the same as the  
5 abovementioned second embodiment that the holding portion 4 can be applied to a side pack, wherein two sides of the holding portion 4 are provided respectively with the buckle 15 and a connected shoulder strap 16, allowing a user to carry on a shoulder. In addition, the front cover sheet 1 can be further provided with an extension portion 132, an end of which is connected to the second joining edge 331 of the flexible enclosure 3 (bag), whereas the  
10 other end of which can be connected to the first joining edge 131 at the inner side of the front cover sheet 1. Therefore, when the holding portion 4 is loaded too heavily, the holding portion 4 can be extended and be put at a bottom in the flexible enclosure 3 (bag) by the extension portion 132, without causing the opening 40 to suspend and be deformed as the holding portion 4 that is connected at the opening 40 is too heavy. Due to the extension  
15 function of the extension portion 132, the holding portion 4 can be extended and be put at the bottom in the flexible enclosure 3 (bag),

need to provide the lower dent 37 (FIG. 35) at the upper rim of the front piece 38 of the flexible enclosure 3 (bag) to fit with the size of the connection portion 12 of the front cover sheet 1 or there is no need to provide the extension portion 132 at other isolation position (not shown in  
5 the drawing) of the holding portion 4.

Referring to FIG. 45, the present embodiment can also apply the holding portion 4 to a backpack by the first joining edge 131 and the second joining edge 331, whereas the flexible enclosure 3 (bag) applies to a large shopping bag or a luggage bag. A dual shoulder strap 7 is  
10 provided behind the backpack, allowing a user to carry the backpack on his or her back. The front cover sheet 1 and the cover piece (assembly) 11 (21) are the same as those in the abovementioned embodiments and as the front cover sheet 1 is connected with the second joining edge 331 of the flexible enclosure 3 (bag) by the first joining edge 131, when a user  
15 opens the cover piece (assembly) 11 (21) and takes the flexible enclosure 3 (bag) out of the containing space 30, he or she then puts the front cover sheet 1, along with the holding portion 4 and the dual shoulder strap 17, in the flexible enclosure 3 (bag) from the opening 40.

Furthermore, as the entire length of an ordinary backpack is longer, the  
20 holding portion 4 can be manufactured in collaboration with the height of

the flexible enclosure 3 (bag) that the holding portion 4 can be put at the bottom of the flexible enclosure 3 (bag), without causing the opening 40 of the flexible enclosure 3 (bag) to suspend and be deformed as the backpack is too heavy. However, if the length cannot fit, then the present embodiment can also apply the abovementioned extension portion 132 to properly extend and put the backpack at the bottom of the flexible enclosure 3 (bag) (not shown in the drawing).

As shown in FIG. 46, the present invention can also apply the flexible enclosure 3 to a clothes bag, wherein the clothes bag is provided with a handle 31 for carrying with a hand or on a shoulder. The front cover sheet 1 and the cover piece (assembly) 11 (21) are the same as those in the abovementioned embodiments and a user can put a piece of clothes in the holding portion 4 from the opening 40 of the flexible enclosure 3 (bag) and hang the clothes with a hanger 18 in the clothes bag. As it belongs to a conventional technology regarding how to hang the clothes on the hanger 18 through the opening 40 and the structural relationship between the hanger 18 and the clothes bag, no further description is provided.

Referring to FIGS. 47 to 49, a fourth embodiment of the present invention is provided with roughly same structures as those of the

Referring to FIGS. 47 to 49, a fourth embodiment of the present invention is provided with roughly same structures as those of the abovementioned third embodiment, wherein the connection portion 12 that connects the front cover sheet 1 and the rear cover sheet 2 is latched from top to bottom at the upper rim of the front piece 38 of the flexible enclosure 3 (bag), and the folded flexible enclosure 3 (bag) can be contained in the containing space 30 formed between the front cover sheet 1 and the rear cover sheet 2. In addition, the holding portion 4 is provided, allowing a user to access an object in the holding portion 4 from the switching piece (assembly) 41 (42).

The difference of the present embodiment from the third embodiment lies in that a fork portion 310 is further provided between the flexible enclosure 3 (bag) and the handle 31, allowing the front cover sheet 1, the rear cover sheet 2 and the holding part portion 4, which have a smaller overall size, to be connected at the upper rim of the flexible enclosure 3 (bag) by the connection portion 12, the first joining edge 131, the second joining edge 331 and the extension portion 132. As the holding portion 4 and the containing structure should be supported by a force a user uses to lift up two end parts of the handle 31, two ends of the fork portion 310 are connected with the uplift force of the

- taken the flexible enclosure 3 (bag) out of the containing space 30 and unfolded the flexible enclosure 3 (bag), the front cover sheet 1, along with the holding portion 4, should pass through a gap 311 in a center of the fork portion 310 and then the front cover sheet 1 and the rear cover sheet 2 are latched at the upper rim of the opening 40 of the front piece 38 of the flexible enclosure 3 (bag). In addition, the fixing piece 22 in the inner side of the front cover sheet 1 can be further positioned with the first positioning assembly 321 at the exterior side of the flexible enclosure 3 (bag).
- 10 For each abovementioned embodiment, the exterior side of the front cover sheet 1 and the exterior side of the flexible enclosure 3 (bag) can be further provided with mutually corresponded textures and patterns to improve a sense of aesthetics and contrast into a different visual effect. When the holding portion 4 is used alone, the front cover sheet 1 and the
- 15 holding portion 4 can manifest the partial textures or patterns. When the flexible enclosure 3 (bag) is unfolded, the front cover sheet 1 and the holding portion 4 can manifest the textures or patterns contrasting with the flexible enclosure 3 (bag) to improve a sense of aesthetics or exhibit a different visual effect (not shown in the drawings).
- 20 Accordingly, in addition to the abovementioned embodiments, the

a different visual effect (not shown in the drawings).

Accordingly, in addition to the abovementioned embodiments, the present invention can be further applied to other bag units of various functions.

The scope of the claims should not be limited by the preferred embodiments set forth  
5 in the examples, but should be given the broadest interpretation consistent with the description as a whole.

## CLAIMS

1. A cover-type containing structure for flexible enclosures, comprising:  
a front cover sheet, an edge of which is provided with a cover piece;  
a rear cover sheet, an edge of which is provided with a cover assembly corresponding to the  
5 cover piece;  
a connection portion which is provided between the front cover sheet and the rear cover  
sheet to connect the two sheets;  
a first joining edge which is provided: at the front cover sheet; at the rear cover sheet;  
between the front cover sheet and the rear cover sheet; or at the connection portion; and  
10 a flexible enclosure which includes a second joining edge, the front cover sheet and the  
flexible enclosure are connected by engaging the first joining edge with the corresponding  
second joining edge, wherein the front cover sheet is disposed at various positions on the  
flexible enclosure at least including the position close to a center or an edge thereof;  
a containing space being formed between the front cover sheet and the rear cover sheet to  
15 contain the flexible enclosure in folded condition, and the front cover sheet and the rear cover  
sheet being covered by the cover piece and the cover assembly.
2. The cover-type containing structure for flexible enclosures, according to claim  
1, wherein the first joining edge is provided with an extension portion to connect with the  
second joining edge.
- 20 3. The cover-type containing structure for flexible enclosures, according to claim  
1, wherein the connection portion is provided at an upper side of the front cover sheet  
corresponding to an upper side of the rear cover sheet or at a lower side of the front cover  
sheet corresponding to a lower side of the rear cover sheet.

4. The cover-type containing structure for flexible enclosures, according to claim 1, wherein the rear cover sheet is further provided with a fixing piece at a side of the rear cover sheet corresponding to a fixing assembly provided by the flexible enclosure, the rear cover sheet being fixed on the surface of the flexible enclosure by the fixing piece and the fixing assembly; the fixing piece and the fixing assembly including: a zipper; a hook and loop fastener; a snap latch; or a magnetic button.

5. The cover-type containing structure for flexible enclosures, according to claim 1, wherein the second joining edge is partially engaged with the first joining edge and a containing port is formed at a place where the first joining edge is separated from the second joining edge; when the flexible enclosure is unfolded, the rear cover sheet being put in a containing space between the front cover sheet and the flexible enclosure from the containing port, whereas, when the flexible enclosure in folded condition is to be contained in the containing space, the rear cover sheet being taken out of the containing port and the rear cover sheet and the front cover sheet being fixed.

6. The cover-type containing structure for flexible enclosures, according to claim 1, wherein a circumferential length of partial engagement of the first joining edge and the second joining edge is at least a half of an entire circumferential length of the front cover sheet.

7. The cover-type containing structure for flexible enclosures, according to claim 1, wherein a side of the front cover sheet or the rear cover sheet is connected with a holding portion.

8. The cover-type containing structure for flexible enclosures, according to claim 1, wherein a side wall is further provided between the front cover sheet and the cover piece, the flexible enclosure further includes a joining portion which corresponds to the side wall,

the joining portion assumes an annulus-like unit, a radius of which is a little smaller than that of the side wall and an interior of which is formed with a containing space.

9. The cover-type containing structure for flexible enclosures, according to claim 8, wherein the second joining edge is abutted at and connected with the first joining edge, allowing the side wall to enclose the joining portion; the second joining edge being abutted at a top rim of and connected with the first joining edge, an upper wall of the annulus-like joining portion being abutted toward an upper wall of the side wall, and a first containing portion being formed in an un-abutted space between a lower wall of the joining portion and the side wall to contain the rear cover sheet in folded condition.

10. The cover-type containing structure for flexible enclosures, according to claim 9, wherein a second containing portion is formed after the inner containing space of the joining portion has been combined with the front cover sheet and the second containing portion further includes a port to connect with the flexible enclosure, allowing the flexible enclosure in folded condition to be contained in the second containing portion through the port.

11. The cover-type containing structure for flexible enclosures, according to claim 10, wherein the rear cover sheet is further provided with a fixing piece below the joining portion corresponding with a fixing assembly provided by the first containing portion; the rear cover sheet in folded condition being contained and fixed in the first containing portion by the fixing piece and the fixing assembly.

12. The cover-type containing structure for flexible enclosures, according to claim 1, wherein the flexible enclosure is a bag unit.

13. The cover-type containing structure for flexible enclosures, according to claim 12, wherein the connection portion is bended and latched on an upper rim of the bag unit from top to bottom.

14. The cover-type containing structure for flexible enclosures, according to claim 5 13, wherein the upper rim of the bag unit is provided with a lower dent, a dented size of which fits with a size of the connection portion; the connection portion being latched between two end parts of a handle at the upper rim of the bag unit.

15. The cover-type containing structure for flexible enclosures, according to claim 10 13, wherein the bag unit is provided at least with a handle, a fork portion is provided between an end part of the handle and the upper rim of the bag unit, and the connection portion is bended and latched from top to bottom in a central space of the fork portion, allowing that weight of the containing structure is supported by a force a user uses to lift up the end parts of the handle.

16. The cover-type containing structure for flexible enclosures, according to claim 15 13, wherein the front cover sheet is further provided with an extension portion, an end of the extension portion is connected at the first joining edge and the other end is connected at the second joining edge of the flexible enclosure; by the extension portion, the containing space formed by the front cover sheet and the rear cover sheet being extended and put at a bottom in the bag unit to prevent the flexible enclosure from suspending and deformation due to 20 weight of the front cover sheet as the connection portion is latched on the upper rim of the bag unit.

17. The cover-type containing structure for flexible enclosures, according to claim 13, wherein an inner side of the front cover sheet is provided with a positioning piece which is positioned with a first positioning assembly at an exterior side of a front piece of the bag

unit or a second positioning assembly at an exterior side of a rear piece of the bag unit; the positioning piece and the first positioning assembly including: a zipper; a hook and loop fastener; a snap latch; or a magnetic button.

18. The cover-type containing structure for flexible enclosures, according to claim 5 1, wherein the flexible enclosure is a piece of clothing, a side of the front cover sheet or the rear cover sheet is connected with a holding portion, the clothing includes the second joining edge, the first joining edge is engaged with the corresponding second joining edge to fix the front cover sheet along with the clothing; the clothing in folded condition is contained in the containing space formed between the front cover sheet and the rear cover sheet which are 10 further closed by the cover piece and the cover assembly.

19. The cover-type containing structure for flexible enclosures, according to claim 18, wherein the clothing further includes an inner belt which is connected with the clothing and is engaged with the holding portion to form a bag unit, such that weight of the bag unit is supported when a user is wearing the clothing.

15 20. The cover-type containing structure for flexible enclosures, according to claim 19, wherein the first joining edge and the second joining edge are added respectively with a first movable joining piece and a second movable joining piece to provide a movable dismantlement function to the clothing and the bag unit; the first joining piece and the second joining piece including: a zipper; a snap latch; a magnetic button; or a hook and loop 20 fastener.

21. The cover-type containing structure for flexible enclosures, according to claim 18, wherein a front side of the clothing is provided with a left and right forepart, each of which is further provided with a closing piece; the front cover sheet being fixed behind the clothing.

22. The cover-type containing structure for flexible enclosures, according to claim 19, wherein the clothing is provided at least with a port which is located behind the clothing, corresponding to end parts of the inner belt passing through the port of the clothing and being engaged with an upper rim of the front cover sheet.

5 23. The cover-type containing structure for flexible enclosures, according to claim 19, wherein the inner belt is a dual shoulder strap or a single shoulder strap, an upper and lower end of which pass respectively through plural through-holes of the clothing to be located at an upper side and a lower side at an exterior side of the rear cover sheet.

24. The cover-type containing structure for flexible enclosures, according to claim 10 19, wherein the bag unit is provided with an outer belt which is a dual strap or a single strap; the outer belt being loosely or fixedly connected with the bag unit.

25. The cover-type containing structure for flexible enclosures, according to claim 19, wherein a mask unit is provided between the front cover sheet and the rear cover sheet, a side of the mask unit is provided with a connection side to connect with the bag unit.

15 26. The cover-type containing structure for flexible enclosures, according to claim 25, wherein the mask unit is further provided with a sheath piece which sheaths and fixes the mask unit at an outer periphery of the bag unit.

27. The cover-type containing structure for flexible enclosures, according to claim 18, wherein the front cover sheet is fixed in front of the clothing.

20 28. The cover-type containing structure for flexible enclosures, according to claim 18, wherein a port is provided in a front of the clothing, corresponding to the front cover sheet; an inner belt passing through the port of the clothing and being engaged with an upper rim of the front cover sheet.

29. The cover-type containing structure for flexible enclosures, according to claim 24, wherein a side wall is further provided at peripheries of the cover piece of the front cover sheet, the outer belt is a side belt and two end parts of the outer belt are provided at a side wall of the bag unit; the outer belt being loosely or fixedly connected with the bag unit.

5 30. The cover-type containing structure for flexible enclosures, according to claim 19, wherein the inner belt is a side belt, two ends of the inner belt pass respectively through plural through-holes from the interior to the exterior of the clothing, and are connected at the front cover sheet of the bag unit.

10 31. The cover-type containing structure for flexible enclosures, according to claim 24, wherein the outer belt is connected at a left and right side of the holding portion forming the bag unit and is transversally fixed at a user's waist after a male snap has been engaged with a female snap, with the male and female snaps being provided at open ends of the outer belt; the outer belt being loosely or fixedly connected with the bag unit.




FIG. 2  
Prior Art




FIG. 1  
Prior Art




FIG. 3




FIG. 4




FIG. 5

131(331)

41(42)

30

4

301

11(21)

FIG. 6

131(331)

41(42)

4

1

3

301

11(21)

2

FIG. 7

131(331)

41(42)

30

1

3

301

11(21)

2

FIG. 8

131(331)

41(42)

4


1

301

11(21)

3

FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG.21

FIG.22

FIG.23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30



FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42






FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48

