




(86) Date de dépôt PCT/PCT Filing Date: 2011/07/12
(87) Date publication PCT/PCT Publication Date: 2012/02/02
(45) Date de délivrance/Issue Date: 2018/05/22
(85) Entrée phase nationale/National Entry: 2013/01/03
(86) N° demande PCT/PCT Application No.: JP 2011/065872
(87) N° publication PCT/PCT Publication No.: 2012/014669
(30) Priorités/Priorities: 2010/07/30 (JP2010-171940);
2010/10/04 (JP2010-224752)

(51) Cl.Int./Int.Cl. *H04L 9/32* (2006.01)
(72) Inventeurs/Inventors:
SAKUMOTO, KOICHI, JP;
SHIRAI, TAIZO, JP;
HIWATARI, HARUNAGA, JP
(73) Propriétaire/Owner:
SONY CORPORATION, JP
(74) Agent: GOWLING WLG (CANADA) LLP

(54) Titre : DISPOSITIF D'AUTHENTIFICATION, PROCEDE D'AUTHENTIFICATION ET PROGRAMME
(54) Title: AUTHENTICATION DEVICE, AUTHENTICATION METHOD, AND PROGRAM



(57) **Abrégé/Abstract:**

Provided is an authentication device including a key holding unit for holding L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), and an interactive protocol execution unit for performing, with a verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. The interactive protocol execution unit includes a challenge reception unit for receiving L challenges Ch_i from the verifier, a challenge selection unit for arbitrarily selecting $(L-1)$ challenges Ch_i from the L challenges Ch_i received by the challenge reception unit, a response generation unit for generating, by using the secret keys s_i , $(L-1)$ responses Rsp_i respectively for the $(L-1)$ challenges Ch_i selected by the challenge selection unit, and a response transmission unit for transmitting the $(L-1)$ responses Rsp_i generated by the response generation unit to the verifier.

ABSTRACT

Provided is an authentication device including a key holding unit for holding L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), and an interactive protocol execution unit for performing, with a verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. The interactive protocol execution unit includes a challenge reception unit for receiving L challenges Ch_i from the verifier, a challenge selection unit for arbitrarily selecting $(L-1)$ challenges Ch_i from the L challenges Ch_i received by the challenge reception unit, a response generation unit for generating, by using the secret keys s_i , $(L-1)$ responses Rsp_i respectively for the $(L-1)$ challenges Ch_i selected by the challenge selection unit, and a response transmission unit for transmitting the $(L-1)$ responses Rsp_i generated by the response generation unit to the verifier.

Description

Title of Invention

AUTHENTICATION DEVICE, AUTHENTICATION METHOD, AND PROGRAM

5

Technical Field

[0001]

10 The present disclosure relates to an authentication device, an authentication method, and a program.

Background Art

[0002]

15 With a rapid development of information processing technology and communication technology, digitisation of documents, official and private, is rapidly advancing. Accordingly, many individuals and companies are greatly interested in security management of electronic documents. With the increase in the interest, security against tampering, such as eavesdropping and forgery of electronic documents, has come to be hotly debated in many fields. The security against

20 eavesdropping on an electronic document is ensured by encrypting the electronic document, for example. Also, the security against forgery of an electronic document is ensured by using a digital signature, for example. However, encryption and the digital signature have to be sufficiently tamper-resistant.

[0003]

25 The digital signature is used for specifying the author of an electronic document. Accordingly, the digital signature should be able to be generated only by the author of the electronic document. If a malicious third party is able to generate the same digital signature, such third party can impersonate the author of the electronic document. That is, an electronic document is forged by the malicious

30 third party. Various opinions have been expressed regarding the security of the digital signature to prevent such forgery. As digital signature schemes that are

currently widely used, schemes that use a RSA signature scheme and a DSA signature scheme are known, for example.

[0004]

The RSA signature scheme takes “difficulty of prime factorisation of a large
5 composite number (hereinafter, prime factorisation problem)” as a basis for security.
Also, the DSA signature scheme takes “difficulty of solving discrete logarithm
problem” as a basis for security. These bases are based on that algorithms that
efficiently solve the prime factorisation problem and the discrete logarithm problem
by using a classical computer do not exist. That is, the difficulties mentioned above
10 suggest the computational difficulty of a classical computer. However, it is said that
solutions to the prime factorisation problem and the discrete logarithm problem can
be efficiently calculated when a quantum computer is used.

[0005]

Similarly to the RSA signature scheme and the DSA signature scheme,
15 many of the digital signature schemes and public key authentication schemes that are
currently used also take difficulty of the prime factorisation problem or the discrete
logarithm problem as a basis for security. Thus, if the quantum computer is put to
practical use, security of such digital signature schemes and public key
authentication schemes will not be ensured. Accordingly, new digital signature
20 schemes and public key authentication schemes are desired that take as a basis for
security a problem different from problems such as the prime factorisation problem
and the discrete logarithm problem that can be easily solved by the quantum
computer. As a problem which is not easily solved by the quantum computer, there
is a difficulty of solving a multivariate polynomial (hereinafter, multivariate
25 polynomial problem), for example.

[0006]

Other problems that are thought to be difficult to solve by the quantum
computer include the Syndrome Decoding problem, the Constrained Linear Equation
problem, the Permuted Kernel problem, the Permuted Perception problem, the
30 section-finding problem on an algebraic surface, and the like.

[0007]

Among these problems, problems other than the section-finding problem on an algebraic surface are known to be NP-hard. As their applications, for example, non-patent literature 1, and non-patent literature 2 mentioned below disclose public key authentication schemes based on the Syndrome Decoding problem. Furthermore, non-patent literature 3 mentioned below discloses a public key authentication scheme based on the Permuted Kernel problem. Other than these, a public key authentication scheme based on the Constrained Linear Equations problem, a public key authentication scheme based on the Permuted Perceptions problem, and the like are also proposed.

10

Citation List

Non-Patent Literature

[0008]

Non-Patent Literature 1: Jacques Stern, A New Identification Scheme Based on Syndrome Decoding, CRYPTO 1993, p13-21

Non-Patent Literature 2: Jacques Stern, A New Paradigm for Public Key Identification, IEEE Transactions on Information Theory, 1996, p13-21

Non-Patent Literature 3: Adi Shamir, An Efficient Identification Scheme Based on Permuted Kernels (Extended Abstract), CRYPTO 1989, p606-609

20

Summary of Invention

Technical Problem

[0009]

Reference will be made here to a security level of a public key authentication scheme. There are two security levels regarding the security level of the public key authentication scheme. One is a security level sufficient for a passive attack. The other is a security level sufficient for an active attack. The security level sufficient for a passive attack is a level of security that takes into account an attacker who can only eavesdrop on an interaction between a prover and a verifier that is in accordance with a legitimate protocol. On the other hand, the security level sufficient for an active attack is a level of security that takes into

30

account a situation where an attacker himself can directly perform an interactive protocol with a prover. That is, the security level sufficient for an active attack takes into account a situation where an attacker can freely perform an interactive protocol with a prover.

5 [0010]

The existing public key authentication schemes described in the non-patent literatures 1 to 3 mentioned above guarantee the security level sufficient for a passive attack. However, with regard to these existing public key authentication schemes, in the case of a parallel-repetition configuration, it is not known whether the security
10 level sufficient for an active attack is absolutely guaranteed or not. This is because, in the case of the parallel-repetition configuration, it is generally known that zero-knowledge is not preserved. Therefore, to absolutely guarantee the security level sufficient for an active attack in the parallel-repetition configuration, it is necessary to guarantee further another property.

15 [0011]

The existing public key authentication scheme are schemes where a prover proves to a verifier “knowing the s that satisfies $y = F(s)$ for y ” by using one key pair (public key y , secret key s). Accordingly, if interaction that will be accepted by verification was performed, it was not possible to prevent the verifier from knowing
20 the information that “the prover who performed the interaction used the s .” Furthermore, in the parallel-repetition configuration of a public key authentication scheme of this type, if collision resistance was not guaranteed for the F , it was not known if the security level sufficient for an active attack was absolutely guaranteed or not. In fact, the collision resistance is not guaranteed for the function F used in
25 the public key authentication schemes described above.

[0012]

In light of the foregoing, it is desirable to provide an authentication device, an authentication method, and a program which are novel and improved, and which are capable of guaranteeing a security level sufficient for an active attack even if an
30 interactive protocol is repeatedly performed in parallel.

Solution to Problem

[0013]

According to an aspect of the present disclosure in order to achieve the above-mentioned object, there is provided an authentication device which includes a key holding unit for holding L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), and an interactive protocol execution unit for performing, with a verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. The interactive protocol execution unit prevents, at the time of performing the interactive protocol with the verifier, the verifier from knowing which secret key s_i was used.

[0014]

Further, the interactive protocol execution unit may include a challenge reception unit for receiving L challenges Ch_i from the verifier, a challenge selection unit for arbitrarily selecting $(L-1)$ challenges Ch_i from the L challenges Ch_i received by the challenge reception unit, a response generation unit for generating, by using the secret keys s_i , $(L-1)$ responses Rsp_i respectively for the $(L-1)$ challenges Ch_i selected by the challenge selection unit, and a response transmission unit for transmitting the $(L-1)$ responses Rsp_i generated by the response generation unit to the verifier.

[0015]

Further, the interactive protocol execution unit may further include a message transmission unit for transmitting, to the verifier, messages Cmt_i each corresponding to each of the L secret keys s_i . In this case, the challenge reception unit receives a challenge Ch_i indicating a verification pattern selected from k ($k \geq 2$) verification patterns by the verifier according to each message Cmt_i transmitted by the message transmission unit.

[0016]

Further, in a case of the message $Cmt_i = (c_{i,1}, \dots, c_{i,N})$, the message transmission unit may calculate a new message $Cmt' = H(Cmt_1, \dots, Cmt_L)$ using a one-way function H and transmits this message Cmt' to the verifier, and the response transmission unit may transmit, together with the response Rsp_i , an element of the

message Cmt_i that the verifier is not able to restore even when using this response Rsp_i .

[0017]

Further, the key holding unit may not have to hold one secret key s_{i_0} ($1 \leq i_0 \leq L$) among the L secret keys s_i . In this case, the interactive protocol execution unit performs, based on a falsification algorithm, processing related to the secret key s_{i_0} that is to be performed in the interactive protocol.

[0018]

Further, according to another aspect of the present disclosure in order to achieve the above-mentioned object, there is provided an authentication device which includes a key holding unit for holding L secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), a challenge reception unit for receiving Q sets ($Q \geq 2$) of L challenges $Ch_i^{(j)}$ ($j = 1$ to Q) from a verifier, a challenge selection unit for arbitrarily selecting one set of L challenges $Ch_i^{(j)}$ from the Q sets of L challenges $Ch_i^{(j)}$ received by the challenge reception unit, a response generation unit for generating, by using the secret keys s_i , L responses Rsp_i respectively for the L challenges $Ch_i^{(j)}$ selected by the challenge selection unit, and a response transmission unit for transmitting the L responses Rsp_i generated by the response generation unit to the verifier.

[0019]

Further, the interactive protocol execution unit may further include a message transmission unit for transmitting, to the verifier, messages Cmt_i respectively corresponding to the L secret keys s_i . In this case, the challenge reception unit receives a challenge $Ch_i^{(j)}$ indicating a verification pattern selected from k ($k \geq 2$) verification patterns by the verifier according to each message Cmt_i transmitted by the message transmission unit.

[0020]

Further, in a case of the message $Cmt_i = (c_{i,1}, \dots, c_{i,N})$, the message transmission unit may calculate a new message $Cmt' = H(Cmt_1, \dots, Cmt_L)$ using a one-way function H and transmits this message Cmt' to the verifier, and the response

transmission unit may transmit, together with the response Rsp_i , an element of the message Cmt_i that the verifier is not able to restore even when using this response Rsp_i .

[0021]

5 Further, according to another aspect of the present disclosure in order to achieve the above-mentioned object, there is provided an authentication method which includes a key generating step for generating L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), and an interactive protocol performing step for
10 performing, with a verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. The interactive protocol execution step prevents, at the time of performing the interactive protocol with the verifier, the verifier from knowing which secret key s_i was used.

[0022]

15 Further, according to another aspect of the present disclosure in order to achieve the above-mentioned object, there is provided a program for causing a computer to realize a key holding function of holding L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), and an interactive protocol execution function of
20 performing, with a verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. The interactive protocol execution function prevents, at the time of performing the interactive protocol with the verifier, the verifier from knowing which secret key s_i was used.

[0023]

25 Further, according to another aspect of the present disclosure in order to achieve the above-mentioned object, there is provided an authentication method which includes a key generating step for generating L secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$), a challenge receiving step for receiving Q sets (Q
30 ≥ 2) of L challenges $Ch_i^{(j)}$ ($j = 1$ to Q) for a verifier, a challenge selecting step arbitrarily selecting one set of L challenges $Ch_i^{(j)}$ from the Q sets of L challenges

$Ch_i^{(j)}$ that have been received in the challenge receiving step, a response generating step for generating, by using the secret keys s_i , L responses Rsp_i respectively for the L challenges $Ch_i^{(j)}$ that have been selected in the challenge selecting step, and a response transmitting step for transmitting the L responses Rsp_i that have been
 5 generated in the response generating step to the verifier.
 [0024]

Further, according to another aspect of the present disclosure in order to achieve the above-mentioned object, there is provided a program for causing a computer to realize a key holding function of holding L secret keys s_i ($i = 1$ to L) and
 10 L public keys y_i that satisfy $y_i = F(s_i)$ with respect to multivariate polynomials F of n -th order ($n \geq 2$), a challenge reception function of receiving Q sets ($Q \geq 2$) of L challenges $Ch_i^{(j)}$ ($j = 1$ to Q) from a verifier, a challenge selection function of arbitrarily selecting one set of L challenges $Ch_i^{(j)}$ from the Q sets of L challenges $Ch_i^{(j)}$ received by the challenge reception function, a response generation function of
 15 generating, by using the secret keys s_i , L responses Rsp_i respectively for the L challenges $Ch_i^{(j)}$ selected by the challenge selection function, and a response transmission function of transmitting the L responses Rsp_i generated by the response generation function to the verifier. According to another embodiment of the present disclosure, there is provided a computer-readable recording medium in which the
 20 program is recorded.

Advantageous Effects of Invention

[0025]

According to the embodiments of the present disclosure described above, it is possible to guarantee a security level sufficient for an active attack even if an
 25 interactive protocol is repeatedly performed in parallel.

Brief Description of Drawings

[0026]

[Fig. 1] FIG. 1 is an explanatory diagram for describing an algorithm structure of a
 30 public key authentication scheme;

[Fig. 2] FIG. 2 is an explanatory diagram for describing an n -pass public key

authentication scheme;

[Fig. 3] FIG. 3 is an explanatory diagram for describing an interactive protocol of an SSH10a public key authentication scheme;

[Fig. 4] FIG. 4 is an explanatory diagram for describing an interactive protocol of an SSH10b public key authentication scheme;

[Fig. 5] FIG. 5 is an explanatory diagram for describing a serial-repetition configuration of an interactive protocol;

[Fig. 6] FIG. 6 is an explanatory diagram for describing a parallel-repetition configuration of an interactive protocol;

[Fig. 7] FIG. 7 is an explanatory diagram for describing a falsification algorithm against the interactive protocol of the SSH10a public key authentication scheme;

[Fig. 8] FIG. 8 is an explanatory diagram for describing a falsification algorithm against the interactive protocol of the SSH10b public key authentication scheme;

[Fig. 9] FIG. 9 is an explanatory diagram for describing a method of applying a present method #1 to the interactive protocol of the SSH10a public key authentication scheme;

[Fig. 10] FIG. 10 is an explanatory diagram for describing a method of applying the present method #1 to the interactive protocol of the SSH10a public key authentication scheme (modified example 1);

[Fig. 11] FIG. 11 is an explanatory diagram for describing a method of applying the present method #1 to the interactive protocol of the SSH10a public key authentication scheme (modified example 2);

[Fig. 12] FIG. 12 is an explanatory diagram for describing a method of applying the present method #1 to the interactive protocol of the SSH10a public key authentication scheme (modified example 3);

[Fig. 13] FIG. 13 is an explanatory diagram for describing a method of applying the present method #1 to the interactive protocol of the SSH10b public key authentication scheme;

[Fig. 14] FIG. 14 is an explanatory diagram for describing a method of applying the present method #1 to the interactive protocol of the SSH10b public key authentication scheme (modified example);

[Fig. 15] FIG. 15 is an explanatory diagram for describing a method of applying a present method #2 to the interactive protocol of the SSH10a public key authentication scheme;

5 [Fig. 16] FIG. 16 is an explanatory diagram for describing a method of applying the present method #2 to the interactive protocol of the SSH10a public key authentication scheme (modified example);

[Fig. 17] FIG. 17 is an explanatory diagram for describing a method of applying the present method #2 to the interactive protocol of the SSH10b public key authentication scheme;

10 [Fig. 18] FIG. 18 is an explanatory diagram for describing a method of applying the present method #2 to the interactive protocol of the SSH10b public key authentication scheme (modified example);

[Fig. 19] FIG. 19 is an explanatory diagram for describing a method of reducing the amount of communication in the interactive protocol of the SSH10a public key
15 authentication scheme;

[Fig. 20] FIG. 20 is an explanatory diagram for describing a method of reducing the amount of communication in the interactive protocol of the SSH10b public key authentication scheme; and

[Fig. 21] FIG. 21 is an explanatory diagram for describing an example hardware
20 configuration of an information processing apparatus capable of realizing an interactive protocol according to a present embodiment.

Description of Embodiments

[0027]

25 Hereinafter, preferred embodiments of the present disclosure will be described in detail with reference to the appended drawings. Note that, in this specification and the appended drawings, structural elements that have substantially the same function and structure are denoted with the same reference numerals, and repeated explanation of these structural elements is omitted.

30 [0028]

[Flow of Explanation]

The flow of explanation on an embodiment of the present disclosure which will be described below will be briefly stated here. First, an algorithm structure of a public key authentication scheme will be described with reference to FIG. 1. Next, an n-pass public key authentication scheme will be described with reference to FIG. 2.

5 Then, an interactive protocol of an SSH10a public key authentication scheme will be described with reference to FIG. 3. Then, an interactive protocol of an SSH10b public key authentication scheme will be described with reference to FIG. 4. Then, repetition configurations of an interactive protocol will be described with reference to FIGS. 5 and 6. At this point, a security level sufficient for an active attack will

10 be briefly described.

[0029]

Next, a falsification algorithm against the interactive protocol of the SSH10a public key authentication scheme will be described with reference to FIG. 7. Then, a falsification algorithm against the interactive protocol of the SSH10b public

15 key authentication scheme will be described with reference to FIG. 8. Then, methods of applying a method according to a first embodiment (present method #1) of the present disclosure to the interactive protocol of the SSH10a public key authentication scheme will be described with reference to FIGS. 9 to 12. Then, methods of applying the present method #1 to the interactive protocol of the SSH10b

20 public key authentication scheme will be described with reference to FIGS. 13 and 14.

[0030]

Next, methods of applying a method according to a second embodiment (present method #2) of the present disclosure to the interactive protocol of the

25 SSH10a public key authentication scheme will be described with reference to FIGS. 15 and 16. Then, methods of applying the present method #2 to the interactive protocol of the SSH10b public key authentication scheme will be described with reference to FIGS. 17 and 18. Then, methods of reducing the amount of communication in the interactive protocols of the present embodiments will be

30 described with reference to FIGS. 19 and 20. Next, an example hardware configuration of an information processing apparatus capable of realizing interactive

protocols according to present embodiments will be described with reference to FIG. 21. Lastly, technical ideas of the embodiment will be summarized and effects obtained by the technical ideas will be briefly described.

[0031]

5 (Description Items)

1: Introduction

1-1: Algorithm Structure of Public Key Authentication Scheme

1-2: N-Pass Public Key Authentication Scheme

1-3: Interactive Protocol of SSH10a Public Key Authentication Scheme

10 1-4: Interactive Protocol of SSH10b Public Key Authentication Scheme

1-5: Repetition Configuration of Interactive Protocol

1-6: Falsification Algorithm against SSH10a Public Key Authentication Scheme

1-7: Falsification Algorithm against SSH10b Public Key Authentication

15 Scheme

2: First Embodiment (Present Method #1)

2-1: Overview

2-2: Application to SSH10a Public Key Authentication Scheme

2-3: Application to SSH10a Public Key Authentication Scheme (Modified

20 Example 1)

2-4: Application to SSH10a Public Key Authentication Scheme (Modified Example 2)

2-5: Application to SSH10a Public Key Authentication Scheme (Modified Example 3)

25 2-6: Application to SSH10b Public Key Authentication Scheme

2-7: Application to SSH10b Public Key Authentication Scheme (Modified Example)

3: Second Embodiment (Present Method #2)

3-1: Overview

30 3-2: Application to SSH10a Public Key Authentication Scheme

3-3: Application to SSH10a Public Key Authentication Scheme (Modified

Example)

3-4: Application to SSH10b Public Key Authentication Scheme

3-5: Application to SSH10b Public Key Authentication Scheme (Modified Example)

5 4: Supplement

4-1: Extension of Scheme

4-2: Non-Interactive Public Key Authentication Scheme

4-3: Method of Reducing Amount of Communication

5: Hardware Configuration

10 6: Summary

[0032]

<1: Introduction>

Before describing embodiments of the present disclosure in detail, an algorithm structure of a general public key authentication scheme and an n-pass public key authentication scheme will be briefly described.

[0033]

[1-1: Algorithm Structure of Public Key Authentication Scheme]

First, an algorithm structure of a public key authentication scheme will be described with reference to FIG. 1. FIG. 1 is an explanatory diagram for describing an algorithm structure of a public key authentication scheme.

[0034]

(Overview)

A public key authentication scheme is an authentication scheme where a person (prover) convinces another person (verifier) that she is the prover herself by using a public key pk and a secret key sk . For example, a public key pk_A of a prover A is made known to the verifier. On the other hand, a secret key sk_A of the prover A is secretly managed by the prover. According to the public key authentication scheme, a person who knows the secret key sk_A corresponding to the public key pk_A is regarded as the prover A herself.

30 [0035]

In the case the prover A attempts to prove to a verifier B that she is the

prover herself, the prover A can perform an interactive protocol with the verifier B and prove that she knows the secret key sk_A corresponding to the public key pk_A . Then, in the case it is proved by the verifier B, by the interactive protocol, that the prover A knows the secret key sk_A , the legitimacy of the prover A (that she is the
 5 prover herself) is proved.

[0036]

Additionally, to ensure security of the public key authentication scheme, two conditions set forth below are to be satisfied.

[0037]

10 The first condition is to lower as much as possible the probability of falsification being established, at the time the interactive protocol is performed, by a falsifier not having the secret key sk . That this first condition is satisfied is called “soundness.” In other words, with a sound interactive protocol, falsification is not established by a falsifier not having the secret key sk with a non-negligible
 15 probability. The second condition is that, even if the interactive protocol is performed, information on the secret key sk_A of the prover A is not at all leaked to the verifier B. That this second condition is satisfied is called “zero knowledge.”

[0038]

The security of the public key authentication scheme is ensured by using an
 20 interactive protocol having the soundness and zero knowledge as described above.

[0039]

(Model)

In a model of the public key authentication scheme, two entities, namely a prover and a verifier, are present, as shown in FIG. 1. The prover generates a pair of
 25 public key pk and secret key sk unique to the prover by using a key generation algorithm Gen. Then, the prover performs an interactive protocol with the verifier by using the pair of secret key sk and public key pk generated by using the key generation algorithm Gen. At this time, the prover performs the interactive protocol by using a prover algorithm P. As described above, in the interactive protocol, the
 30 prover proves to the verifier, by using the prover algorithm P, that she possesses the secret key sk .

[0040]

On the other hand, the verifier performs the interactive protocol by using a verifier algorithm V, and verifies whether or not the prover possesses the secret key corresponding to the public key that the prover has published. That is, the verifier
 5 is an entity that verifies whether or not a prover possesses a secret key corresponding to a public key. As described, a model of the public key authentication scheme is configured from two entities, namely the prover and the verifier, and three algorithms, namely the key generation algorithm Gen, the prover algorithm P and the verifier algorithm V.

10 [0041]

Additionally, expressions “prover” and “verifier” are used in the following description, but these expressions strictly mean entities. Therefore, the subject that performs the key generation algorithm Gen and the prover algorithm P is an information processing apparatus corresponding to the entity “prover”. Similarly,
 15 the subject that performs the verifier algorithm V is an information processing apparatus. The hardware configuration of these information processing apparatuses is as shown in FIG. 21, for example. That is, the key generation algorithm Gen, the prover algorithm P, and the verifier algorithm V are performed by a CPU 902 based on a program recorded on a ROM 904, a RAM 906, a storage unit 920, a removable
 20 recording medium 928, or the like.

[0042]

(Key Generation Algorithm Gen)

The key generation algorithm Gen is used by a prover. The key generation algorithm Gen is an algorithm for generating a pair of public key pk and secret key
 25 sk unique to the prover. The public key pk generated by the key generation algorithm Gen is published. Furthermore, the published public key pk is used by the verifier. On the other hand, the secret key sk generated by the key generation algorithm Gen is secretly managed by the prover. The secret key sk that is secretly managed is used to prove to the verifier of possession of the secret key sk
 30 corresponding to the public key pk. Formally, the key generation algorithm Gen is represented as formula (1) below as an algorithm that takes security parameter 1^λ (λ

is an integer of 0 or more) as an input and outputs the secret key sk and the public key pk .

[0043]

[Expression 1]

$$5 \quad (sk, pk) \leftarrow Gen(1^\lambda)$$

... (1)

[0044]

(Prover Algorithm P)

The prover algorithm P is used by a prover. The prover algorithm P is an
10 algorithm for proving possession of the secret key sk corresponding to the public key pk . The prover algorithm P is defined as an algorithm that takes the public key pk and the secret key sk of a prover as inputs and performs the interactive protocol with a verifier.

[0045]

15 (Verifier Algorithm V)

The verifier algorithm V is used by a verifier. The verifier algorithm V is an algorithm for verifying, in the interactive protocol, whether or not a prover possesses the secret key sk corresponding to the public key pk . The verifier algorithm V is defined as an algorithm that takes the public key pk of a prover as an
20 input, and that outputs 0 or 1 (1 bit) after performing the interactive protocol with the prover. Moreover, in the case of output 0, the prover is assumed to be illegitimate, and in the case of output 1, the prover is assumed to be legitimate.

[0046]

(Supplement)

25 As described above, the public key authentication scheme has to satisfy two conditions, i.e. soundness and zero knowledge, to ensure security. However, in order to make a prover prove that she possesses the secret key sk , it is necessary that the prover perform a procedure dependent on the secret key sk , notify the verifier of the result and make the verifier perform verification based on the notified contents.
30 Execution of the procedure dependent on the secret key sk is necessary to guarantee

the soundness. On the other hand, it is necessary that information on the secret key sk is not at all leaked to the verifier even when the result of the procedure is notified to the verifier. Accordingly, the key generation algorithm Gen , the prover algorithm P , and the verifier algorithm V are designed so as to satisfy these terms.

5 [0047]

In the foregoing, the algorithm structure of the public key authentication scheme has been described.

[0048]

[1-2: N-Pass Public Key Authentication Scheme]

10 Next, an n -pass public key authentication scheme will be described with reference to FIG. 2. FIG. 2 is an explanatory diagram for describing an n -pass public key authentication scheme.

[0049]

As described above, the public key authentication scheme is an
 15 authentication scheme for proving to a verifier, in an interactive protocol, that a prover possesses a secret key sk corresponding to a public key pk . Moreover, to guarantee the security of the public key authentication scheme, two conditions, namely soundness and zero knowledge, have to be satisfied. Accordingly, as shown in FIG. 2, in the interactive protocol, information exchange is performed n times
 20 between the prover and the verifier while execution of processes is being performed by both prover and verifier.

[0050]

In the case of the n -pass public key authentication scheme, a process is performed by the prover using the prover algorithm P (Step 1), and information T_1 is
 25 transmitted to the verifier. Next, a process is performed by the verifier using the verifier algorithm V (Step 2), and information T_2 is transmitted to the prover. Processes (Step 3) to (Step n) are performed in a similar manner and pieces of information $T_3, \dots, T_n$ are transmitted, and a process (Step $n+1$) is performed. Such public key authentication scheme based on an interactive protocol where pieces of
 30 information are transmitted/received n times is called the “ n -pass” public key authentication scheme.

[0051]

In the foregoing, the n-pass public key authentication scheme has been described.

[0052]

5 [1-3: Interactive Protocol of SSH10a Public Key Authentication Scheme]

Next, an interactive protocol of an SSH10a public key authentication scheme will be described with reference to FIG. 3. FIG. 3 is an explanatory diagram for describing an interactive protocol of an SSH10a public key authentication scheme. Additionally, an SSH10a public key authentication scheme is one of the public key authentication schemes devised by the present inventors (Sakumoto, Shirai, and Hiwatari) that are based on the problem of solving a multi-order multivariate simultaneous equation. Furthermore, this SSH10a public key authentication scheme is an example of a 3-pass public key authentication scheme.

[0053]

15 Additionally, the problem of solving the multi-order multivariate simultaneous equation is a problem for obtaining a vector $(s_1, \dots, s_n) \in K^n$ that satisfies $(f_1(s_1, \dots, s_n), \dots, f_m(s_1, \dots, s_n)) = y$ when m multi-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ on a ring K and a vector $y \in K^m$ are given. A problem of solving a multivariate simultaneous equation of second or higher order is called an NP-hard problem, and it belongs to a class of problems that are extremely difficult to solve.

[0054]

Now, the interactive protocol of the SSH10a public key authentication scheme is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. In the following, contents of each algorithm will be described.

[0055]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described.

30 The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and a vector $s =$

$(s_1, \dots, s_n) \in K^n$. Next, the key generation algorithm Gen calculates $y = (y_1, \dots, y_m) \leftarrow (f_1(s), \dots, f_m(s))$. Then, the key generation algorithm Gen sets $(f_1, \dots, f_m, y)$ to the public key pk , and sets s to the secret key. Additionally, in the following, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$.
 5 [0056]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 3. The interactive protocol of the SSH10a public key authentication scheme is for making a verifier prove that “prover knows the s that satisfies $y = F(s)$ ” without leaking information on the s at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.
 15 [0057]

Here, reference will be made to the property of the second-order polynomial.
 [0058]

A set of m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ can be represented as formula (2) below. Moreover, $x = (x_1, \dots, x_n)$ is a vector indicating n variables. Also, $A_1, \dots, A_m$ are an $n \times n$ matrix. Also, $b_1, \dots, b_m$ are an $n \times 1$ vector. Furthermore, c is an $m \times 1$ vector.
 20 [0059]

[Expression 2]

$$F(x) = \begin{pmatrix} f_1(x) \\ \vdots \\ f_m(x) \end{pmatrix} = \begin{pmatrix} x^T A_1 x + b_1^T x \\ \vdots \\ x^T A_m x + b_m^T x \end{pmatrix} + c$$

25

... (2)

[0060]

Using this representation, a set of polynomials F can be represented as formulae (3) and (4) below. That this representation holds can be easily confirmed from formula (5) below.

5 [0061]

[Expression 3]

$$F(x_1 + x_2) = F(x_1) + F(x_2) + F_b(x_1, x_2) - c$$

... (3)

$$F_b(x_1, x_2) = \begin{pmatrix} x_2^T (A_1^T + A_1) x_1 \\ \vdots \\ x_2^T (A_m^T + A_m) x_1 \end{pmatrix}$$

10 ... (4)

$$\begin{aligned} f_l(x_1 + x_2) &= (x_1 + x_2)^T A_l (x_1 + x_2) + b_l^T (x_1 + x_2) + c_l \\ &= x_1^T A_l x_1 + x_1^T A_l x_2 + x_2^T A_l x_1 + x_2^T A_l x_2 + b_l^T x_1 + b_l^T x_2 + c_l \\ &= f_l(x_1) + f_l(x_2) - c_l + x_1^T A_l x_2 + x_2^T A_l x_1 \\ &= f_l(x_1) + f_l(x_2) - c_l + x_1^T (A_l^T)^T x_2 + x_2^T A_l x_1 \\ &= f_l(x_1) + f_l(x_2) - c_l + (A_l^T x_1)^T x_2 + x_2^T A_l x_1 \\ &= f_l(x_1) + f_l(x_2) - c_l + x_2^T (A_l^T x_1) + x_2^T A_l x_1 \\ &= f_l(x_1) + x_2^T (A_l^T + A_l) x_1 + f_l(x_2) - c_l \end{aligned}$$

... (5)

[0062]

When dividing $F(x_1+x_2)$ into three parts, i.e. a part dependent on x_1 , a part
15 dependent on x_2 , and a part dependent on both x_1 and x_2 , in this manner, the part $F_b(x_1, x_2)$ dependent on both x_1 and x_2 will be a bilinear map with respect to x_1 and x_2 .

Additionally, the SSH10a public key authentication scheme described below uses the property of the second-order polynomial as described above.

[0063]

We will return to the explanation of the prover algorithm P and the verifier
5 algorithm V of the interactive protocol of the SSH10a public key authentication scheme (see FIG. 3).

[0064]

Step 1:

First, the prover algorithm P arbitrarily selects a number w . Then, the
10 prover algorithm P applies generates a vector $r \in K^n$ and a number w' by applying the number w to a pseudo random number generator G_1 . That is, the prover algorithm P calculates $(r, w') \leftarrow G_1(w)$. Next, the prover algorithm P generates two vectors $t \in K^n$ and $e \in K^m$ by applying the number w' to a pseudo random number generator G_2 . That is, the prover algorithm P calculates $(t, e) \leftarrow G_2(w')$. Then, the prover
15 algorithm P calculates $z \leftarrow s - r$. This calculation corresponds to an operation of masking the secret key s by the vector r . Furthermore, the prover algorithm P calculates $t' \leftarrow r + t$. Then, the prover algorithm P calculates $e' \leftarrow F(r) - c + e$.

[0065]

Next, the prover algorithm P calculates $F_b(z, t)$ based on the definition of the
20 function F_b shown by the formulac (3) and (4), and generates a hash value c_1 of $F_b(z, t) + e$ and z . That is, the prover algorithm P calculates $c_1 \leftarrow H_1(F_b(z, t) + e, z)$. Furthermore, the prover algorithm P generates a hash value c_2 of the number w' . That is, the prover algorithm P calculates $c_2 \leftarrow H_2(w')$. Furthermore, the prover algorithm P generates a hash value c_3 of two vectors t' and e' . That is, the prover
25 algorithm P calculates $c_3 \leftarrow H_3(t', e')$.

[0066]

Next, the prover algorithm P sets $St \leftarrow (F, y, s, r, t, e, z, t', e')$ and $Cmt \leftarrow (c_1, c_2, c_3)$. Then, Cmt generated in Step 1 is sent to the verifier (verifier algorithm V). Additionally, $H_1(\dots)$, $H_2(\dots)$, and $H_3(\dots)$ are hash functions. Furthermore, the
30 operation of Step 1 will be expressed as $(Cmt; St) \leftarrow P_{a,1}(F, y, s; r, t, e)$.

[0067]

Step 2:

The verifier algorithm V that received Cmt selects a verification pattern to be used from three verification patterns. Then, the verifier algorithm V sends to the prover (prover algorithm P) a challenge $Ch \in_R \{0, 1, 2\}$ indicating the selected verification pattern.
5 [0068]

Step 3:

The prover algorithm P that received Ch generates a response Rsp to be sent back to the verifier algorithm V in response to the challenge Ch received from the verifier algorithm V. If $Ch = 0$, the prover algorithm P generates a response $Rsp \leftarrow (r, t, e)$. Also, if $Ch = 1$, the prover algorithm P generates a response $Rsp = (z, t, e)$. Furthermore, if $Ch = 2$, the prover algorithm P generates a response $Rsp = (z, t', e')$. Additionally, the operation of Step 3 will be expressed as $Rsp \leftarrow P_{a,2}(Ch; St)$. Furthermore, the Rsp generated in Step 3 is sent to the verifier (verifier algorithm V).
10
15 [0069]

Step 4:

The verifier algorithm V that received Rsp performs any of the following verifications for the Rsp that was received.
[0070]

20 If $Ch = 0$, the verifier algorithm V performs $(r'', t'', e'') \leftarrow Rsp$. Then, verifier algorithm V verifies whether $c_2 = H_2(t'', e'')$ and $c_3 = H_3(r'' + t'', F(r'') - c + e'')$ hold true or not.

If $Ch = 1$, the verifier algorithm V performs $(z'', t'', e'') \leftarrow Rsp$. Then, the verifier algorithm V verifies whether $c_1 = H_1(F_b(z'', t'') + e'', z'')$ and $c_2 = H_2(t'', e'')$
25 hold true or not.

If $Ch = 2$, the verifier algorithm V performs $(z'', t''', e''') \leftarrow Rsp$. Then, the verifier algorithm V verifies whether $c_1 = H_1(F(z'') + F_b(z'', t''') + e''' - y, z'')$ and $c_3 = H_3(t''', e''')$ hold true or not.

[0071]

30 Additionally, the verification operation of Step 4 will be expressed as $0/1 \leftarrow Dec_a(F, y; Cmt, Ch, Rsp)$. In this operation, an output 1 indicates a

verification success, and an output 0 indicates a verification failure.

[0072]

In the foregoing, contents of processing by the prover algorithm P and the verifier algorithm V in the SSH10a public key authentication scheme have been
5 described. Additionally, in the above scheme, c_1 , c_2 and c_3 are calculated using the hash functions H_1 , H_2 and H_3 , but a commitment function COM may also be used instead of the hash functions H_1 , H_2 and H_3 . Furthermore, throughout this specification, the hash function may be replaced by the commitment function COM.

[0073]

10 The commitment function COM is a function that takes as arguments a character string S and a random number ρ . Examples of the commitment function include a scheme presented by Shai Halevi and Silvio Micali at the International Conference CRYPTO 1996, and the like. In the case of using this commitment function, random numbers ρ_1 , ρ_2 and ρ_3 are prepared before calculating c_1 , c_2 and c_3 ,
15 and c_1 , c_2 and c_3 are generated by applying commitment functions $\text{COM}(\cdot, \rho_1)$, $\text{COM}(\cdot, \rho_2)$, and $\text{COM}(\cdot, \rho_3)$ instead of hash functions $H_1(\cdot)$, $H_2(\cdot)$, and $H_3(\cdot)$. Furthermore, ρ_1 is sent, included in the response, from the prover algorithm P to the verifier algorithm V.

[0074]

20 [1-4: Interactive Protocol of SSH10b Public Key Authentication Scheme]

Next, an interactive protocol of an SSH10b public key authentication scheme will be described with reference to FIG. 4. FIG. 4 is an explanatory diagram for describing an interactive protocol of an SSH10b public key authentication scheme. Additionally, an SSH10b public key authentication scheme is one of the
25 public key authentication schemes devised by the present inventors (Sakumoto, Shirai, and Hiwatari) that are based on the problem of solving a multi-order multivariate simultaneous equation. Furthermore, this SSH10b public key authentication scheme is an example of a 5-pass public key authentication scheme.

[0075]

30 Similarly to the interactive protocol of the SSH10a public key authentication scheme, the interactive protocol of the SSH10b public key

authentication scheme is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. In the following, contents of each algorithm will be described.

[0076]

5 (Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and a vector $s = (s_1, \dots, s_n) \in K^n$. Next, the key generation algorithm Gen calculates $y = (y_1, \dots, y_m) \leftarrow (f_1(s), \dots, f_m(s))$. Then, the key generation algorithm Gen sets $(f_1, \dots, f_m, y)$ to the public key pk , and sets s to the secret key. Additionally, in the following, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$.

[0077]

15 (Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 4. The interactive protocol of the SSH10b public key authentication scheme is for making a verifier prove that “prover knows the s that satisfies $y = F(s)$ ” without leaking information on the s at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0078]

25 The interactive protocol of the SSH10b public key authentication scheme is configured from processing steps 1 to 6 shown in FIG. 4. In the following, the process of each step will be described.

[0079]

Step 1:

30 First, the prover algorithm P arbitrarily selects a number w . Then, the prover algorithm P generates vectors $r \in K^n$, $t \in K^n$ and $e \in K^m$ by applying the number

w to a pseudo random number generator G. That is, the prover algorithm P calculates $(r, t, e) \leftarrow G(w)$. Next, the prover algorithm P calculates $z \leftarrow s - r$. This calculation corresponds to an operation of masking the secret key s by the vector r.

[0080]

5 Next, the prover algorithm P generates a hash value c_1 of $F_b(z, t) + e$ and z. That is, the prover algorithm P calculates $c_1 \leftarrow H_1(F_b(z, t) + e, z)$. Furthermore, the prover algorithm P generates a hash value c_2 of the vectors r, t and e. That is, the prover algorithm P calculates $c_2 \leftarrow H_2(r, t, e)$. Additionally, $H_1(\dots)$ and $H_2(\dots)$ are hash functions.

10 [0081]

 Next, the prover algorithm P sets $St_A \leftarrow (F, y, s, r, t, e, z)$ and $Cmt_A \leftarrow (c_1, c_2)$. Then, Cmt_A generated in Step 1 is sent to the verifier (verifier algorithm V). Additionally, $H_1(\dots)$ and $H_2(\dots)$ are hash functions. Furthermore, the operation of Step 1 will be expressed as $(Cmt_A; St_A) \leftarrow P_{b,1}(F, y, s; r, t, e)$.

15 [0082]

 Step 2:

 The verifier algorithm V that received Cmt_A selects one random number α from q types of elements of a ring K. Then, the verifier algorithm V sends a challenge $Ch_A = \alpha$ to the prover (prover algorithm P).

20 [0083]

 Step 3:

 The prover algorithm P that received Ch_A calculates $t' \leftarrow \alpha r + t$. Furthermore, the prover algorithm P calculates $e' \leftarrow \alpha(F(r) - c) + e$. Then, the prover algorithm P sets $St_B \leftarrow (St_A, Ch_A, t', e')$ and $Cmt_B \leftarrow (t', e')$. Furthermore, the prover algorithm P sends Cmt_B to the verifier (verifier algorithm V). Additionally, the operation of Step 3 will be expressed as $(Cmt_B; St_B) \leftarrow P_{b,2}(Ch_A; St_A)$.

[0084]

 Step 4:

 The verifier algorithm V that received Cmt_B selects a verification pattern to be used from two verification patterns. Then, the verifier algorithm V sends to the prover (prover algorithm P) a challenge $Ch_B \in_R \{0, 1\}$ indicating the selected

30

verification pattern.

[0085]

Step 5:

The prover algorithm P that received Ch_B generates a response Rsp to be
 5 sent back to the verifier (verifier algorithm V) in response to the challenge Ch_B
 received from the verifier algorithm V in the following manner. If $Ch_B = 0$, the
 prover algorithm P sets to $Rsp \leftarrow r$. If $Ch_B = 1$, the prover algorithm P sets to $Rsp \leftarrow z$.
 Then, the prover algorithm P sends the response Rsp to the verifier (verifier
 algorithm V). Additionally, the operation of Step 5 will be expressed as
 10 $Rsp \leftarrow P_{b,3}(Ch_B; St_B)$.

[0086]

Step 6:

The verifier algorithm V that received the response Rsp performs the
 following verification processes using the response Rsp received from the prover
 15 (prover algorithm P).

[0087]

If $Ch_B = 0$, the verifier algorithm V takes $r'' \leftarrow Rsp$ and verifies whether $c_2 =$
 $H_2(r'', t' - \alpha r'', e' - \alpha(F(r'') - c))$ holds true or not.

If $Ch_B = 1$, the verifier algorithm V takes $z'' \leftarrow Rsp$ and verifies whether $c_1 =$
 20 $H_1(\alpha(F(z'') - y) + F_b(z'', t') + e', z'')$ holds true or not.

[0088]

Additionally, the verification operation of Step 6 will be expressed as
 $0/1 \leftarrow Dec_b(F, y; Cmt_A, Ch_A, Cmt_B, Ch_B, Rsp)$. In this operation, an output 1
 indicates a verification success, and an output 0 indicates a verification failure.

25 [0089]

In the foregoing, contents of processing by the prover algorithm P and the
 verifier algorithm V in the SSH10b public key authentication scheme have been
 described. Additionally, in the above scheme, c_1 and c_2 are calculated using the
 hash functions H_1 and H_2 , but the commitment function COM may also be used
 30 instead of the hash functions H_1 and H_2 .

[0090]

[1-5: Repetition Configuration of Interactive Protocol]

Now, when adopting the interactive protocol of the SSH10a public key authentication scheme described above, the probability of falsification succeeding can be suppressed to $2/3$ or less. Accordingly, if this interactive protocol is performed twice, the probability of falsification succeeding can be suppressed to $(2/3)^2$ or less. In the same manner, if this interactive protocol is performed N times, the probability of falsification succeeding becomes $(2/3)^N$, and if N is a sufficiently large number (for example, $N = 140$), the probability of falsification succeeding is reduced to a negligible level.

10 [0091]

Similarly, when adopting the interactive protocol of the SSH10b public key authentication scheme described above, the probability of falsification succeeding can be suppressed to $(1/2+1/2q)$ or less. Accordingly, if this interactive protocol is performed twice, the probability of falsification succeeding can be suppressed to $(1/2+1/2q)^2$ or less. In the same manner, if this interactive protocol is performed N times, the probability of falsification succeeding becomes $(1/2+1/2q)^N$, and if N is a sufficiently large number (for example, $N = 80$), the probability of falsification succeeding is reduced to a negligible level.

[0092]

20 Additionally, not only for the SSH10a public key authentication scheme and the SSH10b public key authentication scheme, but also for the public key authentication schemes disclosed in the non-patent literatures 1 to 3 mentioned above, when the interactive protocol is performed once and the probability of falsification success is not sufficiently small, the probability of falsification success has to be reduced by repeatedly performing the interactive protocol. As a method of repeatedly performing the interactive protocol, there are a serial-repetition configuration shown in FIG. 5 and a parallel-repetition configuration shown in FIG. 6.

[0093]

30 The serial-repetition configuration is a method of sequentially performing the interactive protocol as shown in FIG. 5, where the interactive protocol is performed once, and when the first round is completed, the second round is

performed, and when the second round is completed, the third round is performed. On the other hand, the parallel-repetition configuration is a method of simultaneously transmitting messages for N rounds at each pass as shown in FIG. 6, where first-pass messages $m_{1,1}, \dots, m_{N,1}$ for N rounds are simultaneously transmitted, and then
5 second-pass messages $m_{1,2}, \dots, m_{N,2}$ for the N rounds are simultaneously transmitted, and then third-pass messages $m_{1,3}, \dots, m_{N,3}$ for the N rounds are simultaneously transmitted.

[0094]

Now, the public key authentication schemes disclosed in the non-patent
10 literatures 1 to 3 mentioned above, the SSH10a public key authentication scheme and the SSH10b public key authentication scheme guarantee a security level sufficient for a passive attack. However, with these public key authentication schemes, it was not known whether a security level sufficient for an active attack was absolutely guaranteed or not in the case the parallel-repetition configuration was adopted.
15 These public key authentication scheme were schemes where a prover proved to a verifier that “the prover knows the s that satisfies $y = F(s)$ for y” by using one key pair (public key y, secret key s).

[0095]

Accordingly, if interaction that will be accepted by verification was
20 performed, it was not possible to prevent the verifier from knowing the information that “the prover who performed the interaction used the s.” Furthermore, collision resistance is not guaranteed for the F that is used in these schemes. As a result, with these public key authentication schemes, it was not known whether a security level sufficient for an active attack was absolutely guaranteed or not in the case the
25 parallel-repetition configuration was adopted. Particularly, in the case of performing these public key authentication schemes using the parallel-repetition configuration described above, no method was known for guaranteeing the security level sufficient for an active attack.

[0096]

30 Accordingly, the present inventors have devised mechanisms of guaranteeing the security level sufficient for an active attack at the time of

performing these public key authentication scheme using the parallel-repetition configuration. These mechanisms (present method #1, present method #2) will be described later in detail taking the SSH10a public key authentication scheme and the SSH10b public key authentication scheme as examples.

5 [0097]

[1-6: Falsification Algorithm against SSH10a Public Key Authentication Scheme]

Here, consideration will be given, with reference to FIG. 7, to a falsification algorithm that succeeds with a probability of $2/3$ in the SSH10a public key authentication scheme (one interactive protocol). FIG. 7 is an explanatory diagram for describing a falsification algorithm that succeeds with a probability of $2/3$ in the SSH10a public key authentication scheme (one interactive protocol). This falsification algorithm is an algorithm where a falsifier “pretends that he knows the s that satisfies $y = F(s)$ ” to a verifier. However, even if this falsification algorithm is adopted, falsification will fail with a probability of $1/3$.

15 [0098]

Step 1:

First, a falsifier (falsification algorithm) generates vectors $s, r, t \in K^n$ and $e \in K^m$. Next, the falsification algorithm arbitrarily selects $Ch^* \in \{0, 1, 2\}$. This Ch^* corresponds to a verification pattern where the falsification algorithm is not able to give a response. Additionally, the s used here is not a legitimate secret key. However, with a verification pattern other than the Ch^* , a prover (prover algorithm P) can give a correct response without using a legitimate secret key.

20 [0099]

Next, the falsification algorithm calculates $z \leftarrow s - r$ and $t' \leftarrow r + t$. Furthermore, if $Ch^* = 0$, the falsification algorithm calculates $e' \leftarrow y - F(s) + F(r) - c + e$. On the other hand, if $Ch^* = 1$ or 2 , the falsification algorithm calculates $e' \leftarrow F(r) - c + e$. Then, if $Ch^* = 0$ or 2 , the falsification algorithm calculates $c_1 \leftarrow H_1(F_b(z, t) + e, z)$. On the other hand, if $Ch^* = 1$, the falsification algorithm calculates $c_1 \leftarrow H_1(F(z) + F_b(z, t') + e' - y, z)$.

30

[0100]

Next, the falsification algorithm calculates $c_2 \leftarrow H_2(t, e)$ and $c_3 \leftarrow H_3(t', e')$. Then, the falsification algorithm sets $St \leftarrow (Ch^*, F, y, s, r, t, e, z, t', e')$ and $Cmt \leftarrow (c_1, c_2, c_3)$. Next, the falsification algorithm sends Cmt to a verifier (verifier algorithm V). Additionally, the operation of Step 1 will be expressed as $(Cmt; St) \leftarrow M_{a,1}(F, y;$
5 $Ch^*, s, r, t, e)$.
[0101]

Step 2:

The verifier algorithm V that received Cmt selects a verification pattern to be used from three verification patterns. Then, the verifier algorithm V sends to the
10 falsifier (falsification algorithm) a challenge $Ch \in_R \{0, 1, 2\}$ indicating the selected verification pattern.
[0102]

Step 3:

The falsification algorithm that received Ch generates a response Rsp to be
15 sent back to the verifier algorithm V in response to the challenge Ch received from the verifier algorithm V . Additionally, if $Ch = Ch^*$, the falsification algorithm outputs an error and ends the interactive protocol. If $Ch \neq Ch^*$ and $Ch = 0$, the falsification algorithm generates a response $Rsp \leftarrow (r, t, e)$. Also, if $Ch = 1$, the falsification algorithm generates a response $Rsp = (z, t, e)$. Furthermore, if $Ch = 2$,
20 the falsification algorithm generates a response $Rsp = (z, t', e')$.
[0103]

Additionally, the operation of Step 3 will be expressed as $Rsp \leftarrow M_{a,2}(Ch; St)$. Furthermore, the Rsp generated in Step 3 is sent to the verifier (verifier algorithm V).
[0104]

25 Step 4:

If $Ch \neq Ch^*$, since the response Rsp is sent to the verifier algorithm V , a verification process $0/1 \leftarrow Dec_a(F, y; Cmt, Ch, Rsp)$ is performed by the verifier algorithm V .

[0105]

30 In the foregoing, a falsification algorithm against the SSH10a public key authentication scheme has been described. As described, even if the s is arbitrarily

selected, a Rsp which will pass verification with a probability of $2/3$ (probability of $Ch \neq Ch^*$) can be sent back to the verifier. Therefore, falsification will succeed with a probability of $2/3$ in a one interactive protocol. Thus, the repetition configuration described above will be adopted.

5 [0106]

[1-7: Falsification Algorithm against SSH10b Public Key Authentication Scheme]

Next, consideration will be given, with reference to FIG. 8, to a falsification algorithm that succeeds with a probability of $1/2$ in the SSH10b public key authentication scheme (one interactive protocol). FIG. 8 is an explanatory diagram for describing a falsification algorithm that succeeds with a probability of $1/2$ in the SSH10b public key authentication scheme (one interactive protocol). This falsification algorithm is an algorithm where a falsifier “pretends that he knows the s that satisfies $y = F(s)$ ” to a verifier. However, even if this falsification algorithm is adopted, falsification will fail with a probability of $1/2$.

15 [0107]

Step 1:

First, a falsifier (falsification algorithm) generates vectors $s, r, t \in K^n$ and $e \in K^m$. Next, the falsification algorithm arbitrarily selects $Ch^*_B \in \{0, 1\}$. This Ch^*_B corresponds to a verification pattern where the falsification algorithm is not able to provide a response with respect to the group of i_0 . Additionally, the s_{i_0} used here is not a legitimate secret key, but the falsification algorithm can give a correct response without using a legitimate secret key with respect to a verification pattern other than the Ch^*_B .

25 [0108]

Next, the falsification algorithm calculates $z \leftarrow s - r$. Then, the falsification algorithm calculates $c_1 \leftarrow H_1(F_b(z, t) + e, z)$ and $c_2 \leftarrow H_2(r, t, e)$. Then, the falsification algorithm sets $St_A \leftarrow (F, y, Ch^*_B, s, r, t, e, z)$ and $Cmt_A \leftarrow (c_1, c_2)$. Then, Cmt_A generated in Step 1 is sent to a verifier (verifier algorithm V). Additionally, $H_1(\dots)$ and $H_2(\dots)$ are hash functions. Furthermore, the operation of Step 1 will be expressed as $(Cmt_A; St_A) \leftarrow M_{b,1}(F, y; Ch^*_B, s, r, t, e)$.

30

[0109]

Step 2:

The verifier algorithm V that received Cmt_A selects a random number α from q types of elements of a ring K . Then, the verifier algorithm V sends a
 5 challenge $Ch_A = \alpha$ to the falsifier (falsification algorithm).

[0110]

Step 3:

The falsification algorithm that received Ch_A calculates $t' \leftarrow \alpha r + t$. Furthermore, if $Ch_B^* = 1$, the falsification algorithm calculates $e' \leftarrow \alpha(F(r) - c) + e$. On
 10 the other hand, if $Ch_B^* = 0$, the falsification algorithm calculates $e' \leftarrow \alpha(y - F(s) + F(r) - c) + e$. Then, the falsification algorithm sets $St_B \leftarrow (St_A, Ch_A, t', e')$ and $Cmt_B \leftarrow (t', e')$. Furthermore, the falsification algorithm sends Cmt_B to the verifier (verifier algorithm V). Additionally, the operation of Step 3 will be expressed as $(Cmt_B; St_B) \leftarrow M_{b,2}(Ch_A; St_A)$.

15 [0111]

Step 4:

The verifier algorithm V that received Cmt_B selects a verification pattern to be used from two verification patterns. Then, the verifier algorithm V sends to the
 falsifier (falsification algorithm) a challenge $Ch_B \in_R \{0, 1\}$ indicating the selected
 20 verification pattern.

[0112]

Step 5:

If $Ch_B = Ch_B^*$, the falsification algorithm that received Ch_B outputs an error and ends the interactive protocol. If $Ch_B \neq Ch_B^*$, the falsification algorithm
 25 generates a response Rsp to be sent back to the verifier (verifier algorithm V) in response to the challenge Ch_B received from the verifier algorithm V in the following manner.

[0113]

If $Ch_B = 0$, the falsification algorithm sets to $Rsp \leftarrow r$. If $Ch_B = 1$, the
 30 falsification algorithm sets to $Rsp \leftarrow z$. Then, the falsification algorithm sends the response Rsp to the verifier (verifier algorithm V). Additionally, the operation of

Step 5 will be expressed as $Rsp \leftarrow M_{b,3}(Ch_B; St_B)$.

[0114]

Step 6:

If $Ch_B \neq Ch_B^*$, since the response Rsp is sent to the verifier algorithm V, a
 5 verification process $0/1 \leftarrow Dec_b(F, y; Cmt_A, Ch_A, Cmt_B, Ch_B, Rsp)$ is performed by the
 verifier algorithm V.

[0115]

In the foregoing, a falsification algorithm against the SSH10b public key
 authentication scheme has been described. As described, even if the s is arbitrarily
 10 selected, a Rsp which will pass verification with a probability of 1/2 (probability of
 $Ch_B \neq Ch_B^*$) can be sent back to the verifier. Therefore, falsification will succeed
 with a probability of 1/2 in one interactive protocol. Thus, the repetition
 configuration described above will be adopted.

[0116]

15 (Supplement)

In the foregoing, the SSH10a public key authentication scheme, the SSH10b
 public key authentication scheme, their falsification algorithms, and the repetition
 configurations of the interactive protocols have been described. These public key
 authentication schemes are schemes where a prover proves to a verifier that “the
 20 prover knows the s that satisfies $y = F(s)$ for y” by using one key pair (public key y,
 secret key s). Accordingly, if interaction that will be accepted by verification was
 performed, it was not possible to prevent the verifier from knowing the information
 that “the prover who performed the verification used the s.” Furthermore, collision
 resistance is not guaranteed for the F used in these schemes. As a result, it was not
 25 known whether or not these public key authentication schemes absolutely guaranteed
 the security level sufficient for an active attack in a case the parallel-repetition
 configuration was adopted.

[0117]

Accordingly, the present inventors have devised a mechanism of
 30 guaranteeing a security level sufficient for an active attack at the time of performing
 these public key authentication schemes while adopting the parallel-repetition

configuration. In the following, this mechanism will be described in detail with citation to concrete examples.

[0118]

<2: First Embodiment (Present Method #1)>

5 First, a first embodiment (hereinafter, present method #1) of the present disclosure will be described.

[0119]

[2-1: Overview]

The present method #1 applies to the SSH10a public key authentication
 10 scheme and the SSH10b public key authentication scheme a mechanism of guaranteeing a security level sufficient for an active attack also in the case of adopting the parallel-repetition configuration. As has been described, the reason why it was not known whether the security level sufficient for an active attack was guaranteed or not is because collision resistance was not guaranteed for the function
 15 F to be used and also because it was not possible to prevent a verifier from knowing the information that “the prover who performed the verification used the s.” Therefore, if the verifier can be prevented from knowing the information that “the prover who performed the verification used the s” in the interactive protocol, the security level sufficient for an active attack can be guaranteed.

20 [0120]

Accordingly, the present inventors have devised a method of causing the secret key s and the public key y to be multiplexed keys. This method takes L ($L \geq 2$) $s_1, \dots, s_L \in K^n$ as a secret key and takes $y_1, \dots, y_L \in K^m$ that satisfies $(y_1, \dots, y_L) = (F(s_1), \dots, F(s_L))$ for m multi-order polynomials of n variables $F(x) = (f_1(x), \dots, f_m(x))$ as a public key. Furthermore, this method is a method of proving “knowledge of the s_i that satisfies $y_i = F(s_i)$ with respect to $L-1$ i ’s among $i = 1, \dots, L$ ” without letting know which s_i was used in the interactive protocol. When applying this method, information related to “which s_i was used” in the interactive protocol will not be leaked, and the security level sufficient for an active attack will be guaranteed.

30 [0121]

According to the scheme of the present method #1, a verifier sends to a

prover challenges $Ch_1, \dots, Ch_L$ (verification patterns) with respect to $i = 1, \dots, L$ and the prover that has received the challenges $Ch_1, \dots, Ch_L$ selects $L-1$ challenges Ch_i and gives a response. When using this method, the prover who know $s_1, \dots, s_L$ can respond to all the L challenges Ch_i but falsification by a falsifier who does not know $s_1, \dots, s_L$ will fail with a certain probability. Furthermore, since the prover has to respond only to $L-1$ challenges Ch_i , authentication can be established without using the s_i for a certain challenge Ch_i . That is, it is not known to the verifier whether or not a certain s_i was used in the interactive protocol.

[0122]

10 [2-2: Application to SSH10a Public Key Authentication Scheme]

First, an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme will be described. FIG. 9 is an explanatory diagram for describing an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10a public
15 key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. In the following, contents of each algorithm will be described.

[0123]

(Key Generation Algorithm Gen)

20 First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as
25 $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Then, the key generation algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0124]

(Prover Algorithm P, Verifier Algorithm V)

30 Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 9. The interactive protocol of the present

scheme #1 is for making a verifier prove that “prover knows the s_i that satisfies $L-1$ pieces of $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier.

5 Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0125]

The interactive protocol of the present scheme #1 is configured from processing steps 1 to 4 shown in FIG. 9. In the following, the process of each step

10 will be described.

[0126]

Step 1:

First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ for $i = 1, \dots, L$. Next, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. Then, the prover algorithm P sends $Cmt_1, \dots, Cmt_L$ to the verifier (verifier algorithm V).

15

[0127]

Step 2:

The verifier algorithm V that received $Cmt_1, \dots, Cmt_L$ selects a verification pattern to be used from three verification patterns. Then, the verifier algorithm V sends to the prover (prover algorithm P) challenges $Ch_1, \dots, Ch_L \in_R \{0, 1, 2\}$ indicating the selected verification pattern.

20

[0128]

Step 3:

The prover algorithm P that received $Ch_1, \dots, Ch_L$ randomly selects, from $i = 1, \dots, L$, one index i (hereinafter, i^*) of a challenge Ch_i to which a response will not be given. Next, the prover algorithm P calculates $Rsp_i \leftarrow P_{a,2}(Ch_i; St_i)$ with respect to $i \in \{1, \dots, L\} \setminus \{i^*\}$. Then, the prover algorithm P sends $(Rsp_1, \dots, Rsp_{i^*-1}, Rsp_{i^*+1}, \dots, Rsp_L, i^*)$ to the verifier (verifier algorithm V).

25

30 [0129]

Step 4:

The verifier algorithm V that received $(\text{Rsp}_1, \dots, \text{Rsp}_{i^*-1}, \text{Rsp}_{i^*+1}, \dots, \text{Rsp}_L, i^*)$ performs $0/1 \leftarrow \text{Dec}_a(F, y_i; \text{Cmt}_i, \text{Ch}_i, \text{Rsp}_i)$ with respect to $i \in \{1, \dots, L\} \setminus \{i^*\}$. Then, in a case of acceptance (output 1) for all of $i \in \{1, \dots, L\} \setminus \{i^*\}$, the verifier algorithm V assumes that verification is established.

5 [0130]

In the foregoing, an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme has been described. It is guaranteed for this interactive protocol that, owing to the security of the SSH10a public key authentication scheme, a falsifier not having the s_i is able to correctly respond, with respect to each $i = 1, \dots, L$, to the challenge Ch_i sent from the verifier with a probability of only $2/3$ or less. Furthermore, by applying the present method #1, since it becomes necessary to correctly respond to the challenge Ch_i sent from the verifier with respect to $L-1$ or more i 's, the probability of success of falsification will be $(2/3)^{L+L(1/3)}(2/3)^{L-1} = (2+L)2^{L-1}/3^L$.

15 [0131]

Furthermore, in the interactive protocol described above, all of $s_1, \dots, s_L$ are used, but if $L \leq 3$, it is possible, when the s_i was not used for one of $i = 1, \dots, L$, to behave exactly like the prover without letting know the verifier which s_i was not used. Accordingly, interactive protocols (modified examples 1 to 3) capable of realizing the same authentication as the above-described interactive protocol without using one s_i will be described.

[0132]

[2-3: Application to SSH10a Public Key Authentication Scheme (Modified Example 1)]

25 First, an interactive protocol (modified example 1) of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme will be described with reference to FIG. 10. FIG. 10 is an explanatory diagram for describing an interactive protocol (modified example 1) of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V.

30

Incidentally, the structure of the falsification algorithm described above is used in the verifier algorithm V. Furthermore, explanation will be given for a case of $L = 3$. Furthermore, the index of s_i that is not used will be made i_0 . In the following, contents of each algorithm will be described.

5 [0133]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Incidentally, a vector which is selected as appropriate is used as s_{i_0} . Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Additionally, $y_{i_0} = F(s_{i_0})$ does not have to be guaranteed. Then, the key generation
10
15 algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0134]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will
20 be described with reference to FIG. 10. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between a prover and a verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0135]

25 The interactive protocol of the present scheme #1 is configured from processing steps 1 to 4 shown in FIG. 10. In the following, the process of each step will be described.

[0136]

Step 1:

30 First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ for $i = 1, 2, 3$. Next, the prover algorithm P selects one $Ch^* \in \{0, 1, 2\}$. This Ch^*

corresponds to a verification pattern where the prover is not able to give a response with respect to the group of i_0 . Next, if $i \neq i_0$, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. On the other hand, if $i = i_0$, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow M_{a,1}(F, y_i; Ch^*, s_i, r_i, t_i, e_i)$. Then, the prover algorithm P
5 sends Cmt_1, Cmt_2 and Cmt_3 to the verifier (verifier algorithm V).
[0137]

Step 2:

The verifier algorithm V that received Cmt_1, Cmt_2 and Cmt_3 selects a verification pattern to be used from three verification patterns. Then, the verifier
10 algorithm V sends to the prover (prover algorithm P) challenges $Ch_1, Ch_2, Ch_3 \in_R \{0, 1, 2\}$ indicating the selected verification pattern.
[0138]

Step 3:

The prover algorithm P that received Ch_1, Ch_2 and Ch_3 selects the index i
15 (hereinafter, i^*) of one challenge Ch_i to which a response will not be given from $i = 1, \dots, L$ in the following manner. If $Ch_{i_0} = Ch^*$, the prover algorithm V sets $i^* \leftarrow i_0$. On the other hand, if $Ch_{i_0} \neq Ch^*$, the prover algorithm V randomly selects the i^* from $i^* \in \{1, 2, 3\} \setminus \{i_0\}$. If this method of setting the i^* is used, then no matter which verification pattern is requested by the verifier, the i^* will take any of values 1, 2 and
20 3 with a probability of $1/3$, respectively. That is, information indicating the value that i_0 took among 1, 2 and 3 is completely hidden.
[0139]

Next, the prover algorithm P calculates Rsp_i with respect to $i \in \{1, 2, 3\} \setminus \{i^*\}$ in the following manner. If $i \neq i_0$, the prover algorithm P calculates $Rsp_i \leftarrow P_{a,2}(Ch_i; St_i)$. If $i = i_0$, the prover algorithm P calculates $Rsp_i \leftarrow M_{a,2}(Ch_i; St_i)$. Then, the
25 prover algorithm P sends $(Rsp_1, \dots, Rsp_{i^*-1}, Rsp_{i^*+1}, \dots, Rsp_L, i^*)$ to the verifier (verifier algorithm V).
[0140]

Step 4:

The verifier algorithm V that received $(Rsp_1, \dots, Rsp_{i^*-1}, Rsp_{i^*+1}, \dots, Rsp_L, i^*)$
30 performs $0/1 \leftarrow Dec_a(F, y_i; Cmt_i, Ch_i, Rsp_i)$ with respect to $i \in \{1, 2, 3\} \setminus \{i^*\}$. Then,

in a case of acceptance (output 1) for all of $i \in \{1, 2, 3\} \setminus \{i^*\}$, the verifier algorithm V assumes that verification is established.

[0141]

In the foregoing, an interactive protocol (modified example) of a case where
 5 the scheme of the present method #1 is applied to the SSH10a public key authentication scheme has been described. Explanation was given taking the case of $L = 3$, but the same can be said for the case of $L = 2$. For example, one i (i^*) that will not be used will be set from $i = 1, 2$ in the following manner. If $Ch_{i_0} = Ch^*$, $i^* = i_0$ will be set. On the other hand, if $Ch_{i_0} \neq Ch^*$, $i^* = i_0$ with a probability of $1/4$ and $i^* \neq i_0$
 10 $\neq i_0$ will be set with a probability of $3/4$. With such setting, no matter which verification pattern is requested by the verifier, the i^* will take either of values 1 and 2 with a probability of $1/2$, respectively. Accordingly, the information indicating the value that i_0 took among 1 and 2 is completely hidden.

[0142]

15 [2-4: Application to SSH10a Public Key Authentication Scheme (Modified Example 2)]

Next, an interactive protocol (modified example 2) of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme will be described with reference to FIG. 11. Additionally, the modified
 20 example 2 is a modified example of the interactive protocol shown in FIG. 9. FIG. 11 is an explanatory diagram for describing an interactive protocol (modified example 2) of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V.
 25 In the following, contents of each algorithm will be described.

[0143]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n
 30 variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and two vectors $s_1, s_2 \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x ,

and m second-order polynomials of n variables ($f_1(x), \dots, f_m(x)$) will be expressed as $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1)$ and $y_2 = F(s_2)$. Then, the key generation algorithm Gen sets (F, y_1, y_2) to the public key pk , and sets (s_1, s_2) to the secret key.

5 [0144]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 11. The interactive protocol of the present scheme #1 is for making a verifier prove that “the prover knows the s_i that satisfies
10 one $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

15 [0145]

The interactive protocol of the present scheme #1 is configured from processing steps 1 to 4 shown in FIG. 11. In the following, the process of each step will be described.

[0146]

20 Step 1:

First, the prover algorithm P generates a vector $r_1, t_1 \in K^n$ and a vector $e_1 \in K^m$. Next, the prover algorithm P calculates $(Cmt_1; St_1) \leftarrow P_{a,1}(F, y_1, s_1; r_1, t_1, e_1)$ and $(Cmt_2; St_2) \leftarrow P_{a,1}(F, y_2, s_2; r_1, t_1, e_1)$. Additionally, Cmt_1 is (c_{11}, c_{12}, c_{13}) and Cmt_2 is (c_{21}, c_{12}, c_{13}) . Then, the prover algorithm P sends c_{11}, c_{12}, c_{13} and c_{21} to the verifier
25 (verifier algorithm V).

[0147]

Step 2:

The verifier algorithm V that received c_{11}, c_{12}, c_{13} and c_{21} selects a verification pattern to be used. Then, the verifier algorithm V sends to the prover
30 (prover algorithm P) a set of challenges $(Ch_1, Ch_2) \in \{0, 1, 2\} \times \{0, 1, 2\}$ indicating the selected verification pattern.

[0148]

Step 3:

The prover algorithm P that received Ch_1 and Ch_2 randomly selects an index i of a challenge Ch_i to which a response is to be given. Next, prover algorithm P
 5 calculates $Rsp_i \leftarrow P_{a,2}(Ch_i; St_i, r_1, t_1, e_1)$ for the selected i . Then, prover algorithm P sends (Rsp_i, i) to the verifier (verifier algorithm V).

[0149]

Step 4:

The verifier algorithm V that received Rsp_i, i performs $0/1 \leftarrow Dec_a(F, y_i; (c_{11}, c_{12}, c_{13}), Ch_i, Rsp_i)$. Then, in a case the output is 1 (in a case of acceptance), the
 10 verifier algorithm V assumes that verification is established.

[0150]

In the foregoing, the interactive protocol (modified example 2) of a case where the scheme of the present method #1 is applied to the SSH10a public key
 15 authentication scheme has been described. The present modified example has its characteristic in that sets of random numbers (r_1, t_1, e_1) and (r_2, t_2, e_2) used at the time of generating Cmt_1, St_1, Cmt_2 and St_2 are made common. By making these random numbers common, (c_{12}, c_{13}) and (c_{22}, c_{23}) among elements forming $Cmt_1 = (c_{11}, c_{12}, c_{13})$ and $Cmt_2 = (c_{21}, c_{22}, c_{23})$ will be common values. Thus, only four values
 20 $(c_{11}, c_{12}, c_{13}, c_{21})$ will have to be sent at the time of sending Cmt_1 and Cmt_2 from the prover to the verifier, and the amount of communication can be reduced. Additionally, in the case of the present modified example, only the information related to one of the groups will be published in the third pass, and thus the zero knowledge will not be lost even if a part of the random numbers is made common as
 25 described above.

[0151]

[2-5: Application to SSH10a Public Key Authentication Scheme (Modified Example 3)]

Next, an interactive protocol (modified example 3) of a case where the
 30 scheme of the present method #1 is applied to the SSH10a public key authentication scheme will be described with reference to FIG. 12. Additionally, the modified

example 3 is a modified example of the interactive protocol (modified example 2) shown in FIG. 11. FIG. 12 is an explanatory diagram for describing an interactive protocol (modified example 3) of a case where the scheme of the present method #1 is applied to the SSH10a public key authentication scheme. This interactive
 5 protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. In the following, contents of each algorithm will be described.

[0152]

(Key Generation Algorithm Gen)

10 First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and two vectors $s_1, s_2 \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as
 15 $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1)$ and $y_2 = F(s_2)$. Then, the key generation algorithm Gen sets (F, y_1, y_2) to a public key pk , and sets (s_1, s_2) to a secret key.

[0153]

(Prover Algorithm P, Verifier Algorithm V)

20 Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 12. The interactive protocol of the present scheme #1 is for making a verifier prove that “prover knows the s_i that satisfies one $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key generation
 25 algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0154]

The interactive protocol of the present scheme #1 is configured from
 30 processing steps 1 to 4 shown in FIG. 12. In the following, the process of each step will be described.

[0155]

Step 1:

First, the prover algorithm P generates a vector $r_1, t_1 \in K^n$ and a vector $e_1 \in K^m$.

Next, the prover algorithm P calculates $(Cmt_1; St_1) \leftarrow P_{a,1}(F, y_1, s_1; r_1, t_1, e_1)$ and
 5 $(Cmt_2; St_2) \leftarrow P_{a,1}(F, y_2, s_2; r_1, t_1, e_1)$. Incidentally, Cmt_1 is (c_{11}, c_{12}, c_{13}) and Cmt_2 is
 (c_{21}, c_{12}, c_{13}) . Next, the prover algorithm P sends c_{11} , c_{12} , c_{13} and c_{21} to the verifier
 (verifier algorithm V).

[0156]

Step 2:

10 The verifier algorithm V that received c_{11} , c_{12} , c_{13} and c_{21} selects a
 verification pattern to be used. At this time, the verifier algorithm V selects a
 verification pattern (a set of challenges (Ch_1, Ch_2)) from
 $(Ch_1, Ch_2) \in \{(0,0), (1,1), (1,2), (2,1), (2,2)\}$. Then, the verifier algorithm V sends to
 the prover (prover algorithm P) the set of challenges (Ch_1, Ch_2) indicating the
 15 selected verification pattern.

[0157]

Step 3:

The prover algorithm P that received Ch_1 and Ch_2 randomly selects an index
 i of a challenge Ch_i to which a response is to be given. Next, the prover algorithm P
 20 calculates $Rsp_i \leftarrow P_{a,2}(Ch_i; St_i, r_1, t_1, e_1)$ for the selected i . Then, the prover
 algorithm P sends (Rsp_i, i) to the verifier (verifier algorithm V).

[0158]

Step 4:

The verifier algorithm V that received (Rsp_i, i) performs $0/1 \leftarrow Dec_a(F, y_i;$
 25 $(c_{11}, c_{12}, c_{13}), Ch_i, Rsp_i)$. Then, in a case the output is 1 (in a case of acceptance), the
 verifier algorithm V assumes that verification is established.

[0159]

In the foregoing, the interactive protocol (modified example 3) of a case
 where the scheme of the present method #1 is applied to the SSH10a public key
 30 authentication scheme has been described. The present modified example has its
 characteristic in that a usable verification pattern is limited to five patterns,

$(Ch_1, Ch_2) \in \{(0,0), (1,1), (1,2), (2,1), (2,2)\}$.

[0160]

In a case the elements (c_{12}, c_{13}) of Cmt_1 and the elements (c_{22}, c_{23}) of Cmt_2 are made common as described above, the response for $Ch_1 = 0$ (the response for c_{12} and c_{13}) and the response for $Ch_2 = 0$ (the response for c_{22} and c_{23}) will be the same. Accordingly, that “it is possible to respond to $(Ch_1, Ch_2) = (0, 0)$ ” means that “it is possible to respond to both $Ch_1 = 0$ and $Ch_2 = 0$.” Therefore, the prover who can respond to $(Ch_1, Ch_2) = (0, 0)$ is able to respond to any of $(Ch_1, Ch_2) = (0,1), (0,2), (1,0), (2,0)$. Accordingly, it is sufficient that the verifier performs verification for five patterns, $(Ch_1, Ch_2) = (0,0), (1,1), (1,2), (2,1), (2,2)$.

[0161]

For the reason as described, it is guaranteed that, as long as the secret key sk is not known, it is not possible to respond to all the five patterns described above. That is, one who does not know the secret key sk can respond to only four patterns at maximum, and thus the falsification probability is $4/5$ at the maximum. In the case of the interactive protocol shown in FIG. 9, the falsification probability in the case of $L = 2$ was $8/9$. Accordingly, applying the configuration of the modified example 3 will reduce the falsification probability.

[0162]

20 [2-6: Application to SSH10b Public Key Authentication Scheme]

Next, an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme will be described with reference to FIG. 13. FIG. 13 is an explanatory diagram for describing an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen , a prover algorithm P and a verifier algorithm V . In the following, contents of each algorithm will be described.

[0163]

30 (Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described.

The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ and L vectors $s_1, \dots, s_L \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next, the

5 key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Then, the key generation algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0164]

(Prover Algorithm P, Verifier Algorithm V)

10 Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 13. The interactive protocol of the present scheme #1 is for making a verifier prove that “the prover knows the s_i that satisfies $L-1$ pieces of $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key

15 generation algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0165]

The interactive protocol of the present scheme #1 is configured from

20 processing steps 1 to 6 shown in FIG. 13. In the following, the process of each step will be described.

[0166]

Step 1:

First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$

25 for $i = 1, \dots, L$. Next, the prover algorithm P calculates $(Cmt_{A,i}; St_{A,i}) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. Then, the prover algorithm P sends $(Cmt_{A,1}, \dots, Cmt_{A,L})$ to the verifier (verifier algorithm V).

[0167]

Step 2:

30 The verifier algorithm V that received $(Cmt_{A,1}, \dots, Cmt_{A,L})$ selects a set of L random numbers $(\alpha_1, \dots, \alpha_L)$ from q types of elements of a ring K . Then, the

verifier algorithm V sends a challenge $(Ch_{A,1}, \dots, Ch_{A,L}) = (\alpha_1, \dots, \alpha_L)$ to the prover (prover algorithm P).

[0168]

Step 3:

5 The prover algorithm P that received $(Ch_{A,1}, \dots, Ch_{A,L})$ calculates $(Cmt_{B,i}; St_{B,i}) \leftarrow P_{b,2}(Ch_{A,i}; St_{A,i})$ with respect to $i = 1, \dots, L$. Then, the prover algorithm P sends $(Cmt_{B,1}, \dots, Cmt_{B,L})$ to the verifier (verifier algorithm V).

[0169]

Step 4:

10 The verifier algorithm V that received $(Cmt_{B,1}, \dots, Cmt_{B,L})$ selects a verification pattern to be used from two verification patterns for each $i = 1, \dots, L$. Then, the verifier algorithm V sends to prover (prover algorithm P) challenges $Ch_{B,1}, \dots, Ch_{B,L} \in_R \{0, 1\}$ indicating the selected verification patterns.

[0170]

15 Step 5:

The prover algorithm P that received $Ch_{B,1}, \dots, Ch_{B,L}$ randomly selects, from $i = 1, \dots, L$, one i (hereinafter, i^*) to which a response will not be given. Then, the prover algorithm P calculates $Rsp_i \leftarrow P_{b,3}(Ch_{B,i}; St_{B,i})$. Then, the prover algorithm P sends $(Rsp_1, \dots, Rsp_{i^*-1}, Rsp_{i^*+1}, \dots, Rsp_L, i^*)$ to the verifier (verifier algorithm V).

20 [0171]

Step 6:

The verifier algorithm V that received $(Rsp_1, \dots, Rsp_{i^*-1}, Rsp_{i^*+1}, \dots, Rsp_L, i^*)$ performs $0/1 \leftarrow Dec_b(F, y_i; Cmt_{A,i}, Ch_{A,i}, Cmt_{B,i}, Ch_{B,i}, Rsp_i)$ with respect to $i \in \{1, \dots, L\} \setminus \{i^*\}$. Then, in a case of acceptance (output 1) for all of $i \in \{1, \dots, L\} \setminus \{i^*\}$, the verifier algorithm V assumes that verification is established.

[0172]

In the foregoing, an interactive protocol of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme has been described. It is guaranteed for this interactive protocol that, owing to the security of the SSH10b public key authentication scheme, a falsifier not having the s_i is able to correctly respond, with respect to each $i = 1, \dots, L$, to the challenge Ch_i

30

sent from the verifier with a probability of only $1/2+1/2q$ or less. Furthermore, by applying the present method #1, since it becomes necessary to correctly respond to the challenge Ch_i sent from the verifier with respect to $L-1$ or more i 's, the probability of success of falsification will be $(1/2+1/2q)^L + L(1/2-1/2q)(1/2+1/2q)^{L-1}$.

5 [0173]

Furthermore, in the interactive protocol described above, all of $s_1, \dots, s_L$ are used, but if $L = 2$, it is possible, even if the s_i was not used for one of $i = 1, \dots, L$, to behave exactly like the prover without letting know the verifier which s_i was not used. Accordingly, an interactive protocol (modified example) capable of realizing the same authentication as the above-described interactive protocol without using one s_i will be described.

[0174]

[2-7: Application to SSH10b Public Key Authentication Scheme (Modified Example)]

15 In the following, an interactive protocol (modified example) of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme will be described with reference to FIG. 14. FIG. 14 is an explanatory diagram for describing an interactive protocol (modified example) of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. Incidentally, the structure of the falsification algorithm described above is used in the verifier algorithm V. Furthermore, explanation will be given for a case of $L = 2$. Furthermore, the index of s_i that is not used will be made i_0 . In the following, contents of each algorithm will be described.

25

[0175]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Incidentally, a vector which is selected as appropriate is used as s_{i_0} .

30

Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Additionally, $y_{i_0} = F(s_{i_0})$ does not have to be guaranteed. Then, the key generation
 5 algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0176]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will
 10 be described with reference to FIG. 14. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between a prover and a verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0177]

15 The interactive protocol of the present scheme #1 is configured from processing steps 1 to 6 shown in FIG. 14. In the following, the process of each step will be described.

[0178]

Step 1:

20 First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ for $i = 1, 2$. Next, the prover algorithm P selects one $Ch_B^* \in \{0, 1\}$. This Ch_B^* corresponds to a verification pattern where the prover is not able to give a response with respect to the group of i_0 . Next, if $i \neq i_0$, the prover algorithm P calculates $(Cmt_{A,i}; St_{A,i}) \leftarrow P_{b,i}(F, y_i, s_i; r_i, t_i, e_i)$. Also, if $i = i_0$, the prover algorithm P
 25 calculates $(Cmt_{A,i}; St_{A,i}) \leftarrow M_{b,i}(F, y_i; Ch_B^*, s_i, r_i, t_i, e_i)$. Then, the prover algorithm P sends $(Cmt_{A,1}, Cmt_{A,2})$ to the verifier (verifier algorithm V).

[0179]

Step 2:

The verifier algorithm V that received $(Cmt_{A,1}, Cmt_{A,2})$ selects a set of two
 30 random numbers (α_1, α_2) from q types of elements of a ring K . Then, the verifier algorithm V sends a challenge $(Ch_{A,1}, Ch_{A,2}) = (\alpha_1, \alpha_2)$ to the prover (prover

algorithm P).

[0180]

Step 3:

The prover algorithm P that received $(Ch_{A,1}, Ch_{A,2})$ calculates $Cmt_{B,i}$ with
 5 respect to $i = 1, 2$ in the following manner. If $i \neq i_0$, the prover algorithm P
 calculates $(Cmt_{B,i}; St_{B,i}) \leftarrow P_{b,2}(Ch_{A,i}; St_{A,i})$. If $i = i_0$, the prover algorithm P
 calculates $(Cmt_{B,i}; St_{B,i}) \leftarrow M_{b,2}(Ch_{A,i}; St_{A,i})$. Then, the prover algorithm P sends
 $(Cmt_{B,1}, Cmt_{B,2})$ to the verifier (verifier algorithm V).

[0181]

10 Step 4:

The verifier algorithm V that received $(Cmt_{B,1}, Cmt_{B,2})$ selects a verification
 pattern to be used from two verification patterns. Then, the verifier algorithm V
 sends to the prover (prover algorithm P) a challenge $(Ch_{B,1}, Ch_{B,2}) \in_R \{0, 1\}$
 indicating the selected verification pattern.

15 [0182]

Step 5:

The prover algorithm P that received $(Ch_{B,1}, Ch_{B,2})$ selects one index i
 (hereinafter, i^*) to which a response will not be given from $i = 1, 2$ in the following
 manner. If $Ch_{i_0} = Ch^*$, the prover algorithm P sets to $Ch_{i_0} \neq Ch^*$. On the other
 20 hand, if $i \neq i_0$, the prover algorithm P randomly performs setting so that it will be $i^* \neq$
 i_0 . If this method of setting the i^* is used, then no matter which verification pattern
 is requested by the verifier, the i^* will take either of values 1 and 2 with a probability
 of $1/2$, respectively. That is, information indicating the value that i_0 took between 1
 and 2 is completely hidden.

25 [0183]

Next, the prover algorithm P calculates Rsp_i with respect to $i \in \{1, 2\} \setminus \{i^*\}$ in
 the following manner. If $i \neq i_0$, the prover algorithm P calculates $Rsp_i \leftarrow P_{b,3}(Ch_i;$
 $St_i)$. If $i = i_0$, the prover algorithm P calculates $Rsp_i \leftarrow M_{b,3}(Ch_i; St_i)$. Then, the
 prover algorithm P sends (Rsp_1, Rsp_2, i^*) to the verifier (verifier algorithm V).

30 [0184]

Step 6:

The verifier algorithm V that received (Rsp_1, Rsp_2, i^*) performs $0/1 \leftarrow Dec_b(F, y_i; Cmt_{A,i}, Ch_{A,i}, Cmt_{B,i}, Ch_{B,i}, Rsp_i)$ with respect to $i \in \{1, 2\} \setminus \{i^*\}$. Then, in a case of acceptance (output 1) for all of $i \in \{1, 2\} \setminus \{i^*\}$, the verifier algorithm V assumes that verification is established.

5 [0185]

In the foregoing, an interactive protocol (modified example) of a case where the scheme of the present method #1 is applied to the SSH10b public key authentication scheme has been described. Explanation was given here for a case of $L = 2$, but the same mechanism can also be realized for a case of $L \geq 3$.

10 [0186]

In the foregoing, the first embodiment of the present disclosure has been described. The above explanation was given taking the SSH10a public key authentication scheme and the SSH10b public key authentication scheme as the examples, but the application scope of the present scheme #1 is not limited to these. Application is also possible to the modified examples of the SSH10a public key authentication scheme and the SSH10b public key authentication scheme and other public key authentication schemes. For example, in the example above, (F, y) is set to the public key, but since the F is a parameter not dependent of the secret key, this F may also be made a parameter common to the entire system instead of being set for each prover. In this case, the public keys to be individually published will be y only, and the size of the public key will be reduced. Furthermore, in the interactive protocol described above, random numbers $\alpha_1, \dots, \alpha_L$ are separately selected for $i = 1, \dots, L$, but these random numbers can be made into one common random number. In this case, the cost of communication at the time of sending the challenge $Ch_{A,i}$ can be reduced.

25 be reduced.

[0187]

<3: Second Embodiment (Present Method #2)>

Next, a second embodiment (present method #2) of the present disclosure will be described.

30 [0188]

[3-1: Overview]

The present method #2 applies to the SSH10a public key authentication scheme and the SSH10b public key authentication scheme a mechanism of guaranteeing a security level sufficient for an active attack. As has been described, the reason why it was not known whether the security level sufficient for an active
 5 attack was guaranteed or not is because collision resistance was not guaranteed for the function F to be used and also because it was not possible to prevent a verifier from knowing the information that “the prover who performed the verification used the s .” Therefore, if the verifier can be prevented from knowing the information that “the prover who performed the verification used the s ” in the interactive protocol,
 10 the security level sufficient for an active attack can be guaranteed.
 [0189]

Accordingly, the present inventors have devised a method of causing the secret key s and the public key y to be multiplexed keys. This method takes L ($L \geq 2$) $s_1, \dots, s_L \in K^n$ as a secret key and takes $y_1, \dots, y_L \in K^m$ that satisfies $(y_1, \dots, y_L) =$
 15 $(F(s_1), \dots, F(s_L))$ for m multi-order polynomials of n variables $F(x) = (f_1(x), \dots, f_m(x))$ as a public key. Furthermore, this method is a method of performing authentication without giving away which s_i is used in the interactive protocol. When applying this method, information related to “which s_i was used” in the interactive protocol will not be leaked, and the security level sufficient for an active attack will be
 20 guaranteed.
 [0190]

According to the scheme of the present method #2, a verifier sends to a prover sets of challenges $(Ch_1^{(0)}, \dots, Ch_L^{(0)})$ and $(Ch_1^{(1)}, \dots, Ch_L^{(1)})$ with respect to $i = 1, \dots, L$, and the prover selects one of the sets of challenges and gives a response.
 25 Generally, according to this scheme, Q sets ($Q \geq 2$) of challenges are sent to the prover, and the prover selects one set of challenges and gives a response. At this point, a case where $Q = 2$ will be described. A prover who knows $s_1, \dots, s_L$ will be able to give a response to both sets of challenges, but a falsifier who does not know $s_1, \dots, s_L$ will fail with a certain probability to give a response to either challenge,
 30 thereby failing in falsification. Additionally, the prover can, with regard to one i , give a response to one of the sets of challenges without using the s_i , and thus even

when an interactive protocol where verification will be accepted was performed, which s_i was used in this interactive protocol will not be known to the verifier.

[0191]

[3-2: Application to SSH10a Public Key Authentication Scheme]

5 First, an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10a public key authentication scheme will be described with reference to FIG. 15. FIG. 15 is an explanatory diagram for describing an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10a public key authentication scheme. This interactive
10 protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. In the following, contents of each algorithm will be described.

[0192]

(Key Generation Algorithm Gen)

15 First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as
20 $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Then, the key generation algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0193]

Next, structures of the prover algorithm P and the verifier algorithm V will
25 be described with reference to FIG. 15. The interactive protocol of the present scheme #1 is for making a verifier prove that “prover knows the s_i that satisfies $L-1$ pieces of $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier.
30 Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0194]

The interactive protocol of the present scheme #2 is configured from processing steps 1 to 4 shown in FIG. 15. In the following, the process of each step will be described.

5 [0195]

Step 1:

First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ with respect to $i = 1, \dots, L$. Next, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. Then, the prover algorithm P sends $Cmt_1, \dots, Cmt_L$ to the verifier (verifier algorithm V).

[0196]

Step 2:

The verifier algorithm V that received $Cmt_1, \dots, Cmt_L$ selects a verification pattern to be used from three verification patterns. At this time, the verifier algorithm V selects a combination of two verification patterns. Then, the verifier algorithm V sends to the prover (prover algorithm P) sets of challenges $(Ch_1^{(0)}, \dots, Ch_L^{(0)})$, $(Ch_1^{(1)}, \dots, Ch_L^{(1)}) \in_R \{0, 1, 2\}$ indicating the selected verification patterns.

[0197]

20 Step 3:

The prover algorithm P that received $(Ch_1^{(0)}, \dots, Ch_L^{(0)})$ and $(Ch_1^{(1)}, \dots, Ch_L^{(1)})$ randomly selects a set of challenges to which a response will be given. Additionally, the result of selection will be expressed as $d \in_R \{0, 1\}$. Then, the prover algorithm P calculates $Rsp_i \leftarrow P_{a,2}(Ch^{(d)}_i; St_i)$ with respect to $i \in \{1, \dots, L\}$. Then, the prover algorithm P sends $(Rsp_1, \dots, Rsp_L, d)$ to the verifier (verifier algorithm V).

[0198]

Step 4:

The verifier algorithm V that received $(Rsp_1, \dots, Rsp_L, d)$ performs $0/1 \leftarrow Dec_a(F, y_i; Cmt_i, Ch^{(d)}_i, Rsp_i)$ with respect to $i \in \{1, \dots, L\}$. Then, in a case of acceptance (output 1) for all of $i \in \{1, \dots, L\}$, the verifier algorithm V assumes that verification is established.

30

[0199]

In the foregoing, an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10a public key authentication scheme has been described. It is guaranteed for this interactive protocol that, owing to the security of the SSH10a public key authentication scheme, a falsifier not having the s_i is able to correctly respond, with respect to each $i = 1, \dots, L$, to the challenge Ch_i sent from the verifier with a probability of only $2/3$ or less. Furthermore, by applying the present method #2, since it becomes necessary to correctly respond to the challenge Ch_i sent from the verifier with respect to L i 's for one of two sets of challenges, the probability of success of falsification will be $(2/3)^L + (2/3)^L - (1/3)^L = (2^{L+1} - 1)/3^L$.

[0200]

Furthermore, in the interactive protocol described above, all of $s_1, \dots, s_L$ are used, but if $L \leq 3$, it is possible, when the s_i was not used for one of $i = 1, \dots, L$, to behave exactly like the prover without letting know the verifier which s_i was not used. Accordingly, an interactive protocol (modified example) capable of realizing the same authentication as the above-described interactive protocol without using one s_i will be described.

[0201]

[3-3: Application to SSH10a Public Key Authentication Scheme (Modified Example)]

In the following, an interactive protocol (modified example) of a case where the scheme of the present method #2 is applied to the SSH10a public key authentication scheme will be described with reference to FIG. 16. FIG. 16 is an explanatory diagram for describing an interactive protocol (modified example) of a case where the scheme of the present method #2 is applied to the SSH10a public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. Incidentally, the structure of the falsification algorithm described above is used in the verifier algorithm V. Furthermore, the index of s_i that is not used will be made i_0 . In the following, contents of each algorithm will be described.

[0202]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Incidentally, a vector which is selected as appropriate is used as s_{i_0} . Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Additionally, $y_{i_0} = F(s_{i_0})$ does not have to be guaranteed. Then, the key generation algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0203]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 16. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between a prover and a verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

[0204]

The interactive protocol of the present scheme #2 is configured from processing steps 1 to 4 shown in FIG. 16. In the following, the process of each step will be described.

[0205]

Step 1:

First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ for $i = 1, \dots, L$. Next, the prover algorithm P selects one $Ch^* \in \{0, 1, 2\}$. This Ch^* corresponds to a verification pattern where the prover is not able to give a response with respect to the group of i_0 . Next, if $i \neq i_0$, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. On the other hand, if $i = i_0$, the prover algorithm P calculates $(Cmt_i; St_i) \leftarrow M_{a,1}(F, y_i; Ch^*, s_i, r_i, t_i, e_i)$. Then, the prover algorithm P

sends $\text{Cmt}_1, \dots, \text{Cmt}_L$ to the verifier (verifier algorithm V).

[0206]

Step 2:

The verifier algorithm V that received $\text{Cmt}_1, \dots, \text{Cmt}_L$ selects a verification
 5 pattern to be used from three verification patterns. At this point, the verifier
 algorithm V selects a combination of two verification patterns. Then, the verifier
 algorithm V sends to the prover (prover algorithm P) sets of challenges
 $(\text{Ch}_1^{(0)}, \dots, \text{Ch}_L^{(0)})$, $(\text{Ch}_1^{(1)}, \dots, \text{Ch}_L^{(1)}) \in_R \{0, 1, 2\}$ indicating the selected verification
 patterns. Additionally, $\text{Ch}_i^{(0)}$ is not equal to $\text{Ch}_i^{(1)}$.

10 [0207]

Step 3:

The prover algorithm P that received $(\text{Ch}_1^{(0)}, \dots, \text{Ch}_L^{(0)})$ and $(\text{Ch}_1^{(1)}, \dots,$
 $\text{Ch}_L^{(1)})$ selects a set of challenges to which a response will be given in the following
 manner. Additionally, the result of selection will be expressed as $d \in_R \{0, 1\}$. If
 15 $\text{Ch}_{i_0}^{(0)} = \text{Ch}^*$ (condition 1), the prover algorithm P sets to $d \leftarrow 1$. On the other hand,
 if $\text{Ch}_{i_0}^{(1)} = \text{Ch}^*$ (condition 2), the prover algorithm P sets to $d \leftarrow 0$. In cases other
 than conditions 1 and 2, the prover algorithm P randomly sets $d \in \{0, 1\}$. According
 to this method of setting, no matter which verification pattern is requested by the
 verifier, the d will take either of values 0 and 1 with a probability of 1/2, and thus
 20 information indicating the value that i_0 takes among 1, ..., L will be completely
 hidden.

[0208]

After the d is set, the prover algorithm P calculates Rsp_i with respect to
 $i \in \{1, \dots, L\}$ in the following manner. If $i \neq i_0$, the prover algorithm P calculates
 25 $\text{Rsp}_i \leftarrow \text{P}_{a,2}(\text{Ch}^{(d)}_i; \text{St}_i)$. On the other hand, if $i = i_0$, the prover algorithm P calculates
 $\text{Rsp}_i \leftarrow \text{M}_{a,2}(\text{Ch}^{(d)}_i; \text{St}_i)$. Then, the prover algorithm P sends $(\text{Rsp}_1, \dots, \text{Rsp}_L, d)$ to
 the verifier (verifier algorithm V).

[0209]

Step 4:

30 The verifier algorithm V that received $(\text{Rsp}_1, \dots, \text{Rsp}_L, d)$ performs
 $0/1 \leftarrow \text{Dec}_a(F, y_i; \text{Cmt}_i, \text{Ch}^{(d)}_i, \text{Rsp}_i)$ with respect to $i \in \{1, \dots, L\}$. Then, in a case of

acceptance (output 1) for all of $i \in \{1, \dots, L\}$, the verifier algorithm V assumes that verification is established.

[0210]

In the foregoing, an interactive protocol (modified example) of a case where
 5 the scheme of the present method #2 is applied to the SSH10a public key authentication scheme has been described. Additionally, in the above explanation, two sets of challenges are sent from the verifier to the prover, but it is also possible to determine beforehand the second challenge to be $Ch_i^{(1)} = Ch_i^{(0)} + 1 \bmod 3$, for example. In this case, one of the sets of challenges does not have to be sent, and
 10 thus the amount of communication can be reduced.

[0211]

[3-4: Application to SSH10b Public Key Authentication Scheme]

Next, an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10b public key authentication scheme will be
 15 described with reference to FIG. 17. FIG. 17 is an explanatory diagram for describing an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10b public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen , a prover algorithm P and a verifier algorithm V . In the following, contents of each algorithm will be
 20 described.

[0212]

(Key Generation Algorithm Gen)

First, a structure of the the key generation algorithm Gen will be described. The key generation algorithm Gen generates m second-order polynomials of n
 25 variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Additionally, a vector of n variables $(x_1, \dots, x_n)$ will be expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next, the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Then, the key generation algorithm Gen sets $(F, y_1, \dots, y_L)$ to the public key pk , and
 30 sets $(s_1, \dots, s_L)$ to the secret key.

[0213]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will be described with reference to FIG. 135. The interactive protocol of the present scheme #2 is for making a verifier prove that “prover knows the s_i that satisfies $L-1$ pieces of $y_i = F(s_i)$ ” without leaking information on “which s_i was used or was not used” at all to the verifier. Additionally, the public key pk generated by the key generation algorithm Gen is assumed to be shared between the prover and the verifier. Also, the secret key sk generated by the key generation algorithm Gen is assumed to be secretly managed by the prover.

10 [0214]

The interactive protocol of the present scheme #2 is configured from processing steps 1 to 6 shown in FIG. 17. In the following, the process of each step will be described.

[0215]

15 Step 1:

First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$ with respect to $i = 1, \dots, L$. Next, the prover algorithm P calculates $(Cmt_{A,i}; St_{A,i}) \leftarrow P_{a,1}(F, y_i, s_i; r_i, t_i, e_i)$. Then, the prover algorithm P sends $(Cmt_{A,1}, \dots, Cmt_{A,L})$ to the verifier (verifier algorithm V).

20 [0216]

Step 2:

The verifier algorithm V that received $(Cmt_{A,1}, \dots, Cmt_{A,L})$ selects a set of L random numbers $(\alpha_1, \dots, \alpha_L)$ from q types of elements of a ring K . Then, the verifier algorithm V sends a challenge $(Ch_{A,1}, \dots, Ch_{A,L}) = (\alpha_1, \dots, \alpha_L)$ to the prover (prover algorithm P).

25

[0217]

Step 3:

The prover algorithm P that received $(Ch_{A,1}, \dots, Ch_{A,L})$ calculates $(Cmt_{B,i}; St_{B,i}) \leftarrow P_{b,2}(Ch_{A,i}; St_{A,i})$ with respect to $i = 1, \dots, L$. Then, the prover algorithm P sends $(Cmt_{B,1}, \dots, Cmt_{B,L})$ to the verifier (verifier algorithm V).

30

[0218]

Step 4:

The verifier algorithm V that received $(Cmt_{B,1}, \dots, Cmt_{B,L})$ selects a verification pattern to be used from three verification patterns. At this point, the verifier algorithm V selects a combination of two verification patterns. Then, the
 5 verifier algorithm V sends to the prover (prover algorithm P) sets of challenges $(Ch_{B,1}^{(0)}, \dots, Ch_{B,L}^{(0)})$, $(Ch_{B,1}^{(1)}, \dots, Ch_{B,L}^{(1)}) \in_R \{0, 1\}^L$ indicating the selected verification patterns. Additionally, $Ch_{B,i}^{(0)}$ is not equal to $Ch_{B,i}^{(1)}$.
 [0219]

Step 5:

10 The prover algorithm P that received $(Ch_{B,1}^{(0)}, \dots, Ch_{B,L}^{(0)})$ and $(Ch_{B,1}^{(1)}, \dots, Ch_{B,L}^{(1)})$ randomly selects one set of challenges to which a response will be given. Additionally, the result of selection will be expressed as $d \in_R \{0, 1\}$. Then, the prover algorithm P calculates $Rsp_i \leftarrow P_{b,2}(Ch_{B,i}^{(d)}; St_{B,i})$ with respect to $i \in \{1, \dots, L\}$. Then, the prover algorithm P sends $(Rsp_1, \dots, Rsp_L, d)$ to the verifier (verifier
 15 algorithm V).
 [0220]

Step 6:

The verifier algorithm V that received $(Rsp_1, \dots, Rsp_L, d)$ performs $0/1 \leftarrow Dec_b(F, y_i; Cmt_{A,i}, Ch_{A,i}, Cmt_{B,i}, Ch_{B,i}^{(d)}, Rsp_i)$ with respect to $i \in \{1, \dots, L\}$.
 20 Then, in a case of acceptance (output 1) for all of $i \in \{1, \dots, L\}$, the verifier algorithm V assumes that verification is established.
 [0221]

In the foregoing, an interactive protocol of a case where the scheme of the present method #2 is applied to the SSH10b public key authentication scheme has
 25 been described. It is guaranteed for this interactive protocol that, owing to the security of the SSH10b public key authentication scheme, a falsifier not having the s_i is able to correctly respond, with respect to each $i = 1, \dots, L$, to the challenge sent from the verifier with a probability of only $1/2 + 1/2q$ or less. Furthermore, by applying the present method #2, since it becomes necessary to correctly respond to
 30 the challenge sent from the verifier with respect to L i's for one of two sets of challenges, the probability of success of falsification will be $(1/2 + 1/2q)^L + (1/2 + 1/2q)^L$

$$= 2(1/2 + 1/2q)^L.$$

[0222]

Furthermore, in the interactive protocol described above, all of $s_1, \dots, s_L$ are used, but even if the s_i is not used for one of $i = 1, \dots, L$, it is possible to behave
 5 exactly like the prover without letting know the verifier which s_i was not used. Accordingly, an interactive protocol (modified example) capable of realizing the same authentication as the above-described interactive protocol without using one s_i will be described.

[0223]

10 [3-5: Application to SSH10b Public Key Authentication Scheme (Modified Example)]

First, an interactive protocol (modified example) of a case where the scheme of the present method #2 is applied to the SSH10b public key authentication scheme will be described with reference to FIG. 18. FIG. 18 is an explanatory diagram for
 15 describing an interactive protocol (modified example) of a case where the scheme of the present method #2 is applied to the SSH10b public key authentication scheme. This interactive protocol is configured from a key generation algorithm Gen, a prover algorithm P and a verifier algorithm V. Incidentally, the structure of the falsification algorithm described above is used in the verifier algorithm V. Furthermore, the
 20 index of s_i that is not used will be made i_0 . In the following, contents of each algorithm will be described.

[0224]

(Key Generation Algorithm Gen)

First, a structure of the key generation algorithm Gen will be described.
 25 The key generation algorithm Gen generates m second-order polynomials of n variables $f_1(x_1, \dots, x_n), \dots, f_m(x_1, \dots, x_n)$ defined on a ring K and L vectors $s_1, \dots, s_L \in K^n$. Incidentally, a vector which is selected as appropriate is used as s_{i_0} . Additionally, a vector of n variables $(x_1, \dots, x_n)$ is expressed as x , and m second-order polynomials of n variables $(f_1(x), \dots, f_m(x))$ will be expressed as $F(x)$. Next,
 30 the key generation algorithm Gen calculates $y_1 = F(s_1), \dots, y_L = F(s_L)$. Additionally, $y_{i_0} = F(s_{i_0})$ does not have to be guaranteed. Then, the key generation algorithm Gen

sets $(F, y_1, \dots, y_L)$ to the public key pk , and sets $(s_1, \dots, s_L)$ to the secret key.

[0225]

(Prover Algorithm P, Verifier Algorithm V)

Next, structures of the prover algorithm P and the verifier algorithm V will
 5 be described with reference to FIG. 18. Additionally, the public key pk generated
 by the key generation algorithm Gen is assumed to be shared between the prover and
 the verifier. Also, the secret key sk generated by the key generation algorithm Gen
 is assumed to be secretly managed by the prover.

[0226]

10 The interactive protocol of the present scheme #2 is configured from
 processing steps 1 to 6 shown in FIG. 18. In the following, the process of each step
 will be described.

[0227]

Step 1:

15 First, the prover algorithm P generates a vector $r_i, t_i \in K^n$ and a vector $e_i \in K^m$
 with respect to $i = 1, \dots, L$. Next, the prover algorithm P selects one $Ch_B^* \in \{0, 1\}$.
 This Ch^* corresponds to a verification pattern where the prover is not able to give a
 response with respect to the group of i_0 . Next, the prover algorithm P calculates
 $(Cmt_{A,i}; St_{A,i}) \leftarrow P_{b,1}(F, y_i, s_i; r_i, t_i, e_i)$ for the case of $i \neq i_0$. Furthermore, the prover
 20 algorithm P calculates $(Cmt_{A,i}; St_{A,i}) \leftarrow M_{b,1}(F, y_i; Ch_B^*, s_i, r_i, t_i, e_i)$ for the case of $i =$
 i_0 . Then, the prover algorithm P sends $(Cmt_{A,1}, \dots, Cmt_{A,L})$ to the verifier (verifier
 algorithm V).

[0228]

Step 2:

25 The verifier algorithm V that received $(Cmt_{A,1}, \dots, Cmt_{A,L})$ selects a set of L
 random numbers $(\alpha_1, \dots, \alpha_L)$ from q types of elements of a ring K. Then, the
 verifier algorithm V sends a challenge $(Ch_{A,1}, \dots, Ch_{A,L}) = (\alpha_1, \dots, \alpha_L)$ to the prover
 (prover algorithm P).

[0229]

30 Step 3:

The prover algorithm P that received $(Ch_{A,1}, \dots, Ch_{A,L})$ calculates $Cmt_{B,i}$

with respect to $i = 1, \dots, L$ in the following manner. First, if $i \neq i_0$, the prover algorithm P calculates $(\text{Cmt}_{B,i}; \text{St}_{B,i}) \leftarrow P_{b,2}(\text{Ch}_{A,i}; \text{St}_{A,i})$. On the other hand, if $i = i_0$, the prover algorithm P calculates $(\text{Cmt}_{B,i}; \text{St}_{B,i}) \leftarrow M_{b,2}(\text{Ch}_{A,i}; \text{St}_{A,i})$. Then, the prover algorithm P sends $(\text{Cmt}_{B,1}, \dots, \text{Cmt}_{B,L})$ to the verifier (verifier algorithm V).

5 [0230]

Step 4:

The verifier algorithm V that received $(\text{Cmt}_{B,1}, \dots, \text{Cmt}_{B,L})$ selects a verification pattern to be used from three verification patterns. At this point, the verifier algorithm V selects a combination of two verification patterns. Then, the
 10 verifier algorithm V sends to the prover (prover algorithm P) sets of challenges $(\text{Ch}_{B,1}^{(0)}, \dots, \text{Ch}_{B,L}^{(0)}), (\text{Ch}_{B,1}^{(1)}, \dots, \text{Ch}_{B,L}^{(1)}) \in_R \{0, 1\}^L$ indicating the selected verification patterns. Additionally, $\text{Ch}_{B,i}^{(0)}$ is not equal to $\text{Ch}_{B,i}^{(1)}$.

[0231]

Step 5:

15 The prover algorithm P that received $(\text{Ch}_{B,1}^{(0)}, \dots, \text{Ch}_{B,L}^{(0)})$ and $(\text{Ch}_{B,1}^{(1)}, \dots, \text{Ch}_{B,L}^{(1)})$ selects a set of challenges to which a response will be given in the following manner. Additionally, the result of selection will be expressed as $d \in_R \{0, 1\}$. If $\text{Ch}_{B,i_0}^{(0)} = \text{Ch}_B^*$, the prover algorithm P sets to $d \leftarrow 1$. On the other hand, if $\text{Ch}_{B,i_0}^{(1)} = \text{Ch}_B^*$, the prover algorithm P sets to $d \leftarrow 0$. When using this method of setting, no
 20 matter which verification pattern is requested by the verifier, the d will take either of values 0 and 1 with a probability of 1/2, respectively. That is, information indicating the value that d took between 0 and 1 is completely hidden.

[0232]

Next, the prover algorithm P calculates Rsp_i with respect to $i = 1, \dots, L$.
 25 The prover algorithm P calculates $\text{Rsp}_i \leftarrow P_{b,3}(\text{Ch}_{B,i}^{(d)}; \text{St}_{B,i})$ for the case of $i \neq i_0$. Also, the prover algorithm P calculates $\text{Rsp}_i \leftarrow M_{b,3}(\text{Ch}_{B,i}^{(d)}; \text{St}_{B,i})$ for the case of $i = i_0$. Then, the prover algorithm P sends $(\text{Rsp}_1, \dots, \text{Rsp}_L, d)$ to the verifier (verifier algorithm V).

[0233]

30 Step 6:

The verifier algorithm V that received $(\text{Rsp}_1, \dots, \text{Rsp}_L, d)$ performs

$0/1 \leftarrow \text{Dec}_b(F, y_i; \text{Cmt}_{A,i}, \text{Ch}_{A,i}, \text{Cmt}_{B,i}, \text{Ch}_{B,i}^{(d)}, \text{Rsp}_i)$ with respect to $i = 1, \dots, L$.
Then, in a case of acceptance (output 1) for all of $i = 1, \dots, L$, the verifier algorithm
V assumes that verification is established.

[0234]

5 In the foregoing, an interactive protocol (modified example) of a case where
the scheme of the present method #2 is applied to the SSH10b public key
authentication scheme has been described. Additionally, in the above explanation,
two sets of challenges are sent from the verifier to the prover, but it is also possible to
determine beforehand the second challenge to be $\text{Ch}_i^{(1)} = \text{Ch}_i^{(0)} + 1 \bmod 2$, for
10 example. In this case, one of the sets of challenges does not have to be sent, and
thus the amount of communication can be reduced.

[0235]

 In the foregoing, the second embodiment of the present disclosure has been
described. The above explanation was given taking the SSH10a public key
15 authentication scheme and the SSH10b public key authentication scheme as the
examples, but the application scope of the present scheme #2 is not limited to these.
Application is also possible to the modified examples of the SSH10a public key
authentication scheme and the SSH10b public key authentication scheme and other
public key authentication schemes. For example, in the example above, (F, y) is set
20 to the public key, but since the F is a parameter not dependent of the secret key, this
 F may also be made a parameter common to the entire system instead of being set for
each prover. In this case, the public keys to be individually published will be y only,
and the size of the public key will be reduced. Furthermore, in the interactive
protocol described above, random numbers $\alpha_1, \dots, \alpha_L$ are separately selected for $i = 1,$
25 $\dots, L$, but these random numbers can be made into one common random number.
In this case, the cost of communication at the time of sending the challenge $\text{Ch}_{A,i}$ can
be reduced.

[0236]

<4: Supplement>

30 A supplemental explanation will be given here of the present methods #1
and #2.

[0237]

[4-1: Extension of Scheme]

In the foregoing, public key authentication schemes based on the problem of multi-order multivariate simultaneous equation have been described. However, the
 5 concept of the present methods #1 and #2 can likewise be applied to other public key authentication schemes. Accordingly, as examples, a method of application to the public key authentication scheme based on the Syndrome Decoding problem, a method of application to the public key authentication scheme based on the Constrained Linear Equations problem, a method of application to the public key
 10 authentication scheme based on the Permuted Kernel problem, a method of application to the public key authentication scheme based on the section-finding problem on an algebraic surface, and a method of application to the public key authentication scheme based on the Permuted Perceptrons problem will be introduced.

15 [0238]

(Application to Syndrome Decoding Problem)

The public key authentication scheme based on the Syndrome Decoding problem is disclosed in, for example, Jacques Stern, "A New Identification Scheme Based on Syndrome Decoding, CRYPTO 1993, p13-21" and Jacques Stern, "A New
 20 Paradigm for Public Key Identification, IEEE Transactions on Information Theory, 1996, p13-21." According to these, this public key authentication scheme includes a 3-pass scheme and a 5-pass scheme.

[0239]

As with the SSH10a public key authentication scheme, there are three
 25 verification patterns for the 3-pass scheme, and there exists a falsification algorithm that can cope with two of the three patterns. Also, as with the SSH10b public key authentication scheme, there are two verification patterns for the 5-pass scheme, and there exists a falsification algorithm that can cope with one of the two patterns. Accordingly, the method described above in relation to the SSH10a public key
 30 authentication scheme can be applied to the 3-pass scheme, and the method described above in relation to the SSH10b public key authentication scheme can be applied to

the 5-pass scheme.

[0240]

(Application to Constrained Linear Equations Problem)

The public key authentication scheme based on the Constrained Linear
 5 Equations problem is disclosed in, for example, Jacques Stern, "Designing
 Identification Schemes with Keys of Short Size, CRYPTO 1994, p164-173."
 According to this, this public key authentication scheme also includes a 3-pass
 scheme and a 5-pass scheme.

[0241]

10 As with the SSH10a public key authentication scheme, there are three
 verification patterns for the 3-pass scheme, and there exists a falsification pattern that
 can cope with two of the three patterns. Also, as with the SSH10b public key
 authentication scheme, there are two verification patterns for the 5-pass scheme, and
 there exists a falsification algorithm that can cope with one of the two patterns.
 15 Accordingly, the method described above in relation to the SSH10a public key
 authentication scheme can be applied to the 3-pass scheme, and the method described
 above in relation to the SSH10b public key authentication scheme can be applied to
 the 5-pass scheme.

[0242]

20 (Application to Permuted Kernel Problem)

The public key authentication scheme based on the Permuted Kernel
 problem is disclosed in, for example, Adi Shamir, "An Efficient Identification
 Scheme Based on Permuted Kernels (Extended Abstract), CRYPTO 1989, p606-609."
 According to this, there are two verification patterns for this public key
 25 authentication scheme, and there exists a falsification algorithm that can cope with
 one of the two patterns. Accordingly, the method described above in relation to the
 SSH10b public key authentication scheme can be applied to the public key
 authentication scheme.

[0243]

30 (Application to Section-Finding Problem on Algebraic Surface)

The public key authentication scheme based on the section-finding problem

on an algebraic surface includes a 3-pass scheme and a 5-pass scheme (for example, see JP 2010-125026A). As with the SSH10a public key authentication scheme, there are three verification patterns for the 3-pass scheme, and there exists a falsification algorithm that can cope with two of the three patterns. Also, as with
5 the SSH10b public key authentication scheme, there are two verification patterns for the 5-pass scheme, and there exists a falsification algorithm that can cope with one of the two patterns. Accordingly, the method described above in relation to the SSH10a public key authentication scheme can be applied to the 3-pass scheme, and the method described above in relation to the SSH10b public key authentication
10 scheme can be applied to the 5-pass scheme.

[0244]

(Application to Permuted Perceptrons Problem)

The public key authentication scheme based on the Permuted Perceptrons problem is disclosed in, for example, David Pointcheval, "A New Identification
15 Scheme Based on the Perceptrons Problem, EUROCRYPT 1995, p319-328" and David Pointcheval and Guillaume Poupard, "A New NP-Complete Problem and Public-Key Identification, Des. Codes Cryptography, 2003, p5-31." According to these, this public key authentication scheme includes a 3-pass scheme and a 5-pass scheme.

20 [0245]

There are four verification patterns for the 3-pass scheme, and there exists a falsification algorithm that can cope with three of the four patterns. On the other hand, there are three verification patterns for the 5-pass scheme, and there exists a falsification algorithm that can cope with two of the three patterns. Accordingly, as
25 with the SSH10a public key authentication scheme and the SSH10b public key authentication scheme, the technologies of the present methods #1 and #2 can be applied to this public key authentication scheme. However, when applying the present method #1 to this public key authentication scheme, the following change has to be made.

30 [0246]

When applying the present method #1 to a scheme with k verification

patterns while causing the secret key to be a multiplexed key including $L = k$ keys, one i (hereinafter, i^*) to which a response will not be given has to be selected from $i = 1, \dots, L$ in the following manner. Specifically, the method of selecting the i^* is a method of selecting $i^* \leftarrow i_0$ in the case of $Ch_{i_0} = Ch^*$, and randomly selecting the i^* from $i^* \in \{1, \dots, L\} \setminus \{i_0\}$ in the case of $Ch_{i_0} \neq Ch^*$.
[0247]

Furthermore, when applying the present method #1 to a scheme with k verification patterns while causing the secret key to be a multiplexed key including L ($L < k$) keys, one i (hereinafter, i^*) to which a response will not be given has to be selected from $i = 1, \dots, L$ in the following manner. Specifically, the method of selecting the i^* is a method of selecting $i^* \leftarrow i_0$ in the case of $Ch_{i_0} = Ch^*$, and selecting $i^* \leftarrow i_0$ with a probability of $(1-1/k)^{-1}(1/L-1/k)$ and randomly selecting the i^* from $i^* \in \{1, \dots, L\} \setminus \{i_0\}$ with a probability of $1-(1-1/k)^{-1}(1/L-1/k)$ in the case of $Ch_{i_0} \neq Ch^*$.
[0248]

According to the above method, no matter which verification pattern is requested by the verifier, the i^* will take a value among $1, \dots, L$ with a probability of $1/L$, and the information indicating the value the i_0 took among $1, \dots, L$ will be completely hidden.
[0249]

As described above, the present methods #1 and #2 can be applied not only to the SSH10a public key authentication scheme and the SSH10b public key authentication scheme, but also to various public key authentication schemes.
[0250]

[4-2: Non-Interactive Public Key Authentication Scheme]

The public key authentication schemes adopting the present methods #1 and #2 described above are schemes where the verifier sends only a random number, and thus modification into a 1-pass (non-interactive) public key authentication scheme is possible. For example, that obtained by applying a hash function to the contents of exchange with the verifier in the configuration of N parallel repetitions may be used instead of the random number to be sent from the verifier. A random number selected by the prover may also be added to the argument of the hash function.

With the prover herself using the hash function instead of the verifier selecting the random number in this manner, a behaviour same as that in the case of the verifier selecting the random number is realized. Additionally, it is desirable that an ideal hash function is used. Furthermore, the number N of repetitions is desirably made
 5 sufficiently large so as not to enable falsification. Such refinement enables modification into the non-interactive public key authentication scheme.

[0251]

[4-3: Method of Reducing Amount of Communication]

A brief supplemental explanation will be given here of a method of reducing
 10 the amount of communication in an interactive protocol with reference to FIGS. 19 and 20.

[0252]

As has been described, a set of messages (c_1, c_2, c_3) is sent from the prover to the verifier in the first pass in the SSH10a public key authentication scheme.
 15 Additionally, in the above explanation, an expression Cmt was used. In the case of the configuration of N parallel repetitions, this set of messages will be ($c_{1,1}, c_{1,2}, c_{1,3}, \dots, c_{N,1}, c_{N,2}, c_{N,3}$) as shown in FIG. 19, and the amount of communication will be extremely large. Thus, the present inventors have devised a configuration for sending these messages collectively as one hash value.

20 [0253]

As shown in FIG. 19, when adopting this configuration, the message to be sent in the first pass will be one hash value only, and the amount of communication can be greatly reduced. Moreover, this hash value and a hash value that is not restored from a response to a challenge sent from the prover are to be sent from the
 25 prover together with the response. According to this configuration, in the case of the configuration of N parallel repetitions, the number of pieces of information to be sent can be reduced by $2N-1$. The same configuration can be applied to the SSH10b public key authentication scheme, as shown in FIG. 20. In this case, the number of pieces of information to be sent can be reduced by $N-1$.

30 [0254]

In the following, a supplementary explanation has been given for the present

methods #1 and #2.

[0255]

<5: Hardware Configuration>

Each algorithm described above can be performed by using, for example,
5 the hardware configuration of the information processing apparatus shown in FIG. 21.
That is, processing of each algorithm can be realized by controlling the hardware
shown in FIG. 21 using a computer program. Additionally, the mode of this
hardware is arbitrary, and may be a personal computer, a mobile information terminal
such as a mobile phone, a PHS or a PDA, a game machine, a contact or contactless
10 IC chip, a contact or contactless IC card, or various types of information appliances.
Moreover, the PHS is an abbreviation for Personal Handy-phone System. Also, the
PDA is an abbreviation for Personal Digital Assistant.

[0256]

As shown in FIG. 21, this hardware mainly includes a CPU 902, a ROM 904,
15 a RAM 906, a host bus 908, and a bridge 910. Furthermore, this hardware includes
an external bus 912, an interface 914, an input unit 916, an output unit 918, a storage
unit 920, a drive 922, a connection port 924, and a communication unit 926.
Moreover, the CPU is an abbreviation for Central Processing Unit. Also, the ROM
is an abbreviation for Read Only Memory. Furthermore, the RAM is an
20 abbreviation for Random Access Memory.

[0257]

The CPU 902 functions as an arithmetic processing unit or a control unit,
for example, and controls entire operation or a part of the operation of each structural
element based on various programs recorded on the ROM 904, the RAM 906, the
25 storage unit 920, or a removal recording medium 928. The ROM 904 is means for
storing, for example, a program to be loaded on the CPU 902 or data or the like used
in an arithmetic operation. The RAM 906 temporarily or perpetually stores, for
example, a program to be loaded on the CPU 902 or various parameters or the like
arbitrarily changed in execution of the program.

30 [0258]

These structural elements are connected to each other by, for example, the

host bus 908 capable of performing high-speed data transmission. For its part, the host bus 908 is connected through the bridge 910 to the external bus 912 whose data transmission speed is relatively low, for example. Furthermore, the input unit 916 is, for example, a mouse, a keyboard, a touch panel, a button, a switch, or a lever.
5 Also, the input unit 916 may be a remote control that can transmit a control signal by using an infrared ray or other radio waves.

[0259]

The output unit 918 is, for example, a display device such as a CRT, an LCD, a PDP or an ELD, an audio output device such as a speaker or headphones, a printer,
10 a mobile phone, or a facsimile, that can visually or auditorily notify a user of acquired information. Moreover, the CRT is an abbreviation for Cathode Ray Tube. The LCD is an abbreviation for Liquid Crystal Display. The PDP is an abbreviation for Plasma Display Panel. Also, the ELD is an abbreviation for Electro-Luminescence Display.

15 [0260]

The storage unit 920 is a device for storing various data. The storage unit 920 is, for example, a magnetic storage device such as a hard disk drive (HDD), a semiconductor storage device, an optical storage device, or a magneto-optical storage device. The HDD is an abbreviation for Hard Disk Drive.

20 [0261]

The drive 922 is a device that reads information recorded on the removal recording medium 928 such as a magnetic disk, an optical disk, a magneto-optical disk, or a semiconductor memory, or writes information in the removal recording medium 928. The removal recording medium 928 is, for example, a DVD medium,
25 a Blu-ray medium, an HD-DVD medium, various types of semiconductor storage media, or the like. Of course, the removal recording medium 928 may be, for example, an electronic device or an IC card on which a non-contact IC chip is mounted. The IC is an abbreviation for Integrated Circuit.

[0262]

30 The connection port 924 is a port such as an USB port, an IEEE1394 port, a SCSI, an RS-232C port, or a port for connecting an externally connected device 930

such as an optical audio terminal. The externally connected device 930 is, for example, a printer, a mobile music player, a digital camera, a digital video camera, or an IC recorder. Moreover, the USB is an abbreviation for Universal Serial Bus. Also, the SCSI is an abbreviation for Small Computer System Interface.

5 [0263]

The communication unit 926 is a communication device to be connected to a network 932, and is, for example, a communication card for a wired or wireless LAN, Bluetooth (registered trademark), or WUSB, an optical communication router, an ADSL router, or a device for contact or non-contact communication. The
 10 network 932 connected to the communication unit 926 is configured from a wire-connected or wirelessly connected network, and is the Internet, a home-use LAN, infrared communication, visible light communication, broadcasting, or satellite communication, for example. Moreover, the LAN is an abbreviation for Local Area Network. Also, the WUSB is an abbreviation for Wireless USB. Furthermore, the
 15 ADSL is an abbreviation for Asymmetric Digital Subscriber Line.

[0264]

<6: Summary>

Lastly, the technical contents according to the embodiment of the present disclosure will be briefly described. The technical contents stated here can be
 20 applied to various information processing apparatuses, such as a personal computer, a mobile phone, a portable game machine, a portable information terminal, an information appliance, a car navigation system, and the like.

[0265]

The functional configuration of the information processing apparatus
 25 described above can be expressed as below. The information processing apparatus includes a key holding unit and an interactive protocol execution unit as below. The key holding unit is for holding L ($L \geq 2$) secret keys s_i ($i = 1$ to L) and L public keys y_i that satisfy $y_i = F(s_i)$ with respect to a set F of multivariate polynomials of n -th order ($n \geq 2$). Also, the interactive protocol execution unit is for performing, with a
 30 verifier, an interactive protocol for proving knowledge of $(L-1)$ secret keys s_i that satisfy $y_i = F(s_i)$. Furthermore, the interactive protocol execution unit prevents, at

the time of performing the interactive protocol with the verifier, the verifier from knowing which secret key s_i was used.

[0266]

By causing the secret key s_i to be a multiplexed key and using a part of the
5 secret keys at the time of performing an interactive protocol and also by preventing
which secret key s_i was used from becoming known in the interactive protocol, a
security level sufficient for an active attack can be guaranteed also in the case of the
parallel-repetition configuration. That is, even if a falsifier tried to impersonate the
verifier and tried to obtain information on the secret key s_i that is used in the
10 authentication, which secret key s_i is used in the interactive protocol is not known
even to the verifier. That is, even in a situation where the interactive protocol can
be performed an arbitrary number of times, information on the secret key s_i is not
leaked by the prover, and a security level sufficient for an active attack can be
guaranteed.

15 [0267]

(Notes)

The information processing apparatus described above is an example of an
authentication device on the prover side or the verifier side. Furthermore, the ROM
904, the RAM 906, the storage unit 920 and a removable recording medium 928 are
20 examples of a key holding unit. Additionally, a secret key s_i and a public key y_i
that are held in the key holding unit are generated by the key generation algorithm
Gen. Furthermore, the prover algorithm P and the verifier algorithm V are
examples of an interactive protocol execution unit. Additionally, in reality, the
function of the interactive protocol execution unit is realized by the prover algorithm
25 P or the verifier algorithm V being performed by the function of the CPU 902.
Furthermore, the functions of a challenge reception unit, a challenge selection unit,
a response generation unit, a response transmission unit and a message transmission
unit are realized by the functions realized by the prover algorithm P . Additionally,
the function of the communication unit 926 is used for the exchange of information.

30 [0268]

The preferred embodiments of the present invention have been described

above with reference to the accompanying drawings, whilst the present invention is not limited to the above examples, of course. A person skilled in the art may find various alternations and modifications within the scope of the appended claims, and it should be understood that they will naturally come under the technical scope of the
5 present invention.

Reference Signs List

- [0269]
- | | | |
|----|-----|--------------------------|
| | Gen | key generation algorithm |
| 10 | P | prover algorithm |
| | V | verifier algorithm |

CLAIMS

1. An authentication device comprising:
circuitry configured to:
 - set $s \in K^n$ to a secret key, and set multi-order polynomials on a ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;
 - transmit message c to a verifier;
 - receive information on one verification pattern selected from k ($k \geq 3$) verification patterns by the verifier according to one piece of the message c ; and
 - transmit response information corresponding to the information on the verification pattern received, the response information being one of k ways of response information to the verifier,
 wherein the response information is calculated using information $z \in K^n$ in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked by $t \in K^n$, polynomial $f_i'(x)$ in which multi-order polynomials $f_i(x+r)$ related to x is masked by polynomial $f_i'(x)$.
2. An authentication device according to claim 1,
 wherein the multi-order polynomials $f_i(x_1, \dots, x_n)$ ($i=1$ to m) is a second-order polynomial, and
 the $f_i'(x)$ is a first-order polynomial.
3. An authentication device according to claim 2,
 wherein the first-order polynomial is a first-order polynomial $f_i(x+t)-f_i(x)-f_i(t)+e_i$ ($e_i \in K$) related to x .
4. An authentication device comprising:
circuitry configured to:
 - set $s \in K^n$ to a secret key, and set second-order polynomials on a

ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;
 transmit message c to a verifier;
 receive information on one verification pattern selected from k
 ($k \geq 3$) verification patterns by the verifier according to one piece of the
 message c ; and
 transmit response information corresponding to the information
 on the verification pattern received, the response information being one
 of k ways of response information to the verifier,
 wherein the response information is calculated using information $z \in K^n$
 in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked
 by $t \in K^n$, $e_i' \in K$ in which $f_i(r)$ substituted by the r for the second-order
 polynomials f_i is masked by $e_i \in K$.

5. An authentication method comprising:

setting, with circuitry, $s \in K^n$ to a secret key, and setting multi-order
 polynomials on a ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;
 transmitting, with the circuitry, message c to a verifier;
 receiving, with the circuitry, information on one verification pattern
 selected from k ($k \geq 3$) verification patterns by the verifier according to one
 piece of the message c ; and

transmitting, with the circuitry, response information corresponding to
 the information on the verification pattern received, the response information
 being one of k ways of response information to the verifier,

wherein the response information is calculated using information $z \in K^n$
 in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked
 by $t \in K^n$, polynomial $f_i'(x)$ in which multi-order polynomials $f_i(x+r)$ related to
 x is masked by polynomial $f_i'(x)$.

6. An authentication method comprising:

setting, with circuitry, $s \in K^n$ to a secret key, and setting second-order

polynomials on a ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;

transmitting, with the circuitry, message c to a verifier;

receiving, with the circuitry, information on one verification pattern selected from k ($k \geq 3$) verification patterns by the verifier according to one piece of the message c ; and

transmitting, with the circuitry, response information corresponding to the information on the verification pattern received, the response information being one of k ways of response information to the verifier,

wherein the response information is calculated using information $z \in K^n$ in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked by $t \in K^n$, $e_i' \in K$ in which $f_i(r)$ substituted by the r for the second-order polynomials f_i is masked by $e_i \in K$.

7. A non-transitory computer readable medium including computer executable instructions, which when executed by a computer cause the computer to perform a method comprising:

setting $s \in K^n$ to a secret key, and setting multi-order polynomials on a ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;

transmitting message c to a verifier;

receiving information on one verification pattern selected from k ($k \geq 3$) verification patterns by the verifier according to one piece of the message c ; and

transmitting response information corresponding to the information on the verification pattern received, the response information being one of k ways of response information to the verifier,

wherein the response information is calculated using information $z \in K^n$ in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked by $t \in K^n$, polynomial $f_i'(x)$ in which multi-order polynomials $f_i(x+r)$ related to x is masked by polynomial $f_i'(x)$.

8. A non-transitory computer readable medium including computer executable instructions, which when executed by a computer cause the computer to perform a method comprising:

setting $s \in K^n$ to a secret key, and setting second-order polynomials on a ring K , $f_i(x_1, \dots, x_n)$ ($i=1$ to m) and $y_i=f_i(s)$ to a public key;


transmitting message c to a verifier;

receiving information on one verification pattern selected from k ($k \geq 3$) verification patterns by the verifier according to one piece of the message c ; and

transmitting response information corresponding to the information on the verification pattern received, the response information being one of k ways of response information to the verifier, wherein the response information is calculated using information $z \in K^n$ in which the secret key s is masked by $r \in K^n$, $t' \in K^n$ in which the r is masked by $t \in K^n$, $e_i' \in K$ in which $f_i(r)$ substituted by the r for the second-order polynomials f_i is masked by $e_i \in K$.


1/20
FIG. 1


PUBLIC KEY AUTHENTICATION SCHEME




2/20
FIG. 2

N-PASS PUBLIC KEY AUTHENTICATION SCHEME







4/20
FIG. 4
SSH10b PUBLIC KEY AUTHENTICATION SCHEME



SP304599WO00


5/20


FIG. 5**FIG. 6**

6/20

FIG. 7

FALSIFICATION ALGORITHM FOR SSH10a
PUBLIC KEY AUTHENTICATION SCHEME






8/20

FIG. 9


APPLICATION OF PRESENT METHOD #1
TO SSH10a PUBLIC KEY AUTHENTICATION SCHEME



9/20

FIG. 10


APPLICATION OF PRESENT METHOD #1
TO SSH10a PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE 1)



10/20

FIG. 11


APPLICATION OF PRESENT METHOD #1
TO SSH10a PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE 2)



11/20

FIG. 12

APPLICATION OF PRESENT METHOD #1
TO SSH10a PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE 3)



12/20

FIG. 13

APPLICATION OF PRESENT METHOD #1
TO SSH10b PUBLIC KEY AUTHENTICATION SCHEME

$pk = (F, y_1, \dots, y_L)$

PROVER

VERIFIER

$sk = (s_1, \dots, s_L)$

Step.1

PERFORM THE FOLLOWING FOR $i=1, \dots, L$:
SELECT $r_i, t_i \in K^n, e_i \in K^m$
 $(Cmt_{A,i}; St_{A,i}) \leftarrow P_{b,1}(F, y_i, s_i; r_i, t_i, e_i)$

$Cmt_{A,i}$
 $i=1, \dots, L$

Step.2

$Ch_{A,1}, \dots, Ch_{A,L} \in R^K$

$Ch_{A,i}$
 $i=1, \dots, L$

Step.3

PERFORM THE FOLLOWING FOR $i=1, \dots, L$
 $(Cmt_{B,i}; St_{B,i}) \leftarrow P_{b,2}(Ch_{A,i}; St_{A,i})$

$Cmt_{B,i}$
 $i=1, \dots, L$

Step.4

$Ch_{B,1}, \dots, Ch_{B,L} \in R^{\{0,1\}}$

$Ch_{B,i}$
 $i=1, \dots, L$

Step.5

SELECT $i' \in \{1, \dots, L\}$
PERFORM THE FOLLOWING FOR $i \in \{1, \dots, L\} \setminus \{i'\}$
 $Rsp_i \leftarrow P_{b,3}(Ch_{B,i}; St_{B,i})$

$i', Rsp_{i'}$
 $i \in \{1, \dots, L\} \setminus \{i'\}$

Step.6


PERFORM THE FOLLOWING FOR $i \in \{1, \dots, L\} \setminus \{i'\}$
 $0/1 \leftarrow Dec_b(F, y_i; Cmt_{A,i}, Ch_{A,i}, Cmt_{B,i}, Ch_{B,i}, Rsp_i)$

SP304599WO00

13/20

FIG. 14


APPLICATION OF PRESENT METHOD #1
TO SSH10b PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE)



14/20

FIG. 15


APPLICATION OF PRESENT METHOD #2
TO SSH10a PUBLIC KEY AUTHENTICATION SCHEME



15/20

FIG. 16


APPLICATION OF PRESENT METHOD #2
TO SSH10a PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE)



16/20

FIG. 17


APPLICATION OF PRESENT METHOD #2
TO SSH10b PUBLIC KEY AUTHENTICATION SCHEME



17/20


FIG. 18

APPLICATION OF PRESENT METHOD #2
TO SSH10b PUBLIC KEY AUTHENTICATION
SCHEME (MODIFIED EXAMPLE)




18/20
FIG. 19

METHOD OF REDUCING COMMUNICATION AMOUNT (CASE OF SSH10a)




19/20
FIG. 20

METHOD OF REDUCING COMMUNICATION AMOUNT (CASE OF SSH10b)



20/20
FIG. 21



APPLICATION OF PRESENT METHOD #1
TO SSH10a PUBLIC KEY AUTHENTICATION SCHEME

