



US009142080B2

(12) **United States Patent**
Templer et al.

(10) **Patent No.:** **US 9,142,080 B2**
(45) **Date of Patent:** **Sep. 22, 2015**

(54) **DISPENSING CONSUMER PRODUCTS**

(75) Inventors: **John Wesley Templer**, Palmer, TX (US);
Mark Allsup, Fort Worth, TX (US)

(73) Assignee: **Sell Trax Investments, LLC**, Palmer,
TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 584 days.

(21) Appl. No.: **12/019,515**

(22) Filed: **Jan. 24, 2008**

(65) **Prior Publication Data**

US 2009/0192837 A1 Jul. 30, 2009

(51) **Int. Cl.**

A47F 1/04 (2006.01)
G05B 13/02 (2006.01)
G06Q 10/00 (2012.01)
G07F 11/04 (2006.01)
G07F 11/00 (2006.01)
G07G 1/00 (2006.01)

(52) **U.S. Cl.**

CPC **G07F 11/04** (2013.01); **G07F 11/002**
(2013.01); **G07G 1/0036** (2013.01)

(58) **Field of Classification Search**

CPC G07F 11/002; G07F 11/04
USPC 221/129, 131; 700/232, 236-237
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,601,237 A * 8/1971 Ovsienko 194/239
3,870,135 A * 3/1975 Allen 194/205
4,482,078 A * 11/1984 Reiss 221/150 HC
4,961,507 A * 10/1990 Higgins 221/129

5,205,436 A * 4/1993 Savage 221/7
5,207,784 A 5/1993 Schwartzendruber
5,243,174 A * 9/1993 Veeneman et al. 235/381
5,467,892 A * 11/1995 Schlamp 221/7
5,805,456 A 9/1998 Higham
5,847,389 A 12/1998 Mertins
5,959,869 A 9/1999 Miller et al.
5,971,205 A 10/1999 Michaels et al.
6,206,234 B1 3/2001 Rawlins
6,213,341 B1 4/2001 Keith
6,259,965 B1 7/2001 Steele
6,269,285 B1 7/2001 Mignault
6,324,520 B1 11/2001 Walker et al.

(Continued)

OTHER PUBLICATIONS

USPTO Non-Final Office Action in U.S. Appl. No. 12/335,873 dated
Apr. 6, 2011, 5 pages.

(Continued)


Primary Examiner — Michael K Collins

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A system for dispensing consumer products includes a prod-
uct bin unit; a product ejector; a product trigger; and a con-
troller. The product bin unit includes a product bin; an ejector
aperture; and a trigger aperture. The product ejector is
coupled to the product bin unit through the ejector aperture
and adapted to drive the product package from the product bin
upon receipt of a dispensing signal. The product trigger is
coupled to the product bin unit through the trigger aperture.
The controller is in communication with the product ejector
and the product trigger and includes at least one memory and
a processor. The memory stores a dispensing module. The
processor is adapted to execute the dispensing module, and
the dispensing module is operable when executed to receive a
dispensing instruction and transmit the dispensing signal to
the product ejector based, at least in part, on the dispensing
instruction.

26 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS


6,384,402 B1 * 5/2002 Hair et al. 250/223 R
6,393,339 B1 * 5/2002 Yeadon 700/237
6,424,884 B1 7/2002 Brooke
6,539,282 B2 3/2003 Metcalf et al.
6,604,652 B1 8/2003 Trautwein
6,684,126 B2 1/2004 Omura et al.
6,708,079 B2 3/2004 Mason
6,711,465 B2 3/2004 Tomassi
6,792,334 B2 9/2004 Metcalf et al.
6,808,082 B2 10/2004 Ohkubo
6,871,756 B1 * 3/2005 Gallo 221/75
6,896,145 B2 5/2005 Higgins et al.
7,086,560 B2 8/2006 Shioya
7,530,113 B2 * 5/2009 Braun 726/28
8,019,471 B2 * 9/2011 Bogash et al. 700/242
8,086,349 B2 * 12/2011 Blust et al. 700/232


8,401,697 B2 3/2013 Templer
2002/0046122 A1 * 4/2002 Barber et al. 705/17
2004/0252676 A1 * 12/2004 Bye 370/352
2004/0254676 A1 * 12/2004 Blust et al. 700/231
2005/0269347 A1 12/2005 Templer et al.
2006/0235569 A1 10/2006 Watts
2007/0185615 A1 * 8/2007 Bossi et al. 700/244
2013/0297067 A1 11/2013 Templer

OTHER PUBLICATIONS

USPTO Final Office Action in U.S. Appl. No. 12/335,873 dated Oct. 28, 2011, 6 pages.
USPTO Non-Final Office Action in U.S. Appl. No. 12/335,873 dated Mar. 9, 2012, 6 pages.
USPTO Quayle Action in U.S. Appl. No. 12/335,873 dated Sep. 21, 2012, 5 pages.

* cited by examiner









FIG. 1C

FIG. 2A








FIG. 2B







FIG. 4A

400

FIG. 4B

FROM FIG. 4A



DISPENSING CONSUMER PRODUCTS

TECHNICAL BACKGROUND

This disclosure relates to dispensing consumer products, and more particularly, to dispensing tobacco products from a system for securing tobacco products against theft.

BACKGROUND

Consumer products, and in particular tobacco products, are sold to the public in a variety of different locations. Such locations may include grocery stores, convenience stores, restaurants, and bars, to name but a few. Generally, an employee of such locations may be responsible for the management and sale of the tobacco products at any given time period. Management of the tobacco products may include, for example, storing the tobacco products in a safe and secure location, performing inspection and inventory on the tobacco products at predetermined intervals, transporting the tobacco products from the secure location to a display stand or cabinet, and completing a sale transaction of the tobacco products to consumers. In some instances, one or more packages of tobacco products may be misplaced, stolen, or otherwise lost, possibly resulting in loss of revenue or profits from the location. Moreover, such loss of revenue or profits may not be transferred to another business, such as a manufacturer of the tobacco products. Theft of tobacco products, and indeed any consumer product, may be a concern for sellers and resellers of such products.

Further, the management of the tobacco products, particularly the inventory procedure, may be time consuming and tedious. Such a procedure, in some cases, may be performed manually by the employee of the location at which the inventory is maintained. Thus, there may be some degree of error associated with the procedure, such as a miscount of revenue or quantity. Errors such as these can lead to mistakes in ordering future product, possibly resulting in an overstock of the product or an out-of-stock condition. Therefore, many sellers of tobacco products may spend a substantial amount of revenue ensuring that such errors do not occur.

SUMMARY

In one general implementation, a system for dispensing consumer products includes a product bin unit; a product ejector; a product trigger; and a controller. The product bin unit includes a product bin adapted to hold at least one product package; an ejector aperture; and a trigger aperture. The product ejector is coupled to the product bin unit through the ejector aperture and adapted to drive the product package from the product bin upon receipt of a dispensing signal. The product trigger is coupled to the product bin unit through the trigger aperture. The controller is communicably coupled to the product ejector and the product trigger and includes at least one memory and one or more processors. The memory stores a dispensing module. The one or more processors are adapted to execute the dispensing module, and the dispensing module is operable when executed to receive a dispensing instruction and transmit the dispensing signal to the product ejector based, at least in part, on the dispensing instruction.

In more specific aspects, the product bin unit may further include a substantially vertical back plate including the ejector aperture; a substantially horizontal bottom plate coupled to the back plate and including the trigger aperture; a first vertical side plate and a second vertical side plate coupled to at least one of the back plate and the bottom plate; and a first

substantially vertical divider plate. The first divider plate may be coupled to at least one of the back plate and the bottom plate and may be arranged between the first and second side plates. At least a portion of the back plate, the bottom plate, the divider plate, and one of the first or second side plates may define the product bin. The product bin may be adapted to receive the product package from a front of the product bin.

In certain aspects of the system, the product package may be a tobacco product, a medicinal product, or a shaving product (e.g., a package of razor blades). The tobacco product may include, for example, a cigarette package or a smokeless tobacco package, and the medicinal product may include, for example, a pain reliever package or a cough syrup package. Additionally, the product ejector may be an electrically actuated piston-cylinder that may include an electromagnet adapted to drive at least a portion of the piston from the cylinder upon energizing and a spring adapted to drive the portion of the piston into the cylinder upon de-energizing of the electromagnet. Further, the product trigger may include a sensor adapted to transmit a confirmation signal to the controller upon actuation of the piston-cylinder.

In some particular aspects, multiple product bin units may be provided and the system may further include a cabinet adapted to enclose at least a portion of the product bin units and the controller. The cabinet may include a supply compartment including a door pivotally coupled to the cabinet and a return compartment including a return opening. The product bin units may include a first product bin that is open in a first direction and a second product bin that is open in a second direction. The second direction may be approximately 180 degrees from the first direction. Also, the first product bin may be adapted to hold a first size product package, and the second product pin may be adapted to hold a second, smaller size product package. The return compartment may include a lockable door pivotally coupled to the return compartment. Additionally, the cabinet may be substantially opaque.

In certain implementations, the system may further include an electronic data reader coupled to the controller and adapted to transmit the dispensing instruction to the controller at least partially based on data stored on a product purchase ticket. The electronic data reader may include a magnetic ink character recognition (MICR) reader. The product purchase ticket may include a MICR code that includes at least one of a representation of a product package quantity and a representation of a product package type.

In particular aspects, the dispensing module may be further operable to present a graphical user interface (GUI) to a user. The dispensing module may receive the dispensing instruction from the user through the GUI, and the dispensing instruction may include a product type and a product quantity. The dispensing module may compare the product type to a product library stored in the memory; compare the product quantity to a product inventory of the product type stored in the memory; determine a product selection based on the product type and the product quantity; generate the dispensing signal based on the product selection; and transmit the dispensing signal to the product ejector. Further, the dispensing module may be operable to receive a request from the user for at least one sales data point, where the request includes a time period. The sales data point may include one of the following: a value of sales in the time period based on the product type; a value of sales in the time period based on the product bin, where the product bin may include at least one product package of the same product type; and a value of sales in the time period based on a time shift period, where the time shift period may be at least a portion of a 24 hour period. The dispensing module may further be operable to generate a

report including the sales data point and to save the report for subsequent presentation to the user through the GUI.

In some aspects, the dispensing module may further be operable to present an authorization code request to the user; receive an authorization code from the user; confirm the authorization code as a valid code; present a sales data request to the user; and receive the sales data request from the user. The request may include the time period and one of the following: the product type; the product bin; or the time shift period. Also, the dispensing module may further be operable to receive an update to the product library stored in the memory; receive a remote request from a remote user for the sales data point; and transmit the sales data point to the remote user. The dispensing module may further be operable to receive a second quantity of product packages of the product type input from the user; calculate a new product inventory of the product type (where the new product inventory is equal to a sum of the product inventory and the second quantity); and present the new product inventory of the product type to the user.

In another general aspect, a method for dispensing consumer product includes: presenting a graphical interface to a user; receiving a product type and a product quantity from the user through the graphical interface; comparing the product type to a product library stored in a memory; comparing the product quantity to a product inventory of the product type stored in the memory; determining a product selection based on the product type and the product quantity; generating a dispensing signal based on the product selection; transmitting the dispensing signal to a product ejector; and driving a first quantity of a product package from a product bin by the product ejector, where the first quantity is equal to the product quantity.

The method may further include receiving a request from the user for at least one sales data point, where the request includes a time period; generating a report comprising the sales data point; and graphically presenting the report to the user. The sales data point may be, for example, one of the following: a value of sales in the time period based on the product type; a value of sales in the time period based on a product bin, where the product bin may include at least one product package of the same product type; and a value of sales in the time period based on a time shift period, where the time shift period includes at least a portion of a 24 hour period.

In some aspects, receiving a request from the user for at least one sales data point may include presenting an authorization code request to the user; receiving the authorization code from the user; confirming the authorization code as a valid code; presenting a sales data request to the user; and receiving the sales data request from the user. The request may include the time period and one of the product type; the product bin; or the time shift period. The method may also include the steps of receiving an update to the product library stored in the memory; receiving a remote request from a remote user for the sales data point; and transmitting the sales data point to the remote user.

In certain aspects, the method may include the steps of receiving a second quantity of product packages of the product type; calculating a new product inventory of the product type, where the new product inventory is approximately equal to a sum of the product inventory and the second quantity; and decreasing the new product inventory by the product quantity upon driving the first quantity of the product package from the product bin by the product ejector. Further, receiving a product type and a product quantity from the user through the

graphical interface may include receiving a product type and a product quantity from the user via a MICR code on a product purchase ticket.

One or more implementations of a system or method for dispensing consumer product described in the present disclosure may include one, some, or all of the following features. For example, a system or method for dispensing consumer product may provide for a more secure location for one or more consumer products, such as tobacco products or medicinal products. As another example, a system or method for dispensing consumer product may help reduce revenue losses of tobacco or medicinal products due to theft. As a further example, a system or method for dispensing consumer product may at least partially increase revenue of a business enterprise by decreasing labor costs. As yet another example, a system or method for dispensing consumer product may allow for expedited and accurate tracking of tobacco or medicinal product sales. Also, a system or method for dispensing consumer product may allow sales of tobacco or medicinal product to be monitored at a location remote from the sale location. Further, a system or method for dispensing consumer product may at least partially assist a business enterprise in maintaining an appropriate inventory size of tobacco and medicinal product. A system or method for dispensing consumer product, additionally, may provide a nondescript container for tobacco and medicinal products. As another example, a system or method for dispensing consumer product may allow for easier sales data and inventory data tracking of tobacco or medicinal products by a business enterprise.

These general and specific aspects may be implemented using a device, system or method, or any combinations of devices, systems, or methods. The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features, objects, and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIGS. 1A-C illustrate a system for dispensing consumer products;

FIGS. 2A-C illustrate an alternative system for dispensing consumer products including a cabinet;

FIG. 3 is an example of a graphical user interface which may be used in a system for dispensing consumer products; and

FIG. 4 is a flowchart illustrating an example of a method for dispensing consumer products.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

FIGS. 1A-C illustrate one implementation of a system **100** for dispensing consumer products. System **100**, for example, may be utilized to dispense tobacco products, medicinal products, or any other consumer product, as appropriate, in a variety of locations. For instance, system **100** may be utilized in a grocery store, a convenience store, a restaurant, or a bar. In some aspects, the system **100** may be mounted behind a sales counter in a convenience store, thereby allowing access to the system **100** by one or more sales associates or sales administrators. Generally, system **100** encloses one or more consumer products and dispenses such consumer products upon receipt of an appropriate electronic instruction.

System 100 includes a product bin unit 105, a controller 140, a point-of-sale (POS) terminal 170, and a remote terminal 175. The product bin unit 105, typically, may be a structure formed of molded plastic, aluminum, or galvanized steel, which includes a back plate 106, a bottom plate 107, one or more side plates 108a and 108b, and one or more divider plates 109. As illustrated, the back plate 106 is substantially vertical and planar, and is coupled at its base to the bottom plate 107. The bottom plate 107 is substantially horizontal and planar and supports the back plate 106, side plates 108a and 108b, and divider plates 109. Each side plate 108a and 108b and divider plate 109 may be coupled to the bottom plate 107 and back plate 106.

A configuration of the product bin unit 105, including the back plate 106, bottom plate 107, side plates 108a and 108b, and divider plates 109, may form one or more product bins 110. Each product bin 110, in some aspects, may be an elongated enclosure with a substantially rectangular transverse cross-section with two open sides, such as is shown in FIGS. 1A-C. One or more product packages 135 may thus be loaded into each product bin 110 from a front side or top side of the bin 110.

One or more components of the product bin unit 105, namely, the back plate 106, bottom plate 107, side plates 108a and 108b, and divider plates 109 may be formed as an integral piece of molded plastic. But the foregoing components may be separately manufactured and fastened together to form the product bin unit 105 through, for example, mechanical fasteners such as drive screws or bolts, or adhesives.

The back plate 106 includes one or more ejector apertures 115. Each ejector aperture 115 is located proximate to the bottom plate 107, such that, for instance, the aperture 115 is aligned with the product package 135 in contact with the bottom plate 107. The ejector aperture 115 allows at least a portion of a product ejector 125 to extend through the back plate 106 proximate to the product package 135 on the bottom plate 107. The bottom plate 107 may include one or more trigger apertures 120, located immediately beneath the product package 135 supported by the bottom plate 107. A trigger aperture 120 allows at least a portion of a product trigger 130 to extend through the bottom plate 107.

One or more product ejectors 125 are attached to the bottom plate 107. Generally, there may be a corresponding product ejector 125 for each product bin 110. The product ejectors 125 may be electrically-actuated to extend a portion of the product ejector 125 through the ejector aperture 115 to contact the product package 135 in contact with the bottom plate 107, thus driving the product package 135 from the product bin 110. In some aspects, the product ejector 125 may be an electrically-actuated piston-cylinder device, including an electromagnet 126. Upon energizing of the electromagnet 126, a piston-portion, at least some of which may be metallic, may be driven through and extend from the cylinder and through the ejector aperture 115. When the piston contacts the product package 135, the package 135 may be driven from the product bin 110, thereby dispensing the product package 135 from the system 100. Upon de-energizing of the electromagnet 126, a spring 127 within the cylinder-portion may force the piston back into the cylinder to await another actuation signal (e.g., dispensing signal 160).

Each product ejector 125 is in communication with the controller 140 through one or more electrical connections coupled to a connection port 185. Therefore, upon receipt of a dispensing signal 160, the product ejector 125 may be actuated to dispense the product package 135. The product trigger 130 is also in communication with the controller 140. Once the product package 135 is dispensed from the system

100, the product trigger 130 may transmit a confirmation signal 165 to the controller 140 confirming that the product package 135 has been driven from the product bin 110. For instance, in some aspects, the product trigger 130 may include an electronic sensor that determines when the product package 135 is dispensed. In some implementations, the product trigger 130 may work in collaboration with the product ejector 125, such that actuation of the product ejector 125 may actuate the product trigger 130 as well.

The controller 140 is a processing device that can receive and transmit electrical or electronic signals for dispensing consumer products and is in communication with one or more product ejectors 125 and one or more product triggers 130. Controller 140 includes a memory 145 and a processor 155. Although illustrated as a single memory, memory 145 may include multiple memory modules. Further, memory 145 may include any memory or database module and may take the form of volatile or non-volatile memory including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable local or remote memory component. Illustrated memory 145 includes or points to a dispensing module 150 and a product library 152. But memory 145 may also include any other appropriate data such as VPN applications or services, firewall policies, a security or access log, print or other reporting files, HTML files or templates, data classes or object interfaces, child software applications or sub-systems, and others.

The processor 155 executes instructions and manipulates data to perform the operations of the controller 140. Processor 155 is, for example, a central processing unit (CPU), a blade, an application specific integrated circuit (ASIC), or a field-programmable gate array (FPGA). Although FIGS. 1A-C illustrate a single processor 155 in the controller 140, multiple processors 155 may be used according to particular needs and reference to processor 155 is meant to include multiple processors 155 where applicable. In the illustrated embodiment, processor 155 executes the dispensing module 150, as well as any other modules, sub-modules, or applications stored on or accessed by the controller 140.

Dispensing module 150, at a high level, provides a structured environment (e.g., a software application) from which one or more consumer product dispensing processes, modules, or applications may be operated by, for instance, the controller 140, the POS terminal 170, or the remote terminal 175. In other words, dispensing module 150 provides an environment in which the controller 140, the POS terminal 170, or the remote terminal 175 may manipulate, manage, or view product dispensing information. Regardless of the particular implementation, "software" may include software, firmware, wired or programmed hardware, or any combination thereof as appropriate. Indeed, dispensing module 150 may be written or described in any appropriate computer language including C, C++, Java, Visual Basic, assembler, Perl, any suitable version of 4GL, as well as others. For example, dispensing module 150 may be a composite application, portions of which may be implemented as Enterprise Java Beans (EJBs) or the design-time components may have the ability to generate run-time implementations into different platforms, such as J2EE (Java 2 Platform, Enterprise Edition), ABAP (Advanced Business Application Programming) objects, or Microsoft's NET. It will be understood that dispensing module 150 may include numerous other sub-modules or may instead be a single multi-tasked module that implements the various features and functionality through various objects, methods, or other processes. Further, while illustrated as internal to the controller 140, one or more pro-

cesses associated with dispensing module **150** may be stored, referenced, or executed remotely. For example, a portion of dispensing module **150** may be a web service that is remotely called, by, for instance, remote terminal **175**, while another portion of dispensing module **150** may be an interface object bundled for processing at the controller **140**. Moreover, dispensing module **150** may be a child or sub-module of another software module or enterprise application (not illustrated) without departing from the scope of this disclosure.

Generally, the dispensing module **150** provides a software interface for a user of the system **100** in order to, for example, dispense one or more product packages **135**, keep track of inventory of the product packages **135** stored in the system **100**, and calculate or store one or more sales metrics, which may be used to predict future requirements or needs of the system **100**. For instance, in some aspects, the dispensing module **150** may provide a graphical interface for display on POS terminal **170**, remote terminal **175**, or a display (not shown) integral to the system **100** itself. The graphical interface may allow for the user to choose a particular type of product package **135** (e.g., a brand of cigarette or particular type of cigarette among several), as well as a quantity of product packages **135** to be dispensed. Once this information is received from the user by the dispensing module **150**, it may determine the appropriate dispensing signal **160** to transmit to one or more product ejectors **125**. In some aspects, this information is included in a dispensing instruction **180** transmitted from the POS terminal **170** to the controller **140**.

Further, the dispensing module **150** may ensure that product packages **135** of identical type, which reside in distinct product bins **110**, are dispensed evenly, thereby ensuring that quantities of the product packages **135** in the product bins **110** decrease evenly. As one example, adjacent product bins **110** may each contain a particular type of cigarette packages. If the user enters a quantity of two for the particular type of cigarette, then one cigarette package from each product bin **110** is dispensed according to an appropriate dispensing signal **160** generated by the dispensing module **150**.

The dispensing module **150** may also, typically, generate and store inventory data for one or more product packages **135** contained in the product bins **110**. For example, a total quantity of product packages **135** contained in each product bin **110** may be input into the dispensing module **150** by the user at, for example, the POS terminal **170**, remote terminal **175**, or other stand alone computing device as appropriate. As product packages **135** are dispensed (e.g., sold) from the system **100**, the dispensing module **150** adjusts various data to account for such sales. For instance, the dispensing module **150** may keep track of data including: total sales of product packages **135** over a particular time frame (e.g., hour, day, week, month, work shift); total sales of product packages **135** of a particular type or brand; total sales of product packages **135** from a particular bin **110**; total value of product packages **135** presently in the system **100**; total value of product packages **135** of a particular type or brand presently in the system **100**; and total value of product packages **135** presently within a particular bin **110**. As further examples, the dispensing module **150** may also account for data such as: a time and date when one or more product packages **135** were added to the system **100** and an employee or user which added product packages **135** to the system **100**. The dispensing module **150** may also generate one or more reports including information and data to be displayed on, for example, the POS terminal **170**, remote terminal **175**, or other appropriate device, such as a mobile computing device or a personal digital assistant (PDA).

Memory **145** may also store or point to the product library **152**. The product library **152** typically includes data describing various parameters of the product packages **135** stored in the system **100**. Product library **152** may be in any appropriate format, such as, for example, in a relational format, thus allowing the memory **145** to provide access to such data using a structured query language (SQL), which may include any of the plurality of versions of the SQL relational database query and manipulation language such as, for example, SEQUEL, ANSI SQL, any other proprietary or public variant of SQL, or other suitable or generic query language (such as eXtensible Markup Language (XML)). Memory **145** may include all of the product library **152**, but product library **152** may be stored on one or more remote servers, memories, or data repositories, including, for example, POS terminal **170** and remote terminal **175**.

The product library **152** may store various data associated with the product packages **135**, including: a sale price, a brand name, a type, and an SKU of an individual product package **135**. Further, the product library **152** may store a graphical representation (e.g., a .JPEG, .JPG, .TIF, .TIFF, or .BMP file) of each particular brand or type of product packages **135** contained in the system **100**. Thus, the graphical representations of each particular type of product package **135** may be displayed to the user of the system **100** via the POS terminal **170**, remote terminal **175**, or integral display (not shown) of the system **100**. In some aspects, the product library **152** may be updated to include data associated with new or additional product packages **135**. For instance, a new brand or type of product package **135** (e.g., cigarette package) may be inserted into a product bin **110** for sale. The sales price, SKU, brand name, or other information may be added to the product library **152** for the new brand or type via the POS terminal **170** or remote terminal **175**.

POS terminal **170** is communicably coupled to the controller **140** and, generally, may be any computing device that monitors or manages the controller **140** and the dispensing of product packages **135** from the system **100**. Generally, POS terminal **170** includes memory, as well as one or more processors, and comprises an electronic computing device operable to receive, transmit, process, store, or manage data associated with the system **100**. POS terminal **170** may also be communicably connected to the remote terminal **175** and a variety of other networks or services, such as, for example, a payment verification service provided by a credit or debit card company or financial institution. In some aspects, POS terminal **170** is located within the premises of a retail environment such as a retail convenience store, grocery store, or "big box" retailer. Regardless of the location, the POS terminal **170** typically provides a display through which the dispensing module **150** may present a graphical user interface (GUI) to a user of the system **100** in order to facilitate the dispensing of one or more product packages **135**. Further, the POS terminal **170** may provide a display and, in some aspects, an associated printing device, capable of displaying or printing one or more reports (e.g., sales data or inventory reports) generated by the dispensing module **150**. The POS terminal **170** may also provide an appropriate input device, such as, for example, a keyboard, keypad, mouse, or light pen, to facilitate the entry of dispensing information (e.g., a brand or type and a quantity of a product package **135**) into the POS terminal **170**. The dispensing information may thus be transmitted to the controller **140** via dispensing instruction **180**. In some aspects, the POS terminal **170** may include a touch screen display, which may allow one or more items of dispensing information to be input into the POS terminal **170**.

Remote terminal **175** may be, generally, any computing device that remotely monitors or manages the controller **140** and the dispensing of product packages **135** from the system **100**. This disclosure provides merely one example of computers that may be used with the disclosure. As used in this document, the term “computer” is intended to encompass any suitable processing device. For example, in some aspects, the remote terminal **175** may be located at a corporate headquarters of a retail enterprise utilizing the system **100**. Thus, sales data generated and/or stored by the dispensing module **150** may be accessed by the remote terminal **175**. Further, sales data or inventory reports generated by the dispensing module **150** may be access and/or viewed via the remote terminal **175**. Updated or additions to the product library **152** may also be transmitted to the controller **140** from the remote terminal **175**.

FIGS. 2A-C illustrate another implementation of a system **200** for dispensing consumer products including a cabinet **205**. Cabinet **205** includes a supply compartment **210**, a return compartment **220**, and one or more product bin units **230**. In some implementations, the system **200** may include an electronic data reader **260** communicably coupled to the system **200**. Further, each product bin unit **230** may include one or more product bins **235**; one or more ejector apertures **240**; one or more product ejectors **245**; one or more trigger apertures **275**; one or more product triggers **280**; and contain one or more product packages **250**. The foregoing components of the product bin unit **230**, in some aspects, may be substantially similar to these same components described with reference to FIGS. 1A-C. System **200** may also include a controller (not shown) communicably coupled to the product ejectors **245** and product triggers **280** and enclosed, at least in part, by the cabinet **205**. Generally, the system **200** provides a stand-alone product dispensing system that may be located in, for instance, a retail enterprise or food and beverage enterprise, for dispensing one or more product packages **250** (e.g., cigarette packages, smokeless tobacco packages, or medicinal packages).

Cabinet **205** may be a modular or unitized cabinet constructed of, for example, molded plastic, aluminum with a powder-coat finish, or stainless steel, to name but a few. With reference to FIG. 2A in particular, the cabinet **205** contains three modules including a product compartment **207**, the supply compartment **210**, and the return compartment **220**. In general, the product compartment **207** encloses at least a portion of one or more product bin units **230** and includes one or more doors **232** pivotally coupled to the compartment **207**. In some aspects, as shown in FIG. 2B, the product compartment **207** may includes doors **232** on opposed sides of the cabinet **205**. Thus, product bin units **230** may be enclosed back-to-back in the product compartment **207**, allowing product packages **250** to be dispensed to either side of the cabinet **205**. This may allow, in some aspects, a greater total number of product packages **250** to be enclosed within the cabinet **205**.

Supply compartment **210**, in some implementations, may be located below the product compartment **207** and includes one or more supply doors **215** pivotally coupled to the supply compartment **210**. Generally, the supply compartment **210** provides an enclosed space to contain one or more dispensed product packages **250**. For example, in some aspects, the product compartment **207** and supply compartment **210** may share a common volume of vertical space **237** between the doors **232** and product bin units **230**, which allows a particular product package **250** driven from a product bin **235** to fall within the cabinet **205** from the product compartment **207** to the supply compartment **210**.

In some aspects, as shown more particularly in FIG. 2C, the supply compartment **210** may also include a ramp **217** extending from a back side of the cabinet **205** to a front side (e.g., the side including the supply doors **215**) and across a width of the cabinet **205**. The ramp **217**, for example, may allow for product packages **250** dispensed from one or more product bin units **230** facing the back side of the cabinet **205** to slide to the front side of the cabinet. Thus, regardless of which product bin unit **230** a certain product package **250** is dispensed from and, more particularly, regardless of an orientation of the product bin units **230**, the user of the system **200** may have a single access location to retrieve the dispensed package **250** from the supply compartment **210**.

In some aspects, the supply compartment **210** may also enclose at least a portion of a controller, such as the controller **140** illustrated in FIGS. 1A-C. For example, the controller may be detachably mounted within the supply compartment **210** to a bottom side of the product compartment **207** and be communicably coupled to the product ejectors **245** and the product triggers **280**. Further, similar to controller **140**, the controller in system **200** may be communicably coupled to, for example, a POS terminal and/or a remote terminal.

The return compartment **220**, generally, may be located beneath the supply compartment **210** and may provide a substantially secure and enclosed space in which product packages **250** mistakenly dispensed may be stored. For example, in some aspects, the return compartment **220** may not share the vertical space **237** with the product compartment **207** and supply compartment **210**. In such aspects, the return compartment **220** may only be accessible through a return door **227**, which includes a lock **255**, and is pivotally coupled to the return compartment **220**. The return door **227** includes a return slot **225**, which allows a product package **250** to be placed into the return compartment **220** without unlocking or opening the return door **227**.

For instance, the user of the system **200** (e.g., a sales clerk) may accidentally dispense a certain product package **250** of an incorrect brand or type as requested by a customer. The user may not have access to the product compartment **207** for security reasons, so the mistakenly dispensed product package **250** may be inserted into the return slot **225** for storage. At a future time, for example, at the end of a work shift when a manager is present, any product package **250** in the return compartment **220** may be returned to the appropriate product bin **235** in the product compartment **207**.

In some aspects, the system **200** includes the electronic data reader **260**, which may be communicably coupled to the controller (not shown) of the system. Generally, the electronic data reader **260** may transmit information, such as a dispensing instruction, to the controller of the system **200** so that one or more product packages **250** may be dispensed. Such information may be based on electronic data, such as a brand or type and quantity of a particular product package **250**, stored on a product purchase ticket **265**. For instance, in some implementations, a customer may purchase one or more product packages **250** (e.g., cigarette packages) at a location remote from the cabinet **205**, such as a check out terminal in a grocery store. Once payment is made by the customer, a sales clerk may provide the customer with a product purchase ticket **265** indicating the particular item purchased, as well as its quantity. The customer may then take the ticket **265** to the system **200** and insert the ticket **265** into the electronic data reader **260**. In some aspects, the customer may enter a code printed on the ticket **265** into the electronic data reader **260**. The code may specify the brand or type and quantity of a particular product package **250**. Once the correct product package or packages **250** are dispensed to the supply compartment **210**,

the customer may retrieve the purchased product via the supply door 215. In various implementations, the electronic data reader 260 may be a magnetic ink character recognition (MICR) character reader and data is printed on the product purchase ticket 265 with magnetic ink or toner.

FIG. 3 illustrates one example of a graphical user interface (GUI) 300, which may be generated by a dispensing module in a system for dispensing consumer products. Graphical user interface 300, for example, may be utilized by the dispensing module 150 in system 100 illustrated in FIGS. 1A-C. Further, GUI 300 may be presented to a user on, for example, a POS terminal or a remote terminal, such as the POS terminal 170 or remote terminal 175, as well as a display monitor integral to the system. As shown in FIG. 3, GUI 300 may present a graphical list of product packages 305, such as graphical representations of cigarette packages. Once a particular brand is chosen, for example Brand "X" as shown in FIG. 3, an additional selection window 310 is presented to the user by the dispensing module. Also, the selected product package 305, in some implementations, may be grayed out once selected. As illustrated, the selection window 310 may display a graphical representation of the selected product package 305, as well as a quantity selection box in which a particular numeric value may be entered. The selection window 310, in some aspects, may provide the user with the unit price of the selected product package 305 and a total sale price of one or more selected product packages 305.

FIG. 4 is a flowchart illustrating an example method 400 for dispensing consumer products. Method 400 may be implemented by a system for dispensing consumer products, such as for example, system 100 including a product bin unit including one or more product bins, product ejectors, and product triggers; a controller including a dispensing module; a POS terminal; and a remote terminal. Further, method 400 may be implemented by system 200 illustrated in FIGS. 2A-C. For instance, the dispensing module presents a graphical user interface (GUI) to a user [402]. In some aspects, the GUI may be displayed to the user at the POS terminal, as well as the remote terminal. The dispensing module receives a dispensing instruction from the user [404]. The dispensing instruction, for example, may consist of a type of a product, such as a package of cigarettes, to be purchased, as well as a quantity of the product to be purchased. The dispensing module compares the product type in the dispensing instruction to a corresponding product type in a product library [406]. The product library may be stored in, for example, the controller, the POS terminal, or the remote terminal, and stores such information as product price. The dispensing module then compares the product quantity in the dispensing instruction to a product inventory of the selected product type [408]. The product inventory may also be stored in the controller, the POS terminal, or remote terminal, and may be continually updated (e.g., reduced or increased) as product is added and sold to and from the system. If the product quantity requested in the dispensing instruction is greater than the existing product inventory in the system [410], then the dispensing module may present an insufficient quantity message to the user [412] and present the GUI to the user [402].

If the product quantity requested in the dispensing instruction is less than or equal to the existing product inventory in the system, a product selection based on the product type and product quantity is determined by the dispensing module [414]. The dispensing module then generates a dispensing signal based on the product selection [416], i.e., based on the requested product type and product quantity. The dispensing signal is transmitted from the dispensing module via the controller to one or more product ejectors [418], thus electri-

cally actuating the product ejectors to drive the requested product from the appropriate product bins. The dispensing module then receives a confirmation signal from each product trigger coupled to the product bins from which the requested product was dispensed [420]. The confirmation signal or signals, for example, may indicate to the dispensing module that a particular inventory value of product packages (e.g., cigarette packages) within a product bin should be decreased by the product quantity dispensed from the product bin.

According to method 400, the dispensing module may also receive a request for a sales data point from the user [422]. If no request is received, the dispensing module presents the GUI to the user [402]. If a request for a sales data point is received, however, the dispensing module presents an authorization code request to the user [424]. For example, an administrator of the system may require password access to protect any financial or proprietary information stored and/or managed by the dispensing module. The dispensing module receives an authorization code from the user [426] and compares the received code to a valid code. The valid code may be a preset alphanumeric code input into the dispensing module by, for example, the administrator of the system. If the received authorization code does not match at least one valid code [428], the dispensing module may present another authorization code request to the user [424]. In some aspects, the administrator may limit the number of attempts to access the sales data point to a finite number before locking the user out of the system.

If, however, the authorization code received by the dispensing module matches the valid code, the dispensing module presents a sales data interface to the user [430]. The sales data interface may, for example, allow the user to input various criteria, which may constrain the sales data point. More specifically, the user may request via the sales data interface the sales data point of a particular product type or brand, or even multiple types or brands, within a defined time period. Further, the user may request the sales data point of product packages contained in one or more particular product bins in the system. The time period may, for instance, be a daily, weekly, monthly, or yearly time period, or even a daily fraction, such as a 12-hour work shift. The dispensing module thus receives the sales data request criteria from the user [432]. Based on the received sales data request, the dispensing module generates a report of sales data [434]. The report is then presented to the user through the graphical interface [436].

According to the method 400, the dispensing module may also receive an input of an additional quantity of product packages into the system [438]. For example, in some aspects, the dispensing module may provide an indication to the user when a predetermined minimum number of product packages of a particular type or brand remains in one or more product bins. Once such an indication is given, the user may supply the product bins with additional product packages (e.g., cigarette packages) and input in the additional quantity into the dispensing module via the POS terminal, remote terminal, or other appropriate device. The dispensing module then calculates a new product inventory based on the additional quantity of product packages and existing quantity of product packages in the product bins [440]. The dispensing module then presents the new product inventory to the user through the graphical interface [442].

Although FIG. 4 illustrates one method for dispensing consumer product packages, such as cigarette packages, other consumer product dispensing methods including a dispensing module may include fewer and/or a different arrangement of operations. For example, the dispensing module of method

13

400 may also keep track of a specific number of product packages remaining in each product bin as the product packages are dispensed from the system. Moreover, some operations in method **400** may be done in parallel to other operations.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made. Accordingly, other implementations are within the scope of the following claims.

What is claimed is:

1. A system for dispensing consumer products, comprising:

a product dispensing apparatus that comprises a housing that at least partially encloses:

a product bin unit comprising:

a product bin adapted to hold at least one product package;

an ejector aperture; and

a trigger aperture;

a product ejector coupled to the product bin unit through the ejector aperture and adapted to drive the product package from the product bin upon receipt of a dispensing signal, wherein the product ejector comprises an electrically actuated piston-cylinder comprising: an electromagnet adapted to drive at least a portion of the piston to extend from the cylinder through the ejector aperture to be in contact with the product package upon energizing, and a spring adapted to drive the portion of the piston into the cylinder upon de-energizing of the electromagnet;

a product trigger coupled to the product bin unit through the trigger aperture; and

a controller in communication with the product ejector and the product trigger through one or more electrical connections, the controller comprising:

at least one memory, the memory storing a dispensing module and at least a portion of confidential data describing financial or proprietary information related to the consumer products; and

one or more processors adapted to execute the dispensing module, the dispensing module operable when executed to:

present an authorization code request to a user that comprises a sales administrator or a sales associate of the product dispensing apparatus and is associated with management or sale of the consumer products enclosed in the product dispensing apparatus;

receive an authorization code from the user, the authorization code comprising a password operable to secure the confidential data, wherein the password comprises an administrator's password facilitating administrator-level access to the portion of confidential data;

confirm the password as a valid code;

receive a dispensing instruction from the user;

transmit the dispensing signal to the product ejector based at least in part on the dispensing instruction and confirmation of the password as the valid code, such that the product ejector is electrically actuated to directly drive the product package from the product bin unit upon receipt of the dispensing signal;

receive, from the product trigger, a particular confirmation signal confirming that the product package has been driven from the product bin unit;

14

receive a request from the user for at least one sales data point associated with a value of sales of the product package in a specified time period, wherein the portion of confidential data describes financial or proprietary information related to the sales data point;

generate a report comprising the sales data point; and

save the report for subsequent presentation to the user.

2. The system of claim 1, wherein the product bin unit further comprises:

a substantially vertical back plate comprising the ejector aperture;

a substantially horizontal bottom plate coupled to the back plate, the bottom plate comprising the trigger aperture;

a first vertical side plate and a second vertical side plate coupled to at least one of the back plate and the bottom plate; and

a first substantially vertical divider plate coupled to at least one of the back plate and the bottom plate, the first divider plate arranged between the first and second side plates, at least a portion of the back plate, the bottom plate, the divider plate, and one of the first or second side plates defining the product bin.

3. The system of claim 1, wherein the product package comprises one of:

a tobacco product;

a medicinal product; or

a shaving product.

4. The system of claim 1, wherein the product package comprises a tobacco product comprising one of a cigarette package or a smokeless tobacco package.

5. The system of claim 1, wherein the product package comprises a medicinal product comprising one of a pain reliever package or a cough syrup package.

6. The system of claim 1, wherein the product trigger comprises a sensor adapted to transmit a confirmation signal to the controller upon actuation of the piston-cylinder.

7. The system of claim 1, wherein the product bin unit comprises a first product bin unit, the system further comprising a second product bin unit and a cabinet adapted to enclose at least a portion of the first product bin unit, the second product bin unit, and the controller, the cabinet comprising:

a supply compartment comprising a door pivotally coupled to the cabinet; and

a return compartment comprising a return opening.

8. The system of claim 7, wherein the first product bin unit comprises a first product bin open in a first direction and the second product bin unit comprises a second product bin open in a second direction that is approximately 180 degrees from the first direction, wherein product dispensed from the first product bin and product dispensed from the second product bin is received into the supply compartment and removable from the supply compartment through the door facing the first direction.

9. The system of claim 8, wherein the first product bin is adapted to hold a first size product package and the second product bin is adapted to hold a second size product package, the first size product package larger than the second size product package.

10. The system of claim 7, wherein the cabinet comprises a substantially opaque cabinet enclosing at least a portion of the first product bin unit, the second product bin unit, and the controller.

11. The system of claim 1, wherein the system further comprises an electronic data reader coupled to the controller

15

and adapted to transmit the dispensing instruction to the controller at least partially based on data stored on a product purchase ticket.

12. The system of claim 11, wherein the electronic data reader comprises a magnetic ink character recognition (MICR) reader, the product purchase ticket comprising a MICR code, the MICR code comprising at least one of:

- a representation of a product package quantity; and
- a representation of a product package type.

13. The system of claim 1, wherein the product bin is adapted to receive the product package from a front of the product bin.

14. The system of claim 1, wherein the dispensing module is further operable to:

- present a graphical user interface (GUI) to a user;
- receive the dispensing instruction from the user through the GUI, the dispensing instruction comprising a product type and a product quantity;
- compare the product type to a product library stored in the memory;
- compare the product quantity to a product inventory of the product type stored in the memory;
- determine a product selection based on the product type and the product quantity;
- generate the dispensing signal based on the product selection; and
- transmit the dispensing signal to the product ejector.

15. The system of claim 1, wherein the sales data point comprises one of:

- a value of sales in the specified time period based on the product type;
- a value of sales in the specified time period based on the product bin, the product bin comprising at least one product package of the same product type; and
- a value of sales in the specified time period based on a time shift period, the time shift period comprising at least a portion of a 24 hour period.

16. The system of claim 15, wherein the dispensing module is further operable to:

- present a sales data request to the user; and
- receive the sales data request from the user, the request comprising the specified time period and one of:
 - the product type;
 - the product bin; or
 - the time shift period.

17. The system of claim 14, wherein the dispensing module is further operable to:

- receive an update to the product library stored in the memory;
- receive a remote request from a remote user for the sales data point; and
- transmit the sales data point to the remote user.

18. The system of claim 14, wherein the dispensing module is further operable to:

- receive a second quantity of product packages of the product type input from the user;
- calculate a new product inventory of the product type, the new product inventory equal to a sum of the product inventory and the second quantity; and
- present the new product inventory of the product type to the user.

19. A method for dispensing consumer product, comprising:

- presenting an authorization code request to a user that comprises a sales administrator or a sales associate of a product dispensing apparatus and is associated with

16

management or sale of consumer products enclosed in the product dispensing apparatus;

receiving an authorization code from the user, the authorization code comprising a password operable to secure at least a portion of confidential data describing financial or proprietary information related to the consumer products, wherein the password comprises an administrator's password facilitating administrator-level access to the portion of confidential data, and the portion of confidential data describing financial or proprietary information related to at least one sales data point associated with a value of sales of a product package in a specific time period;

confirming the password as a valid code;

based at least in part on the confirmation of the password, presenting a graphical interface to the user;

receiving a product type and a product quantity from the user through the graphical interface;

comparing the product type to a product library stored in a memory;

comparing the product quantity to a product inventory of the product type stored in the memory;

determining a product selection based on the product type and the product quantity;

generating a dispensing signal based on the product selection;

transmitting the dispensing signal to a product ejector; electrically actuating the product ejector to directly drive a first quantity of a product package from a product bin, the first quantity equal to the product quantity, wherein the product bin and the product ejector are enclosed in the product dispensing apparatus, and electrically actuating the product ejector comprises electrically actuating a piston-cylinder by an electromagnet to drive at least a portion of the piston to extend from the cylinder through an ejector aperture to be in contact with the product package upon energizing and by a spring to drive the portion of the piston into the cylinder upon de-energizing of the electromagnet;

receiving, from a product trigger enclosed in the product dispensing apparatus, a particular confirmation signal confirming that the first quantity of the product package has been driven from the product bin;

receiving a request from the user for the sales data point; generating a report comprising the sales data point; and saving the report for subsequent presentation to the user.

20. The method of claim 19, wherein the sales data point comprises one of:

- a value of sales in the specified time period based on the product type;
- a value of sales in the specified time period based on a product bin, the product bin comprising at least one product package of the same product type; and
- a value of sales in the specified time period based on a time shift period, the time shift period comprising at least a portion of a 24 hour period.

21. The method of claim 20, wherein receiving a request from the user for the sales data point comprises:

- based at least in part on the confirmation of the password, presenting a sales data request to the user; and
- receiving the sales data request from the user, the request comprising the specified time period and one of:
 - the product type;
 - the product bin; or
 - the time shift period.

22. The method of claim 19, wherein the method further comprises:

17

receiving an update to the product library stored in the memory;
 receiving a remote request from a remote user for the sales data point; and
 transmitting the sales data point to the remote user.

23. The method of claim 19, wherein the method further comprises:

receiving a second quantity of product packages of the product type;

calculating a new product inventory of the product type, the new product inventory approximately equal to a sum of the product inventory and the second quantity; and

decreasing the new product inventory by the product quantity upon driving the first quantity of the product package from the product bin by the product ejector.

24. The method of claim 19, wherein receiving a product type and a product quantity from the user through a graphical user interface comprises receiving a product type and a product quantity from the user via a MICR code on a product purchase ticket.

18

25. The method of claim 19, wherein the product bin comprises a first product bin, the method further comprising:

dispensing the first quantity of the product package from the first product bin open in a first direction into a supply compartment;

dispensing a second quantity of the product package from a second product bin open in a second direction into the supply compartment, the second direction approximately 180 degrees opposed to the first direction,

wherein the supply compartment comprises a door open in the first direction configured to allow removal of the first and second quantities of the product package.

26. The method of claim 19, wherein receiving a particular confirmation signal comprises receiving the particular confirmation signal transmitted from a sensor in the product trigger upon electrically actuating the piston-cylinder.

* * * * *