



US 20020071248A1

(19) **United States**

(12) **Patent Application Publication**
Huang et al.

(10) **Pub. No.: US 2002/0071248 A1**

(43) **Pub. Date: Jun. 13, 2002**

(54) **LOCKING DEVICE**

Publication Classification

(75) Inventors: **Chin Chu Huang**, Taoyuan Shien
(TW); **Chen Yu Yu**, Taoyuan Shien
(TW)

(51) **Int. Cl.⁷** G06F 1/16

(52) **U.S. Cl.** 361/685

Correspondence Address:

VOLPE AND KOENIG, P.C.
SUITE 400, ONE PENN CENTER
1617 JOHN F. KENNEDY BOULEVARD
PHILADELPHIA, PA 19103 (US)

(57) **ABSTRACT**

(73) Assignee: **Delta Electronics Inc.**, Taoyuan Shien
(TW)


A locking device adapted to secure a retractable storing device in a frame of an electrical apparatus is provided. The locking device includes a main body, an activating element assembled with the main body and having an activating button and a first engaging member thereon, and a handle pivotally connected to the main body and having a second engaging member for engaging with the first engaging member when the retractable storing device is secured in the frame, wherein the activating button, being invisibly disposed in a concavity of the main body, is used for disengaging the second engaging member from the first engaging member when the retractable storing device is retracted from the frame.

(21) Appl. No.: **09/957,759**

(22) Filed: **Sep. 21, 2001**

(30) **Foreign Application Priority Data**

Dec. 12, 2000 (TW)..... 89221539






Fig. 1(PRIOR ART)




Fig. 2(PRIOR ART)




Fig. 3




Fig. 4

LOCKING DEVICE

FIELD OF THE INVENTION

[0001] The present invention is related to a locking device, and more particularly to a locking device adapted to secure a retractable storing device in a frame of an electrical apparatus.

BACKGROUND OF THE INVENTION

[0002] A storing device, e.g. a disk array system, applied in an electrical apparatus, e.g. a personal computer, generally possesses a function of hot swap. That is, during the running process of the personal computer, the personal computer doesn't need to be shut down if the user of the personal computer would like to replace the disk array system, e.g. a hard disk or a CDROM, with another one for some purposes. What the user merely have to do is to retract the disk array system through a locking device assembled therewith. Conventionally, the disk array system combined with a locking device is disposed in a frame of the personal computer for securing which with the personal computer.

[0003] Please refer to **FIG. 1** which is a schematic diagram illustrating a structure of a disk array system **11** combined with a conventional locking device **10** disposed in a frame **12** of a personal computer. The conventional locking device **10** includes a rotatable handle **101** and a key hole **102**. The disk array system **11** is secured in the frame **12** of a personal computer (not shown). To replace the disk array system **11** during the running process of the personal computer with another one, the user have to insert the key into the key hole **102** first to unlock the disk array system **11**. Thereafter, the disk array system **11** is retracted from the frame **12** by pulling the rotatable handle **101** out. Finally, another disk array system is then pushed into the frame **12** and secured therein by inserting the key into the key hole **102** to lock the disk array system **11**. However, the structure of the locking device **10** is very complicated. Particularly, if one of the elements for locking the disk array system **11** in the frame **12** malfunctions, a big trouble would be made. In addition, by forming a key hole **102** for locking the disk array system **11** in the frame **12**, the manufacturing cost is raised.

[0004] Please refer to **FIG. 2** which is a schematic diagram illustrating a structure of a disk array system **11** combined with another conventional locking device **13** disposed in a frame **12** of a personal computer. The conventional locking device **13** includes a rotatable handle **131** and a locking element **132**. The disk array system **11** is secured in the frame **12** of a personal computer (not shown). To replace the disk array system **11** during the running process of the personal computer with another one, the user have to push a locking member **1321** of the locking element **132** toward right first to unlock the disk array system **11**. Thereafter, the disk array system **11** is retracted from the frame **12** by pulling the rotatable handle **131** out. Finally, another disk array system is then pushed into the frame **12** and secured therein by pushing the locking member **1321** of the locking element **132** toward left to lock the disk array system **11**. Although the structure of the locking device **13** is not so complicated as that of **FIG. 1**, it is very easy for an infant or a child to arbitrarily retract the disk array system **11** by merely pushing the locking member **1321** of the locking

element **132**. Predictably, arbitrary locking/unlocking of the disk array system would result in easy damage of the locking device **13**.

[0005] Accordingly, it is attempted by the present invention to overcome the drawbacks encountered in the prior arts.

SUMMARY OF THE INVENTION

[0006] An object of the present invention is to provide a locking device of simple structure adapted to secure a retractable storing device in a frame of an electrical apparatus.

[0007] Another object of the present invention is to provide a locking device adapted to secure a retractable storing device in a frame of an electrical apparatus for preventing from arbitrary locking/unlocking of the storing device.

[0008] According to the present invention, a locking device adapted to secure a retractable storing device in a frame of an electrical apparatus is disclosed. The locking device includes a main body, an activating element assembled with the main body and having an activating button and a first engaging member thereon, and a handle pivotally connected to the main body and having a second engaging member for engaging with the first engaging member when the retractable storing device is secured in the frame, wherein the activating button, being invisibly disposed in a concavity of the main body, is used for disengaging the second engaging member from the first engaging member when the retractable storing device is retracted from the frame.

[0009] Preferably, the storing device is a disk array system of a personal computer.

[0010] Preferably, the disk array system is a hard disk.

[0011] Preferably, the disk array system is a CDROM.

[0012] Preferably, the main body is made of plastic.

[0013] Preferably, the main body is formed by injection molding.

[0014] Preferably, the activating element is made of plastic.

[0015] Preferably, the activating element is formed by injection molding.

[0016] Preferably, the handle is made of plastic.

[0017] Preferably, the handle is formed by injection molding.

BRIEF DESCRIPTION OF THE DRAWING

[0018] The present invention may best be understood through the following description with reference to the accompanying drawings, in which:

[0019] **FIG. 1** is a schematic diagram illustrating a structure of a disk array system combined with a conventional locking device disposed in a frame of a personal computer;

[0020] **FIG. 2** is a schematic diagram illustrating a structure of a disk array system combined with another conventional locking device disposed in a frame of a personal computer;

[0021] FIG. 3 is a schematic diagram illustrating a structure of a disk array system combined with a locking device disposed in a frame of a personal computer according to the present invention; and

[0022] FIG. 4 is a schematic diagram illustrating a rear view of a locking device according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0023] The present invention will now be described more specifically with reference to the following embodiments. It is to be noted that the following descriptions of preferred embodiments of this invention are presented herein for purpose of illustration and description only; it is not intended to be exhaustive or to be limited to the precise form disclosed.

[0024] Herein, the present invention is illustrated by respectively using a disk array system and a personal computer as a storing device and an electrical apparatus. Please refer to FIGS. 3 and 4 which are schematic diagrams respectively illustrating a structure of a disk array system 31 combined with a locking device 30 disposed in a frame 32 of a personal computer, and a rear view of the locking device 30 according to the present invention. The locking device 30 is used for securing the disk array system 31 in the frame 32 of a personal computer (not shown). The locking device 30 includes a main body 301, an activating element 302 assembled with the main body 301 and having an activating button 3021 and a first engaging member 3022 thereon, and a handle 303 pivotally connected to the main body 301 and having a second engaging member 3031 for engaging with the first engaging member 3022 when the retractable disk array system 31 is secured in the frame 32. The activating button 3021 is used for disengaging the second engaging member 3031 from the first engaging member 3022 when the retractable disk array system 31 is retracted from the frame 32. For preventing an infant or a child from arbitrarily locking/unlocking the disk array system 31, the activating button 3021 is disposed in an invisible concavity 3012 of the main body 301. To assemble the activating element 302 with the main body 301, the first assembling member 3023 of the activating element 302 is engaged with the second assembling member 3011 of the main body 301 as shown in FIG. 4.

[0025] To replace the disk array system 31 during the running process of the personal computer with another one, the user just need to poke his finger into the invisible concavity 3012 of the main body 301 to press the activating button 3021 first. In the meantime, the second engaging member 3031 will be disengaged from the first engaging member 3022, i.e. the disk array system 31 is unlocked. Thereafter, the disk array system 31 is retracted from the frame 32 by pulling the handle 303 out. Then, another disk array system can be pushed into the frame 32 and secured therein by engaging the second engaging member 3031 with the first engaging member 3022, i.e. locking the disk array system 31.

[0026] Preferably, the main body, the activating element and the handle of the locking device is made of plastic. Certainly, the main body, the activating element and the handle of the locking device can be formed by injection molding.

[0027] According to the present invention, the structure of the locking device 30 is simple. In addition, the activating button 3021 is disposed in an invisible concavity 3012 of the main body 301 such that it's not easy for an infant or a child to arbitrarily press the activating button 3021 and therefore disengaging the second engaging member 3031 from the first engaging member 3022, i.e. unlocking the disk array system 31. Accordingly, the drawbacks encountered in the prior arts are solved.

[0028] While the invention has been described in terms of what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention need not be limited to the disclosed embodiment. On the contrary, it is intended to cover various modifications and similar arrangements included within the spirit and scope of the appended claims which are to be accorded with the broadest interpretation so as to encompass all such modifications and similar structures. Therefore, the above description and illustration should not be taken as limiting the scope of the present invention which is defined by the appended claims.

What is claimed is

1. A locking device adapted to secure a retractable storing device in a frame of an electrical apparatus, comprising:

a main body

an activating element assembled with said main body and having an activating button and a first engaging member thereon; and

a handle pivotally connected to said main body and having a second engaging member for engaging with said first engaging member when said retractable storing device is secured in said frame,

wherein said activating button, being invisibly disposed in a concavity of said main body, is used for disengaging said second engaging member from said first engaging member when said retractable storing device is retracted from said frame.

2. The locking device according to claim 1 wherein said storing device is a disk array system of a personal computer.

3. The locking device according to claim 2 wherein said disk array system is a hard disk.

4. The locking device according to claim 2 wherein said disk array system is a CDROM.

5. The locking device according to claim 1 wherein said main body is made of plastic.

6. The locking device according to claim 5 wherein said main body is formed by injection molding.

7. The locking device according to claim 1 wherein said activating element is made of plastic.

8. The locking device according to claim 7 wherein said activating element is formed by injection molding.

9. The locking device according to claim 1 wherein said handle is made of plastic.

10. The locking device according to claim 9 wherein said handle is formed by injection molding.

* * * * *