



US 20040051003A1

(19) **United States**

(12) **Patent Application Publication**  
**Cheung**

(10) **Pub. No.: US 2004/0051003 A1**

(43) **Pub. Date: Mar. 18, 2004**

(54) **ECONOMY AIRCRAFT SLEEPER SEAT**

(52) **U.S. Cl. .... 244/118.6**

(76) **Inventor: Kwun-Wing W. Cheung, Shoreline, WA (US)**

(57) **ABSTRACT**

Correspondence Address:  
**Thomas E. Donohue**  
**Artz & Artz, P.C.**  
**Suite 250**  
**28333 Telegraph Road**  
**Southfield, MI 48034 (US)**


(21) **Appl. No.: 10/245,235**

(22) **Filed: Sep. 17, 2002**

**Publication Classification**

(51) **Int. Cl.<sup>7</sup> ..... B64D 11/06; B64D 13/00**

An aircraft seat assembly **10** is provided including a plurality of aircraft seat elements **12**. The aircraft seat assembly **10** includes a first aircraft seat element **18**, having a first seat portion **16** and a first back portion **18**. The first back portion **18** includes a lower back portion **22** and an upper back portion **24**. The lower back portion **22** is rotatable between a raised position **26**, wherein the lower back portion **22** is tangential with the upper back portion **24** to form a contiguous back rest **29**, and a lowered position **28**, wherein the lower back portion **22** is tangential with the first seat portion **16** to form an extended horizontal sleeping platform **32**.






FIG. 1




FIG. 2

## ECONOMY AIRCRAFT SLEEPER SEAT

### TECHNICAL FIELD

[0001] The present invention relates generally to an aircraft sleeper seat, and more particularly to an aircraft sleeper seat that is alternately operational as a standard aircraft seat.

### BACKGROUND OF THE INVENTION

[0002] Aircraft interiors have often been influenced as much by economic factors as they have been by engineering concerns. Weight savings for individual components affect not only aircraft performance but profitability as well. In this light, considerable effort has been expended in attempts to limit aircraft weight and improve efficiency. Working in conjunction with weight and efficiency, passenger occupancy has also played a significant role in aircraft economic factors. Increased passenger occupancy capacities have been one approach toward increasing airline economic efficiency.

[0003] Increased passenger occupancy allows airlines to sell a greater number of individual tickets for a given flight. Profits are thereby increased, while the increase in flight overhead related to the additional passengers is only minimally impacted. Unfortunately, the increase in passenger occupancy has resulted in restrictive seating arrangements as perceived by many passengers. As the number of passengers and passenger seating has been increased within aircraft, the amount of individual space allocated to each passenger has been respectively diminished. Comfort adjustments such as seat reclining are often extremely limited and often ineffectual. Luxuries such as sleeper seating has been all-but extinguished from coach seating. Cost concerns have thereby directly impacted passenger comfort and convenience.

[0004] Although in many cases the impact on passenger comfort has been viewed as an acceptable cost of operation, the loss of customer satisfaction and the increase of passenger irritability and discomfort should not be ignored. Air travel can be inherently stressful many passengers. Often larger passengers find the reduced personal space on modern aircraft to further increase their stress and discomfort levels. On many flights, multiple seats are often not filled and remain empty. These unsold seats represent a loss of valuable space that could be utilized to increase customer comfort. In addition, these unsold seats represent lost revenue for the airline. It would represent a real value to the airlines if revenue could be derived from these unused seats. If such increased revenue could be combined with increased customer satisfaction and comfort, the airline could benefit doubly. It would therefore be highly desirable to have an airline seat that could function both as a traditional seat as well as a sleeper seat when used in conjunction with a neighboring seat. This would allow for additional comfort and possible revenue if the use of the sleeper seat could be marketed to passengers at an additional cost.

### SUMMARY OF THE INVENTION

[0005] It is, therefore, an object of the present invention to provide an aircraft seat capable of providing traditional passenger seating in addition to alternately providing sleeper seating to adjoining passengers when not in use. It is a further object of the present invention to provide an aircraft seat that can provide potential revenue for airlines when not

sold as a traditional seat by providing marketable value as an upgrade to adjoining passengers.

[0006] In accordance with the objects of the present invention, an aircraft seat assembly is provided. The aircraft seat assembly includes a first aircraft seat element, having a first seat portion and a first back portion. The first back portion includes a lower back portion and an upper back portion. The lower back portion is rotatable between a raised position, wherein the lower back portion is tangential with the upper back portion to form a contiguous back rest, and a lowered position, wherein the lower back portion is tangential with the first seat portion to form an extended horizontal sleeping platform.

[0007] Other objects and features of the present invention will become apparent when viewed in light of the detailed description of the preferred embodiment when taken in conjunction with the attached drawings and appended claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] **FIG. 1** is an illustration of an embodiment of an aircraft seat assembly in accordance with the present invention, the aircraft seat assembly illustrated in the primary seating configuration; and

[0009] **FIG. 2** is an illustration of the aircraft seat assembly illustrated in **FIG. 1**, the aircraft seat assembly illustrated in the optional sleeper configuration.

### DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

[0010] Referring now to **FIG. 1**, which is an illustration of an aircraft seat assembly **10** in accordance with the present invention. The aircraft seat assembly **10** includes a plurality of aircraft seat elements **12**, each including a seat portion **14** and a back portion **16**. It is contemplated that the aircraft seat assembly **10** maybe constructed with any number of aircraft seat elements **12** to suit a variety of layouts applicable to individual aircraft or airline designs. A first aircraft seating element **18** and a second aircraft seating element **20** are shown in **FIG. 1** for illustrative purposes. It is further contemplated that the present invention is intended for use in combination with a wide variety of different size and shape aircraft seat elements.

[0011] The present invention further includes a back portion **16** comprised of a lower back portion **22** and an upper back portion **24**. The lower back portion **22** is rotatably movable between a raised position **26** and a lowered position **28** (see **FIG. 2**). In the raised position **26**, the lower back portion **22** is positioned in a tangential arrangement with the upper back portion **24** to form a contiguous back rest **28**. When in this arrangement, the contiguous back rest **29** preferably functions as any normal airline seat thereby allowing the aircraft seat assembly **10** to be marketed, sold, and utilized in a traditional fashion. It is contemplated that the contiguous back rest **29** can include any or all of the operations associated with traditional airline seating including, but not limited to, reclining functions and tray table **30** storage/mounting.

[0012] The present invention, however, adds improved value and function to the aircraft seat assembly **10** by having the lower back portion **22** rotatably movable to the lowered

position **28**. In the lowered position **28**, the lower back portion **22** is positioned in a tangential arrangement with the seat portion **14** to form an extended horizontal sleeping platform **32**. Although a single aircraft seat element **12** may utilize the present invention with some benefit, the placement of aircraft seats within most economy seating on aircraft can make such an individual use unpractical. It is therefore contemplated that the present invention can include a second aircraft seating element **20** positioned behind the first aircraft seating element **18**. The second aircraft seating element **20** includes a second seating back portion **34** and a second seating seat portion **36**. The lower back portion **22** is proportioned such that when it is in the lowered position **28** it is close proximity to, and tangentially orientated to, the second seating seat portion **36**. In some embodiments, however, it is contemplated that an exit gap **38** may be located between the lower back portion **22** in the lowered position **28** and the second seat portion **36** to provide sufficient exit passage during emergencies. The use of the second seating seat portion **36** in either event allows the extended horizontal sleeping platform **32** to be increased in length and further improve its usefulness.

[0013] Although it is contemplated that the present invention may be utilized in a variety of fashions, one embodiment contemplates that the extended horizontal sleeping platform **32** be made available to a passenger **38** seated within the second aircraft seating element **20** when the first aircraft seating element **18** is unoccupied. In one concept, every aircraft seat element may include the aforementioned features. Other conceptions limit the placement of such improve aircraft seating assemblies **10** to use within outer seating of the aircraft to reduce passenger traffic concerns. Furthermore, it is contemplated that although these features may be made generally available to improve customer satisfaction, sales and placement of passengers within the aircraft compartment can be controlled such that the availability of use of the extended horizontal sleeping platform **32** may be marketed and sold as an upgrade to passengers **38** and thereby increase revenue for the airlines by deriving revenue from unsold seats.

[0014] In light of the last conceived usage, it is further contemplated that the back portion **16** may further include a locking element **40** securing the lower back portion **22** into the raised position **26**. This locking element **40** can provide a dual purpose. It can be utilized to secure the lower back portion **22** to prevent unintended rotation into the lowered position **28**. Additionally, however, it can be used to prevent unauthorized movement of the lower back portion **22** as well. In this scenario, an airline attendant may be required to unlock the locking element **40** in response to either a fee paid to the attendant during flight or in response to a pre-paid upgrade purchased prior to departure. Although a simple locking mechanism has been illustrated, a wide variety of securing mechanisms are contemplated by the present invention.

[0015] While particular embodiments of the invention have been shown and described, numerous variations and alternative embodiments will occur to those skilled in the art. Accordingly, it is intended that the invention be limited only in terms of the appended claims.

What is claimed is:

1. An aircraft seating assembly comprising:
  - a first aircraft seat element including a first seat portion and a first back portion;
  - a fixed upper back portion and a rotatable lower back portion forming said first back portion, said lower back portion rotatably movable between a raised position tangential with said upper back portion and a lowered position tangential with said seat portion; and
  - an extended horizontal sleeping platform comprising said first aircraft seat element and said lower back portion rotated into said lowered position.
2. An aircraft seating assembly as described in claim 1 further comprising:
  - a tray table mounted to said upper back portion.
3. An aircraft seating assembly as described in claim 1, further comprising:
  - a locking element capable of securing said lower back portion in said raised position.
4. An aircraft seating assembly as described in claim 1, further comprising:
  - a locking element securing said lower back portion in said raised position, said locking element only unlockable by airline personnel.
5. An aircraft seating assembly as described in claim 1, further comprising:
  - a second aircraft seating element positioned rearward of said first aircraft seating element, said second aircraft seating element including a second seat portion and a second back portion, said second seat portion positioned tangential with said lower back portion when said lower back portion is in said lowered position.
6. An aircraft seating assembly as described in claim 5, further comprising:
  - an exit gap positioned between said second seat portion and said lower back portion when said lower back portion is in said lowered position.
7. An aircraft seating assembly as described in claim 1, wherein said first seating element is positioned within an outer seating of an aircraft.
8. An aircraft seating assembly comprising:
  - a first aircraft seat element including a first seat portion and a first back portion;
  - a fixed upper back portion and a rotatable lower back portion forming said first back portion, said lower back portion rotatably movable between a raised position tangential with said upper back portion and a lowered position tangential with said seat portion;
  - a second aircraft seating element positioned rearward of said first aircraft seating element, said second aircraft seating element including a second seat portion and a second back portion;
  - an extended horizontal sleeping platform comprising said first aircraft seat element, said second seat portion, and said lower back portion rotated into said lowered position.
9. An aircraft seating assembly as described in claim 8 further comprising:
  - a tray table mounted to said upper back portion.

**10.** An aircraft seating assembly as described in claim 8, further comprising:

a locking element capable of securing said lower back portion in said raised position.

**11.** An aircraft seating assembly as described in claim 8, further comprising:

a locking element securing said lower back portion in said raised position, said locking element only unlockable by airline personnel.

**12.** An aircraft seating assembly as described in claim 8, further comprising:

an exit gap positioned between said second seat portion and said lower back portion when said lower back portion is in said lowered position.

**13.** A method of utilizing unoccupied aircraft seating comprising:

folding down a lower back portion of a first aircraft seating element until said lower back portion is tangential with a first seat portion;

utilizing said first seat portion, said lower back portion and a second seat portion, positioned rearward of said lower back portion, as an extended horizontal sleeping surface.

**14.** A method as described in claim 13, further comprising:

selling said extending sleeping surface to a passenger seated in a second seating element positioned rearward of said first aircraft seating element.

**15.** A method as described in claim 13, further comprising:

locking said lower back portion in a raised position tangential with an upper back portion to create a contiguous back rest when said first aircraft seating element is occupied.

**16.** A method as described in claim 14, wherein said extending sleeping surface is sold to said passenger by an airline attendant during flight.

**17.** A method as described in claim 14, wherein said extending sleeping surface is sold to said passenger as an upgrade option during airline ticket purchasing.

**18.** A method as described in claim 14, wherein said extending sleeping surface is sold to said passenger as an upgrade option during pre-flight checkin.

**19.** A method as described in claim 13, further comprising:

unlocking said lower back portion from a raised position tangential with an upper back portion in order to fold said lower back portion into said lowered position.

**20.** A method as described in claim 19, wherein said unlocking can only be performed by airline personnel.

\* \* \* \* \*