



(12)

Oversættelse af
europæisk patentskriftPatent- og
Varemærkestyrelsen

(51) Int.Cl.: **A 24 D 3/06 (2006.01)** **A 24 D 3/04 (2006.01)**

(45) Oversættelsen bekendtgjort den: **2019-07-22**

(80) Dato for Den Europæiske Patentmyndigheds
bekendtgørelse om meddelelse af patentet: **2019-06-26**

(86) Europæisk ansøgning nr.: **11725505.9**

(86) Europæisk indleveringsdag: **2011-03-28**

(87) Den europæiske ansøgnings publiceringsdag: **2013-02-06**

(86) International ansøgning nr.: **IB2011001107**

(87) Internationalt publikationsnr.: **WO2011117743**

(30) Prioritet: **2010-03-26 US 318248 P**

(84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**

(73) Patenthaver: **Philip Morris Products S.A., Quai Jeanrenaud 3, 2000 Neuchâtel, Schweiz**

(72) Opfinder: **ALLEN, Jeffrey, Lynn, 18010 West Countyline Road, Midlothian, VA 23112, USA**
WILLIAMS, Dwight, D., 1508 Swiftwood Drive, Powhatan, VA 23139, USA
LONGEST, Cary, 1506 Ableway Drive, Midlothian, VA 23114, USA
LEE, Robert, E., 11802 Regent Prince Place, Richmond, VA 23238, USA

(74) Fuldmægtig i Danmark: **Plougmann Vingtoft A/S, Strandvejen 70, 2900 Hellerup, Danmark**

(54) Benævnelse: **PROPFILTER MED PROPRUM MED AROMAKUGLE**

(56) Fremdragne publikationer:
EP-A2- 0 232 166
US-A1- 2007 000 505
US-A1- 2007 012 327

DK/EP 2552261 T3

DESCRIPTION

BACKGROUND

[0001] Smoking articles, particularly cigarettes, generally comprise a tobacco rod of shredded tobacco (usually, in cut filler form) surrounded by a paper wrapper, and a cylindrical filter aligned in an end-to-end relationship with the tobacco rod. The tobacco rod is generally between about 6.0 millimeters and about 10.0 millimeters in diameter and between about 50 millimeters and about 125 millimeters in length.

[0002] Typically, the filter includes a plug of cellulose acetate tow attached to the tobacco rod by tipping paper. Ventilation of mainstream smoke can be achieved with a row or rows of perforations about a location along the filter.

[0003] When flavorants such as menthol are applied to cigarette filter in the form of a solution, staining or spotting of the outer surface of the cigarette can occur, particularly at high loadings of menthol in large amounts of solvent. Further, such a direct application of flavorants such as menthol to the cigarette filter does not allow for the regulation of menthol release during smoking and can lead to migration and loss of menthol during storage of the cigarette.

[0004] Accordingly, it would be desirable to provide a filter component for a smoking article, which provides added flavorant such as menthol to the mainstream smoke and can be easily manufactured and produced with existing filter forming equipment.

[0005] US 2007/0012327 A describes a filter assembly for a smoking article comprising a first adsorbent member of cellulose acetate, a second adsorbent member of cellulose acetate disposed apart from the first adsorbent member, with a capsule provided in a space between the members. The capsule may have a diameter of between 4.5 and 4.7 millimeters, and the first and second adsorbent members may have a diameter of about 5 mm. The capsule contains an additive which is a fluid material for modifying characteristics of tobacco smoke during smoking of the cigarette.

SUMMARY

[0006] In accordance with an exemplary embodiment, a filter component for a smoking article comprises: an upstream segment of filter material; a downstream segment of filter material in a spaced apart relation to the upstream segment of filter material so as to define a cavity therebetween; and a single flavor bead comprising tobacco particles and water disposed in the cavity. The flavor bead preferably has an outer diameter, which is at least 75% of the spaced apart relation of the upstream segment of filter material and the downstream segment of filter material and wherein the outer diameter of the flavor bead does not exceed an outer diameter

of either the upstream segment or downstream segment of filter material. The upstream segment of filter material has the lowest RTD (resistance to draw) of the segments of the filter component.

[0007] By 'spaced-apart relation' is meant the longitudinal distance between the upstream segment of filter material and the downstream segment of filter material (*i.e.*, the length of the cavity).

[0008] The upstream segment and the downstream segment of filter material may each comprise a plug of cellulose acetate tow.

[0009] In accordance with another exemplary embodiment, a smoking article comprises: a tobacco rod; and a filter component (or multi-component filter) comprising: an upstream segment of filter material; a downstream segment of filter material in a spaced apart relation to the upstream segment of filter material so as to define a cavity therebetween; a single flavor bead comprising tobacco particles and water disposed in the cavity, and wherein the flavor bead has an outer diameter, which is at least 75% of the spaced apart relation of the upstream segment of filter material and the downstream segment of filter material and wherein the outer diameter of the flavor bead does not exceed an outer diameter of either the upstream or downstream segments of filter material. The upstream segment of filter material has the lowest RTD (resistance to draw) of the segments of the filter component.

[0010] The filter component may comprise a filter wrapper which circumscribes the upstream segment of filter material, the downstream segment of filter material and the flavor bead.

[0011] The smoking article may further comprise ventilation around an outer periphery of the filter component.

[0012] In accordance with a further exemplary embodiment, a method of manufacturing a filter component comprises the steps of: dispensing an upstream filter segment having a first length onto a filter rod forming portion of a filter rod forming apparatus; dispensing a downstream filter segment having a second length in a spaced apart relationship to the upstream filter segment so as to define a cavity therebetween onto the filter rod forming portion; placing a single flavor bead comprising tobacco particles and water within the cavity; and circumscribing the upstream filter segment, the downstream filter segment and the flavor bead with a filter wrapper. The flavor bead has an outer diameter, which is at least 75% of the spaced apart relation of the upstream segment of filter material and the downstream segment of filter material and wherein the outer diameter of the flavor bead does not exceed an outer diameter of the upstream and downstream segments of filter material. The upstream segment of filter material has the lowest RTD (resistance to draw) of the segments of the filter component.

[0013] The method may comprise forming a filter rod comprising at least two segments of the first filter segment, at least two segments of the second filter segment, and at least two flavor beads in the cavities formed between the first filter segments and the second filter segments.

[0014] Preferably the method further comprises circumscribing the filter rod with a filter wrapper.

[0015] Preferably, the method further comprises cutting the filter rod into a plurality of individual filter components having at least one flavor bead therein.

[0016] Preferably, the method further comprises placing a tobacco rod adjacent to a tobacco end of an individual filter component such that the filter component and the tobacco rod are axially aligned in an end-to-end relationship and forms a smoking article.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017]

FIG. 1 is a perspective view of a smoking article in accordance with an embodiment;

FIG. 2 is a cross-sectional view of a smoking article in accordance with one embodiment;

FIG. 3 is a cross-sectional view of a filter rod in accordance with an embodiment;

FIG. 4 is a cross-sectional view of a smoking article in accordance with a further embodiment;

FIG. 5 is a cross-sectional view of a filter rod in accordance with another embodiment; and

FIG. 6 is a cross-sectional view of a method of forming filter components in accordance with an exemplary embodiment.

[0018] The drawings are exemplary only, and should not be construed as limiting the various embodiments set forth herein.

DETAILED DESCRIPTION

[0019] In accordance with an exemplary embodiment, as shown in FIG. 1, a smoking article 100 includes a generally cylindrical rod 110 of smoking material 120 (shown in FIG. 2), contained in a circumscribing outer wrapper 130. The outer wrapper 130 is typically a porous wrapping material or paper wrapper. The rod 110 is typically referred to as a "tobacco rod" and has a lit end 112 and a mouth end 114. As such, the tobacco rod 110 burns back from the lit end 112 thereof towards the opposite end (*i.e.*, mouth end 114) thereof, and the smoking material 120 of the tobacco rod 110 is consumed by combustion during the smoking period. The smoking material 120 is preferably a shredded tobacco or tobacco cut filler. However, any suitable smoking material 120 can be used.

[0020] The smoking article 100 also includes a filter system 140 adjacent to the mouth end 114 of the tobacco rod 110 such that the filter system 140 and tobacco rod 110 are axially aligned in an end-to-end relationship, preferably abutting one another. The filter system 140 has a generally cylindrical shape, and the diameter thereof is essentially equal to the diameter of the tobacco rod 110. The ends (i.e., upstream end 146 (shown in FIG. 2)) and downstream end 148 of the filter system 140 are open to permit the passage of air and smoke therethrough. It can be appreciated that the smoking article 100, which includes the tobacco rod 110 and the filter system 140 is generally between about 6.0 millimeters and about 10.0 millimeters in diameter and between about 75 millimeters and about 150 millimeters in length.

[0021] Herein, the "upstream" and "downstream" relative positions between filter segments and other features are described in relation to the direction of mainstream smoke as it is drawn from the tobacco rod 110 and through the filter system 140.

[0022] In accordance with an exemplary embodiment, the filter system 140 includes a plurality of filter segments 230, 240 (FIG. 2) circumscribed by a filter wrapper (or plug wrap) 144. The filter wrapper (or plug wrap) 144 is preferably a paper which optionally incorporates a carbonaceous material. Preferably, the filter wrapper (or plug wrap) 144 circumscribes the total length of the filter system 140. The filter system 140 is attached to the tobacco rod 110 by a tipping material 150, which circumscribes both the entire length of the filter system 140 and an adjacent region of the tobacco rod 110. The tipping material 150 is typically a paper like product; however, any suitable material can be used. The inner surface of the tipping material 150 is fixedly secured to the outer surface of the filter wrapper (or plug wrap) 144 and the outer surface of the wrapping material 130 of the tobacco rod 120, using a suitable adhesive. A ventilated or air diluted smoking article can be provided with an air dilution means, such as a series of ventilation holes or perforations 101, each of which extend through the tipping material 150 and optionally the filter wrapper (or plug wrap) 144.

[0023] In accordance with an exemplary embodiment as shown in FIG. 2, the smoking article 200 includes a tobacco rod 210 and a filter system (or multi-component filter) 220, which comprises a plug-space-plug filter sub-assembly that includes an upstream filter component 230, a downstream filter component 240 in spaced apart relation to the upstream filter component 230 so as to define a cavity 250 therebetween, and a flavor bead 260 disposed in the cavity 250. The upstream filter component 230 is located adjacent the tobacco rod 210 and preferably, comprises a plug of cellulose acetate tow 232 of low resistance to draw ("RTD") or other suitable fibrous or webbed material of moderate to low particulate efficiency. In accordance with an exemplary embodiment, the upstream filter component 230 is made as short as possible within the limits of high-speed machineability and preferably has the lowest particulate RTD amongst the filter components comprising the multi-component filter.

[0024] The downstream filter component 240 (or mouth end (buccal) component) is preferably in the form of a cellulose acetate plug 242 or other suitable fibrous or webbed material of moderate to low particulate efficiency. Preferably, the particulate efficiency is low, with the

denier and grand total denier being selected such that the desired total RTD of the filter is achieved.

[0025] Preferably, one or more circumferential rows of perforations (not shown) are formed through the filter wrapper 280 and the tipping paper 290 at a location along the filter 220, preferably at an upstream end portion of the filter 220. In accordance with an exemplary embodiment, the placement of the one or more circumferential rows of perforations is at a maximum distance between the buccal end (or mouth end) 214 of the smoking article 200 and the perforations, which preferably is at least 12 mm (millimeters) or more, so that a smoker's lips do not occlude the perforations. Furthermore, because the introduction of diluting air flows at an upstream end portion of the filter 220, itself, lowers the particulate efficiency of the downstream portions of the segment, the upstream location of the ventilation along the filter component facilitates design of the component to provide a more elevated (yet moderate) RTD without a significant elevation of particulate efficiency, so as to help maintain a desired low particulate efficiency in the central component and throughout the filter.

[0026] In accordance with an exemplary embodiment as shown in FIG. 2, the length of tobacco rod 210 is about 50 millimeters to about 80 millimeters, and more preferably about 55 millimeters to about 65 millimeters, and most preferably about 56 millimeters. The length of the filter 220 is preferably about 20 millimeters to about 35 millimeters and more preferably about 27 millimeters. The length of the filter components of the smoking article in an embodiment is as follows: the upstream filter component 230 is preferably about 7 millimeters; the space or cavity 250, which encapsulates the flavor bead 260 is preferably about 6 millimeters; and downstream filter component (*i.e.*, mouth end component) 240 is preferably about 14 millimeters. Also preferably, the upstream filter component 230, the flavor bead 240, and the downstream filter component 240 are surrounded or circumscribed by the filter wrapper 280.

[0027] It can be appreciated that the upstream and downstream filter components 230, 240 are preferably of low particulate efficiency. Amongst all the fibrous or web segments, the upstream end component is of lowest RTD and particulate efficiency, because it is upstream of the ventilation and therefore has greater effect upon the mainstream smoke. Unlike those other fibrous or webbed components, the upstream end component receives the mainstream smoke in the absence of a diluting air stream.

[0028] Although certain dimensions are disclosed with reference to the embodiments shown, such dimensions can be varied to provide different configurations related to the upstream and the downstream filter components 230, 240 and the flavor bead 260 within the filter 220.

[0029] The tobacco rod 210 may be wrapped with a conventional cigarette wrapper or banded paper can be used for this purpose. Banded cigarette paper has spaced apart integrated cellulose bands that encircle the finished tobacco rod of cigarette to modify the mass burn rate of the cigarette so as to reduce risk of igniting a substrate if the smoking article is left thereon smoldering. U.S. Patent Nos. 5,263,999 and 5,997,691 describe banded cigarette paper.

[0030] In accordance with an exemplary embodiment, the flavor bead 260 is in the form of a tobacco bead. In accordance with an exemplary embodiment, the flavor bead 260 consists essentially of tobacco particles, water and optional flavorants but without added binder ingredients. The flavor bead can be extruded and/or spheronized. In the alternative, the flavor bead 260 may further contain an added binder ingredient, wherein the binder is preferably a cellulosic material. A preferred cellulosic material is microcrystalline cellulose. Additional dry and liquid binders may be present in the beads as well as additional flavorants and fillers. If desired, the flavor bead 260 can include one or more coatings 262. Flavorants such as menthol crystals can be used to form a mentholated flavor bead, and/or other flavorants can also be added to the flavor bead 260 and/or to the coatings 262 of the bead 260. However, as noted above, the flavor bead 260 preferably is a bead comprising tobacco particles and water that is held together without addition of a binder additive other than water.

[0031] Not wishing to be bound by theory, at the downstream location of the flavor bead 260, the temperature of tobacco smoke passing through the filter is in a cooled condition, essentially at or about room temperature. Despite the absence of heat from the cigarette coal (or any addition of moisture), it has been found that a flavor bead 260 is effective in releasing flavor into the mainstream smoke so as to produce a flavored smoke. The flavors released from the flavor bead 260 are flavors specific to the tobacco source and/or flavors added to the bead 260 during their production. The organoleptic notes from using a flavor bead 260 are associated with enhanced tobacco character. Preferably, the flavors from the tobacco particulates and/or flavor components are released into the mainstream tobacco smoke under essentially ambient conditions.

[0032] In accordance with an exemplary embodiment, the flavor bead 260 can be a crushable capsule or bead, wherein the flavor bead releases at least a portion of the flavorant or additive material, such as menthol when the filter 220 is subjected to an external force.

[0033] In accordance with an exemplary embodiment, the flavor beads 260 are preformed. Flavorants can be included during the process of making the flavor or can be later added to the beads. Alternatively or in addition, flavorants can be added to a coating on the bead 260, said coating having perhaps the additional function of providing a controlled release of the components in the beads 260. Volatile flavorants can be added during the process of preparing the beads or to the preformed beads, depending on the process used for preparing the beads. Depending on the method of preparing the beads 260, it may be more preferable to add volatile flavorants to the preformed beads rather than during the process of preparing the beads. Liquid compounds can be added to the beads 260 by for example impregnating the beads with liquid formulations containing for example volatile flavors, diluents, and the like. Alternatively, compounds and compositions can be added to the beads by mixing the beads or by fluidized bed spraying of the beads or by other suitable methods.

[0034] It can also be appreciated that the functionality of the flavor bead 260 can be tailored to have more of controlled-delivery release of active compounds. For example, diffusion of the flavors from the bead 260 can be adjusted by bead porosity and density as well as by any

controlled-release coating added to the beads. For instance, the beads 260 can be overcoated with polymeric coatings of different functionalities and or compositions (for example, single or multiple overcoats depending on the application) to control the delivery and release of the active compounds.

[0035] In another aspect, the flavor bead 260 can act as a delivery system for delivering flavors naturally occurring in the components of the bead formulation. Alternatively, the flavor beads can act as a medium for creating and/or enhancing naturally occurring flavors through Maillard, enzymatic, or other types of reactions. It is further contemplated that the beads 260 can be altered or enhanced by thermal treatment of the beads 260 after formation. The thermal treatment can further enhance reactions such as Maillard reactions and enzymatic reactions and thereby flavors of the smoking article containing said beads.

[0036] Another embodiment contemplates that the flavor bead 260 can be further enhanced by adding additives during the bead making process. This can include additives such as flavors as well as components which would enhance the formation of flavors by reactions such as Maillard reactions between the components to naturally enhance the smoke. The optional flavorant includes flavor materials that are practically unlimited, although water-soluble, alcohol-soluble and oil-soluble flavors are preferable. Typical flavors include lavender, cinnamon, cardamom, apium graveolens, fenugreek, cascara, sandalwood, bergamot, geranium, honey essence, rose oil, vanilla, lemon oil, orange oil, mint oils, cassia, caraway, cognac, jasmine, chamomile, menthol, cassia, ylang-ylang, sage, spearmint, ginger, coriander, and coffee. Each of the flavors can be used singly or mixed with others. If desired, diluent agents can be added to the tobacco beads. Diluent agents which can be used for this purpose include powdered starch, such as but not limited to corn starch and potato starch, rice powder, calcium carbonate, diatomaceous earth, talc, acetate powder, and pulp flock. The optional flavorant can also be in the form of a solid matrix (liquid flavorants spray dried with a starch). The optional flavorant can also be in the form of solids, liquids or gels. The optional flavorant can be present in the tobacco beads in an amount of up to about 50% by weight (for example, 0.1% to 5%, 5% to 10%, 10% to 15%, 15% to 20%, 20% to 25%, 25% to 30%, 30% to 35%, 35% to 40%, 40% to 45% or 45% to 50%).

[0037] For tobacco particles containing additive binder such as a non-tobacco cellulosic material, microcrystalline cellulose (MCC) is the preferred cellulosic material in combination with tobacco particles. Whereas various flavor carriers may need heat or water to release volatile flavor compounds into mainstream smoke, cellulosic binder containing flavor beads and/or tobacco beads 260 can release such flavor constituents under ambient conditions.

[0038] The flavor beads 260 are preferably in the form of "spheroids" having diameters in the range of about 3.5 millimeters to about 10.0 millimeters, more preferably from about 4.0 millimeters to about 7.0 millimeters and most preferably from about 4.5 millimeters to about 5.0 millimeters (and any 0.1 value in between these ranges). The flavor bead 260 (or spheroids) can be round or oval in structure. In accordance with an exemplary embodiment, the flavor bead 260 preferably has an outer diameter, which is at least 75% of the spaced apart relation

of the upstream segment of filter material (or upstream filter component) 230 and the downstream segment of filter material (or downstream filter component) 240 and wherein the outer diameter of the flavor bead 260 does not exceed an outer diameter of either the upstream segment 230 of filter material or downstream segment 240 of filter material.

[0039] It can be appreciated that the flavor bead 260 in the form of a tobacco bead can be used to flavor mainstream smoke in cigarettes, which allows a standard tobacco mixture to be used in the tobacco rod of a standard lit-end cigarette and the desired taste attributes of different cigarette products (for example, regular, mild, full flavor, etc.) to be provided by a tobacco bead 260, which contain flavorant effective to achieve the desired taste of the mainstream smoke.

[0040] The preferred embodiments are merely illustrative and should not be considered restrictive in any way. The scope of the invention is given by the appended claims, rather than the preceding description, and all variations and equivalents which fall within the range of the claims are intended to be embraced therein. Moreover, the present invention may be practiced with cigarettes of various circumferences, narrow cigarettes as well as wide. Also, while the present invention is preferably practiced with unflavored tobacco rods, flavored tobacco filler is also contemplated.

[0041] As used herein, the term "about" and/or "approximately" when used in conjunction with a stated numerical value or range denotes somewhat more or somewhat less than the stated value or range, to within a range of $\pm 10\%$ of that stated.

[0042] It can be appreciated that the filter 220 can be manufactured by making and filling upstream and downstream plug-space-plug sections in sequence or simultaneously. For instance as shown in FIG. 3, a continuous filter rod 300 can be manufactured with repeating segments corresponding to the upstream filter segment 230, the cavity 250 containing a flavor bead 260 and a downstream filter segment 240, which is twice the desired length of the downstream filter segment 240, which are placed on a filter rod forming portion of a filter forming apparatus (or filter combiner). A second cavity 250 containing a flavor bead 260, another upstream filter segment 230, which is twice the desired length of the upstream filter segment 230, a third cavity 250 containing a flavor bead 260, another downstream filter segment 240, which is twice the desired length of the downstream filter segment 240, a fourth cavity 250 with a flavor bead 260 and an upstream segment of filter material is added to the filter rod forming portion of the filter rod apparatus. The segments 230, 240 and each of the cavities 250 with a flavor bead 260 are then circumscribed within a filter wrapper (or plug wrap) and cut into individual filter components 220 as shown in FIG. 2.

[0043] As shown in FIG. 3, the continuous filter rod 300 is approximately 108 mm in length and upon cutting into individual filter components 220 comprises four (4) filter components 220 of approximately 27 mm in length. In accordance with an exemplary embodiment, each of the four (4) individual filter components 220 comprise an upstream filter segment 230, which is about 7 mm in length, a downstream filter segment 240, which is about 14 mm in length, and a

flavor bead 260 within a cavity 250. In accordance with an embodiment, the cavity 250 is about 6 mm in length. As set forth above, although certain dimensions are disclosed with reference to the embodiments shown, such dimensions can be varied to provide different configurations related to the upstream and the downstream filter components 230, 240 and the flavor bead 260 within the filter 220.

[0044] In accordance with an exemplary embodiment, the flavor bead 260 has an outer diameter 264, which is at least 75 % of the spaced apart relation of the upstream segment of filter material 230 and the downstream segment of filter material 240 and wherein the outer diameter 264 of the flavor bead 260 does not exceed an outer diameter 224 of the filter component 200 and/or the upstream or the downstream segments of filter material 230, 240. For example, for a cavity 250 which is about 6 mm in length, the flavor bead 260 preferably has an outer diameter 264 of about 4.5 mm or greater.

[0045] In accordance with another embodiment, as shown in FIG. 4, a smoking article 400 includes a tobacco rod 410, which is about 58 mm long, and a filter or filter component 420, which is about 25 mm long held together by tipping paper 412. The filter 420 includes an upstream segment of filter material 430 in a spaced apart relationship to a downstream segment of filter material 440 so as to define a cavity 450 containing a flavor bead 460, and a recess 470 at the downstream end of the downstream segment of filter material 440. From the downstream end (or mouth end) of the filter 420, the segments preferably include a 5 mm long recess 470, a 10 mm long downstream segment of filter material 440 preferably in the form of a cellulose acetate (CA) plug, a 5 mm long cavity 450 containing a flavor bead 460, and a 5 mm long upstream segment of filter material 430 preferably in the form of another cellulose acetate (CA) plug.

[0046] As shown in FIG. 5, a continuous filter rod 500 can be manufactured with repeating segments corresponding to the upstream segment of filter material 430, the cavity 450 containing a flavor bead 460, the downstream segment of filter material 440, and a recess 480, which is twice the cut or desired length of the recess 470, which is placed on the rod forming portion of the filter forming apparatus. Another downstream segment of filter material 440, a cavity 450 with flavor bead 460, an upstream segment of filter material 430, another cavity 450 with flavor bead 460, a downstream segment of filter material 440, a recess 480, which is twice the desired length of the recess 470, another downstream segment of filter material 440, another cavity 450 with flavor bead 460 and an upstream segment of filter material 430 are then added to the rod forming portion of the filter forming apparatus. The entire rod is circumscribed in a filter wrapper, and then cut into individual filter components 420 for assembly with a tobacco rod 410 to form a smoking article 400 as shown in FIG. 4.

[0047] As shown in FIG. 5, in accordance with an exemplary embodiment, the continuous rod 500 is about 100 mm in length and can be cut into four (4) filter components 420, which are about 25 mm in length. Each individual filter component 420 comprises a 5 millimeter recess 470, a 10 mm downstream segment of filter material 440, a 5 millimeter cavity 450 having a flavor bead 460 disposed therein, and a 5 millimeter upstream segment of filter material 430.

[0048] In accordance with another exemplary embodiment, FIG. 6 shows a system 600 for manufacturing a filter (or filter component) 220, 420 and/or a continuous filter rod 300, 500 as shown in FIGS. 2-5. As shown in FIG. 6, the system 600 includes at least two hoppers 610, 620, which include filter segments preferably having a first length (i.e., first filter segment) 612 and a second length (i.e., second filter segment) 622, respectively, and a hopper 630 filled with flavor beads 632 of a desired diameter. The first and second filter segments 612, 622 are placed in a spaced apart relationship on a filter combiner 640 (or filter forming apparatus) so as to define a cavity therebetween. A flavor bead 632 is then placed in the cavity, and the process is repeated until a continuous filter rod 650 is formed. The filter segments 612, 622, and the individual flavor beads 632 are then wrapped with a filter wrapper 652 to form the continuous filter rod 650, which is then cut into individual filter components 660.

[0049] It can be appreciated that the flavor beads 632 can be placed or positioned within the cavity by any known method including dispensing the flavor bead by gravitation force, vacuum assisted method, such as a vacuum wheel and/or other known methods of placing a spherical object or bead within a cavity.

[0050] The continuous filter rod 650 before cutting preferably includes at least two segments of the first filter segment 612, at least two segments of the second filter segment 622, and at least two flavor beads 632 in the cavities formed between the first filter segments and the second filter segments. The filter segments 612, 622 are then wrapped in a filter paper or plug wrap 652 and cut into a plurality of filter components 660 having at least one flavor bead 630 therein. The individual filter components 660 are assembled with a tobacco rod to form a smoking article 670.

[0051] In accordance with another exemplary embodiment, an additional hopper 680 can include a recessed filter segment 682, which is placed adjacent to either the first filter segment and/or the second filter segment as described and shown in FIGS. 4 and 5. It will be appreciated that a recess adjacent to either the first filter segment and/or the second filter segment may also be formed in other ways, such as, for example, by placing neighboring pairs of the first or second filter segments 612, 622 in a spaced apart relationship on the filter combiner 640.

[0052] It should be understood that the foregoing description is of the preferred embodiments, and is merely representative of the article and methods of manufacturing the same. It can be appreciated that variations and modifications of the different embodiments in light of the above teachings will be readily apparent to those skilled in the art. Accordingly, exemplary embodiments, as well as alternative embodiments, may be made without departing from the scope of the articles and methods set forth in the attached claims.

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US20070012327A [0005]
- US5263999A [0029]
- US5997691A [0029]

Patentkrav**1. Filterkomponent til en rygeartikel (100) omfattende:**

et opstrøms filtermaterialesegment (230);

5 et nedstrøms filtermaterialesegment (240) anbragt med afstandsforhold til opstrøms filtermaterialesegmentet for at definere et hulrum (250) derimellem; og

en enkelt aromakugle (260) anbragt i hulrummet, idet aromakuglen omfatter tobakspartikler og vand, hvor aromakuglen har en udvendig 10 diameter, der er mindst 75% af afstandsforholdet mellem opstrøms filtermaterialesegmentet (230) og nedstrøms filtermaterialesegmentet (240), og den udvendige diameter af aromakuglen (260) ikke overstiger en udvendig diameter af enten opstrøms filtermaterialesegmentet eller nedstrøms filtermaterialesegmentet,

15 hvor opstrøms filtermaterialesegmentet (230) har den laveste RTD (trækmodstand) af segmenterne i filterkomponenten.

2. Filterkomponent ifølge krav 1, endvidere omfattende et fordybningssegment på en nedstrøms ende af nedstrøms filtermaterialesegmentet (240).

20

3. Filterkomponent ifølge krav 1, hvor nedstrøms filtermaterialesegmentet (240) har en længde, der er mindst to gange en længde af opstrøms filtermaterialesegmentet (230).

25 **4. Filterkomponent ifølge krav 1, hvor opstrøms filtermaterialesegmentet (230) er mellem ca. 5 millimeter og ca. 10 millimeter i længden.**

5. Filterkomponent ifølge krav 1, hvor nedstrøms filtermaterialesegmentet (240) er mellem ca. 5 millimeter og ca. 20 millimeter i længden.

30

6. Filterkomponent ifølge krav 1, hvor hulrummet (250) er mellem ca. 5 millimeter og ca. 7 millimeter i længden.

7. Filterkomponent ifølge krav 1, hvor aromakuglen (260) er i form af en sfæroide med en diameter på ca. 4,5 millimeter til ca. 5 millimeter.

8. Filterkomponent ifølge krav 1, hvor aromakuglen er en polymercoatet
5 mentoltobakskugle.

9. Filterkomponent ifølge krav 1, hvor opstrøms filtermaterialesegmentet (230), nedstrøms filtermaterialesegmentet (240) og aromakuglen er omgivet af en filterindpakning (144).

10

10. Rygeartikel (100) omfattende:

en tobaksstang (110); og

en filterkomponent ifølge et hvilket som helst af kravene 1 til 9:

15

11. Fremgangsmåde til fremstilling af en filterkomponent omfattende:

at afgive et nedstrøms filtersegment (240) med en første længde på en filterstang som er del af en filterstangdannende anordning;

at afgive et opstrøms filtersegment (230) med en anden længde i et afstandsforhold til nedstrøms filtersegmentet for at definere et hulrum

20

(250) derimellem på den filterstangdannende del; og

at anbringe en enkelt aromakugle (260) omfattende tobakspartikler og vand inde i hulrummet,

hvor aromakuglen har en udvendig diameter, der er mindst 75% af afstandsforholdet af opstrøms filtermaterialesegmentet og nedstrøms

25

filtermaterialesegmentet, og hvor den udvendige diameter af aromakuglen ikke overstiger en udvendig diameter af opstrøms og nedstrøms filtermaterialesegmenterne; og

hvor opstrøms filtermaterialesegmentet (230) har den laveste RTD (trækmodstand) af segmenterne i filterkomponenten.

30

12. Fremgangsmåde ifølge krav 11, endvidere omfattende at omslutte nedstrøms filtersegmentet, opstrøms filtersegmentet og aromakuglen med en filterindpakning (144).




13. Fremgangsmåde ifølge krav 11, omfattende at danne en filterstang omfattende mindst to segmenter af nedstrøms filtersegmentet, mindst to segmenter af opstrøms filtersegmentet, og mindst to aromakugler i hulrummene dannet mellem nedstrøms filtersegmenterne og opstrøms filtersegmenterne.

5

14. Fremgangsmåde ifølge krav 13, endvidere omfattende at omslutte filterstangen med en filterindpakning (144).

15. Fremgangsmåde ifølge krav 11, endvidere omfattende at danne et 10 fordybningssegment som støder op til enten nedstrøms filtersegmentet eller opstrøms filtersegmentet.

DRAWINGS






FIG. 4




FIG. 5




FIG. 6