



(51) International Patent Classification:

**A61B 18/18** (2006.01) **A61B 18/20** (2006.01)  
**A61M 1/36** (2006.01) **A61N 5/067** (2006.01)

(21) International Application Number:

PCT/US20 11/021801

(22) International Filing Date:

20 January 2011 (20.01.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/296,730 20 January 2010 (20.01.2010) US

(71) Applicant (for all designated States except US): **CERAMOPTEC INDUSTRIES, INC.** [US/US]; 515- Shaker Road, East Longmeadow, MA 01028 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **NEUBERGER, Wolfgang** [AT/AE]; P.O. Box 505072, Dubai (AE).

(74) Agent: **SKUTNIK, Bolesh**; CeramOptec Industries, Inc., 515 Shaker Road, East Longmeadow, MA 01028 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: DEVICE AND METHOD FOR VESSEL TREATMENT



(57) Abstract: An endoluminal lasing system for treating vascular disorders is disclosed. Treatment comprises an elongated member that conveys laser radiation to tissue and a motorized mechanism, through which elongated member is rotated. As the motor is driven, its movement spins elongated member thus leading to a spiral movement as physician manually moves member in a longitudinal direction. In a preferred embodiment, elongated member is an optical fiber for endoluminal vessel treatment, in another preferred embodiment optical fiber comprises an off-axis firing end or side-firing distal end. In other preferred embodiments, optical fiber is a radial emitting fiber or a direct emitting fiber. Spin velocity can be varied according to treatment needs, i.e., pathology, type of vessel, energy source, vessel diameter, etc. One advantage of this invention is that spiral movement prevents adherence of elongated member to vessel wall in various treatment situations, such as when vessel shrinks due to absorption of laser radiation. Another advantage of spiral movement is that radiation is applied more uniformly along vessel wall, regardless of its tortuosity or elongated member's offset from longitudinal axis. As a consequence, the vessel wall is more evenly treated in spite of radius and/or fiber position variation. Treatment velocity and its reproducibility are enhanced with this procedure, and human errors are highly minimized.

## DEVICE AND METHOD FOR VESSEL TREATMENT

Inventors: Wolfgang Neuberger

Assignee: CeramOptec Industries Inc.

### Background of the Invention

#### Related Patent Information

This application claims the benefit of U.S. Provisional Application Serial  
5 No.61/296,730 by Wolfgang Neuberger, entitled "Device and Method for Vessel  
Treatment" filed January 20th, 2010, which is incorporated by reference herein.

#### 1. Field of the invention

The present invention relates to minimally invasive treatments and in  
10 particular, to the treatment of vascular disorders by using local energy emitting  
devices and conveying means.

#### 2. Invention Disclosure Statement

The blood vessels are the part of the circulatory system that transport blood  
15 throughout the body. There are three major types of blood vessels: the arteries, which  
carry the blood away from the heart, the capillaries, which enable the actual exchange  
of water and other substances between the blood and the tissues; and the veins, which  
carry blood from the capillaries back towards the heart.

Arteries and veins have the same basic structure. Three distinct layers can be  
20 identified, from inside to outside: tunica intima, tunica media and tunica adventitia.  
The main difference between arteries and veins is the proportions in which these  
components are present.

In the arterial system, blood pressure is usually around 120 mmHg systolic  
and 80 mmHg diastolic. In contrast, pressures in the venous system are constant and  
25 rarely exceed 10 mmHg.

The venous system comprises valves, whose main function is to achieve  
unidirectional blood flow back to the heart. Venous valves are usually bicuspid  
valves, with each cusp forming a blood reservoir, which force their free surfaces

together under retrograde blood pressure. As a consequence, when properly operating, retrograde blood flow is prevented, allowing only antegrade flow to the heart. A valve becomes incompetent when their cusps are unable to seal properly under retrograde pressure gradient, so retrograde blood flow occurs. When retrograde blood flow  
5 occurs, pressure increases in the lower venous sections, dilating veins and usually leading to additional valvular failure.

Valvular failure, usually referred to as venous insufficiency, is a chronic disease that can lead to skin discoloration, varicose veins, pain, swelling and ulcerations. Varicose veins refer to blood vessels that have become enlarged and  
10 twisted and have progressively lost their wall elasticity. Due to the widening of the blood vessels, vein valves cannot be completely closed and veins lose their ability to carry blood back to the heart. This leads to an accumulation of blood inside the vessels, enlarging and twisting the veins even more. Furthermore, varicose veins usually have a blue or purple color and may protrude twisted above the surface of the  
15 skin, this being responsible for their characteristically unattractive appearance. They are commonly formed in the superficial veins of the legs, which are subject to high pressure when standing. Other types of varicose veins include venous lakes, reticular veins and telangiectasias. A special case of venous insufficiency may occur in arteriovenous fistula: a connection between an artery and a vein. These can be  
20 congenital, surgically created or acquired due to pathologic process. A fistula may be surgically created for hemodialysis treatments (vascular access). Arteriovenous fistula for vascular access is carried out previous to hemodialysis treatment, in order to render a larger and stronger vein for easy access to the blood system. As a consequence, an adequate vascular access is achieved, through which blood is  
25 withdrawn, purified, and returned to the body. Vascular accesses are thus entranceways into the bloodstream that lie completely beneath the skin. It is well known that vascular accesses have a high incidence of complications, finally determining vascular access failure. These can be divided into non-thrombotic and thrombotic complications, finally determining vascular access failure. Regarding non-  
30 thrombotic complications, venous hypertension is one of the most important since it may cause valvular incompetence or central venous stenosis. This may lead to severe

upper limb edema, skin discoloration, access dysfunction and peripheral ischemia with resultant fingertip ulceration.

There are a number of treatments available intending to cure these kinds of vascular pathologies. Some of them only consist in relief of symptoms but they do not  
5 treat varicose veins nor prevent them from forming. These include elevating the legs by lying down or using a footstool when sitting, elastic stockings and exercise.

Varicose veins are frequently treated by eliminating the insufficient veins. This forces the blood to flow through the remaining healthy veins. Various methods can be used to eliminate the problem of insufficient veins, including, sclerotherapy,  
10 surgery (vein stripping), electro-cautery, and laser treatments.

Laser treatments are usually preferred by those skilled in the art. Minimally invasive laser surgery has been improved due to new diode laser systems. In endovascular laser surgery, laser radiation applies thermal energy to the vein by means of an optical fiber, and while fiber is withdrawn, the vein closes and, ideally,  
15 eventually disappears through resorption. In these and other cases, endovascular laser treatment provides an effective technique for eliminating or diminishing skin and vascular problems. A well known prior art describing endovascular laser ablation procedure includes the following steps: first, a guide wire is inserted into the vein to be treated, with the help of an entry needle. Second, an introducer sheath is  
20 introduced over the guide wire and advanced to a treatment site. Then, the guide wire is removed leaving the introducer sheath in place. The optical fiber (coupled to a laser source) is inserted through the introducer sheath and positioned so that the emitting end at the distal tip of the fiber and the sheath are at the same point. Tumescant anesthesia is then applied to the tissue surrounding the vein to be treated.  
25 Prior to lasing, the sheath is pulled back from the emitting end a distance sufficient to prevent the emitted laser energy from damaging the sheath. Then, laser is fired to emit laser radiation into the blood and/or vein wall directly in front of the emitting face. Finally, while laser energy is emitted, optical fiber and introducer sheath are withdrawn together to treat and close a desired length of the vein. Laser energy is  
30 absorbed by the blood and/or vein wall tissue. As a consequence, vein is thermally damaged, thus leading to fibrosis of the vein, which is resorbed after some time.

From previously described laser ablation technique it can be seen that laser irradiation is fired once optical fiber is inserted inside the vein and placed in the desired position inside it. However, optical fiber seldom remains centered inside the vein while irradiation is being performed, due to the vein morphology variation along its length when fiber is displaced longitudinally. Some approaches have been proposed in order to maintain fiber centered while withdrawing. For example, U.S. Patent No. 7,273,478 B2 describes an endoluminal catheter with a spacer design for achieving fiber centering. This kind of approaches, even when efficient, adds complexity to laser probes. In addition, it often increases probe's diameter and some designs may not fit into vein and/or may damage tissue. Furthermore, it is well known that morphology variation is usually increased in varicose veins due to their tortuosity, usually leading to failure of the approaches described in related patents, inability to keep the optical fiber centered may lead to inefficient treatments and/or post-surgery complications. In the first case, vein closure may be incomplete thus leading to recurrent varicose veins. In the second case, a non-centered fiber may irradiate vein unevenly and cause vein wall perforation in those regions of high energy deposition, thus causing hemorrhages. Moreover, perivenous tissue damage is more likely to occur when uneven irradiation is applied. As a consequence, nerves may be damaged and patient's recovery delayed.

Recently, due to improvements in endovenous laser ablation devices and techniques, some of these drawbacks have been overcome. Patent application SN 12/395,455 by Neuberger, discloses substantial improvements in optical fiber, including a rounded tip configuration and emission of radiation radially with respect to its main axis (radial fiber). As a consequence, guide wire and tumescent anesthesia would be no longer required when carrying out endovascular laser treatment. The need of tumescent anesthesia is further reduced by the usage of wavelengths that are highly absorbed in the components surrounding fiber tip, for example, 1470nm. As a consequence, thermal effect caused in tissue by laser radiation is restricted to the zone of interest, thus preventing from damaging non-target tissue (e.g., nerves are not affected by thermal effects, thus rendering a virtually painless procedure).

As previously mentioned, optical fiber is usually withdrawn as the insufficient vein is being irradiated, in order to cause obliteration along its length. This pullback

movement can be carried out manually or by means of some automatic system. An example of the second case is described in U.S. Patent No. 7,524,316 B2 by Hennings et al., in which a motorized pullback is described. In spite of technique's mentioned advantages, experience has shown that in practice a smooth pullback movement is not achieved, due to the adherence that occurs between the vein wall and the laser probe's emitting end. This undesired "sticky vein effect", may cause the vein to tear apart. In addition, vein carbonization can occur in those vein wall spots receiving excessive laser energy. When this happens, energy deposition is non-uniform and incomplete vein closure is likely to occur.

According to the previously mentioned, improvements may be carried out with respect to current vein treatments in order to enhance outcomes and render an easier and more efficient procedure.

Arteries, too, are affected by numerous pathologies. Among the most important are the congenital anomalies. One of the most important is the aneurysm: an abnormal widening or ballooning of a portion of an artery due to congenital weakness in its wall. Aneurysms are most prominent and significant in the abdominal aortic artery, intracranial arteries (supplying blood to the brain), and the aorta, but also occur in peripheral vessels such as in the popliteal arteries, femoral arteries, carotid arteries, and in arteries feeding arms and kidneys. Although it is still not exactly clear what causes aneurysms, high blood pressure and high cholesterol may raise occurrence risk of some types of aneurysms. The main complications of aneurysm include: compression of nearby structures such as nerves, infection and rupture, which can cause massive bleeding that may lead eventually to death. Furthermore, thrombi may form in the dilated pouch giving rise to emboli that may obstruct smaller vessels. In some cases, the aneurysm may dissect into the wall of an artery, blocking some of the branches.

Invasive treatments of aneurysms are either endovascular techniques (angioplasty with stent) or open surgery techniques. Open techniques include exclusion and excision.

For aneurysms in the aorta, arms, legs, or head, the weakened section of the vessel may be replaced by a bypass graft that is sutured at the vascular stumps.

Endovascular treatments are less invasive and involve insertion of a catheter into the femoral artery in the patient's leg and navigating it through the vascular system, into the aneurysm. Thermal sources have been used for treating aneurysms. For instance, U.S. Patent 4,735,201 by O'Reilly discloses an optical fiber with detachable metallic tip affixed to laser energy transmitting optical fiber by hot-melt adhesive. Metallic tip serves to generate heat by absorption of laser energy for cauterization of tissue surrounding the neck of an aneurysm or other vascular opening to be occluded. The device is used for intravascular laser coagulation of arteries, veins, aneurysms, vascular malformations and arteriovenous fistulas. The heat generating tip of the device is positioned intravascularly within the neck of the aneurysm or other vascular opening to be occluded and laser energy is transmitted through the optical fiber to heat the tip and thereby coagulate the tissue surrounding the tip. As another example, U.S. Patent 5,405,322, by Lennox, discloses an apparatus and method for treating an aneurysm in a vessel that isolates and evacuates volume around aneurysm site by application of RF heating, via spaced electrodes and one or more inflatable balloons within catheter. An apparatus and method for treating an aneurysm in a vessel that isolates a volume around the aneurysm, evacuates that volume and heats the aneurysm wall are disclosed. A catheter includes one or more inflatable balloons for defining the isolated volume and occluding and preventing any blood flow through the volume. When the treatment is completed, the balloons are deflated and the catheter is removed from the vessel. Thermal sources present many disadvantages. First, as heat is an unspecific source of energy, treatment precision may be compromised. Second, some studies suggest that risk of thrombosis may be significant with this kind of treatments. Third, recurrence is likely to occur after some time. Finally, these thermal methods require permanent contact between heated tip and the vessel wall for them to be effective and thus energy is delivered to the vein wall essentially only through such points of contact. Specifically regarding to RF, some drawbacks can also be mentioned. RF methods can be more time consuming and thus more stressful to the patient than otherwise desired. Moreover, the catheters used and RF electrodes are relatively complex and more expensive to manufacture than those developed for other treatment methods (e.g. laser procedures). Need for

evacuation of blood in the treatment site also complicates the system and method, providing additional aspects where failure can occur.

As previously detailed, numerous approaches based on the application of laser energy have been proposed for the treatment of vein and artery pathologies. These approaches present several drawbacks. For instance, in most of prior art, optical fiber doesn't remain centered inside the vein while irradiation is being performed. Approaches trying to address this drawback usually fail due to varicose vein increased tortuosity. Furthermore, even when efficient, they add complexity to laser probes and often increase tissue damage risk due to probe's greater diameter. Inability to keep the optical fiber centered may lead to inefficient treatments (recurrent varicose veins) and/or post-surgery complications (wall perforation). Optical fiber is withdrawn while irradiating insufficient vein, in order to cause obliteration along its length. This pullback movement can be carried out manually or by means of some automatic system. Experience has shown that in practice, a smooth motorized pullback movement is seldom achieved, due to the adherence that occurs between the vein wall and the laser probe's emitting end. This undesired "sticky vein effect", may cause the vein to tear apart. In addition, vein carbonization can occur in those vein wall spots receiving excessive laser energy. When this happens, energy deposition is non-uniform and incomplete vein closure is likely to occur.

There is thus a need for a minimally invasive vascular treatment that improves on the state of the art, assuring an even irradiation inside the vessel and improving pullback movement, to enhance safety and efficiency, while reducing procedure time. The present invention addresses these needs.

## **Objectives and Brief Summary of the Invention**

It is an objective of the present invention to provide a device and method for improved vascular treatment of vessel disorders.

It is another objective of the present invention to treat dysfunctional vessels accurately and precisely, by using a localized, directed energy source and conveying means.



It is also an objective of the present invention to provide a device and method for safer, painless and more reliable vascular treatment by means of an effective spiral radiation pattern, which guarantees a uniform delivery of energy to tissue.

It is yet another objective of the present invention to provide a device and  
5 method for preventing conveying means adherence to vessel wall by means of rotational movements, facilitating its longitudinal displacement thus leading to an improved vascular treatment.

Briefly stated, an endoluminal lasing system for treating vascular disorders is  
10 disclosed. Treatment device comprises an elongated member that conveys laser radiation to tissue and a motorized mechanism, through which elongated member is rotated. As the motor is driven, its movement spins elongated member thus leading to a spiral movement as physician manually moves member in a longitudinal direction. In a preferred embodiment, elongated member is an optical fiber for endoluminal  
15 vessel treatment. In another preferred embodiment optical fiber comprises an off-axis firing end or side-firing distal end. In another preferred embodiment, optical fiber is a radial emitting fiber or a direct emitting fiber. Spin velocity can be regulated according to treatment needs, i.e., pathology, type of vessel, energy source, vessel diameter, etc. One advantage of this invention is that spiral movement prevents  
20 adherence of elongated member to vessel wall in various treatment situations, such as when vessel shrinks due to absorption of radiation energy. Another advantage of spiral movement is that radiation is applied more uniformly along vessel wall, regardless of its tortuosity or elongated member's offset from longitudinal axis. As a consequence, the vessel wall is more evenly treated in spite of its radius and/or fiber  
25 position variation. Treatment velocity, as well as its reproducibility, is enhanced with this procedure, and human errors are highly minimized. Other medical treatments involving treatment of non-hollow tissue structures can benefit from this device, including but not limited to treatment of enlarged prostates, fat removal or firming of tissue applications.

30 The above and other objects, features and advantages of the present invention will become apparent from the following description read in conjunction with the

accompanying drawings (in which like reference numbers in different drawings designate the same elements).

### Brief Description of Figures

5        FIGS. **1a** and **1b** depict a preferred embodiment of present invention describing main components of the system disclosed.

FIG. **2** shows a preferred embodiment of the present invention including an embedded laser source in the rotation drive system.

10        FIG. **3** depicts an embodiment in which temperature is monitored during procedure by means of sensors placed near optical fiber tip.

FIG. **4** shows a preferred embodiment of present invention in which radiation conveying means includes multiple optical fibers.

FIG. **5** depicts preferred embodiments in which different types fiber tips are used.

15

### Detailed Description of Preferred Embodiments

The present invention addresses prior art disadvantages by assuring a uniform irradiation inside the vessel and an improved axial movement, to enhance safety and efficiency, while reducing procedure time. Axial movement is improved by means of a rotating irradiation system. Therefore, adherence between vessel wall and probe's distal end is prevented through this rotational movement of the radiation delivery member. In some applications, such as endoluminal treatment of insufficient veins, such rotational movement is preferably carried out while irradiating insufficient vein during removal so as to cause complete closure of vessel. Other applications where the goal is to strengthen but not completely close a tubular structure, for example in treatment of aneurysms, rotation may be required during introduction.

20

25

In a preferred embodiment, depicted in FIGS. **1a** and **1b**, optical fiber **102** comprising off-axis firing end 104 is attached to rotation drive system 108. Off-axis firing end fiber is described in U.S. Patent Application 12/714,155 by Neuberger, and is commonly referred to as "twister fiber". Optical fiber's firing end 104 emits

30

radiation close to vessel wall. Studies suggest that highly efficient procedures are accomplished when laser energy is applied near or contacting vessel wall in a controlled manner. The method disclosed in the present invention consists in inserting optical fiber **102** endoluminally into a vessel with the help of an entry needle. Then, under echographic guidance or by direct vision of aiming beam through skin, optical fiber is advanced to treatment site. Optical fiber **102** is coupled to rotation drive system **108**, which is connected to laser source (not shown). Radiation from laser source is coupled to rotation drive system **108** by means of appropriate lenses that allow an efficient electromagnetic radiation transmission between a static system and a rotational system (spinning fiber). Afterwards, laser is fired to emit electromagnetic radiation into vessel wall directly in front of the emitting face **104**. While laser energy is emitted, optical fiber **102** is withdrawn to treat and close a desired length of the vein. Grip **106** is provided to facilitate manual pullback. While pulling optical fiber **102** back, it is rotated with an appropriate speed by rotation drive system **108**, providing an additional benefit preventing adherence, thus, of optical fiber **102** to vessel wall. By avoiding adherence, a smooth withdrawal movement is accomplished, thus increasing precision of laser energy deposition on vessel's surface. As a consequence, various treatment situations, e.g. vessel shrinkage due to laser radiation absorption, are managed successfully with this procedure. Spinning movement is performed according to treatment needs and describes a spiral radiation pattern inside the vessel when combined with withdrawal movement. Another advantage of spiral movement is that radiation is applied uniformly along vessel wall, regardless of its tortuosity or elongated member centering. The procedure is thus safer, as there is considerably less risk of vein perforation and damage to surrounding tissue. Treatment velocity, as well as its reproducibility, is enhanced with this procedure, and human errors are highly minimized.

In another preferred embodiment, spinning velocity is regulated in real-time by means of rotation drive system **108**, which processes feedback parameters, such as withdrawal speed. In this case, withdrawal speed is monitored in real time and used as an input to rotation drive system **108**. Spinning velocity is determined by applying an appropriate algorithm based on physiological models, incorporated in the system.

In another embodiment, spinning motion in one or another direction also causes forward or backward motion respectively of fiber. Thus rotation speed and axial speed are mechanically related. This can be achieved, for example with a rotational clamp system with a thread to translate the rotating motion into a axial motion.

In another preferred embodiment of the present invention, depicted in FIG. 2, rotation drive system 208 also includes an embedded laser source 210. Laser source 210 is rotated by spinning driver 212. As a consequence, a complete treatment system is provided in a single device. This is possible to accomplish thanks to the reduced size of diode lasers, which allows for embedding them as a part of other systems. Therefore, laser source 210 may rotate along with spinning fiber 202, as an embedded part of rotation drive system 208, thus avoiding the use of lenses or other similar coupling means which may add complexity to the system. In another embodiment, laser source may remain static with respect to spinning fiber, thus coupling radiation from laser source to rotation drive system by means of an appropriate system.

FIG. 3 shows another preferred embodiment of the present invention, in which optical spinning fiber 302 comprises temperature sensors 314 near emitting tip 304. Based on the temperature measured in the emission zone by temperature sensors 314, spinning velocity is regulated for achieving desired effect on tissue, by means of applying an appropriate fluency to it. Therefore, according to treatment needs, laser energy deposition in vessel wall is accomplished precisely and efficiently, thus diminishing undesired effects and complications usually caused by temperature excess, e.g. vein perforation, damage to surrounding tissue, etc. Furthermore, spinning speed may be adjusted according to withdrawal velocity (as previously explained), thus rendering a procedure regulated by two interdependent variable controls (temperature and speed of withdrawal). As a consequence, treatment reliability and safety are greatly enhanced.

In another preferred embodiment showed in FIG. 4, spinning optical fiber 400 comprises multiple off-axis firing end fibers 402. By emitting at multiple sites inside the vessel, optical fiber withdrawal speed can be increased without detriment to treatment efficiency. As a consequence, faster procedures can be performed while maintaining treatment precision.

In other preferred embodiments, as shown in FIG. 5, optical fibers 502 with different fiber tip configurations are employed. Variants include but are not limited to off-axis tips 516, radial emitting tips 518 and direct emitting tips 520. Here again, rotational movements of fiber prevent possible adherence to vessel walls.

5 In other preferred embodiments, optical fibers with different fiber tip configurations are employed. Variants include but are not limited to radial emitting fibers and direct emitting fibers. Here again, rotational movements of fiber prevent possible adherence to vessel walls.

10 In order to treat aneurysms in an efficient manner, the controlled shrinkage and strengthening of its wall structure needs to be accomplished. In a preferred embodiment of the present invention, aneurysms are treated by applying direct laser energy of appropriate wavelength and pattern thus rendering shrinkage as well as strengthening of vessel wall. A helicoidal radiation pattern is preferred and can be achieved by using a twister or side-emitting fiber, through rotational or oscillatory  
15 movements while longitudinally displacing it, thus applying energy in an even, more controlled and guided manner. It is also possible to bring the output end(s) of energy delivery devices in contact or at a controlled distance from the tissue by means of spreaders, levers, balloons, spacers or other suitable means and it is possible to use fiber optic assemblies such as fiber optic bundles.

20 Treatment method in this case will be similar to that previously disclosed in the embodiment regarding FIG. 1. Radiation is transported in a controlled manner via a radiation conveying means to the site where energy is needed. Radiation conveying means is inserted through the skin and inside the artery to a location nearby aneurysm in order to perform an endoluminal procedure. Once distal end of radiation conveying  
25 means is in the desired position, proximal end is connected to the rotation drive system, which in turn is connected to (or directly comprises) the energy emitting device and energy is applied to the artery wall. While applying laser energy, optical fiber is rotated or swept and displaced longitudinally. Maximum sweeping angle (to define a desired treatment area) and velocity can be set directly in the rotation drive  
30 system by the physician. As a consequence of the energy absorbed in the vessel wall, its diameter is reduced in a controlled manner, accomplishing the controlled shrinkage and strengthening of wall structure. This minimally invasive method of treating

aneurysms can be used to prevent their growth at their early stages or to shrink larger ones.

In a preferred embodiment, a mini-endoscope is used to control the process by visual inspection from the inside of the vein. In addition, a real time imaging means  
5 such as ultrasound can be added to control the procedure. Additionally, a high resolution endovascular image can be obtained for studying the tissue to be treated in detail. For example, optical coherence tomography (OCT) imaging technology may be employed.

When laser radiation is used to apply energy to the vessel, different  
10 wavelengths can be chosen. Laser wavelength is chosen, in the present case, according to the desired penetration depth in tissue. It has been found that a wavelength that is essentially absorbed within less than a millimeter fits best the actual dimensions of the vessel wall's thickness. In a preferred embodiment, wavelength of approximately  $1470 \pm 60\text{nm}$  is used. Radiofrequency, microwave,  
15 thermal and other energy sources may be used to reliably and control ably perform the task and the method described, provided suitable enhancers and/or imaging means as described are used. Biological means such as growth factors or stimulants of collagen formation, for instance may be added to supplement and enhance the treatment effects by strengthening and speeding up the strengthening of the vessel structure.

In yet another preferred embodiment, specific radiation absorbers (and/or  
20 scattering enhancers) can be located at suitable positions inside the vessel wall or near the tissue to be treated, thus radiation can then selectively target tagged locations. If scatterers or absorbers are used with suitable wavelengths, energy can be transported through thicker zones. If, for instance, the absorber works at a wavelength of 980nm,  
25 then this wavelength can also be useful for treatment. Dye molecules could be suitable absorbers or scatterers.

Although the present invention has been disclosed for treating vessels in general, it is to be understood that it is not limited thereto and may be employed to treat hollow anatomical structures in other areas of the body which may be affected by  
30 diverse pathologies.

In another preferred embodiment, non-hollow anatomical structures can be treated. For example, firming of tissue or removal of fat or other undesired tissue such

as enlarged prostate tissue is rendered more efficient with present invention for several reasons. First of all, spinning system facilitates access of irradiation element to target tissue. Secondly, by spinning irradiation element while irradiating, a larger target area is reached in shorter time. Third, adherence between tissue and probe's  
5 distal end is prevented. Finally, in treatment techniques that require turning by surgeon, treatment becomes more reliable, as steadier and more constant rotation can be performed in comparison to manual rotation by surgeon.

Having described preferred embodiments of the invention with reference to  
10 the accompanying drawings, it is to be understood that the invention is not limited to the precise embodiments, and that various changes and modifications may be effected therein by skilled in the art without departing from the scope or spirit of the invention as defined in the appended claims.

**What is claimed is:**

1. A method of treating hollow anatomical structures in a mammal with an energy-transmission means, which rotates during treatment.
2. A method of treating vessels in a mammal wherein a treatment source delivers energy to inside walls of said vessel through an energy-transmission means coupled to said energy source and wherein said energy-transmitting means is rotating during treatment to minimize contact, or attraction to said walls.
3. The method of treating vessels according to claims 1 or 2, wherein rotating speed of said energy-transmitting means is coupled with its axial speed and amount of energy emitted.
4. A method of treating hollow anatomical structures in a mammal with an energy-transmission means, which rotates during treatment and withdrawal.
5. A method of treating vessels in a mammal wherein a treatment source delivers energy to inside walls of said vessel through an energy-transmission means coupled to said energy source and wherein said energy-transmitting means is rotating during withdrawal and emission of radiation treatment to minimize contact, or attraction to said walls.
6. The method of treating vessels according to claims 4 or 5, wherein rotating speed of said energy-transmitting means is coupled with its withdrawal speed and amount of energy emitted.
7. A treatment system to treat hollow anatomical structures in mammals comprising; an energy source, energy-transmission means; a rotation source coupled



to said transmission means, wherein said transmission means rotates during treatment to improve reliability and reproducibility of a treatment.

8. A vessel treatment system to treat vessels in mammals from within comprising: an energy source; energy-transmission means; a rotation source coupled to said transmission means at or near its proximal end; wherein said transmission means also has a distal end wherein energy is directed to said vessel walls; and wherein said transmission means rotates while being moved within said vessel, thus preventing/minimizing attachment/contact to said vessel wall.

9. A treatment system to treat hollow anatomical structures in mammals comprising: an energy source, energy-transmission means; a rotation source coupled to said transmission means, wherein said transmission means rotates during treatment and withdrawal to improve reliability and reproducibility of a treatment.

10. A vessel treatment system to treat vessels in mammals from within comprising: an energy source; energy-transmission means; a rotation source coupled to said transmission means at or near its proximal end; wherein said transmission means also has a distal end wherein energy is directed to said vessel walls; and wherein said transmission means rotates while being removed from said vessel, thus preventing/minimizing attachment/contact to said vessel wall.

11. The vessel treatment system according to claim 8 or 10, wherein said energy source is selected from the group of light sources, RF sources, MW sources and thermal sources.



12. The vessel treatment system according to claim 8 or 10, wherein said energy source is a light source and said energy transmission means is at least one optical fiber.

13. The vessel treatment system according to claim 8 or 10, wherein said energy source is embedded onto said transmission means proximal end and in close proximity to said rotation source.

14. The vessel treatment system according to claim 8 or 10, further comprising a means to regulate said rotation source, based on feedback from one or both of withdrawal speed and level energy output from said energy source.

15. The vessel treatment system according to claim 8 or 10, wherein said distal end of said energy-transmission means is positioned in said vessel section to be treated, so as to be off axis and structured so as to output energy directly at said vessel's wall, such as a off-axis firing fiber including side firing fibers, a twister fibers, radial tip fibers.

16. A treatment system to treat non-hollow anatomical structures in mammals comprising; an energy source, energy-transmission means; a rotation source coupled to said transmission means, wherein said transmission means rotates during treatment, minimizing adherence of said transmission means to said anatomical structure, and providing therefore improved reliability and reproducibility of said treatment .






Fig. 2






Fig. 3



**Fig 4**



**Fig. 5**