

PCT

WORLD INTELLECT
Int



INTERNATIONAL APPLICATION PUBLISHED

WO 9603490A1

(51) International Patent Classification ⁶ :
C11D 17/00, 3/33, 3/02, 7/06, 7/08, 7/12,
7/14

A1

(43) International Publication Date: 8 February 1996 (08.02.96)

(21) International Application Number: PCT/US95/08707

(22) International Filing Date: 12 July 1995 (12.07.95)

(30) Priority Data:
08/278,770 22 July 1994 (22.07.94) US
08/399,867 7 March 1995 (07.03.95) US

(71) Applicant: MONSANTO COMPANY [US/US]; 800 North Lindbergh Boulevard, St. Louis, MO 63167 (US).

(72) Inventors: BACKES, Thomas, Whitner; 15121 Stillhouse Creek Road, Chesterfield, MO 63017 (US). VERRETT, Sheldon, Philip; 20 Ladel Court, Olivette, MO 63132 (US). DINGMAN, Sean, Douglas; 1st floor, 6933 Garner Avenue, St. Louis, MO 63139 (US).

(74) Agent: BOLDING, James, Clifton; Monsanto Company, 800 North Lindbergh Boulevard, St. Louis, MO 63167 (US).

(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.

(54) Title: BLOCK DETERGENT CONTAINING NITRILOTRIACETIC ACID

(57) Abstract

A solid, block detergent containing an alkali metal salt of nitrilotriacetic acid, an acid, alkali metal containing hydroxides and silicates, and alkali metal containing carbonates and sulfates is taught. A process for producing the block detergent is also taught.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|----|--------------------------|----|--|----|--------------------------|
| AT | Austria | GB | United Kingdom | MR | Mauritania |
| AU | Australia | GE | Georgia | MW | Malawi |
| BB | Barbados | GN | Guinea | NE | Niger |
| BE | Belgium | GR | Greece | NL | Netherlands |
| BF | Burkina Faso | HU | Hungary | NO | Norway |
| BG | Bulgaria | IE | Ireland | NZ | New Zealand |
| BJ | Benin | IT | Italy | PL | Poland |
| BR | Brazil | JP | Japan | PT | Portugal |
| BY | Belarus | KE | Kenya | RO | Romania |
| CA | Canada | KG | Kyrgystan | RU | Russian Federation |
| CF | Central African Republic | KP | Democratic People's Republic of Korea | SD | Sudan |
| CG | Congo | KR | Republic of Korea | SE | Sweden |
| CH | Switzerland | KZ | Kazakhstan | SI | Slovenia |
| CI | Côte d'Ivoire | LI | Liechtenstein | SK | Slovakia |
| CM | Cameroon | LK | Sri Lanka | SN | Senegal |
| CN | China | LU | Luxembourg | TD | Chad |
| CS | Czechoslovakia | LV | Larvia | TG | Togo |
| CZ | Czech Republic | MC | Monaco | TJ | Tajikistan |
| DE | Germany | MD | Republic of Moldova | TT | Trinidad and Tobago |
| DK | Denmark | MG | Madagascar | UA | Ukraine |
| ES | Spain | ML | Mali | US | United States of America |
| FI | Finland | MN | Mongolia | UZ | Uzbekistan |
| FR | France | | | VN | Viet Nam |
| GA | Gabon | | | | |

BLOCK DETERGENT CONTAINING NITRILOTRIACETIC ACIDBACKGROUND OF THE INVENTION

5 This invention relates to solid detergent blocks. More particularly, this invention relates to a solid block detergent incorporating a salt of nitrilotriacetic acid as the primary builder and a method for preparing the solid block detergent.

DESCRIPTION OF THE PRIOR ART

10 In conventional institutional and industrial washing machines, detergents are added to the wash tank by means of automatic dispenser systems. These detergents generally have a high degree of alkalinity. Accordingly, they contain alkali metal hydroxides such as sodium hydroxide as well as chemicals that are particularly useful for hard surface cleaning. Examples of these include phosphates, silicates, chlorine-containing compounds, defoamers and organic polyelectrolyte polymers.

20 Solid detergents for machine washing were originally available in powder and granular forms. A serious problem with those forms of the detergent was the strong tendency of the material to cake or lump when it was exposed to small amounts of moisture or humidity. "Anticaking" agents were used; however, they were generally ineffective in the presence of larger amounts of moisture. The clumping or caking of the powder or granular detergent was avoided by producing the detergent in a block form.

30 Another major problem with automatic washing detergents is the inability of the detergents to be easily measured and dispensed. Solid block detergents provide a means whereby the safety, convenience and performance of the detergent and cleaning system can be enhanced. The use of solid, cast detergents minimizes contact between the user and the high performance or high alkalinity detergent composition.

35

-2-

Additionally, the block detergents provide ease in installation and replacement.

One problem found in both solid, cast block detergent compositions and in powder detergent
5 compositions is caused by the differing solubilities of the various components in water. The components of standard detergents dissolve at differing rates or have differing equilibrium solubilities, thus the first effluent from a solid, cast detergent may be
10 rich in certain compounds while lacking in other key detergent compounds causing the effectiveness of the detergent to vary greatly through the wash cycle or from washing to washing.

Various sequestrants have been incorporated
15 into the caustic melts with varying degrees of success. One sequestrant, sodium tripolyphosphate, is extremely effective.

U.S. Patent 4,569,780 outlines a method for making solid, cast detergents in which an alkali metal
20 hydroxide is heated to a temperature above its melt point and alkaline hydratable compounds, such as sodium tripolyphosphate present in an alkaline solution, are added to the melt.

U.S. Patent 4,753,755 teaches a process for
25 the production of a solid detergent. A hardness sequestering agent selected from the group consisting of alkali salts of nitrilotriacetic acid, phosphonic acid, glutonic acid, ethylene diamine tetraacetic acid or mixture thereof, which functions as a suitable
30 substitute for sodium tripolyphosphate, is mixed into an aqueous solution containing alkali metal hydroxides, alkali metal silicates and mixtures thereof. Alkali metal salts of nitrilotriacetate such as sodium nitrilotriacetate and the like are
35 preferred. An amount of a solid alkaline material is added to the dispersion to cause eventual solidification. However, the added solid alkaline

-3-

material is required to be the same alkaline material as used to produce the aqueous solution, that is, alkali metal hydroxides, alkali metal silicates and mixtures thereof.

5 In addition to the desire to produce a more effective solid, cast block detergent for use in washing systems, there is a desire to reduce the phosphate compounds present in effluent streams.

SUMMARY OF THE INVENTION

10 This invention is directed to a solid, block detergent produced from an alkali metal salt of nitrilotriacetic acid. The solid, block detergent contains:

- 15 a. from about 5% to about 60% by weight of the formulation alkali metal salt of nitrilotriacetic acid;
- b. from about 0.1% to about 10% by weight of the formulation acid;
- 20 c. from about 5% to about 40% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein when the alkali metal containing compound is an alkali metal hydroxide or a mixture containing an alkali metal hydroxide, the alkali metal containing compound must include
25 from about 0.1% to about 20% by weight of the formulation potassium hydroxide; and
- 30 d. from about 5% to about 25% by weight of the formulation of a second alkali metal containing compound selected from
35 the group consisting of alkali metal carbonates, alkali metal sulfates and

-4-

mixtures of alkali metal carbonates and alkali metal sulfates.

This invention is also directed to a process for producing a phosphate-free, solid, block detergent from an alkali metal salt of nitrilotriacetic acid comprising the steps of:

- a. preparing an aqueous alkaline solution containing from about 5% to about 40% by weight of the formulation of an alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali metal hydroxides must include from about 0.1% to about 20% by weight of the formulation potassium hydroxide;
- b. mixing from about 5% to about 60% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry;
- c. adding from about 0.1% to about 10% by weight of the formulation of an acid to the slurry;
- d. mixing from about 5% to about 25% by weight of the formulation of an alkali metal containing compound selected from the group consisting of alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
- e. curing the slurry.

-5-

The acid is preferably sulfuric acid, but other acids such as, for example nitric acid, phosphoric acid, acetic acid and formic acid may be used. The slurry is preferably cured, or allowed to solidify, in a mold to provide the block with the desired shape.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In accordance with the present invention, there is provided a phosphate-free, solid, block detergent produced from an alkali metal salt of nitrilotriacetic acid. The solid, cast block detergent contains:

- a. from about 5% to about 60% by weight of the formulation alkali metal salt of nitrilotriacetic acid;
- b. from about 0.1% to about 10% by weight of the formulation acid;
- c. from about 5% to about 40% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein when the alkali metal containing compound is an alkali metal hydroxide or a mixture containing an alkali metal hydroxide, the alkali metal containing compound must include from about 0.1% to about 20% by weight of the formulation potassium hydroxide; and
- d. from about 5% to about 25% by weight of the formulation of a second alkali metal containing compound selected from the group consisting of alkali metal carbonates, alkali metal sulfates and

-6-

mixtures of alkali metal carbonates and alkali metal sulfates.

The solid, block detergent of this invention contains from about 5% to about 60%, preferably from about 25% to about 50% and more preferably about 35%
5 to about 50%, by weight of the formulation of an alkali metal salt of nitrilotriacetic acid. Trisodium nitrilotriacetate monohydrate, sold commercially in powder form by Monsanto Company, is the preferred
10 alkali metal salt of nitrilotriacetic acid, but other alkali metal salts of nitrilotriacetic acid may be used. The salt is a hardness sequestering agent in the formulation which is capable of sequestering hardness caused by the presence of ions such as magnesium,
15 calcium and the like in the water used for washing. The trisodium nitrilotriacetate monohydrate does not contribute to the blocking process, that is, it does not absorb additional water, or absorbs only a very small amount, by hydration as generally required to
20 form solid, block detergents. Thus, the inclusion of substantial amounts of the alkali metal salt of nitrilotriacetic acid in the formulation requires more efficient performance from the other components of the formulation as the other components must provide all
25 of the hydration, the absorption of the water present into the solid crystals, that causes solidification of the slurry into a solid, block detergent.

The term "by weight of the formulation" used in this application means the amount or weight of the component "by weight based upon the total weight of
30 the finished solid, block detergent."

The solid block detergent also contains from about 0.1% to about 10%, preferably from about 2% to about 8% and more preferably from about 3% to about
35 6%, by weight of the formulation acid. The acid is preferably sulfuric acid, but other mineral acids such as nitric acid and phosphoric acid and low molecular

-7-

weight organic acids such as acetic acid and formic acid may be used. Examples of other acids which may be used include propionic acid, nitrilotriacetic acid, ethylene diamine tetra-acetic acid, diethylene

5 triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-1,1-diphosphonic acid, diethylene triamine

10 penta(methylene phosphonic acid), oxalic acid, succinic acid, adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid. Sulfuric acid is preferred because it provides

15 a strong neutralizing acid for the slurry and it forms a hydratable salt to improve the hardness of the resulting block detergent. When the acid is added to the slurry, a minor amount of heat is generated and cooling may be desired.

20 The addition of an acid to the formulation is in direct conflict with the processes generally used at the current time to produce solid block detergents. In the production of solid, block detergents, highly alkaline formulations are desired

25 and the addition of an acid reduces the pH of the formulation, a reduction that must be overcome by other components of the formulation. However, in the process of this invention, the acid addition is an important step in the production of the desired solid

30 block detergent. The acid partially neutralizes the alkali metal salts within the formulation, including the alkali metal salts of nitrilotriacetic acid, to contribute to the solidification of the block.

35 From about 5% to about 40%, and preferably from about 15% to about 30%, by weight of the formulation is an alkali metal containing compound selected from the group consisting of alkali metal

-8-

hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates. When the alkali metal containing compound is an alkali metal hydroxide or a mixture containing an alkali metal hydroxide, the alkali metal containing compound must include from about 0.1% to about 20%, and preferably from about 3% to about 8%, by weight of the formulation potassium hydroxide.

Sodium is the preferred alkali metal for both the hydroxides and the silicates, but other alkali metals may be used. Alkali metal silicates may be used in the production of the block detergent as set forth in this application without regard to the inclusion of other components in the formulation. However, when an alkali metal hydroxide such as sodium hydroxide, for example, which is frequently used in the preparation of block detergents, is included in the formulation, potassium hydroxide must also be included.

While Applicants are not bound by any theory by which the invention of this application operates, one possible explanation is that the inclusion of potassium containing compounds in the formulation may result in the formation of other salts containing combinations of the various cations in the mixture, specifically sodium, potassium and hydrogen. Some of these salts may be more capable of absorbing water by hydration than the original raw materials. It is the presence of mixed sodium potassium salts that is believed to cause the detergent blocks to harden. One likely example of this would be the reaction of sodium carbonate and potassium hydroxide to form sodium potassium carbonate, which exists in the solid form as a hexahydrate. Sodium potassium carbonate has a higher hydration capacity than either of the individual salts. Evidence for this is provided by the reaction when sodium carbonate was replaced by

-9-

sodium bicarbonate - the mixture hardened virtually instantaneously. It therefore appears that when sodium carbonate is combined with an acid, the exchange of a sodium from the carbonate for a proton from the acid (any acid) occurs, followed by reaction of the proton with available potassium to form the sodium potassium hydrating agent. Addition of the full sodium salt and an acid slows the ultimate formation of the mixed sodium potassium salt to provide sufficient time for the mixture to be transferred into a mold prior to solidification. Another possible example could be the formation of mixed salts of the nitrilotriacetate such as a potassium sodium salt.

Based upon this theory and recognizing that the process of this invention includes the addition of potassium salts, sodium salts and an acid, it appears possible that both the rate and extent of solidification of the slurry may be controlled by controlling the ratio of the three cations in the slurry. Detergent blocks containing the three cations appear to have more desirable physical and performance characteristics. The blocks are harder, as all of the free water is consumed by hydration, and during use the blocks dissolve from the surface at a controlled rate without absorption of excess water and the resulting, undesired softening of the detergent block.

From about 5% to about 25%, and preferably from about 10% to about 20%, by weight of the formulation is an alkali metal containing compound selected from the group consisting of alkali metal carbonates, alkali metal sulfates and mixtures of alkali metal carbonates and alkali metal sulfates which act as blocking agents. The alkali metal carbonate, and more specifically sodium carbonate, is preferred. However alkali metal sulfates, preferably sodium sulfate, may also be used.

-10-

Today block detergent products are produced by mixing detergent ingredients to form a pourable slurry which hardens upon curing into a solid brick. Typical constituents in the machine washing blocks are alkalinity sources such as caustic, sodium silicate and sodium carbonate; a builder such as sodium tripolyphosphate; water; and a chlorine source such as sodium hypochlorite.

In the solid, block detergent of this invention, an alkali metal salt of nitrilotriacetic acid such as sodium nitrilotriacetate is used as the builder to produce a solid, cast block detergent. This detergent will reduce the phosphate compounds present in effluent streams. Block detergents produced by this process also show no tendency to expand during curing or solidification which can be a problem with phosphate containing formulations.

This invention is also directed to a process for producing a phosphate-free, solid, cast block detergent. Detergent blocks are produced by mixing hydratable compounds with water to form a slurry which forms a block through the hydration of the component ingredients. In general terms the process includes the steps of (1) blending water with silicate and caustic compounds to produce an aqueous alkaline solution, (2) mixing an alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry, (3) adding an acid to the slurry, (4) mixing carbonate or sulfate compounds into the slurry, and (5) curing or solidifying the slurry in a mold.

More specifically this invention is directed to a process for producing a solid, block detergent from an alkali metal salt of nitrilotriacetic acid comprising the steps of:

- a. preparing an aqueous alkaline solution containing from about 5% to about 40%,

-11-

- 5 and preferably from about 15% to about 30%, by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali metal hydroxides must include sufficient potassium hydroxide to constitute from about 0.1% to about 20%, and preferably from about 3% to about 8%, by weight of the formulation;
- 10
- 15 b. mixing from about 5% to about 60%, preferably about 25% to about 50% and more preferably from about 35% to about 50%, by weight of the formulation of an alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry;
- 20
- c. adding from about 0.1% to about 10%, preferably from about 2% to about 8% and more preferably from about 3% to about 6%, by weight of the formulation of an acid to the slurry;
- 25
- d. mixing from about 5% to about 25%, and preferably from about 10% to about 20%, by weight of the formulation of a second alkali metal containing compound selected from the group consisting of alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
- 30
- 35 e. curing the slurry.

-12-

The acid is preferably sulfuric acid, but other mineral acids such as nitric acid and phosphoric acid and low molecular weight organic acids such as acetic acid and formic acid may be used. Examples of other acids which may be used include propionic acid, nitrilotriacetic acid, ethylene diamine tetra-acetic acid, diethylene triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-1,1-diphosphonic acid, diethylene triamine penta(methylene phosphonic acid), oxalic acid, succinic acid, adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid. Sulfuric acid is preferred because it provides a strong neutralizing acid for the slurry and it forms a hydratable salt to improve the hardness of the resulting block detergent. When the acid is added to the slurry, a minor amount of heat is generated and cooling may be desired. The slurry is preferably cured, or allowed to solidify, in a mold to provide the block with the desired shape.

Key considerations in the production of detergent blocks are the process rheology, cure times, and block expansion. The processing and product characteristics are controlled by the selection and concentrations of hydratable constituents. Variations in the composition of the formulation will cause differences in the cycle time, that is the time from the beginning of the process until a solid block detergent is formed. Variations in the composition of the formulation will also cause differences in the physical characteristics of the slurry, particularly the handling characteristics, and in properties of the block detergent such as the hardness and solubility.

-13-

This invention requires the use of an alkali metal salt of nitrilotriacetic acid, which is preferably the sodium salt, and an acid, which is preferably sulfuric acid. These two components of the formulation may be added by two separate steps in the process, as discussed above, in which the alkali metal salt of nitrilotriacetic acid is the preferred trisodium nitrilotriacetate monohydrate, sold commercially in powder form by Monsanto Company, and the acid is the preferred sulfuric acid.

Alternatively, the alkali metal salt of nitrilotriacetic acid and the acid can be added to the process together in one process step in the form of an acid treated alkali metal salt of nitrilotriacetic acid. The acid treated alkali metal salt of nitrilotriacetic acid forms a solid, granular product which can replace the trisodium nitrilotriacetate monohydrate powder and acid in the process and eliminate one process step.

One process for the production of the granular, acid treated alkali metal salt of nitrilotriacetic acid produces granular alkali metal nitrilotriacetate having a density of from about 0.70g/cc to about .81g/cc and absorptivity of surfactant in the range of from about 12 to 14 ml/100g. The process comprises the steps of (1) contacting trisodium nitrilotriacetate monohydrate powder with an aqueous solution containing from about 35% to about 60%, by weight, sulfuric acid; (2) mixing the wetted trisodium nitrilotriacetate monohydrate powder providing an acid addition time/mixing time ratio in the range of above about .75 to about 1; and (3) drying the granules.

When the granular, acid treated alkali metal salt of nitrilotriacetic acid is used in the process of this invention to produce a phosphate-free, solid, block detergent from an alkali metal salt of

-14-

nitrilotriacetic acid, the acid addition step is deleted and the process comprises the steps of:

- a. preparing an aqueous alkaline solution containing from about 5% to about 40%, and preferably from about 15% to about 30%, by weight of the formulation of an alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali metal hydroxides must include from about 0.1% to about 20%, and preferably from about 3% to about 8%, by weight of the formulation potassium hydroxide;
- b. mixing from about 5% to about 60%, preferably about 25% to about 50% and more preferably from about 35% to about 50%, by weight of the formulation of a granular, acid treated alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry;
- c. mixing from about 5% to about 25%, and preferably from about 10% to about 20%, by weight of the formulation of a blocking agent selected from the group consisting of alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
- d. curing the slurry.

Free hydroxide ions, provided as an alkali metal salt which is preferably sodium hydroxide and potassium hydroxide, are used to saponify soils and to

-15-

cut greases rapidly in industrial and institutional
cleaners. Increased levels are often used in
applications with routine heavy soil loadings. These
hydroxides can be used in block detergents in either
5 anhydrous or solution forms. Use of the solution form
of the hydroxide reduces temperature exotherms
associated with the heats of solution and hydration.

Silicates such as sodium silicates are added
to block detergents to provide improved corrosion
10 protection for overglaze, glassware and soft metal
applications. The silicates provide an alkalinity
source and also improve fluidity during the pour
cycle. Sodium metasilicates and liquid silicates such
as RU[®] Silicate (SiO₂/Na₂O ratio = 2.4) provided by PQ
15 Corporation are typically used in formulations.

Sodium carbonate (soda ash) finds widespread
use in detergent products as a low-cost alkalinity
source. In detergent blocks, anhydrous sodium
carbonate is used to bind water through hydration.

20 Surfactants should be selected for a low
foaming profile as they act as a defoamer for food
oils, help the caustic to wet and assist in the final
rinsing of the caustic. In highly built detergent
blocks, physical separation of surfactants from the
25 process mixture is another important consideration.
The surfactants typically used in block detergents are
ethoxylated propoxylated block copolymers such as
Polytergent SLF-18[®] produced by Olin Corporation and
Plurafac RA-25[®] produced by BASF Corporation. Other
30 well known surfactants include alcohol alkoxyates,
alkyl aryl alkoxyates, alkylene oxide adducts of
hydrophobic bases and alkoxyates of linear aliphatic
alcohols. Surfactant concentrations are generally
less than 2% in the block.

35 Deionized water is recommended for use in
block detergent manufacture to maximize the total
builder or hardness ion control capability in the end

-16-

use. Water which contains calcium or magnesium ions can result in increased cure times.

Sodium sulfate is sometimes used in block detergent formulations as a filler and processing aid.

5 There are other compounds which may be added to the formulation, if desired, including polymeric electrolytes such as polyacrylates which are anti-redeposition or anti-spotting agents, agents to reduce mineral deposits in the equipment, dyes, fragrances,
10 and non-chlorinated bleaching agents such as sodium perborates and peroxide bleaches.

 The process of this invention takes place at or near ambient temperature, between 20°C. and 40°C. During the addition of the acid to the slurry, a minor
15 amount of heat may be generated and cooling may be desired, but it is not required. No outside heating source is required for the mixing of the components or for the curing or solidification of the slurry into
20 the block detergent.

 Mixing equipment should be selected which accommodates the physical transition from thin liquids to pasty slurries. Viscosities of the processed materials range from a few centipoise during the early
25 process steps to a few thousand centipoise when the slurry is ready for curing or solidification in a mold. Thus mixers such as a Hobart mixer or a high intensity anchor type proximity agitation system should be considered.

 This invention will be explained in detail
30 in accordance with the examples below, which are for illustrative purposes only and shall not limit the present invention.

Example I

 A mixture of 16 grams of deionized water,
35 two grams of a low foam anionic surfactant, alkylated diphenyl oxide disulfate (Dowfax 3B2® from Dow Chemical Company), and 29 grams of a 47% solution of

-17-

sodium silicate with a $\text{SiO}_2/\text{Na}_2\text{O}$ ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) was stirred in a 250 milliliter slurry cup for 5 minutes. To the mixture were added 25 grams of hydratable, granular sodium nitrilotriacetic acid, produced by agglomerating trisodium nitrilotriacetate with aqueous sulfuric acid and drying, and 28 grams of sodium carbonate. The slurry was mixed for 10 minutes and poured into a hexagonal mold. The slurry formed a solid, cast detergent in about 2 hours.

Example II

A mixture of 10 grams of deionized water, two grams of a low foam alcohol ethoxylate surfactant (Tergitol 15-S-9[®] from Union Carbide Corporation), 20 grams of a 47% solution of sodium silicate with a $\text{SiO}_2/\text{Na}_2\text{O}$ ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) and 10 grams of a 50% solution of sodium hydroxide was stirred in a 250 milliliter slurry cup for 5 minutes. The solids, 43 grams of hydratable, granular sodium nitrilotriacetic acid and 15 grams of sodium carbonate, were blended prior to their addition to the mixture. The blended solids were gradually added to the liquid mixture while increasing the mechanical stirring to a maximum of 500 rpm. The slurry was stirred for 5 minutes and poured into a hexagonal mold. The slurry formed a solid, cast detergent in about 6 hours.

Example III

A mixture of 30 grams of deionized water, 2 grams of a low foam anionic surfactant, alkylated diphenyl oxide disulfonate (Dowfax 3B2[®] from Dow Chemical Company) and 20 grams of a 47% solution of sodium silicate with a $\text{SiO}_2/\text{Na}_2\text{O}$ ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) was stirred in a 250 milliliter beaker, forming a clear solution. A slurry was formed by adding 33 grams of granulated sodium nitrilotriacetate to the solution. The

-18-

granulated nitrilotriacetate was produced by agglomerating trisodium nitrilotriacetate with aqueous sulfuric acid and drying. The slurry was mixed for approximately 2 minutes to achieve uniformity and 15 grams of sodium carbonate were then added. This final slurry was mixed for approximately 5 minutes, after which it was poured into a mold. The slurry solidified over a period of a few hours, producing a block that was sufficiently solid to be removed from the mold. The surface of the block was dry and yielded only slightly to attempts to deform it with thumb pressure.

Example IV

A mixture of 2 grams of a low foam anionic surfactant, alkylated diphenyl oxide disulfonate (Dowfax 3B2[®] from Dow Chemical Company), 30 grams of a 47% solution of sodium silicate with a SiO₂/Na₂O ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) and 10 grams of a 50% solution of aqueous potassium hydroxide was stirred in a 250 milliliter beaker, forming a clear solution. A slurry was formed by adding 48 grams of granulated sodium nitrilotriacetate to the solution. The granulated nitrilotriacetate was produced by agglomerating trisodium nitrilotriacetate with aqueous sulfuric acid and drying. The slurry was mixed for approximately 2 minutes to achieve uniformity and 10 grams of sodium carbonate were then added. This final slurry was mixed for approximately 5 minutes, after which it was poured into a mold. The slurry solidified over a period of a few hours, producing a block that was sufficiently solid to be removed from the mold. The surface of the block was dry and did not yield to attempts to deform it with thumb pressure.

35

Example V

A mixture of 8 grams of deionized water, 2 grams of a low foam anionic surfactant, alkylated

-19-

diphenyl oxide disulfonate (Dowfax 3B2[®] from Dow Chemical Company), 20 grams of a 47% solution of sodium silicate with a SiO₂/Na₂O ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) and 10 grams of a 50% solution of aqueous potassium hydroxide was stirred in a 250 milliliter beaker, forming a clear solution. A slurry was formed by adding 40 grams of trisodium nitrilotriacetate monohydrate powder (NTA from Monsanto Company) to the solution. The slurry was stirred as 5 grams of 98% sulfuric acid were added over a period of approximately 5 minutes. The acid feed rate was selected based upon the ability of the agitator to disperse localized concentrations of acid to maintain a constant temperature and to prevent localized boiling caused by the heat of neutralization at the point of acid addition. Following the acid addition, the slurry was mixed for approximately 2 minutes to achieve uniformity and 15 grams of sodium carbonate were then added. This final slurry was mixed for approximately 5 minutes, after which it was poured into a mold. The slurry solidified over a period of a few hours, producing a block that was sufficiently solid to be removed from the mold. The surface of the block was dry and did not yield to attempts to deform it with thumb pressure.

Example VI

A mixture of 8 grams of deionized water, 2 grams of a low foam anionic surfactant, alkylated diphenyl oxide sulfonate (Dowfax 3B2[®] from Dow Chemical Company), 20 grams of a 47% solution of sodium silicate with a SiO₂/Na₂O ratio of 2.40 (RU[®] Sodium Silicate from PQ Corporation) and 10 grams of a 50% solution of aqueous potassium hydroxide was stirred in a 250 milliliter beaker, forming a clear solution. A slurry was produced by adding 40 grams of trisodium nitrilotriacetate monohydrate powder (NTA from Monsanto Company) to the solution. The slurry

-20-

was stirred as 2 grams of 85% phosphoric acid was added over a period of about 2 minutes. Following acid addition, 18 grams of sodium carbonate were added. The final slurry was then stirred for about 5
5 minutes, after which it was poured into a mold. The slurry solidified over a period of a few hours, producing a very hard, solid block.

It will be apparent from the examples that many other variations and modifications may be made in
10 the compositions and processes described without departing from the concept and spirit of the invention. Accordingly, it should be understood that the description and examples are illustrative only and are not intended to limit the scope of the invention.

15

We claim:

1. A solid, block detergent comprising:
 - a. from about 5% to about 60% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid;
 - b. from about 0.1% to about 10% by weight of the formulation of acid;
 - c. from about 5% to about 40% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein when the alkali metal containing compound is an alkali metal hydroxide or a mixture containing an alkali metal hydroxide, the alkali metal containing compound must include from about 0.1% to about 20% by weight of the formulation potassium hydroxide; and
 - d. from about 5% to about 25% by weight of the formulation of a second alkali metal containing compound selected from the group consisting of alkali metal carbonates, alkali metal sulfates and mixtures of alkali metal carbonates and alkali metal sulfates.
2. The solid, block detergent of claim 1 wherein the alkali metal salt of nitrilotriacetic acid is from about 25% to about 50% by weight of the formulation.
3. The solid, block detergent of claim 2 wherein the alkali metal salt of nitrilotriacetic acid is from about 35% to about 50% by weight of the formulation.

-22-

4. The solid, block detergent of claim 1 wherein the alkali metal salt of nitrilotriacetic acid is trisodium nitrilotriacetate monohydrate.

5. The solid, block detergent of claim 1 wherein the acid is from about 2% to about 8% by weight of the formulation.

6. The solid, block detergent of claim 5 wherein the acid is from about 3% to about 6% by weight of the formulation.

7. The solid, block detergent of claim 1 wherein the acid is selected from the group consisting of sulfuric acid, nitric acid, phosphoric acid, acetic acid, formic acid, propionic acid, nitrilotriacetic acid, ethylene diamine tetra-acetic acid, diethylene triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-1,1-diphosphonic acid, diethylene triamine penta(methylene phosphonic acid), oxalic acid, succinic acid, adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid.

8. The solid, block detergent of claim 7 wherein the acid is sulfuric acid.

9. The solid, block detergent of claim 1 wherein the first alkali metal compound is from about 15% to about 30% by weight of the formulation.

10. The solid, block detergent of claim 9 wherein the first alkali metal compound must include from about 3% to about 8% by weight of the formulation potassium hydroxide.

11. The solid, block detergent of claim 1 wherein the first alkali metal compound is selected from the group consisting of alkali metal hydroxides

-23-

and mixtures of alkali metal hydroxides and alkali metal silicates.

12. The solid, block detergent of claim 11 wherein the first alkali metal compound is sodium hydroxide.

13. The solid, block detergent of claim 1 wherein the first alkali metal compound must include from about 3% to about 8% by weight of the formulation potassium hydroxide.

14. The solid, block detergent of claim 1 wherein the second alkali metal compound is from about 10% to about 20% by weight of the formulation.

15. The solid, block detergent of claim 1 wherein the second alkali metal compound is sodium carbonate.

16. The solid, block detergent of claim 1 wherein the second alkali metal compound is sodium sulfate.

17. The solid, block detergent of claim 1 comprising:

- a. from about 35% to about 50% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid;
- b. from about 3% to about 6% by weight of the formulation of an acid selected from the group consisting of sulfuric acid, nitric acid, phosphoric acid, acetic acid, formic acid, propionic acid, nitrilotriacetic acid, ethylene diamine tetra-acetic acid, diethylene triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-1,1-diphosphonic acid, diethylene triamine penta(methylene phosphonic acid),

-24-

- 5 oxalic acid, succinic acid, adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid;
- 10 c. from about 15% to about 30% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein when the alkali
- 15 metal containing compound is an alkali metal hydroxide or a mixture containing an alkali metal hydroxide, the alkali metal containing compound must include from about 3% to about 8% by weight of
- 20 the formulation potassium hydroxide; and
- 25 d. from about 10% to about 20% by weight of the formulation of a second alkali metal containing compound selected from the group consisting of alkali metal carbonates, alkali metal sulfates and mixtures of alkali metal carbonates and alkali metal sulfates.
- 30 18. The solid, block detergent of claim 1 comprising:
- a. from about 35% to about 50% by weight of the formulation trisodium nitrilotriacetate monohydrate;
- 35 b. from about 3% to about 6% by weight of the formulation sulfuric acid;
- c. from about 15% to about 30% by weight of the formulation of a mixture of

-25-

- sodium hydroxide and from about 3% to about 8% by weight of the formulation potassium hydroxide; and
- 5 d. from about 10% to about 20% by weight of the formulation of sodium carbonate.
19. The solid, block detergent of claim 1 comprising:
- 10 a. from about 35% to about 50% by weight of the formulation trisodium nitrilotriacetate monohydrate;
- b. from about 3% to about 6% by weight of the formulation sulfuric acid;
- c. from about 15% to about 30% by weight of the formulation of sodium silicate;
- 15 and
- d. from about 10% to about 20% by weight of the formulation of sodium carbonate.
20. A process for producing a solid, block detergent comprising the steps of:
- 20 a. preparing an aqueous alkaline solution containing from about 5% to about 40% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of
- 25 alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali
- 30 metal hydroxides must include sufficient potassium hydroxide to constitute from about 0.1% to about 20% by weight of the formulation;
- 35 b. mixing from about 5% to about 60% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid

-26-

into the aqueous alkaline solution to form a slurry;

- 5 c. adding from about 0.1% to about 10% by weight of the formulation of an acid to the slurry;
- d. mixing from about 5% to about 25% by weight of the formulation of a second alkali metal containing compound selected from the group consisting of
10 alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
- e. curing the slurry.

15 21. The process of claim 20 in which the aqueous alkaline solution contains from about 15% to about 30% by weight of the formulation of the first alkali metal containing compound.

20 22. The process of claim 21 in which the first alkali metal compound in the aqueous alkaline solution is selected from the group consisting of alkali metal hydroxides and mixtures of alkali metal hydroxides and silicates.

25 23. The process of claim 22 in which the first alkali metal compound in the aqueous alkaline solution is sodium hydroxide.

30 24. The process of claim 20 in which, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali metal hydroxides must include sufficient potassium hydroxide to constitute from about 3% to about 8% of the weight of the formulation.

35 25. The process of claim 20 which includes mixing from about 25% to about 50% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry.

-27-

26. The process of claim 25 which includes mixing from about 35% to about 50% by weight of the formulation of an alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry.

27. The process of claim 20 in which the alkali metal salt of nitrilotriacetic acid is trisodium nitrilotriacetate monohydrate.

28. The process of claim 20 which includes adding from about 2% to about 8% by weight of the formulation of an acid to the slurry.

29. The process of claim 28 which includes adding from about 3% to about 6% by weight of the formulation of an acid to the slurry.

30. The process of claim 20 in which the acid is selected from the group consisting of sulfuric acid, nitric acid, phosphoric acid, acetic acid, formic acid, propionic acid, nitrilotriacetic acid, ethylene diamine tetra-acetic acid, diethylene triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-1,1-diphosphonic acid, diethylene triamine penta(methylene phosphonic acid), oxalic acid, succinic acid, adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid.

31. The process of claim 30 in which the acid is sulfuric acid.

32. The process of claim 20 which includes mixing from about 10% to about 20% by weight of the formulation of the second alkali metal containing compound into the slurry.

-28-

33. The process of claim 20 in which the second alkali metal containing compound is sodium carbonate.

34. The process of claim 20 which includes:
- 5 a. preparing an aqueous alkaline solution containing from about 15% to about 30% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of
- 10 alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali
- 15 metal hydroxides must include sufficient potassium hydroxide to constitute from about 3% to about 8% by weight of the formulation;
- 20 b. mixing from about 35% to about 50% by weight of the formulation of trisodium nitrilotriacetate monohydrate into the aqueous alkaline solution to form a slurry;
- 25 c. adding from about 3% to about 6% by weight of the formulation of an acid selected from the group consisting of sulfuric acid, nitric acid, acetic acid, formic acid, propionic acid, nitrilotriacetic acid, ethylene diamine
- 30 tetra-acetic acid, diethylene triamine pentaacetic acid, hydroxy ethylene diamine tetra-acetic acid, amino acids, polyamino acids, amino tri(methylene phosphonic acid), 1-hydroxyethylidene-
- 35 1,1-diphosphonic acid, diethylene triamine penta(methylene phosphonic acid), oxalic acid, succinic acid,

-29-

- adipic acid, citric acid, maleic acid, malic acid, fumaric acid, tartaric acid, gluconic acid, benzoic acid, ascorbic acid, sorbic acid, linear alkylbenzene sulfonic acid, polyacrylic acid and boric acid to the slurry;
- 5
- d. mixing from about 10% to about 20% by weight of the formulation of a second alkali metal containing compound
- 10 selected from the group consisting of alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
- 15 e. curing the slurry.
35. The process of claim 34 which includes:
- a. preparing an aqueous alkaline solution containing from about 15% to about 30% by weight of the formulation of an
- 20 alkali metal hydroxides which must include sufficient potassium hydroxide to constitute from about 3% to about 8% by weight of the formulation;
- b. mixing from about 35% to about 50% by weight of the formulation of trisodium nitrilotriacetate monohydrate into the aqueous alkaline solution to form a
- 25 slurry;
- c. adding from about 3% to about 6% by weight of the formulation of sulfuric acid to the slurry;
- 30 d. mixing from about 10% to about 20% by weight of the formulation of sodium carbonate into the slurry; and
- 35 e. curing the slurry.

-30-

36. A process for producing a solid, block detergent comprising the steps of:

- 5
- 10
- 15
- 20
- 25
- 30
- a. preparing an aqueous alkaline solution containing from about 5% to about 40% by weight of the formulation of a first alkali metal containing compound selected from the group consisting of alkali metal hydroxides, alkali metal silicates and mixtures of alkali metal hydroxides and silicates, wherein, when the aqueous alkaline solution contains alkali metal hydroxides, the alkali metal hydroxides must include sufficient potassium hydroxide to constitute from about 0.1% to about 20% by weight of the formulation;
 - b. mixing from about 5% to about 60% by weight of the formulation of a granular, acid treated alkali metal salt of nitrilotriacetic acid into the aqueous alkaline solution to form a slurry;
 - c. mixing from about 5% to about 25% by weight of the formulation of a second alkali metal containing compound selected from the group consisting of alkali metal sulfates, alkali metal carbonates and mixtures of alkali metal sulfates and alkali metal carbonates into the slurry; and
 - d. curing the slurry.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 95/08707

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 C11D17/00 C11D3/33 C11D3/02 C11D7/06 C11D7/08
 C11D7/12 C11D7/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|---------------------------|
| A | WO,A,92 07929 (ECOLAB INC) 14 May 1992 see claims 1,4-27 --- | 1,2,9, 11,12, 15,20 |
| A | WO,A,92 13061 (ECOLAB INC) 6 August 1992 see claims; example 28; table 1 --- | 1,2,4,9, 11,12,20 |
| A | EP,A,0 340 589 (HENKEL KGAA) 8 November 1989 see claims 1-9 --- | 1,2,4,20 |
| A | EP,A,0 203 523 (HENKEL KGAA) 3 December 1986 see claims; examples --- | 1,9,20 |
| | -/-- | |

Further documents are listed in the continuation of box C. Patent family members are listed in annex.

* Special categories of cited documents :

| | |
|--|--|
| <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> | <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> |
|--|--|

| | |
|--|---|
| Date of the actual completion of the international search 20 November 1995 | Date of mailing of the international search report 24.11.1995 |
|--|---|

| | |
|--|--|
| Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016 | Authorized officer Grittern, A |
|--|--|

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 95/08707

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|-----------------------|
| A | US,A,4 753 755 (GANSSE ROBERT E) 28 June 1988 cited in the application see claims; examples ----- | 1-4,20 |

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

| |
|--|
| International Application No PCT/US 95/08707 |
|--|

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|--|------------------|-------------------------|------------------|
| WO-A-9207929 | 14-05-92 | US-A- 5340501 | 23-08-94 |
| | | CA-A- 2093021 | 02-05-92 |
| | | EP-A- 0555218 | 18-08-93 |
| | | JP-T- 6501717 | 24-02-94 |
| | | | |
| WO-A-9213061 | 06-08-92 | AU-B- 663483 | 12-10-95 |
| | | AU-B- 1225092 | 27-08-92 |
| | | EP-A- 0569445 | 18-11-93 |
| | | JP-T- 6505280 | 16-06-94 |
| | | NZ-A- 239112 | 22-12-94 |
| | | | |
| EP-A-0340589 | 08-11-89 | DE-A- 3814857 | 16-11-89 |
| | | WO-A- 8910957 | 16-11-89 |
| | | WO-A- 8910995 | 16-11-89 |
| | | EP-A, B 0340588 | 08-11-89 |
| | | EP-A- 0415955 | 13-03-91 |
| | | EP-A- 0415968 | 13-03-91 |
| | | FI-B- 91646 | 15-04-94 |
| | | JP-T- 3504088 | 12-09-91 |
| US-A- 5167350 | 01-12-92 | | |
| | | | |
| EP-A-0203523 | 03-12-86 | DE-A- 3519353 | 04-12-86 |
| | | | |
| US-A-4753755 | 28-06-88 | NONE | |
| | | | |