



US010890474B2

(12) **United States Patent**
Bestic et al.

(10) **Patent No.:** **US 10,890,474 B2**
(45) **Date of Patent:** **Jan. 12, 2021**

(54) **FLUID MONITORING MODULE ARRANGEMENTS**
(71) Applicant: **Swagelok Company**, Solon, OH (US)
(72) Inventors: **Michael D. Bestic**, Sagamore Hills, OH (US); **David J. Hasak**, Concord, OH (US); **Bryan S. Reiger**, Willowick, OH (US); **Andrew Creque**, Macedonia, OH (US); **Marius O. Stroescu**, Mayfield Hts., OH (US); **William Michael Ponikvar**, Sagamore Hills, OH (US); **Cal R. Brown**, Lyndhurst, OH (US); **Matthew R. Dixon**, Parma, OH (US); **Joshua Webb**, Stow, OH (US); **Theodore J. Gausman**, Lyndhurst, OH (US); **Michael Whisler**, Southington, OH (US); **Randy Rieken**, Littleton, CO (US); **Robert Bianco**, Columbia Station, OH (US); **Andrew P. Marshall**, University Heights, OH (US)

(73) Assignee: **SWAGELOK COMPANY**, Solon, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/573,289**

(22) Filed: **Sep. 17, 2019**

(65) **Prior Publication Data**
US 2020/0088558 A1 Mar. 19, 2020

Related U.S. Application Data
(60) Provisional application No. 62/895,115, filed on Sep. 3, 2019, provisional application No. 62/844,399, filed (Continued)

(51) **Int. Cl.**
G01F 1/88 (2006.01)
G01F 1/40 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G01F 1/88** (2013.01); **G01F 1/363** (2013.01); **G01F 1/40** (2013.01); **G08C 17/02** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

4,153,083 A 5/1979 Imler
4,576,204 A 3/1986 Smallhorn
(Continued)

FOREIGN PATENT DOCUMENTS


CN 203117796 8/2013
EP 1369672 7/2009
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion from PCT/US2019/051375 dated Jan. 27, 2020.
(Continued)

Primary Examiner — Harshad R Patel
(74) *Attorney, Agent, or Firm* — Calfee, Halter & Griswold LLP

(57) **ABSTRACT**
A fluid monitoring module includes a flow sensing device and a controller disposed in an enclosure. The flow sensing device includes a body including an inlet port, an outlet port, an upstream sensor port, a downstream sensor port, and a flow passage disposed between the inlet port and the outlet port, and between the upstream sensor port and the downstream sensor port. A first fluid sensor is assembled with the upstream sensor port, and a second fluid sensor is assembled with the downstream sensor port. The controller is in circuit communication with the first and second fluid sensors for receiving at least one of pressure indicating signals and
(Continued)



temperature indicating signals from each of the first and second fluid sensors, and for measuring fluid data based on the received signals.

21 Claims, 33 Drawing Sheets

Related U.S. Application Data

on May 7, 2019, provisional application No. 62/844,390, filed on May 7, 2019, provisional application No. 62/844,383, filed on May 7, 2019, provisional application No. 62/775,066, filed on Dec. 4, 2018, provisional application No. 62/732,848, filed on Sep. 18, 2018.

(51) **Int. Cl.**

G01F 1/36 (2006.01)
G08C 17/02 (2006.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,930,357 A * 6/1990 Thurston G01F 1/3227
137/833
5,174,765 A * 12/1992 Williams E21B 17/028
439/86
5,295,790 A 3/1994 Bossart
5,303,731 A 4/1994 Vavra
5,361,676 A * 11/1994 Gibbs B64G 1/641
102/378
5,415,065 A * 5/1995 McMills B25B 13/06
81/124.2
5,454,945 A 10/1995 Spearman
5,469,749 A * 11/1995 Shimada G01F 1/363
73/721
5,535,633 A * 7/1996 Kofoed A61B 5/087
73/861.52
5,576,498 A 11/1996 Shambayati
5,672,832 A * 9/1997 Cucci G01F 1/44
73/861.52
5,750,892 A 5/1998 Huang
5,893,354 A 4/1999 Detweiler
6,436,720 B1 8/2002 Oberbeck
6,539,968 B1 4/2003 White
6,561,010 B2 5/2003 Wilson
6,609,431 B1 * 8/2003 Tietsworth B67D 1/0855
73/861.52
6,843,139 B2 1/2005 Schumacher
7,096,738 B2 * 8/2006 Schumacher G01F 1/383
73/718
7,447,599 B2 11/2008 Ellender et al.
7,729,869 B2 6/2010 Brown
7,740,024 B2 6/2010 Brodeur
7,775,126 B2 * 8/2010 Eckhardt A61M 5/14
604/131
7,784,361 B2 * 8/2010 Wiedmann G01F 1/40
73/861.52
7,891,256 B2 * 2/2011 Ushigusa G01F 1/363
73/861.52

7,942,069 B2 * 5/2011 Peterson G01F 1/36
73/716
8,082,946 B2 12/2011 Laverdiere
8,281,669 B2 * 10/2012 Ertl G01F 1/363
73/272 R
8,281,817 B2 10/2012 Tinker
8,297,478 B2 10/2012 Hughes
8,376,312 B2 2/2013 Mudd
8,418,549 B2 4/2013 Speldrich
8,656,772 B2 2/2014 Qasimi
8,718,954 B2 5/2014 vonBlumenthal
8,746,057 B2 6/2014 Yasuda
8,826,731 B2 9/2014 Speldrich
9,494,947 B2 11/2016 Hirata
9,562,796 B2 2/2017 Lull
9,683,429 B2 6/2017 Mathiesen
9,752,486 B2 9/2017 Yang
10,087,943 B2 10/2018 Taketomi
2001/0032674 A1 10/2001 Brunet
2002/0002425 A1 * 1/2002 Dossey G01F 1/44
700/284
2003/0061888 A1 * 4/2003 Gould G01F 1/38
73/861.52
2004/0083807 A1 5/2004 Mudd
2004/0177703 A1 * 9/2004 Schumacher G01F 1/363
73/861.52
2006/0010989 A1 * 1/2006 Clark A61M 5/16813
73/861.53
2007/0017303 A1 * 1/2007 Fujiwara G01F 15/00
73/861.52
2007/0151366 A1 * 7/2007 McDonald G01F 1/44
73/861.63
2008/0250854 A1 10/2008 Ding
2009/0157040 A1 * 6/2009 Jacobson A61M 5/16804
604/505
2009/0221986 A1 * 9/2009 Wang A61M 5/16877
604/503
2013/0247995 A1 9/2013 Erlich
2014/0116217 A1 5/2014 Hashish et al.
2016/0076909 A1 * 3/2016 Klicpera G01F 15/066
73/198
2017/0060143 A1 3/2017 Ding et al.
2017/0292864 A1 * 10/2017 Zhang G01F 1/6845
2018/0246533 A1 8/2018 Somani
2019/0321815 A1 * 10/2019 Schmid G01N 35/1072

FOREIGN PATENT DOCUMENTS

EP 980507 7/2011
EP 2703787 9/2015
EP 2787329 2/2017
GB 2150039 1/1988
JP 3244849 1/2002
JP 2004157719 6/2004
KR 1855746 6/2018
WO 2017049782 3/2017

OTHER PUBLICATIONS

International Search Report and Written Opinion from PCT/US2019/051618 dated Jan. 27, 2020.

* cited by examiner




FIG. 1




FIG. 1A




FIG. 1B




FIG. 2






FIG. 3






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13C




FIG. 13B




FIG. 13A




FIG. 14A




FIG. 14C




FIG. 14B




FIG. 14E




FIG. 14D




FIG. 14G




FIG. 14F




FIG. 14I




FIG. 14H




FIG. 15




FIG. 16B

FIG. 16A




FIG. 16D




FIG. 16C




FIG. 18A




FIG. 16E




FIG. 17




FIG. 18C




FIG. 18B




FIG. 18E




FIG. 18D




FIG. 19





FIG. 20






FIG. 22




FIG. 23

FLUID MONITORING MODULE ARRANGEMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to and all benefit of U.S. Provisional Patent Application Ser. No. 62/732,848, filed on Sep. 18, 2018 and entitled LAMINAR FLOW ELEMENT, U.S. Provisional Patent Application Ser. No. 62/775,066, filed on Dec. 4, 2018 and entitled FLOW SENSING MODULE, U.S. Provisional Patent Application Ser. No. 62/844,383, filed on May 7, 2019 and entitled FLUID MONITORING MODULE ARRANGEMENTS, U.S. Provisional Patent Application Ser. No. 62/844,390, filed on May 7, 2019 and entitled FLUID MONITORING MODULE ARRANGEMENTS, U.S. Provisional Patent Application Ser. No. 62/844,399, filed on May 7, 2019 and entitled FLUID MONITORING MODULE ARRANGEMENTS, and U.S. Provisional Patent Application Ser. No. 62/895,115, filed on Sep. 3, 2019 and entitled FLUID MONITORING MODULE ARRANGEMENTS, the entire disclosures of each of which are incorporated herein by reference.

BACKGROUND

Laminar flow elements (or LFEs) are generally used to measure the flow of gases, for example, for use with mass flowmeters or other such monitoring devices. A conventional laminar flow element operates by producing a differential pressure that is proportional to the velocity of the gas passing through a section of the laminar flow element, which is specifically configured to maintain the gas flow in a laminar state. Upstream and downstream pressure sensors detect this pressure differential, which is used to calculate the flow rate. Due to the typical length-to-diameter requirements of the restricting flow path of a laminar flow element (e.g., a 25:1 ratio), large size, intricate machining, or complex assembly requirements often result in increased manufacturing costs, extensive lead times, and/or undesirably large LFE components.

SUMMARY

According to an aspect of the present disclosure, a flow sensing device includes a cross-shaped body including laterally extending inlet and outlet ports and axially extending upstream and downstream sensor ports, an upstream pressure sensor installed in the upstream sensor port, and a downstream pressure sensor installed in the downstream sensor port. The inlet port is connected in fluid communication with the upstream sensor port by an inlet branch port, and the outlet port is connected in fluid communication with the downstream sensor port by an outlet branch port. The upstream and downstream sensor ports are connected in fluid communication by a laminar flow restricting passage extending generally axially from the upstream sensor port to the downstream sensor port.

According to another aspect of the present disclosure, a fluid monitoring module includes a flow sensing device and a controller disposed in an enclosure. The flow sensing device includes a body including an inlet port, an outlet port, an upstream sensor port, a downstream sensor port, and a flow passage disposed between the inlet port and the outlet port, and between the upstream sensor port and the downstream sensor port. A first fluid sensor is assembled with the upstream sensor port, and a second fluid sensor is assembled

with the downstream sensor port. The controller is in circuit communication with the first and second fluid sensors for receiving at least one of pressure indicating signals and temperature indicating signals from each of the first and second fluid sensors, and for measuring fluid data based on the received signals.

According to another aspect of the present disclosure, a flow sensing device includes first and second body members, a flow restricting element, and upstream and downstream pressure sensors. The first body member includes an inlet port, an upstream sensor port, and a first connecting port, each connected by an internal upstream passage. The second body member includes an outlet port, a downstream sensor port, and a second connecting port, each connected by an internal downstream passage. The flow restricting element includes a first end connection coupled to the first connecting port, a second end connection coupled to the second connecting port, and a flow restricting passage disposed between the first and second end connections. The upstream pressure sensor is installed in the upstream sensor port, and the downstream pressure sensor is installed in the downstream sensor port.

According to another aspect of the present disclosure, a method of monitoring fluid conditions in a fluid line is contemplated. In an exemplary method, a fluid monitoring module is provided, including a first pressure sensor sealingly installed in a first sensor port and electrically connected with a controller. The first sensor port is coupled to a first branch connector of the fluid line for generation of first pressure indicating data signals by the first pressure sensor. The pressure indicating data signals are transmitted to the controller, and fluid data based on the received data signals is measured.

According to another aspect of the present disclosure, a flow sensing device includes a body, an upstream pressure sensor, and a downstream pressure sensor. The body includes inlet and outlet ports and upstream and downstream sensor ports. The inlet port is connected in fluid communication with the upstream sensor port by an internal upstream passage, and the outlet port is connected in fluid communication with the downstream sensor port by a downstream internal passage. The upstream and downstream sensor ports are connected in fluid communication by a flow restricting element disposed in a cavity in the body. The upstream pressure sensor is installed in the upstream sensor port, and the downstream pressure sensor is installed in the downstream sensor port. The flow restricting element includes a central portion defining a flow passage and an outer peripheral solid portion that forms an annular recess into which fluid contaminants collect without blocking or further restricting the flow passage.

According to another aspect of the present disclosure, a flow sensing device includes a body, an upstream pressure sensor, and a downstream pressure sensor. The body includes inlet and outlet ports and upstream and downstream sensor ports. The inlet port is connected in fluid communication with the upstream sensor port by an internal upstream passage, and the outlet port is connected in fluid communication with the downstream sensor port by a downstream internal passage. The upstream and downstream sensor ports are connected in fluid communication by a flow restricting element including a flow passage. The upstream pressure sensor is installed in the upstream sensor port, and the downstream pressure sensor is installed in the downstream sensor port. A heating arrangement surrounds the flow passage, and is operable to remove or prevent formation of condensation in the flow passage.

According to another aspect of the present disclosure, a fluid monitoring and grab sampling system includes a fluid line, a fluid monitoring module, a wireless transmitter, an RFID reader, and a sample cylinder. The fluid monitoring module is connected in fluid communication with the fluid line and includes a fluid sensor and a controller in circuit communication with the fluid sensor, the wireless transmitter, and the RFID reader. The controller receives fluid data from the fluid sensor, including at least one of pressure indicating data and temperature indicating data. The sample cylinder is connectable with a branch port in the fluid line, and includes an RFID tag configured to communicate cylinder data including at least an identification code to the RFID reader when the sample cylinder is connected with the branch port. The wireless transmitter is configured to wirelessly communicate the fluid data and the cylinder data to a remote device.

According to another aspect of the present disclosure, a method of monitoring a grab sampling operation is contemplated. In an exemplary method, fluid data is transmitted from a fluid sensor in fluid communication with a fluid line to a controller connected to the fluid sensor, with the fluid data including at least one of pressure indicating signals and temperature indicating signals generated by the fluid sensor. A sample cylinder is connected with a branch port in the fluid line to collect a sample from the fluid line. Cylinder data is transmitted from the sample cylinder to the controller, with the cylinder data including at least a cylinder identification code. The fluid data and the cylinder data are transmitted from the controller to a remote device.

BRIEF DESCRIPTION OF THE DRAWINGS

Further advantages and benefits will become apparent to those skilled in the art after considering the following description and appended claims in conjunction with the accompanying drawings, in which:

FIG. 1 is a cross-sectional view of an exemplary flow sensing device, in accordance with an aspect of the present disclosure;

FIG. 1A is a perspective view of the flow sensing device of FIG. 1;

FIG. 1B is a side view of a multiple flow sensing device system, in accordance with another aspect of the present disclosure;

FIG. 2 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 3 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 4 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 5 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 6 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 7 is a cross-sectional view of an exemplary flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 8 is a schematic view of a flow sensing device, in accordance with another aspect of the present disclosure;

FIG. 9 is a schematic view of another flow sensing device, in accordance with another aspect of the present disclosure; and

FIG. 10A is a front perspective view of an exemplary wireless fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 10B is a rear perspective view of the wireless fluid monitoring module of FIG. 10A;

FIG. 10C is an exploded perspective view of the wireless fluid monitoring module of FIG. 10A;

FIG. 11A is a side cross-sectional view of the wireless fluid monitoring module of FIG. 10A;

FIG. 11B is a top cross-sectional view of the wireless fluid monitoring module of FIG. 10A;

FIG. 12 is a side cross-sectional view of another exemplary wireless fluid monitoring module, in accordance with another aspect of the present application;

FIG. 13A is a perspective view of another exemplary wireless fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 13B is a perspective view of another exemplary wireless fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 13C is a perspective view of another exemplary wireless fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 14 is a schematic view of a fluid monitoring module, in accordance with another aspect of the present disclosure;

FIGS. 14A-14I are cross-sectional views of exemplary flow restricting elements for a fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 15 is a schematic view of another fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 16A is a side view of an exemplary wireless fluid monitoring module having an external flow restricting element, in accordance with another aspect of the present disclosure;

FIG. 16B is a side view of another exemplary wireless fluid monitoring module having an external flow restricting element, in accordance with another aspect of the present disclosure;

FIG. 16C is a side view of another exemplary wireless fluid monitoring module having an external flow restricting element, in accordance with another aspect of the present disclosure;

FIG. 16D is a side view of another exemplary wireless fluid monitoring module having an external flow restricting element, in accordance with another aspect of the present disclosure;

FIG. 16E is a side view of another exemplary wireless fluid monitoring module having an external flow restricting element, in accordance with another aspect of the present disclosure;

FIG. 17 is a side cross-sectional view of an exemplary sensor port mounting arrangement for a wireless fluid monitoring module having an external flow restricting element;

FIG. 18A is a side view of an exemplary wireless fluid monitoring module having a dual fluid monitoring arrangement, in accordance with another aspect of the present disclosure;

FIG. 18B is a side view of another exemplary wireless fluid monitoring module having a dual fluid monitoring arrangement, in accordance with another aspect of the present disclosure;

5

FIG. 18C is a side view of another exemplary wireless fluid monitoring module having a dual fluid monitoring arrangement, in accordance with another aspect of the present disclosure;

FIG. 18D is a cross-sectional perspective view of an exemplary blank coupling connection, in accordance with another aspect of the present disclosure;

FIG. 18E is a cross-sectional perspective view of an exemplary coupling connection with blank disc insert, in accordance with another aspect of the present disclosure;

FIG. 19 is a schematic view of a fluid system with a portable fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 20 is a schematic view of another fluid system with another portable fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 21 is a schematic view of another fluid system with another portable fluid monitoring module, in accordance with another aspect of the present disclosure;

FIG. 22 is a schematic view of another fluid system with another portable fluid monitoring module, in accordance with another aspect of the present disclosure; and

FIG. 23 is a schematic view of an exemplary fluid monitoring and grab sampling system, in accordance with another aspect of the present disclosure.

DETAILED DESCRIPTION

While various inventive aspects, concepts and features of the inventions may be described and illustrated herein as embodied in combination in the exemplary embodiments, these various aspects, concepts and features may be used in many alternative embodiments, either individually or in various combinations and sub-combinations thereof. Unless expressly excluded herein all such combinations and sub-combinations are intended to be within the scope of the present inventions. Still further, while various alternative embodiments as to the various aspects, concepts and features of the inventions—such as alternative materials, structures, configurations, methods, circuits, devices and components, software, hardware, control logic, alternatives as to form, fit and function, and so on—may be described herein, such descriptions are not intended to be a complete or exhaustive list of available alternative embodiments, whether presently known or later developed. Those skilled in the art may readily adopt one or more of the inventive aspects, concepts or features into additional embodiments and uses within the scope of the present inventions even if such embodiments are not expressly disclosed herein. Additionally, even though some features, concepts or aspects of the inventions may be described herein as being a preferred arrangement or method, such description is not intended to suggest that such feature is required or necessary unless expressly so stated. Still further, exemplary or representative values and ranges may be included to assist in understanding the present disclosure, however, such values and ranges are not to be construed in a limiting sense and are intended to be critical values or ranges only if so expressly stated. Still further, exemplary or representative values and ranges may be included to assist in understanding the present disclosure, however, such values and ranges are not to be construed in a limiting sense and are intended to be critical values or ranges only if so expressly stated. Parameters identified as “approximate” or “about” a specified value are intended to include both the specified value and values within 10% of the specified value, unless expressly stated otherwise. Further, it is to be understood that the drawings accompanying

6

the present disclosure may, but need not, be to scale, and therefore may be understood as teaching various ratios and proportions evident in the drawings. Moreover, while various aspects, features and concepts may be expressly identified herein as being inventive or forming part of an invention, such identification is not intended to be exclusive, but rather there may be inventive aspects, concepts and features that are fully described herein without being expressly identified as such or as part of a specific invention, the inventions instead being set forth in the appended claims. Descriptions of exemplary methods or processes are not limited to inclusion of all steps as being required in all cases, nor is the order that the steps are presented to be construed as required or necessary unless expressly so stated.

The Detailed Description merely describes exemplary embodiments and is not intended to limit the scope of the claims in any way. Indeed, the invention as claimed is broader than and unlimited by the exemplary embodiments, and the terms used in the claims have their full ordinary meaning. For example, while specific exemplary embodiments in the present disclosure describe flow sensing devices with pressure sensors for measuring differential pressure and correlating the differential pressure to flow rate, in other embodiments, one or more of the features described herein may be applied to other fluid system components, including, for example, conduit fittings and valves.

According to an aspect of the present disclosure, as illustrated in the cross-sectional view of FIG. 1, a flow sensing device 100 may be provided with a cross-shaped body 110 including laterally extending inlet and outlet ports 111, 112 and axially extending upstream and downstream sensor ports 113, 114. As shown, the inlet port 111 may, but need not, be substantially coaxial with the outlet port 112 (along axis X, as shown), and the upstream sensor port 113 may, but need not, be substantially coaxial with the downstream sensor port 114 (along axis Y, as shown). The inlet and outlet ports 111, 112 may include any suitable fluid system connectors, including, for example, one or more tube fittings, face seal fittings, threaded pipe ends, or weld ends. The inlet port 111 is connected in fluid communication with the upstream sensor port 113 by an inlet branch port 116, and the outlet port 112 is connected in fluid communication with the downstream sensor port 114 by an outlet branch port 117. The upstream and downstream sensor ports 113, 114 are connected by a flow restricting passage 115 extending generally axially from the upstream sensor port 113 to the downstream sensor port 114. While the flow restricting passage 115 may be specifically configured to maintain laminar flow through the device 100 (e.g., as a laminar flow element, or LFE), in other embodiments, the flow restricting passage may permit turbulent flow, or a combination of laminar flow and turbulent flow, while still providing for a consistent desired flow rate or range of flow rates. As shown, other than the branch ports 116, 117, the body 110 may (but need not) be substantially symmetrical about either or both of the X and Y axes.

An upstream pressure sensor 120 is installed in the upstream sensor port 113 and is configured to generate a signal corresponding to an upstream pressure, and a downstream pressure sensor 130 is installed in the downstream sensor port and is configured to generate a signal corresponding to a downstream pressure. The pressure sensors 120, 130 may transmit signals to an electronic controller, shown schematically at 150, in circuit communication with the pressure sensors, for example, by wired or wireless communication, with the electronic controller being configured to evaluate the upstream and downstream pressures

corresponding to the received signals, to determine a pressure differential across the flow restricting passage and a corresponding flow rate through the flow sensing device 100.

The upstream and downstream pressure sensors 120, 130 may include any suitable type of pressure sensor (e.g., a piezoresistive strain gauge, a capacitive pressure sensor, an electromagnetic pressure sensor, a piezoelectric pressure sensor), which may be securely retained within the corresponding sensor port 113, 114, for example, using a retaining ring 121, 131, and may be sealed within the corresponding sensor port 113, 114, for example, using an O-ring or gasket seal 122, 132. In an exemplary embodiment, the sensor may be configured to detect or measure both pressure and temperature, and transmit pressure and temperature indicating signals to the controller. The controller may be configured to process the pressure and temperature indicating signals, for example, to determine pressure, temperature, and/or flow rate, and/or to provide a measured output of any one or more of these parameters. An exemplary sensor configured to measure pressure and temperature is the LD series piezoresistive OEM pressure transmitter, manufactured by Keller.

The compact arrangement of the cross-shaped body 110 of the flow sensing device 100 may allow the flow sensing device to be incorporated into smaller enclosures or smaller equipment, or more seamlessly into existing systems. While a system including a plurality of flow sensing devices may include a separate controller connected with each of the flow sensing devices, in another embodiment, the compact flow sensing devices may be arranged and configured for electrical connection with a single controller. FIG. 1B illustrates an exemplary system 10 including a plurality of flow sensing devices 100 arranged end to end, with upstream and downstream pressure sensors 120, 130 electrically connected to the controller 150, and inlet and outlet ports 111, 112 connected to parallel fluid lines 11, 12.

Many different suitable laminar flow restricting passages may be utilized. In some embodiments, one or more flow restricting passages may be integrally formed in the body, for example, by drilling, machining, or additive manufacturing (e.g., 3D printing). In other embodiments, one or more flow restricting passages may be defined by a flow restricting element formed from one or more inserts (e.g. plugs, plates, etc.) installed in a cavity in the body between the upstream and downstream sensor ports. This type of flow passage insert arrangement may facilitate formation of the flow passages, and/or may allow for adaptability of the flow sensing device, for example, by allowing for different ranges of flow rate and pressure differential.

In one example, as shown in FIG. 2, a body 110a of a flow sensing device 100a includes a narrow axially extending (e.g., capillary) passage 115a extending between the upstream sensor port 113a and the downstream sensor port 114a. In another exemplary embodiment, as shown in FIG. 3, a body 110b of a flow sensing device 100b includes multiple narrow axially extending passages 115b extending between the upstream sensor port 113b and the downstream sensor port 114b, for example, to provide for increased laminar flow while limiting the axial length of the body 110b.

In another exemplary embodiment, as shown schematically in FIG. 4, the body 110c of a flow sensing device 100c may be provided with one or more narrow, laminar flow restricting passages 115c having a plurality of coils or convolutions arranged to provide an extended passage length over a limited axial dimension of the body, between the upstream and downstream sensor ports 113c, 114c. These convoluted or coiled passages may be formed, for

example, by additive manufacturing to facilitate production of one or more convoluted laminar flow restricting passages 115c between the upstream sensor port 113c and the downstream sensor port 114c. In another exemplary embodiment, as shown in FIG. 5, the body 110d of a flow sensing device 100d may include a central cavity 119d retaining a stack of plates 140d having holes and/or slots aligned to define the passage(s) 115d. In other embodiments, convoluted or selectively contoured passages (formed, for example, by additive manufacturing) may be utilized to provide or perform other fluid flow functions such as, for example, mixing, swirling, heat/cold tracing or other such functionality.

In other exemplary embodiments, as shown in FIG. 6, a body 110e of a flow sensing device 100e may include a flow restricting element 140e (e.g., a sintered element) installed in a cavity 119e of the body 110e to define a flow passage 115e that restricts flow to a desired flow condition (e.g., laminar flow and/or a desired flow range). An O-ring or other such gasket seal 149e may be provided around the flow restricting element 140e (e.g., in an inner peripheral groove in the body cavity 119e, and/or in an outer peripheral groove in the flow restricting element 140e) may be provided around the flow restricting element to seal against leakage/flow past the periphery of the flow restricting element. In another exemplary embodiment, as shown in FIG. 7, the body 110f of a flow sensing device 100f may be formed by additive manufacturing to facilitate production of a porous, axially extending portion 140f of the body between the upstream and downstream sensor ports 113f, 114f, with a pore size and density selected to provide a desired flow condition.

Flow restricting sintered elements or other such porous or narrow passage restricting portions may tend to get blocked or clogged by contaminants in the system fluid, which may affect system flow rates and the flow readings provided by the device. According to another aspect of the present disclosure, a flow sensing device body may be provided with a flow restricting element shaped or otherwise configured to divert or collect contaminants into a recessed portion of the body cavity, thereby minimizing the clogging or blocking of the porous flow restricting element.

FIG. 8 schematically illustrates an exemplary flow sensing device 1100 including a body member 1110 having inlet and outlet ports 1111, 1112 and upstream and downstream sensor ports 1113, 1114. The inlet and outlet ports 1111, 1112 may include any suitable fluid system connectors, including, for example, one or more tube fittings, face seal fittings, threaded pipe ends, or weld ends. The inlet port 1111 is connected in fluid communication with the upstream sensor port 1113 by an internal upstream passage 1116, and the outlet port 1112 is connected in fluid communication with the downstream sensor port 1114 by an internal downstream passage 1117. The upstream and downstream sensor ports 1113, 1114 sealingly retain sensors 1120, 1130 and are connected by a porous flow restricting element 1140 disposed in a cavity 1119 of the body 1110 to define a flow restricting passage 1115. While the flow restricting passage 1115 may be specifically configured to maintain laminar flow through the device 1100, in other embodiments, the flow restricting passage may permit turbulent flow, or a combination of laminar flow and turbulent flow, while still providing for a consistent desired flow rate or range of flow rates.

As shown, the exemplary flow restricting element 1140 includes a conical central porous portion 1141 and an outer peripheral solid or non-porous portion 1142 that forms an annular recess into which fluid contaminants may collect

without blocking or further restricting the flow path. The internal upstream passage **1116** may be shaped to direct fluid flow toward the surfaces of the body cavity **1119** and the annular recess **1142**. Alternatively, as shown, an upstream end or tip **1143** of the flow restricting element may also be solid or non-porous, and the internal upstream passage **1116** in the body **1110** may be shaped to direct fluid flow toward the solid restricting element tip, such that the contoured tip directs contaminants radially outward while minimizing any tendency for the contaminants to become embedded in the porous portions of the flow restricting element. Other porous element shapes may be utilized including, for example, hemispherical or pyramid shaped elements. The flow restricting element **1140** may be provided as an insert for installation in the body cavity **1119**, similar to the embodiment of FIG. 6. Alternatively, the flow restricting element **1140** may be integrally formed with the body **1110**, similar to the embodiment of FIG. 7. In either case the flow restricting element may be formed using additive manufacturing (e.g., 3D printing) which may be well suited to selectively form portions of the element in porous and non-porous materials.

Porous restricting portions or narrow restricting passages may become partially blocked or clogged by condensation in a gaseous fluid system, for example, where the fluid system is subjected to lower temperatures or sudden changes in temperature. According to another aspect of the present disclosure, a flow sensing device body may be provided with a flow restriction heating arrangement, for example, to selectively evaporate or boil off condensation, or to maintain the flow restricting element at temperatures that will prevent condensation, thereby preventing this type of restricting element blockage.

FIG. 9 schematically illustrates an exemplary flow sensing device **1200** including a body member **1210** having inlet and outlet ports **1211**, **1212** and upstream and downstream sensor ports **1213**, **1214**. The inlet and outlet ports **1211**, **1212** may include any suitable fluid system connectors, including, for example, one or more tube fittings, face seal fittings, threaded pipe ends, or weld ends. The inlet port **1211** is connected in fluid communication with the upstream sensor port **1213** by an internal upstream passage **1216**, and the outlet port **1212** is connected in fluid communication with the downstream sensor port **1214** by an internal downstream passage **1217**. The upstream and downstream sensor ports **1213**, **1214** sealingly retain sensors **1220**, **1230** and are connected by a flow restricting element **1240** disposed in a cavity **1219** of the body **1210** and defining a flow restricting passage **1215** (e.g., one or more formed passages or a porous flow restricting material). While the flow restricting passage **1215** may be specifically configured to maintain laminar flow through the device **1200**, in other embodiments, the flow restricting passage may permit turbulent flow, or a combination of laminar flow and turbulent flow, while still providing for a consistent desired flow rate or range of flow rates.

As shown, the flow restricting device **1200** includes a flow restriction heating arrangement surrounding the flow passage **1215** in the flow restricting element **1240**. The heating arrangement **1270**, which may be formed in the flow restricting element **1240**, around the flow restricting element (e.g., between an outer surface of the flow restricting element and an inner surface of the body cavity **1219**), or around the body member **1210** in alignment with the flow passage. A wide variety of flow restricting heating arrangements may be utilized, including, for example: one or more heating circuits configured to receive a current for heating the flow restrict-

ing element, or one or more heat trace passages for passing heated fluid (e.g., steam) through or around the flow restricting element. The flow restricting element **1240** may be provided as an insert for installation in the body cavity **1219**, similar to the embodiment of FIG. 6. Alternatively, the flow restricting element **1240** may be integrally formed with the body **1210**, similar to the embodiment of FIG. 7. In either case the flow restricting element may be formed using additive manufacturing (e.g., 3D printing) which may be well suited to form heat trace or circuit receiving passages in or around the flow restricting element.

While the controller(s) may be separate from, and physically and electrically tethered to, the flow sensing element(s), in other embodiments, a flow sensing element may be provided in a self-contained module, for example, for ease of installation in a fluid system, with an enclosure containing the flow sensing device (with external connectors for connecting the flow sensing device with the fluid system) and the controller. The controller may be configured to communicate (e.g., by wired or wireless communication) with an external device (e.g., server, router, computer, tablet, smartphone) to deliver information about the fluid flow conditions (e.g., pressure, temperature, flow rate). Additionally or alternatively, the module may be provided with a user interface for providing information about the fluid flow conditions at the module (e.g., using an LED array or LCD display screen).

FIGS. 10A-11B illustrate various views of an exemplary fluid monitoring module **500**, including an enclosure **501** formed from a housing **502** and a cover **503** (secured together, for example, using bolts or other fasteners) enclosing a flow sensing device **505** and controller **550**. The flow sensing device **505** may, for example, be similar to any of the flow sensing devices **100a-f** described herein, and may be provided with end connectors **506** extending through openings in the enclosure **501**. Gaskets or other such seals **504** (FIG. 11A) may surround the end connectors **506** in the openings, for example, to prevent moisture or other contaminants from entering the enclosure. While the end connectors may be provided in a variety of locations and orientations, in the illustrated embodiment, the end connectors **506** extend from a common wall of the enclosure, for example, to facilitate installation into an existing fluid system. As shown in FIGS. 10C and 11A, the flow sensing device **505** may be provided with elbow fittings or other such connectors and adapters to position the end connectors **506** at the desired location and orientation. In one such example, the end connectors **506** of the module **500** may be spaced and oriented to corresponding with a conventional flow rate measuring device (e.g., a rotameter-style flow rate measuring device), such that the conventional flow rate measuring device of an existing system may be easily replaced with the module **500**. In another embodiment (not shown), the end connectors may extend axially from the fluid monitoring module, for example, to facilitate inline installation of the flow sensing device, or of multiple flow sensing devices with multiple parallel, closely spaced fluid lines. In still other embodiments, the end connectors may be offset from each other and may extend in opposite directions from opposite sides of the housing, or perpendicularly from adjacent sides of the housing.

While the module may be provided with external wiring for connection with an external power source (e.g., wall outlet), the module **500** may additionally or alternatively include one or more batteries **560**, as shown in FIG. 11A, electrically connected with the controller **550** to power the controller hardware (e.g., processor, transmitter, LEDs) and

sensors **520**, **530** of the flow sensing device **505**. As shown, the batteries **560** may be disposed in a sleeve **561**, for example, to protect and securely position the batteries. In some embodiments, the module may be provided with rechargeable batteries that may be recharged, for example, by electrically connecting external wiring of the module to an external power source. Additionally or alternatively, the enclosed batteries may serve as a back-up power source (e.g., in the event of a building power failure), with the module primarily operating off of an external power source. As shown in FIG. **10C**, a spacer bracket **509** may be provided within the enclosure **501**, for example, to secure the internal components of the module in a desired position.

The exemplary flow sensing device assembly **505** includes upstream and downstream sensors **520**, **530** installed in upstream and downstream sensor ports **513**, **514** of a body member **510**. The sensors **520**, **530** are connected (e.g., by wiring within the module enclosure) to the controller **550** to transmit pressure and temperature indicating signals to the controller. The controller **550** is configured to process the pressure and temperature indicating signals, for example, to determine pressure, temperature, and/or flow rate of fluid passing through the flow sensing device, and/or to provide a measured output of any one or more of these parameters.

In the embodiment of FIGS. **10A-11B**, the sensor ports **513**, **514** of the body **510** are oriented to face the sides of the housing **502**. Alternatively, as shown in FIG. **12**, the sensor ports **513'**, **514'** of the body **510'** may be oriented to face the housing rear wall and the cover **503'**, allowing the width of the enclosure to be reduced. Additionally or alternatively, the battery size may be reduced (e.g., replacing two C cell batteries **560** with one D cell battery **560'**), as shown in FIG. **12**) to allow the height of the enclosure to be reduced.

The module may be provided with external wiring for a wired connection with an external device (e.g., computer). Additionally or alternatively, as shown, the module **500** may be provided with a wireless transmitter (e.g., provided on a circuit board of the controller **550**) for wirelessly transmitting fluid data to a remote device (e.g., server, router, computer, tablet, smartphone), for example, using direct or indirect wireless communication with the remote device. The transmitter may be configured to communicate using any number of suitable wireless communication protocols and capabilities, such as, for example, WiFi, Bluetooth, ZigBee, RFID, NFC, and wireless USB communication. As shown, the module **500** may include an external antenna **555**, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device. In an exemplary system, a WiFi gateway router may be provided for wireless communication with one or more modules, for example, to establish a browser interface (which may eliminate the need for desktop software), facilitate commissioning of field devices, establish data system/cloud interfaces, and provide for simplified troubleshooting and diagnostics.

To facilitate commissioning and control (e.g., power on/off, synchronization) of the module, the module may be provided with a user interface, such as, for example, one or more knobs, switches or buttons. In the illustrated embodiment, the module **500** includes an external, user depressible button **507** disposed in an opening in the cover **503** and positioned for actuation of a button switch **557** on the controller **550**, which may be actuated, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller. The button **507** may be provided in a transparent or translucent material, to provide illumi-

nation from one or more LEDs **558** on the controller **550**, which may be illuminated, for example, to provide user indication of a controller status (e.g., power on/off, connectivity, recognized user actuation). The LEDs **558** may provide multi-color illumination (either by providing multiple LEDs each having different color illumination, or one or more multi-color LEDs) and/or pulsed illumination, for example, to identify multiple distinguishable status conditions.

In addition to, or instead of, wired or wireless communication with an external device, the module may be provided with a user interface configured to display fluid flow data on the module. FIG. **13A** illustrates an exemplary module **500a** including a user interface display screen **559a** (e.g., LCD, OLED) disposed on an outer surface of the enclosure (e.g., on the cover **503a**) and connected in circuit communication with the module controller, for display of one or more fluid conditions (e.g., flow rate, temperature, pressure). Alternatively, to provide a simpler output display, an LED array **559b**, **559c** may be used to provide a digital display (e.g., one or more numerical digits), as shown in FIG. **13B**, or a multi-bar proportional readout display (e.g., three or more LEDs showing proportional levels of flow rate, pressure, and/or temperature), as shown in FIG. **13C**. In an exemplary embodiment of the present disclosure, digital or multi-bar LED displays may utilize multi-color LEDs to display multiple types of fluid data using the same set of LEDs. For example, the digital LED display **559b** of FIG. **13B** may provide for illumination of the corresponding LEDs in a first color (e.g., white) to identify a measured flow rate, a second color (e.g., red) to identify a measured pressure, and a third color (e.g., green) to identify a measured temperature. Similarly, the digital LED display **559c** of FIG. **13C** may provide for illumination of the corresponding LEDs in a first color (e.g., white) to identify a proportional flow rate level, a second color (e.g., red) to identify a proportional pressure level, and a third color (e.g., green) to identify a proportional temperature level. A user may selectively toggle between fluid data by actuating a user interface (e.g., button or knob), or the display may be configured to automatically periodically switch (e.g., every 3-10 seconds) between the different fluid flow data.

In one or more exemplary embodiments, a fluid monitoring module, such as, for example, any of the modules described herein, may be configured to provide a number of desired properties and conditions, including. For example, a fluid monitoring module may be configured to provide typical desired sample stream and bypass flow ranges, including, for example, gas flow rates of about 0.05 to 20 SLPM (analyzer) or liquid flow rates of about 0.05-20 LPM (bypass). An exemplary fluid monitoring module may be configured to provide flow measurement accuracy of less than about 10% of full scale (e.g., about +/-5% accuracy), and may be configured to provide excellent repeatability and stability. An exemplary fluid monitoring module may, for example, be rated for use from about -20 C to 80 C, or at a maximum ambient temperature of about 85 C. An exemplary fluid monitoring module may, for example, be rated for operating pressures between about 50 psig and 150 psig, and may be rated for 1900 psig proof or 3500 psig burst. Exemplary materials of construction may include, for example, 316 stainless steel, Hastelloy, FKM, and FFKM. An exemplary fluid monitoring module may include appropriate safety ratings, including, for example, class 1 division **1** for the transmitter, class 1 division **2** for the gateway, ATEX Zone **1**, and/or IECEx Zone **1**. An exemplary fluid monitoring module may be configured for 2.4 GHz mesh

wireless communication. An exemplary fluid monitoring module may include a disposable lithium battery with at least a five year life. An exemplary fluid monitoring module may be rated for a lag time of T₉₀=5 seconds maximum for 0.2 SLPM gas flow.

In one or more exemplary embodiments, a fluid monitoring module, such as, for example, any of the modules described herein, may be used in a variety of applications, including, for example, any one or more locations in a process analytical system. Examples include field stations, fast loop systems, grab sampling locations, calibration and switching locations, sample conditioning locations, gas and/or utilities analyzers, and sample disposal locations.

According to another aspect of the present disclosure, a flow sensing device may be configured to facilitate removal of a flow restricting element without removing the flow sensing device from the system, for example, to replace a damaged or contaminated flow restricting element, to facilitate inspection of the flow restricting element, or to replace the flow restricting element with a second flow restricting element providing a different flow condition (e.g., different flow rate). In one such embodiment, the flow sensing element may be provided with first and second end connections facilitating disconnection and removal of the flow sensing element from the inlet/outlet ports and the upstream/downstream sensor ports. As one example, first and second end connections of a flow sensing element may include zero clearance fittings (e.g., gasketed VCO fittings manufactured by Swagelok Co.) facilitating removal and reinstallation/replacement of the flow sensing element without repositioning the ported ends of the flow sensing device.

FIG. 14 illustrates an exemplary fluid monitoring module 600 including a flow sensing device 605 configured to facilitate removal of a flow restricting element 640. The exemplary flow sensing device 605 includes first and second T-shaped body members 610-1, 610-2 including first run ports defining laterally outward extending inlet and outlet ports 611, 612, second run ports defining laterally inward extending upstream and downstream sensor ports 613, 614, and branch or connecting ports defining axially extending first and second restrictor connections 618, 619 for connecting with first and second end connectors 648, 649 of the flow restricting element 640. Upstream and downstream sensors 620, 630 (which may be similar to the sensors 120, 130, 520, 530 of the embodiments of FIGS. 1-13) are sealingly installed in the upstream and downstream sensor ports 613, 614.

The inlet port 611, upstream sensor port 613 and first restrictor connection 618 of the first body member 610-1 are connected in fluid communication by an internal T-shaped upstream passage 616 of the first body member 610-1, and the outlet port 612, downstream sensor port 614, and second end connection 619 are connected in fluid communication by an internal T-shaped downstream passage 617 of the second body member 610-2. The ports may include any suitable fluid system connectors, including, for example, one or more tube fittings, face seal fittings, threaded pipe ends, or weld ends.

The upstream and downstream passages 616, 617 are connected by a flow restricting passage 615 in the flow restricting element 640. As described above, the flow restricting passage 615 may take one or more of a variety of forms including, for example, one or more straight or convoluted passages or one or more sintered or other such flow restricting materials. The passage(s) may be formed using one or more of a variety of processes, including machining or additive manufacturing. The flow restricting

passages may be formed in one or more inserts 641 (e.g., plugs, plates, etc.) retained in a coupling body 642 to which the first and second end connections 648, 649 are attached (e.g., by welding or integrally forming). In one embodiment, the flow restricting insert(s) may be removable from the coupling body for replacement with alternative flow restricting inserts providing different flow rates, flow paths, materials, or other such properties. In other embodiments, the flow restricting component may be integrally or monolithically formed with the coupling body, such that the entire flow restricting element is replaced. In other embodiments, the flow restricting element 640 may be replaced with a flow restricting element having a different axial length, for example, to adjust the offset of the inlet and outlet ports 611, 612. In still other embodiments, variations in the offset of the inlet and outlet ports may be accommodated by providing the inlet and outlet ports with flexible end connections, such as, for example, hose connections.

The first and second end connections 648, 649 of the exemplary flow restricting element 640 include zero clearance connectors for connection with mating zero clearance connectors of the first and second connections 618, 619 of the first and second body members 610-1, 610-2. An exemplary zero clearance fitting is a VCO fitting, manufactured by Swagelok Co. In one embodiment, the coupling body 642 is provided with male threaded body connectors, and the body members 610-1, 610-2 are provided with welded glands and captured female threaded nuts for coupling with the male threaded body connectors. In another embodiment, the body members 610-1, 610-2 are provided with male threaded body connectors, and the coupling body 642 is provided with welded glands and captured female threaded nuts for coupling with the captured nuts. In still another embodiment, the coupling body 642 is provided with a male threaded body connector for connecting with a captured female nut on one of the first and second body members, and a captured female threaded nut for connecting with a male threaded body connector on the other of the first and second body members. This arrangement may provide an assurance that the flow restricting element is installed in the correct directional orientation.

The flow restricting element may be provided as a multiple piece subassembly including one or more connectors detachable to facilitate removal and/or replacement of the flow restricting insert from the coupling body. FIG. 14A illustrates an exemplary flow restricting element 640a with a two-piece body including a male threaded gland 643a joined with a female threaded connector 644a to form the coupling body 642a. A flow restricting insert 641a, defining a flow restriction or orifice 615a is received in a recess in the connector 644a, and the exemplary gland 643a includes a face seal O-ring 645a that seals against the retainer body recess and the insert. The gland 643a retains a female threaded zero clearance fitting nut 648a for connecting with a male threaded zero clearance fitting body on a first body member of the flow restricting device, and the retainer body defines a male threaded zero clearance fitting body 649a for connecting with a female threaded zero clearance fitting nut on a second body member of the flow restricting device. To repair (e.g., clean) or replace the flow restricting insert 641a, the fitting nut 648a is unthreaded from the male threaded fitting body of the device (not shown), and the connector 644a is unthreaded from the female threaded nut of the device (not shown) to remove the flow restricting element subassembly 640a from the device. The gland 643a is then unthreaded from the connector 644a for removal and repair/reinstallation or replacement of the flow restricting insert

641a. Alternatively, the entire flow restriction element sub-assembly 640a may be replaced.

FIG. 14B illustrates another exemplary flow restricting element 640b having a two-piece body 642b including a first male threaded zero clearance connector 643b having a female threaded (e.g., NPT threads) end and a second male threaded zero clearance connector 644b having a mating male threaded (e.g., NPT threads) end joined with the female threaded end to form the coupling body. A flow restricting insert 641b defining a flow restricting orifice 615b is received in a recess in the first connector 643b, and may be secured against a counterbore portion 645b of the first connector by an end face 646b of the male threaded end of the second connector 644b. To repair (e.g., clean) or replace the flow restricting insert 641b, the first and second male connectors 643b, 644b are unthreaded from corresponding female threaded nuts (not shown) of the device to remove the flow restricting element subassembly 640b from the device. The first and second male connectors 643b, 644b may then be unthreaded from each other for removal and repair/reinstallation or replacement of the flow restricting insert 641b. Alternatively, the entire flow restriction element subassembly 640b may be replaced.

FIG. 14C illustrates an exemplary flow restricting element 640c with a two-piece arrangement including a male threaded zero clearance connector 643c joined with a gland 644c by a female threaded zero clearance nut 648c. A flow restricting insert 641c, defining a flow restricting orifice 615c, is received and sealed between a face seal O-ring 645c assembled with the male connector 643c (e.g., retained in an end face groove of the male threaded end) and a face seal O-ring 646c assembled with the gland 644c (e.g., retained in an end face groove of the gland). In an exemplary embodiment, the male connector 643c may be affixed with (e.g., welded to, coupled to, or integrally machined with) a first fitting body defining an first (e.g., inlet, outlet) port and a sensor retaining first (e.g., upstream, downstream) sensor port, and the gland may be affixed with (e.g., welded to, coupled to) a second fitting body defining a second (e.g., inlet, outlet) port and a sensor retaining second (e.g., upstream, downstream) sensor port. To repair (e.g., clean) or replace the flow restricting insert 641c, the female threaded nut 648c is unthreaded from the male threaded connector 643c, and the flow restricting insert 641c is slid out of engagement from the face seal O-rings 645c, 646c for repair/reinstallation or replacement of the flow restricting insert 641c.

In other embodiments, the flow restricting element may be provided as a single piece body having a flow restriction assembled with or integral with the body. FIG. 14D illustrates an exemplary flow restricting element 640d with a single piece body 642d including first and second male threaded zero clearance connections 648d, 649d and a flow restriction 615d integrally formed along a through bore 647d (e.g., centrally located, as shown). To repair (e.g., clean) or replace the flow restriction 615d, the first and second male connections 648d, 649d are unthreaded from corresponding female threaded nuts (not shown) of the device to remove the flow restricting element 640d from the device.

In other embodiments, a flow restricting insert may be assembled with a single piece flow restricting element body, for example, using a threaded engagement, press fit engagement, or retaining clip engagement, and may in some embodiments include a gasket or seal to prevent leakage between the flow restricting element body and an outer periphery of the insert. FIG. 14E illustrates an exemplary flow restricting element 640e with a single piece body 642e

including first and second male threaded zero clearance connections 648e, 649e and a press-in orifice disc or apertured insert 641e (defining orifice 615e), installed in a through bore 647e of the body (e.g., seated against a counterbore in the through bore). FIG. 14F illustrates an exemplary flow restricting element 640f with a single piece body 642f including first and second male threaded zero clearance connections 648f, 649f and a press-in sintered element or porous insert 641f installed in a through bore 647f of the body (e.g., seated against a counterbore in the through bore) to define a porous flow path 615f. While the flow restricting insert may be positioned in a central portion of the through bore, between the end connections, as shown in FIGS. 14E and 14F, in other embodiments, the flow restricting insert may be installed within at least one of the end connections, in an end portion of the through bore. FIG. 14G illustrates an exemplary flow restricting element 640g with a single piece body 642g including first and second male threaded zero clearance connections 648g, 649g and a press-in sintered element or porous insert 641g installed in an end portion of the through bore 647g, in the first end connection 648g (e.g., seated against a counterbore in the through bore) to define a porous flow path 615g. FIG. 14H illustrates an exemplary flow restricting element 640h with a single piece body 642h including first and second male threaded zero clearance connections 648h, 649h and a restrictor set screw or threaded apertured insert 641h (defining orifice 615h) installed in a female threaded end portion of the through bore 647h, in the first end connection 648h. FIG. 14I illustrates an exemplary flow restricting element 640i with a single piece body 642i including first and second male threaded zero clearance connections 648i, 649i and an orifice disc or apertured insert 641i (defining orifice 615i) installed in an end face counterbore of the through bore 647i, in the first end connection 648i (e.g., snap fit or press fit). In one such embodiment, the o-ring seal 645i of the first end connection 648i provides a seal between the outer periphery of the orifice disc 641i and the counterbore.

To repair (e.g., clean) or replace the flow restricting inserts 641e-h, the first and second male connections 648e-h, 649e-h are unthreaded from corresponding female threaded nuts (not shown) of the device to remove the flow restricting element 640e-h from the device. The insert 641e-h may be removed (e.g., unthreaded, pressed) from the body 642e-h for cleaning or replacement. Alternatively, the entire flow restricting element 640e-h may be replaced.

Referring back to FIG. 14, the exemplary fluid monitoring module 600 includes an enclosure (shown schematically at 601) affixed to (e.g., at least partially enclosing) the flow sensing device 605 and enclosing a controller, shown schematically at 650 (which may be similar to the controller 550 of the embodiments of FIGS. 10A-13C). The sensors 620, 630 are connected (e.g., by wiring within the module enclosure) to the controller 650 to transmit pressure and temperature indicating signals to the controller. The controller 650 is configured to process the pressure and temperature indicating signals, for example, to determine pressure, temperature, and/or flow rate of fluid passing through the flow sensing device, and/or to provide a measured output of any one or more of these parameters. Similar to the exemplary embodiment of FIGS. 10A-13C, the module 600 may additionally be provided with one or more of: one or more internal batteries 660; a wireless transmitter (e.g., provided on a circuit board of the controller 650) for wirelessly transmitting fluid data to a remote device; an external antenna 655, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device; a

user interface, such as, for example, one or more knobs, switches or buttons, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller, and one or more display elements (e.g. indicator LEDs and/or display screen), as described in greater detail above.

The enclosure 601 may be provided with a cover or lid (not shown) to selectively enclose the flow sensing device 605, while being movable or removable for exposure of the flow sensing device, for example, to facilitate removal and/or replacement of the flow restricting element.

Still other arrangements may be utilized to facilitate removal and/or replacement of a flow restricting element from a flow sensing device. FIG. 15 schematically illustrates a fluid monitoring module 700 including a flow sensing device 705 having first and second T-shaped body members 710a, 710b including first run ports defining laterally outward extending inlet and outlet ports 711, 712, second run ports defining laterally inward extending upstream and downstream sensor ports 713, 714 (retaining upstream and downstream sensors 720, 730), and branch ports defining laterally extending first and second connections 718, 719, perpendicular to the inlet/outlet and sensor ports 711, 712 (i.e., extending outward from the drawing sheet), 713, 714, for connecting with first and second end laterally extending connectors 748, 749 of a U-shaped flow restricting element 740. The U-shaped flow restricting element 740 includes an axially extending portion defining one or more flow restricting passages 715, which may be formed, for example, in one or more inserts 741 (e.g., plugs, plates, etc.) retained in a U-shaped coupling body 742 to which the first and second end connections 748, 749 are attached (e.g., by welding or integrally forming). The coupling body 742 may be provided as a multiple piece assembly including one or more connectors 744 detachable to facilitate removal and/or replacement of the insert 741 from the coupling body. In one embodiment, the flow restricting insert(s) may be removable from the coupling body for replacement with alternative flow restricting inserts providing different flow rates, flow paths, materials, or other such properties. In other embodiments, the flow restricting component may be integrally or monolithically formed with the coupling body, such that the entire flow restricting element is replaced.

The U-shaped configuration of the flow restricting element 740 may facilitate removal from the flow sensing device 705 and may facilitate the use of end connections that are not zero-clearance connections (e.g., fittings that do not use elastomeric seals, for example, to allow for a wider range of system conditions), including, for example, tube fittings, quick disconnect fittings, and push-to-connect fittings.

According to another aspect of the present disclosure, a fluid monitoring module may be provided with a flow sensing device arranged such that at least a flow restricting element of the flow sensing device is external to a housing of the fluid monitoring module, for example, to facilitate removal of the flow restricting element without removing, disassembling, or otherwise adjusting the module housing. As one example, as shown in FIG. 16A, a fluid monitoring module 400a may be provided with a flow sensing device 405a having first (e.g., upstream) and second (e.g., downstream) sensor ports 413a, 414a mounted to the module enclosure 401a for electrical connection of retained sensors (which may be similar to the sensors 120, 130, 520, 530 of the embodiments of FIGS. 1-13C) to a controller enclosed within the module enclosure 401a, such that the flow restricting element 440a (e.g., any of the exemplary flow

restricting elements 640a-i of FIGS. 14A-I) is disposed external to the module enclosure 401a, for example, to facilitate removal and replacement/repair of the flow restricting element 440a.

In the embodiment of FIG. 16A, the flow sensing device 405a includes first and second T-shaped body members 410a-1, 410a-2 including first run ports defining laterally outward extending inlet and outlet ports 411a, 412a, second run ports defining the laterally inward extending sensor ports 413a, 414a, and branch or connecting ports defining axially extending first and second restrictor connections 418a, 419a for connecting with the flow restricting element 440a. As described above, the restrictor connections 418a, 419a may be zero-clearance connections to facilitate removal of the flow restricting element 440a.

In another exemplary arrangement, as shown in FIG. 16B, a fluid monitoring module 400b includes an externally mounted flow sensing device 405b having first and second T-shaped body members 410b-1, 410b-2 including first run ports defining axially extending inlet and outlet ports 411b, 412b, second run ports defining axially extending first and second restrictor connections 418b, 419b for connecting with the flow restricting element 440b (e.g., any of the exemplary flow restricting elements 640a-i of FIGS. 14A-I), and branch or connecting ports defining laterally inward extending sensor ports 413b, 414b mounted to the module enclosure 401b for electrical connection of the retained sensors (which may be similar to the sensors 120, 130, 520, 530 of the embodiments of FIGS. 1-13C) to a controller enclosed within the module enclosure 401b.

In another exemplary arrangement, as shown in FIG. 16C, a fluid monitoring module 400c includes an externally mounted flow sensing device 405c having first and second T-shaped body members 410c-1, 410c-2 including first run ports defining laterally outward extending inlet and outlet ports 411c, 412c, second run ports defining laterally inward extending first and second (e.g., upstream and downstream) sensor ports 413c, 414c mounted to the module enclosure 401c for electrical connection of the retained sensors (which may be similar to the sensors 120, 130, 520, 530 of the embodiments of FIGS. 1-13C) to a controller enclosed within the module enclosure 401c, and branch ports defining perpendicular laterally extending first and second restrictor connections 418c, 419c for connecting with a U-bend flow restricting element 440c (which may be similar to the flow restricting element 740 of FIG. 15).

Many different arrangements may be utilized to mount the sensor ports of the flow sensing device to the module enclosure. FIG. 17 illustrates an exemplary arrangement including a flow sensing device body member 410' including a male threaded sensor port or connector 413' received through a mounting aperture 408' in the module enclosure 401' and secured against the module enclosure by a panel nut 481' threaded with the male connector 413'. A sensor 420' is installed in the sensor port connector 413' and is secured against a counterbore 483' by a retaining collar 485' extending through the sensor port 413' to engage a surface of the sensor 420'. A fitting nut 487' is threadably assembled with the male connector 413' to secure an end portion 486' of the retaining collar 485', and a wire connector 489' (e.g., M8 connector) is installed in a central bore in the retaining collar end portion 486' to provide a connection between wiring 423' from the sensor 420' and the controller (not shown). Gasket seals 482', 484', 488' (e.g., O-ring seals) may be provided between the body member 410' and module enclosure 401', between the retaining collar 485' and male connector 413', and between the male connector 413' and wire

connector **489'**, for example, to seal the module enclosure **401'** from moisture or other contamination. A gasket seal **422'** (e.g., O-ring seal) around the sensor **420'** provides a leak tight seal to prevent system fluid leakage past the sensor **420'**.

In other exemplary arrangements, as illustrated, for example, in FIG. 16D, a fluid monitoring module **400d** may be provided with a flow sensing device **405d** having a first body member **410d-1** with a first (e.g., upstream) sensor port **413d** mounted to the module enclosure **401d** (e.g., using the arrangement of FIG. 17) for electrical connection of a retained sensor (e.g., as described above) to a controller enclosed within the module enclosure **401d**, and a second body member **410d-2** with a second (e.g., downstream) sensor ports **414d** spaced apart from the module enclosure and retaining a sensor (e.g., as described above) electrically connected (e.g., by flexible wiring **452d** extending from the second sensor port **414d** to the module enclosure **401d**) to a controller enclosed within the module enclosure **401d**, such that the flow restricting element **440d** is disposed external to the module enclosure **401d**, for example, to facilitate removal and replacement/repair of the flow restricting element **440d**. The single sensor port mount arrangement may allow for use of different sized flow restricting elements (e.g., different offset dimensions between the sensor ports, different lengths of flow restrictions) and/or different sized module enclosures. Additionally, the single sensor port mount arrangement may facilitate removal of the flow restricting element **440d** from the flow sensing device **405d** without using zero clearance connections (e.g., to eliminate polymeric seals in the connections), as the second sensor port is not fixedly mounted.

In still other exemplary arrangements, as illustrated, for example, in FIG. 16E, a fluid monitoring module **400e** may be provided with a flow sensing device **405e** having first and second body members **410e-1**, **410e-2** defining inlet and outlet ports **411e**, **412e**, and first and second (e.g., upstream and downstream) sensor ports **413e**, **414e** spaced apart from the module enclosure **401e** and retaining sensors (e.g., as described above) electrically connected (e.g., by flexible wiring **451e**, **452e** extending from the first and second sensor ports **413e**, **414e** to the module enclosure **401e**) to a controller enclosed within the module enclosure **401e**, such that the flow restricting element **440e** is disposed external to the module enclosure **401e**, for example, to facilitate removal and replacement/repair of the flow restricting element **440e**. The detached or remote, wire connected sensor port arrangement may allow for use of different sized flow restricting elements (e.g., different offset dimensions between the sensor ports, different lengths of flow restrictions) and/or different sized module enclosures. Additionally, the wire connected sensor port arrangement may facilitate removal of the flow restricting element **440e** from the flow sensing device **405e** without using zero clearance connections (e.g., to eliminate polymeric seals in the connections), as the sensor ports are not fixedly mounted and thus easily moveable with respect to each other. Additionally, in one such configuration, the module **400e** may be configured to easily disconnect from the sensor wiring **451e**, **452e**, for example, to allow use of the monitoring module with multiple flow sensing devices or to perform maintenance on the monitoring module.

According to another aspect of the present disclosure, a fluid monitoring module may be configured or adapted to provide separate sensing of fluid conditions in multiple fluid lines, or at multiple locations in a single fluid line, for example, to monitor changes in pressure over time (e.g., as

an indication of filter or fluid line contamination). In one such arrangement, the flow restriction may be eliminated, with the flow sensing arrangement providing separate sensor engaging flow paths. As one example, as shown in FIG. 18A, a fluid monitoring module **300a** may be provided with separate first and second sensing devices **305a-1**, **305a-2** having first and second (e.g., inlet and outlet) ports **311a-1**, **311a-2**, **312a-1**, **312a-2** and first and second sensor ports **313a-1**, **313a-2** mounted to the module enclosure **301a** for electrical connection of retained sensors (as described above) to a controller enclosed within the module enclosure **301a**.

As another example, a fluid monitoring module with an external flow restricting element may be converted to a fluid monitoring module having separate fluid sensing devices by separating the flow restriction with one or more blind or blank coupling members. FIG. 18B illustrates an exemplary fluid monitoring module **300b**, similar to the fluid monitoring module **400a** of FIG. 16A, except with the flow restricting element replaced with a fluid blocking blind or blank coupling **340b** installed between connections **318b**, **319b** of first and second body members **310b-1**, **310b-2**, to provide two separate dead-leg fluid monitoring locations. Alternatively (not shown), separate plugs may be assembled to the opposed body member connections.

FIG. 18C illustrates an exemplary fluid monitoring module **300c** including first and second cross-shaped flow sensing bodies **310c-1**, **310c-2**, with sensor ports **313c**, **314c** mounted to the module enclosure **301c**, first, axially outward extending ports **311c-1**, **311c-2**, second, laterally outward extending ports **312c-1**, **312c-2**, and axially inward extending restrictor connections **318c**, **319c**. To use the monitoring module **300c** to monitor flow rate, a flow restricting element (e.g., any of the flow restricting elements **440a-h** of FIGS. 14A-14I) may be assembled with the restrictor connections **318c**, **319c**, one of the ports **311c-1**, **312c-1** of the first flow sensing body **310c-1** may be connected with a fluid inlet line, one of the ports **311c-2**, **312c-2** of the second flow sensing body **310c-2** may be connected with a fluid outlet line, and the two unused ports may be plugged. To use the monitoring module **300c** to monitor two separate fluid locations, a blank or blind coupling **340c** (as shown, for example, in FIG. 18D) or blank/blind insert **341c** (as shown, for example, in FIG. 18E) may be assembled with the restrictor connections **318c**, **319c**, one of the ports **311c-1**, **312c-1**, **311c-2**, **312c-2** of each of the first and second flow sensing bodies **310c-1**, **310c-2** may be connected with first and second fluid inlet lines, and the others of the ports of each of the first and second flow sensing bodies **310c-1**, **310c-2** may be connected with first and second fluid outlet lines.

According to another aspect of the present disclosure, a fluid monitoring module may be configured to be provided as a separate, portable device that may be configured to be selectively connected to a fluid line for measurement of flow, temperature, and/or pressure conditions, thereby allowing for use of a single fluid monitoring module for multiple fluid lines.

FIG. 19 illustrates an exemplary system including a fluid line L with an engineered flow restriction R (e.g., provided in a flow restricting coupling, valve, etc.), and a fluid monitoring module **800**. The fluid line L includes branch connectors **C1**, **C2** (e.g., quick disconnect couplings) upstream and downstream of the flow restriction R, for connection with sensor port connectors **811**, **812** of upstream and downstream sensor ports **813**, **814** (e.g., using mating quick disconnect couplings) of the fluid monitoring module

21

800. Upstream and downstream sensors **820**, **830** (which may be similar to the sensors described above) are sealingly installed in the upstream and downstream sensor ports **813**, **814**, and are electrically connected to a controller **850** disposed in an enclosure **801** of the fluid monitoring module **800**. Similar to the exemplary embodiments of FIGS. 10A-13C, the module **800** may additionally be provided with one or more of: one or more internal batteries; a wireless transmitter (e.g., provided on a circuit board of the controller **850**) for wirelessly transmitting flow data to a remote device; an external antenna, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device; a user interface, such as, for example, one or more knobs, switches or buttons, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller, and one or more display elements (e.g. indicator LEDs and/or display screen), as described in greater detail above.

To monitor the flow conditions of the fluid line L, the upstream sensor port connector **811** is connected with the upstream fluid line branch connector C1 for measuring the pressure and/or temperature upstream of the flow restriction R, and the downstream sensor port connector **812** is connected with the downstream fluid line branch connector C2 for measuring the pressure and/or temperature downstream of the flow restriction R. Corresponding signals are transmitted from the sensors **820**, **830** to the controller **850** for calculation and identification (e.g., through a user interface or communication of the data to a remote computer) of the pressure, temperature, flow rate, and/or other fluid conditions.

In another embodiment, a fluid monitoring module may be configured to measure only pressure and temperature of a fluid, and not flow rate. In such an arrangement, the module may be provided with a single sensor port and sensor. FIG. 20 illustrates an exemplary system including a fluid line L and a fluid monitoring module **900**. The fluid line L includes a branch connector C (e.g., a quick disconnect coupling) for connection with a sensor port connector **911** of a sensor port **913** (e.g., using mating quick disconnect couplings) of the fluid monitoring module **900**. A sensor **920** (which may be similar to the sensors described above) is sealingly installed in the sensor port **913** and is electrically connected to a controller **950** disposed in an enclosure **901** of the fluid monitoring module **900**. Similar to the exemplary embodiments of FIGS. 10A-13C, the module **900** may additionally be provided with one or more of: one or more internal batteries; a wireless transmitter (e.g., provided on a circuit board of the controller **950**) for wirelessly transmitting fluid data to a remote device; an external antenna, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device; a user interface, such as, for example, one or more knobs, switches or buttons, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller, and one or more display elements (e.g. indicator LEDs and/or display screen), as described in greater detail above. In another application, the single sensor monitoring module **900** may be used to sequentially measure pressure at an upstream branch connector C1 and at a downstream branch connector C2 (see FIG. 16) to sequentially measure pressure upstream and downstream of an engineered flow restriction R in the fluid line L, thereby enabling the controller **950** to calculate a flow rate in the fluid line by using only one sensor.

In another embodiment, a portable, selectively connectable fluid monitoring module may include a bypass flow

22

path with a flow restricting passage between upstream and downstream sensor ports, thereby allowing for the elimination of the flow restriction from the fluid line, for example, to minimize contamination or erosion of the flow restriction.

FIG. 21 illustrates an exemplary system including a fluid line L and a fluid monitoring module **1000**. The fluid line L includes upstream and downstream branch connectors C1, C2 (e.g., quick disconnect couplings) for connection with inlet and outlet connectors **1011**, **1012** (e.g., mating quick disconnect couplings) of the module **1000**. The module **1000** further includes an upstream sensor port **1013** connected to the inlet connector **1011** by an upstream passage **1016**, and a downstream sensor port **1014** connected to the outlet connector **1012** by a downstream passage **1017**. Upstream and downstream sensors **1020**, **1030** (which may be similar to the sensors described above) are sealingly installed in the upstream and downstream sensor ports **1013**, **1014** and electrically connected to a controller **1050** disposed in an enclosure **1001** of the fluid monitoring module **1000**. The upstream and downstream passages **1016**, **1017** are connected by a flow restricting passage **1015**. The inlet and outlet connectors **1011**, **1012**, upstream and downstream sensor ports **1013**, **1014**, internal passages **1016**, **1017**, and flow restricting passage **1015** may be provided in a flow sensing device **1005** assembled with the module enclosure **1001**, as shown in the many exemplary embodiments described herein.

Similar to the exemplary embodiment of FIGS. 10A-13C, the module **1000** may additionally be provided with one or more of: one or more internal batteries; a wireless transmitter (e.g., provided on a circuit board of the controller **1050**) for wirelessly transmitting flow data to a remote device; an external antenna, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device; a user interface, such as, for example, one or more knobs, switches or buttons, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller, and one or more display elements (e.g. indicator LEDs and/or display screen), as described in greater detail above.

To monitor the flow conditions of the fluid line L, the inlet connector **1011** of the module is connected with the upstream fluid line branch connector C1 and the outlet connector **1012** is connected with the downstream fluid line branch connector C2. A shutoff valve V may be disposed in the fluid line L between the upstream and downstream branch connectors C1, C2, and may be shut off to bypass all fluid line flow through the fluid monitoring module **1000**. Alternatively, switching valves (shown in phantom at V1, V2) may be used to divert fluid flow from the fluid line L through the fluid monitoring module **1000**. The upstream sensor **1020** measures the pressure and/or temperature upstream of the flow restricting passage **1015**, and the downstream sensor **1030** measures the pressure and/or temperature downstream of the flow restricting passage **1015**. Corresponding signals are transmitted from the sensors **1020**, **1030** to the controller **1050** for calculation and identification (e.g., through a user interface or communication of the data to a remote computer) of the pressure, temperature, flow rate, and/or other fluid conditions.

In still another embodiment, a portable fluid monitoring module may be provided without fluid components (e.g., ports, connectors, passages), and with a wireless transceiver for communicating wirelessly with one or more fluid sensors integrated into the fluid line of a system, such that an operator may perform a fluid monitoring operation at one or

more locations in a fluid system by bringing the portable fluid monitoring module into proximity with the integrated fluid sensor(s).

FIG. 22 illustrates an exemplary system including a fluid line L with an engineered flow restriction R (e.g., provided in a flow restricting coupling, valve, etc.), and a portable fluid monitoring module 1400. The fluid line L includes fluid sensors 1420, 1430 (which may be similar to the sensors described above) upstream and downstream of a flow restriction 1415. While the fluid sensors 1420, 1430 and flow restriction 1415 may be integrated into the fluid line L, in an exemplary embodiment, the fluid sensors and flow restriction may be provided in a separate flow sensing device 1405 including connectors 1411, 1412 (e.g., zero clearance fittings) configured to facilitate coupling and decoupling from the fluid line L. The flow restriction 1415 may be provided in a flow restricting element 1440 having connectors 1448, 1449 to facilitate removal of the flow restricting element from the flow sensing device 1405 (e.g., for maintenance or replacement with a different flow restricting element having different sizing and/or flow characteristics).

The fluid monitoring module 1400 includes a transceiver 1470 configured to wirelessly communicate (e.g., RFID, Bluetooth, NFC, or other such wireless communication), for example, through an antenna 1475, with the fluid sensors 1420, 1430, when the fluid monitoring module 1400 is in proximity with the sensors 1420, 1430. Wireless communication may be automatically initiated when in proximity (e.g., as a result of periodic query or ping transmissions by the transceiver), or by actuation of a button or other such user interface. The transceiver 1470 communicates received data signals corresponding to the fluid system (e.g., identification codes, upstream/downstream pressure, temperature, time stamp) to a controller 1450 in the module enclosure 1401. Similar to the exemplary embodiment of FIGS. 10A-13C, the module 1400 may additionally be provided with one or more of: one or more internal batteries 1460; a wireless transmitter (e.g., provided on a circuit board of the controller 1450) for wirelessly transmitting flow data to a remote device; an external antenna 1455, electrically connected with the controller transmitter, for enhanced wireless communication with a remote device; a user interface, such as, for example, one or more knobs, switches or buttons, for example, to turn on the controller, to turn off the controller, or to commission/synchronize the controller, and one or more display elements (e.g. indicator LEDs and/or display screen), as described in greater detail above.

In one embodiment, the fluid monitoring module 1400 may be a smart phone or other such portable computing device that may be provided with a software or web-based application configured to initiate communication with the sensors 1420, 1430, process the received data signals, display data related to the fluid system conditions, and/or transmit fluid data to a remote system.

According to another aspect of the present disclosure, a fluid monitoring module having a controller configured for communicating with an external device may be further configured to receive data transmissions from other proximate fluid system components for communication of properties and characteristics of these proximate fluid system components to an external device for tracking or monitoring. As one example, a portable sample cylinder selectively connected to a fluid system (e.g., for obtaining a grab sample for off-site laboratory analysis) may include communication circuitry (e.g., RFID tag) configured to communicate directly or indirectly with a fluid monitoring module of the fluid system when the sample cylinder is proximate to the

fluid monitoring module. In one example, the fluid monitoring module may include or be connected with (e.g., by a wired or wireless connection) an RFID reader configured to initiate wireless communication (e.g., near field communication, Bluetooth® communication, or other such short range wired or wireless communication) with an RFID tag or transmitter provided with the sample cylinder when the sample cylinder is brought into range of the fluid monitoring module (e.g., by responding to a periodic query or ping from the reader). In other embodiments, communication between the RFID tag/transmitter and the RFID reader may be initiated by a user operated push button switch, or by a switch that is automatically activated when the sample cylinder is connected to the fluid system or when a valve is opened to fill the cylinder.

FIG. 23 schematically illustrates an exemplary system including a fluid line L with which a fluid monitoring module 1300 (e.g., any of the fluid monitoring modules described herein) is installed. The fluid line L includes a branch connector C to which a sample cylinder 1370 may be connected (e.g., by a quick disconnect coupling connection), for example, for obtaining a grab sample of the fluid in the fluid line. The sample cylinder 1370 includes an RFID tag/transmitter 1375 for communicating data regarding the sample cylinder (e.g., serial/ID number, time stamp associated with time of connection to fluid line L) to an RFID reader 1380 provided with or connected to the fluid monitoring module 1300. The data received by the RFID reader 1380 may be communicated to the controller 1350 of the module 1300 (e.g., by a wired or wireless connection between the controller and the RFID reader) and compiled with other contemporaneous fluid system data collected by the controller (e.g., flow rate, pressure, temperature of fluid in the fluid line as measured by sensors 1320, 1330, serial/ID number of the module 1300), and wirelessly communicated via transmitter antenna 1355 to an external device, for example, via a wireless gateway 1390, as powered, for example, by module battery 1360. Such an arrangement allows for real time tracking of a grab sampling operation without providing separate power and wireless transmission capability to the grab sample arrangement, by using the fluid monitoring module as a hub for such data collection and wireless communication.

In other applications, other data may be collected and communicated via the fluid monitoring modules. For example, operator identification data (e.g., as collected from a user ID RFID tag) and an associated timestamp may be transmitted to the controller when one or more operations are performed, such as, for example, grab sampling, maintenance, system shutoff, etc.

The inventive aspects have been described with reference to the exemplary embodiments. Modification and alterations will occur to others upon a reading and understanding of this specification. It is intended to include all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

We claim:

1. A fluid monitoring module comprising:

a flow sensing device including:

- a body including an inlet port, an outlet port, an upstream sensor port, a downstream sensor port, and a flow restricting passage disposed between the inlet port and the outlet port, and between the upstream sensor port and the downstream sensor port;
- a first fluid sensor assembled with the upstream sensor port; and

25

a second fluid sensor assembled with the downstream sensor port;
 an enclosure; and
 a controller disposed within the enclosure and in circuit communication with the first and second fluid sensors for receiving at least one of pressure indicating signals and temperature indicating signals from each of the first and second fluid sensors, and for measuring fluid data based on the received signals;
 wherein the flow sensing device body includes a first body member defining the inlet port and the upstream sensor port, a second body member defining the outlet port and the downstream sensor port, and a flow restricting element defining the flow restricting passage and including a first end connection coupled to a first connecting port of the first body member and a second end connection coupled to a second connecting port of the second body member.

2. The fluid monitoring module of claim 1, wherein the flow restricting passage is configured to provide laminar flow.

3. The fluid monitoring module of claim 1, further comprising a battery arrangement disposed within the enclosure and electrically connected with the controller.

4. The fluid monitoring module of claim 1, further comprising a wireless transmitter for wirelessly communicating the fluid data from the controller to a remote device.

5. The fluid monitoring module of claim 1, wherein the fluid data comprises at least one of fluid pressure, fluid temperature and fluid flow rate.

6. The fluid monitoring module of claim 1, further comprising a user interface disposed on an exterior surface of the enclosure and in circuit communication with the controller, the user interface being configured to display information corresponding to the measured fluid data.

7. The fluid monitoring module of claim 6, wherein the user interface comprises a display screen.

8. The fluid monitoring module of claim 6, wherein the user interface comprises an LED array arranged in one of a digital display and a multi-bar display.

9. The fluid monitoring module of claim 8, wherein the LED array comprises a plurality of multi-colored LEDs, wherein the controller is configured to illuminate the plurality of multi-colored LEDs in a first color to display information corresponding to a first fluid property, and in a second color to display information corresponding to a second fluid property.

26

10. The fluid monitoring module of claim 9, wherein the first fluid property comprises one of flow rate, temperature, and pressure, and the second fluid property comprises another of flow rate, temperature and pressure.

11. The fluid monitoring module of claim 1, wherein the first and second end connections comprise zero clearance connectors.

12. The fluid monitoring module of claim 1, wherein the first and second connecting ports extend laterally from the first and second body members in a first direction, and the flow restricting element includes an axially extending portion disposed between the first and second end connections.

13. The fluid monitoring module of claim 1, wherein the flow restricting element is external to the enclosure.

14. The fluid monitoring module of claim 13, wherein at least one of the upstream and downstream sensor ports is mounted to the enclosure, such that a corresponding at least one of the first and second fluid sensors is disposed within the enclosure.

15. The fluid monitoring module of claim 13, wherein at least one of the upstream and downstream sensor ports is spaced apart from the enclosure, with a wired connection between the corresponding at least one of the first and second fluid sensors and the enclosure for circuit communication with the controller.

16. The fluid monitoring module of claim 1, wherein the flow restricting element comprises at least a first coupling member defining at least one of the first and second end connections.

17. The fluid monitoring module of claim 16, wherein the flow restricting passage is integrally formed in the first coupling member.

18. The fluid monitoring module of claim 16, wherein the flow restricting passage is defined by a flow restricting insert assembled with the first coupling member.

19. The fluid monitoring module of claim 18, wherein the flow restricting insert is disposed in a through bore between the first and second end connections.

20. The fluid monitoring module of claim 18, wherein the flow restricting insert is disposed in one of the first and second end connections.

21. The fluid monitoring module of claim 16, further comprising a second coupling member joined with the first coupling member and defining the other of the first and second end connections.

* * * * *