




(86) Date de dépôt PCT/PCT Filing Date: 2012/05/23
(87) Date publication PCT/PCT Publication Date: 2012/12/27
(45) Date de délivrance/Issue Date: 2019/03/12
(85) Entrée phase nationale/National Entry: 2013/11/28
(86) N° demande PCT/PCT Application No.: GB 2012/000455
(87) N° publication PCT/PCT Publication No.: 2012/175907
(30) Priorités/Priorities: 2011/06/21 (GB1110461.9);
2012/05/08 (GB1208011.5); 2012/05/22 (GB1208962.9)

(51) Cl.Int./Int.Cl. E04B 1/41 (2006.01)

(72) Inventeur/Inventor:
SOMERFIELD, ALAN, GB
(73) Propriétaire/Owner:
GRIPPLE LIMITED, GB
(74) Agent: ROBIC

(54) Titre : DISPOSITIF D'ANCRAGE ET PROCEDE D'UTILISATION D'UN ENSEMBLE D'ANCRAGE COMPRENANT LE DISPOSITIF
(54) Title: ANCHOR DEVICE AND METHOD OF USING AN ANCHOR ASSEMBLY COMPRISING THE ANCHOR DEVICE



(57) Abrégé/Abstract:

An anchor device (10) for a floor, the anchor device comprising an article securing arrangement (12) to which an article (26) can be secured. The article has a moveable securing mechanism (27). The article securing arrangement defines a cavity (24) to receive the moveable securing mechanism, and the article securing arrangement includes a co-operating means (20) to co-operate with the moveable securing mechanism in the cavity and secure the article to the anchor device. The anchor device has a height which is no more than 30 mm.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(10) International Publication Number

WO 2012/175907 A1

(43) International Publication Date
27 December 2012 (27.12.2012)

(51) International Patent Classification:
E04B 1/41 (2006.01)

(21) International Application Number:
PCT/GB2012/000455

(22) International Filing Date:
23 May 2012 (23.05.2012)

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
1110461.9 21 June 2011 (21.06.2011) GB
1208011.5 8 May 2012 (08.05.2012) GB
1208962.9 22 May 2012 (22.05.2012) GB

(71) Applicant (for all designated States except US):
GRIPPLE LIMITED [GB/GB]; The Old West Gun Works, Savile Street East, Sheffield, South Yorkshire S4 7UQ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SOMERFIELD, Alan** [GB/GB]; 53 Malton Road, Lincoln LN6 8HZ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: ANCHOR DEVICE




Fig. 1

(57) Abstract: An anchor device (10) for a floor, the anchor device comprising an article securing arrangement (12) to which an article (26) can be secured. The article has a moveable securing mechanism (27). The article securing arrangement defines a cavity (24) to receive the moveable securing mechanism, and the article securing arrangement includes a co-operating means (20) to co-operate with the moveable securing mechanism in the cavity and secure the article to the anchor device. The anchor device has a height which is no more than 30 mm.

Anchor Device And Method Of Using An anchor Assembly Comprising The Anchor
Device

This invention relates to anchor devices for floors. More particularly, but not exclusively, this invention relates to anchor devices for metal deck or wood form floors. Embodiments of the invention relate to anchor devices for concrete floors.

In some buildings, concrete floors are provided in storeys above ground level. It is often necessary to provide anchor devices to which light fittings can be attached for 10 the room below. The concrete floor can be arranged over a wood form or metal deck, on which the anchor devices are mounted. In the case of wooden forms, the anchor device can be removably mounted on the wooden forms. The wooden forms are removed once the concrete has set to leave the concrete with anchors embedded therein.

According to the present invention, there is provided an anchor assembly comprising an anchor device and an article; the anchor device comprising an article securing arrangement to which the article is securable; and the article comprising a movable securing mechanism having a main part and a securing member movably mounted on 20 the main part; wherein the article securing arrangement defines a cavity to receive the movable securing mechanism, the article securing arrangement includes a formation in the cavity to co-operate with the movable securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted into the cavity, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device; and wherein the securing member projects beyond the main part when the securing member is in the non-securing position.

According to the present invention, there is also provided a method of using an anchor 30 assembly, said anchor assembly comprising: an anchor device and an article; the anchor device comprising an article securing arrangement to which the article is securable; and the article comprising a movable securing mechanism having a main part and a securing member movably mounted on the main part; wherein the article

securing arrangement defines a cavity having an inner surface, the cavity being configured to receive the movable securing mechanism, the article securing arrangement including a formation in the cavity to co-operate with the movable securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted upwardly into the cavity through an underside of the securing arrangement, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device; wherein the securing member projects beyond the main part when the securing member is in the non-
10 securing position, and the securing member extends transverse to the main part when the securing member is in the securing position; and wherein the method comprises inserting the article upwardly into the cavity, and engaging the securing member against the inner surface to move the securing member to the securing position.

Preferred embodiments are described hereunder.

According to one aspect of this invention, there is provided an anchor device for a floor, the anchor device comprising an article securing arrangement to which an article can be secured, wherein the article securing arrangement defines a cavity to receive a
20 portion of the article, and the anchor device has a height which is no more than 30 mm.

The article securing arrangement may have an underside and the article may be secured to the article securing arrangement through said underside.

The article may have a moveable securing mechanism, and the cavity may be configured to receive the moveable securing mechanism. The article securing arrangement may include co-operating means to co-operate with the moveable securing mechanism in the cavity and secure the article to the anchor device.

30 According to another aspect of this invention, there is provided an anchor device for a floor, the anchor device comprising an article securing arrangement to which an article can be secured from below, wherein the article securing arrangement defines a cavity to receive the article, and the article securing arrangement includes a co-

operating means to co-operate with the article in the cavity and secure the article to the anchor device.

According to another aspect of this invention, there is provided an anchor device for a floor, the anchor device comprising an article securing arrangement to which an article can be secured, the article having a moveable securing mechanism, wherein the article securing arrangement defines a cavity to receive the moveable securing mechanism, and the article securing arrangement includes co-operating means to co-operate with the moveable securing mechanism in the cavity and secure the article to the anchor device.

According to another aspect of this invention, there is provided an anchor assembly comprising an anchor device as described above and an article comprising a moveable securing mechanism, wherein the article securing arrangement defines a cavity to receive the moveable securing mechanism, and the article securing arrangement includes co-operating means to co-operate with the moveable securing mechanism in the cavity and secure the article to the anchor device.

The securing mechanism may comprise a main part and a securing member movably mounted on the main part. The securing member may be pivotally mounted on the main part. The securing arrangement may be configured to receive the securing mechanism from below. The securing arrangement may have an underside, and may be configured to receive the securing mechanism through said underside.

The anchor device may further include fastening means to enable the anchor device to be fastened to the floor. The floor may comprise a metal deck or wood form floor.

The anchor device may have a low profile configuration. The anchor device may have a height which is no more than 30 mm.

The article securing arrangement may comprise a body part comprising a base element and a cover element extending over the base element. The base element

and the cover element may define the cavity. The securing arrangement may be configured to receive the securing mechanism through the base element.

The article securing arrangement may define an aperture through which the article can extend. The aperture may be defined by the base element. The co-operating means may comprise the base element.

The securing mechanism may be moveable from a non-securing condition to a securing condition. When the securing mechanism is in the non-securing condition, the securing mechanism can be inserted into the cavity. When the securing mechanism is in the securing condition in the cavity, the article is secured to the anchor device.

The securing member may be moveable, for example pivotally moveable, relative to the main part from a non-securing position, to allow the securing member to be inserted into the cavity, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device. When the securing member is in the non-securing position, the securing member may be aligned with the main part. When the securing member is in the securing position, the securing member may extend transverse to the main part.

The cavity may be wider than the aperture, whereby when the securing member is received in the cavity, movement of the securing member to the securing position moves the securing member to a position in which it extends across the aperture to engage the base element, thereby retaining the securing member in the cavity.

The securing member may be pivotally mounted on the main portion of the article, and may be pivotally moveable from the non-securing position to the securing position.

The anchor device may include a floor engaging member for engaging the floor, the floor engaging member defining a channel therethrough in communication with the

aperture, whereby the article can extend through the aperture and through the channel.

In a first embodiment, the anchor device may include a receiving arrangement defining a space for receiving a curable material, such as concrete. The receiving arrangement may define at least one gap providing communication with the space, to allow said curable material to enter the space. The receiving arrangement may define a plurality of said gaps. The first embodiment may be suitable for use with a floor made with a wood form,

The receiving arrangement may comprise a plurality of outwardly extending fingers, wherein the, or each, gap is defined between adjacent fingers. The fingers may extend to a region substantially coplanar with a lower region of the article securing arrangement, such as the floor engaging member. The receiving arrangement may extend from the article securing arrangement.

The receiving arrangement may comprise first and second support portions extending from the article securing arrangement. The first and second support portions may extend opposite each other from the body part. The base element may extend outwardly from the body part to provide the, or each, support portion.

The receiving arrangement may further include a plurality of the fingers on each of the first and second support portions. Each of the fingers may have distal free end region for engaging the surface. The distal free end region may be V shaped.

Alternatively, the distal end region of the fingers may be connected to one another by a connecting member. The connecting member may be substantially circular, and may comprise a web. The connecting member may extend substantially wholly around the article securing arrangement. The distal end region of each finger may taper outwardly to a wide portion, wherein said wide portion is attached to the connecting member.

The article securing arrangement may be configured to substantially prevent the curable material being received in the cavity.

The fastening means may comprise a fastener holding means for holding a fastener. The fastener may comprise a screw or a nail, and the holding means may comprise a holding member, which may be tubular. The fastener may extend through the holding member.

The holding means may comprise two holding members, which may be arranged opposite each other on the article securing arrangement.

In a second embodiment, suitable for use with a floor made with a metal deck, the fastening means may comprise a fastening member, which can be inserted through an opening in the floor. The fastening member may comprise a tube through which the article can extend.

The fastening member may include a formation for engaging the floor around said opening, and thereby fasten the anchor device to the floor. The formation may comprise a detent formation. The detent formation may be defined by the fastening member. The recess may extend around the fastening member.

The fastening means may comprise a floor engaging member configured to engage the floor. The floor engaging member may comprise an outwardly extending member extending outwardly from the fastening member. The outwardly extending member may extend radially outwardly from the fastening member.

The base element of the second embodiment may be arranged between the cover element and the fastening means. The cover element may have a body portion to define the cavity. The cover element may also have a flange portion extending outwardly from the main portion to engage the base element.

The flange portion and the body portion of the cover have corresponding co-operating formations which may co-operate with each other to attach the cover

element to the base element. The co-operating formations may comprise a plurality of through holes and a plurality of corresponding push-fit members which can be received in the holes, thereby securing the cover element to the base element. In one embodiment, the holes may be defined by the base element and the push-fit members may be provided on the cover element.

The floor engaging member of the fastening means may have formations to co-operate with corresponding formations on the article securing arrangement. The formations may be holes in the floor engaging member to receive the push-fit members on the cover element.

Hence, according to a broad aspect, the invention provides a method of using an anchor assembly, the anchor assembly comprising: an anchor device and an article; the anchor device comprising an article securing arrangement to which the article can be secured and the article comprising a movable securing mechanism having a main part and a securing member movably mounted on the main part; wherein the article securing arrangement defines a cavity having an inner surface, the cavity being configured to receive the movable securing mechanism, the article securing arrangement including a formation in the cavity to co-operate with the movable securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted upwardly into the cavity through an underside of the securing arrangement, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device; wherein the securing member projects beyond the main part when the securing member is in the non-securing position, and the securing member extends transverse to the main part when the securing member is in the securing position; and wherein the method comprises inserting the article into the cavity and engaging the securing member against the inner surface of the article securing arrangement to move the securing member to the securing position.

According to another broad aspect, the invention provides an anchor assembly, comprising: an anchor device and an article; the anchor device comprising an article securing arrangement to which the article can be secured and the article comprising a

movable securing mechanism having a main part and a securing member movably mounted on the main part; wherein the article securing arrangement defines a cavity having an inner surface, the cavity being configured to receive the movable securing mechanism, the article securing arrangement includes a formation in the cavity to cooperate with the movable securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted into the cavity, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device; and wherein the securing member projects beyond the main part when the securing member is in the non-securing position to engage the inner surface of the article securing arrangement and move to the securing position.

Variants, examples and preferred embodiments of the invention will now be described by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a first embodiment of an anchor device in use;

Figure 2 is a side view of the first embodiment of the anchor device in use;

Figure 3 is a sectional side view of the first embodiment of the anchor device being fastened to a surface;

Figure 4 is a sectional side view showing an article being secured to the first embodiment of the anchor device, with a securing mechanism in a non-securing position;

Figure 5 is a sectional side view showing the article secured to the first embodiment of the anchor device, with the securing mechanism in a securing position;

Figure 6A shows the article with the securing mechanism in a non-securing position;

Figure 6B shows the article with the securing mechanism in a securing position;

Figure 7 shows a second embodiment of an anchor device mounted in a well of a floor deck;

Figure 8 is a sectional side view of the second embodiment of the anchor device;

Figure 9 is an exploded view of the second embodiment of the anchor device;

Figure 10 is a close up of the region marked X in Figure 8;

Figure 11 is a top plan view of an alternative version of the embodiment shown in Figures 1 to 5; and

Figure 12 is a side view of the embodiment shown in Figure 11.

Referring to the Figures 1 to 5 of the drawings, there is shown a first embodiment of an anchor device 10 for use in providing an anchor device on a floor. In the embodiment shown, the anchor device 10 is used for securing, for example, a ceiling light to a ceiling. The anchor device 10 is arranged on the floor above the room where the ceiling light is to be installed. The cable for the ceiling light extends downwardly from the anchor device 10 through the floor to the room below, so that the ceiling light is suspended from the ceiling of the room below.

The anchor device 10 is particularly useful where the floor is to be a concrete floor. In such circumstances, the concrete floor is constructed by first providing a wood form 100 upon which the concrete is laid. When the concrete has set the wood form is removed.

Prior to pouring the concrete, the anchor device 10 is arranged on the wood form 100 in positions where a ceiling light is to hang from the ceiling of the room below. Alternatively, the wood form may remain in place. An opening 102 (see Figures 3, 4 and 5) can be drilled through the wood form 100 prior to mounting of the anchor device 10 thereon.

The anchor device 10 comprises an article securing arrangement 12 and a receiving arrangement 14. The receiving arrangement 14 comprises first and second support portions 16, 18 extending opposite each other from the article securing arrangement 12.

The article securing arrangement 12 comprises a body part in the form of a base element 20 and a dome shaped cover element 22. The base element 20 defines an aperture 21 therethrough. The cover element 22 extends over the base element 20 and defines a cavity 24 therewith. The cover element 22 provides a seal around the base element 20, thereby preventing the concrete from being received therein.

An article can extend through the aperture 21 into the cavity 24. In the embodiment described herein, the article is an elongate suspension device 26, which may be used for suspending a ceiling light. The suspension device 26 includes a securing mechanism 27. The securing mechanism 27 is secured in the cavity 24 in a manner described below. Thus, an anchor assembly is provided, the anchor assembly comprising the anchor device 10 and the elongate suspension device 26.

The base element 20 extends outwardly in opposite directions from the article securing arrangement 12 to provide the first and second support portions 16, 18. Thus, the base element 20 and the first and second support portions 16, 18 are formed of a single piece of a suitable material, for example a plastics material. The first and second support portions 16, 18 extend outwardly and upwardly from the base element 20.

The receiving arrangement 14 further includes a plurality of fingers 28 on the first and second support portions 16, 18. The embodiment shown in Figures 1 to 5 has eight fingers 28 arranged in two groups of four fingers 28 opposite each other.

The fingers 18 extend from, and are supported by, the first and second support portions 16, 18. Gaps 30 are defined between adjacent fingers 28. A receiving space 32 is defined by each of the first and second support portions 16, 18 and the

fingers 28. The receiving space can receive concrete spread on the lower layer 100, as explained in more detail below.

Each finger 28 comprises a first region 28A extending outwardly from the first or second support portions 16, 18 and a second region 28B extending downwardly from the first regions 28A. Each of the second regions 28B has a V shaped distal end region 28C which can engage the lower layer 100.

The anchor device 10 further includes holding means in the form of first and second tubular holding members 34, 36, through which fasteners in the form of nails 38 can extend into the lower layer 100.

A floor engaging part 40 extends downwardly from the base part 20 and defines a channel 42 in communication with the aperture 21 in the base part 20. The channel 38 is aligned with the aperture 21, and tapers outwardly therefrom.

The anchor device 10 is disposed on the lower layer 100 with the aperture 21 and the channel 42 in alignment with the opening 102. In this position, the distal end regions 28C of the fingers 28 engage the lower layer 100. In order to fasten the anchor device 10 to the lower layer 100, nails 38 are driven through the tubular holding members 34, 36 into the lower layer 100.

Referring to Figures 6A and 6B, the suspension device 26 comprises the securing mechanism 27 and an elongate cable 38. The securing mechanism 27 is provided on one end of the cable 38. The securing mechanism 27 comprises a main part 44 and a securing member in the form of a toggle 46 pivotally mounted on the main part 44. The toggle 46 can pivot between a non-securing position shown in Figures 4 and 6, and a securing position shown in Figures 5 and 6B.

When the toggle 46 is in the securing position, the toggle 46 extends across the aperture 21, and cannot pass through the aperture 21. As a result, the toggle 46 is retained in the cavity 24, and the article is thus secured to the anchor device 10.

As can be seen in Figure 4, the suspension device 26 is installed in the anchor device 10 by disposing the toggle 46 in the non-securing position, and pushing the securing mechanism 27 through the opening 102 in the floor and through the channel 42 and the aperture 21. This inserts the toggle 46 into the cavity 24.

The toggle 46 is appropriately weighted so that, when it is inserted into the cavity 24, the toggle 46 pivots automatically to its securing position shown in Figure 5. This prevents the securing mechanism 27 from being removed from the anchor device 10, thereby securing the suspension device 26 to the anchor device 10.

Alternatively, the toggle can be inserted into the cavity 24 so that, upon insertion, the toggle 46 engages the inside of the cover element 22, which dislodges the toggle 46 from its non-securing position to its securing position.

When the anchor device 10 has been fastened to the lower layer 100 by the use of the nails 38, as described above, the concrete is spread over the lower layer 100, and over the anchor device 10 so that the anchor device 10 is wholly embedded within the concrete.

During such spreading, the concrete flows through the gaps 30 between the fingers 28, and into the receiving spaces 32. When the concrete sets, the anchor device 10 is held in its position on the lower layer by the nails 38 and the concrete.

There is thus described an anchor device 10 which allows suspension arrangements to be anchored thereon from which lights can be suspended.

The anchor device 10 has an advantage that, in the embodiment described herein, the receiving portions extend outwardly from the main body over a distance which is substantially equal to the diameter of the main body. This allows the anchor device 10 to be of a low profile configuration, thereby making it less likely that workers pouring the concrete over the anchor device 10 will accidentally kick it thereby damaging it or themselves.

A second embodiment of the invention is shown in Figures 7 to 10.

The second embodiment of the anchor device is generally designated 110, and is intended to be mounted in a well 202 of a metal deck 200 forming a floor (not shown). After the necessary number of the anchor devices 110 are mounted on the metal deck 200, concrete can be laid on the deck 200 to form the floor.

Referring to Figures 8, 9 and 10, the anchor device 110 comprises an article securing arrangement 112, which comprises a base element 120 and a cover element 122. The base element 120 defines an aperture 121.

The cover element 122 is mounted on the base element 120 and defines a cavity 124 therewith, the aperture 121 providing communication between a region external of the anchor device 110 and the cavity 124. The cover element 122 provides a seal around the base element 120, thereby preventing the concrete from being received therein.

The cover element 122 has a dome shaped body portion 126, which defines the cavity 124 with the base element 120. The cover element 122 may also have a substantially circular flange portion 128 extending outwardly from the body portion 126 to engage the base element 120.

A circumferential edge member 129 extends downwardly from the flange portion 128 at the outer edge thereof. The edge member 129 defines a circular shallow recess 129A in which the base element 120 is received. The base element 120 is of a size that it just fits within the recess 129A.

The base element 120 is in the form of a substantially circular disc. The aperture 121 is defined substantially centrally of the base element 120. The base element also defines a plurality of through holes 130 (see Figure 10) arranged in a circumferential array adjacent the outer edge of the base element 120. The flange portion 128 of the cover element 122 has a plurality of downwardly extending push-fit members 132.

The push-fit members 132 and the through holes 130 are provided on or in the respective flange portion 128 and base element 120 in corresponding positions. The positions of the through holes 130 and the push-fit members 132 are such that the push-fit members 132 are received in the through holes 130 when the base portion 120 is received in the recess 129A.

The push-fit members 132 are a tight fit within the through holes 130 and thereby secure the base element 120 to the cover element 122.

The anchor device 110 is mounted on the metal deck 200 over an opening 204 therein, and is positioned on the metal deck 200 so that the aperture 121 in the base element 120 is aligned with the opening 204, as shown in Figure 10.

A fastening means 134 is provided to fasten the anchor 110 to the deck 200. The fastening means 134 comprises a floor engaging member 136 to engage the deck 200. The floor engaging member defines a central aperture 135.

The fastening means 134 further includes an elongate tubular fastening member 138 extending downwardly from the floor engaging member 136 at the aperture 135. The fastening member 138 defines a cylindrical passage 139 communicating with the aperture 135 in the floor engaging member 136.

The fastening member 138 has a fastening formation in the form of a detent 140 closely spaced from the floor engaging member 136. The detent 140 is circular and extends around the tubular fastening member 138.

A circular recess 142 is defined around the fastening member 138 between the detent 140 and the floor engaging member 136. In order to mount the fastening member on the deck 200, the tubular fastening member 138 is first inserted into the opening 121 from above, with the floor engaging member 136 uppermost. The fastening means 134 is then pushed downwardly through the opening 121 until the detent 140 engages the deck 200 around the opening 121.

Further pushing of the fastening means 134 downwardly causes the detent 140 to deform inwardly until the detent passes over the deck 200. The detent 140 snaps back to its non-deformed position to engage the underside of the deck 200 around the opening 121. As a result, the region of the deck 200 surrounding the opening 121 is held between the detent 140 and the floor engaging member 136, thereby fastening the fastening means to the deck 200.

The article securing arrangement 112 fastened to the floor engaging member by means of the push-fit members 132. Lower portions of the push-fit members 132 extend beyond the through holes 130 on the underside of the base element 120.

The floor engaging member 136 defines a plurality of through holes 144 arranged in a circumferential array adjacent the outer edge of the base element floor engaging member 136. The positions of the through holes 144 are such that lower portions of the push-fit members 132 can be received in the through holes 144 when the anchor device is assembled as shown in Figure 10.

A suspension device 26, similar to that described above can then be arranged so that the toggle 46 is in its non-securing position inserted upwardly through the tubular fastening member 138. When the toggle 46 is received in the cavity 124, it moves to the securing position shown in Figure 10, either under its weight, or by being engaged against the inner surface of the cover element 122.

When the toggle 46 is in its securing position in the cavity 124, as shown in Figure 10, it cannot be removed therefrom via the aperture 121 and, therefore, secures the suspension device 26 to the anchor device 110.

The provision of the securing mechanism 27 and the cavity 24, as described above provides the advantage that the height of the anchor devices 10, 110 is considerably less than known anchor devices. The height of each of the anchor devices 10, 110 shown in the drawings is substantially 30 mm. A consequence of this is that the anchor devices 10, 110 are much less likely to be kicked or tripped over by those

working on the construction of the floor, which results in less damage to the anchor devices 10, 110, and less likelihood of injury to the workers.

Various modifications can be made without departing from the scope of the invention. For example, Figures 11 and 12 depict an alternative version of the first embodiment of the anchor device 10 shown in Figures 1 to 5.

The embodiment shown in Figures 11 and 12 has many of the same features as the first embodiment, and these features have been designated with the same reference numerals as in Figures 1 to 5. The anchor device 10 shown in Figures 11 and 12 differs from the first embodiment in that it has four equi-spaced fingers 28 instead of eight fingers 28.

In addition, the fingers 28 have distal end regions 28C that taper outwardly from the second region 28B. The distal end regions 28C are connected to a horizontally extending circular flange portion 200, which extends around the fingers 28. The underside 202 of the flange portion 200 engages the form 100 to provide a stable platform for the anchor device 10.

CLAIMS

1. A method of using an anchor assembly, the anchor assembly comprising:
an anchor device and an article;
the anchor device comprising an article securing arrangement to which the article can be secured and the article comprising a movable securing mechanism having a main part and a securing member movably mounted on the main part;
wherein the article securing arrangement defines a cavity having an inner surface, the cavity being configured to receive the movable securing mechanism, the article securing arrangement including a formation in the cavity to co-operate with the movable securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted upwardly into the cavity through an underside of the securing arrangement, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device;
wherein the securing member projects beyond the main part when the securing member is in the non-securing position, and the securing member extends transverse to the main part when the securing member is in the securing position; and
wherein the method comprises inserting the article into the cavity and engaging the securing member against the inner surface of the article securing arrangement to move the securing member to the securing position.
2. A method according to claim 1, wherein the securing member is pivotally mounted on the main part for pivotal movement from the non-securing position to the securing position.
3. A method according to claim 1 or 2, wherein the article securing arrangement having an underside and the article being secured to the article securing arrangement through the underside.

4. A method according to claim 1, 2 or 3, wherein the article securing arrangement is configured to receive the securing mechanism through the underside.
5. A method according to any one of claims 1 to 4, wherein the article securing arrangement comprises a body comprising a base element and a cover element extending over the base element, the base element and the cover element defining the cavity.
6. A method according to claim 5, wherein the base element defines an aperture through which the securing member can be inserted into the cavity, the cavity being wider than the aperture, whereby when the securing member is received in the cavity, movement of the securing member to the securing position moves the securing member to a position in which it extends across the aperture to engage the base element, thereby retaining the securing member in the cavity.
7. A method according to any one of claims 1 to 6, wherein when the securing member is in the non-securing position, the securing member is substantially aligned with the main part.
8. A method according to any one of claims 1 to 7, wherein when the securing member is in the non-securing position, the securing mechanism can be inserted into the cavity.
9. An anchor assembly, comprising:
 - an anchor device and an article;
 - the anchor device comprising an article securing arrangement to which the article can be secured and the article comprising a movable securing mechanism having a main part and a securing member movably mounted on the main part;
 - wherein the article securing arrangement defines a cavity having an inner surface, the cavity being configured to receive the movable securing mechanism, the article securing arrangement includes a formation in the cavity to co-operate with the movable

securing mechanism and secure the article to the anchor device, and the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted into the cavity, to a securing position, to secure the securing member in the cavity and thereby secure the article to the anchor device; and

wherein the securing member projects beyond the main part when the securing member is in the non-securing position to engage the inner surface of the article securing arrangement and move to the securing position.

10. An anchor assembly according to claim 9, wherein the securing member is pivotally mounted on the main part for pivotal movement from the non-securing position to the securing position.

11. An anchor assembly according to claim 9 or 10, wherein the article securing arrangement having an underside and the article being secured to the article securing arrangement through the underside.

12. An anchor assembly according to claim 9, 10 or 11, wherein the article securing arrangement is configured to receive the securing mechanism through the underside.

13. An anchor assembly according to any one of claims 9 to 12, wherein the article securing arrangement comprises a body comprising a base element and a cover element extending over the base element, the base element and the cover element defining the cavity.

14. An anchor assembly according to claim 13, wherein the base element defines an aperture through which the article can be inserted into the cavity, the cavity being wider than the aperture, whereby when the securing member is received in the cavity, movement of the securing member to the securing position moves the securing member to a position in which it extends across the aperture to engage the base element, thereby retaining the securing member in the cavity.

15. An anchor assembly according to any one of claims 9 to 14, wherein when the securing member is in the non-securing position, the securing member is substantially aligned with the main part, and when the securing member is in the securing position, the securing member extends transverse to the main part, whereby when the securing member is in the non-securing position, the securing mechanism can be inserted into the cavity.

16. An article for use in an anchor assembly as defined in claim 9, the article comprising a securing mechanism comprising a main part and a securing member movably mounted on the main part, the securing member being movable relative to the main part from a non-securing position, to allow the securing member to be inserted into a cavity defined by an article securing arrangement through an aperture in the article securing arrangement, to a securing position, to secure the securing member in the cavity and thereby secure the article to the securing arrangement, wherein the securing member projects beyond the main part when the securing member is in the non-securing position to engage the inner surface of the cavity and move to the securing position.

17. An article according to claim 16, wherein the securing member is pivotally mounted on the main part for pivotal movement from the non-securing position to the securing position.

18. An article according to claim 16 or 17, wherein when the securing member is in the non-securing position, the securing member is substantially aligned with the main part, and when the securing member is in the securing position, the securing member extends transverse to the main part.

19. An article according to claim 16, 17 or 18, wherein, when the securing member is received in the cavity, movement of the securing member to the securing position moves the securing member to a position in which it can extend across the aperture to engage the base element, thereby retaining the securing member in the cavity.

1/12




Fig. 1


2/
12

Fig. 2


3/
12

Fig. 3


4/
12

Fig. 4


5
12

Fig. 5


6
12

Fig. 6A




Fig. 6B





Fig. 7






Fig. 9


10
12

Fig. 10


11
12

Fig. 11


12
12

Fig. 12

