




(86) Date de dépôt PCT/PCT Filing Date: 2008/02/08
(87) Date publication PCT/PCT Publication Date: 2008/10/30
(85) Entrée phase nationale/National Entry: 2009/10/06
(86) N° demande PCT/PCT Application No.: US 2008/053471
(87) N° publication PCT/PCT Publication No.: 2008/130731
(30) Priorité/Priority: 2007/04/17 (US11/736,318)

(51) Cl.Int./Int.Cl. *B01D 63/04* (2006.01),
B01D 53/22 (2006.01)
(71) Demandeur/Applicant:
NEW YORK AIR BRAKE CORPORATION, US
(72) Inventeurs/Inventors:
WRIGHT, ERIC, US;
KOHAR, RICHARD, CA
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : DISPOSITIF DE DESSICCATION D'AIR A MEMBRANE AVEC REGULATION DE L'AIR DE BALAYAGE
(54) Title: MEMBRANE AIR DRYER WITH SWEEP AIR CONTROL



(57) **Abrégé/Abstract:**

The membrane (40) air dryer includes a housing (44) with an air inlet (46) adjacent a first end of the housing, an air outlet (48) adjacent a second end of the housing, a sweep air inlet (51) and a sweep air outlet (54). A first sweep air passage in the housing extends between the first and second ends of the membrane along the surfaces of the membrane. The first sweep air passage has an inlet adjacent the air outlet and an outlet adjacent the air inlet and connected to the sweep air outlet. The sweep air inlet and outlet is adjacent the air inlet. A second sweep air passage extends between the first and second ends of the membrane. The second sweep air passage has an inlet (140) that is connected to the sweep air inlet and is adjacent the air inlet and has an outlet (154) that is adjacent the air outlet and in fluid communication with the inlet of the first sweep air passage. The membrane air dryer is mounted to extend into the reservoir (26).





PCT

(10) International Publication Number
WO 2008/130731 A1

(57) Abstract: The membrane (40) air dryer includes a housing (44) with an air inlet (46) adjacent a first end of the housing, an air outlet (48) adjacent a second end of the housing, a sweep air inlet (51) and a sweep air outlet (54). A first sweep air passage in the housing extends between the first and second ends of the membrane along. The surfaces of the membrane. The first sweep air passage has an inlet adjacent the air outlet and an outlet adjacent the air inlet and connected to the sweep air outlet. The sweep air inlet and outlet is adjacent the air inlet. A second sweep air passage extends between the first and second ends of the membrane. The second sweep air passage has an inlet (140) that is connected to the sweep air inlet and is adjacent the air inlet and has an outlet (154) that is adjacent the air outlet and in fluid communication with the inlet of the first sweep air passage. The membrane air dryer is mounted to extend into the reservoir (26).

MEMBRANE AIR DRYER WITH SWEEP AIR CONTROL**BACKGROUND AND SUMMARY OF THE DISCLOSURE**

[0001] The present invention relates generally to air dryers, and more specifically, to a membrane air dryer with sweep air control for a brake system for vehicles.

[0002] Air dryers employing membranes consisting of a permeable membrane capable of blocking the passage of nitrogen and oxygen molecules, but allowing water vapor molecules to pass through, as described in U.S. Patents 6,719,825 and 5,525,143 amongst many others. In one variation of the technology, the air to be dried passes through the center of the membrane element. The membrane permits the passage of the water vapor to the outside of the membrane, but prevents the passage of the air to the outside of the membrane, thereby drying the air.

[0003] To work effectively, the outside of the membrane must be kept dry and at a lower pressure than the inside, creating the partial pressure differential to drive the water vapor out. This is done by providing some fraction of the dry output air as a counter flow sweep air across the outside of the membrane. The sweep air can be provided by sweep air orifice(s) connecting the dry air in the membrane air dryer outlet to the sweep air chamber surrounding the outside of the membrane. The orifices control the volume of sweep air, typically 10-20% of the dryer capacity and create a pressure drop in the sweep air volume. The sweep air and entrapped moisture are expelled to atmosphere.

[0004] U.S. Patent 6,719,825 shows a control valve at the inlet for the sweep air. U.S. Patent 5,375,620 shows a self-adjusting flow metering device for the sweep air. An air dryer including a coalescing and charcoal pre-filters and a membrane filter is also shown by U.S. Patent 6,719,825.

[0005] The present disclosure is directed to an air dryer, for example, for locomotives, packaged to fit inside a reservoir with a pre-filter exterior the reservoir. The air dryer is generally cylindrical with a circular mounting flange on one end, which bolts to a similar mounting flange welded to the end of the reservoir. This arrangement solves the problem of finding room for the air dryer between main reservoir #1 and #2 on a locomotive, protects the air dryer and especially the vulnerable membrane element from the very high ambient temperatures (as high as 300°F) during operation of the locomotive in tunnels; protects the air dryer from environmental hazards, like flying stone ballast; eliminates installation piping, and minimizes weight.

[0006] The membrane air dryer includes a housing with an air inlet adjacent a first end of the housing, an air outlet adjacent a second end of the housing, a sweep air inlet and a sweep air outlet. A membrane separator has surfaces extending between and connected to the air inlet and the air outlet. A first sweep air passage in the housing extends between the first and second ends of the membrane along and including surfaces of the membrane. The first sweep air passage has an inlet adjacent the air outlet and an outlet adjacent the air inlet and connected to the sweep air outlet. The sweep air inlet and outlet is adjacent the air inlet. A second sweep air passage in the housing extends between the first and second ends of the membrane. The second sweep air passage has an inlet that is connected to the sweep air inlet and is adjacent the air inlet and has an outlet that is adjacent the air outlet and in fluid communication with the inlet of the first sweep air passage.

[0007] The first and second sweep air passages are concentric to each other and the membrane. The sweep air from the outlet of the second sweep air passage passes through the membrane to the inlet of the first sweep air passage. A valve is connected between the air inlet and the sweep air inlet and the sweep air outlet is connected to atmosphere.

[0008] The membrane air dryer includes a first tube having a first end including an inlet in fluid communication with the outlet of the first sweep passage and an outlet in fluid communication with the sweep air outlet. The first tube has a second end adjacent the air outlet and includes the outlet of the second sweep air passage. The dryer includes a second tube having a first end in fluid communication with the sweep air inlet and having a second end connected to an interior of the first tube between and fluically isolating the inlet of the first tube and the outlet of the second sweep air passage.

[0009] A reservoir having an inlet includes the subject membrane air dryer extending from a reservoir inlet into the interior of the reservoir so that the housing air inlet is the inlet of the reservoir, the housing air outlet and the sweep air inlet are interior the reservoir and the sweep air outlet of the housing is exterior the reservoir. A vehicle brake system including a brake controller and the reservoir with the membrane air dryer therein includes a valve connected between the air inlet and the sweep air inlet, and the brake controller controls the valve.

[00010] A combination of a reservoir having an air port and a membrane separator having a housing with a separator member between an air inlet and an air outlet and a sweep air inlet and outlet. The housing extends from the reservoir air port into the interior of the reservoir so that the housing's air inlet and sweep air outlet are exterior the reservoir and the housing's air outlet and the sweep air inlet are interior the reservoir. A valve is connected between the air

inlet and the sweep air inlet and the sweep air outlet is connected to atmosphere. A vehicle brake system includes a brake controller and the combined reservoir and membrane separator and the brake controller controls the valve.

[00011] These and other aspects of the present method will become apparent from the following detailed description of the method, when considered in conjunction with accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

[00012] Figure 1 is a schematic of a locomotive air supply and brake controller according to the present disclosure.

[00013] Figure 2 is an embodiment of a membrane air dryer according to the present disclosure.

[00014] Figure 3 is an embodiment of a membrane air dryer with a removable membrane air dryer module according to the present disclosure.

[00015] Figure 4 is an embodiment of an air dryer with a removable membrane air dryer module with integral coalescing filter and particulate filter and two liquid drains according to the present disclosure.

[00016] Figure 5 is an embodiment of an air dryer with a removable membrane air dryer module, with integral coalescing filter and particulate filter and three liquid drains according to the present disclosure.

[00017] Figure 6 is an embodiment of a membrane air dryer with integral particulate and coalescing filters arranged for inside-out flow of air through the coalescer.

[00018] Figure 7 is an embodiment of a membrane air dryer with integral particulate, coalescing and charcoal prefilters arranged for inside-out flow of air through the coalescer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[00019] A locomotive brake supply and brake controller is shown in Figure 1. A compressor 10 driven by the engines of the locomotive provides a source of compressed air through line 12 to inlet 14 of the first main reservoir MR 16. The outlet 18 of the reservoir 16 is connected to other non-brake air consuming devices at line 20. The outlet 18 is also connected to the inlet 24 of the second main reservoir 26 via one-way check valve 22. The outlet 28 of the second main reservoir MR 26 is connected to a brake controller illustrated as a CCB computer controlled brake system 32. The outlet 34 of the computer controlled brake

system 32 provides an appropriate pneumatic control signals for the locomotive and train brakes.

[00020] As will be discussed below, the computer controlled brake system 32 provides, via line 36, control of the drain 54 of membrane air filter 40 within the main reservoir 26. This not only controls the drain, but the air flow in the sweep air passages. Alternatively, the control may be provided on the input of the air sweep passage as also described below. Control of the drain valve 19 of the first main reservoir MR 16 may be either from the computer brake control system 32 or other control systems on the locomotive.

[00021] The main reservoir 16 includes a coalescing pre-filter 60 therein. Coalescing pre-filter 60, although shown schematically in the outlet 18 of MR 16, can alternately be provided in the inlet 14 of MR 16.

[00022] A membrane air dryer 40 is shown in Figure 2 as including a housing 44 with an air inlet 46, an air outlet 48 and a liquid drain outlet 54. A membrane separator 42 is shown schematically with an inner surface and an outer surface extending between a first and second ends of the membrane 42. Typical construction of a membrane module is a bundle of small diameter hollow fibers (membrane), each with an inner surface and an outer surface extending between a first and second ends of the membrane. A first passage 50, made up of the inner diameters of each of the hollow fiber membranes in the housing 44 is connected to the air inlet 46 and air outlet 48 at its respective ends and extends between the first and second ends of the membrane 42 along one of the interior and the exterior of the membrane. A second passage 52 including the outer diameters of each of the hollow fiber membranes in the housing 44 is connected to the sweep air/drain outlet 54 and a sweep air inlet adjacent the housing's air outlet 48 at its respective ends. The second passage 52 extends between the first and second ends of the membrane 42 along the other of the interior and the exterior of the membrane. A valve 56,58 is connected between the second passage 52 and the drain outlet 54 for controlling the draining of the liquid and sweep air flow through the second passage 52.

[00023] The valve may be an electro-pneumatic valve or a solenoid controlled diaphragm-type (or conventional-type) drain valve 56,58. A cover plate 47 is removable mounted to the housing 44 adjacent the membrane 42 to allow removal of the membrane 42 from the housing 44. The air inlet 46 and the drain outlet 54 are offset from the axis of the membrane 42 and the cover plate 47. This allows servicing the membrane element 42 by removal of a cover or cover plate 47, without disturbing piping or removal of the complete unit from the reservoir 26.

[00024] The housing 44 may be mounted in the inlet 24 of a reservoir by a collar 45 which may be welded to the main reservoir 26 or bolted to a flange on the inlet 24. The housing extends from the reservoir inlet 24 into the interior of the main reservoir 26 so that the housing inlet 46 is the inlet 24 of the main reservoir 26. The housing outlet 48 is interior the reservoir 26 and the drain outlet 54 of the housing 44 is exterior the main reservoir 26.

[00025] Most membrane dryers for industrial use have a constant sweep flow. This is undesirable on a locomotive as it wastes air and may deplete the air in the reservoir if the locomotive is idled with power shut off. Further, unlike many industrial uses, the air is consumed from the reservoirs 16 and 26 only intermittently by the pneumatic brake system. Main Reservoir 26, is generally protected by the check valve 22 and is used exclusively by the brakes. The membrane air dryer 40 for a locomotive solves this problem of wasted air due to a constant sweep flow by adding a solenoid controlled diaphragm-type (or conventional-type) drain valve 56,58 to the output of the sweep air chamber 52 shown in Figure 2. Although the sweep air or drain valve 56,58 is shown schematically at the exhaust of the sweep air chamber, it could also be arranged to control the flow of sweep air into the inlet of the sweep air chamber while still venting the sweep air to the outside of the MR 26 as shown in Figure 2.

[00026] When closed, the valve 56 closes the communication of the sweep volume through passage 52 to atmosphere, thereby preventing the venting of the sweep air. The drain valve 56 is controlled by a solenoid valve 58 which is controlled by the CCB computer controlled brake system 32 on the locomotive. The CCB 32, because it is a computer controlled brake system with transducers and other controls necessary for brake operation, can determine when the brakes are consuming air from the MR 26. In operation, the CCB 32 will open the dryer drain valve 56 whenever the brake system is consuming air from MR 26, which allows the resumption of flow of sweep air around the outside of the membrane element 42 in passage 52 at the same time that moisture laden air is flowing into the inlet 46 of the air dryer 40 to replenish the air used by the brakes. Thus, the air dryer 40 only consumes sweep air when sweep air is needed to dry air flowing through the air dryer.

[00027] Further, the CCB 32 can maintain sweep flow for a period of time after the brake system is no longer consuming air from MR 26 before closing the drain valve 56 to assure that the MR 26 is fully replenished with dry air, further it can maintain sweep flow for an additional predetermined time to assure that the sweep air volume is free of moisture. The lag time, during which the sweep flow is maintained after air consumption by the brakes, can be calculated based on the air flow measured by the CCB 32 and the duration of the flow,

knowledge of compressor **10** on-off pressure switch points, and knowledge of the compressor output capacity. The lag time can alternatively or concurrently be determined by monitoring the pressure increase in MR **26** as it is replenished by the air supply system. When the rate of pressure increases in MR **26** decreases to some pre-determined level and/or the pressure in MR **26** reaches the compressor control upper limit pressure, the sweep air is terminated. Optionally the lag time calculation could be optimized by CCB **32** reading a digital signal from the compressor control indicating whether the compressor is pumping or not.

[00028] Sweep flow would be enabled whenever 1) the brake system consumes air, 2) the compressor **10** is turned on and the pressure in MR **26** is less than the compressor pressure upper limit control, typically 145 psi, and 3) for some lag time after cessation of air consumption by the brakes, until the MR **26** is substantively recharged and the sweep air volume is substantively purged of moist air.

[00029] Figure 2 shows the housing **44** as defining the appropriate passage for the filter element **42** to be removed from the housing **44**. A variation is illustrated in Figure 3 and shows the membrane filter element **42** and its housing **44A** removable as a module from the housing **44**. The housing **44** is joined to flange **45** of the MR **26** and includes air inlet **46**. The membrane housing **44A** includes the membrane member **42** and has an air inlet **46A** and the outlet **48**. A collar **41** of the housing **44A** is received in the housing **44**. It is sealed thereto by sealing means **43**, shown as o-rings. The pair of o-rings **43** on each side of the drain passage **54A** which is aligned with passage **54B** with housing **44** and connects it to the drain the drain outlet **54**. Valve **56,58** are provided at the drain outlet **54**. For maintenance, the cover plate **47** is removed and the membrane filter **40** including housing **44A**, collar **41** and membrane **42** are removed. A new membrane air dryer or filter **40** may then be installed. The passages **50** and **52** are present, but are not shown.

[00030] The air dryer system for a locomotive may optionally include a coalescing pre-filter **60** to remove liquid water and oil vapor from the air stream prior to passing through the membrane **42**, as well as the back-flow check valve **22** typically installed between MR **16** and **26**. The coalescing pre-filter **60** can likewise be packaged in a cylindrical form with a circular mounting flange for mounting in the inlet **14** or discharge **18** end of MR **16**, which feeds MR **26**.

[00031] Alternatively, the coalescing pre-filter **60** may be installed in the inlet **14** of MR **16**, instead of (or in addition to) the outlet **18** of MR **16**. The backflow check valve **22** may be deleted or could be included as part of the membrane air dryer assembly. Coalescing filters generally work optimally when the air flow is directed from inside to outside the filter

element and the coalesced liquid is allowed to drain from the outside of the element. Positioning the coalescing pre-filter in the inlet 14 to the MR 16 has the advantage of inside to outside air flow while eliminating a need for circuitous air routing in the filter housing, and eliminating the need for a pressure tight filter housing. In this arrangement, the coalesced liquid can drip to the bottom of the MR 16 where it is discharged by pre-existing automatic drain valves 19.

[00032] As a further alternative, the coalescing pre-filter 60 may be installed exterior and between both reservoirs 16 and 26. A drain valve would be provided and controlled by the computer control brake system 32 or other locomotive computer. The coalescing pre-filter 60 may be an integral unit with the membrane filter 40 or mounted to the inlet of the membrane filter 40 exterior the reservoir 26.

[00033] Coalescing pre-filter 60 may also be provided in the MR 26 in combination with the membrane air dryer 40 as illustrated in Figures 4-7. The housing 44 is enlarged to include a chamber 49 for receiving a coalescing element 62 by itself or in combination with a particulate filter 80. They are mounted between the housing 44 and the cover plate 47. Appropriate recesses or ledges are provided on the housing 44 and the cover plate 47 to align and secure the filters 62 and 80 in the housing 44. As shown in Figure 4, housing 44 is modified to provide a sump 45 to which a drain valves 82,84 are connected. These valves are identical to the valves 56,58 and may also be controlled by the CCB 32 such that they are opened at the appropriate time in the operation of the locomotive and/or flow of the air from the air supply.

[00034] In Figures 4, 5 and 7, the filter 62 and 80 are concentric with each other and coaxial to the membrane air dryer 40. The air through inlet 46 passes through the filter 62 and 80 prior to being received in the air inlet 46A of the membrane dryer 40. As well-known, the coalescing filter element 62 precipitates air-born water and oil vapor from the air stream. The particulate filter 80 filters out very fine air-born dust and solid material such as carbon particles from diesel combustion or other contaminants or other particulates which contaminate the membrane dryer module 40.

[00035] The present design differentiates from the prior art in that the coalescing filter 62, the particulate filter 80 and the air dryer 40 of the prior art are all connected in series external to the reservoir 26. The present design is an improvement over the prior art in that merely removing the cover plate 47 allows replacement and maintenance of the filters 62 and 80 and the dryer 40. No major disassembly is required. While the coalescing filter element 62 and

the particulate filter 80 require annual maintenance, the membrane dryer 40 would be replaced every six to eight years depending on actual service conditions.

[00036] A variation of the combined module of Figure 4 is illustrated in Figure 5. Instead of a common drain valve in 82,84 for the coalescing filter element 62 and the particular filter 80, each filter has its own set of valves. The bottom of chamber 49 adjacent the coalescing filter includes a two-series valve 84A and 84C separated by sump 84B. A separate port as provided at the inner surface of the particular filter 80. A series set of valves 86A and 86C are separated by a sump 86B. The valves 84A and 84C and 86A and 86C are controlled by the CCB 32 as described for the valves 58 and 84 of Figure 4. The valves 84A,86A are operated to remove the water, oil, etc., from the housing chamber 49 and empty into respective sumps 84B,86B. The valves 84C,86C, which empty the sumps 84B,86B, may be operated at a different time than valve 84A,86A.

[00037] As a further modification, perforated tube 88 is provided between the cover plate 47 and the inlet 46A of the membrane dryer 40. This secures the membrane dryer within the housing 44.

[00038] Figure 6 shows yet further modification whereby the particulate filter 80 and coalescing filter elements 62 are arranged axially, which provides for simplified inside-outside air flow through the coalescer. The chamber 49 of the housing 44 is divided into three chambers 49A,49B and 49C by walls 100 and 102. The air as shown by arrow 104 flows from inlet 46 and passes through particulate filter 80 and a portion of perforated tube 88 in chamber 49A to chamber 49B. The air then flows through portion of the perforated tube 88 and the coalescing filter element 62 in chamber 49B. Next, the air flows into chamber 49C and through perforated pipe 106 in chamber 49C to the inlet 46A of the membrane dryer 40.

[00039] Although the Figure 6 shows separate drain valves for the particulate filter chamber 49A and coalescing chamber 49B, a single drain valve could be used to drain both chambers as described for Figure 4.

[00040] The interior of the reservoir 26 may include a support bracket 90 welded or otherwise suitably attached thereto. A seat 92 receives end cap 41A of the membrane dryer 40. O-rings may be provided on end cap 41A to secure the end cap 41A in the seat 92 and to minimize harmful vibration between the two. A cam surface 94 is provided to guide and align the end cap 41A into the seat 92. The bracket 90 may be provided in all the shown embodiments.

AMENDED SHEET

- [00041]** Although not shown in Figures 1-6, the area of the air inlet **46** into the chamber **49** is shaped or includes a baffle to distribute the air around the filters **62** and **80**. A portion of this structure is shown in Figure 7.
- [00042]** Figure 7 illustrates a variation of the pre-filter housing which combines the concepts of the pre-filter illustrated in Figures 5 and 6. It provides concentric filters with an in/out flow through the coalescer filter **62**.
- [00043]** The air dryer housing **44** includes housing portion **44A** which houses the membrane element **42** and a housing portion **44B** mounted in the opening in the inlet **24** of the reservoir **26**, pre-filter housing portion **44C** and a connecting housing portion **44D**. As previously discussed, the membrane filter housing portion **44A** is removable from the housing portion **44B** which is mounted to the reservoir **26** either welded as shown in Figure 7 or welded and connected to a flange welded on the exterior of the outlet **24** of the reservoir **26**. Fasteners **111**, shown as bolts, secure the housing section **44C** to the housing portion **44B**. The housing portion **44D** is mounted on the cover plate **47** and the cover plate **47** is secured to housing portion **44C** by fasteners **113**, also illustrated as bolts.
- [00044]** Cylindrical wall **110** divides housing portion **44C** into an inner chamber **114** and a concentric outer chamber **112**. The coalescer **62** and the filter **80** are concentrically mounted in the outer chamber **112**. A third filter **118** which may be, for example, a charcoal filter, is mounted in the inner chamber **114**. A cap **115** secures the filter **118** to the cover plate **47** by a nut **119** threaded onto thread shaft **117**. Housing portion **44D** forms a chamber **116** between itself and the cover plate **47**.
- [00045]** The air inlet **46** for the reservoir and the air dryer is connected through aperture **120** in the wall of housing portion **44C**. It is introduced into the wall of annular chamber **122**. The oblong aperture **120** provides somewhat of a tangential entry so as to create a swirling or circumferential airflow. The input air in annular chamber **122** is provided through a plurality of inlets **124** in the housing portion **44C** interior the filter **80** and coalescer **62**. The outlet for chamber **112** is through a plurality of outlets **126** exterior the coalescer **62** into chamber **116**. This produces the inward/outward flow through the coalescer **62**. The filtered air in chamber **116** is introduced into the interior of filter **118** by a plurality of inlets **128**. The triple filtered air in chamber **114** is then provided through a plurality of outlets **130** in collar or manifold **41** to chamber **131** the inlet of **46A** the membrane filter **40**.
- [00046]** The structure of the housing as shown allows for disassembly and removal of the four filter elements without modification of the reservoir **26**. The removal of fasteners **113** allows the removal of the cover plate **47** with housing portion **44D**. This allows access and removal

of the coalescer 62, the filter 80 and access to the filter 118. Removal of nut 119 allows replacement of the filter 118. The removal of fasteners 111 allows removal of housing portion 44C which allows access to the collar 41 and the membrane filter housing 44A and the membrane filter 42 itself.

[00047] As in the previous Figures 5 and 6, valves 84A and 84C and sump 84B control the draining of the liquid from sump portion 45 of chamber 112 exterior the coalescer 62.

[00048] Another variation of the embodiment of Figure 7 is that the sweep air is controlled at the sweep air inlet 51 instead of the sweep air outlet and drain 54. The drain 54 is open and exposed to atmosphere. The control valve 58 is at the inlet 51. The housing portion 44B in combination with the collar 41 constructed as a manifold provides the appropriate interconnections.

[00049] The inlet 51 for the sweep air passage from the interior of the reservoir 26 is not adjacent to the outlet 48 of the membrane filter 40, but is into passage 132 adjacent the inlet 44 of the membrane filter 40. Passage 132 is connected to the input of valve 58. The outlet of valve 58 is connected to passage 134 in housing portion 44B into circumferential chamber 136 in the collar manifold 41. A plurality of radial passages 138 connects the circumferential passage 136 to a centered inlet 140 in the collar 41. A tube 142 connects the inlet 140 to the interior of tube 150. The end 144 of tube 142 is flared and sealed to the interior of tube 150. This divides tube 150 into an inlet portion 150A and an outlet portion 150B, which terminates at end 152. The inlet portion 150A exits out of a plurality of orifices 154 radially into the membrane filter 40 and flows through the first sweep air chamber or passage 52 (not shown). Tube 142 and tube portion 150A form a second sweep air passage having an inlet 140 adjacent the air inlet 46, 120 and an outlet 154 adjacent the air outlet 48.

[00050] The circulation of air in chamber 52 is opposite or counter to the air at inlets 130 to the membrane filter. The outlet of the sweep air passage 52 enters tube section 150B through a plurality of openings 156. The outlet of tube section 150B is connected at 158 to a plurality of radial passages 160 which are connected to an annular passage 162 which is connected directly to the drain 54.

[00051] The sweep passage air at inlet 51 is controlled by valve 58 to circulate through tube 142 and tube section 150A substantially the length of the membrane filter 40 to inlet openings 154 into the membrane filter. The counterflow from inlets 154 to outlets 156 through the sweep air passage 52 then exits through tube section 150B to drain 54. While the exterior sweep air inlet 51 and air outlet 54 are adjacent the air inlet for the membrane filter,

the interior openings **154** and **156** provide the appropriate counterflow required for the membrane filter.

[00052] Although the pre-filter of Figure 7 is shown with a unique sweep air control at the inlet, this pre-filtered structure may be used with the membrane control at the outlet of Figures 5 and 6.

[00053] It should be noted by controlling the sweep air at the inlet of the membrane filter, it eliminates pressure cycling of the membrane bundle which can result in fatigue failure of the membrane fibers. This would limit their useful life. Thus, the outlet and the membrane are continuously exposed to atmospheric pressure which is 14.7 psi. When the sweep air is flowing, the sweep air pressure around the membrane is less than 2 psi. This small change of pressure minimizes the pressure fluctuation or cycling of the membranes. Also by controlling the sweep air at the inlet versus the outlet, dry air from the interior of the reservoir **26** is flowing through the control valve **58**. This not only extends the life of the control valve **58** but also does not require a heater at the control valve **58** to prevent freezing.

[00054] Although the present method has been described and illustrated in detail, it is to be clearly understood that this is done by way of illustration and example only and is not to be taken by way of limitation. Although the dryer has been shown in a train air supply system, it can also be used in a truck brake system. The particular filter structure may be used even if it is not mounted interior the reservoir. The scope of the present method is to be limited only by the terms of the appended claims.

SUBSTITUTE SHEET**1. A membrane air dryer comprising:**

a housing with an air inlet adjacent a first end of the housing, an air outlet adjacent a second end of the housing, a sweep air inlet and a sweep air outlet, the air inlet and the air outlet being axially disposed at first and second ends of the housing;

a manifold defining at least a portion of the first end of the housing, the manifold defining radial passageways for the sweep air inlet and the sweep air outlet, the sweep air inlet and the sweep air outlet being axially disposed adjacent to one another and also being axially disposed adjacent to the air inlet;

a membrane separator, with first and second ends, extending axially between and connected to the air inlet and the air outlet;

a first sweep air passage in the housing extending axially between the first and second ends of the membrane separator, the first sweep air passage comprising a first sweep air passage inlet adjacent the air outlet and a first sweep air passage outlet connected to the sweep air outlet;

a second sweep air passage in the housing extending axially between the first and second ends of the membrane separator, the second sweep air passage comprising a second sweep air passage inlet connected to the sweep air inlet a second sweep air passage outlet adjacent the air outlet and connected to the first sweep air passage inlet; and

a membrane module disposed in the first sweep air passage, the membrane module comprising a plurality of hollow fiber membranes defining interior passages to conduct air from the air inlet to the air outlet and defining exterior passages to conduct sweep air from the first sweep air passage inlet to the first sweep air passage outlet.

2. The membrane air dryer according to claim 1, wherein the first and second sweep air passages are concentric.

3. The membrane air dryer according to claim 1, further comprising:

a first tube with a first end and a second end, the first tube extending axially between the first and second sweep air passages.

SUBSTITUTE SHEET

4. The membrane air dryer according to claim 1, wherein the sweep air from the second sweep air passage outlet passes through the tube to the first sweep air passage inlet.

5. The membrane air dryer according to claim 1, further comprising:
a second tube having a first end in fluid communication with the sweep air inlet and having a second end connected to an interior of the first tube to fluidally isolate the first end of the first tube from the second end of the first tube.

6. The membrane air dryer according to claim 1, further comprising:
a valve controlling flow of the sweep air through the sweep air inlet.

7. A reservoir having a reservoir inlet and the membrane air dryer of claim 1 extending from a the reservoir inlet into the an interior of the reservoir, wherein the air outlet and the sweep air inlet fluidally communicate with the interior the reservoir and the sweep air outlet of the housing is exterior the reservoir.

8. A vehicle brake system including a brake controller and the reservoir of claim 7; including a valve controlling flow of sweep air through the sweep air inlet; and wherein the brake controller controls the valve.

9. The system according to claim 8, wherein the brake controller opens the valve when the brake system uses air from the reservoir and closes the valve after the brake system terminates using air from the reservoir.

10. The system according to claim 9, wherein the brake controller delays closing the valve after the brake system terminates using air from the reservoir until the reservoir is recharged.

SUBSTITUTE SHEET

11. The system according to claim 8, wherein the sweep air outlet is connected to atmosphere.

12. A combination of a reservoir having a reservoir air port and a membrane separator having a housing with a membrane separator between an air inlet and an air outlet and a sweep air inlet and a sweep air outlet, wherein the housing extends from the reservoir air port into the interior of the reservoir so that the air inlet and sweep air outlet are exterior to the reservoir and the air outlet and the sweep air inlet are interior to the reservoir.


13. The combination according to claim 12, including a valve controlling flow of sweep air through the sweep air inlet and wherein the sweep air outlet is connected to atmosphere.


14. A vehicle brake system including a brake controller and the combined reservoir and membrane separator of claim 13; wherein the brake controller controls the valve.



15. The membrane air dryer according to claim 5, further comprising:
openings through the first tube at the first end to permit the sweep air to exit from the first sweep air passage.


16. The membrane air dryer of claim 15, further comprising:
a sweep air outlet defined by the manifold to exhaust the sweep air from the first sweep air passage.


17. The membrane air dryer of claim 6, wherein the sweep air outlet vents to atmosphere.





*FIG. 3**FIG. 4*








FIG 7

