



(22) Date de dépôt/Filing Date: 2000/12/15

(41) Mise à la disp. pub./Open to Public Insp.: 2002/06/15

(45) Date de délivrance/Issue Date: 2005/05/10

(51) Cl.Int.⁷/Int.Cl.⁷ H04L 12/12, G06F 9/445


(72) Inventeur/Inventor:
LAU, JAMES S., CA

(73) Propriétaire/Owner:
IBM CANADA LIMITED-IBM CANADA LIMITEE, CA

(74) Agent: ROSEN, ARNOLD

(54) Titre : METHODES, SYSTEMES, SIGNAUX ET SUPPORTS ENCOURAGEANT LES UTILISATEURS DE CONTENU LISIBLE PAR ORDINATEUR A S'INSCRIRE

(54) Title: METHODS, SYSTEMS, SIGNALS AND MEDIA FOR ENCOURAGING USERS OF COMPUTER READABLE CONTENT TO REGISTER



(57) Abrégé/Abstract:

A method and system for encouraging users of computer readable content to register. The method involves embedding in the computer readable content, instruction codes operable to direct a processor circuit to automatically establish a connection to a



(57) **Abrégé(suite)/Abstract(continued):**

server, when the content is in use by the processor circuit, to transmit registration information to the server and operable to control further use of the content by the processor circuit in response to a key received from the server.

**METHODS, SYSTEMS, SIGNALS AND MEDIA FOR ENCOURAGING USERS OF
COMPUTER READABLE CONTENT TO REGISTER**

5

ABSTRACT

10

A method and system for encouraging users of computer readable content to register. The method involves embedding in the computer readable content, instruction codes operable to direct a processor circuit to automatically establish a connection to a server, when the content is in use by the processor circuit, to transmit registration information to the server and operable to control further use of the content by the processor circuit in response to a key received from the server.

METHODS, SYSTEMS, SIGNALS AND MEDIA FOR ENCOURAGING USERS OF COMPUTER READABLE CONTENT TO REGISTER

5 BACKGROUND OF THE INVENTION

1. Field of Invention

This invention relates to user registration of software and more particularly to methods, systems, signals and media for encouraging users of computer readable content to register with a server.

2. Description of Related Art

10 With the proliferation of computer readable content for sale such as software applications, music, data or movie files, for example, available for purchase on computer readable media such as a CD- ROM®, or a DVD® or floppy disc, or available for download via an Internet connection
15 with a web server, unauthorized access and copying of computer readable content has become more and more widespread. Currently a computer user attempting to gain access to locked content such as on a CD- ROM®, must make live contact with the content owner or licensor and must purchase or license a key to access the content. This is inefficient and does not restrict the user from making use of the application on other computers or from providing the key to others
20 to the detriment of the content owner. What is needed therefore is a more robust way to ensure that a person accessing the computer readable content is authorized to do so. In particular, it would be advantageous to have a way to restrict access to the content so that it can only be accessed from a single user's computer. This would effectively prevent unauthorized access to the content even if large numbers of copies of the work are distributed without control.

25 SUMMARY OF THE INVENTION

The present invention addresses the above problem by providing a method for encouraging users of computer readable content to register. The method includes embedding in the computer readable content, instruction codes operable to direct a processor circuit to automatically
30 establish a connection to a server, when the content is in use by the processor circuit. The

instruction codes are operable to direct a processor circuit to transmit registration information to the server and operable to control further use of the content by the processor circuit in response to a key received from the server.

5 The method may also include storing the computer readable content and the embedded instruction codes on a stationary or portable memory medium, and providing the computer readable content and the embedded instruction codes for use by a user computer.

10 The method may also include embedding a self-executing apple in the computer readable content, and producing the apple such that the apple contains the instruction codes.

15 In accordance with another aspect of the invention there is provided a method for encouraging users of computer readable content to register. The method includes providing to a user computer the computer readable content and instruction codes embedded in the computer readable content. The instruction codes are operable to direct a processor circuit of the user computer to automatically establish a connection to a server, when the content is in use by the user computer, to transmit registration information to the server and operable to control further use of the content by the user computer in response to a key received from the server.

20 The method may include transmitting the computer readable content and the embedded instruction codes to the user computer, on a communications network, and/or providing a computer readable medium to a user. The computer readable medium may have stored thereon the content and the embedded instruction codes.

25 In accordance with another aspect of the invention there is provided a method for encouraging users of computer readable content to register. The method includes executing instruction codes embedded in the computer readable content, when the content is in use by a processor circuit, to automatically establish a connection to a server to transmit registration information to the server and to control subsequent use of the content by the processor circuit in response to a key received
30 from the server.

The method may include causing the instruction codes to be executed when access is made to the content by the processor circuit and producing a measure of use of the content by the processor circuit, which may further include determining a number of times the content is accessed by the processor circuit, and/or determining memory usage of functional descriptive content in the computer readable content, and/or determining document usage by functional descriptive content in the computer readable content. The method may also include establishing the connection to the server when the measure of use exceeds a threshold value, by establishing an Internet protocol connection with the server.

The method may also include launching a browse session with a uniform resource locator pointing to a user registration page for permitting a user to enter registration information. The method may also include controlling subsequent use of the content by enabling subsequent use of the content when the key is received from the server, and disabling further use of the content when no key is received from the server.

The method may also include deleting files produced by functional descriptive content in the computer readable content, warning a user of the processor circuit that files are about to be deleted, maintaining a count of the number of times a warning about deleting files is presented to a user of the processor circuit, and deleting files produced by functional descriptive content in the computer readable content when the count exceeds a threshold value.

In accordance with another aspect of the invention there is provided a method of controlling use of computer readable content. The method includes transmitting to a user computer a key operable to co-operate with the user computer to deactivate execution of instruction codes embedded in the computer readable content at the user computer, in response to receipt of registration information from the user computer.

The method may also include hosting a uniform resource locator pointing to a user registration page for permitting a user to provide the registration information to register as a user of the computer readable content. The method may also include validating the registration information,

and transmitting the key to the user computer when the registration information is successfully validated.

5 In accordance with another aspect of the invention, there is provided a computer readable medium on which is stored computer readable content and instruction codes embedded in the computer readable content, the instruction codes being operable to direct a processor circuit to automatically establish a connection to a server, when the content is in use by the processor circuit, to transmit registration information to the server and operable to control further use of the content by the processor circuit in response to a key received from the server.

10 In accordance with another aspect of the invention, there is provided a data signal comprising a first code segment providing computer readable content and a second code segment embedded in the first code segment such that the second code segment is rendered operational when the first segment is used. The second code segment comprises instructions for directing a processor circuit to automatically establish a connection to a server, when the content is in use by the processor circuit, to transmit registration information to the server and operable to control further use of the content by the processor circuit in response to a key received from the server.

15 In accordance with another aspect of the invention, there is provided a system operable to encourage users of computer readable content to register. The system includes a processor circuit, a communications interface in communication with the processor circuit for communicating with a server, and a receiver for receiving computer readable content with instruction codes embedded therein. The instruction codes are operable to cause the processor circuit to automatically cause the communications interface to establish a connection to a server to transmit registration information to the server, and to control subsequent use of the computer readable content by the processor circuit, in response to a key received from the server.

20 In accordance with another aspect of the invention, there is provided a system for controlling the use of computer readable content. The system includes a receiver for receiving registration information from a user computer, and a transmitter for transmitting to a user computer a key operable to cooperate with the user computer to deactivate execution of instruction codes

embedded in computer readable content at the user computer, in response to receipt of registration information at the receiver.

Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

In drawings which illustrate embodiments of the invention,

- 10 Figure 1 is a pictorial representation of a system for encouraging users of computer readable content to register, according to a first embodiment of the invention;
- Figure 2 is a tabular representation of portions of an apple to be used in the system shown in Figure 1;
- Figure 3 is a flowchart of an invocation portion of the apple shown in Figure 2;
- 15 Figure 4 is a flowchart of a connection establishment portion of the apple shown in Figure 2;
- Figure 5 is a flowchart of a key response portion of the apple shown in Figure 2.

DETAILED DESCRIPTION

- 20 Referring to Figure 1, a system for encouraging users of computer readable content to register, according to a first embodiment of the invention is shown generally at 10. In this embodiment the system includes a computer readable content provider 12, a user computer 14 and a server 16. The computer readable content provider 12 provides functional descriptive computer readable content and/or functional non-descriptive content for use by user computers such as user
- 25 computer 14. The server 16 provides a registration service for legitimate users of the computer readable content provided by the content provider 12.

- In general, functional descriptive computer readable content may include a program such as Netscape Communicator®, Lotus 1-2-3®, or Microsoft Word®, for example and generally describes any computer readable instructions which cause a processor circuit to carry out some
- 30 designated functionality. Non-functional descriptive computer readable content may include

music, video, or graphic content, for example and generally describes any computer readable content defining information.

The user computer described herein may be a conventional personal computer such as shown as 15, a personal data assistant 18, a Moving Pictures Expert Group Layer-3 (MP3) player 20, or any other program execution or content using device having a processor circuit for executing computer readable instructions or for manipulation of information content. The user computer in this embodiment is also operable to establish communications using an Internet Protocol and includes a browser for supporting communications of this type.

In accordance with one aspect of the invention described herein, the content provider 12 presents a method for encouraging users of computer readable content to register, involving embedding in the computer readable content, instruction codes operable to direct a user computer 14 to automatically establish a connection to the server 16, when the content is in use by the user computer 14, to transmit registration information to the server 16 and operable to control further use of the content by the user computer 14 in response to a key received from the server 16, such that the instruction codes are automatically executed by the user computer 14 when the computer readable content is used by the user computer 14.

Effectively, the content provider 12 writes records, or otherwise acquires computer readable content it intends to provide to users. The computer readable content 24 might be of the type which is distributed to users by sale, in stores, on portable computer readable media such as a floppy disk, CD-ROM 22, or DVD® for example, or by distribution of the content using an IP protocol network such as the Internet. However, prior to finalizing the content for distribution, or during development of the content, for example, instruction codes 26 are embedded therein. This may be accomplished by incorporating the instruction codes 26 into an applet, such as a self executing Java® applet embedded in the program such that the applet is automatically executed when the content is executed, if it is functional descriptive content or such that the applet is automatically executed when the content is accessed, if it is non-functional descriptive content. The content and embedded applet can then be burned onto a CD-ROM 22 or recorded on a floppy

disk, for example, or may be made available for distribution on a communications network such as an IP protocol network operating as an intranet, or internet, for example. In general, any of the aforementioned modes of distribution may be used to provide to a user computer the computer readable content 24 and instruction codes 26 embedded in the computer readable content 24.

Once the content 24 with embedded instruction codes 26 is received at the user computer 14, the content may be rendered operational by executing a setup or run program, for example, where the user computer is a personal computer 15, for configuring the operating system of the personal computer to respond to the content. The use of setup or run programs for rendering programs operational in personal computers is well known and therefore not described further here.

If, for example, the content 24 is provided to the user on a CD-ROM 22, the user inserts the CD-ROM 22 into a receiver, such as a media reader 27 the user computer 14 and performs the usual operations to invoke the program. This may include, for example operating a user input device at the user computer to execute a run command offered by the operating system of the user computer 14. In this embodiment, the operating system may generally be any operating system which has a Java® Virtual Machine that supports Java® applets, where the instruction codes according to this embodiment are provided as a Java® apple. Alternatively, specific versions of the instruction codes may be provided in languages such as C or C++, where the operating system does not support Java®. The operating system may be Windows 98® for example, in which case execution of the run command invokes the Microsoft program utility which will load the content and embedded apple into operational memory for execution and use by a processor circuit 28 of the user computer 14. The program utility also launches any functional descriptive content, e.g., any program, causing it to be executed by the processor circuit 28 and also launches the instruction codes 26 for simultaneous execution by the processor circuit. Effectively, by launching the instruction codes 26, the user computer 14 executes instruction codes embedded in the computer readable content 24, when the content is in use by the processor circuit 28, to automatically cause a communications interface 29 at the user computer 14 to establish a connection to the server 16 through a communications network 31

such as the Internet, to transmit registration information to the server and to control subsequent use of the content by the processor circuit in response to a key received from the server. This communications interface **29** may include an Internet browse to support such communications, for example.

5

In general, whenever the processor circuit **28** is directed by the user to access the content, either by running the functional descriptive content portion or by accessing a non-functional descriptive portion or both, the instruction codes **26** are run. Thus the processor circuit **28** is caused to execute the instruction codes **26** when access is made to the content **24** or the content is used.

10

Referring to Figure **2**, in this embodiment, the instruction codes **26** are provided in an apple having four main portions including a measurement portion **30**, an invocation portion **32**, a connection establishment portion **34** and a key response portion **36**. The measurement portion **30** includes instructions for directing the processor circuit **28** to produce a measure of use of the content by the processor circuit. In one embodiment, this may involve monitoring the number of bytes used in a designated folder maintained by the functional portion of the content. For example, if the functional portion maintains a document folder in which documents produced and edited by the user are stored, the measurement portion **30** may monitor the number of bytes attributed to this folder to produce a measure of the number of bytes that have been produced in response to user activity.

15

20

Alternatively, the measurement portion **30** may count the number of files created by the user in a designated folder. Or, a count of the number of accesses to non-functional content may be kept, particularly in the case where the non-functional content is music, video, or graphical information, for example.

25

Referring to Figure **3**, the invocation portion of the apple is shown generally at **32**, as a plurality of blocks of code, each of which serves a function as depicted by corresponding labels associated with each block. A first block of codes **42** directs the processor circuit **28** to communicate with the measurement portion **30** to determine a measure of the use of the content **24** by the user. A

30

second block 44 directs the processor circuit 28 to determine whether or not the amount of use exceeds a pre-defined threshold amount and if the usage of the program has not exceeded the pre-defined threshold, no action is taken. However, if the usage has exceeded the pre-defined threshold, the connection establishment portion 34 shown in Figure 2 is executed.

5

For example, if the user has produced more than 5 documents, or if the user has stored documents amounting to more than 100K bytes, or if access has been made to non-functional content more than 2 times, where 5, 100K and 2 are the threshold values, and at least one of these values has been exceeded, the connection establishment portion 34 is executed to establish a connection to the server 16. It should be appreciated that not all conditions above need be used to determine whether or not to proceed to the connection establishment portion 34. Rather any one of them or any combination of them may be used depending upon the nature of the content in the program.

10

15

Referring to Figure 4 the connection establishment portion of the apple is shown generally at 34. Effectively, the connection establishment portion 34, where appropriate, checks to see if an internet connection is active, establishes an internet protocol connection with the server, launches a browse session with the server uniform resource locator stored in the apple pointing to a user registration page permitting a user to enter registration information and cooperates with the key response portion 36 shown in Figure 2 to determine whether or not the user has been sufficiently warned of impending deletion of files for failure to register and deletes files where such sufficient warning has occurred.

20

25

Referring back to Figure 4, the determination of whether or not the user has been given sufficient warning that files will be deleted is made by a first block of instructions 50 which interact with a warning counter maintained by the key response portion 36 of the apple. Effectively, as will be seen below, the key response portion 36 maintains a count of the number of times a warning about file deletion is presented to the user.

The first block of instructions **50** directs the processor circuit **28** to read the value of the warning counter to determine whether or not the user has been warned a pre-defined number of times. If the user has been warned this pre-defined number of times, the processor circuit **28** is directed to block **52** which directs the processor circuit **28** to delete the content **24** and any data files created by the user, from the operational memory so that the processor circuit **28** is no longer able to use the content. Rather, the content would have to be reinstalled to enable it to be used again. Execution of the instruction codes **56** is then ended.

If at block **50** the processor circuit **28** determines that the pre-defined number of warnings have not been shown to the user, the processor circuit is directed to continue execution with the remainder of the connection establishment portion **34** of the apple.

The remainder of the connection establishment portion **34** of the apple includes block **54** which directs the processor circuit **28** to communicate with a task manger of the operating system to determine whether or not a communications session has already been established with at least one device, on a communications network. This may be done by using known methods for determining whether a browse session is active or pending, for example. At block **56**, if a communications session has not been established, the processor circuit **28** is directed back to block **54**. If a communications session has already been established however, block **58** directs the processor circuit **28** to create an IP connection to a uniform resource locator (URL) pointing to a user registration page hosted by the server **16**, and to launch a browse session at the user computer **14** to permit the user to provide registration information to register as a user of the computer readable content. The processor circuit **28** is then directed to the key response portion **36** of the apple.

Upon completion of the connection establishment portion **34** the user is presented with a registration form from the server **16**, prompting the user for information such as user identification, computer identification, program media identification, for identifying the CD-ROM **22** on which the content **24** was received, and/or product identification, for example. The server **16** thus acts as a web server.

If, for example, the owner of the content **24** were a provider of music and the content **24** itself were simply non-functional content such as an MP3 file, the server **16** or registration service at the server may be maintained by web server operated by the owner of the content or perhaps a copyright authority such as the American Society of Composers and Performers (ASCAP). Furthermore, where the program is provided over a computer network, the server which provides the content **24** to the user may also act as the web server to provide for registration.

When the user enters registration information onto the form presented by the server **16** and actuates a Aregister@ button on the registration page, the server receives the registration information at a "receiver" **41** of the server which in this embodiment is simply a web server interface. The server **16** then executes a program which validates the user registration information and, if appropriate, actuates a transmitter **43**, which includes a program for communicating information from the web server **16** to the user computer, and which transmits back to the user computer **14** a key operable to cooperate with the user computer **14** to control subsequent operation of the content **24** and in this embodiment that involves deactivating execution of the instruction codes **26** embedded in the computer readable content **24** at the user computer **14**.

Validating the user registration information may occur in a plurality of ways and the criteria for validation may vary widely. For example, simply determining that the user has entered what appear to be names and addresses in known formats may be sufficient to validate user registration information. Or, an identical match of a user id code with a pre-defined user id code may be required. Or user registration information may include credit card information, requiring the user to give a credit card number in order to use the program and validation may involve obtaining a charge authorization number from the corresponding credit issuer. In any event, the registration information is validated by or for the server **16** and the key is transmitted from the server **16** only when the registration information is successfully validated. The key may simply be a code recognizable by the instruction codes **26**.

Referring to Figure 5, the key response portion 36 is shown and begins with a block 60 which directs the processor circuit 28 to wait in the background while the browse session at the user computer 14 facilitating entry of user registration information is active. Effectively block 60 directs the processor circuit 28 to monitor transmissions from the server 16 to receive the key when it is sent by the server 16. Such transmissions may be in a hypertext transfer protocol (http) format, for example.

When a transmission containing the key is received at the user computer, block 60 directs the processor circuit 28 to block 62 which causes the processor circuit 28 to deactivate only the instruction codes 26, not the descriptive content 24, such that they can no longer be executed, and thus, execution of the instruction codes is completed and ended. Deactivation may be achieved by deleting the instruction codes 26 from the operational memory or by otherwise inhibiting their operation so that they cannot delete the content 24 from operational memory. Thus, subsequent use of the content 24 is enabled when a key is received at the user computer 14.

If at block 60, a key is not received within a designated time period, block 64 directs the processor circuit 28 to communicate with the task manager to determine whether or not the browse session has been closed. If it has not been closed, the processor circuit 28 is directed back to block 60 to continue to wait for the key.

When the user finally closes the browse session, block 66 directs the processor circuit 28 to open a message window to present a warning notice on a display of the user computer 14 to warn the user that files will be deleted if registration is not effected. For example the warning message may appear in a window with a red background and black text stating "PLEASE REGISTER NOW. FAILURE TO REGISTER WILL RESULT IN DELETION OF THIS PROGRAM AND OF THE FILES IT HAS CREATED A. Also in this message window, the user may be provided with a Aregister@ button causing the processor circuit 28 to be directed back to block 58 of the connection establishment portion 34 shown in Figure 4 to repeat the connection to the server and URL providing the registration page.

Referring back to Figure 5, if when presented with the warning message, should the user simply close the message window, block 68 directs the processor circuit 28 to increment the warning counter value, which maintains a count of the number of times the warning about deleting files is presented to the user, for reading by the processor circuit 28 at block 50 in the connection establishment portion 34 shown in Figure 4 to determine whether or not the program should be disabled and the associated files deleted at block 52. A warning may be broadcast to the user indicating how many more warnings he/she will receive before file deletion.

Thus, when no key is received from the server 16 and more particularly when no key is received and the user has been warned more than some number of times, the subsequent use of the content is controlled and in this embodiment such control is effected by disabling further use of the content 24, as provided at block 52 in Figure 4. Other means of control could alternatively be provided, such as disabling some features of the functional portion of the content 24, for example, or the content may be encrypted or scrambled by the instruction codes 26, for example.

It will be appreciated that by appropriate setting of the warning count threshold and the usage threshold, varying degrees of use and tolerance of non-registering users can be accommodated. For example, the usage threshold may be set to zero in which case a key would have to be obtained each time the user wanted to use the content. Or the usage threshold value may be set quite high to enable a user time to create important documents which are very valuable and which he/she cannot afford to lose.

From the foregoing it will be appreciated that using the invention described herein a user of computer readable content 24 is encouraged to register to become a registered user of the computer readable content as the consequences of not registering could result in deletion of important files and loss of use of the computer readable content.

While specific embodiments of the invention have been described and illustrated, such embodiments should be considered illustrative of the invention only and not as limiting the invention as construed in accordance with the accompanying claims.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A method for encouraging users of computer readable content to register said computer
5 readable content, the method comprising embedding in said computer readable content,
instruction codes operable to direct a processor circuit to produce a measure of use of said
content by said processor circuit and automatically establish a connection to a server, when said
content is in use by said processor circuit and said measure of use exceeds a threshold value, to
transmit registration information to said server and operable to enable further use of said content
10 by said processor circuit in response to a key received from said server.
2. The method of claim 1 further comprising storing said computer readable content and
said embedded instruction codes on a portable memory medium.
- 15 3. The method of claim 1 further comprising providing said computer readable content and
said embedded instruction codes for use by a user computer.
4. The method of claim 1 wherein embedding comprises embedding a self executing apple
20 in said computer readable content.
5. The method of claim 4 further comprising producing said apple such that said apple
contains said instruction codes.
6. A method for encouraging users of computer readable content to register said computer
25 readable content, the method comprising providing to a user computer said computer
readable content and instruction codes embedded in said computer readable content, said
instruction codes being operable to direct a processor circuit of said user computer to
produce a measure of use of said content by said processor and to automatically establish
a connection to a server, when said content is in use by said user computer and said
30 measure of use exceeds a threshold value, to transmit registration information to said

server and operable to enable further use of said content by said user computer in response to a key received from said server.

- 5 7. The method of claim 6 wherein providing comprises transmitting said computer readable content and said embedded instruction codes to said user computer.
8. The method of claim 7 wherein transmitting comprises transmitting said computer readable content and said embedded instruction codes on a communications network.
- 10 9. The method of claim 7 wherein transmitting comprises providing a computer readable medium to a user, said computer readable medium having stored thereon said content and said embedded instruction codes.
- 15 10. A method for encouraging users of computer readable content to register said computer readable content, the method comprising executing instruction codes embedded in said computer readable content to direct a processor circuit of said user computer to produce a measure of use of said content by said processor, when said content is in use by a processor circuit, and to automatically establish a connection to a server to transmit registration information to said server when said measure of use exceeds a threshold
- 20 value and to enable subsequent use of said content by said processor circuit in response to a key received from said server.
11. The method of claim 10 wherein executing comprises causing said instruction codes to be executed when access is made to said content by said processor circuit.
- 25 12. The method of claim 1 wherein producing said measure of use of said content comprises determining a number of times said content is accessed by said processor circuit.
13. The method of claim 1 wherein producing said measure of use comprises determining
- 30 memory usage of functional descriptive content in said computer readable content.

14. The method of claim 1 wherein producing said measure of use comprises determining document usage by function descriptive content in said computer readable content.
- 5 15. The method of claim 1 wherein establishing said connection comprises establishing an internet protocol connection with said server.
16. The method of claim 1 further comprising launching a browse session with a uniform resource locator pointing to a user registration page for permitting a user to enter registration information.
- 10 17. The method of claim 10 wherein controlling subsequent use of said content comprises enabling subsequent use of said content when said key is received from said server.
- 15 18. The method of claim 10 wherein controlling subsequent use of said content comprises disabling further use of said content when no key is received from said server.
19. The method of claim 18 further comprising deleting files produced by functional descriptive content in said computer readable content.
- 20 20. The method of claim 19 further comprising warning a user of said processor circuit that files are about to be deleted.
21. The method of claim 10 wherein controlling subsequent use of said content comprises maintaining a count of the number of times a warning about deleting files is presented to a user of the processor circuit.
- 25 22. The method of claim 21 wherein controlling comprises deleting files produced by functional descriptive content in said computer readable content when said count exceeds a threshold value.
- 30

23. A method of controlling a use of computer readable content, the method comprising transmitting to a user computer a key operable to cooperate with said user computer to deactivate execution of instruction codes embedded in said computer readable content at said user computer, in response to receipt of registration information from said user computer.
24. The method of claim 23 further comprising hosting a uniform resource locator pointing to a user registration page for permitting a user to provide said registration information to register as a user of said computer readable content.
25. The method of claim 24 further comprising validating said registration information.
26. The method of claim 25 further comprising executing the act of transmitting when said registration information is successfully validated.
27. A computer readable medium on which is stored computer readable content and instruction codes embedded in said computer readable content, said instruction codes being operable to direct a processor circuit to produce a measure of use of said content by said processor and to automatically establish a connection to a server, when said content is in use by the processor circuit and said measure of use exceeds a threshold value, to transmit registration information to the server and operable to enable further use of the content by the processor circuit in response to a key received from the server.
28. A data signal comprising a first code segment providing computer readable content and a second code segment embedded in said first code segment such that said second code segment is rendered operational when said first segment is used, said second code segment comprising instructions for directing a processor circuit to produce a measure of use of said content by said processor and to automatically establish a connection to a server, when said content is in use by the processor circuit and said measure of use

exceeds a threshold value, to transmit registration information to the server and operable to enable further use of the content by the processor circuit in response to a key received from the server.

5 **29.** The computer readable medium of claim **27** wherein said instruction codes are provided in a self executing apple.

30. A system operable to encourage users of computer readable content to register, the system comprising:

10 a) a processor circuit;

 b) a communications interface in communication with said processor circuit for communicating with a server; and

15 c) a receiver for receiving computer readable content with instruction codes embedded therein, said instruction codes being operable to cause said processor circuit to produce a measure of use of said content by said processor and to automatically cause said communications interface to establish a connection to a server, when said measure of
20 use exceeds a threshold value, to transmit registration information to the server, and to enable subsequent use of said computer readable content by said processor circuit, in response to a key received from the server.

31. The system of claim **30** wherein said receiver includes a media reader.

25 **32.** The system of claim **30** wherein said communications interface is operable to establish communications on a network.

33. The system of claim **30** wherein said processor circuit is part of a personal computer.

34. A system for controlling the use of computer readable content, the system comprising:

a) a receiver for receiving registration information from a user computer; and

5 b) a transmitter for transmitting to a user computer a key operable to cooperate with said user computer to deactivate execution of instruction codes embedded in computer readable content at said user computer, in response to receipt of registration information at said receiver.

10 35. The system of claim 34 wherein said receiver includes a web server operable to host a uniform resource locator pointing to a user registration page for permitting a user to provide registration information to register as a user of said computer readable content.

15 36. The system of claim 35 wherein said web server is programmed to validate said registration information.

37. The system of claim 36 wherein said web server includes said transmitter.




FIG. 1




FIG. 2





FIG. 3






FIG. 5

CONNECTION ESTABLISHMENT

