

(21) Application No: 1911622.7
(22) Date of Filing: 12.09.2016
Date Lodged: 14.08.2019

(62) Divided from Application No
1615448.6 under section 15(9) of the Patents Act 1977

(71) Applicant(s):
iPulse Limited
Office Block A, Bay Studios Business Park,
Fabian Way, Swansea, SA1 8QB, United Kingdom

(72) Inventor(s):
Stuart Terry Jones

(74) Agent and/or Address for Service:
Urquhart-Dykes & Lord LLP
UDL Intellectual Property, 7th Floor, Churchill House,
17 Churchill Way, Cardiff, CF10 2HH, United Kingdom

(51) INT CL:
A61N 5/06 (2006.01) A61B 18/18 (2006.01)

(56) Documents Cited:
WO 2000/030714 A1 US 20130060309 A1

(58) Field of Search:
INT CL A61B, A61N
Other: WPI, EPODOC, Patent Fulltext

(54) Title of the Invention: **Apparatus for dermatological treatment**
Abstract Title: **A light emitting dermatological treatment apparatus**

(57) A light emitting apparatus for dermatological treatment designed to emit intense pulsed light, comprising a housing structure 6 for housing a light source 12 arranged to emit light externally, and a fan 26 configured to direct air heated by operation of the light source 12 into a duct 28 of the apparatus. Heated air is directed in a pathway 31 from an outlet port 32 at a distal end 28a of the duct 28 through an aperture (4, fig 4) in the housing 6. In order to minimize heat exchange between the heated air and the housing 6, no part of the housing 6 extends into the pathway 31 exiting from the duct 28. The aperture (4, fig 4) comprises a housing duct having an inlet 11 and an outlet 32. The aperture (4, fig 4) tapers outwardly in the direction of the airflow intermediate the inlet 11 and the outlet 32. The distal end of the duct 28a can be recessed relative to the housing structure 6.




Fig. 3




Fig. 1




Fig. 2




Fig. 3




Fig. 4

Apparatus for Dermatological Treatment

The present invention relates to a light emitting device for providing dermatological treatment.

5

The use of light is widely known for use in various treatments of tissue for both therapeutic and cosmetic purposes, including but not limited to hair removal, treatment of acne and lesions and tissue rejuvenation.

- 10 A typical light emitting device for dermatological treatment comprises a charge storage device in the form of a capacitor, a housing, a light emitting source in the form of a flashlamp and a cooling fan and a housing arrangement.

In operation energy is released from the capacitor through the flashlamp thereby generating
15 an intense pulse of light energy. Generation of the intense pulse of light energy by the flashlamp has the unwanted side effect of generating a significant amount of heat. In order to prevent overheating, air is moved through the housing by the fan to cool the operation of the lamp and other internal components, which is then expelled from the housing through an outlet vent area, which is often covered by a grid to prevent access to internal components.

- 20 A problem exists in that it is desirable for pulse repetition rate to be high which enables the device to be moved over the skin quickly improving ease of use. As a result there is reduced time in between each pulse for the device to cool. Therefore, significant amounts of heat can be generated, and the air can be at a high temperature which may exceed 80°C. As a result the housing temperature may increase to a value which is higher than regulatory safety
25 limits that prevent burning of a user. This is clearly undesirable. One method of mitigating this is to reduce the firing rate. This reduction in firing rate may be continuous, or adaptive, based on a monitored temperature of a component of the device such as the housing and preventing firing of the lamp if the temperature of the housing exceeds a predetermined safe value. The effect of this however is an overall reduction in pulse repetition rate meaning
30 operation is slower and the treatment takes longer. Furthermore, operation can be inconsistent if the device is being drawn across the skin at an approximately constant speed,

then firing of the lamp may be at irregular intervals reducing efficacy of treatment as some areas of the skin will undergo different treatments to other areas.

The present invention provides an improved arrangement.

5

According to the present invention there is a light emitting apparatus for dermatological treatment as defined in claim 1.

10 The present invention enables an improved air flow of air heated by the light emitting source away from the apparatus thereby enabling the time between pulses of light energy being emitted by the light source (pulse repetition rate) to be decreased. This provides significant benefits in operation as the apparatus can be moved over the skin at a faster rate whilst still maintaining efficacy. The hold period where a user cannot move the apparatus due to the necessary cooling time between pulses can be eliminated.

15

The housing structure has the user accessible external surfaces of the device that can be easily touched during normal use.

20 The duct beneficially focusses the airstream out of the housing structure in a direction that is not towards the housing structure. However, it will be appreciated that depending on for example external conditions to the apparatus or speed of movement of the apparatus itself there may be some deflection of heated air exiting the duct towards the housing arrangement. However, the present invention minimises this effect through the relative configuration of the duct and housing structure to provide no part of the housing structure in the focussed
25 airstream pathway.

It will be appreciated that the housing structure provides a handset for a user to grasp.

30 The relative configuration of the duct outlet and housing structure is beneficially such that the hot air exits the handset in one or more high speed jets that minimise contact between the heated air and the surrounding housing structure thus minimising heat exchange from the hot air to the housing structure that is held by a user.

The housing aperture has a length and a width both in an axis substantially perpendicular to the airstream pathway, wherein the width is small enough that a finger cannot be readily inserted. A suitable width is less than about 6mm. Thus the aperture of the housing is small
5 enough that a finger cannot be readily inserted. The housing aperture is preferably elongate in an axis substantially perpendicular to the airstream pathway, the length of the aperture is preferably significantly greater than the width. This configuration prevents insertion of a finger whilst also ensures high air flow rate from the housing structure.

- 10 The duct and housing structure are beneficially relatively arranged to direct the airstream away from and substantially perpendicular to the housing structure. Thus, irrespective of the external shape of the housing structure (preferably convex) the airstream is directed away from the housing structure in a direction that minimises heating of the housing structure either side of the airstream and effectively centralises the airstream between either side of
15 the housing structure defining the aperture.

The airstream is uninterrupted after exiting the distal end of the duct. It is beneficial that a grid or mesh or similar that can be easily touched by the user is not provided covering the outlet port. In the present invention the aperture in the housing structure may be kept open
20 and uninterrupted by a grid or mesh, meaning there is no touchable grid or mesh provided directly in the airflow pathway becoming heated by the exhaust air jet and thus forming a burning hazard to a user.

It may be beneficial to use a material for the aperture surround area of the housing structure
25 that has a low thermal conductivity such as thermoplastic.

The distal end of the duct is beneficially insulated from the housing structure. This beneficially reduces conduction of heat from the relatively hot duct to the handset enclosure. The distal end of the duct is preferably insulated from the housing by a separation gap,
30 preferably an air gap. It is beneficial that the insulation is provided by a space defined between a portion of the distal end of the duct and the housing structure. It is preferable that

the space extends around a majority of the distal end of the duct. The space may be an annular space defined between the distal end of the duct and the housing.

The duct is preferably positioned inside the housing structure. The duct may therefore
5 terminate rearwardly of the housing aperture. Thus, the distal end of the duct may be substantially hidden behind the housing structure. By positioning the duct in the housing structure the chance of accidental contact with the duct significantly heated by the airstream is minimised. The duct preferably comprises a duct opening at the distal end thereof substantially aligned with the opening defined by the housing aperture.

10

The housing aperture comprises a housing duct having an inlet and an outlet, and wherein the housing duct tapers outwardly in the direction of the airflow intermediate the inlet and the outlet. The housing duct through which the airstream exits therefore beneficially does not have a constant cross sectional area. Instead the cross sectional area may increase
15 towards the external surface of the housing structure. This configuration reduces the heating effect upon the edge of the housing structure defining the housing structure aperture due to any divergence of the airstream after exiting the distal end of the duct.

Despite the arrangements so far described, the housing material directly surrounding the
20 housing structure aperture may still increase in temperature more than desired. Therefore, a further preferred feature of the invention is for the housing structure to comprise one or more air inlet ports for enabling airflow into the housing structure. This allows relatively cool air from outside the housing structure to be drawn into the housing structure through the air inlet ports or cooling ducts due to the pressures generated by fan. The flow of air through the
25 cooling ducts will act to cool the material surrounding the aperture thus helping to prevent an excessive temperature rise. The one or more air inlet ports may be located adjacent the housing aperture. The air inlet ports provide a secondary (or more) airflow path in addition to the main lamp cooling airflow that is designed for keeping the housing structure cool. A plurality of air inlet ports may be provided in array adjacent the housing aperture.

30

The fan is preferably a radial fan. A radial fan enables the housing to be have a reduced size in comparison to an axial fan due to relatively high pressure and flow rate that can be generated, and also the increased compactness of the air outlet.

- 5 The distal end of the duct is beneficially recessed relative to the housing structure. This provides a safety benefit in that it is more difficult for a user to touch the heated duct.

The cross-sectional area of the duct may reduce and may taper towards the distal end. This beneficially accelerates the flow of air improves smooth airflow through the duct creating a
10 high speed jet.

The duct is at least partially curved. This aids in reducing the overall size of the housing structure, particularly when utilising a radial fan.

- 15 One or more baffles may be provided in the duct for reducing divergence and/or rotation of the airflow exiting the duct. These baffles, which may also be termed air flow guide ribs within the duct cannot be easily touched and may be used to help form and direct the high speed airstream.

- 20 Aspects of the present invention will now be described by way of example only with reference to the accompanying drawings where:

Figure 1 is a plan view of an apparatus according to an exemplary embodiment of the present invention.

25

Figure 2 is a schematic cross sectional view cut through line A-A of figure 1 according to an exemplary embodiment of the present invention.

- Figure 3 is a magnified schematic representation of the air flowpath through the apparatus
30 as presented in figure 2.

Figure 4 is a schematic part cross sectional representation of an apparatus according to an alternative exemplary embodiment of the present invention.

Referring to figure 1 there is a schematic plan representation of an apparatus according to an exemplary embodiment of the present invention. The apparatus presented is an Intense Pulse Light (IPL) device comprising a housing structure in the form of a handset (6) connected via an umbilical cable (3) to a charging module (not shown). The charging module in turn is connected to a mains power supply). As described in more detail in subsequent figures there is a housing aperture (4) through which heated air is expelled. A dividing rib (7) may be provided for distinguishing to a user between the handle portion of the housing structure and the venting portion incorporating the aperture (4). As can be seen in figure 1, the aperture (4) is elongate having a length and a width, and the length is significantly greater than the width. Further as clearly shown in figure 4 are optional baffles (9) and air inlet ports (11) described in detail with respect to figure 4.

Referring to figure 2 there is a cross-sectional representation through the handset (6) presenting the components of the handset. A flash lamp in the form of a xenon flash lamp (12) is provided and is driven by the storage capacitor (14). Light energy output from the lamp (12) is focused by reflector (16) forwardly through filter arrangement (18) which is present to remove harmful wavelengths of light below approximately 510nm. The light energy having passed through the filter (18) is output from the apparatus from the mouth (20). One or more of a skin contact/skin tone sensor (not shown) is provided at the forward end of the handset (6) adjacent to the mouth (20). Such a skin contact/tone sensor (22) is in communication with the controller taking the form of a control PCB (24) to prevent operation of the apparatus unless a valid skin contact/tone reading is received.

Due to the significant amount of heat generated by the lamp (12) a cooling fan (26) is provided to draw air into the handset (6) thereby cooling the lamp. Hot air is output through the duct (28) and exits the handset from housing aperture (4). Further components comprise a user operable actuator in the form of a button to cause operation of the device and there is further provided a skin contact indicator light indicating that the forward end of the handset is in contact or is in proximity to the skin.

The duct (28) can be seen to provide an airflow pathway to directing an airstream from the fan (26) to the outlet aperture (4). The fan (26) is a radial fan. The duct (28) can be seen to have a maximum cross-sectional area adjacent the fan (26) reducing to a minimum cross-sectional area at the outlet aperture (4). The speed of the heated air travelling through the duct (28) may be increased towards the outlet aperture (4). The duct (28) itself may taper towards the outlet aperture (4).

The fan (26) itself may be retained by an enclosure (27) and in operation draws in heated air axially and expels the heated air radially into the duct (28). A primary airflow inlet (29) is beneficially provided to ensure sufficient air flow through the housing (6) and out through the aperture (4). Additional air inlet ports (11) can be seen adjacent to aperture (4). As presented in figure 2, dashed line (31) represents air flow pathway through the housing (6).

Referring now to figure 3 the fan (26), duct (28) and aperture (4) are presented in more detail. Duct (28) provides the function of directing heated air in an airstream pathway from the fan (26) to an outlet port (32) at the distal end of the duct (28a). The duct (28) directs the heated air in the airstream pathway through the aperture (4) provided in the housing (6). The duct (28) and housing (6) are relatively arranged such that no part of the housing structure extends into the airstream pathway exiting from the duct (28). This is clearly apparent in figure 3. Thus, the airstream is uninterrupted as it exits the outlet (32) of the distal end (28) of the duct. The distal end of the duct (28a) is positioned rearwardly of housing (6). It is thus extremely difficult for a user to accidentally contact the distal end of the duct (28a) which will be hot due to the effect of the heated air passing therethrough. A small separation gap (34) is preferably provided between the distal end of the duct (28a) and the housing (6) to prevent conduction of heat therebetween. One or more baffles (36) may be provided in the duct (28) to improve alignment of the air flow in the air stream pathway. This further improves the coherence of the direction of travel of the air through the duct (28) and improves air coherence exiting the opening (28a) and thus the aperture (4).

To further reduce the effect of heating of the housing (6) the aperture (4) is defined by a wall (38) that tapers outwardly from an upstream to a downstream location and is thus wider at

the outlet than the inlet. This further reduces heating of the housing (6) adjacent to the aperture (4) due to any dispersion of the heated airflow after exiting the apparatus. Accordingly, heat exchange from the heated air to the housing structure is minimised.

- 5 Referring now to figure 4, an embodiment of the invention is presented in a cross section as presented in figure 3 without the provision of additional air inlet ports (11). Again a separation gap (34) is beneficial between the distal end (28a) of the duct and the housing (6). Furthermore, the optional baffles (36) have not been positioned in the duct (28). Importantly, however, no part of the housing (6) extends into the airstream pathway in order to minimise
- 10 heat exchange from the heated air to the housing.

Additional changes or modifications may be forming the duct (28) integrally with the fan (26). It will also be appreciated that an axial fan could be utilised.

- 15 Aspects of the present invention have been described by way of example only and it will be appreciated to the skilled addressee that modifications and variations made be made without departing from the scope of protection afforded by the appended claims.

Claims

1. A light emitting apparatus for dermatological treatment comprising a housing structure for housing a light emitting source, a fan and a duct, the light emitting source arranged to emit light energy to external of the device, the fan configured for directing air heated by operation of the light emitting source into the duct, the duct being arranged to direct heated air in an airstream pathway from an outlet port of a distal end of the duct and through an aperture in the housing structure, wherein the housing structure and the duct are relatively arranged such that no part of the housing structure extends into the airstream pathway in order to minimise heat exchange from the heated air to the housing structure, wherein the housing aperture comprises a housing duct having an inlet and an outlet, and wherein the housing duct tapers outwardly in the direction of the airflow intermediate the inlet and the outlet.
2. An apparatus according to claim 1 wherein the housing aperture has a length and a width both in an axis substantially perpendicular to the airstream pathway, wherein the width is less than 6mm.
3. An apparatus according to any preceding claim wherein the housing aperture is elongate in an axis substantially perpendicular to the airstream pathway.
4. An apparatus according to any preceding claim wherein the distal end of the duct is recessed relative to the housing structure.
5. An apparatus according to any preceding claim wherein the duct is positioned inside the housing structure.
6. An apparatus according to claim 5 wherein the duct comprises a duct opening at the distal end thereof substantially aligned with the opening defined by the housing aperture.

7. An apparatus according to any preceding claim wherein the housing structure comprises one or more air inlet ports for enabling airflow into the housing.
8. An apparatus according to claim 7 wherein the one or more air inlet ports are located adjacent the housing aperture.
9. An apparatus according to any of claims 7-8 wherein the one or more inlet ports comprises a plurality of air inlet ports provided in an array.
10. An apparatus according to any preceding claim wherein the fan is a radial fan.
11. An apparatus according to any preceding claim wherein the duct is at least partially curved.
12. An apparatus according to any preceding claim comprising one or more baffles provided in the duct for reducing divergence and/or rotation of the airflow exiting the duct.
13. An apparatus according to any preceding claim wherein the duct has a length extending from the fan to the distal end, wherein the cross-sectional area of the duct reduces towards the distal end.
14. An apparatus according to claim 13 wherein the cross-sectional area of the duct tapers towards the distal end.

Claims

1. A light emitting apparatus for dermatological treatment comprising a housing structure for housing a light emitting source, a fan and a duct, the light emitting source arranged to emit light energy to external of the device, the fan configured for directing air heated by operation of the light emitting source into the duct, the duct being arranged to direct heated air in an airstream pathway from an outlet port of a distal end of the duct and through an aperture in the housing structure, wherein the housing structure and the duct are relatively arranged such that no part of the housing structure extends into the airstream pathway in order to minimise heat exchange from the heated air to the housing structure, wherein the housing aperture comprises a housing duct having an inlet and an outlet, and wherein the housing duct tapers outwardly in the direction of the airflow intermediate the inlet and the outlet.
2. An apparatus according to claim 1 wherein the housing aperture has a length and a width both in an axis substantially perpendicular to the airstream pathway, wherein the width is less than 6mm.
3. An apparatus according to any preceding claim wherein the housing aperture is elongate in an axis substantially perpendicular to the airstream pathway.
4. An apparatus according to any preceding claim wherein the distal end of the duct is recessed relative to the housing structure.
5. An apparatus according to any preceding claim wherein the duct is positioned inside the housing structure, and wherein the duct comprises a duct opening at the distal end thereof substantially aligned with the opening defined by the housing aperture.
6. An apparatus according to any preceding claim wherein the housing structure comprises one or more air inlet ports for enabling airflow into the housing.

7. An apparatus according to claim 6 wherein the one or more air inlet ports are located adjacent the housing aperture.
8. An apparatus according to any of claims 6-7 wherein the one or more inlet ports
5 comprises a plurality of air inlet ports provided in an array.
9. An apparatus according to any preceding claim wherein the fan is a radial fan.
10. An apparatus according to any preceding claim wherein the duct is at least partially
10 curved.
11. An apparatus according to any preceding claim comprising one or more baffles
provided in the duct for reducing divergence and/or rotation of the airflow exiting the
duct.
15
12. An apparatus according to any preceding claim wherein the duct has a length extending
from the fan to the distal end, wherein the cross-sectional area of the duct reduces
towards the distal end.
- 20 13. An apparatus according to claim 12 wherein the cross-sectional area of the duct tapers
towards the distal end.



Application No: GB1911622.7

Examiner: Dr Chris Perry

Claims searched: 1-14

Date of search: 28 August 2019

Patents Act 1977: Search Report under Section 17

Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance
A	---	US2013/060309 A1 (BRADLEY)
A	---	WO00/30714 A1 (VOVES)

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^X:

Worldwide search of patent documents classified in the following areas of the IPC

A61B; A61N

The following online and other databases have been used in the preparation of this search report

WPI, EPODOC, Patent Fulltext

International Classification:

Subclass	Subgroup	Valid From
A61N	0005/06	01/01/2006
A61B	0018/18	01/01/2006