



(43) International Publication Date
7 January 2016 (07.01.2016)

- (51) International Patent Classification:
H01H 50/02 (2006.01) *H01H 11/00* (2006.01)
F16J 15/14 (2006.01)
- (21) International Application Number:
PCT/EP2015/065179
- (22) International Filing Date:
3 July 2015 (03.07.2015)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
14306082.0 3 July 2014 (03.07.2014) EP
- (71) Applicant: VALEO EQUIPEMENTS ELECTRIQUES
MOTEUR [FR/FR]; 2 rue André Bouille, F-94046 Creteil
Cedex (FR).
- (72) Inventor: BALZAM, Sébastien; Skalskiego 5/9 street,
Poland, PL-42-500 Bedzin (PL).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: COVER OF A CONTACTOR OF STARTERS FOR MOTOR VEHICLE




Fig. 2

(57) Abstract: The present invention refers to a cover (17) of a contactor (1) of a starter for motor vehicle, comprising - a plastic portion (18) delimiting a contact chamber (15) volume, - two plugs (43, 45) in an electrical conductor material which cross the plastic portion, each of the two plugs (43, 45) having an end in the contact chamber (15), - a seal (37) which is arranged on the plastic portion (18) to isolate the contact chamber (15) when the cover (17) is assembled with a coil casing (5) of the contactor (1), the seal (37) being assembled in a fixed manner to the cover (17).

COVER OF A CONTACTOR OF STARTERS FOR MOTOR VEHICLE

5 The present invention refers to the domain of the starters for motor vehicles and more particularly to the contactor of the starters.

 The contactors of the state of the art comprise a coil arranged in a coil casing and configured for moving axially the mobile part of a magnetic core located in the center of the coil. The magnetic core is acting on a rod which controls a contact plate located outside of the coil casing in a contact chamber. The contact plate is destined for joining two electrical contacts having their ends in the contact chamber when the mobile part of the magnetic core is moved axially by the coil. The contact chamber is delimited by a cover through which the two electrical contacts are arranged. The cover is fastened to the coil casing. Furthermore, in order to ensure the isolation of the contact chamber in particular against humidity, a seal is needed between the cover and the coil casing. In the state of the art, the seal is made using a rubber seal which is positioned during assembly of the cover thanks to coil wires going through the cover. However, with such seal, there is a risk of deformation of the seal during transport (before assembly on the contactor) due to the flexibility of the material so that dedicated packaging needs to be foreseen leading to extra costs. Furthermore, the positioning of the seal is cumbersome and there is a risk of incorrect positioning which may lead to an isolation failure that may induce humidity to enter into the chamber and may cause lack of electrical contact due to the formation of ice on the contacts in low temperature. Ice is formed due to humidity condensation on terminals because of the temperature gradient induced by the accelerated cooling of the terminals with respect to the internal contact chamber temperature.

25

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to overcome the precited drawbacks of

-2-

the state of the art and to provide a solution enabling to ease the assembly of the contactor while ensuring a correct isolation.

Thus, the present invention refers to a cover of a contactor of a starter for motor vehicle,
5 comprising

- a plastic portion delimiting a contact chamber volume,
- two plugs in an electrical conductor material which cross the plastic portion, each of the two plugs having an end in the contact chamber,
- a seal which is arranged on the plastic portion to isolate the contact chamber when the
10 cover is assembled with a coil casing of the contactor, the seal being assembled in a fixed manner to the cover.

According to another aspect of the present invention, the seal is assembled to the plastic portion by overmolding.

15 According to a further aspect of the present invention, the plastic portion and the seal are obtained by a bi-injection process.

According to another aspect of the present invention, the plastic portion and the seal are
20 assembled together using a self-adhesive tape.

According to another aspect of the present invention, the plastic portion and the seal are glued together.

25 According to an additional aspect of the present invention, the seal and the plastic portion comprise a plurality of pins and a plurality of holes complementary to the pins to ensure the fixation of the seal to the cover.

30 According to another aspect of the present invention, the pins have a length comprised in

-3-

a range from 2 to 5 mm and a diameter comprised in a range from 1 to 3 mm.

According to a further aspect of the present invention, the seal comprises more than ten pins and wherein the pins are spaced apart of 3 to 10 mm.

5

According to an additional aspect of the present invention, the seal has a rectangular shape.

According to another aspect of the present invention, the seal is made of thermoplastic elastomer.

10

According to another aspect of the present invention, the seal is around the chamber in order to add a contact plate after the seal on the cover.

15

According to another aspect of the present invention, the seal comprise an opening corresponding to a contact plate of the contactor.

This allows facilitating the process by mounting the seal on the cover and adding a contact plate with a rod after with a fixed part and the other elements of the contactor.

20

The present invention also refers to a contactor comprising a cover as disclosed above.

According a a aspect of the invention, the contactor comprising a fixed part of the magnetic core, a contact plate which is between the magnetic core and the two plugs, and wherein the seal is around the contact plate.

25

The present invention also refers to a starter comprising a contactor as disclosed above.

BRIEF DESCRIPTION OF THE DRAWINGS

30 – Fig.1 represents a sectionnal view of a contactor;

-4-

- Fig.2 represents a diagram of a cover and an associated seal according to the present invention;
- Fig.3 represents a diagram of a cover according to the present invention;
- Fig.4 represents a diagram of a seal according to the present invention.

5

In these drawings, the elements having the same reference correspond to elements having a similar function.

DETAILED DESCRIPTION OF THE INVENTION

10

Figure 1 represents a diagram of a contactor 1 of a starter comprising a coil 3 located in a coil casing 5. The center of the coil 3 defines a tubular chamber 6 wherein a magnetic core 7 is arranged. The magnetic core 7 comprises a mobile part 7a configured to be displaceable axially from a rest position represented in fig.1 to an active position. In this rest position, the mobile part 7a is in contact with a stop 9 under the constraint of a first helicoidal spring 11. In the active position, the mobile part 7a of the magnetic core comes in contact with a fixed part 7b of the magnetic core 7 under the action of the coil 3. When moving to the active position, the mobile part 7a of the magnetic core 7 acts on a rod 13, also called contact axis, which lies from the tubular chamber 6 through the fixed part 7b of the magnetic core 7 and protrudes in a contact chamber 15 which is delimited by a cover 17. The cover 17 is fastened to the coil casing 5 and is crossed by two conductive plugs 43 and 45 having each an end protruding in the contact chamber 15. The two conductive plugs 23 protrude therefore on one side of the contact chamber 15 whereas the rod 13 protrudes on the opposite side. The rod 13 is linked to a contact plate 19 located in the contact chamber 15, the rod 13 and the contact plate 19 forming a contact element 21. The contact plate 19 is arranged to come into contact with both plugs 23 and 25 when the contact element 21 is moved by the displacement of the moving part 7a of the magnetic core 7 in the active position. The contact element 21 is therefore configured to be displaceable between a first position wherein the contact plate 19 is in contact with the fixed part 7b of the magnetic core 7 and a second position wherein the contact plate 19 comes into contact with both plugs 23 and 25. A second helicoidal spring 27 is disposed between the cover 17 and the contact element

21 to force the contact element 21 in the first position when the moving part 7a of the magnetic core 7 is in its rest position.

The cover 17 will now be described in more details based on figure 2.

5

The cover 17 comprises a circular face that comes into contact with the fixed part 7b of the magnetic core 7 and with the coil casing 5 surrounding the magnetic core 7. The cover 17 is fastened to the coil casing 5 or to the fixed part 7b of the magnetic core 7 for example thanks to coil ends (not represented in figure 2) arranged through the holes 29 and 31. The cover 17 may
10 comprise a positioning coding such as a pair of pins 33 and 35 in the present case in order to ensure the right positioning of the cover 17 on the coil casing 5 or the fixed part of the magnetic core 7. The cover comprises two plugs 43 and 45 (represented in figure 3) made of an electrical conductor material, for example copper, that protrude in the contact chamber 15 through dedicated holes 47 and 49.

15 Furthermore, a seal 37 is placed between the cover 17 and the fixed part 7b of the magnetic core 7 to ensure a hermetic closing of the contact chamber 15 to prevent the introduction of impurities and/or humidity within the contact chamber 15. The seal 37 is arranged in a fixed manner to the cover 17. The fixation is ensured for example by a plurality of pins 39 and complementary holes 41 as represented in figures 3 and 4. The pins 39 can be
20 arranged on the seal 37 and the holes 41 arranged on the cover 17 as represented in figures 3 and 4 or the pins can also be arranged on the cover 17 so that the holes are then located on the seal 37.

In an alternative embodiment, the pins 39 can be distributed between the seal 37 and the cover 17. The number and the size of the pins 39 may vary depending on the required fixation
25 force between the seal 37 and the cover 17. In the present case, the pins 39 have a length comprised in a range from 3 to 5mm and a diameter comprised in a range from 1 to 3mm. The space between two pins 39 may also vary depending on the fixation required. In the present case, the spacing is regular and is comprised in a range from 5 to 10 mm. The seal 37 has a rectangular shape but other shapes may also be chosen depending on the shape of the contact chamber 15.
30 The structure 18 of the cover 17 is made of a plastic having a high stiffness, such as a

-6-

thermoplastic material, for example a polyamide (PA46 or PA66) filled with fiber glass in different ratios or thermoset materials such as phenolic resins filled with fiber glass in different ratios, in order to apply the required pressure on the seal 37 to ensure the hermetic closing of the contact chamber 15 whatever the constraints imposed by the movement of the different elements of the contactor 1 and notably the contact element 21. Alternatively or in combination with the pins, self-adhesive tape or glue can be used for assembly of the seal to the cover.

The seal 37 is made of a plastic, for example a thermoplastic elastomer or a rubber which can be injected such as TPE du type EPDM-PP like the SantopreneTM, which is softer than the plastic used for the plastic portion 18 of the cover 17 and that can be compressed between the cover 17 and the fixed part 7b of the magnetic core 7 or the coil casing 5 to ensure the hermetic closing of the contact chamber 15. Furthermore, the plastic of the seal 37 needs to be adapted to be injected or overmolded.

According to a first embodiment, the seal 37 is overmolded directly on the cover 17.

According to a second embodiment, the plastic portion 18 of the cover 17 and the seal 37 are obtained by bi-injection.

With these processes, the manufacturing of the seal 37 is easy. Furthermore, there is no problem of placement or deformation of the seal 37 before assembly as the seal 37 is already placed in fixed manner on the cover 17 during manufacturing. The risk of leaks due to a non-compliant seal 37 is therefore greatly reduced.

CLAIMS

5

1. Cover (17) of a contactor (1) of a starter for motor vehicle, comprising

- a plastic portion (18) delimiting a contact chamber (15) volume,
- two plugs (43, 45) in an electrical conductor material which cross the plastic portion, each of the two plugs (43, 45) having an end in the contact chamber (15),
- a seal (37) which is arranged on the plastic portion (18) to isolate the contact chamber (15) when the cover (17) is assembled with a coil casing (5) of the contactor (1), the seal (37) being assembled in a fixed manner to the cover (17).

10

15

2. Cover (17) in accordance with claim 1 wherein the seal (37) is assembled to the plastic portion (18) by overmolding.

3. Cover (17) in accordance with claim 1 wherein the plastic portion (18) and the seal (37) are obtained by a bi-injection process.

20

4. Cover (17) in accordance with one of the previous claims wherein the seal (37) and the plastic portion (18) comprise a plurality of pins (39) and a plurality of holes (41) complementary to the pins (39) to ensure the fixation of the seal (37) to the cover (17).

25

5. Cover (17) in accordance with claim 4 wherein the pins (39) have a length comprised in a range from 2 to 5 mm and a diameter comprised in a range from 1 to 3 mm.

30

6. Cover (17) in accordance with claim 4 or 5 wherein the seal (37) comprises more than ten pins (39) and wherein the pins (39) are spaced apart of 3 to 10 mm.

7. Cover (17) in accordance with one of the previous claims wherein the seal (37)

has a rectangular shape.

8. Cover (17) in accordance with one of the previous claims wherein the seal (37) is made of a thermoplastic elastomer.

5

9. Cover (17) in accordance with one of the previous claims wherein the seal is around the chamber in order to add a contact plate (19) after the seal on the cover.

10

10. Cover (17) in accordance with one of the previous claims wherein the seal comprise an opening corresponding to a contact plate (19) of the contactor.

11. Contactor (1) comprising a cover (17) according to one of the previous claims.

15

12. Contactor (1) according to claim 11, comprising a fixed part 7b of the magnetic core 7, a contact plate (19) which is between the magnetic core and the two plugs, and wherein the seal is around the contact plate.

13. Starter comprising a contactor (1) according to claim 11 or 12.

1/2




Fig.1




Fig.2

2/2




Fig.3




Fig.4

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2015/065179

A. CLASSIFICATION OF SUBJECT MATTER
INV. H01H50/02 F16J15/14 H01H11/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H01H F16J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 973 581 A (JACQUIN PASCAL [FR] ET AL) 26 October 1999 (1999-10-26)	1,7,11, 13
Y	figures 1-4 column 1, line 6 - line 7 column 2, line 46 - line 52 column 4, line 38 - line 39 column 5, line 11 - line 29 -----	2,3,8
Y	EP 2 282 316 A1 (VALEO SIST S DE SEGURIDAD Y DE CIERRE [ES]) 9 February 2011 (2011-02-09) paragraph [0039] - paragraph [0040]; figure 3B -----	2,8
Y	EP 0 878 814 A1 (SI BE R S P A [IT]) 18 November 1998 (1998-11-18) column 2, line 37 - line 46; figures 1, 2 ----- -/--	3



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

1 September 2015

Date of mailing of the international search report

10/09/2015

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Bilard, Stéphane

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2015/065179

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 740 604 A1 (VALEO EQUIP ELECTR MOTEUR [FR]) 30 April 1997 (1997-04-30) figures 1,2 page 6, line 7 - line 19 -----	9,10,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2015/065179

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5973581	A	26-10-1999	BR 9803376 A 03-11-1999
		DE 69822407 D1 22-04-2004	
		DE 69822407 T2 03-03-2005	
		EP 0920045 A1 02-06-1999	
		ES 2218784 T3 16-11-2004	
		FR 2768259 A1 12-03-1999	
		US 5973581 A 26-10-1999	
EP 2282316	A1	09-02-2011	EP 2282316 A1 09-02-2011
		JP 2013500561 A 07-01-2013	
		KR 20120079460 A 12-07-2012	
		WO 2011012556 A1 03-02-2011	
EP 0878814	A1	18-11-1998	BR 9801616 A 15-06-1999
		EP 0878814 A1 18-11-1998	
		IT BS970049 U1 12-11-1998	
FR 2740604	A1	30-04-1997	NONE