



(51) International Patent Classification:
H04L 12/56 (2006.01)

(21) International Application Number:
PCT/EP2005/012225

(22) International Filing Date:
11 November 2005 (11.11.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04292820.0 30 November 2004 (30.11.2004) EP

(71) Applicant (for all designated States except US): **ALCATEL** [FR/FR]; 54, rue La Boétie, F-75008 Paris (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BECK, Michaël, Andries, Thomas** [BE/BE]; Azalealei 105, B-2170 Merksem (BE). **BORGHS, Eric, Frans, Elisa** [BE/BE]; Kollegestraat 75, B-2440 Geel (BE). **CAUTEREELS, Paul, Henri, Marie** [BE/BE]; V. De Witstraat 51, B-2880 Himene (BE). **DEQUEKER, Hans, Maurice, Felix, Corneel** [BE/BE]; Dorenstraat 207, B-3020 Herent (BE). **GYSELINGS, Tim** [BE/BE]; Van Havrelei 55, B-2100 Deurne (BE).

(74) Agent: **NARMON, Gisèle**; Intellectual Property Department, Alcatel Bell N.V., Francis Wellesplein 1, B-2018 Antwerp (BE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLOW-AWARE ETHERNET DIGITAL SUBSCRIBER LINE ACCESS MULTIPLEXER DSLAM



(57) Abstract: An access node (1) that is preferably a Flow Aware Ethernet DSLAM adapted to transmit Ethernet data frames between subscribers (2) and an aggregation network (3). The access node comprises a first memory (4) for storing classification rules and a second memory (6) for storing flow rules. These rules are applied by a classification agent (5) and by a service agent (7) to information extracted from incoming data frames in order to infer flow awareness information of outgoing frames corresponding to these incoming data frame. In this way, the subscriber access network evolves to a multi-service architecture by replacing ATM with Ethernet for cost reasons. The concept of "flow awareness" is applied to the present access node. With respect to known tunnel-based Ethernet DSLAMs, the present access node removes all dependency on correct encapsulation or labeling at the customer side and at the service provider side. By removing the need for tunnels, traffic may be inserted at any intermediate point, as may be required for multicast.

FLOW-AWARE ETHERNET DIGITAL SUBSCRIBER LINE ACCESS
MULTIPLEXER DSLAM

The present invention relates to an access node adapted to transmit Ethernet data frames between a plurality of subscribers and an aggregation network.

Such an access node is generally known in the art. It is for instance a well-known Digital Subscriber Line Access Multiplexer DSLAM.

Subscriber access networks comprising an access node are evolving to a multi-service architecture, while trying to replace Asynchronous Transfer Mode ATM with Ethernet for cost reasons. To support a multi-service architecture, ATM-like features must be added to Ethernet, such as "flow awareness". This is the ability to treat traffic differently depending on the subscriber to whom it belongs, and the type of service it represents.

To date, Quality-of-Service QoS, policing and forwarding decisions are made in the access node by means of tunnel-based protocols, such as ATM, Point-to-Point Protocol over ATM PPPoA, and Point-to-Point Protocol over Ethernet PPPoE, or Differentiated Services DiffServ labeling techniques.

The mechanism relies on correct encapsulation or labeling at the customer side and at the service provider side. There is no possibility to insert traffic into a tunnel at an intermediate point, as may be required for multicast. There is no possibility to dynamically increase or decrease the number of quality-of-service levels at an intermediate point.

Furthermore, the known access nodes always operate at a single layer of the network for all traffic: either layer 2 (Ethernet switch) or layer 3 (Internet Protocol IP router).

An object of the present invention is to introduce the concept of "flow awareness", well known in the field of ATM and IP, to an access node, as for instance an Ethernet DSLAM.

According to the invention, this object is achieved due to the fact that said access node comprises a memory adapted to store classification rules applicable to said data frames, and that said access node further comprises a classification agent coupled to said memory and adapted to
5 extract source information from an incoming data frame, and to apply said classification rules onto said extracted source information in order to infer flow awareness information of an outgoing frame corresponding to said incoming data frame.

In this way, the concept of "flow awareness" may be applied to the
10 present access node, a flow being a set of data frames characterized by any specific combination of fields up to layer 3 of the protocol stack. With respect to tunnel-based Ethernet DSLAMs, the present access node removes all dependency on correct encapsulation or labeling at the customer side and at the service provider side. By removing the need for tunnels, traffic may now
15 be inserted at any intermediate point, as may be required for multicast.

In a preferred characterizing embodiment of the present invention, said access node is an Ethernet Digital Subscriber Line Access Multiplexer.

In other words, the present access node is a Flow-Aware Ethernet
20 DSLAM that combines the advantages both of the Ethernet DSLAM and of the flow concept. This combination is a necessary step towards the evolution to an Ethernet-based access and aggregation network. A flow-aware Ethernet DSLAM would thus provide the benefits of an Ethernet DSLAM (low cost, packet-based switching) with the Quality-of-Service and policing
25 capabilities of a tunnel-based DSLAM.

Another characterizing embodiment of the present invention is that said classification agent is adapted to apply said classification rules onto first source information extracted from at least one first incoming data frame of a flow, and to calculate frame signatures from second source
30 information extracted from the following data frame of said flow.

Implementing the flow concept in a large access multiplexer, e.g. a fiber aggregator, involves a significant amount of processing power, given the huge amounts of data traveling through the box. To facilitate the implementation, the concept of "stateful flow awareness" is introduced by the invention: only the first frame(s) of a flow, i.e. the pilot frames, need(s) to be inspected in detail in order to make a global policing, classification, and forwarding decision for the entire flow, based on a set of formal rules. Later frames belonging to the same flow, recognized by a "signature", are treated according to the decision established for the pilot frames. Metering may be implemented on a per-flow basis.

Also another characterizing embodiment of the present invention is that said source information consists in one or more of a source Media Access Control MAC address, a destination Media Access Control MAC address, a Virtual Local Area Network Identification Number VLAN ID, a user-priority field, a source Internet Protocol IP address, a destination IP address, and a Type Of Service TOS field.

Physical port, logical port (if applicable), source and/or destination MAC address, VLAN id, 802.1p bits, source and/or destination IP address, TOS bits are all fields of the protocol stack up to layer 3. In other words, the decision to forward a flow to a particular outbound port may be based among other criteria on its destination MAC address (Ethernet bridging), the VLAN identifier and destination MAC address (VLAN bridging), or the destination IP address (basic IP router function).

Yet another characterizing embodiment of the present invention is that said access node further comprises a service agent coupled to said classification agent and adapted to extract additional information from said incoming data frames, and that said service agent is adapted to apply said classification rules to a combination of said source information and said additional information in order to infer flow awareness information of an outgoing frame corresponding to said incoming data frame.

Additionally or alternatively to the above described embodiment, the flow may be committed to a "service blade" or an internal agent that is capable of treating the individual frames of the flow with regard to higher-layer content information.

5 Again another characterizing embodiment of the present invention is that said additional information consists in one or more of an Internet Protocol IP field, a source Transmission Control Protocol TCP port, a destination TCP port, a source User Datagram Protocol UDP port, and a destination UDP port.

10 This further granularity is obtained by looking at fields from layer 4 of the protocol stacks up.

 The present invention is further characterized in that said flow awareness information consists in one or more of outbound port identity, format, header fields, priority, and drop precedence of an outgoing frame
15 corresponding to said incoming data frame.

 The information obtained by identifying the flow to which certain traffic belongs can thus be used inter-alia to make a forwarding decision (outbound port selection), to rebuild the frame structure (protocol translation), or to set the quality of service parameters of the outgoing
20 frame.

 Still another characterizing embodiment of the present invention is that said access node further comprises a service agent coupled to said classification agent and adapted to apply cryptographic transformations to at least parts of said incoming data frames.

25 Flow awareness allows a dynamic increase or decrease of the number of quality-of-service levels at the flow-aware Ethernet DSLAM. Another advantage is the possibility to apply additional processing to certain flows, including network address translation and encryption. Further characterizing embodiments of the present access node are
30 mentioned in the appended claims.

It is to be noticed that the term 'comprising', used in the claims, should not be interpreted as being restricted to the means listed thereafter. Thus, the scope of the expression 'a device comprising means A and B' should not be limited to devices consisting only of components A and B. It
5 means that with respect to the present invention, the only relevant components of the device are A and B.

Similarly, it is to be noticed that the term 'coupled', also used in the claims, should not be interpreted as being restricted to direct connections only. Thus, the scope of the expression 'a device A coupled to a
10 device B' should not be limited to devices or systems wherein an output of device A is directly connected to an input of device B. It means that there exists a path between an output of A and an input of B which may be a path including other devices or means.

The above and other objects and features of the invention will
15 become more apparent and the invention itself will be best understood by referring to the following description of an embodiment taken in conjunction with the accompanying drawings wherein the single Figure represents a flow-aware Ethernet access node 1 according to the invention.

The access node 1 shown in the Figure is able to transmit
20 Ethernet data frames between subscribers 2 and an aggregation network 3. It is preferably an Ethernet Digital Subscriber Line Access Multiplexer DSLAM provided with Asynchronous Transfer Mode ATM-like features that allows it to support a multi-service architecture. One of these ATM-like features is for instance "flow awareness", which is the ability to treat traffic
25 differently depending on the subscriber to whom it belongs and the type of service it represents.

To achieve this, the access node 1, which will thus preferably be a Flow-Aware Ethernet DSLAM, comprises a first memory 4 storing classification rules applicable to the Ethernet data frames, and a
30 classification agent 5 applying these rules onto source information extracted from incoming data frames. The aim of the classification agent 5 is to infer

flow awareness information of outgoing frames corresponding to incoming data frames. The memory 4 is coupled to the classification agent 5 that is itself coupled to both the subscribers 2 and the aggregation network 3.

In a preferred embodiment, the classification agent 5 of the access node 1 applies the classification rules of the memory 4 only onto source information extracted from one or more first incoming data frames of a flow, also called pilot frames. This source information is inspected in detail, based on the set of the formal classification rules, in order to make a global policing, classification, and forwarding decision for the entire flow. The classification agent 5 further calculates frame signatures from source information extracted from the following data frame of the same flow. Recognized by their signature to belong to the same flow, these later frames are treated according to the decision established for the pilot frames. This concept is called "stateful flow awareness".

It is to be noted that the source information extracted from the Ethernet data frames consists in at least one or a combination of:

- a source Media Access Control MAC address,
- a destination Media Access Control MAC address,
- a Virtual Local Area Network Identification Number VLAN ID,
- a user-priority field, a source Internet Protocol IP address,
- a destination IP address, and/or
- a Type Of Service TOS field.

Physical port, logical port (if applicable), source and/or destination MAC address, VLAN id, 802.1p bits, source and/or destination IP address, TOS bits are all fields of the protocol stack up to layer 3.

In other words, the decision to forward a flow to a particular outbound port may be based, among other criteria, on its destination MAC address (Ethernet bridging), the VLAN identifier and destination MAC address (VLAN bridging), or the destination IP address (basic IP router function).

The access node 1 also comprises a second memory 6 coupled to the classification agent 5 and storing flow rules applicable to the signatures of the data frames. The classification agent 5 applies the flow rules onto frame signatures in order to infer flow awareness information of outgoing frames corresponding to incoming data frames.

Furthermore, the access node 1 also comprises a service agent 7 coupled in a bi-directional way to the classification agent 5 and able to extract additional information from the incoming data frames.

As for the classification agent 5, the service agent 7 applies the classification rules of the first memory 4 but now to a combination of the above source information and of the additional information. The aim of the service agent 7 is to infer flow awareness information of outgoing frames corresponding to incoming data frames. It can be seen that the flow may be committed to a "service blade" or an internal agent that is capable of treating the individual frames of the flow with regard to higher-layer content information, i.e. the additional information.

The additional information consists in at least one or a combination of:

- an Internet Protocol IP field,
- a source Transmission Control Protocol TCP port,
- a destination TCP port,
- a source User Datagram Protocol UDP port, and/or
- a destination UDP port.

This further granularity is obtained by looking at fields from layer 4 of the protocol stacks up.

The above-mentioned flow awareness information consists in one or more of outbound port identity, format, header fields, priority, and drop precedence of an outgoing frame corresponding to the incoming data frame.

Flow awareness allows a dynamic increase or decrease of the number of quality-of-service levels at the flow-aware Ethernet DSLAM. Another advantage is the possibility to apply additional processing to

certain flows, including network address translation and encryption. To this end, the service agent 7 may be adapted to apply cryptographic transformations to at least parts of the incoming data frames.

5 It to be noted that flow classification does not require a match of all the fields that the classification agent 5 is able to inspect; certain fields or certain rules may be treated as “wildcards”, which means that their value does not influence the identification of the frame as belonging to a particular flow.

10 A final remark is that embodiments of the present invention are described above in terms of functional blocks. From the functional description of these blocks, given above, it will be apparent for a person skilled in the art of designing electronic devices how embodiments of these blocks can be manufactured with well-known electronic components. A detailed architecture of the contents of the functional blocks hence is not
15 given.

While the principles of the invention have been described above in connection with specific apparatus, it is to be clearly understood that this description is merely made by way of example and not as a limitation on the scope of the invention, as defined in the appended claims.

CLAIMS

1. An access node (1) adapted to transmit Ethernet data frames between a plurality of subscribers (2) and an aggregation network (3),

characterized in that said access node (1) comprises a memory (4)
5 adapted to store classification rules applicable to said data frames,

in that said access node further comprises a classification agent (5) coupled to said memory and adapted to extract source information from an incoming data frame, and to apply said classification rules onto said extracted source information in order to infer flow awareness information of
10 an outgoing frame corresponding to said incoming data frame.

2. The access node according to claim 1, *characterized in that* said access node (1) is an Ethernet Digital Subscriber Line Access Multiplexer (DSLAM).
15

3. The access node according to claim 1, *characterized in that* said classification agent (5) is adapted to apply said classification rules onto first source information extracted from at least one first incoming data frame of a flow, and to calculate frame signatures from second source
20 information extracted from the following data frame of said flow.

4. The access node according to claim 1, *characterized in that* said source information consists in one or more of a source Media Access Control MAC address, a destination Media Access Control MAC address, a
25 Virtual Local Area Network Identification Number VLAN ID, a user-priority field, a source Internet Protocol IP address, a destination IP address, and a Type Of Service TOS field.

5. The access node according to claim 4,

characterized in that said access node (1) further comprises a service agent (7) coupled to said classification agent (5) and adapted to extract additional information from said incoming data frames

5 *and in that* said service agent is adapted to apply said classification rules to a combination of said source information and said additional information in order to infer flow awareness information of an outgoing frame corresponding to said incoming data frame.

10 6. The access node according to claim 5, *characterized in that* said additional information consists in one or more of an Internet Protocol IP field, a source Transmission Control Protocol TCP port, a destination TCP port, a source User Datagram Protocol UDP port, and a destination UDP port.

15

7. The access node according to claim 1,

characterized in that said classification agent (5) is further adapted to calculate frame signatures of said incoming data frames from said extracted source information,


20 *in that* said access node (1) further comprises a second memory (6) coupled to said classification agent and adapted to store flow rules applicable to said signatures,

and in that said classification agent is adapted to apply said flow rules onto said frame signatures in order to infer said flow awareness information
25 of an outgoing frame corresponding to said incoming data frames.

8. The access node according to any of the claims 1, 5 or 7, *characterized in and in that* said flow awareness information consists in one or more of outbound port identity, format, header fields, priority, and drop
30 precedence of an outgoing frame corresponding to said incoming data frame.

9. The access node according to claim 1, *characterized in that* said access node (1) further comprises a service agent (7) coupled to said classification agent (5) and adapted to apply cryptographic transformations to at least parts of said incoming data frames.

1/1



Figure

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2005/012225

A. CLASSIFICATION OF SUBJECT MATTER

H04L12/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 453 260 A (HUAWEI TECHNOLOGIES CO., LTD) 1 September 2004 (2004-09-01)	1,2,4,8
Y	column 1, line 19 - column 2, line 30	3,7
A	column 2, line 53 - column 3, line 27	5,6,9
	column 4, line 3 - column 7, line 41	
	claims 1,2,5-8,10	
	figures 1,3-5	
Y	WO 2004/080024 A (INTELLIGUARD I.T. PTY LTD; REED, DARREN, JAMES; BAKER, KENNETH, GEORGE) 16 September 2004 (2004-09-16)	3,7
A	page 2, line 25 - page 3, line 26	1,2,4-6, 8,9
	claims 1,6,7,10	
	----- -/--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

30 January 2006

Date of mailing of the international search report

06/02/2006

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Schrembs, G

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2005/012225

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 073 251 A (TEXAS INSTRUMENTS INCORPORATED) 31 January 2001 (2001-01-31) page 2, line 3 - line 41 page 5, line 16 - line 39 page 9, line 7 - line 13 claims 1,2,12 figures 1-4,7 -----	1-9
A	US 6 424 657 B1 (VOIT ERIC A ET AL) 23 July 2002 (2002-07-23) column 1, line 15 - line 25 column 2, line 49 - line 65 column 3, line 53 - column 5, line 60 column 7, line 16 - column 8, line 31 claims 1,11,18 figures 1-8 -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2005/012225

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1453260	A	01-09-2004	CN 1525702 A	01-09-2004
			JP 2004260832 A	16-09-2004
			US 2004177107 A1	09-09-2004
WO 2004080024	A	16-09-2004	NONE	
EP 1073251	A	31-01-2001	CN 1291029 A	11-04-2001
			TW 488134 B	21-05-2002
US 6424657	B1	23-07-2002	NONE	