



US 20170238984A1

(19) **United States**(12) **Patent Application Publication**
Kleiner(10) **Pub. No.: US 2017/0238984 A1**(43) **Pub. Date: Aug. 24, 2017**(54) **BONE GRAFT DELIVERY DEVICE WITH POSITIONING HANDLE**(71) Applicant: **Spinal Surgical Strategies, LLC,**
Denver, CO (US)(72) Inventor: **Jeffrey Kleiner,** Denver, CO (US)(21) Appl. No.: **15/424,205**(22) Filed: **Feb. 3, 2017****Related U.S. Application Data**

(63) Continuation-in-part of application No. 14/887,598, filed on Oct. 20, 2015, now Pat. No. 9,629,729, which is a continuation-in-part of application No. 14/263,963, filed on Apr. 28, 2014, now Pat. No. 9,186,193, which is a continuation-in-part of application No. 14/088,148, filed on Nov. 22, 2013, now Pat. No. 8,709,088, which is a continuation of application No. 13/947,255, filed on Jul. 22, 2013, now Pat. No. 8,685,031, which is a continuation-in-part of application No. 13/714,971, filed on Dec. 14, 2012, now Pat. No. 9,173,694, which is a continuation-in-part of application No. 13/367,295, filed on Feb. 6, 2012, now Pat. No. 9,060,877, which is a continuation-in-part of application No. 12/886,452, filed on Sep. 20, 2010, now Pat. No. 8,906,028.

(60) Provisional application No. 62/290,755, filed on Feb. 3, 2016, provisional application No. 61/243,664, filed on Sep. 18, 2009.


Publication Classification(51) **Int. Cl.****A61B 17/88** (2006.01)**A61F 2/46** (2006.01)**A61F 2/44** (2006.01)(52) **U.S. Cl.**

CPC **A61B 17/8816** (2013.01); **A61F 2/4455** (2013.01); **A61F 2/4601** (2013.01); **A61B 17/8805** (2013.01); **A61F 2002/4624** (2013.01); **A61F 2002/30579** (2013.01)

(57)

ABSTRACT

The present disclosure relates to an apparatus and method for near-simultaneous and integrated delivery of bone graft material and placement of surgical cages or other medical implants in a patient's spine. The integrated fusion cage and graft delivery device according to various embodiments delivers and disperses biologic material through a fusion cage to a disc space and, without withdrawal from the surgical site, may detach the fusion cage for deposit. The integrated fusion cage and graft delivery device is formed such that a hollow tube and plunger selectively and controllably place bone graft material and a fusion cage in or adjacent to the bone graft receiving area. In certain embodiments, the integrated fusion cage is an expandable integrated fusion cage.






FIG. 1A




FIG. 1B






FIG. 1C









FIG. 4






FIG. 6




FIG. 7



FIG. 8



FIG. 9




FIG. 10A

FIG. 10B

FIG. 10C

FIG. 10D




FIG. 11A




FIG. 11B





FIG. 11C



SECTION A-A

FIG. 11D




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 15A




FIG. 15B






FIG. 15C



SECTION A-A

FIG. 15D







FIG.17A



SECTION A-A

FIG.17B




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 21A




FIG. 21B




FIG. 21C






FIG. 21D












FIG.26






FIG.29




FIG.30




FIG.31




FIG.32




FIG.33




FIG.34A




FIG.34B

- 1ml DISK REMOVAL = 6.6+/-0.9ml
- 2ml DISK REMOVAL = 8.4+/-2.8ml
- 3ml DISK REMOVAL = 8.8+/-2.0ml
- 4ml DISK REMOVAL = 10.2+/-3.5ml
- 5ml DISK REMOVAL = 12.1+/-1.9ml
- 6ml DISK REMOVAL = 11.6+/-2.4ml
- 7ml DISK REMOVAL = 11.1+/-3.1ml
- 8ml DISK REMOVAL = 12.3+/-2.3ml

FIG.35A




FIG.35B






FIG.36










FIG. 39








FIG.42




FIG. 43










FIG.44












FIG. 49A




FIG. 49B





FIG. 49c














FIG. 50c

















FIG. 57A




FIG. 57C











FIG. 57B

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----


FIG. 57B








ASSEMBLED VIEW,
EXPANDED








FIG. 62A




FIG. 62B




FIG. 63A




FIG. 63B






FIG. 64









FIG. 6C






FIG. 68A





FIG. 68B






FIG. 70





FIG. 71






FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84

BONE GRAFT DELIVERY DEVICE WITH POSITIONING HANDLE

[0001] This U.S. Non-Provisional Patent Application claims the benefit of priority from U.S. Provisional Patent Application Ser. No. 62/290,755, filed Feb. 3, 2016, the entire disclosure of which is hereby incorporated by reference. This Application also claims the benefit of priority from U.S. patent application Ser. No. 14/887,598, filed Oct. 20, 2015, which is a Continuation-in-Part of U.S. patent application Ser. No. 14/263,963, filed Apr. 28, 2014 and issued as U.S. Pat. No. 9,186,193, which is a Continuation-in-Part of U.S. patent application Ser. No. 14/088,148, filed Nov. 22, 2013 and issued as U.S. Pat. No. 8,709,088, which is a Continuation of U.S. patent application Ser. No. 13/947,255, filed Jul. 22, 2013 and issued as U.S. Pat. No. 8,685,031, which is a Continuation-in-Part of U.S. patent application Ser. No. 13/714,971, filed Dec. 14, 2012 and issued as U.S. Pat. No. 9,173,694, which is a Continuation-in-Part of U.S. patent application Ser. No. 13/367,295, filed Feb. 6, 2012 and issued as U.S. Pat. No. 9,060,877, which is a Continuation-in-Part of U.S. patent application Ser. No. 12/886,452, filed Sep. 20, 2010 and issued as U.S. Pat. No. 8,906,028, which claims priority from U.S. Provisional Patent Application Ser. No. 61/243,664, filed Sep. 18, 2009, the entire disclosures of which are hereby incorporated by reference in their entireties.

FIELD

[0002] The disclosure relates generally to bone graft delivery devices and methods of use, such as bone graft delivery devices comprising detachable handles.

BACKGROUND OF THE INVENTION

[0003] According to the American Academy of Orthopedic Surgeons, about 250,000 spinal fusion surgeries are performed every year, mostly on adults between the ages of 45 to 64. Spinal fusion is a process by which two or more of the vertebrae that make up the spinal column are fused together with bone grafts and internal devices (such as rods) that heal into a single solid bone. Spinal fusion can eliminate unnatural motion between the vertebrae and, in turn, reduce pressure on nerve endings. In addition, spinal fusion can be used to treat, for example, injuries to spinal vertebrae caused by trauma; protrusion and degeneration of the cushioning disc between vertebrae (sometimes called slipped disc or herniated disc); abnormal curvatures (such as scoliosis or kyphosis); and weak or unstable spine caused by infections or tumors.

[0004] Individuals who suffer degenerative disc disease, natural spine deformations, a herniated disc, spine injuries or other spine disorders may require surgery on the affected region to relieve the individual from pain and prevent further injury to the spine and nerves. Spinal surgery may involve removal of damaged joint tissue, insertion of a tissue implant and/or fixation of two or more adjacent vertebral bodies. In some instances a medical implant is also inserted, such as a fusion cage. The surgical procedure will vary depending on the nature and extent of the injury. Generally, there are five main types of lumbar fusion, including: posterior lumbar fusion (“PLF”), posterior lumbar interbody fusion (“PLIF”), anterior lumbar interbody fusion (“ALIF”), circumferential 360 fusion, and transforaminal lumbar interbody fusion (“TLIF”). More recently, direct lateral interbody fusion

(“D-LIF”) has become available. A posterior approach is one that accesses the surgical site from the patient’s back, an anterior approach is one that accesses the surgical site from the patient’s front or chest, and a direct lateral approach is one that accesses the surgical site from the patient’s side. There are similar approaches for fusion in the interbody or cervical spine regions. For a general background on some of these procedures and the tools and apparatus used in certain procedures, see U.S. Prov. Pat. Appl. No. 61/120,260 filed on Dec. 5, 2008, the entire disclosure of which is incorporated by reference in its entirety. In addition, further background on procedures and tools and apparatus used in spinal procedures is found in U.S. patent application Ser. No. 12/632,720 filed on Dec. 7, 2009, the entire disclosure of which is incorporated by reference in its entirety.

[0005] Vertebrectomy, or the removal or excision of a vertebra, is another type of spinal surgery that may be necessary to alleviate pain and/or correct spinal defects, such as when disk material above and below a particular vertebra protrudes from the spine and contacts the spinal cord. Once the problematic vertebra is removed, a specialized fusion cage (also called a vertebrectomy cage) may be inserted into its place to restore structural continuity to the spine.

[0006] Some disadvantages of traditional methods of spinal surgery include, for example, the pain associated with the procedure, the length of the procedure, the complexity of implements used to carry out the procedure, the prolonged hospitalization required to manage pain, the risk of infection due to the invasive nature of the procedure, and the possible requirement of a second procedure to harvest autograft bone from the iliac crest or other suitable site on the patient for generating the required quantity of cancellous and/or cortical bone.

[0007] A variety of semisolid bone graft materials are available on the market which ostensibly increase spinal fusion rates without the morbidity of autograft bone harvest. Each of the manufacturers espouses their product as the most advantageous for healing. These products all have similar handling characteristics and the literature reveals that they have similar healing prospects. They come in a syringe and it is up to the surgeon to apply the selected material to the target site. The most common site for application is to the disk space after it has been prepared to a bleeding bed and ready to accept a cage and/or the grafting material. This represents a long and narrow channel even in open procedures. The surgeon is left to his own devices as to how to get the graft from its container to the active site. The devices which have been used have included a “caulking gun” construct and a variety of barrel shaft with a plunger design.

[0008] Bone graft typically includes crushed bone (cancellous and cortical), or a combination of these (and/or other natural materials), and may further comprise synthetic biocompatible materials. Bone graft of this type is intended to stimulate growth of healthy bone. As used herein, “bone graft” shall mean materials made up entirely of natural materials, entirely of synthetic biocompatible materials, or any combination of these materials. Bone graft often is provided by the supplier in a gel or slurry form, as opposed to a dry or granule form. Many companies provide various forms of bone graft in varying degrees of liquidity and viscosity, which may cause problems in certain prior art delivery devices in both prepackaged or packaged by the surgeon embodiments. In addition, the method of delivery of

bone graft to a particular location varies depending on the form of the bone graft utilized.

[0009] Autogenous bone (bone from the patient) or allograft bone (bone from another individual) are the most commonly used materials to induce bone formation. Generally, small pieces of bone are placed into the space between the vertebrae to be fused. Sometimes larger solid pieces of bone are used to provide immediate structural support. Autogenous bone is generally considered superior at promoting fusion. However, this procedure requires extra surgery to remove bone from another area of the patient's body such as the pelvis or fibula. Thus, it has been reported that about 30 percent of patients have significant pain and tenderness at the graft harvest site, which may be prolonged, and in some cases outlast the back pain the procedure intended to correct. Similarly, allograft bone and other bone graft substitutes, although eliminating the need for a second surgery, have drawbacks in that they have yet to be proven as cost effective and efficacious substitutes for autogenous bone fusion.

[0010] An alternative to autogenous or allograft bone is the use of growth factors that promote bone formation. For example, studies have shown that the use of bone morphogenic proteins ("BMPs") results in better overall fusion, less time in the operating room and, more importantly, fewer complications for patients because it eliminates the need for the second surgery. However, use of BMPs, although efficacious in promoting bone growth, can be prohibitively expensive.

[0011] Another alternative is the use of a genetically engineered version of a naturally occurring bone growth factor. This approach also has limitations. Specifically, surgeons have expressed concerns that genetically engineered BMPs can dramatically speed the growth of cancerous cells or cause non-cancerous cells to become more sinister. Another concern is unwanted bone creation. There is a chance that bone generated by genetically engineered BMPs could form over the delicate nerve endings in the spine or, worse, somewhere else in the body.

[0012] Regenerative medicine, which harnesses the ability of regenerative cells, e.g., stem cells (i.e., the unspecialized master cells of the body) to renew themselves indefinitely and develop into mature specialized cells, may be a means of circumventing the limitations of the prior-art techniques. Stem cells, i.e., both embryonic and adult stem cells, have been shown to possess the nascent capacity to become many, if not all, of the 200+ cell and tissue types of the body, including bone. Recently, adipose tissue has been shown to be a source of adult stem cells (See e.g. Zuk, Patricia Z. et al., "Multilineage Cells from Human Adipose Tissue: Implication for Cell-Based Therapies," *Tissue Engineering*, April 2001, 7:211-28; Zuk, Patricia A. et al., "Human Adipose Tissue Is A Source Of Multipotent Stem Cells," *Molecular Biology of the Cell*, 2002, 13:4279-4295). Adipose tissue (unlike marrow, skin, muscle, liver and brain) is comparably easy to harvest in relatively large amounts with low morbidity (See e.g. Commons, G. W., Halperin, B., and Chang, C. C. (2001) "Large-volume liposuction: a review of 631 consecutive cases over 12 years" *Plast. Reconstr. Surg.* 108, 1753-63; Katz, B. E., Bruck, M. C. and Coleman, W. P. 3 (2001b) "The benefits of powered liposuction versus traditional liposuction: a paired comparison analysis" *Dermatol. Surg.* 27, 863-7). Accordingly, given the limitations of the prior art spinal fusion techniques, there exists a need for a

device that incorporates regenerative cells, e.g., stem cells that possess the ability to induce bone formation.

[0013] Many different methods and approaches have been attempted to induce bone formation or to promote spinal fusion. The traditional devices for inserting bone graft impair the surgeon's visualization of the operative site, which can lead to imprecise insertion of bone graft and possible harm to the patient. The caulking gun and the collection of large barrel/plunger designs typically present components at the top of their structure which block the view of the surgical site. The surgeon must then resort to applying pressure to the surgical site to approximate the location of the device's delivery area. Such rough maneuvering can result in imprecise placement of bone graft, and in some cases, rupture of the surgical area by penetrating the annulus and entering the abdominal cavity. Also, in some surgical procedures, the devices for inserting bone graft material are applied within a cannula inserted or placed in the surgical area, further limiting the size and/or profile of the bone graft insertion device. When a cannula is involved, some traditional devices such as the large barrel/plunger designs and/or the chalking gun designs simply cannot be used as they cannot be inserted within the cannula.

[0014] Traditional devices for inserting bone graft deliver the bone graft material at the bottom of the delivery device along the device's longitudinal axis. Such a delivery method causes the bone grafting material to become impacted at the bottom of the delivery device, and promotes risk of rupture of the surgical area by penetrating the annulus and entering the abdominal cavity. Further, traditional devices that deliver bone graft material along their longitudinal axis may cause rupture of the surgical area or harm to the patient because of the ensuing pressure imparted by the ejected bone graft material from the longitudinal axis of the device.

[0015] As mentioned, the method of delivery of bone graft to a particular location varies depending on the form of the bone graft utilized. For example, in the case of slurry type bone graft, various dispensing devices have been developed having applicators designed to accommodate this type of bone graft. One such device is disclosed by U.S. Pat. No. 5,925,051 issued to Mikhail on Jul. 20, 1999 ("Mikhail"). Mikhail provides a caulking gun type dispenser for introducing bone graft in an enlarged bone (e.g. femoral) cavity. The device preferably includes a barrel pre-loaded with bone graft and a cannulated ejector positioned over a multi-section guide wire. This arrangement purports to accomplish both ejecting bone graft from the barrel and compacting the bone graft material while being guided on the guide wire. Mikhail, however, is designed solely for use with slurry-type bone graft, and does not accommodate bone graft in granule form, which often varies in size among granules and does not have the same "flow" or viscosity characteristics as slurry-type bone graft. Thus, the applicator of Mikhail is insufficient for introducing most bone graft to a surgical site in a patient.

[0016] U.S. Pat. No. 6,019,765 issued to Thornhill et al. on Feb. 1, 2000 ("Thornhill") also teaches a bone graft delivery device. The bone graft device applicator of Thornhill is used to apply bone graft to an artificial joint without having to remove a previously implanted prosthesis component. The applicator device includes a hollow tube with an actuation mechanism for discharging the bone graft from the device via a nozzle coupled to a distal end of the tube. The bone graft delivery device of Thornhill may include various

components for loading the device with the bone graft, and may further include a plurality of nozzles each having a geometry suited for a particular application. Like Mikhail, the Thornhill delivery device is designed for use with bone slurry, and requires much custom instrumentation and different sized parts to achieve success in many bone graft delivery applications, which in turn increases the time to assemble and use the delivery device and may create further problems during the surgical operation.

[0017] U.S. Pat. No. 5,697,932 issued to Smith et al. on Dec. 16, 1997 ("Smith") discloses yet another bone graft delivery system and method. In Smith, a hollow tube of pre-loaded bone graft and a plunger are used to facilitate delivery of the bone graft to a bone graft receiving area. A positioning structure is provided on the plunger to maintain the plunger in a desirable position with respect to the hollow tube. Adjunct positioning means may also be provided to ensure that the plunger remains in the desirable position during the packing of bone graft into the bone graft receiving area. Like the devices of Thornhill and Mikhail, the device disclosed by Smith is clearly designed solely for slurry type bone graft, and does not provide an effective opening for receiving the desired amount of bone graft. Furthermore, the hollow tube shown by Smith is narrow and does not have a footing or other apparatus associated with the delivery device for preventing the device from penetrating, for example, the abdominal region of a patient, which may occur during tamping or packing of the bone graft. This in turn may cause serious injury to a patient if not controlled, and for these reasons the device of Smith is also insufficient for delivery of bone graft to a surgical site.

[0018] Traditional devices for inserting a fusion cage or other medical implants into a patient's spine or other surgical area are distinct and separate from traditional devices that deliver bone graft material to the surgical site. For example, once an implant has been positioned, then bone growth material is packed into the internal cavity of the fusion cage. Also, sometimes the process is reversed, i.e., the bone growth is inserted first, and then the implant. These bone growth inducing substances come into immediate contact with the bone from the vertebral bone structures which project into the internal cavity through the apertures. Two devices are thus traditionally used to insert bone graft material into a patient's spine and to position and insert a fusion cage. These devices thus necessitate a disc space preparation followed by introduction of the biologic materials necessary to induce fusion and, in a separate step, application of a structural interbody fusion cage.

[0019] The problems associated with separate administration of the biologic material bone graft material and the insertion of a fusion cage include applying the graft material in the path of the cage, restricting and limiting the biologic material dispersed within the disk space, and requiring that the fusion cage be pushed back into the same place that the fusion material delivery device was, which can lead to additional trauma to the delicate nerve structures.

[0020] Fusion cages provide a space for inserting a bone graft between adjacent portions of bone. Such cages are often made of titanium and are hollow, threaded, and porous in order to allow a bone graft contained within the interior of the cage of grow through the cage into adjacent vertebral bodies. Such cages are used to treat a variety of spinal disorders, including degenerative disc diseases such as Grade I or II spondylolistheses of the lumbar spine.

[0021] Surgically implantable intervertebral fusion cages are well known in the art and have been actively used to perform spinal fusion procedures for many years. Their use became popularized during the mid 1990's with the introduction of the BAK Device from the Zimmer Inc., a specific intervertebral fusion cage that has been implanted worldwide more than any other intervertebral fusion cage system. The BAK system is a fenestrated, threaded, cylindrical, titanium alloy device that is capable of being implanted into a patient as described above through an anterior or posterior approach, and is indicated for cervical and lumbar spinal surgery. The BAK system typifies a spinal fusion cage in that it is a highly fenestrated, hollow structure that will fit between two vertebrae at the location of the intervertebral disc.

[0022] Spinal fusion cages may be placed in front of the spine, a procedure known as anterior lumbar interbody fusion, or ALIF, or placed in back of the spine. The cages are generally inserted through a traditional open operation, though laparoscopic or percutaneous insertion techniques may also be used. Cages may also be placed through a posterior lumbar interbody fusion, or PLIF, technique, involving placement of the cage through a midline incision in the back, or through a direct lateral interbody fusion, or D-LIF, technique, involving placement of the cage through an incision in the side.

[0023] A typical procedure for inserting a common threaded and impacted fusion cage is as follows. First, the disc space between two vertebrae of the lumbar spine is opened using a wedge or other device on a first side of the vertebrae. The disk space is then prepared to receive a fusion cage. Conventionally, a threaded cage is inserted into the bore and the wedge is removed. A disk space at the first side of the vertebrae is then prepared, and a second threaded fusion cage inserted into the bore. Alternatively, the disk space between adjacent vertebrae may simply be cleared and a cage inserted therein. Often, only one cage is inserted obliquely into the disk space. Use of a threaded cage may be foregone in favor of a rectangular or pellet-shaped cage that is simply inserted into the disk space. Lastly, bone graft material may be inserted into the surgical area using separate tools and devices.

[0024] U.S. Pat. No. 4,743,256 issued to Brantigan ("Brantigan") discloses a traditional spinal back surgical method involving the implantation of a spinal fusion cage. The cage surfaces are shaped to fit within prepared endplates of the vertebrae to integrate the implant with the vertebrae and to provide a permanent load-bearing strut for maintaining the disc space. Brantigan teaches that these cages typically consist of a homogeneous nonresorbable material such as carbon-reinforced polymers such as polyether ether ketone (PEEK) or polyether ketone ether ketone ketone ("PEKEKK"). Although these cages have demonstrated an ability to facilitate fusion, a sufficient fusion is sometimes not achieved between the bone chips housed within the cage and the vertebral endplates. In particular, achieving a complete fusion in the middle portion of the cage has been particularly problematic. As shown in FIG. 6 herein, the upper U and lower L surfaces of these cages C have large transverse pores P which facilitate bone ingrowth, and these pores lead to an inner void space IVS which houses bone graft (not shown) which facilitates the desired fusion. In any case, Brantigan teaches the separate process and procedure for the insertion of a fusion cage and the insertion of bone

graft. Indeed, local bone graft harvested from the channel cuts into the vertebrae to receive the plug supplements the fusion.

[0025] U.S. Pat. Appl. 20070043442 of Abernathie et al. (“Abernathie”) discloses another traditional spinal back surgical method involving the implantation of a spinal fusion cage. Abernathie relates generally to an implantable device for promoting the fusion of adjacent bony structures, and a method of using the same. More specifically, Abernathie relates to an expandable fusion cage that may be inserted into an intervertebral space, and a method of using the same. Abernathie includes an aperture in the fusion cage to allow bone growth therethrough, as a separate procedure to the insertion of the fusion cage.

[0026] Traditional fusion cages are available in a variety of designs and composed of a variety of materials. The cages or plugs are commonly made of an inert metal substrate such as stainless steel, cobalt-chromium-molybdenum alloys, titanium or the like having a porous coating of metal particles of similar substrate metal, preferably titanium or the like as disclosed, for example, in the Robert M. Pilliar U.S. Pat. No. 3,855,638 issued Dec. 24, 1974 and U.S. Pat. No. 4,206,516 issued Jun. 10, 1980. These plugs may take the form of flat sided cubical or rectangular slabs, cylindrical rods, cruciform blocks, and the like.

[0027] U.S. Pat. No. 5,906,616 issued to Pavlov et al. (“Pavlov”) discloses a fusion cage of various cylindrical and conical shapes and a method of insertion. Like Brantigan, Pavlov teaches the separate process and procedure for the insertion of a fusion cage and the insertion of bone graft. U.S. Pat. No. 5,702,449 (“McKay”) discloses a spinal implant comprising a cage made of a porous biocompatible material reinforced by an outer sleeve made of a second material which is relatively stronger under the compressive load of the spine than the biocompatible material. U.S. Pat. No. 6,569,201 issued to Moumene et al. (“Moumene”) teaches a bone fusion device having a structural bioresorbable layer disposed upon the outer surface of a non-resorbable support. As the bioresorbable structural layer resorbs over time, the load upon the bone graft housed within the non-resorbable support increases. Published PCT Application No. WO 99/08627 (“Gresser”) discloses a fully bioresorbable interbody fusion device, as well as homogeneous composite devices containing at least 25% resorbable materials. U.S. Pat. No. 7,867,277 issued to Tohmeh discloses a spinal fusion implant of bullet shaped end.

[0028] U.S. Pat. No. 7,846,210 issued to Perez-Cruet et al. (“Perez-Cruet”) discloses an interbody device assembly consisting of a fusion device and an insertion device. The insertion device positions the fusion device between two vertebrae, provides bone graft material, and then detaches from the fusion device, leaving the fusion device in place to restore disc space height. However, the Perez-Cruet device is designed to receive bone graft material from its insertion device and distribute the material away from the fusion device. In most embodiments of the fusion device, a center plate is positioned immediately downstream of the received bone graft material and directs the bone graft to opposing sides of the fusion device. (See, for example, FIG. 20 depicting plate 308 directing bone graft material 392 along the exterior sides of the fusion device 302). As such, the Perez-Cruet fusion device is unlikely to completely fill the areas near of its fusion cage and deliver bone graft material to the surrounding bone graft site. Furthermore, none of the

Perez-Cruet fusion device embodiments feature a defined interior space or a cage-style design. Indeed, the Perez-Cruet fusion device explicitly teaches away from a contained-interior, fusion-cage-style device, asserting that its fusion device fills all of the disc space as opposed to a cage design, which contains the bone material. Furthermore, the Perez-Cruet does not feature a distal tip that functions to precisely position the fusion device and stabilize the device during delivery of bone graft material.

[0029] U.S. Pat. No. 7,985,256 issued to Grotz et al. (“Grotz”) discloses an expandable spinal implant for insertion between opposed vertebral end plates. The implant is a cylinder block of slave cylinders; a central cavity between the cylinders receives bone graft material and pistons positioned within the cylinders provide a corrective bone engaging surface for expanding against a first vertebral end plate. The insertion tool used to place the spinal implant includes a handle and hollow interior for housing hydraulic control lines and a bone graft supply line. The Grotz system does not allow precise positioning or delivery of bone graft material without an implant and requires a complex and bulky insertion tool.

[0030] U.S. Pat. Appl. 2010/0198140 to Lawson (“Lawson”) discloses a tool comprising a cannula with an open slot at the distal end and a closed tip. Lawson’s tool employs tamps to push bone aside and open up a void for filling; solid bone pellets are then rammed down the hollow interior of the cannula by a tamper and delivered to the surgical site. Lawson does not allow precise positioning or delivery of viscous bone graft material and has no capability to interconnect or integrate with an implant such as a bone graft fusion cage.

[0031] U.S. Pat. Appl. 2010/0262245 to Alfaro et al. (“Alfaro”) discloses a delivery system for an intervertebral spacer and a bone grafting material comprising a spacer disengagingly attached to a hollow handle. The handle comprises a chamber and bone grafting material-advancing means for introducing bone grafting material from the chamber into the spacer and the intervertebral spaces. The Alfaro system does not allow precise positioning or delivery of bone graft material through a distal tip that precisely positions the fusion device and stabilizes the device during delivery of bone graft material, and does not allow primarily lateral injection of bone graft fusion material.

[0032] The prior art bone graft delivery devices listed above typically must come pre-loaded with bone graft, or alternatively require constant loading (where permissible) in order to constantly have the desired supply of bone graft available. Moreover, these bone graft delivery devices generally cannot handle particulate bone graft of varying or irregular particulate size. Furthermore, the prior art devices for inserting a fusion cage or other medical implant into a patient’s spine or other surgical area are commonly distinct and separate from traditional devices that deliver bone graft material to the surgical site. As such, two devices are traditionally used to insert bone graft material into a patient’s spine and to position and insert a fusion cage. The problems associated with separate administration of the biologic material bone graft material and the insertion of a fusion cage include applying the graft material in the path of the cage, restricting and limiting the biologic material dispersed within the disk space, and requiring that the fusion cage be pushed back into the same place that the fusion material delivery device was, which can lead to additional

trauma to the delicate nerve structures. These problems can be a great inconvenience, cause avoidable trauma to a patient and make these prior art devices unsuitable in many procedures.

[0033] Therefore, there is a long-felt need for an apparatus and method for near-simultaneous and integrated precision delivery of bone graft material during the placement of surgical cages or other medical implants in a patient's spine. The present invention solves these needs. The present invention allows biologic material to flow directly to the fusion cage and be dispersed within the disc space in a single step, and can precisely and simply deliver particulate bone graft of varying or irregular particulate size. Thus, the present invention allows application of bone graft material through a detachable fusion cage, eliminates otherwise restriction of the volume of biologic material that may be dispersed within the disc space, and eliminates the requirement that the fusion cage be pushed back into the same place that the fusion material delivery device was, which can lead to additional trauma to the delicate nerve structures.

SUMMARY

[0034] A variety of instrumentation techniques have become available to assist with lumbar interbody stabilization. These include different approaches for placing fusion cages (oblique, lateral, anterior or posterior), using stackable cages, expandable cages and the application of cage coatings. Although this is a limited inventory, these available inventive strategies do not assist the surgeon with the most vexing problem of interbody fusion: delivery of bone graft or bone graft extenders, (collectively, BG) to the interbody space.

[0035] Bone graft ("BG") material it is a "compressible fluid" and a pressure applied to it by the plunger of a conventional, end-dispensing bone graft delivery tool (BGDT) preferentially drives out the liquid part of the mixture, leaving a condensed plug of the graft material trapped within the cylindrical tool. Removing, clearing and reinserting the cannula can traumatize the neighboring nerve tissue. A fixed funnel provided on a conventional BGDT prevents a surgeon from visualizing the tip of the cannula as it is placed in the disc space annulotomy. This puts the contents of the spinal canal at risk during BGDT insertion. Additionally, a tip of the cannula is round and end-dispensing, and cannot enter a collapsed disc space without damaging the endplates or skating off to an undesired location. Finally, the conventional, end-dispensing delivery device deposits BG directly in the path of the fusion cage to be applied and does not disperse the graft material into the surrounding, prepared disc space.

[0036] Based upon these considerations, novel BGDTs are provided herein that comprise a detachable funnel and an increased internal cross sectional area to improve the flow of BG material. Devices of the present disclosure comprise a modified cannula tip to allow entrance into a collapsed disc space and large portals are provided on the sides of the cannula to allow the BG to exit into the prepared disc space out of the way of the fusion cage.

[0037] Certain embodiments of the present disclosure relate to an apparatus and method for near-simultaneous and integrated delivery of bone graft material during the placement of surgical cages or other medical implants in a patient's spine. The integrated fusion cage and delivery device (the "device") is comprised generally of a tubular

member and a plunger for expelling bone graft from the tubular member, through a surgical fusion cage, and into a bone graft receiving area, then disengaging the fusion cage at the surgical site in a human patient. Thus, the apparatus and method allows the biologic material to flow directly into and through the fusion cage and dispersed within the disc space in a single step, and leave the detachable fusion cage in the surgical area. In one embodiment, the integrated fusion cage is an expandable integrated fusion cage. Other embodiments and alternatives to this device are described in greater detail below.

[0038] By way of providing additional background, context, and to further satisfy the written description requirements of 35 U.S.C. §112, the following references are incorporated by reference in their entireties for the express purpose of explaining the nature of the surgical procedures in which bone graft is used and to further describe the various tools and other apparatus commonly associated therewith: U.S. Pat. No. 6,309,395 to Smith et al.; U.S. Pat. No. 6,142,998 to Smith et al.; U.S. Pat. No. 7,014,640 to Kemppanien et al.; U.S. Pat. No. 7,406,775 to Funk, et al.; U.S. Pat. No. 7,387,643 to Michelson; U.S. Pat. No. 7,341,590 to Ferree; U.S. Pat. No. 7,288,093 to Michelson; U.S. Pat. No. 7,207,992 to Ritland; U.S. Pat. No. 7,077,864 Byrd III, et al.; U.S. Pat. No. 7,025,769 to Ferree; U.S. Pat. No. 6,719,795 to Cornwall, et al.; U.S. Pat. No. 6,364,880 to Michelson; U.S. Pat. No. 6,328,738 to Suddaby; U.S. Pat. No. 6,290,724 to Marino; U.S. Pat. No. 6,113,602 to Sand; U.S. Pat. No. 6,030,401 to Marino; U.S. Pat. No. 5,865,846 to Bryan, et al.; U.S. Pat. No. 5,569,246 to Ojima, et al.; U.S. Pat. No. 5,527,312 to Ray; and U.S. Pat. Appl. No. 2008/0255564 to Michelson.

[0039] By way of providing additional background, context, and to further satisfy the written description requirements of 35 U.S.C. §112, the following references are incorporated by reference in their entireties for the express purpose of explaining the nature of the surgical procedures in which fusion cages are used and to further describe the various tools and other apparatus commonly associated therewith: U.S. Pat. No. 6,569,201 to Moumene et al.; U.S. Pat. No. 6,159,211 to Boriani et al.; U.S. Pat. No. 4,743,256 to Brantigan; U.S. Pat. Appl. 2007/0043442 to Abernathie et al.; U.S. Pat. Nos. 3,855,638 and 4,206,516 to Pilliar; U.S. Pat. No. 5,906,616 issued to Pavlov et al.; U.S. Pat. No. 5,702,449 to McKay; U.S. Pat. No. 6,569,201 to Moumene et al.; PCT Appl. No. WO 99/08627 to Gresser; U.S. Pat. Appl. 2012/0022651 to Akyuz et al.; U.S. Pat. Appl. 2011/0015748 to Molz et al.; U.S. Pat. Appl. 2010/0249934 to Melkent; U.S. Pat. Appl. 2009/0187194 to Hamada; U.S. Pat. No. 7,867,277 issued to Tohmeh; U.S. Pat. No. 7,846,210 to Perez-Cruet et al.; U.S. Pat. No. 7,985,256 issued to Grotz et al.; U.S. Pat. Appl. 2010/0198140 to Lawson; and U.S. Pat. Appl. 2010/0262245 to Alfaro et al.

[0040] By way of providing additional background and context, the following references are also incorporated by reference in their entireties for the purpose of explaining the nature of spinal fusion and devices and methods commonly associated therewith: U.S. Pat. No. 7,595,043 issued to Hedrick et al.; U.S. Pat. No. 6,890,728 to Dolecek et al.; U.S. Pat. No. 7,364,657 to Mandrusov, and U.S. Pat. No. 8,088,163 to Kleiner.

[0041] In addition, by way of providing additional background and context, the following references are also incorporated by reference in their entireties for the purpose of

explaining the nature of spinal fusion and devices and methods commonly associated therewith: U.S. Pat. No. D647,202 entitled “Bone Marrow Harvesting Device” to Scifert issued Oct. 18, 2011; U.S. Pat. No. 7,897,164 entitled “Compositions and Methods for Nucleus Pulposus Regeneration” to Scifert issued Mar. 1, 2011; US Pat. Appl. No. 2010/0112029 entitled “Compositions and Methods for Nucleus Pulposus Regeneration” to Scifert issued May 6, 2010; US Pat. Appl. No. 2010/0021518 entitled “Foam Carrier for Bone Grafting” to Scifert issued Jan. 28, 2010; U.S. Pat. No. 7,824,703 entitled “Medical Implants with Reservoir(s), and Materials Preparable From Same” to Scifert, et al., issued Nov. 2, 2010; US Pat. Appl. No. 2006/0247791 entitled “Multi-Purpose Medical Implant Devices” to McKay, et al., issued Nov. 2, 2006; US Pat. Appl. No. 2007/0225811 entitled “Conformable Orthopedic Implant” to Scifert, et al., issued Sep. 27, 2007; U.S. Pat. No. 6,746,487 entitled “Intramedullary Trial Fixation Device” to Scifert, et al., issued Jun. 9, 2004; US Pat. Appl. No. 2013/0073041 entitled “Medical Implants With Reservoir (s), and Materials Preparable From Same” to Scifert et al., issued Mar. 21, 2013; US Pat. Appl. No. 2010/0266689 entitled “Tissue Augmentation With Active Agent For Wound Healing” to Simonton et al., issued Oct. 21, 2010; US Pat. Application No. 2011/0028393 entitled “Flowable Paste And Putty Bone Void Filler” to Vickers et al., issued Feb. 3, 2011; US Pat. Appl. No. 2009/0099660 entitled “Instrumentation To Facilitate Access Into The Intervertebral Disc Space And Introduction Of Materials Therein” to Scifert issued Apr. 16, 2009; US Pat. Appl. No. 2011/0014587 entitled “System And Methods Of Preserving An Oral Socket” to Spagnoli et al., issued Jan. 20, 2011; U.S. Pat. No. 8,148,326 entitled “Flowable Carrier Matrix and Methods for Delivering to a Patient” to Beals et al., issued Apr. 3, 2012; US Pat. Appl. No. 2008/0260598 entitled “Devices, Methods and Systems for Hydrating a Medical Implant Material” to Gross et al., issued Oct. 23, 2008; US Pat. Appl. No. 2007/0265632 entitled “Bone Cutting Template and Method of Treating Bone Fractures” to Scifert et al., issued Nov. 15, 2007; U.S. Pat. No. 8,293,232 entitled “Flowable Carrier Matrix and Methods for Delivering to a Patient” to Beals et al., issued Oct. 23, 2012; U.S. Pat. No. 8,198,238 entitled “Flowable Carrier Matrix and Methods for Delivering to a Patient” to Beals et al., issued Jun. 12, 2012; U.S. Pat. No. 7,939,092 entitled “Cohesive Osteogenic Putty and Materials Therefor” to McKay et al., issued May 10, 2011; US Pat. Appl. No. 2007/0264300 entitled “Therapeutic Agent Carrier and Method of Treating Bone Fractures” to Scifert et al., issued Nov. 15, 2007; US Pat. Appl. No. 2011/0020768 entitled “Implantable Screw and System for Socket Preservation” to Spagnoli et al., issued Jan. 27, 2011; US Pat. Appl. No. 2012/0065687 entitled “Multi-Radius Vertebral Rod with a Varying Stiffness” to Ballard et al., issued Mar. 15, 2012; US Pat. No. 2007/0225219 entitled “Intramedullary Drug Delivery Device and Method of Treating Bone Fractures” to Boden et al., issued Sep. 27, 2007; U.S. Pat. No. 7,723,291 entitled “Release of BMP, Bioactive Agents and/or Cells Via a Pump into a Carrier Matrix” to Beals et al., issued May 25, 2010; U.S. Pat. No. 7,671,014 entitled “Flowable Carrier Matrix And Methods For Delivering To A Patient” to Beals et al., issued Mar. 2, 2010; U.S. Pat. No. 7,897,564 entitled “Flowable Carrier Matrix and Methods for Delivering to a Patient” to Beals et al., issued Mar. 1, 2011; US Pat. Application No.

2011/0160777 entitled “System and Methods of Maintaining Space for Augmentation of the Alveolar Ridge” to Spagnoli et al., issued Jun. 30, 2011; US Pat. Application No. 2009/0246244 entitled “Malleable Multi-Component Implants and Materials Therefor” to McKay et al., issued Oct. 1, 2009; US Pat. Application No. 2009/0246244 entitled “Malleable Multi-Component Implants and Materials Therefor” to McKay et al., issued Oct. 1, 2009; US Pat. No. 2013/0110169 entitled “Vertebral Rod System and Methods of Use” to Hynes, et al., issued May 2, 2013; US Pat. Appl. No. 2011/0184412 entitled “Pre-Assembled Construct With One Or More Non-Rotating Connectors For Insertion Into a Patient” to Scifert, et al., issued Jul. 28, 2011; U.S. Pat. No. 7,964,208 entitled “System and Methods of Maintaining Space For Augmentation of the Alveolar Ridge” to Spagnoli, et al., issued Jun. 21, 2011; U.S. Pat. No. 8,080,521 entitled “Flowable Carrier Matrix and Methods for Delivering to a Patient” to Beals, et al., issued Dec. 20, 2011; US Pat. Appl. No. 2009/0142385 entitled “Compositions for Treating Bone Defects” to Gross, et al., issued Jun. 4, 2009; U.S. Pat. No. 7,578,820 entitled “Devices and Techniques for a Minimally Invasive Disc Space Preparation and Implant Insertion” to Moore, et al., issued Aug. 25, 2009; US Pat. Appl. No. 2010/0305575 entitled “Methods and Apparatus for Performing Knee Arthroplasty” to Wilkinson, et al., issued Dec. 2, 2010; US Pat. Appl. No. 2011/0021427 entitled “Biphasic Calcium Phosphate Cement for Drug Delivery” to Amsden, et al., issued Jan. 27, 2011; US Pat. Appl. No. 2012/0259335 entitled “Patello-Femoral Joint Implant and Instrumentation” to Scifert, et al., issued Oct. 11, 2012; US Pat. Appl. No. 2011/0106162 entitled “Composite Connecting Elements for Spinal Stabilization Systems” to Ballard, et al., issued May 5, 2011; US Pat. Appl. No. 2004/0073314 entitled “Vertebral Body and Disc Space Replacement Devices” to White, et al., issued Apr. 15, 2004; U.S. Pat. No. 7,513,901 entitled “Graft Syringe Assembly” to Scifert, et al., issued Apr. 7, 2009; US Pat. Appl. No. 2010/0004752 entitled “Vertebral Body and Disc Space Replacement Devices” to White, et al., issued Jan. 7, 2010; U.S. Pat. No. 7,615,078 entitled “Vertebral Body and Disc Space Replacement Devices” to White, et al., issued Nov. 10, 2009; U.S. Pat. No. 6,991,653 entitled “Vertebral Body and Disc Space Replacement Devices” to White, et al., issued Jan. 31, 2006; US Pat. Appl. No. 2010/0331847 entitled “Methods and Apparatus for Performing Knee Arthroplasty” to Wilkinson, et al., issued Dec. 30, 2010; US Pat. Appl. No. 2006/0116770 entitled “Vertebral Body and Disc Space Replacement Devices” to White, et al., issued Jun. 1, 2006; and U.S. Pat. No. 8,246,572 entitled “Bone Graft Applicator” to Cantor, et al., issued Aug. 21, 2012.

[0042] According to varying embodiments described herein, the present invention is directed to near-simultaneous and integrated delivery of bone graft material during the placement of surgical cages or other medical implants into a patient's spine. The delivery of the bone graft material may be to any area of the body, and in particular to the intervertebral joints of the spine, for achieving bone graft fusion. The device may be used without the optional near-simultaneous and integrated placement of surgical cages with the delivery of bone graft material. Also, the invention may be used in the repair of a bone joint or in connection with the implantation of prosthetic devices in the body, including, by way of example but not limitation, the hip, knee and a variety of spinal joints. Additionally, the present invention

may be used in primary surgery, in which a bone graft is being supplied to promote new bone growth or to reconstruct a joint for the first time, as well as in revision surgery, in which a follow-up procedure is being performed in an area that has previously been subject to one or more surgeries. Further, the invention may be used in any application where material is to be delivered with precision to a confined area where access is restricted, to include surgical procedures, repair of installed or uninstalled mechanical or electrical devices, and arming or disarming of explosive devices.

[0043] Although well suited for use in human patients, and although much of the discussion of the present invention is directed toward use in humans, advantages offered by the present invention may be realized in the veterinary and scientific fields for the benefit and study of all types of animals and biological systems. Additionally, although the fusion cages of the present invention are particularly well-suited for implantation into the spinal column between two target vertebrae, and although much of the discussion of the present invention is directed toward their use in spinal applications, advantages offered by embodiments of the present invention may also be realized by implantation at other locations within a patient where the fusion of two or more bony structures may be desired. As one of skill in the art will appreciate, the present invention has applications in the general field of skeletal repair and treatment, with particular application to the treatment of spinal injuries and diseases. It should be appreciated, however that the principles of the present invention can also find application in other areas, specifically where there is a desire to constrain added fluid material to particular regions. For example, the present invention finds application in methods where the objective is to confine added material to predetermined areas of interest and to prohibit the undesired translocation of such material until an operation is complete and/or until a predetermined later time.

[0044] According to various embodiments of the present disclosure, one aspect of the invention is to provide an integrated fusion cage and graft delivery device that comprises a tubular member, which is substantially hollow or contains at least one inner lumen and that has a generally rectangular cross-sectional shape. This generally rectangular cross-sectional shape offers a larger amount of surface area through which bone graft material may be inserted and ejected from the hollow tubular member. Furthermore, this generally rectangular shape is more congruent with the size or shape of the annulotomy of most disc spaces, which frequently are accessed by a bone graft delivery device for delivery of bone graft. However, as one skilled in the art would appreciate, the tool cross-section need not be limited to a generally rectangular shape. For example, cross-sections of an oval shape or those with at least one defined angle to include obtuse, acute, and right angles can provide a shape in some situations that is more congruent with the size or shape of the annulotomy of a particular disc space. A substantially round shape may also be employed that provides the surgeon with an indication of directional orientation.

[0045] The phrase “removably attached” and/or “detachable” is used herein to indicate an attachment of any sort that is readily releasable.

[0046] The phrase “integrated fusion cage”, “spinal fusion implant”, “biological implant” and/or “fusion cage” is used here to indicate a biological implant.

[0047] According to various embodiments of the present disclosure, it is another aspect that the hollow tubular member further comprise at least one opening on a lateral face or surface of the hollow tubular member, at one distal end, for ejecting bone graft material into a bone graft receiving area, such as a disc space, such that the bone graft material is ejected from the hollow tubular member through an additional implant, such as a structural cage implant. In addition, the graft material is dispersed into the area of the debrided disc space surrounding and within the cage. Furthermore, the structural cage implant is removably attached to the hollow tubular member so as to be deposited into the surgical area. Thus, the device may be used in an integrated and near-simultaneous method for depositing bone graft material into a debrided disc space through a structural cage implant and leaving the structural implant.

[0048] According to various embodiments of the present disclosure, one aspect of the invention is to provide an integrated fusion cage detachable component of the integrated fusion cage and graft delivery device that comprises a biological implant that fits over the distal end of the substantial hollow tube, and which has a shape that is substantially congruent with the distal end of the hollow tube. However, the shape and configuration of the integrated fusion cage need not be limited to a generally rectangular shape. For example, cross-sections of an oval shape or those with at least one defined angle to include obtuse, acute, and right angles can provide a shape in some situations that is more congruent with the size or shape of the annulotomy of a particular disc space. A substantially round shape may also be employed that provides the surgeon with an indication of directional orientation.

[0049] In a preferred embodiment, the fusion cage has a tapered tip, and several open channels along the medial surfaces. In a preferred embodiment, the fusion cage and/or the bone graft delivery portion of the integrated fusion cage and graft delivery device is of oblong or rectangular, or square shape. The integrated fusion cage and graft delivery device is designed to avoid blocking or impacting bone graft material into a surgical disc space, thereby limiting the bone graft material that may be delivered, and not allowing available fusion space to be fully exploited for fusion.

[0050] In a preferred embodiment, the fusion cage has a keel-shaped tip to separate disk and prevent annular penetration. Also, the fusion cage has dual portals for bone graft discharge. In one embodiment, the medial openings are larger than the lateral openings. In another embodiment, the medial openings and the lateral openings are of the same size. In another embodiment, the medial and the lateral openings are symmetrical. In another embodiment, the medial openings are smaller than the lateral openings.

[0051] Further, the fusion cage may be designed in variable heights and lengths so that it fits snugly into the prepared disk space.

[0052] In a preferred embodiment that is ideal for anterior lumbar interbody fusion, the fusion cage has two portals for bone graft discharge positioned on opposite sides of the fusion cage. In a preferred embodiment that is ideal for direct lateral interbody fusion, the fusion cage has six portals for bone graft discharge, with three portals on one side of the fusion cage and three portals on an opposite side of the fusion cage. And, in a preferred embodiment that is ideal for post-vertebrectomy use, two opposing wall portions of the fusion cage are substantially porous to bone graft slurry,

while the substantial remainder of the wall of the fusion cage is substantially impervious to bone graft slurry.

[0053] In another embodiment of the device, the hollow tube engages with the fusion cage via a break-off collar and the plunger inserts into the interior of the hollow tube. The break-off collar may be severed by any of several means, to include application of torsion and/or rotational force and/or lateral force to the break-off collar, for example by twisting on the hollow tube and/or the plunger. The break-off collar may be formed by any of several means, comprising a thinner and/or reduced cross-sectional, that is thickness, a pre-set fracture-line, one or more notches, a frangible portion defined by a discrete, extended area that is weaker in one or more respects as compared to surrounding and/or adjacent material, and any means known to those skilled in the art to achieve reliable break-off. Preferably a clean break is achieved such that no surgically significant issues arise so such severance of the cage-portion and the hollow for the portion. In other embodiments, other ways devices and features can be employed to achieve separation of or first delivery tube structure and a second structure intended to remain in a patient. For example, electric and/or magnetic disconnecting mechanisms can be used in lieu of a physical breaking/severing of two discrete portions that define the above-referenced first and second structures. A smooth edge preferably remains after such severance of the cage. Moreover, it will be understood as being within the scope of the present invention to use more conventional coupling/decoupling mechanisms to achieve desired separation of the first and second structures, e.g. bayonette mounted features, tongue and groove, male/female interlocking structures, clamping devices, nested arrangements, etc., all of which find support in the various cited references incorporated herein by reference. In one example method of use, the connected hollow tube and fusion cage is inserted into the surgical area, bone graft material is inserted into the hollow tube (or already provided as a pre-packaged material), the plunger is pushed into the hollow tube, so as to deliver bone graft material to the site, then the plunger is reversed or pulled-out so to retreat from the site and move higher or beyond the break-off collar, and then the break-off collar is broken so as to disengage the fusion cage from the hollow tube and therein leave the fusion cage at the surgical site. In another embodiment of the device, the hollow tube engages with a connector conduit which in turn connects with the fusion cage via a break-off collar. One or more connectors connect the hollow tube with the connector conduit. The hollow tube fits over the connector conduit. The one or more connectors fit through the hollow tube and the connector conduit. Alternately, the hollow tube may fit over the connector conduit via a press-fit, aka interference fit, without need of one or more connectors. In one embodiment, the connectors comprise set screws, pins and tabs. The connector conduit allows, for example, various fusion cages designs to be fitted to a common hollow tube/plunger combination. This allows, for example, the common hollow tube/plunger combination to be re-sterilized and thus reused in multiple surgical procedures. In one embodiment, the hollow tube/plunger combination is re-usable and the fusion cage is disposable.

[0054] In one embodiment of the connector conduit, the connector conduit is of circular cross-section. In another embodiment, the connector conduit is of conical shape, or

any shape that allows a transition in diameter between the fusion cage and the hollow tube.

[0055] In one example method of use, the hollow tube is inserted over the connection conduit (which is attached to the fusion cage), then inserted into the surgical area, bone graft material is inserted into the hollow tube (or already provided as a pre-packaged material), the plunger is pushed into the hollow tube (and past the connection conduit), so as to deliver bone graft material to the site, then the plunger is reversed or pulled-out so to retreat from the site and move higher or beyond the break-off collar, and then the break-off collar is broken so as to disengage the fusion cage from the hollow tube (which is still connected to the connection conduit) and therein leave the fusion cage at the surgical site.

[0056] The break-off collar may be severed by any of several means, to include application of torsion and/or rotational force and/or lateral force to break-off collar, for example by twisting on the hollow tube and/or the plunger.

[0057] In one embodiment of the fusion cage, the fusion cage is of rectangular cross-section, such that one pair of opposite sides, for example a height first pair of sides, has a dimension of approximately 8-14 mm, and a second pair of opposite sides, for example a length dimension, of approximately 22-36 mm. One skilled in the art will appreciate that the exact dimensions of the fusion cage may be adapted to conform to particulars of the surgical site, for example, the relative sizing between the particular vertebrae in which bone graft material and/or a fusion cage is to be inserted. In other embodiments of the fusion cage, the fusion cage is of a substantially cylindrical shape. For example, a preferred embodiment of a fusion cage for use in an ALIF procedure forms a substantially cylindrical shape, with a height of approximately 8-14 mm and a diameter of less than about 36 millimeters. As another example, a preferred embodiment of a fusion cage for use in conjunction with a vertebrectomy has a substantially cylindrical shape with a height equal to or greater than the height of the vertebra (or the collective height of the vertebrae) it is intended to replace and a diameter of less than about 36 millimeters. Preferably, the separation "zone" between the cage and the hollow filling tube is at one end of the cage, preferably the end of the cage (when implanted) closer to the incision site.

[0058] A preferred method of using the integrated fusion cage and graft delivery device comprises precisely inserting the integrated fusion cage and graft delivery device, in one or more of the embodiments contained herein, into the surgical area. The integrated fusion cage and graft delivery device is then filled with bone graft material in its one or more substantially hollow tubes, the one or more plungers are inserted into the one or more hollow tubes, and the one or more plunger are pushed into the one or more hollow tubes, guided precisely as enabled by the minimal profile of the device, therein controllably depositing the bone graft material into the surgical area through and into the surgical implant cage. The surgical implant device may then be selectively detached from the integrated fusion cage and graft delivery device so as to remain at the surgical site.

[0059] Another method of using the integrated fusion cage and graft delivery device comprises inserting the integrated fusion cage and graft delivery device into a prepared disk space, such that the fusion cage portion fits snugly into the prepared disk space (the fusion cage is designed in variable heights and lengths so as to fit snugly into the prepared disk space), pushing the plunger through the hollow shaft so as

to push biological fusion material (e.g. bone graft) through the hollow shaft to flow the biological material through the fusion cage's open lateral and/or medial portals in communication with the hollow tube and plunger, thereby delivering biological material into the prepared disk space, after which the fusion cage is detached from the hollow tube and left in the disk space. Thus, the fusion cage is left in the disk space with a maximum and/or optimal amount of biological material near-simultaneously delivered within the fusion cage and/or surrounding the fusion cage in the disk space.

[0060] Using the integrated fusion cage and graft delivery device as described overcomes a problem associated with the traditional separate application of bone graft material and insertion of a fusion cage. Specifically, in the traditional method, the volume of disk space which does not contain bone graft material is limited, which, for example, limits the effectiveness of the surgical procedure. For example, using the traditional two-step procedure, bone graft may be inserted into, for example, a cylindrically-shaped area of radius r to a height h of 8 mm, and then a cylindrically-shaped fusion cage inserted of height h of 14 mm. Thus, the surgical area is left without a complete volume of bone graft material, i.e. because the volume of a cylinder is $\text{Volume} = \pi r^2 h$, the bone graft area is left without $\pi r^2 (14 \text{ mm} - 8 \text{ mm})$, or $6\pi r^2$ of bone graft material. (Note that this represents a 75% increase in bone graft material delivered to the surgical site for these example dimensions). This effectively dilutes the bone graft material and reduces its effectiveness. The present invention can substantially or completely fill the available disk space with bone graft material, because distraction of the disk space is performed substantially simultaneously with application of the fusion cage. Because more biological material is delivered to the prepared disk space, the fusion rate should increase. Also, by directly implanting fusion material, e.g. bone graft material, though a fusion cage positioned for detachment (and then detached) as a single step, time is saved and there is less manipulation of the sensitive nerve tissue at the fusion site (which increases safety).

[0061] Furthermore, the integrated fusion cage and graft delivery device may be used without the surgical implant delivery device portion such that the method comprises precisely inserting the integrated fusion cage and graft delivery device, in one or more of the embodiments contained herein, into the surgical area that may already contain one or more additional implants, such as a structural cage implant. The integrated fusion cage and graft delivery device is then filled with bone graft material in its one or more substantially hollow tubes, the one or more plungers are inserted into the one or more hollow tubes, and the one or more plunger are pushed into the one or more hollow tubes, guided precisely as enabled by the minimal profile of the device, therein controllably depositing the bone graft material into the surgical area without depositing bone graft material into the path of any structural cage implant or other implant that may already be present.

[0062] According to a still further aspect of the present invention, the integrated fusion cage may be introduced into a spinal target site without the use of the graft delivery device that is through use of any of a variety of suitable surgical instruments having the capability to engage the implant. The integrated fusion cage is capable of being used in minimally invasive surgical procedures, needing only a relatively small operative corridor for insertion. The inte-

grated fusion cage may also be used in open procedures. According to a still further aspect of the present invention, the integrated fusion cage of the present invention may be used in a variety of configurations in a fusion procedure, including but not limited to (and by way of example only) unilateral, paired unilateral and bilateral.

[0063] Furthermore, the integrated fusion cage and graft delivery device and method of use is applicable to position and deliver fusion cages from the side, directly anterior or in the anterior fusion cages of the cervical spine.

[0064] In a preferred embodiment, the integrated fusion cage and graft delivery device comprises a hollow tube or contains at least one inner lumen constructed to receive bone graft, and a plunger adapted for insertion at least partially within the hollow tube and preferably through the full extent of the hollow tube. The plunger of some embodiments is generally of the same geometric configuration as the hollow interior portion of the hollow tube so that the plunger, once fully inserted in to the hollow tube, is substantially congruent with the hollow interior portion of the hollow tube, e.g. both the plunger and the hollow tube are substantially the same shape and/or class. The plunger preferably extends about the same length as the hollow tube, and further comprises an end portion, e.g. at least one knob or handle for grasping and manipulation by a user, or in robotic or automated or semi-automated control or surgeries, by a machine.

[0065] Also according to a preferred embodiment, the hollow interior portion of the hollow tube further comprises a sloped or curved surface at a second end (e.g. positioned near a place for deposit of bone graft material) adjacent and opposite a lateral window or opening in a lateral face of the hollow tube. As the interior of the hollow tube comprises a sloped or curved surface at its second end, the plunger also comprises a sloped or curved surface at a second end of the plunger. The plunger terminates opposite the curved surface at its second end with a laterally faced surface, which corresponds to the lateral window or opening at the second end of the hollow tube. The distal end of the hollow tube is fitted with a substantially conformal fusion cage that covers the exterior surface of the hollow tube, fitted with one or more openings that align with one or more openings of the hollow tube. Thus, in cooperation, the plunger may be inserted into the opening of the hollow tube, and extended the entire length of the hollow tube, at least to a point where the laterally faced surface of plunger is in communication with the lateral window or opening at the second end of the hollow tube. This configuration permits a user to eject substantially all of the bone graft material that is placed into the hollow tube in a lateral direction at the bone graft receiving area, through the substantially conformal and detachable fusion cage that covers the exterior surface of the hollow tube, optionally detach the detachable fusion cage, during a surgical procedure.

[0066] In a preferred embodiment, the integrated fusion cage and graft delivery device comprises an integrated fusion cage that comprises a first proximal end and a second distal end, wherein the first proximal end contains an opening adapted to allow fitting and/or engagement to the distal end of the hollow tube. This fitting and/or engagement may be over the external surface of the hollow tube or inside the interior of the hollow tube. Further, the integrated fusion cage may comprise one or more medial openings and one or more lateral openings that align with one or more openings

at the distal end of the hollow tube. Further, the integrated fusion cage may contain surfaces, such as belts or striations, along one or more medial surfaces of the integrated fusion cage. The integrated fusion cage is configured such that when a plunger, once fully inserted in to the hollow tube, is substantially congruent with the hollow interior portion of the hollow tube, e.g. both the plunger and the hollow tube are substantially the same shape and/or class and bone graft material is delivered through the integrated fusion cage into the surgical area.

[0067] In one embodiment, a substantially hollow implant is detachably interconnected to a distal end of the hollow tube, the implant having a proximal end and a tapered distal end, the tapered distal end having an exterior tapered surface and a tapered interior surface, and the plunger adapted for inserting into the proximal end of the hollow tube, the plunger having a tapered distal end being contoured to the tapered interior surface of the distal end of the implant to form a conforming fit between the tapered distal end of the plunger and the tapered interior surface of the distal end of the implant when the plunger is fully inserted into the implant such that bone graft material within the hollow tube is delivered to a graft receiving area through at least one opening of the implant. Further, the distal end of the implant may comprise a closed distal tip, and the tapered distal end of the plunger may be wedge-shaped and the tapered interior surface of the closed distal tip of the distal end of the implant may be wedge-shaped.

[0068] The spinal fusion implant of the present invention may be used to provide temporary or permanent fixation along an orthopedic target site.

[0069] The spinal fusion implant of the present invention may be provided with any number of additional features for promoting fusion, such as one or more apertures extending between the top and bottom surfaces which allow a boney bridge to form through the spinal fusion implant.

[0070] The spinal fusion implant may also be provided with any number of suitable anti-migration features to prevent the implant from migrating or moving from the disc space after implantation. Suitable anti-migration features may include, but are not necessarily limited to, angled teeth or ridges formed along the top and bottom surfaces of the implant and/or rod elements disposed within the distal and/or proximal ends.

[0071] According to a further aspect of the present invention, the spinal fusion implant may be provided with one or more radiographic markers at the proximal and/or distal ends. These markers allow for a more detailed visualization of the implant after insertion (through radiography) and allow for a more accurate and effective placement of the implant.

[0072] According to a still further aspect of the present invention, the distal end of the spinal fusion implant may have a conical (bullet-shaped) shape including a pair of first tapered (angled) surfaces and a pair of second tapered (angled) surfaces. The first tapered surfaces extend between the lateral surfaces and the distal end of the implant, and function to distract the vertebrae adjacent to the target intervertebral space during insertion of the spinal fusion implant. The second tapered surfaces extend between the top and bottom surfaces and the distal end of the spinal fusion implant, and function to maximize contact with the anterior portion of the cortical ring of each adjacent vertebral body. Furthermore, the second tapered surfaces provide for a better

fit with the contour of the vertebral body endplates, allowing for a more anterior positioning of the spinal fusion implant and thus advantageous utilization of the cortical rings of the vertebral bodies.

[0073] Another embodiment for the integrated fusion cage and graft delivery device comprises a detachable fusion cage that is detachable, or removably attached, by any of several means. As disclosed above, in one embodiment, the fusion cage is substantially conformal with the distal end of the hollow tube in that it covers the exterior surface of the hollow tube, wherein the fusion cage is configured with one or more openings that align with one or more openings of the hollow tube. In one preferred embodiment, the fusion cage of the integrated fusion cage and graft delivery device forms an interference fit with the fusion cage, such that when the integrated fusion cage and graft delivery device is inserted into the surgical area, the integrated fusion cage and graft delivery device presses against bone and/or vertebrates such that when an axial force is applied to the integrated fusion cage and graft delivery device in a rearward direction (toward the proximal end of the integrated fusion cage and graft delivery device), the fusion cage detaches from the integrated fusion cage and graft delivery device and thereby remains in the surgical area.

[0074] In another embodiment for the integrated fusion cage and graft delivery device and its method of use, the fusion cage is substantially filled with bone graft material after the fusion cage is implanted. In another embodiment for the integrated fusion cage and graft delivery device and its method of use, the fusion cage is substantially filled with bone graft material simultaneously with the implantation of the fusion cage.

[0075] In another embodiment for the integrated fusion cage and graft delivery device and its method of use, the fusion cage and/or the bone graft material associated with the fusion cage may be accessed during subsequent surgical operations.

[0076] In another embodiment for the integrated fusion cage and graft delivery device and its method of use, the fusion cage is a separate device, for example a pre-packaged implant device, which may be installed independently from the integrated fusion cage and graft delivery device or installed in coordination with the integrated fusion cage and graft delivery device. In either situation, the device may be used to provide bone graft material in and/or around the pre-packaged implant.

[0077] In another embodiment for the integrated fusion cage and graft delivery device and its method of use, some or all of the bone graft material is provided as a component of a per-packaged implant. In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by way of a indent-tab that penetrates the interior of the hollow tube, such, when the plunger is substantially inserted into the hollow tube, the indent-tab is pushed out from the interior of the hollow tube so as to no longer be attached to the integrated fusion cage and graft delivery device, thereby remaining in the surgical area.

[0078] In another embodiment, the hollow tube is of cylindrical shape and includes one or more locking tabs or indent tabs configured to engage one or more locking slots of the fusion cage. The locking tabs may permanently or not permanently engage the locking slots, and may be of a shape to include rectangular, circular and oblong. In one embodi-

ment of the locking tabs and locking slots, the locking tabs and locking slots engage one another by rotating the hollow tube clockwise and are released by counterclockwise rotation. In another embodiment of the configuration of the locking tabs and locking slots, the locking tabs and locking slots engage one another by rotating the hollow tube counterclockwise and are released by clockwise rotation.

[0079] In another embodiment, the fusion cage has internal ramps which assist in directing the bone graft material to one or more openings in the fusion cage.

[0080] In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by way of receipt of an electrical, mechanical, pneumatic, hydraulic or other communication imparted by the user upon the plunger and/or hollow tube so as to detach the fusion cage and thereby deposit the fusion cage into the surgical area.

[0081] In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by way of a Luer taper or Luer fitting connection, such as in a Luer-Lok® or Luer-Slip® configuration or any other Luer taper or Luer fitting connection configuration. For purposes of illustration, and without wishing to be held to any one embodiment, the following U.S. Patent Application is incorporated herein by reference in order to provide an illustrative and enabling disclosure and general description of means to selectably detach the fusion cage of the integrated fusion cage and graft delivery device: U.S. Patent Appl. No. 2009/0124980 to Chen.

[0082] In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by way of a pedicle dart by threadable rotation to achieve attachment, detachment, and axial movement. Other ways include a quick key insertion, an external snap detent, or magnetic attraction or any other structure. For purposes of illustration, and without wishing to be held to any one embodiment, the following U.S. Patent Application is incorporated herein by reference in order to provide an illustrative and enabling disclosure and general description of means to selectably detach the fusion cage of the integrated fusion cage and graft delivery device: U.S. Patent Appl. No. 2009/0187194 to Hamada.

[0083] In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by use of magnetism. More specifically, the detachable fusion cage can be made to feature a magnetic field pattern and a resulting force R that are adjustable and may be of different character than the rest of the integrated fusion cage and graft delivery device. With permanent magnets, such adjustments can be made mechanically by orienting various permanent magnet polar geometries and corresponding shapes relative to one another. U.S. Pat. No. 5,595,563 to Moisdon describes further background regarding such adjustment techniques, which is hereby incorporated by reference in its entirety. Alternatively or additionally, electromagnets could be used in combination with permanent magnets to provide adjustability. In further embodiments, the magnets and corresponding fields and the resultant magnetic field pattern can include both attraction forces from placement of opposite pole types in proximity to one another and repulsion forces from placement of like pole types in proximity to one another. As used herein, “repulsive magnetic force” or “repulsive force” refers to a force resulting from the placement of like magnetic poles in proximity

to one another either with or without attractive forces also being present due to opposite magnetic poles being placed in proximity to one another, and further refers to any one of such forces when multiple instances are present. U.S. Pat. No. 6,387,096 is cited as a source of additional information concerning repulsive forces that are provided together with attractive magnetic forces, which is hereby incorporated by reference. In another alternative embodiment example, one or more of surfaces of the fusion cage are roughened or otherwise include bone-engaging structures to secure purchase with vertebral surfaces. In yet other embodiments, the selectable detachable feature between the detachable fusion cage and the integrated fusion cage and graft delivery device can include one or more tethers, cables, braids, wires, cords, bands, filaments, fibers, and/or sheets; a nonfabric tube comprised of an organic polymer, metal, and/or composite; an accordion or bellows tube type that may or may not include a fabric, filamentous, fibrous, and/or woven structure; a combination of these, or such different arrangement as would occur to one skilled in the art. Alternatively or additionally, the selectable detachable feature between the detachable fusion cage and the integrated fusion cage and graft delivery device can be arranged to present one or more openings between members or portions, where such openings extend between end portions of the fusion cage. For purposes of illustration, and without wishing to be held to any one embodiment, the following U.S. Patent Application is incorporated herein by reference in order to provide an illustrative and enabling disclosure and general description of means to selectably detach the fusion cage of the integrated fusion cage and graft delivery device: U.S. Patent Appl. No. 2011/0015748 to Molz et al.

[0084] In another embodiment for the integrated fusion cage and graft delivery device, the detachable fusion cage is detachable by use of plasma treatment. The term “plasma” in this context is an ionized gas containing excited species such as ions, radicals, electrons and photons. (Lunk and Schmid, *Contrib. Plasma Phys.*, 28: 275 (1998)). The term “plasma treatment” refers to a protocol in which a surface is modified using a plasma generated from process gases including, but not limited to, O_2 , He, N_2 , Ar and N_2O . To excite the plasma, energy is applied to the system through electrodes. This power may be alternating current (AC), direct current (DC), radiofrequency (RF), or microwave frequency (MW). The plasma may be generated in a vacuum or at atmospheric pressure. The plasma can also be used to deposit polymeric, ceramic or metallic thin films onto surfaces (Ratner, *Ultrathin Films (by Plasma deposition)*, 11 *Polymeric Materials Encyclopedia* 8444-8451, (1996)). Plasma treatment is an effective method to uniformly alter the surface properties of substrates having different or unique size, shape and geometry including but not limited to bone and bone composite materials. Plasma Treatment may be employed to effect magnetic properties on elements of the integrated fusion cage and graft delivery device, or to provide selectable detachment of the fusion cage. For purposes of illustration, and without wishing to be held to any one embodiment, the following U.S. Patent Application is incorporated herein by reference in order to provide an illustrative and enabling disclosure and general description of means to selectably detach the fusion cage of the integrated fusion cage and graft delivery device: U.S. Pat. No. 7,749,555 to Zanella et al.

[0085] One having skill in the art will appreciate that the fusion cage may be selectively detachable to the integrated fusion cage and graft delivery device, for example, by means that mechanically grasp the head, means that attach by vacuum, and means that attach by friction, or other means known to those of skill in the art for attaching the head of an apparatus to the shaft of an apparatus.

[0086] It is another aspect of the present disclosure that the distal end of the integrated fusion cage and graft delivery device be equipped with various other tools to aid in the procedure. Such tools may include, for example, devices used to assess the condition of the implantation site and surrounding tissue. This may include, for example, a device that transmits or provides an image or signal which carries an image for visual inspection and photography. Such an image capture device may include, for example, a device to illuminate the implant site coupled with an image capture and/or transmission device. Another tool may also include, for example, a device that aids in irrigation or drainage of the surgical site, a tool used to sample or biopsy tissue.

[0087] Another embodiment for the integrated fusion cage and graft delivery device comprises a hollow tube constructed to receive bone graft, where the hollow tube has a proximal and distal end, a plunger adapted for insertion at least partially within the hollow tube at the proximal end of the hollow tube, whereby the plunger is constructed and arranged with respect to the hollow tube so as to prevent rotation of the plunger during insertion into said hollow tube, whereby the plunger has a distal end that is contoured to an interior surface of the distal end of the hollow tube such that the contoured distal end of the plunger is nearly congruent with the interior surface of the distal end of the hollow tube for removing substantially all of the bone graft received by the hollow tube and whereby the bone graft is delivered to the graft receiving area. Still another embodiment provides a rifling structure in the hollow tube interior that facilitates rotational movement of the plunger along a lengthwise axis of the hollow tube, therein delivering a substantially steady pressure and/or rate of delivery of the bone graft material as the plunger descends the hollow tube when the plunger is forced through the hollow tube. The rifling or screw-like movement may also translate to a predetermined delivery of material per full rotation, e.g. each 360 degree rotation of the plunger equates to 5 cc of bone graft material delivered to the bone graft site.

[0088] Another aspect of the present invention includes providing a hollow tube and plunger assembly, in which the hollow tube and/or the plunger assembly are disposable. The tube may also be at least portions of biocompatible material which can stay in the canal without impairing the final implantation. Alternatively, it may thus be a material that is resorbable, such as a resorbable polymer, in the canal after implantation, so as not to interfere with the growth of the bone or stability of the implant.

[0089] A further embodiment of the invention provides pre-packaged inserts for loading into the hollow tube element, or if there are a plurality of hollow tube elements, into one or more of the hollow tube elements. The pre-packaged inserts may be of varying lengths, and/or layered of differing materials or components, to include the patient's own bone graft matter.

[0090] Another embodiment of the present invention provides an integrated fusion cage and graft delivery system, by which a hollow tube and/or a hollow tube/plunger assembly

can be prepared prior to opening a patient, thus minimizing the overall impact of the grafting aspect of a surgical implantation or other procedure. Moreover, the hollow tube may be made to be stored with bone graft in it for a period of time, whether the tube is made of plastic, metal or any other material. Depending upon the surgical application, it may be desirable to only partially fill the tube for storage, so that a plunger can be at least partially inserted at the time of a surgery.

[0091] A further embodiment of the present invention provides a bone graft insertion apparatus comprising a hollow tube constructed to receive bone graft, the hollow tube having a proximal and distal end whereby the hollow tube contains least one opening on a surface of the distal end of the hollow tube. The at least one opening is preferably positioned other than completely along the axial or longitudinal axis of the device. The number and size and shape of such openings can vary but are preferably adapted to deliver bone graft material in a direction substantially transverse to the axial extent of the substantially hollow tube. In one embodiment, two or more apertures are provided. In certain embodiments, apertures are on the same side of the hollow tube, where in others, apertures are on different sides (e.g. opposing sides) of a hollow tube. A plunger, adapted for insertion at least partially within the hollow tube, is constructed and arranged with respect to the hollow tube so as to present at least one substantially flat contour, whereby the plunger has a distal end that is contoured to an interior surface of the distal end of the hollow tube such that the contoured distal end of the plunger is nearly congruent with the interior surface of the distal end of the hollow tube. This facilitates removing substantially all of the bone graft received by the hollow tube whereby the bone graft is delivered to the graft receiving area. It is important to remove substantially all of the bone graft material as it is expensive and/or difficult to obtain.

[0092] In another embodiment of the present disclosure the distal end of the plunger is flexible to allow, for example, the user to maneuver the distal end and thereby any bone graft material in the hollow tube to the implantation site. One skilled in the art will appreciate that the flexible aspect of certain embodiments can be both passive and active in nature. Active flexibility and manipulation in the distal end of the plunger may incorporate, for example, the manipulative capabilities of an endoscope, including components for manipulation such as guidewires along the longitudinal axis of the shaft of the plunger.

[0093] In another embodiment of the invention, the distal end and the proximal end of the hollow tube are in communication via a conduit to enable electrical, hydraulic, pneumatic, or mechanical transmission, the latter such as a wire. Such hydraulic communication allows, for example, a medical or other liquid to be delivered or extracted from the surgical area. Such mechanical communication allows, for example, the distal end to be maneuvered precisely.

[0094] In another embodiment of the present disclosure, the hollow tube and/or plunger may be curved and/or may have an angular aspect, in addition to the sloped or curved surface at a second end of the hollow tube/plunger. This shape may, for example, aid the surgeon in more comfortably introducing the delivery device to the implant site, be shaped to better accommodate implantation sites on right or left sides of the body, or be shaped to better accommodate right or left-handed surgeons. One having skill in the art will

appreciate that the delivery device may have multiple angles and curved aspects which enable aspects of embodiments of the present disclosure or aid in ergonomics.

[0095] In one embodiment of the present disclosure, the device further comprises a footing or shelf at the distal end of the tubular device that is nearest the operating site for preventing or mitigating risk of injury to the patient during surgery. According to this embodiment, the footing may be flexible, semi-flexible, semi-rigid or rigid. The footing serves to protect the anatomy of the patient from being penetrated by the hollow tube of the integrated fusion cage and graft delivery device when the plunger is being inserted or during tamping of the hollow tube or the plunger by the surgeon, which may occur during the surgical procedure for a variety of reasons. In certain embodiments, the distal tip region of the hollow tube comprises a softer, malleable and/or less rigid material than the remainder of the hollow tube. For example, the distal tip could be made of a bioactive collagen.

[0096] It is yet another aspect of the present disclosure to provide an integrated fusion cage and graft delivery device that contains one or more detachable elements for use in an operation where bone graft material must be inserted into the integrated fusion cage and graft delivery device and ejected to a bone graft receiving area. According to various embodiments, these detachable devices may include a detachable funnel for gathering and inserting bone graft material at a graspable end of the integrated fusion cage and graft delivery device. The present disclosure may also comprise a plunger that has a detachable handle, which may be selectively removed to avoid blocking the surgeon's view of the operating site. The integrated fusion cage and graft delivery device may further comprise a detachable footing or shelf at one distal end of the hollow tubular member. In one embodiment this footing or shelf is selectively positionable about various points along the hollow tube. For example, a distal portion of the hollow tube has a rotatable portion that can be positioned to deliver bone graft material to areas of a disc space in a manner such that a surgeon has angular directional control as to where bone graft material is directed. Other detachable elements are also contemplated with the present invention, such as a funnel at the proximal end of the hollow tube, or exterior or interior guide wires attached to the hollow tube, or a camera which is positioned near the delivery site of the bone graft material.

[0097] In another embodiment of the invention, the device is configured such that the upper or first end of the device (that is, the end in which the plunger is inserted) is not substantially in-line with the second end of the device (that is, the end from which bone graft material is emitted and/or a fusion cage is attached). For example, the body of the hollow tube may be configured with an angle or kink along its length, appearing to be rotated along its length. In this embodiment, the plunger element is flexible and/or conformable so as to flex inside of the tube portion and otherwise traverse through the tube portion. This embodiment of the device is useful, for example, when the user requires entry to the disc space at other than a right angle. Further, the angle or kink along the length of the device may be configured is capable of selectively locking (e.g., by a pin) the upper device portion into a particular position, e.g. so that a desired angle is created between the upper device portion and the remaining portion of the device. The means for communication itself can be locked to alternatively achieve this objective. In one embodiment, when the rotat-

ing member is in an unlocked mode, the member is free to rotate in at least one plane. The selective locking mechanism can be remotely accessed by a user of the tool at the upper end of the handle by, for example, an external shaft that communicates with the locking mechanism of the rotating member on the distal end of the body. Yet another aspect of the present disclosure is that the device can be variably angled to allow for a variety of insertion angles. A ratcheting adapter can be fitted to allow for this application.

[0098] The present invention can be used in veterinary conditions, in the thoracic spine or can be used for insertion of a laterally based disk replacement.

[0099] Thus, according to various embodiments of the present disclosure, a method of introducing bone graft material to a desired operating site ("bone graft receiving area") is provided by use of a hollow tubular member comprising a generally rectangular cross-sectional area, whereby the desired operating area is capable of receiving at least one plunger. The one or more plunger having at least one distal end which is designed to accommodate ejecting bone graft or other material to be inserted into the joint space or between intervertebral members in a generally lateral direction, as opposed to a generally longitudinal direction (in relation to the direction of the primary axis of the device).

[0100] One skilled in the art will appreciate that the distal end of the tubular device need not be limited to those specific embodiments described above. Other forms, shapes or designs that enable the foregoing aspects of the present invention are hereby incorporated into this disclosure. Forms, shapes and designs that relate to the provision of an end of a tubular device to perform lateral introduction of bone or bone substitute to an operating site are considered to be within the scope of the present disclosure.

[0101] One aspect of the present invention provides an integrated fusion cage and graft delivery device system for delivering bone graft, in a partially formed, fully formed or unformed condition to a bone graft receiving area in a body.

[0102] In yet another embodiment the hollow tube of the integrated fusion cage and graft delivery device may further comprise a funnel on the graspable end of the hollow tube, which may be selectively positioned about the graspable end of the hollow tube, for facilitating insertion of new or additional bone graft into the hollow tube. The funnel may take on a variety of shapes and sizes, depending on the nature of the bone graft material being inserted in the hollow tube.

[0103] One embodiment of the substantially hollow tube provides that the hollow tube is telescoping, thereby allowing its length to be adapted to the particular desires of the surgeon and/or the surgical area. In this embodiment, the plunger may also be telescoping to substantially conform to the configuration and/or size and/or shape of the substantially hollow tube.

[0104] In another embodiment, the size and/or shape of the one or more hollow tubes of the device are sized to fit, and/or not substantially obscure access to the aperture of, the cannula or cannulas that the device is fitted through for delivery of bone graft material to the operating site. In this embodiment, the device's one or more pair of hollow tubes and plungers do not substantially impair access to the operating site nor the surgeon's view of the operating site.

[0105] In one embodiment of the invention, a bone graft insertion apparatus comprises: a hollow tube constructed to receive bone graft, said hollow tube having an extended axis

and a proximal end and a distal end, said distal end having an interior surface; a plunger adapted for inserting into said proximal end of said hollow tube, said plunger having a distal end being contoured to said interior surface of said distal end of said hollow tube such that bone graft material within said hollow tube is delivered to a graft receiving area through at least one opening near the distal end of said hollow tube; wherein said graft receiving area is configured to accommodate at least one substantially hollow implant.

[0106] In another embodiment of the invention, a bone graft insertion apparatus comprises: a hollow tube constructed to receive bone graft, said hollow tube having a proximal and distal end; whereby said hollow tube contains least one opening on a surface of said distal end of said hollow tube; whereby said opening on a surface of said distal end of said hollow tube is positioned other than completely along the axial or longitudinal axis of the device; a plunger adapted for insertion at least partially within said hollow tube at proximal end of said hollow tube; whereby said plunger is constructed and arranged with respect to said hollow tube so as to present at least one substantially flat contour; whereby said plunger has a distal end that is contoured to an interior surface of said distal end of said hollow tube such that said contoured distal end of said plunger is nearly congruent with said interior surface of said distal end of said hollow tube for removing substantially all of said bone graft received by said hollow tube; whereby said bone graft is delivered to a graft receiving area.

[0107] In another embodiment of the invention, a method of inserting bone graft comprises: preparing a surgical area to receive bone graft; inserting a tool into said surgical area, said tool consisting essentially of a hollow tube adapted to receive bone graft, a plunger adapted for insertion into said hollow tube, said plunger constructed to prevent rotation during insertion into said hollow tube, said plunger having a distal end contoured to the interior surface of the distal end of said hollow tube; providing bone graft material into the said hollow tube of said tool; inserting said plunger into the proximal end of said hollow tube; inserting said distal end of said hollow tube of said tool into surgical area; applying force to said plunger thereby advancing said plunger through said hollow tube wherein said bone graft is inserted into said surgical area.

[0108] In another embodiment of the invention, an integrated fusion cage and graft delivery device apparatus comprises: a hollow tube constructed to receive bone graft, the hollow tube having an extended axis and a proximal end and a distal end, the distal end having an interior surface; a plunger adapted for inserting into the proximal end of the hollow tube, the plunger having a distal end being contoured to the interior surface of the distal end of the hollow tube; a selectably detachable fusion cage, the selectably detachable fusion cage having at least one opening that substantially aligns with at least one opening near the distal end of the hollow tube, such that bone graft material within the hollow tube is delivered to a graft receiving area through at least one opening of the selectably detachable fusion cage; and the selectably detachable fusion cage having a means for detachment whereby the fusion cage is delivered to the graft receiving area.

[0109] In one embodiment, the device is not a caulking gun style device, that is the bone graft material and/or the fusion cage are not delivered and/or positioned using a hand-pump and/or hand-squeeze mechanism. Instead, the

device delivers graft material and/or a fusion cage using a hollow tube and plunger arrangement which is not a caulking gun style device and further, does not appreciably disrupt or block the user's view of the surgical site and/or enable precision delivery of bone graft material and/or a fusion cage to the surgical site. Indeed, the device is distinctly unlike the chalking gun device of U.S. Pat. Appl. No. 2004/0215201 to Lieberman ("Lieberman"), which requires an L-shaped base member handle, rack teeth to advance a plunger member, and user action on a lever of the L-shaped base member handle to deploy bone graft material. In one embodiment, the device of this application is not a caulking gun style device and does not comprise rack teeth, a base member handle and at least one component that obscures user viewing of the surgical site. Lieberman is incorporated by reference in its entirety for all purposes.

[0110] Similarly, in one embodiment, the device is distinctly unlike the chalking gun device of U.S. Pat. Appl. No. 2002/0049448 to Sand et al ("Sand"), which requires a gun and trigger mechanism in which the user squeezes together a gun-style handle to deploy material into bone. The Sand device obstructs the view of the user of the delivery site. In one embodiment, the device of this application is not a caulking gun style device and does not comprise an opposing-levered, gun-style delivery mechanism and at least one component that obscures user viewing of the surgical site. Sand is incorporated by reference in its entirety for all purposes.

[0111] In one embodiment, the device is configured to deliver bone graft material substantially laterally from its delivery end, that is substantially not in the axial direction but rather substantially from the side and/or in a radial direction. This is distinctly different than devices that deliver bone graft material along their vertical axis, that is, along or out their bottom end, and/or obstruct the user view of the bone graft and/or fusion cage delivery site, such as that of U.S. Pat. Appl. No. 2010/0087828 to Krueger et al ("Krueger"), U.S. Pat. Appl. No. 2009/0264892 to Beyar et al ("Beyar"), U.S. Pat. Appl. No. 2007/0185496 to Beckman et al ("Beckman"), U.S. Pat. Appl. No. 2009/0275995 to Truckai et al ("Truckai") and U.S. Pat. Appl. No. 2006/0264964 to Seifert et al ("Seifert"). Krueger, Beyar, Beckman, Truckai and Seifert are incorporated by reference in their entireties for all purposes.

[0112] In one embodiment, the device is configured to deliver bone graft material so as to completely fill the defined interior of its fusion cage and subsequently deliver bone graft material to the surrounding bone graft site, rather than, for example, to contain the bone material as are the fusion cage designs of U.S. Pat. No. 7,846,210 to Perez-Cruet ("Perez-Cruet"). Further, the fusion device of this application features a distal tip that functions to precisely position the fusion device and stabilize the device during delivery of bone graft material. Perez-Cruet is incorporated by reference in its entirety for all purposes.

[0113] In one embodiment, a bone graft insertion apparatus is disclosed, the bone graft insertion apparatus comprising: a hollow tube constructed to receive bone graft, said hollow tube having an extended axis and a proximal end and a distal end, said distal end having a substantially tapered distal tip interior surface and a distal end interior surface of rectangular cross-section; a plunger adapted for inserting into said proximal end of said hollow tube, said plunger having a distal end exterior surface of rectangular cross-

section contoured to said distal end interior surface of said hollow tube, said plunger having a substantially tapered distal tip contoured to said substantially tapered distal tip interior surface of said hollow tube to form a substantially congruent fit, wherein bone graft material within said hollow tube is delivered to a graft receiving area through one or more lateral openings near said distal end of said hollow tube, said one or more lateral openings substantially precluding the delivery of bone graft material directly along said axis of said hollow tube, said plunger precluded from rotating when inserted into said hollow tube.

[0114] In another embodiment, a bone graft insertion apparatus is disclosed, the bone graft insertion apparatus comprising: a hollow tube having a length, a proximal end and a distal end, said hollow tube having a rectangular cross-section, said distal end having a tapered tip interior surface and at least one opening; a plunger adapted for insertion within said hollow tube at said proximal end of said hollow tube, said plunger having a rectangular cross-section end portion and a distal tip contoured to conform to the distal end of said hollow tube, said plunger having a length sufficient such that when fully inserted into said hollow tube, said plunger distal end contacts at least one opening.

[0115] In another embodiment, a bone graft insertion apparatus is disclosed, the bone graft insertion apparatus comprising: a hollow tube constructed to receive bone graft having an extended axis, a length, a proximal end and a distal end, said hollow tube having a rectangular cross-section, said distal end having a tapered tip interior surface with a terminus and two oval-shaped openings having an upper and a lower end located on opposite lateral sides of said distal end, said tapered tip extending into said hollow tube and said terminus positioned adjacent to said oval-shaped openings; a plunger adapted for insertion within said hollow tube at said proximal end of said hollow tube, said plunger having a rectangular cross-section end portion and a distal lower surface, said plunger having a length sufficient such that when fully inserted into said hollow tube, said plunger distal lower surface contacts said hollow tube terminus at a position adjacent to said oval-shaped openings, said plunger rectangular cross-section end portion forming a continuous surface adjacent each of the oval-shaped openings from a position opposite said terminus to a point extending beyond said upper end of each oval-shaped opening; wherein bone graft material within said hollow tube is delivered to a graft receiving area through said oval-shaped openings of said hollow tube, said oval-shaped openings precluding the delivery of bone graft material directly along said axis of said hollow tube, said plunger precluded from rotating when inserted into said hollow tube; wherein said oval-shaped openings near the distal end of said hollow tube are positioned within a 25% length from said distal end relative to a total length of said hollow tube.

[0116] In one embodiment, a combination bone graft insertion and implant insertion apparatus is disclosed, the apparatus comprising: a hollow tube constructed to receive bone graft, said hollow tube having an extended axis and a proximal end and a distal end, said hollow tube having a rectangular interior cross-section from said proximal end to said distal end; a plunger adapted for inserting into said proximal end of said hollow tube along the extended axis, said plunger having a distal end exterior surface of rectangular cross-section contoured to said interior cross-section of said hollow tube, said plunger with a distal exterior tip,

said plunger distal end exterior surface of rectangular cross-section forming a substantially congruent fit with said hollow tube rectangular interior cross-section; and an expandable implant comprising a first plate, a second plate, a front block, a rear block and a screw, the expandable implant configured to move the first plate vertically from the second plate by rotation of the screw which rotates without moving transversely with respect to either the first or the second plate, said first plate and second plate moving in parallel upon rotation of the screw, the screw moving the front and the rear blocks so as to move the first and the second plate, the blocks defining an aperture on each lateral side of the expandable implant; wherein said hollow tube and said plunger are configured to deliver bone graft material to the expandable implant and to an adjacent surgical site through at least the apertures on each lateral side of the expandable implant.

[0117] In addition, by way of providing additional background and context, the following references are also incorporated by reference in their entireties for the purpose of explaining the nature of spinal fusion and devices and methods commonly associated therewith, to include, without limitation, expandable fusion cages: U.S. Pat. No. 4,863,476 to Shepperd; U.S. Pat. No. 6,743,255 to Ferree; U.S. Pat. No. 6,773,460 to Jackson; U.S. Pat. No. 6,835,206 to Jackson; U.S. Pat. No. 6,972,035 to Michelson; U.S. Pat. No. 7,771,473 to Thramann; U.S. Pat. No. 7,850,733 to Baynham; U.S. Pat. No. 8,506,635 to Palmatier; U.S. Pat. No. 8,556,979 to Glerum; U.S. Pat. No. 8,628,576 to Triplett; U.S. Pat. No. 8,709,086 to Glerum; U.S. Pat. No. 8,715,351 to Pinto; U.S. Pat. No. 8,753,347 to McCormack; U.S. Pat. No. 8,753,377 to McCormack; U.S. Design Patent No. D708,323 to Reyes; U.S. Pat. No. 8,771,360 to Jimenez; U.S. Pat. No. 8,778,025 to Ragab; U.S. Pat. No. 8,778,027 to Medina; U.S. Pat. No. 8,808,383 to Kwak; U.S. Pat. No. 8,814,940 to Curran; U.S. Pat. No. 8,821,396 to Miles; U.S. Patent Application Publication No. 2006/0142858 to Collieran; U.S. Patent Application Publication No. 2008/0086142 to Kohm; U.S. Patent Application Publication No. 20100286779 to Thibodean; U.S. Patent Application Publication No. 20110301712 to Palmatier; U.S. Patent Application Publication No. 20120022603 to Kirschman; U.S. Patent Application Publication No. 20120035729 to Glerum; U.S. Patent Application Publication No. 20120089185 to Gabelberger; U.S. Patent Application Publication No. 20120123546 to Medina; U.S. Patent Application Publication No. 20120197311 to Kirschman; U.S. Patent Application Publication No. 20120215316 to Mohr; U.S. Patent Application Publication No. 20130158664 to Palmatier; U.S. Patent Application Publication No. 20130178940; U.S. Patent Application Publication No. 20140012383 to Triplett; U.S. Patent Application Publication No. 20140156006; U.S. Patent Application Publication No. 20140172103 to O'Neil; U.S. Patent Application Publication No. 20140172106 to To; U.S. Patent Application Publication No. 20140207239 to Barreiro; U.S. Patent Application Publication No. 20140228955 to Weiman; U.S. Patent Application Publication No. 20140236296 to Wagner; U.S. Patent Application Publication No. 20140236297 to Iott; U.S. Patent Application Publication No. 20140236298 to Pinto.

[0118] Furthermore, by way of providing additional background and context, the following references are also incorporated by reference in their entireties for the purpose of explaining the nature of spinal fusion and devices and

methods commonly associated therewith, to include, without limitation, expandable fusion cages: U.S. Pat. No. 7,803, 159 to Perez-Cruet et al.; U.S. Pat. No. 8,852,282 to Farley et al.; U.S. Pat. No. 8,858,598 to Seifert et al.; U.S. Pat. No. D714,933 to Kawamura; U.S. Pat. No. 8,795,366 to Varela; U.S. Pat. No. 8,852,244 to Simonson; U.S. Patent Application Publication No. 2012/0158146 to Glerum et al.; U.S. Pat. No. 8,852,242 to Morgenstern Lopez et al.; U.S. Pat. No. 8,852,281 to Phelps; U.S. Pat. No. 8,840,668 to Donahoe et al.; U.S. Pat. No. 8,840,622 to Vellido et al.; U.S. Patent Application Publication No. 20140257405; U.S. Patent Application Publication No. 20140257490 to Himmelberger et al.; U.S. Pat. No. 8,828,019 to Raymond et al.; U.S. Patent Application Publication No. 20140288652 to Boehm et al.; U.S. Patent Application Publication No. 20140287055 to Kunjachan; U.S. Patent Application Publication No. 20140276896 to Harper; U.S. Patent Application Publication No. 20140277497 to Bennett et al.; U.S. Patent Application Publication No. 20120029635 to Schoenhoeffer et al.; U.S. Patent Application Publication No. 20140303675 to Mishra; U.S. Patent Application Publication No. 20140303731 to Glerum; U.S. Patent Application Publication No. 20140303732 to Rhoda et al.; U.S. Pat. No. 8,852,279 to Weiman; PCT WO2012031267 to Weiman; U.S. Pat. No. 8,845,731 to Weiman; U.S. Pat. No. 8,845,732 to Weiman; U.S. Pat. No. 8,845,734 to Weiman; U.S. Patent Application Publication No. 20140296985 to Balasubramanian et al.; U.S. Patent Application Publication No. 20140309268 to Arnou; U.S. Patent Application Publication No. 20140309548 to Merz et al.; U.S. Patent Application Publication No. 20140309697 to Iott et al.; U.S. Patent Application Publication No. 20140309714 to Mercanzini et al.; U.S. Pat. No. 8,282,683 to McLaughlin et al.; U.S. Pat. No. 8,591,585 to McLaughlin et al.; U.S. Pat. No. 8,394,129 to Morgenstern Lopez et al.; U.S. Patent Application Publication No. 20110208226 to Fatone et al.; U.S. Patent Application Publication No. 20100114147 to Biyani; U.S. Patent Application Publication No. 20110144687 to Kleiner; U.S. Pat. No. 8,852,243 to Morgenstern Lopez et al.; U.S. Pat. No. 8,597,333 to Morgenstern Lopez et al.; U.S. Pat. No. 8,518,087 to Lopez et al.; U.S. Patent Application Publication No. 20120071981 to Farley et al.; U.S. Patent Application Publication No. 20130006366 to Farley et al.; U.S. Patent Application Publication No. 20120065613 to Pepper et al.; U.S. Patent Application Publication No. 20130006365 to Pepper et al.; U.S. Patent Application Publication No. 20110257478 to Kleiner et al.; U.S. Patent Application Publication No. 20090182429 to Humphreys et al.; U.S. Patent Application Publication No. 20050118550 to Turri; U.S. Patent Application Publication No. 20090292361 to Lopez; U.S. Patent Application Publication No. 20110054538 to Zehavi et al.; U.S. Patent Application Publication No. 20050080443 to Fallin et al.; U.S. Pat. No. 8,778,025 to Ragab et al.; U.S. Pat. No. 8,628,576 to Triplett et al.; U.S. Pat. No. 8,808,304 to Weiman, and U.S. Pat. No. 8,828,019 to Raymond.

[0119] One of ordinary skill in the art will appreciate that embodiments of the present disclosure may have various sizes. The sizes of the various elements of embodiments of the present disclosure may be sized based on various factors including, for example, the anatomy of the implant patient, the person or other device operating the apparatus, the implant location, physical features of the implant including,

for example, with, length and thickness, and the size of operating site or the size of the surgical tools being used with the device.

[0120] One of ordinary skill in the art will appreciate that embodiments of the present disclosure may be constructed of materials known to provide, or predictably manufactured to provide the various aspects of the present disclosure. These materials may include, for example, stainless steel, titanium alloy, aluminum alloy, chromium alloy, and other metals or metal alloys. These materials may also include, for example, PEEK, carbon fiber, ABS plastic, polyurethane, rubber, latex, synthetic rubber, and other fiber-encased resinous materials, synthetic materials, polymers, and natural materials. The plunger element could be flexible, semi-rigid, or rigid and made of materials such as stainless steel, titanium alloy, aluminum alloy, chromium alloy, and other metals or metal alloys. Similarly, the tubular element could be flexible, semi-rigid, or rigid and made of materials such as stainless steel, titanium alloy, aluminum alloy, chromium alloy, and other metals or metal alloys. In certain embodiments, the plunger and hollow tube are composed of plastic and are intended for one use only and then discarded. In another embodiment, some or all elements of the device, or portions of some or all of the elements, are luminescent. Also, in another embodiment, some or all elements of the device, or portions of some or all of the elements, include lighting elements. In another embodiment, the hollow tube and/or plunger are made of a substantially transparent material and/or are rigidly opaque.

[0121] In one embodiment of the fusion cage, the fusion cage comprises a polymer, such as PEEK, titanium and composite materials.

[0122] One of ordinary skill in the art will appreciate that embodiments of the present disclosure may be controlled by means other than manual manipulation. Embodiments of the present disclosure may be designed and shaped such that the apparatus may be controlled, for example, remotely by an operator, remotely by an operator through a computer controller, by an operator using proportioning devices, programmatically by a computer controller, by servo-controlled mechanisms, by hydraulically-driven mechanisms, by pneumatically-driven mechanisms or by piezoelectric actuators.

[0123] Embodiments of the present disclosure present several advantages over the prior art including, for example, the speed of the procedure, the minimally invasive aspect of the procedure, the ability to introduce the implant material to the implant site with minimal risk and damage to the surrounding tissue, the lower risk of infection, more optimally placed implant material, a more stable delivery device which is designed to reduce the likelihood of the implant material becoming dislodged prior to fixation, and fewer tools in a surgical site due to the integration of several components required to provide bone graft to a bone graft receiving area. Further, the lower profile of the device allows improved viewing of the area intended for receipt of bone graft material, and use of a reduced set and size of elements therein provided a less expensive device. Also, the device disclosed provides that substantially all of the bone graft material may be ejected from the device and delivered to the surgical site, rather than wasted as unretrievable matter remaining inside the device. The ability to remove substantially all of the bone graft material is of significant benefit because the bone graft material is expensive and/or hard to obtain.

[0124] This Summary of the Invention is neither intended nor should it be construed as being representative of the full extent and scope of the present disclosure. The present disclosure is set forth in various levels of detail in the Summary of the Invention as well as in the attached drawings and the Detailed Description of the Invention, and no limitation as to the scope of the present disclosure is intended by either the inclusion or non-inclusion of elements, components, etc. in this Summary of the Invention. Additional aspects of the present disclosure will become more readily apparent from the Detailed Description, particularly when taken together with the drawings.

[0125] The above-described benefits, embodiments, and/or characterizations are not necessarily complete or exhaustive, and in particular, as to the patentable subject matter disclosed herein. Other benefits, embodiments, and/or characterizations of the present disclosure are possible utilizing, alone or in combination, as set forth above and/or described in the accompanying figures and/or in the description herein below. However, the Detailed Description of the Invention, the drawing figures, and the exemplary claim set forth herein, taken in conjunction with this Summary of the Invention, define the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0126] The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the disclosure and together with the general description of the disclosure given above and the detailed description of the drawings given below, serve to explain the principles of the disclosures.

[0127] It should be understood that the drawings are not necessarily to scale. In certain instances, details that are not necessary for an understanding of the disclosure or that render other details difficult to perceive may have been omitted. It should be understood, of course, that the disclosure is not necessarily limited to the particular embodiments illustrated herein.

[0128] FIG. 1A is a front perspective view of the device for delivering bone graft;

[0129] FIG. 1B is a front perspective view of the plunger of the device;

[0130] FIG. 1C is a cross sectional view of a portion of the device shown in FIG. 1A;

[0131] FIG. 2 is another front perspective view of the device of FIGS. 1A and 1B, showing the relationship between the tubular and plunger portions of the device;

[0132] FIG. 3 is a front perspective view of the device according to one alternative embodiment where the tubular portion includes a foot section and where the plunger portion has been fully inserted into the tubular portion;

[0133] FIG. 4 is a partial front perspective view of another alternative embodiment of the device where the tubular portion includes a funnel at its proximal end designed to receive bone graft;

[0134] FIG. 5 is a partial front perspective view of the device according to one embodiment where the device is positioned in a disc space during a surgical operation;

[0135] FIG. 6 is a front perspective view of one embodiment of the device, showing the relationship between the tubular and plunger portions where the tubular portion includes two lateral facing openings at the distal end of the tubular portion and a wedge-shaped distal end of the tubular member;

[0136] FIG. 7 is another front perspective view of the tubular portion of the device of FIG. 6 showing the second of two lateral openings at the distal end of the tubular portion and a wedge-shaped distal end of the tubular member;

[0137] FIG. 8 is a front elevation view of the distal end of the tubular portion of the device of FIG. 6;

[0138] FIG. 9 is a bottom elevation view of the proximal end of the tubular device of FIG. 6;

[0139] FIG. 10A is a top plan view of the device of FIG. 6 with the plunger portion fully inserted into the tubular portion;

[0140] FIG. 10B is a left elevation view of the device of FIG. 6 with the plunger portion fully inserted into the tubular portion;

[0141] FIG. 10C is a bottom plan view of the device of FIG. 6 with the plunger portion fully inserted into the tubular portion;

[0142] FIG. 10D is a right elevation view of the device of FIG. 6 with the plunger portion fully inserted into the tubular portion;

[0143] FIG. 11A is a front perspective view of one embodiment of the fusion cage of the device, showing a tapered proximal end and medial openings;

[0144] FIG. 11B is a top plan view of the fusion cage of FIG. 11A;

[0145] FIG. 11C is a left elevation view of the fusion cage of FIG. 11A;

[0146] FIG. 11D is a rear elevation view of the fusion cage of FIG. 11A;

[0147] FIG. 12A is a front perspective view of another embodiment of the fusion cage of the device;

[0148] FIG. 12B is a front perspective view of yet another embodiment of the fusion cage of the device;

[0149] FIG. 12C is a front perspective view of yet another embodiment of the fusion cage of the device;

[0150] FIG. 13 is a front perspective view of one embodiment of the device, showing the relationship between the tubular and plunger portions where the tubular portion includes two lateral facing openings at the distal end of the tubular portion and a wedge-shaped distal end of the tubular member, and a fusion cage fitting over the exterior distal end of the tubular member;

[0151] FIG. 14A is a top plan view of the device of FIG. 13 with the plunger portion fully inserted into the tubular portion and the fusion cage fully inserted over the tubular portion;

[0152] FIG. 14B is a left elevation view of the device of FIG. 13 with the plunger portion fully inserted into the tubular portion and the fusion cage fully inserted over the tubular portion;

[0153] FIG. 14C is a bottom plan view of the device of FIG. 13 with the plunger portion fully inserted into the tubular portion and the fusion cage fully inserted over the tubular portion;

[0154] FIG. 14D is a right elevation view of the device of FIG. 13 with the plunger portion fully inserted into the tubular portion and the fusion cage fully inserted over the tubular portion;

[0155] FIG. 15A is a front perspective view of another embodiment of the fusion cage of the device;

[0156] FIG. 15B is a top plan view of another embodiment of the device wherein the fusion cage of the device includes

internal ramps and locking slots configured to engage locking tabs of the tubular portion, and the plunger includes a tapered tip;

[0157] FIG. 15C is a left elevation view of the fusion cage of FIG. 15B;

[0158] FIG. 15D is a front elevation view of the tubular portion of FIG. 15B;

[0159] FIG. 16 is a top plan view of another embodiment of the device with the plunger portion partial inserted into the tubular portion and the fusion cage engaged with the tubular portion via a break-off collar;

[0160] FIG. 17A is a top plan view of another embodiment of the device wherein the fusion cage engages with a connector conduit which in turn engages with the tubular portion;

[0161] FIG. 17B is a cross-sectional view of section A-A of FIG. 17A;

[0162] FIG. 18A is a top plan view of another embodiment of the device wherein the tubular portion comprises a telescoping feature;

[0163] FIG. 18B is a left elevation view of the device of FIG. 18A;

[0164] FIG. 18C is a bottom plan view of the device of FIG. 18A;

[0165] FIG. 18D is a right elevation view of the device of FIG. 18A;

[0166] FIG. 19A is a top plan view of a fusion cage of an embodiment of the device particularly adapted for use in anterior lumbar interbody fusion procedures;

[0167] FIG. 19B is a front elevation view of the device of FIG. 19A;

[0168] FIG. 19C is a left elevation view of the device of FIG. 19A;

[0169] FIG. 19D is a view of the device of FIG. 19A inserted between vertebrae;

[0170] FIG. 20A is a cross-sectional top plan view of a fusion cage of an embodiment of the device particularly adapted for use in direct lateral interbody fusion procedures;

[0171] FIG. 20B is a front elevation view of the device of FIG. 20A;

[0172] FIG. 20C is a left elevation view of the device of FIG. 20A;

[0173] FIG. 20D is a view of the device of FIG. 20A inserted between vertebrae;

[0174] FIG. 21A is a front perspective view of a fusion cage of an embodiment of the device particularly adapted for use in connection with vertebrectomy procedures;

[0175] FIG. 21B is a left perspective view of the device of FIG. 21A;

[0176] FIG. 21C is a front elevation view of the device of FIG. 21A inserted into a surgical site;

[0177] FIG. 21D is a left elevation view of the device of FIG. 21A inserted into a surgical site;

[0178] FIG. 22 is a front perspective view of another embodiment of the device for delivering bone graft;

[0179] FIG. 23 is a front perspective exploded view of the device shown in FIG. 22;

[0180] FIG. 24 is a top plan view of the device shown in FIG. 22;

[0181] FIG. 25 is a front elevation view of the device shown in FIG. 22;

[0182] FIG. 26 is a right elevation view of the device shown in FIG. 22;

[0183] FIG. 27 is a bottom plan view of the device shown in FIG. 22;

[0184] FIG. 28 is a cross-sectional view of section A-A of FIG. 25;

[0185] FIG. 29 is a front elevation view of the plunger element of the device shown in FIG. 22;

[0186] FIG. 30 is a cross-sectional view of section B-B of FIG. 29;

[0187] FIG. 31 is a cross-sectional of section C-C of FIG. 29;

[0188] FIG. 32 is a detailed front perspective view of a portion of the device shown in FIG. 22;

[0189] FIG. 33 is a cross-sectional view of section D-D of FIG. 32;

[0190] FIG. 34A is a bar graph describing experimental results of bone graft delivery and disk material removed for L4-5;

[0191] FIG. 34B is a bar graph describing experimental results of bone graft delivery and disk material removed for L5-S1;

[0192] FIG. 35A is a table describing experimental results of bone graft delivery and disk material removed;

[0193] FIG. 35B is a graph of the table of FIG. 35A describing experimental results of bone graft delivery and disk material removed;

[0194] FIG. 36 is a front perspective exploded view of an integrated fusion cage and graft delivery device according to another embodiment;

[0195] FIG. 37 is a front perspective view of the device of FIG. 36;

[0196] FIG. 38 is a closed-up front perspective view of the device of FIG. 36;

[0197] FIG. 39 is a front perspective view of the ejection tool element of the device of FIG. 36;

[0198] FIG. 40 is a front perspective view of an integrated fusion cage and graft delivery device according to yet another embodiment;

[0199] FIG. 41 is a closed-up front perspective view of the device of FIG. 40;

[0200] FIG. 42 is a close-up front perspective view of the ejection tool element first end;

[0201] FIG. 43 is a cut-away cross-sectional view of the element of FIG. 42;

[0202] FIG. 44 is a close-up cut-away cross-sectional view of one embodiment of the integrated fusion cage and graft delivery device;

[0203] FIGS. 45A-G provide scaled views of one embodiment of the fusion cage element of yet another embodiment of the integrated fusion cage and graft delivery device configured to operate with the hollow tube of FIGS. 46A-H, plunger of FIGS. 47A-D and ejection tool of FIGS. 48A-E;

[0204] FIGS. 46A-H provide scaled views of one embodiment of the hollow tube (aka snap on cannula) of the integrated fusion cage and graft delivery device configured to operate with the fusion cage element of FIGS. 45A-G, plunger of FIGS. 47A-D and ejection tool of FIGS. 48A-E;

[0205] FIGS. 47A-D provide scaled views of one embodiment of the plunger (aka snap on plunger) of the integrated fusion cage and graft delivery device configured to operate with the fusion cage element of FIGS. 45A-G, hollow tube of FIGS. 46A-H, and ejection tool of FIGS. 48A-E;

[0206] FIGS. 48A-E provide scaled views of one embodiment of the ejection tool (aka cage insertion tool) of the integrated fusion cage and graft delivery device configured

to operate with the fusion cage element of FIGS. 45A-G, hollow tube of FIGS. 46A-H and plunger of FIGS. 47A-D; [0207] FIG. 49A is a left perspective view of an embodiment of the fusion cage with expandable fusion cage feature, the fusion cage in an unexpanded state;

[0208] FIG. 49B is a rear perspective view of the device shown in FIG. 49A;

[0209] FIG. 49C is a top perspective view of the device shown in FIG. 49A;

[0210] FIG. 50A is a left perspective view of the device shown in FIG. 49A, the fusion cage in an expanded state;

[0211] FIG. 50B is a rear perspective view of the device shown in FIG. 50A;

[0212] FIG. 50C is a top perspective view of the device shown in FIG. 50A;

[0213] FIG. 51 is a scaled rear perspective exploded view of an embodiment of the fusion cage with expandable fusion cage feature;

[0214] FIGS. 52A-E provide scaled views of the device shown in FIG. 51, the fusion cage in an unexpanded state;

[0215] FIGS. 53A-E provide scaled views of the device shown in FIG. 51, the fusion cage in an expanded state;

[0216] FIGS. 54A-F provide scaled views of the upper plate component of the device shown in FIG. 51;

[0217] FIGS. 55A-E provide scaled views of the front block component of the device shown in FIG. 51;

[0218] FIGS. 56A-F provide scaled views of the rear block component of the device shown in FIG. 51;

[0219] FIGS. 57A-C provide scaled views of the expansion screw component of the device shown in FIG. 51;

[0220] FIG. 58 is a rear perspective exploded view of another embodiment of the fusion cage with expandable fusion cage feature;

[0221] FIGS. 59A-E provide scaled views of the device shown in FIG. 58, the fusion cage in an unexpanded state;

[0222] FIGS. 60A-E provide scaled views of the device shown in FIG. 58, the fusion cage in an expanded state;

[0223] FIG. 61A is a front left perspective view of yet another embodiment of the fusion cage with expandable fusion cage feature, comprising a vertical wedge angle feature;

[0224] FIG. 61B is a left elevation view of the device of FIG. 61A;

[0225] FIG. 62A is a front left perspective view of yet another embodiment of the fusion cage with expandable fusion cage feature, comprising a horizontal wedge angle feature;

[0226] FIG. 62B is a left elevation view of the device of FIG. 62A;

[0227] FIG. 63A is a left rear perspective view of a fusion cage with expandable fusion cage feature configured to communicate with an installer/impactor component according to yet another embodiment;

[0228] FIG. 63B is a close-up partial left rear perspective view of the devices of FIG. 63A;

[0229] FIG. 64 is a left rear perspective view of the rear block component of the fusion cage of FIG. 63A;

[0230] FIG. 65A is a left rear perspective view of the devices of FIG. 63A, shown with the fusion cage and installer/impactor components in an engaged state, and the installer/impactor comprising an installer/impactor handle;

[0231] FIG. 65B is a left front perspective partial cross-sectional view of the devices of FIG. 63A in the state of FIG. 65A, shown with the fusion cage and installer/impactor

components in an engaged state, the devices engaged with an expansion driver component, the installer/impactor component shown in partial cross-section to partially show the expansion driver fitted within the interior of the installer/impactor;

[0232] FIG. 66 is a left front perspective view of the devices of FIG. 63A, shown with the fusion cage and installer/impactor components in an engaged state, with the hollow tube component engaged with the installer/impactor component;

[0233] FIG. 67 is a left rear perspective view of the devices of FIG. 63A, shown with the fusion cage and installer/impactor components in an engaged state, and shown with the fusion cage and hollow tube in an engaged state;

[0234] FIG. 68A is a left rear perspective view of the devices of FIG. 63A, shown in the configuration of FIG. 67, with a removal pliers component engaged with the hollow tube component;

[0235] FIG. 68B is a close-up partial perspective view of the devices of FIG. 68A;

[0236] FIG. 69 is a left rear exploded perspective view of a fusion cage with expandable fusion cage feature engaged with a hollow tube component and a funnel component, as configured to engage with a plunger component;

[0237] FIG. 70 is a left front partial perspective view of another embodiment of the hollow tube component configured to engage a fusion cage with expandable fusion cage feature, the hollow tube configured with hollow tube slot and hollow tube slot aperture features;

[0238] FIG. 71 is a left rear perspective view of another embodiment of the lower plate component of a fusion cage with expandable fusion cage feature, the lower plate configured with a plate tab feature configured to engage the hollow tube slot and hollow tube slot aperture features of FIG. 70;

[0239] FIG. 72 is a left front partial cross-section perspective view of the devices of FIGS. 70 and 71, shown with the plate tab feature engaged with the hollow tube slot and hollow tube slot aperture features;

[0240] FIG. 73 is a right rear exploded view of another embodiment of the fusion cage with expandable cage feature; and

[0241] FIG. 74 depicts the fusion cage with expandable cage feature engaged with an angled insertion tool.

[0242] FIG. 75 is perspective view of a bone graft delivery device according to the prior art.

[0243] FIG. 76 is a cross-sectional view of an intervertebral disc space and a bone graft delivery device.

[0244] FIG. 77 is a plan view of a bone graft delivery device according to one embodiment of the present disclosure.

[0245] FIG. 78 is a plan view of a bone graft delivery device according to one embodiment of the present disclosure.

[0246] FIG. 79 is a perspective view of a portion of a bone graft delivery device according to one embodiment of the present disclosure.

[0247] FIG. 80 is a cross-sectional elevation view of a surgical site and a bone graft delivery device according to one embodiment of the present disclosure.

[0248] FIG. 81 is a cross-sectional elevation view of a surgical site and a bone graft delivery device according to one embodiment of the present disclosure.

[0249] FIG. 82 is a cross-sectional elevation view of a surgical site and a bone graft delivery device according to one embodiment of the present disclosure.

[0250] FIG. 83 is an elevation view of a bone graft material and method of preparation according to one embodiment of the present disclosure.

[0251] FIG. 84 is a perspective view of bone graft material contemplated for use with embodiments of the present disclosure.

[0252] To provide further clarity to the Detailed Description provided herein in the associated drawings, the following list of components and associated numbering are provided as follows:

REFERENCE NO.	COMPONENT	
[0253]	1 Integrated fusion cage and graft delivery device	
[0254]	2 Hollow tube	
[0255]	3 Hollow tube first exterior surface	
[0256]	4 Opening (of Hollow tube)	
[0257]	5 Hollow tube second exterior surface	
[0258]	6 First end (of Hollow tube)	
[0259]	6A Knob	
[0260]	7 Hollow tube first distal opening	
[0261]	8 Second end (of Hollow tube)	
[0262]	8A Hollow tube cage clamp	
[0263]	8B Hollow tube cage clamp radial surface	
[0264]	9 Hollow tube distal interior ramp	
[0265]	9A Hollow tube distal interior ramp surface	
[0266]	10 Curved surface (of Hollow tube)	
[0267]	10A Curved interior surface (of Hollow tube)	
[0268]	11 Footing (of Hollow tube)	
[0269]	12 Plunger	
[0270]	13 Plunger distal first surface	
[0271]	14 Plunger distal second surface	
[0272]	15 Plunger distal third surface	
[0273]	16 Handle (of Plunger)	
[0274]	16A Plunger stop	
[0275]	17 Plunger medial portion	
[0276]	18 Second end (of Plunger)	
[0277]	19 Horizontal surface (of Plunger)	
[0278]	20 Curved surface (of Plunger)	
[0279]	30 Funnel	
[0280]	32 Sleeve (of Funnel)	
[0281]	34 Opening (of Funnel)	
[0282]	40 Disc space	
[0283]	50 Wedge-shaped Second end (of Hollow tube)	
[0284]	52 Wedge-shaped Second end (of Plunger)	
[0285]	60 Fusion Cage	
[0286]	61 Fusion cage surface texture	
[0287]	62 Fusion Cage First End	
[0288]	64 Fusion Cage Second End	
[0289]	65 Fusion Cage First Opening Pair	
[0290]	66 Fusion Cage First End Opening	
[0291]	67 Fusion Cage Second Opening Pair	
[0292]	68 Fusion Cage Medial Opening	
[0293]	69 Fusion Cage Lateral Opening	
[0294]	70 Fusion Cage Medial Surfaces	
[0295]	72 Fusion Cage Internal Ramps	
[0296]	80 Hollow Tube Locking Tabs	
[0297]	82 Fusion Cage Locking Slots	
[0298]	90 Break-off Collar	
[0299]	92 Fusion Cage Collar	
[0300]	93 Fusion Cage Collar Face	
[0301]	94 Fusion Cage Collar Cavity	
[0302]	96 Fusion Cage Tab Extension	
[0303]	97 Fusion Cage Tab Extension Latch	
[0304]	100 Connector Conduit	
[0305]	102 Connectors	
[0306]	110 ALIF Fusion Cage	
[0307]	112 ALIF Fusion Cage Portals	
[0308]	114 ALIF Fusion Cage Chamber	
[0309]	116 ALIF Fusion Cage Break-off Collar	
[0310]	120 D-LIF Fusion Cage	
[0311]	122 D-LIF Fusion Cage Portals	
[0312]	124 D-LIF Fusion Cage Chamber	
[0313]	126 D-LIF Fusion Cage Break-off Collar	
[0314]	130 Vertebroctomy Fusion Cage	
[0315]	132 Vertebroctomy Fusion Cage Porous Wall Portion	
[0316]	134 Vertebroctomy Fusion Cage Chamber	
[0317]	136 Vertebroctomy Fusion Cage Break-off Collar	
[0318]	138 Vertebroctomy Fusion Cage Impervious Wall Portion	
[0319]	140 Ejection Tool	
[0320]	142 Ejection Tool First (Proximal) End	
[0321]	143 Ejection Tool Stop	
[0322]	144 Ejection Tool Cover	
[0323]	145 Ejection Tool Cover Cavity	
[0324]	146 Spring Cover	
[0325]	147 Spring Cover Attachment	
[0326]	148 Spring	
[0327]	149 Ejection Tool Wings	
[0328]	150 Ejection Tool Wings Cavity	
[0329]	151 Ejection Tool L-cut	
[0330]	152 Ejection Tool Second (Distal) End	
[0331]	160 Ejection Tool Rod	
[0332]	200 Upper Plate	
[0333]	201 Upper Plate Front	
[0334]	202 Upper Plate Rear	
[0335]	203 Upper Plate Opening	
[0336]	204 Upper Plate Surface Texture	
[0337]	205 Upper Plate Track	
[0338]	206 Upper Plate Slot	
[0339]	209 Upper Plate Ridge	
[0340]	210 Lower Plate	
[0341]	211 Lower Plate Front	
[0342]	212 Lower Plate Rear	
[0343]	213 Lower Plate Opening	
[0344]	214 Lower Plate Surface Texture	
[0345]	215 Lower Plate Track	
[0346]	216 Lower Plate Slot	
[0347]	217 Plate Tab	
[0348]	218 Plate Nose	
[0349]	219 Lower Plate Ridge	
[0350]	220 Front Block	
[0351]	222 Front Block Upper Rail	
[0352]	224 Front Block Lower Rail	
[0353]	225 Front Block Nose	
[0354]	226 Front Block Ramp	
[0355]	227 Front Block Aperture	
[0356]	228 Block Spine	
[0357]	230 Rear Block	
[0358]	231 Rear Block Groove	
[0359]	232 Rear Block Upper Rail	
[0360]	234 Rear Block Lower Rail	
[0361]	236 Rear Block Ramp	

[0362]	237 Rear Block Aperture
[0363]	238 Rear Block Aft
[0364]	239 Rear Block Detent
[0365]	240 Expansion Screw
[0366]	242 Expansion Screw Head
[0367]	244 Expansion Screw Tip
[0368]	246 Expansion Screw Disk
[0369]	250 Installer/Impactor
[0370]	252 Installer/Impactor Tip
[0371]	253 Installer/Impactor Aperture
[0372]	254 Installer/Impactor Ridge
[0373]	255 Installer/Impactor Channel
[0374]	256 Installer/Impactor Ramp
[0375]	258 Installer/Impactor Handle
[0376]	260 Expansion Driver
[0377]	268 Expansion Driver Handle
[0378]	270 Removal Pliers
[0379]	280 Hollow Tube External Ramp
[0380]	282 Hollow Tube Notch
[0381]	284 Hollow Tube Slot
[0382]	285 Hollow Tube Slot Aperture
[0383]	290 Cam
[0384]	292 Nose Cone
[0385]	294 Ramps
[0386]	300 Adaptor
[0387]	400 Prior Art Fusion Cage
[0388]	400' Modified Prior Art Fusion Cage
[0389]	A Height of Opening (in Hollow tube)
[0390]	B Width of Opening (in Hollow tube)

DETAILED DESCRIPTION

[0391] The present invention relates to a device and method for integrated and near-simultaneous delivery of bone graft material and a fusion cage to any portion of a patient which requires bone graft material and/or a fusion cage. Thus, for example, the foregoing description of the various embodiments contemplates delivery to, for example, a window cut in a bone, where access to such window for bone grafting is difficult to obtain because of orientation of such window, presence of muscle tissue, risk of injury or infection, etc. The integrated fusion cage and graft delivery device is formed such that the one or more hollow tubes and/or plungers may be helpful in selectively and controllably placing bone graft material and a fusion cage in or adjacent to such window. The integrated fusion cage and graft delivery device is formed to allow delivery of bone graft material and/or a fusion cage in a direction other than solely along the longitudinal axis of the device, and in some embodiments transverse to the primary axis used by the surgeon or operator of the device when inserting the device into a cannula or other conduit to access the surgical site. This same concept applies to other areas of a patient, whether or not a window has been cut in a bone, for example in a vertebral disc space, and may be used whether this is a first surgery to the area or a follow-up surgery. The present invention also contemplates the delivery of bone graft material and/or a fusion cage with or without the use of a plunger, and with or without the use of various other tools described in greater detail herein.

[0392] Referring now to FIGS. 1-33 and 36-45, several embodiments of the present invention are shown.

[0393] In regard to FIG. 1A, an integrated fusion cage and graft delivery device portion is shown, which is comprised of a hollow tubular member or hollow tube or contains at

least one inner lumen 2, which has a first proximate end 6 (which is referred to elsewhere in this specification as the “graspable end” of hollow tube 2), and a second distal end 8, with a general hollow structure therebetween. Thus, as shown in FIG. 1, the hollow tube 2 allows bone graft material to be inserted into the opening 4 at the graspable end 6 of the hollow tube 2, and ultimately exited from the hollow tube 2 through the second end 8. According to a preferred embodiment, the hollow tube 2 also comprises at least one sloped or curved surface 10 at or near the second end 8 of the hollow tube 2. Although a generally rectangular cross-section is depicted, the cross-section need not be limited to a generally rectangular shape. For example, cross-sections of an oval shape or those with at least one defined angle to include obtuse, acute, and right angles can provide a shape in some situations that is more congruent with the size or shape of the annulotomy of a particular disc space.

[0394] Referring now in detail to FIG. 1B, a plunger 12 is shown for use with the hollow tube 2 of FIG. 1A. The plunger 12 is generally of the same geometry as the hollow portion of the hollow tube 2, extending at least the same length of hollow tube 2. The plunger 12 may include, as depicted in FIG. 1B at least one knob or handle 16 for grasping by a user of the plunger 12. As with the interior of the hollow tube 2 at its second end 8, the plunger 12 also comprises at least one sloped or curved surface 20 at or adjacent to a second end 18 of the plunger 12. The plunger 12 terminates in a generally flat, horizontal surface 19, which corresponds to the opening at the second end 8 of the hollow tube 2 shown in FIG. 1A. Thus, in cooperation, the plunger 12 may be inserted into the opening 4 of the hollow tube 2 shown in FIG. 1A, and extended the entire length of the hollow tube 2, at least to a point where the horizontal surface 19 of plunger 12 is in communication with the second end 8 of the hollow tube 2. This configuration permits a user to eject substantially all of the bone graft material that is placed into the hollow tube 2 during a surgical procedure. One skilled in the art will appreciate that the plunger need not terminate in a generally flat, horizontal surface to effect the substantial removal of all of the bone graft material placed into the hollow tube; more specifically, any shape that allows conformance between the internal contour of the distal end of the hollow tube and the distal end of the plunger will effect the substantial removal of the bone graft material. Further details about the relationship are described below in regard to FIG. 2.

[0395] In the embodiment, of FIG. 1A-C, a contoured leading edge is provided on the plunger to correspond with the internal contour of distal end of the hollow tube of the delivery device. This contoured plunger serves several purposes: First, it maintains the plunger in a desirable rotational position with respect to the hollow tube (i.e., prevents the plunger from inadvertently or intentionally being manipulated to rotate about the longitudinal axis of the hollow tube). Second, it ensure that when the plunger is fully inserted, the plunger removes substantially all of the bone graft material from the hollow tube. Also, the contoured plunger, corresponding to the contoured tubular member, allows immediate identification of the orientation of the device, and more specifically the direction of eject of the bone graft material into the surgical area. Alternative positioning means may also be provided to ensure that the plunger remains in the desirable position during delivery of

bone graft into the hollow tube, for example by a machined bevel or edge on the outer surface of the plunger, and a corresponding groove in the interior surface of the hollow tube, which must be aligned when inserting the plunger in the hollow tube.

[0396] Referring now to FIG. 1C, an elevation view of the hollow tube 2 shown in FIG. 1A is shown in detail. The second end 8 of the hollow tube 2 has an opening with a height A and width B according to the needs of the surgeon, the location of the bone graft receiving area, the nature of the surgical operation to be performed, and the quantity and type of bone graft that is being inserted in (and ultimately ejected from) this integrated fusion cage and graft delivery device. According to a preferred embodiment, the height A of the opening at the second end 8 of the hollow tube 2 is in the range of 4 mm to 9 mm, and in a most preferred embodiment is about 7 mm. According to a preferred embodiment, the width B of the opening at the second end 8 of the hollow tube 2 is in the range of 7 mm to 14 mm, and in a most preferred embodiment is about 10 mm.

[0397] Referring to FIGS. 1A-C, it is to be understood that although these particular drawings reflect an embodiment where the second end 8 of the hollow tube 2, and the second end 18 of the plunger 12 comprise a curved or sloped surface which extends at least a certain distance laterally away from the generally longitudinal axis of the hollow tube 2/plunger 12, that in other embodiments, the second end 8 of the hollow tube 2 (and thereby, the second end 18 of the plunger 12) do not extend a lateral distance away, but rather terminate along the longitudinal wall of the hollow tube 2. In this embodiment, the hollow tube 2 may have a second end 8 which has an opening that is carved out of the side of the wall of the hollow tube 2, such that it appears as a window in the tubular body of hollow tube 2. According to this embodiment, the horizontal face 19 of the plunger 12 would also be a face on the outer surface of plunger 12, without extending any lateral distance away from the body of plunger 12. According to this embodiment, the plunger 12 would still retain the curved or sloped surface at the opposite end of the horizontal face 19 (referred to in FIG. 1B as 20) and similarly the hollow tube 2 would still comprise a sloped or curved surface 10 opposite the opening at second end 8. It is to be expressly understood that other variations which deviate from the drawing FIGS. 1A-C are also contemplated with the present invention, so long as that the opening at the second end 8 of hollow tube 2 is oriented to permit bone graft to be exited from the hollow tube 2 in a generally lateral direction (in relation to the longitudinal direction of the axis of the hollow tube 2).

[0398] According to another embodiment, the plunger 12 shown in FIG. 1B may further comprise a secondary handle (not shown in FIG. 1B), which includes an opening about at least one end of secondary handle such that it is permitted to couple with handle 16 of plunger 12. In this fashion, the secondary handle may be larger, contain one or more rings or apertures for placing a users hand and/or fingers, or may simply be of a more ergonomic design, for accommodating use of the plunger 12 during a surgical operation. The secondary handle, according to this embodiment, is selectively removable, which permits a surgeon to use the secondary handle for inserting the plunger 12, and then at a later point remove the secondary handle, for instance, to improve visibility through the incision or through the hollow tube 2,

and/or to determine whether substantially all of the bone graft material has been ejected from the hollow tube 2.

[0399] Referring now in detail to FIG. 2, the plunger 12 is shown inserted into the hollow tube 2, such that the horizontal face 19 is substantially planar with the opening at the second end 8 of the hollow tube 2. As described above, the geometry of plunger 12 is such that it fits snugly or tightly in the interior of the hollow tube 2. This configuration is such that the sloped or curved surface 10 of the hollow tube 2 is substantially congruent to the sloped or curved surface 20 (not shown in FIG. 2), thereby allowing the plunger to be inserted into the hollow tube 2 and allowing substantially all of bone graft material which is placed into the hollow tube 2 to be ejected by the user.

[0400] Referring now in detail to FIG. 3, an alternate embodiment of the present invention is shown. According to this embodiment, the hollow tube 2 comprises a footing 11 at the second end 8 of the hollow tube 2. This footing 11 extends in a lateral direction, opposite the direction of the opening at the second end 8 of the hollow tube 2. The purpose of this footing 11 is to prevent injury to the annulus of a patient, or other sensitive anatomy adjacent the bone graft receiving area. This footing 11 is helpful when a surgeon or other user of the integrated fusion cage and graft delivery device is using the plunger 12 to drive bone graft through the hollow tube 2, or using another tool, such as a tamp, mallet, or other driving or impacting device to strike the plunger 12 and/or hollow tube 2 during the surgical procedure. Without the footing 11, the hollow tube 2 would have a generally angular second end 8, which may cause damage to the patient during these types of procedures. Thus, the footing 11 prevents the second end 8 of the hollow tube 2 from penetrating the annulus or other sensitive anatomy of the patient.

[0401] According to this embodiment, the footing 11 may also operate to ensure a fixed position of the second end 8 of the hollow tube 2 in the surgical site. This in turn allows a user to ensure that bone graft ejecting the second end 8 of the hollow tube 2 is being ejected laterally, and in the desired direction. This may be important, for example, when the integrated fusion cage and graft delivery device is placed within a disc space, and bone graft is being ejected laterally from the second end 8 of the hollow tube 2 in a specific direction. In other embodiments, the footing 11 may also serve as a visual marker for the surgeon, as it extends away from the horizontal wall of the hollow tube 2, and is therefore visible at the second end 8 of the hollow tube 2. As shown in FIG. 3, the presence of the footing 11 does not affect the interior slope or curved surface 10A of the hollow tube 2, so that the plunger 12 of the design shown in FIG. 1B may still be used with the hollow tube 2 of this alternate embodiment.

[0402] Referring now in detail to FIG. 4, a removable funnel 30 is shown, which comprises an opening 34 which is generally larger in diameter or dimension when compared to the opening 4 of the hollow tube 2. This removable funnel 30 further comprises a sleeve 32, the sleeve 32 having an internal cross-section which is substantially congruent with the external cross-section of the first end 6 of the hollow tube 2. Thus, according to this embodiment, the funnel 30 is selectively removable from the first end 6 of the hollow tube 2, and may allow a surgeon to more easily place new or additional bone graft into the hollow tube 2 by way of the opening 34 of the funnel 30. This funnel 30 may be used in

connection with a hollow tube 2 that has been pre-filled with bone graft, or a hollow tube which is not pre-filled with bone graft. Thus, the funnel may be selectively positioned on the first end 6 of the hollow tube 2 at any point during the surgical operation when the surgeon desires new or additional bone graft be placed in the hollow tube 2 of the integrated fusion cage and graft delivery device.

[0403] Referring now in detail to FIG. 5, one particular application of the integrated fusion cage and graft delivery device is shown in a perspective view. Here, the integrated fusion cage and graft delivery device is shown with the embodiment of the hollow tube 2 further comprising a footing 11, and a second end opening for ejecting bone graft in a generally lateral direction, here in the interior of a disc space 40. The disc is shown with an opening on one end for inserting the second end 8 of the hollow tube 2 of the integrated fusion cage and graft delivery device. As opposed to prior art integrated fusion cage and graft delivery devices which have an opening at a second end that is open to the longitudinal axis of the delivery device, the present invention comprises a lateral opening, which as shown in FIG. 5 allows a surgeon to eject bone graft into the lateral direction and thereby into the opened areas of the disc space 40. A surgeon has the option to rotate the direction of the opening in the second end 8 of the hollow tube 2 for ejecting additional bone graft to other open areas in the disc space 40. Once the disc space 40 is substantially full of bone graft, the surgeon may remove the hollow tube 2 without disturbing the disc or anatomy of the patient. The surgeon may also accomplish the delivery of bone graft without displacing any cage or other structural implantable device which may be present in or adjacent the disc space. One skilled in the art will appreciate that the hollow tube 2 further comprising a footing 11, and a second end opening for ejecting bone graft in a generally lateral direction, may effect the delivery of bone graft in a lateral direction simultaneous with delivery in a longitudinal direction.

[0404] Referring now to FIGS. 6-10, a preferred embodiment of the device is shown. In regard to FIG. 6, an integrated fusion cage and graft delivery device portion is shown, comprised of a hollow tubular member 2, which has a first proximate end 6 and a second distal end 8, with a general hollow structure therebetween. The generally hollow tube 2 is shown with one of two lateral openings at the distal end 8 of the tubular member 2 viewable (the other is viewable in FIG. 7). Also in FIG. 6, the plunger member 12 is shown. The manner of insertion of plunger member 12 into tubular member 2 is also provided. Thus, as shown in FIG. 6, the hollow tube 2 allows bone graft material to be inserted into the opening 4 at the proximal end 6 of the hollow tube 2, and ultimately exited from the hollow tube 2 through the second distal end 8 from the lateral openings at the distal end 8 of the hollow tubular member 2.

[0405] Furthermore regarding FIG. 6, a preferred embodiment of the distal end 10 of the tubular member 2 and the distal end 20 of the plunger member 12 is provided. The configuration provided, a wedge-shaped end 50 of the tubular member and a wedge-shaped end of the plunger 52, allows substantially all of the bone graft material to be removed and thus inserted into the surgical area when the plunger 2 is fully inserted into the tubular member 2. The wedge-shaped feature 50 of the distal end 10 of the tubular member 2 and the wedge-shaped end 52 of the distal end 20 of the plunger member 12 is discussed in additional detail

with respect to FIGS. 8 and 9 below. The ability to remove substantially all of the bone graft material is an important feature of the invention because bone graft material is traditionally expensive and may require surgery to obtain.

[0406] Referring now to FIG. 7, a perspective view of a preferred embodiment of the hollow tubular member 2 is provided. Consistent with FIG. 6, the generally hollow tube 2 is shown with one of two lateral openings at the distal end 8 of the tubular member 2 viewable (the other is viewable in FIG. 6). Thus, in operation the hollow tube 2 allows bone graft material to be inserted into the opening 4 at the proximal end 6 of the hollow tube 2, and ultimately exited from the hollow tube 2 through the second distal end 8 from the lateral openings at the distal end 8 of the hollow tubular member 2. In this configuration, bone graft material is ejected into the surgical area in two lateral directions. One skilled in the art will appreciate that the openings at the distal end 8 of the hollow tubular member 2 need not be positioned exclusively on one or more lateral sides of the distal end 8 of the tubular member to allow bone graft material to be provided to the surgical site in other than a purely axial or longitudinal direction. Further, one skilled in the art will appreciate that the specific absolute and relative geometries and numbers of lateral openings may vary, for example the distal end 8 of the tubular member 2 may have more than two openings that are of different shape (e.g. oval, rectangular).

[0407] Referring now to FIG. 8, an elevation view of the wedge-shaped distal end 50 of the tubular member 2 is provided. In this embodiment, the proximal end of the plunger would conform to the same shape, to allow close fitting of the plunger and the hollow tubular member. This contoured plunger, corresponding to the contoured tubular member, serves several purposes: First, it maintains the plunger in a desirable rotational position with respect to the hollow tube (i.e., prevent the plunger from inadvertently or intentionally being manipulated to rotate about the longitudinal axis of the hollow tube); Second, it ensure that when the plunger is fully inserted, the plunger removes substantially all of the bone graft material from the hollow tube. Also, the contoured plunger, corresponding to the contoured tubular member, allows immediate identification of the orientation of the device, and more specifically the direction of eject of the bone graft material into the surgical area. One skilled in the art will appreciate that the plunger need not terminate in a wedge-shape surface to effect the substantial removal of all of the bone graft material placed into the hollow tube; more specifically, any shape that allows conformance between the internal contour of the distal end of the hollow tube and the distal end of the plunger will effect the substantial removal of the bone graft material.

[0408] Referring now to FIG. 9, an elevation view of the opening 4 of the distal end 6 of the hollow tubular member 2 is provided. As shown in FIG. 9, the opening 4 at the proximal end 6 of the hollow tube 2 allows deposit of bone graft material. In this configuration, the cross-section of the opening 4 at the proximal end 6 of the hollow tube 2 is generally square. Although a generally square cross-section is depicted, the cross-section need not be limited to a generally square shape. For example, cross-sections of an oval shape or those with at least one defined angle to include obtuse, acute, and right angles can provide a shape in some situations that is more congruent with the size or shape of the annulotomy of a particular disc space.

[0409] Referring to FIGS. 10A-D, sequential elevation views of the square-shaped embodiment of the integrated fusion cage and graft delivery device 1 are provided, depicting the complete insertion of the plunger 12 into the hollow tubular member 2. In each of FIGS. 10A-D, the wedge-shaped distal end 50 of the tubular member 2 is depicted. Also, each of FIGS. 10A-D depict the additional length of the plunger element 12 when inserted into the tubular member 2. FIG. 10A shows one of two lateral openings at the distal end 8 of the hollow tubular member 2. FIG. 10C shows another of the two lateral openings at the distal end 8 of the hollow tubular member 2. One skilled in the art will appreciate that the openings at the distal end 8 of the hollow tubular member 2 need not be positioned exclusively on one or more lateral sides of the distal end 8 of the tubular member 2 to allow bone graft material to be provided to the surgical site in other than a purely axial or longitudinal direction. Further, one skilled in the art will appreciate that the specific absolute and relative geometries and numbers of lateral openings may vary, for example the distal end 8 of the tubular member 2 may have more than two openings that are of different shape (e.g. oval, rectangular).

[0410] Referring to FIGS. 11A-D, a fusion cage 60 of an integrated fusion cage and graft delivery device 1 portion is shown, which is comprised of a integrated fusion cage 60 that comprises a first proximal end 62 and a second distal end 64 wherein the first proximal end contains an opening 66 adapted to allow fitting and/or engagement to the distal end 8 of the hollow tube 2. This fitting and/or engagement may be over the external surface of the hollow tube 2 or inside the interior of the hollow tube 2. Further, the integrated fusion cage 60 may comprise one or more medial openings 68 that align with one or more openings at the distal end 8 of the hollow tube 2. Further, the integrated fusion cage 60 may contain non-smooth surfaces, such as belts or striations, along one or more medial surfaces 70 of the integrated fusion cage 60. The integrated fusion cage 60 is configured such that when a plunger 12, once fully inserted in to the hollow tube 2, is substantially congruent with the hollow interior portion of the hollow tube 2, e.g. both the plunger 12 and the hollow tube 2 are substantially the same shape and/or class and bone graft material is delivered through the integrated fusion cage 60 into the surgical area.

[0411] In a preferred embodiment, the fusion cage 60 has a tapered tip, and several open channels along the medial and lateral surfaces. In a preferred embodiment, the fusion cage 60 and/or the bone graft delivery portion of the integrated fusion cage and graft delivery device is of oblong or rectangular or square shape. The integrated fusion cage and graft delivery device 1 is designed to avoid blocking or impacting bone graft material into a surgical disc space, thereby limiting the bone graft material that may be delivered, and not allowing available fusion space to be fully exploited for fusion.

[0412] In a preferred embodiment, the fusion cage 60 has a keel-shaped tip to separate disk and prevent annular penetration. Also, the fusion cage 60 may have dual portals for bone graft discharge, with the medial openings 68 larger than the lateral openings 69. Further, the fusion cage may be designed in variable heights and lengths so that it fits snugly into the prepared disk space.

[0413] Referring now to FIGS. 12A-C, two alternate embodiments of the fusion cage 60 are provided. FIG. 12A shows an embodiment of the integrated fusion cage 60 with

a second distal end 64 tapered to a flat rectangular shape end. FIG. 12B shows an embodiment of the integrated fusion cage 60 with a second distal end 64 tapered to a wedged-shaped end. Such a configuration would be, for example, would be conformal with the wedge-shaped second end 50 of the hollow tube 2, as shown in FIGS. 6-8. FIG. 12C shows an embodiment of the integrated fusion cage 60 with belts of striations imparted to the upper medial surface 70 of the fusion cage 60.

[0414] In regard to FIG. 13, an integrated fusion cage and graft delivery device 1 is shown, comprised of a hollow tubular member 2, which has a first proximate end 6 and a second distal end 8, with a general hollow structure therebetween. The generally hollow tube 2 is shown with one of two lateral openings at the distal end 8 of the tubular member 2 viewable. Also in FIG. 13, the plunger member 12 is shown and the fusion cage 60. The manner of insertion of plunger member 12 into tubular member 2 is also provided, as is the manner of insertion of fusion cage 60 over tubular member 2 and into the fusion cage first end opening 66. Thus, as shown in FIG. 13, the hollow tube 2 allows bone graft material to be inserted into the opening 4 at the proximal end 6 of the hollow tube 2, and ultimately exited from the hollow tube 2 through the second distal end 8 from the lateral openings at the distal end 8 of the hollow tubular member 2 and through the medial openings 68 and/or the lateral openings 69 of the fusion cage 60. In one embodiment as shown in FIG. 13, the lateral openings at the distal end 8 of the hollow tubular member 2 are preferably disposed within a distance from the distal end 8 not exceeding 25% of the total distance (or length) of the hollow tube member 2, more preferably not exceeding 15% of this identified distance, and most preferably not exceeding 10% of this identified distance. In one embodiment as shown in FIG. 13, the lateral openings at the distal end 8 of the hollow tubular member 2 are preferably disposed within a distance from the distal end 8 not exceeding 10 cm of the total distance (or length) of the hollow tube member 2, more preferably not exceeding 8 cm of this identified distance, and most preferably not exceeding 5 cm of this identified distance.

[0415] Referring to FIGS. 14A-D, sequential elevation views of the square-shaped embodiment of the integrated fusion cage and graft delivery device 1 are provided, depicting sequential elevation views of the integrated fusion cage and graft delivery device 1 with the plunger portion 12 fully inserted into the tubular portion 2 and the fusion cage 60 fully inserted over the tubular portion 2. One skilled in the art will appreciate that the openings at the distal end 8 of the hollow tubular member 2 need not be positioned exclusively on one or more lateral sides of the distal end 8 of the tubular member 2 to allow bone graft material to be provided to the surgical site in other than a purely axial or longitudinal direction. Further, one skilled in the art will appreciate that the specific absolute and relative geometries and numbers of lateral and medial openings may vary, for example the distal end 8 of the tubular member 2 may have more than two openings that are of different shape (e.g. oval, rectangular).

[0416] Referring to FIGS. 15A-D, a fusion cage 60 of an integrated fusion cage and graft delivery device portion is shown, which is comprised of a integrated fusion cage 60 that comprises a first proximal end 62 and a second distal end 64 wherein the first proximal end contains an opening 66 adapted to allow fitting and/or engagement to the distal end

8 of the hollow tube 2. This fitting and/or engagement may be over the external surface of the hollow tube 2 or inside the interior of the hollow tube 2. Further, the integrated fusion cage 60 may contain non-smooth surfaces, such as belts or striations, along one or more medial surfaces 70 of the integrated fusion cage 60. The integrated fusion cage 60 is configured such that when a plunger 12, once fully inserted in to the hollow tube 2, is substantially congruent with the hollow interior portion of the hollow tube 2, e.g. both the plunger 12 and the hollow tube 2 are substantially the same shape and/or class and bone graft material is delivered through the integrated fusion cage 60 into the surgical area.

[0417] In a preferred embodiment, the fusion cage 60 has a tapered tip, and several open channels along the medial and lateral surfaces. In a preferred embodiment, the fusion cage 60 is of a square shape and the bone graft delivery portion of the integrated fusion cage and graft delivery device is of a cylindrical shape. The integrated fusion cage and graft delivery device 1 is designed to avoid blocking or impacting bone graft material into a surgical disc space, thereby limiting the bone graft material that may be delivered, and not allowing available fusion space to be fully exploited for fusion.

[0418] In a preferred embodiment, the fusion cage 60 has a keel-shaped tip to separate disk and prevent annular penetration and has internal ramps 72 which assist in directing the bone graft material to one or more lateral openings 69. As the plunger 12 is inserted into the hollow tube 2, bone graft material is directed by the fusion cage internal ramps 72 out the lateral openings 69, and bone additionally bone graft material may flow out the one or more medial openings 68. The plunger end 18 may be configured to be conformal with the internal ramps 72 of the fusion cage 60, as depicted in FIG. 15B. Also, the fusion cage 60 may have dual portals for bone graft discharge, with the medial openings 68 larger than the lateral openings 69. Further, the fusion cage may be designed in variable heights and lengths so that it fits snugly into the prepared disk space.

[0419] In a preferred embodiment as shown in FIGS. 15B-D, the hollow tube 2 is of cylindrical shape and includes one or more locking tabs 80 configured to engage one or more locking slots 82 of the fusion cage 60. The locking tabs 80 may permanently or not permanently engage the locking slots 82, and may be of shape to include rectangular, circular and oblong. The instruments used with the integrated fusion cage and graft delivery device described above in its varying embodiments may include one or more tamps, preferably having a configuration which at least in part corresponds in shape and contour of the hollow tube portion of the delivery device. The one or more tamps may be adapted to correspond further to the shape and contour of the graspable end of the plunger, for use in driving the plunger through the hollow tube portion of the delivery device to ensure any remaining bone graft located in the hollow tube is delivered to the graft receiving area.

[0420] In the embodiment of the device of FIG. 16, the hollow tube 2 engages with the fusion cage 60 via a break-off collar 90 and the plunger 12 inserts into the interior of the hollow tube 2. The plunger 12 is depicted partially inserted into the hollow tube 2. The break-off collar 90 may be severed by any of several means, to include application of torsion and/or rotational force and/or lateral force to break-off collar 90, for example by twisting on the hollow tube 2 and/or the plunger 12.

[0421] In the embodiment of the device of FIG. 17A-B, the hollow tube 2 engages with a connector conduit 100 which in turn connects with the fusion cage 60 via a break-off collar 90. One or more connectors 102 connect the hollow tube 2 with the connector conduit 100. The hollow tube 2 fits over the connector conduit 100. The one or more connectors 102 fit through the hollow tube 2 and the connector conduit 100. The break-off collar 90 may be severed by any of several means, to include application of torsion and/or rotational force and/or lateral force to break-off collar 90, for example by twisting on the hollow tube 2 and/or the plunger 12. In one embodiment of the connector conduit 100, as shown in FIG. 17B, the connector conduit 100 is of circular cross-section.

[0422] Referring to FIGS. 18A-D, sequential elevation views of the square-shaped embodiment of the integrated fusion cage and graft delivery device 1 are provided, depicting sequential elevation views of the integrated fusion cage and graft delivery device 1 with telescoping tubular portion 2 and the fusion cage 60 fully inserted over the tubular portion 2. One skilled in the art will appreciate that the openings at the distal end 8 of the hollow tubular member 2 need not be positioned exclusively on one or more lateral sides of the distal end of the tubular member to allow bone graft material to be provided to the surgical site in other than a purely axial or longitudinal direction.

[0423] In an embodiment of the invention particularly suited for ALIF procedures, a fusion cage 110 as shown in FIGS. 19A-D comprises a hollow internal chamber 114 in fluid communication with bone graft discharge portals 112 and a charging portal 116, which comprises a break-off collar in some embodiments such as those depicted in FIGS. 17A-D. The fusion cage 110 has a substantially cylindrical shape, with the discharge portals 112 located opposite each other on the curved lateral portion of the fusion cage 110 and the charging portal 116 located substantially in between the discharge portals 112 on the curved anterior portion of the fusion cage 110. The curved posterior portion of the fusion cage 110 is substantially devoid of portals from the internal chamber 114 to the exterior of the fusion cage 110. The charging portal 116 is adapted to receive a hollow tube such as the hollow tube 2 shown in other embodiments described herein. Bone graft material enters the internal chamber 114 through a hollow tube connected to the charging portal 116, and exits the internal chamber 114 through the discharge portals 112. The discharge portals 112 are positioned so that when the fusion cage 110 is properly positioned in between two vertebrae, bone graft material discharged therethrough fills the space in between the vertebrae on the lateral sides of the spine, but does not discharge into or fill the anterior or posterior space in between the vertebrae. In embodiments of fusion cage 110 comprising a break-off collar, once the fusion cage 110 is properly positioned and the desired amount of bone graft material has been inserted into the chamber 114 and discharged through the discharge portals 112, the break-off collar is severed from the fusion cage 110 (as described with respect to other embodiments herein) and removed from the patient's body.

[0424] In embodiments that do not comprise a break-off collar, the charging portal 116 of fusion cage 110 is adapted to removably receive a hollow tube (such as the hollow tube 2 shown in other embodiments described herein). For

example, the walls of the charging portal 116 may be threaded so that the hollow tube can be screwed into the charging portal 116.

[0425] The fusion cage 110 preferably has a height of from about 8 millimeters to about 14 millimeters, and a diameter of less than about 36 millimeters. The fusion cage 110 is made from polyether ether ketone (PEEK), titanium, a composite material, or any other material suitable for implantation in a human body. The fusion cage 110 comprises, in some embodiments, ramps within internal chamber 114 to guide bone graft material to discharge portals 112.

[0426] In an embodiment of the invention particularly suited for D-LIF procedures, a fusion cage 120 as shown in FIGS. 20A-D comprises a hollow internal chamber 124 in fluid communication with bone graft discharge portals 122 and a charging portal 126, which in some embodiments—including the embodiment shown in FIGS. 20A-D—comprises a break-off collar. The fusion cage 120 is substantially shaped as a rectangular prism, with the discharge portals 122 located on opposite sides of the fusion cage 120 and the charging portal 126 located on a lateral face of the fusion cage 120. The opposite lateral face of the fusion cage 120 is devoid of portals from the internal chamber 124 to the exterior of the fusion cage 120. The charging portal 126 is adapted to receive a hollow tube such as the hollow tube 2 shown in other embodiments described herein. Bone graft material enters the chamber 124 through a hollow tube connected to the charging portal 126, and exits the internal chamber 124 through the discharge portals 122. The discharge portals 122 are positioned so that when the fusion cage 120 is properly positioned in between two vertebrae, bone graft material discharged therethrough fills the space in between the vertebrae towards the anterior and posterior of the spine, but does not discharge into or fill the lateral space in between the vertebrae. As with other embodiments described herein, in embodiments that comprise a break-off collar, once the fusion cage 120 is properly positioned and the desired amount of bone graft material has been inserted into the chamber 124 through charging portal 126 and discharged through the discharge portals 122, the break-off collar is severed from the fusion cage 120 (as described with respect to other embodiments herein) and removed from the patient's body.

[0427] In embodiments that do not comprise a break-off collar, the charging portal 126 is adapted to removably receive a hollow tube (such as the hollow tube 2 shown in other embodiments described herein). For example, the internal walls of charging portal 126 may be threaded so that the hollow tube can be screwed into the charging portal 126.

[0428] The fusion cage 120 preferably has a height of from about 8 millimeters to about 14 millimeters, and a length of from about 22 millimeters to about 36 millimeters. The fusion cage 120 is made from polyether ether ketone (PEEK), titanium, a composite material, or any other material suitable for implantation in a human body. The fusion cage 120 comprises, in some embodiments, ramps within internal chamber 124 to guide bone graft material to discharge portals 122.

[0429] Referring now to FIGS. 21A-D, in embodiments of the invention particularly suited for use in connection with a vertebrectomy, a fusion cage 130 comprises a substantially cylindrical wall surrounding an internal chamber 134. Thus, the fusion cage 130 has a substantially cylindrical shape. Internal chamber 134 is open at the top and the bottom of

fusion cage 130, and lateral portions 132 of the cylindrical wall of the fusion cage 130 are porous to bone graft material (i.e. bone graft slurry). Anterior and posterior portions 138 of the cylindrical wall of fusion cage 130 in between porous portions 132 are impervious to bone graft material. A charging portal 136—which in some embodiments, including the embodiment shown in FIGS. 21A-D, comprises a break-off collar—is positioned on an impervious portion 138 of fusion cage 130. The charging portal 136 is adapted to receive a hollow tube such as the hollow tube 2 shown in other embodiments described herein. Bone graft material enters the chamber 134 through a hollow tube connected to the charging portal 136, and exits the chamber 134 through porous wall portions 132. The porous wall portions 132 are positioned so that when the fusion cage 130 is properly positioned in between two vertebrae, bone graft material discharged therethrough fills the space in between the vertebrae on either side of the spine, but the impervious wall portions 138 prevent bone graft material from discharging into the anterior or posterior space in between the vertebrae, thus preventing bone graft material from pushing against the spinal cord. In embodiments of fusion cage 130 comprising a break-off collar, once the fusion cage 130 is properly positioned and the desired amount of bone graft material has been inserted into the chamber 134 through charging portal 136 and discharged through the porous wall portions 132, the break-off collar 136 is severed from the fusion cage 130 (as described with respect to other embodiments herein) and removed from the patient's body.

[0430] In embodiments that do not comprise a break-off collar, the charging portal 136 is adapted to removably receive a hollow tube (such as the hollow tube 2 shown in other embodiments described herein). For example, the internal walls of the charging portal 136 may be threaded so that the hollow tube can be screwed into the charging portal 136.

[0431] The fusion cage 130 preferably has a height equal to or greater than the vertebra or vertebrae it is intended to replace, and a diameter of less than about 36 millimeters. The fusion cage 130 is made of polyether ether ketone, titanium, a composite material, or any other material suitable for implantation in a human body. In some embodiments, ramps in the internal chamber 134 guide the bone graft material to the porous lateral faces 132.

[0432] Referring now to FIGS. 22-33, another embodiment of the device for delivering bone graft is provided. In regard to FIGS. 22-28, integrated fusion cage and graft delivery device 1 is shown. FIG. 22 is a perspective view of the device 1, FIG. 23 a perspective exploded view, FIG. 24 a top plan view, FIG. 25 a front elevation view, FIG. 26 a right elevation view, FIG. 27 is a bottom plan view, and FIG. 28 is a cross-sectional view of section A-A of FIG. 25.

[0433] Device 1 is comprised of a hollow tubular member or hollow tube 2, a plunger 12 which fits within the hollow tube 2, and a funnel 30. The funnel 30 engages the upper or distal or first end 6 of the hollow tube, and comprises a sleeve 32 and opening 34. Medical material, such as bone graft material, is inserted into opening 34 of funnel 30, which in turn enters hollow tube 2. Hollow tube 2 comprises hollow tube first exterior surface 3, hollow tube second exterior surface 5, first end 6, second end 8, and hollow tube first distal opening 7. Hollow tube 2 is generally of symmetrical shape such that first exterior surface 3 comprises two such surfaces opposite or at 180 degrees from one

another, and second exterior surface 5 comprises two such surfaces opposite or at 180 degrees from one another. Also, hollow tube first distal opening 7 is positioned on each of two opposite sides of hollow tube 2 at second end 8, each opening from hollow tube first exterior surface 3.

[0434] Funnel 30 is configured with sleeve 32 such that funnel 30 may be positioned at second end 8 of hollow tube 2 such that hollow tube may fit through funnel 30, enabling funnel 30 to move along hollow tube 2 from second end 8 of hollow tube 2 to first end 6 of hollow tube 2 until funnel 30 engages first end 6 of hollow tube, such as at protrusion or shelf depicted in FIG. 23.

[0435] Plunger 12 comprises handle 16 at upper or proximal end of plunger 12, plunger distal or second end 18. Plunger second end 18 comprises distal first surface 13, distal second surface 14 and distal third (or bottom) surface 15. Plunger second end 18 is generally of symmetrical shape such that distal first surface 13 comprises two such surfaces opposite or at 180 degrees from one another, and distal third surface 15 comprises two such surfaces opposite or at 180 degrees from one another. Plunger 12 is configured such that second end 18 forms a congruent or conformal engagement with the interior of the hollow tube 2. Stated another way, the plunger second end 18 fits within the hollow tube 2 so as to slide within the hollow tube with minimal to no effective spacing between the exterior surface of the plunger second end 18 and the interior of the hollow tube 2, thereby forcing through bone graft material positioned in the hollow tube 2 through the hollow tube when the plunger 12 (and thus its second end 18) is axially moved from hollow tube first end 6 to hollow tube second end 8.

[0436] In regard to FIGS. 29-31, further features of the plunger 12 are described. FIG. 29 is a front elevation view of the plunger element of the device shown in FIG. 22, FIG. 30 is a cross-sectional view of section B-B of FIG. 29, and FIG. 31 is a cross-sectional view of section C-C of FIG. 29. Plunger 12 comprises handle 16 at upper or proximal end of plunger 12, plunger distal or second end 18. Plunger second end 18 comprises distal first surface 13, distal second surface 14 and distal third (or bottom) surface 15. Plunger medial portion 17 forms a cross configuration, as depicted in FIG. 30, such that distal first surfaces 13 are of reduced width relative to width at second end 18. Similarly, plunger distal second surfaces 14, at plunger medial portion 17, are of reduced width relative to width at second end 18. At distal end 18 of plunger 12, plunger cross-section is a rectangle, as depicted in FIG. 31.

[0437] In regard to FIGS. 32 and 33, additional detail of the distal portion of device 1 are provided. FIG. 32 is a detailed view of a portion of the device 1 shown in FIG. 22 and FIG. 33 is a cross-sectional view of section D-D of FIG. 32. Each of FIGS. 32 and 33 depict the device 1 when the plunger 12 is fully inserted into the hollow tube 2, and the plunger distal third surface 15 has engaged and is in contact with the hollow tube distal interior ramp 9. Hollow tube distal interior ramp 9 comprises hollow tube distal interior ramp surfaces 9A, symmetrically positioned about the middle of the hollow tube second end 8. Hollow tube distal interior ramp surfaces 9A are of curvilinear shape forming a terminus, and urge bone graft material, when disposed within the hollow tube 2, to substantially exit the pair of first distal openings 7 of the device 1.

[0438] Referring now to FIGS. 36-39 another embodiment of an integrated fusion cage and graft delivery device 1 is

provided. With reference to FIGS. 36-39, the integrated fusion cage and graft delivery device 1 comprises plunger 12, hollow tube 2, fusion cage 60 and ejection tool 140. The fusion cage 60 comprises fusion cage second or distal end 64 with tapered end feature and fusion cage first or proximal end 62 comprising fusion cage collar 92, fusion cage collar face 93 and fusion cage collar cavity 94. Hollow tube 2 comprises hollow tube second end 8 which engages fusion cage collar 92 by fitting over fusion cage collar 92 in a press or interference fit. Plunger 12 fits within hollow tube 12, and further may optionally fit within fusion cage collar cavity 94 so as to enter into interior of fusion cage 60 as previously described above.

[0439] Ejection tool 140 comprises ejection tool second or distal end 152 and ejection tool first or proximal end 142. Ejection tool second end 152 engages fusion cage collar face 93 to apply force or push fusion cage 60 from engagement with hollow tube 2. Ejection tool second end 152 is configured such that it may not travel past or into the fusion cage. When sufficient axial force is applied to the ejection tool 140 in the direction of the fusion cage 60, the interference fit that secures the fusion cage 60 (at fusion cage collar 92) to hollow tube 2 (at second end 8 of hollow tube) is overcome and the fusion cage 60 is released or disengaged from the hollow tube 2. Ejection tool 140 further comprises an ejection tool L-cut 151 that engages knobs 6A of hollow tube 2. In one embodiment, knobs 6A of hollow tube 2 are configured to additionally or alternatively engage L-cuts of the funnel 30 at funnel sleeve 32 (See FIG. 23). Plunger 16 further comprises handle 16 and plunger stop 16A which engages upper portion of hollow tube 2. Plunger stop 16A may be configured to prevent plunger distal most portion from entering fusion cage collar cavity 94 and therefore further prevent entry into interior of fusion cage 60.

[0440] Fusion cage 60 further comprises fusion cage internal ramps 72 as described above. The fusion cage internal ramps 72 may be symmetrical about a centerline of the device 1, and may be linear or sloped inwardly. In one embodiment, plunger stop 16A may be configured to prevent plunger distal most portion from striking or contacting fusion cage internal ramps 72 but otherwise allowing entry into fusion cage collar cavity 94 and therefore also allow entry into interior of fusion cage 60.

[0441] Fusion cage 60 further comprises fusion cage first opening or port pair 65 and fusion cage second opening or port pair 67. Fusion cage first opening pair 65 are symmetric about a vertical plane intersecting a centerline of the fusion cage 60, and are located such that at least a portion of the openings are adjacent the tip of the fusion cage internal ramps 72. The fusion cage first opening pair 65 are of an oblong racetrack shape, but in other embodiments may be oval, circular and rectangular. The fusion cage second opening pair 67 are of an oval shape, but in other embodiments may be oblong racetrack, circular and rectangular. The fusion cage may have rounded or no square edges, and may have a non-smooth exterior surface or any or all portions. That is, the fusion cage 60 may have ridges, bumps, contours, sawtooth profile edges along or on top of any or all exterior surfaces, such as surfaces adjacent the fusion cage second opening pair 67 and/or fusion cage first opening pair 65.

[0442] Referring now to FIGS. 40-41, another embodiment of an integrated fusion cage and graft delivery device 1 is provided. FIG. 40 is a front perspective view of an

integrated fusion cage and graft delivery device 1, and FIG. 41 is a closed-up front perspective view of a portion of the device of FIG. 40. The embodiment of FIGS. 40-41 comprises a pair of fusion cage tab extensions 96, each of which comprises a fusion cage tab extension latch 97. Integrated fusion cage and graft delivery device 1 comprises plunger 12, hollow tube 2 and fusion cage 60. FIG. 40 depicts the integrated fusion cage and graft delivery device 1 with plunger 12 fully inserted into hollow tube 2 such that plunger stop 16A engages upper portion of hollow tube 2. The fusion cage 60 comprises fusion cage second or distal end 64 with tapered end feature and fusion cage first or proximal end 62 comprising fusion cage collar 92, fusion cage collar face 93 and fusion cage collar cavity 94.

[0443] Fusion cage 60 further comprises fusion cage internal ramps 72 as described above. The fusion cage internal ramps 72 may be symmetrical about a centerline of the device 1, and may be linear or sloped inwardly. Fusion cage 60 further comprises fusion cage first opening or port pair 65 and fusion cage second opening or port pair 67. Fusion cage first opening pair 65 are symmetric about a vertical plane intersecting a centerline of the fusion cage 60, and are located such that at least a portion of the openings are adjacent the tip of the fusion cage internal ramps 72. The fusion cage first opening pair 65 are of an oblong racetrack shape, but in other embodiments may be oval, circular and rectangular. The fusion cage second opening pair 67 are of an oval shape, but in other embodiments may be oblong racetrack, circular and rectangular. The fusion cage may have rounded or no square edges. Fusion cage 60 has fusion cage surface texture 61, depicted as a series of lateral sawtooth-like ridges.

[0444] Fusion cage tab extensions 96, each of which comprises a fusion cage tab extension latch 97, function, among other things, to increase stability of the interface or connection between the distal end of the hollow tube 2 and the fusion cage 60. The fusion cage tab extension latches 97 may be configured to engage corresponding grooves on the interior surface of the hollow tube 2. The fusion cage tab extensions 96 fit inside the end of the hollow tube and, in one embodiment, provide a force directed outwards to or against the interior of the hollow tube. The vertical height and longitudinal (axial) length of the fusion cage tab extensions 96 provide more secure fit between the hollow tube 2 and the fusion cage 60 by restricting rotational movement, for example, of the hollow tube 2 with respect to the fusion cage 60. After bone graft material is provided to the fusion cage 60 by way of the plunger 12 (as described above), the fusion cage tab extensions 96 may be broken-off by application of a tool, such as the ejection tool 140, engaged with the fusion cage tab extension latches 97 so as to fatigue or otherwise sever the fusion cage tab extensions 96.

[0445] Referring now to FIGS. 42-43, another embodiment of the ejection tool 140 of an integrated fusion cage and graft delivery device 1 is provided. FIG. 42 is a close-up front perspective view of the ejection tool first end 142, and FIG. 43 is a cut-away cross-sectional view of FIG. 42. Ejection tool 140 comprises ejection tool cover 144 which engages ejection tool wings 149. Ejection tool 140 engages with hollow tube 2 at hollow tube knobs 6A via ejection tool L-cuts 151. Ejection tool cover 144 comprises cylindrically-shaped ejection tool cover cavity 145 which fits over cylindrically-shaped ejection tool wings cavity 150 and over spring cover 146. Spring cover is secured to ejection tool

cover 144 by spring cover attachment 147, which may be a pin, a screw or other means known in the art, and further fits around at least a portion of coiled spring 148. When ejection tool cover 144 is pushed downward toward fusion cage 60, the spring 148 compresses and imparts a force in the opposite direction, thereby returning the ejection tool cover 144 to its original (retracted) position. In use, after securing the ejection tool first end 142 to hollow tube 2 as described above, the user (e.g. surgeon) squeezes the ejection tool cover 144 against the ejection tool wings 149, thereby advancing the ejection tool rod 160 downwards inside the hollow tube so as to engage the fusion cage 60 at the fusion cage collar face 93 and release or disengage the fusion cage 60 from the hollow tube 2. The ejection tool 140 and hollow tube 2 may then be removed from the surgical site (e.g. spinal disk space) as one unit, leaving the fusion cage in the surgical site.

[0446] FIG. 44 is a close-up cut-away cross-sectional view of one embodiment of the integrated fusion cage and graft delivery device 1. FIG. 44 depicts a configuration of the integrated fusion cage and graft delivery device 1 wherein the plunger 12 is configured to traverse the length of the hollow tube 2, past the fusion cage collar 92 and into the fusion cage 60, stopping just prior to engaging the tip of the fusion cage internal ramps 72. Fusion cage 60 is depicted with fusion cage first opening pair 65 and fusion cage second end 64.

[0447] FIGS. 45-48 are scaled drawings of, respectively, the fusion cage 60, the hollow tube 2, the plunger 12 and the ejection tool 140 of yet another embodiment of the integrated fusion cage and graft delivery device 1, and operate in coordination with one another.

[0448] FIGS. 45A-G provide scaled views of one embodiment of the fusion cage element of yet another embodiment of the integrated fusion cage and graft delivery device configured to operate with the hollow tube of FIGS. 46A-H, plunger of FIGS. 47A-D and ejection tool of FIGS. 48A-E. Fusion cage 60 comprises fusion cage second or distal end 64 with tapered end feature and fusion cage first or proximal end 62 comprising fusion cage collar 92, fusion cage collar face 93 and fusion cage collar cavity 94. Fusion cage 60 further comprises fusion cage first opening or port pair 65, fusion cage second opening or port pair 67, fusion cage surface texture 61 and fusion cage internal ramps 72.

[0449] FIGS. 46A-H provide scaled views of one embodiment of the hollow tube (aka snap on cannula) of the integrated fusion cage and graft delivery device configured to operate with the fusion cage element of FIGS. 45A-G, plunger of FIGS. 47A-D and ejection tool of FIGS. 48A-E. Hollow tube 2 comprises first end 6 with knobs 6A and second end 8 comprising hollow tube cage clamp 8A and hollow tube cage clamp radial surface 8B. Hollow tube cage clamp radial surface 8B is configured to engage fusion cage collar 92, for example by an interference or friction fit (i.e. to "snap-on"). Other means of connection comprise those known to those skilled in the art, such as a threaded-screw engagement and a tongue and groove engagement.

[0450] FIGS. 47A-D provide scaled views of one embodiment of the plunger (aka snap on plunger) of the integrated fusion cage and graft delivery device configured to operate with the fusion cage element of FIGS. 45A-G, hollow tube of FIGS. 46A-H, and ejection tool of FIGS. 48A-E. Plunger 12 comprises handle 16, plunger stop 16A, plunger medial

portion 17 and second end 18. Second end 18 may be configured to pass into and/or through fusion cage collar cavity 94.

[0451] FIGS. 48A-E provide scaled views of one embodiment of the ejection tool (aka cage insertion tool) of the integrated fusion cage and graft delivery device configured to operate with the fusion cage element of FIGS. 45A-G, hollow tube of FIGS. 46A-H and plunger of FIGS. 47A-D. Ejection tool 140 comprises ejection tool second or distal end 152, ejection tool first or proximal end 142 and ejection tool stop 143. Ejection tool second end 152 engages fusion cage collar face 93 to apply force or push fusion cage 60 from engagement with hollow tube 2. Ejection tool second end 152 is configured such that it may not travel past or into the fusion cage.

[0452] A method of use of the integrated fusion cage and graft delivery device 1 as depicted in any of the aforementioned embodiments of FIGS. 37-48 would be performed as follows. The fusion cage 60 is attached to the hollow tube 2 by way of the above-discussed interference fit at fusion cage collar 92 and interior surface of distal end of hollow tube 2. Funnel 30 is then attached to upper portion of hollow tube at first or upper or proximal end of hollow tube 2 via knobs 6A. Bone graft or other suitable substance as known to one skilled in the art is inserted at upper or first end 6 of hollow tube 2. Plunger 12 is then inserted into hollow tube 2 at upper or proximal end of hollow tube and pushed or advanced axially down interior of hollow tube, thereby urging or pushing or advancing the bone graft material down the hollow tube 2 toward fusion cage 60. Bone graft then proceeds into the fusion cage 60 whereby it at least substantially fills fusion cage 60 interior and further engages fusion cage internal ramps 72 and emits bone graft material through fusion cage first opening pair 65 and fusion cage second opening pair 67 and thus enters surgical area (e.g. a spinal surgical area). Upon sufficient user (i.e. surgeon) selectable injection of bone graft material into surgical site and fusion cage 60, the plunger 12 is retracted and removed from the hollow tube 2 by opposite axial movement, i.e. by moving the plunger 12 away from the fusion cage 60. The funnel 30 may then be optionally removed. Next, the ejection tool 140 is inserted into hollow tube 2 at upper or proximal end. Ejection tool 140 is advanced until ejection tool second end 152 engages fusion cage collar face 93, whereupon downward force is applied to push fusion cage 60 from engagement with hollow tube 2. As discussed, ejection tool second end 152 is configured such that it may not travel past or into the fusion cage. When sufficient axial force is applied to the ejection tool 140 in the direction of the fusion cage 60, the interference fit that secures the fusion cage 60 (at fusion cage collar 92) to hollow tube 2 (at second end 8 of hollow tube) is overcome and the fusion cage 60 is released or disengaged from the hollow tube 2. The engagement tool 140, and the hollow tube 2 in which it is inserted, are then removed from the surgical site, leaving a fusion cage at least substantially filled with bone graft and a surgical site also at least substantially filled with bone graft.

[0453] In one embodiment, all or a portion of fusion cage collar 92 is of a material different than the remainder of the fusion cage 60, e.g. comprising a metal alloy. In one embodiment, a portion of the distal end of the hollow tube 2 is of a material different than the remainder of the hollow

tube 2, e.g. comprising a metal alloy. In one embodiment, a portion of the distal end of the ejection tool is comprised of a metal alloy.

[0454] In one embodiment of the device, the tip of the hollow tube and/or fusion cage may separate under a threshold pressure as applied axially from the inside of the hollow tube or fusion cage respectively. Such a user-selected threshold would allow bone graft material to enter the surgical site if bone graft material becomes clogged in the hollow tube and/or fusion cage.

[0455] Referring now to FIGS. 49-62, various embodiments and components of a fusion cage 60 with expandable fusion cage feature are depicted. Generally, the fusion cage 60 comprises an upper plate 200, lower plate 210, front block 220, rear block 230, and expansion screw 240. By rotating the expansion screw 240, each of the front block 220 and rear block 230 advance toward the center of the fusion cage 60 while simultaneously advancing each of the lower plate 210 and upper plate 220 away from the center of the fusion cage 60, thereby expanding the overall height of the fusion cage 60. Each of the unexpanded state of the fusion cage 60 and expanded state of the fusion cage 60 are understood most immediately by comparing FIGS. 49A and 50A, respectively. The fusion cage 60 may be expanded in a scalable manner to a maximum threshold height value. At the maximum threshold height value of the fusion cage 60, each of the front block 220 and rear block 230 are unable to continue to advance toward the center of the fusion cage 60 (such a state is shown as FIG. 50A). It is noted that in the embodiments of FIGS. 49-60, the lower plate 210 and upper plate 220 remain substantially parallel in all configurations. Stated another way, the lower plate 210 and upper plate 220 remain substantially parallel in the unexpanded fusion cage 60 state (e.g. FIG. 49A), in the maximum threshold height value expanded state of the fusion cage 60 (e.g. FIG. 50A), and in all states in between. In contrast, in the fusion cage 60 embodiment of FIGS. 61A-B, the lower plate 210 and upper plate 220 maintain a relative vertical wedge angle, and in the embodiment of FIGS. 62A-B, the lower plate 210 and upper plate 220 maintain a relative horizontal wedge angle.

[0456] Expansion screw 240 comprises expansion screw head 242, expansion screw tip 244 and expansion screw disk 246. The expansion screw 240 rotationally engages each of the front block 220 via front block aperture 227 and rear block 230 via rear block aperture 237. The expansion screw disk 246 engages each of the upper plate 200 via upper plate slot 206 and the lower plate 210 via lower plate slot 216. The expansion screw 240 is configured with opposing screw threads on each side of expansion screw disk 246. Each of the front block aperture 227 and rear block aperture 237 are tapped to accept the expansion screw 240 threads. As such, as the expansion screw 240 is rotated, each of the opposing screw threads engage each of the front block aperture 227 and rear block aperture 237 and advance the respective front block 220 and rear block 230 toward the center of the fusion cage 60. As provided in FIGS. 57A-C, expansion screw 240 comprises left hand threads on a first portion of expansion screw 240 proximal to the expansion screw head 242 and right hand threads on a second portion of expansion screw 240 distal to the expansion screw head 242. Thus, the left hand threads engage the rear block aperture 237 and the right hand threads engage the front block aperture 227. The left hand and right hand threads are symmetrical although in opposite directions such that rotation of the expansion screw

240 results in equal movement of each of the front block **220** and rear block **230**. Stated another way, the operation of the expansion screw **240** with respect to the front block **220** and rear block **230** is such that each block advances toward (or retreats from) the center of the fusion cage **60** in equal amounts or distance with rotation of the expansion screw **240**.

[**0457**] In an alternate embodiment, the thread configurations (and respective tapped apertures) are reversed. The expansion screw head **242** is fitted with a star terminus so as to engage a star (a.k.a. Torx™) screwdriver. In other embodiments, the expansion screw head **242** is fitted with a star screwhead (i.e. female, i.e. receptor, end) so as to engage a star screwdriver (i.e. a male screwdriver.) In other embodiments, any means of screw drive known to those skilled in the art may be employed, to include slot or regular, phillips, pozidriv, square, Robertson, hex, hex socket, tri-wing, spanner head, clutch, double-square, triple-square, polydrive, spline drive, double hex, Bristol and pentabolular.

[**0458**] Front block **220** comprises front block upper rail **222**, front block lower rail **224**, front block nose **225**, front block ramp **226** and front block aperture **227**. As described above, front block aperture **227** is tapped to engage the threads of expansion screw **240**. Each of front block upper rail **222** and front block lower rail **224** engage, respectively, upper plate track **205** and lower plate track **215**. Such a configuration or arrangement may be referred to as a dovetail joint slider. As the expansion screw is rotated, front block upper rail **222** moves or slides within upper plate track **205** toward the center of fusion cage and front block lower rail **224** moves or slides within lower plate track **215** toward the fusion cage. Because of the wedged-shaped geometry of each of the front block **220** and rear block **230**, such movement toward the center of the fusion cage **60** results in an expansion (in height) of the fusion cage **60**. Such movement also causes a reduction in the length of the fusion cage **60**, in that the front block nose **225** retreats to the interior of the fusion cage **60**, thereby leaving the upper plate front **201** and lower plate front **211**, or the expansion screw tip **244**, to define the most distal end of the fusion cage **60**. Such a change in fusion cage **60** length is apparent by comparing, for example, FIGS. **49A** and **50A**. In one embodiment, the expansion screw tip **244** is configured such that, when the fusion cage **60** is in a maximum expansion state, the expansion screw tip **244** does not extend beyond a plane between the most distal end of the upper plate front **210** and lower plate front **211**. It is noted that in all states of expansion of the fusion cage **60**, no aperture is formed at the nose of the fusion cage **60**, e.g. between the front block **220** and each of the upper plate **200** and lower plate **210**. Stated another way, in all states of expansion of the fusion cage **60**, to span unextended state (e.g. FIG. **49a**) and maximum extended state (e.g. FIG. **50A**), no path for egress of material (e.g. bone graft) is provided from the interior of the fusion cage **60** through the front or nose area (i.e. in a longitudinal direction.) In an alternate embodiment, the front block **220** is configured with one or more apertures, e.g. on one or more of front block ramp **236**, so as to allow a path for said egress.

[**0459**] Front block **220** is symmetrical about a vertical plane (i.e. a plane running parallel to each of front block upper rail **222** edge and front block lower rail **224** edge longitudinal axes and bisecting front block aperture **227** at 12 and 6 o'clock positions.) Front block is symmetrical about a horizontal plane (i.e. a plane running parallel to each

of front block upper rail **222** surface and front block lower rail **224** surface and bisecting front block aperture **227** at 3 and 9 o'clock positions.)

[**0460**] Rear block **230** comprises rear block groove **231**, rear block upper rail **232**, rear block lower rail **234**, rear block ramp **236**, rear block aperture **237**, rear block aft **238** and rear block detent **239**. As described above, rear block aperture **237** is tapped to engage the threads of expansion screw **240**. Each of rear block upper rail **232** and rear block lower rail **234** engage, respectively, upper plate track **205** and lower plate track **215**. As the expansion screw is rotated, rear block upper rail **232** moves or slides within upper plate track **205** toward the center of fusion cage and rear block lower rail **234** moves or slides within lower plate track **215** toward the fusion cage. Because of the wedged-shaped geometry of each of the rear block **230** and rear block **230**, such movement toward the center of the fusion cage **60** results in an expansion (in height) of the fusion cage **60**. The rear block aft **238** is configured such that when the fusion cage **60** is in an unexpanded state (e.g. FIG. **49A**), the rear block aft **238** is flush with the edges of each of upper plate rear **202** and lower plate rear **212**. In one embodiment, the expansion screw head **242** is configured such that, when the fusion cage **60** is in an unexpanded state, the expansion screw head **242** is flush with the edges of each of upper plate rear **202**, lower plate rear **212** and rear block aft **238**.

[**0461**] Rear block **230** is similarly symmetrical about the same relative axes as front block **220**. That is, rear block **230** is symmetrical about a vertical plane (i.e. a plane running parallel to each of rear block upper rail **232** edge and rear block lower rail **234** edge longitudinal axes and bisecting rear block aperture **237** at 12 and 6 o'clock positions.) Rear block is symmetrical about a horizontal plane (i.e. a plane running parallel to each of rear block upper rail **232** surface and rear block lower rail **234** surface and bisecting front block aperture **237** at 3 and 9 o'clock positions.)

[**0462**] Upper plate **200** comprises upper plate front **201**, upper plate rear **202**, upper plate opening **203**, upper plate surface texture **204**, upper plate track **205**, upper plate slot **206**, upper plate ridge **209** and plate tab **217**. Upper plate surface texture **204** is formed of consecutive ridges in a lateral orientation, i.e. left-right rather than fore-aft. In alternate embodiments, the upper plate surface texture **204** is formed in a longitudinal direction, i.e. fore-aft rather than left-right. In other alternate embodiments, the upper plate surface texture **204** is of other configurations known to those skilled in the art, to comprise grooves and ridges. Upper plate opening **203** comprises a pair of oval race-track openings. In other embodiments, upper plate opening **203** is a single opening, is of circular shape, is of rectangular shape, or other shapes known to those skilled in the art and/or conventionally used in fusion cages. Upper plate **200** is symmetric about a vertical plane running longitudinally between the two upper plate openings **203** and the upper plate track **205**.

[**0463**] Lower plate **210** comprises lower plate front **211**, lower plate rear **212**, lower plate opening **213**, lower plate surface texture **214**, lower plate track **215**, lower plate slot **216**, lower plate ridge **219** and plate tab **217**. Lower plate surface texture **214** is formed of consecutive ridges in a lateral orientation, i.e. left-right rather than fore-aft. In alternate embodiments, the lower plate surface texture **214** is formed in a longitudinal direction, i.e. fore-aft rather than left-right. In other alternate embodiments, the lower plate

surface texture **214** is of other configurations known to those skilled in the art, to comprise grooves and ridges. Lower plate opening **213** comprises a pair of oval race-track openings. In other embodiments, lower plate opening **213** is a single opening, is of circular shape, is of rectangular shape, or other shapes known to those skilled in the art and/or conventionally used in fusion cages. Lower plate **210** is symmetric about a vertical plane running longitudinally between the two lower plate openings **213** and the lower plate track **215**.

[**0464**] When the fusion cage **60** is in the unexpanded state (e.g. FIG. **49A**), upper plate ridge **209** and lower plate ridge **219** are in communication, i.e. are touching or substantially touching.

[**0465**] Upper plate **200** and lower plate **210** are identical, and are assembled to form the fusion cage **60** by positioning in opposite orientations. Stated another way, upper plate **200** and lower plate **210** are positioned to mirror one another about a horizontal plane through the center and middle height of the fusion cage **60**. Among other things, identical upper plate **200** and lower plate **210** allow fewer unique parts to be used to assemble the fusion cage **60**, thereby reducing costs, reducing complexity, and increasing robustness. Also, the fusion cage **60** design is such that the fusion cage remains structural stable and strong while expanded, to include when in the maximum expanded state, as enabled by the type and degree of connections between the wedged blocks and the plates. That is, as enabled by the rail/track connections between the blocks and the plates, and also the adjacent surface connections of the wedged blocks (i.e. the area adjacent the rails of each block) and the plates.

[**0466**] The fusion cage **60** is a modular system in that components may be combined to cover several sizes and configurations. Although each of the upper plate **200** and lower plate **210** are identical, these paired plates may be provided in several sizes. For example, as provided in FIGS. **54A-F**, a set of paired (i.e. one upper plate **200** and one lower plate **210**) plates may be provided in lengths of 26 mm, 32 mm and 36 mm. Also, the paired wedged blocks (i.e. a front block **220** and a rear block **230**) may be provided in assorted sizes, e.g. an 8 mm and an 11 mm size, as depicted in FIGS. **55A-E**. Lastly, the expansion screw **240** may be provided in various configurations, as provided in FIGS. **57A-C**, to match combinations of paired plates and paired wedged blocks. In one embodiment, the fusion cage **60** may be constructed to range in size from 8×26 mm to 14×36 mm.

[**0467**] In one embodiment, the expansion screw **240** comprises stainless steel and titanium, and the upper plate **200** and lower plate **210** comprise stainless steel, titanium and polyether ether ketone (PEEK.)

[**0468**] Additional components that are configured to engage the fusion cage **60** are provided in FIGS. **63-72**. Generally, the additional components comprise those that allow the fusion cage **60** to be positioned at or within a surgical site, to expand and/or contract the fusion cage **60**, deliver bone graft material within the fusion cage **60** and to the surrounding surgical site, and detach the fusion cage.

[**0469**] With attention to FIGS. **63-69**, a fusion cage **60** with expandable fusion cage feature, as described above, is depicted with an installer/impactor **250** component. The installer/impactor **250** comprises installer/impactor tip **252**, installer/impactor aperture **253**, installer/impactor ridge **254**, installer/impactor channel **255**, installer/impactor ramp **256** and installer/impactor handle **258**. The installer/impactor

aperture **253** is configured to engage the rear block aperture **253** and the installer/impactor ridges **254** are configured to engage the rear block detent **239**; once these elements are engaged, the fusion cage **60** may be accurately and reliably positioned at the surgical site. The installer/impactor handle **258**, with integrated striking plate, may be used to assist in guiding the fusion cage **60** into place, and further allows a “persuading” with a mallet. The installer/impactor handle **258** attaches in place with, for example, a ball detent or similar feature that secures the installer/impactor handle **250** in place yet allows quick and easy removal.

[**0470**] FIG. **65A** details the installer/impactor **250** engaged with the fusion cage **60**, the fusion cage **60** in an unexpanded state. FIG. **65B** details the same system and configuration of FIG. **65A**, except that the expansion driver **260**, with expansion driver handle **268**, is engaged with the fusion cage **60**. More specifically, the expansion driver **260**, which fits within the installer/impactor **250**, engages the expansion screw head **242** (e.g. the expansion screw head **242** is a male star or Torx™ screw head that engages with the female star or Torx™ screwdriver end of the expansion driver **260**.) FIG. **66** details the installer/impactor **250** engaged with the fusion cage **60**, the fusion cage **60** in an expanded state (as a result of the expansion driver **260** engaging the expansion screw head **242** and, through rotation of the expansion screw head **242**, expanding the fusion cage **60**), and the hollow tube **2** fitted over the installer/impactor **250**.

[**0471**] After the fusion cage **60** is expanded to the desired degree, i.e. height, the expansion driver **260** disengages from the expansion screw head **242** and is removed. The hollow tube **2** is then slid downward or distally so as to engage the fusion cage **60**, and the installer/impactor **250** must be removed (so as to allow bone graft material to be delivered via hollow tube **2** into the fusion cage **60** and the surrounding surgical site.) FIG. **67** details the installer/impactor **250** engaged with the fusion cage **60**, the fusion cage **60** in an expanded state, and the hollow tube **2** fitted over the installer/impactor **250** and engaged with the fusion cage **60**; this is the configuration of the an integrated expandable fusion cage and bone graft delivery device when the installer/impactor **250** must be removed so as to enable bone graft delivery. In an alternate embodiment, the installer/impactor **250** is not used, and instead the hollow tube **2** is used to position the fusion cage **60** by way of the hollow tube external ramp **280** and/or hollow tube notch **282**. The hollow tube external ramp **280** may form a press-fit with the fusion cage **60**. The hollow tube may also engage the fusion cage **60** via the hollow tube notch **282**, the hollow tube notch **282** configured to engage the rear block aft **238** portion above and below the rear block aperture **237**.

[**0472**] FIGS. **68A-B** detail a means with which the installer/impactor **250** may be removed by use of removal pliers **270**. The removal pliers **270** are configured to engage the first end **6** of hollow tube and the proximal end of the installer/impactor **250**, so as to pull the installer/impactor **250** from engagement with the fusion cage **60**. Note that the installer/impactor **250** is configured to allow the installer/impactor tip **252** to spread apart over the rear block detent **239** groove, as facilitated by the installer/impactor channel **255**.

[**0473**] After the fusion cage **60** has been positioned in the surgical site and expanded as required, bone graft material may be inserted into the fusion cage **60** and into the

surrounding surgical site. FIG. 69 presents an exploded perspective view of the fusion cage 60 with expandable fusion cage feature engaged with the hollow tube 2 component and funnel 30 component, as configured to engage with the plunger 12 component. As described previously, bone graft material is placed into the funnel 30 and advanced down the hollow tube 2 by the plunger 12, whereby bone graft material flows into the fusion cage 60 and outward into the surgical site via one or more of the upper plate openings 203, lower plate openings 213, and lateral openings distal to the front block 230.

[0474] FIGS. 70-72 depict an alternate embodiment of hollow tube 2 and fusion cage 60 to enable the fusion cage 60 to be accurately and reliably positioned at a surgical site. The hollow tube 2 comprises two pairs of hollow tube slots 284, each with a hollow tube slot aperture 285 at the distal end. Each hollow tube slot 284 is disposed at least partially on the hollow tube external ramp 280. Each of the upper plate 200 and lower plate 210 comprise a pair of plate tabs 217, each of which engages one of the hollow tube slot apertures 285. When such an engagement occurs, the fusion cage 60 is slightly expanded as the hollow tube 2 is inserted into the fusion cage 60. In this arrangement, as the fusion cage 60 is expanded, the plate tabs 217 retreat or release from the hollow tube slot apertures 285; however, the hollow tube 2 still engages or registers with the fusion cage 60 via the hollow tube notches 282 which remain engaged with the rear block aft 238.

[0475] In one embodiment, the expansion screw 240 is configured to lock at defined expansion states of the fusion cage 60, to include at a maximum expansion state (as defined, e.g. as the maximum height dimension of which the fusion cage 60 may expand.)

[0476] In another embodiment, the fusion cage 60 with expandable cage feature is configured of modified and integrated embodiments of the afore-mentioned components. For example, FIG. 73 depicts a fusion cage 60 with expandable fusion cage feature wherein the upper plate 200 and lower plate 210 are joined through a plate nose element 218 ("plate/nose element"). These combined components are configured to form a first state wherein a minimal vertical height is provided and/or a flat profile is presented. Horizontal notches fitted between the upper plate 200 and plate nose element 218, and between the lower plate element 210 and plate nose element 218, enable the integrated upper plate 200, lower plate 210 and plate nose element to expand upon engagement with an integrated front block 220 and rear block 230 element. The integrated front block 220 and rear block 230 element comprises a block spine 228 ("block/spine element") such that, when inserted into the afore-mentioned plate/nose element, the fusion cage 60 expands. In one embodiment, each of the afore-mentioned integrated components would be held in a pistol grip type insertion tool (as known to those skilled in the art) which would allow placement of the unexpanded (i.e. the collapsed) plate/nose element into the surgical site (e.g. a disk space) with the block/spine element staged right behind. Upon pulling a lever on the pistol grip tool, the plate/nose element would be inserted into the block/spine element (in one embodiment, this insertion is facilitated by upper plate track 205 and lower plate track 215 engaging respective upper and lower rails of the block/spine element), thereby expanding the plate/nose element and forming an expanded fusion cage 60. In one embodiment, a locking feature is provided such that

the plate/nose and block/spine elements are secured or locked together. In one embodiment, the insertion of this fusion cage 60 embodiment is by way of hollow tube 2 (e.g. the embodiment described in FIGS. 70-72). In one embodiment of the fusion cage 60 as provided in FIG. 73, one or more upper plate openings 203 and/or one or more lower plate openings 213 are provided.

[0477] In one embodiment, no springs, such as wire springs, are employed to expand the fusion cage 60. In one embodiment, other means, as known to those skilled in the art, are used to expand the fusion cage 60, to include springs, gears, cams, magnetic, electrical, electro-mechanical, electro-magnetic, and optical.

[0478] The means and components disclosed may engage, integrate and/or communicate with the fusion cage 60 embodiments of the disclosure as well as with traditional and conventional fusion cages. That is, the components of the disclosure may be readily adapted to engage conventional fusion cages, including expandable fusion cages, of the prior art. More specifically, the hollow tube 2, installer/impactor 250, expansion driver 260, and/or plunger 12 may be adapted to engage fusion cages of the prior art. FIG. 74 provides a representative depiction of adaptations of components of the disclosure so as to engage conventional fusion cages, both fixed or static fusion cages and expandable fusion cages.

[0479] In one embodiment, the bone graft delivery system of the disclosure may engage with an expandable fusion cage of the prior art. For example, the hollow tube 2 may be configured to engage the prior art (expandable) fusion cage 400 shown by, for example, geometric sizing of the hollow tube first distal opening 8, and/or fitting the hollow tube first distal opening 8 with a malleable portion that may be compressed and/or expanded so as to engage the prior art (expandable) fusion cage 400, and/or fitting to an adaptor 300 portion. Additionally, the installer/impactor 250 may be adapted (e.g. to use the same configuration of expansion end as that of the depicted fusion cage) to communicate with the end portion of the prior art (expandable) fusion cage 400 so as to enable the expansion of the prior art (expandable) fusion cage 400. The prior art (expandable) fusion cage 400 may also be engaged with one or more components of the disclosure, e.g. the hollow tube 2 and/or installer/impactor 250.

[0480] In one embodiment of the fusion cage 60, the fusion cage of the prior art is adapted wherein one or more of the upper plate 200 and/or lower plate 210 is adapted to fit on paired opposite sides of the fusion cage.

[0481] In another embodiment, the bone graft delivery system of the disclosure may engage with an unexpandable fusion cage of the prior art. The hollow tube 2 is configured to engage the prior art (unexpandable) fusion cage 400 shown by, for example, geometric sizing of the hollow tube first distal opening 8, and/or fitting the hollow tube first distal opening 8 with a malleable portion that may be compressed and/or expanded so as to engage the prior art (expandable) fusion cage 400, and/or fitting to an adaptor portion 300.

[0482] FIG. 74 depicts the bone graft delivery system of the disclosure, as engaged with an unexpandable fusion cage of the prior art, specifically an unexpandable fusion cage provided in US2012/0065613 and/or <http://thompsonmis.com/node/23>, incorporated by reference in entirety. The hollow tube 2 is configured to engage the prior art (unex-

pandable) fusion cage **400** shown by, for example, geometric sizing of the hollow tube first distal opening **8**, and/or fitting the hollow tube first distal opening **8** with a malleable portion that may be compressed and/or expanded so as to engage the prior art (expandable) fusion cage **400**, and/or fitting to an adaptor portion **300** (as shown).

[0483] In one embodiment, the adaptor **300** comprises at least two forked tines to engage, for example, exterior surfaces of a fusion cage. In one embodiment, the adaptor **300** forms an angled tool, that is, the adaptor **300** and the hollow tube **2** are not aligned or linear. In another embodiment, the adaptor **300** forms an angled tool relative to a fusion cage when engaged with a fusion cage, that is, the adaptor **300** and the hollow tube **2** are aligned or linear but are not in alignment with an engaged fusion cage.

[0484] In one embodiment, the fusion cage **60** is actuated, eg the expansion screw **240** is operated, remotely, e.g. through electrical means, magnetic means or other means known to those skilled in the art, during surgery or post-operative. The later situation, i.e. post-operative, enables adjustment of the height of the fusion cage **60** after surgery. In one embodiment, the fusion cage e.g. the expansion screw is operated or manipulated by way of additional devices to comprise a servo-motor.

[0485] In one embodiment, the fusion cage **60** is used in applications comprising L-LIF, A-LIF, Corpectomy adaptation, deformity correction and increasing lordosis.

[0486] In one embodiment, the expansion screw **240**, comprising a left hand and a right hand threaded screw portion and a central disk, engages two opposing blocks at a 30 degree ramp angle with a dovetail joint. As the blocks are drawn in, the cage plates are forced outward (in the vertical direction). The narrow disk at the center of the screw registers in the slots of the cage plates to keep the plates from shifting fore/aft, reducing if not eliminating binding of the mechanism.

[0487] In one embodiment, at least some of the fusion cage is manufactured using 3-D printing technologies, metal additive manufacturing (AM), subtractive machining and/or direct metal laser sintering (DMLS) and may be provided a porous coating. In one embodiment, the fusion cage **60** comprises one or more surfaces, especially exterior surfaces, with pores so as to, for example, promote osseointegration. The article "EOS Teams with Medical Implant Designer to Advance 3D Printing in Medicine" published Oct. 17, 2012 in Graphic Speak is incorporated by reference in entirety.

[0488] In one configuration, the fusion cage comprises a titanium alloy, such as Ti6AL4V and/or lattice structures, the lattice structures covering all or at least part of one or more apertures of the fusion cage **60**. In one configuration, the lattice structures in FIG. **82**, herein incorporated by reference in entirety.

[0489] In one configuration, the hollow tube **2** is configured such that its distal upper and lower interior surfaces have grooves to engage the upper and lower portions of the rear cage actuating wedge. The screw tool, fitting inside the cannula, is still used to expand the cage. Once expanded, the screw tool is removed. Then BG material is inserted using the cannula/plunger scheme. The screw tool is put back in to engage the expandable screw and hold the fusion cage in place. The modified (interior grooved) cannula is pulled away from the cage with the screw tool providing an opposing force to the cage. The screw tool is then removed. Furthermore, the distal end of the modified cannula may be

made of an elastic material so that, if initially engaged with the cage in compression, it expands as the cage expands to provide a sealed fit with the cage as the cage expands, thereby allowing a clean flow of BG material into the cage i.e. no back-flow.

[0490] In one embodiment, one or more alignment markers are placed on the funnel, e.g. lines at 0 degree and 180 degree. In one embodiment, one or more clamps are applied to the hollow tube for additional support and/or stability. The clamps may be, e.g. scissor-type clamps. In one embodiment, all or a portion of the plunger, hollow tube, fusion cage and ejection tool comprise a thermoplastic polycarbonate such as Lexan™. In one embodiment, the fusion cage comprises a different material than one or more of the hollow tube, plunger and ejection device. In one embodiment, the plunger comprises an elastic portion and elastic seal which functions, among other things, to restrict wiggle of the plunger when moving through the hollow tube. In one embodiment, one or more portions of the device are manufactured via sonic welding, and/or comprise a sonic weld. For example, the tip of the hollow tube and/or fusion cage may be sonic welded or comprise a sonic weld.

[0491] In one embodiment of the device, the width of the hollow tube second exterior surface **5** is between 10 and 14 mm. In a preferred embodiment, the width of the hollow tube second exterior surface **5** is between 11 and 13 mm. In a most preferred embodiment, the width of the hollow tube second exterior surface **5** is between 11.5 mm and 12.5 mm. In a preferred embodiment, the width of the hollow tube second exterior surface **5** is 12 mm.

[0492] In one embodiment of the device, the width of the hollow tube first exterior surface **3** is between 6 and 10 mm. In a preferred embodiment, the width of the hollow tube first exterior surface **3** is between 7 and 9 mm. In a most preferred embodiment, the width of the hollow tube first exterior surface **3** is between 7.5 mm and 8.5 mm. In a preferred embodiment, the width of the hollow tube first exterior surface **3** is 8 mm.

[0493] In one embodiment of the device, the ratio of the width of the hollow tube second exterior surface **5** and the width of the hollow tube first exterior surface **3** is between 1.7 and 1.3. In a preferred embodiment, the ratio of the width of the hollow tube second exterior surface **5** and the width of the hollow tube first exterior surface **3** is between 1.6 and 1.4. In a most preferred embodiment, the ratio of the width of the hollow tube second exterior surface **5** and the width of the hollow tube first exterior surface **3** is between 1.55 and 1.45. In one embodiment, the ratio of the width of the hollow tube second exterior surface **5** and the width of the hollow tube first exterior surface **3** is 1.5.

[0494] In one embodiment of the device, the width of the interior of the hollow tube major axis (located adjacent the second exterior surface **5**) is between 9 and 13 mm. In a preferred embodiment, the width of the interior of the hollow tube major axis is between 10 and 12 mm. In a most preferred embodiment, the width of the interior of the hollow tube major axis is between 10.5 mm and 11.5 mm. In a preferred embodiment, the width of the interior of the hollow tube major axis is 11 mm.

[0495] In one embodiment of the device, the width of the interior of the hollow tube minor axis (located adjacent the first exterior surface **3**) is between 5 and 9 mm. In a preferred embodiment, the width of the interior of the hollow tube minor axis is between 6 and 8 mm. In a most preferred

embodiment, the width of the interior of the hollow tube minor axis is between 6.5 mm and 7.5 mm. In a preferred embodiment, the width of the interior of the hollow tube minor axis is 7 mm.

[0496] In one embodiment of the device, the ratio of the width of the interior of the hollow tube major axis and the width of the interior of the hollow tube minor axis is between 1.7 and 1.3. In a preferred embodiment, the ratio of the width of the interior of the hollow tube major axis and the width of the interior of the hollow tube minor axis is between 1.6 and 1.4. In a most preferred embodiment, the ratio of the width of the interior of the hollow tube major axis and the width of the interior of the hollow tube minor axis is between 1.55 and 1.45. In one embodiment, the ratio of the width of the interior of the hollow tube major axis and the width of the interior of the hollow tube minor axis is 1.5.

[0497] It should be noted that the rectangular configuration of the hollow tube affords several advantages over conventional circular configuration. For example, for a surgical area with smallest dimension set at a width of 8 mm with thickness dimension 0.5 mm, a conventional circular device (with resulting interior diameter of 7 mm or a radius of 3.5 mm) would realize a surface area of 38.48 mm². Applicants' device would carry interior dimension of 7 mm by 11 mm for a surface area of 77 mm, an increased surface area factor of 2.0, thereby resulting in more bone graft material delivery, because, among other things, a given volume of bone graft encounters less surface area of the interior of a particular device which results in, among other things, reduced chance of jamming of bone graft material within the device.

[0498] In one embodiment, a one or more edges of the device are rounded. For example, the exterior edges of the hollow tube are rounded, and/or the interior edges of the hollow tube are rounded (in which case the edges of the plunger, at least at the plunger distal end, are identically rounded to ensure a congruous or conformal fit between the edges of the plunger and the interior of the hollow tube so as to, among other things, urge the majority of bone graft material to move through the hollow tube).

[0499] In one embodiment, the handle 16 of plunger is a planar disk shape, as depicted in FIG. 23. In another embodiment, handle 16 is not planar. For example, handle 16 is angled so as to conform to interior of funnel 30 when the plunger 12 is fully inserted into hollow tube 2.

[0500] In one embodiment, the hollow tube distal interior ramp surfaces 9A are linear in shape, that is, forming a triangle in cross-section. In another configuration, the hollow tube distal interior ramp surfaces 9A are of any shape that urges egress of bone graft material contained in the hollow tube to exit the interior of the hollow tube through the pair of first distal openings 7 of the device 1.

[0501] A bone graft tamping device may also be provided, which is adapted to be telescopically inserted into the hollow tube after the plunger is removed from the hollow tube. The bone graft tamping device, according to this embodiment, may include one or more longitudinal channels along the outer circumference of the bone graft packer for permitting any trapped air to flow from the bone graft receiving area to the graspable end of the hollow tube during packing of bone graft. The bone graft packer may further include a handle at one end designed ergonomically for improving ease of use. The bone graft packer in this embodiment thereby facilitates packing of bone graft within the hollow tube.

[0502] The hollow tube may also be fitted with a passage-way wherein a surgical tube or other device may be inserted, such as to deliver a liquid to the surgical area or to extract liquid from the surgical area. In such an embodiment, the plunger is adapted in cross-section to conform to the hollow tube's cross-section.

[0503] In another embodiment of the present invention, a kit of surgical instruments comprises a plurality of differently sized and/or shaped hollow tubes and a plurality of differently sized and/or shaped plungers. Each of the plungers correspond to at least one of the hollow tubes, whereby a surgeon may select a hollow tube and a plunger which correspond with one another depending upon the size and shape of the graft receiving area and the amount or type of bone graft to be implanted at such area. The corresponding hollow tubes and plungers are constructed and arranged such that bone graft can be placed within the hollow tubes with the plungers, and inserted nearly completely into the hollow tubes for removing substantially all of the bone graft material from the hollow tubes, such as in the preferred embodiments for the plunger described above. The use of more than one hollow tube/plunger combination permits at least two different columns of material to be selectively delivered to the targeted site, e.g. one of bone graft material from the patient and another of Bone Morphogenetic Protein (BMP), or e.g. two different types of bone graft material or one delivering sealant or liquid. Also, one or both hollow tubes could be preloaded with bone graft material.

[0504] The kit of surgical instruments may comprise a plurality of differently sized and/or shaped graft retaining structures, each corresponding to at least one hollow tube and at least one plunger.

[0505] The bone graft receiving area can be any area of a patient that requires delivery of bone graft. In the preferred embodiment, the bone graft is delivered in a partially formed manner, and in accordance with another aspect of the present invention, requires further formation after initial delivery of the bone graft.

[0506] Another embodiment of the present invention provides a method by which a hollow tube and a plunger associated with the hollow tube are provided to facilitate delivery of the bone graft to a bone graft receiving area.

[0507] According to one embodiment, the present invention provides a bone graft delivery system, by which a hollow tube and/or plunger assembly may be prepared prior to opening a patient, thus minimizing the overall impact of the grafting aspect of a surgical implantation or other procedure. Moreover, the hollow tube may be made to be stored with bone graft in it for a period of time, whether the tube is made of plastic, metal or any other material. Depending upon the surgical application, it may be desirable to only partially fill the tube for storage, so that a plunger can be at least partially inserted at the time of a surgery.

[0508] Thus, the integrated fusion cage and graft delivery device may either come with a pre-filled hollow tube, or a non-filled hollow tube, in which the surgeon will insert bone graft received from the patient (autograft), or from another source (allograft). In either case, the surgeon may first remove any wrapping or seals about the hollow tube, and/or the pre-filled bone graft, and insert the hollow tube into the patient such that the second end of the hollow tube is adjacent the bone graft receiving area. Once the hollow tube is in place, and the opening at the second end of the hollow tube is oriented in the direction of the desired placement of

bone graft, the surgeon may then insert the second end of the plunger into the opening at the first end of the hollow tube, and begin pressing the second end of the plunger against the bone graft material in the hollow tube. In this fashion, the plunger and hollow tube cooperate similar to that of a syringe, allowing the surgeon to steadily and controllably release or eject bone graft from the second end of the hollow tube as the plunger is placed farther and farther into the opening in the hollow tube. Once the desired amount of bone graft has been ejected from the hollow tube (for in some instances all of the bone graft has been ejected from the hollow tube) the surgeon may remove the plunger from the hollow tube, and complete the surgery. In certain operations, the surgeon may elect to place additional bone graft into the hollow tube, and repeat the steps described above. Furthermore, the pre-filled bone graft elements may be color-coded to readily identify the type of bone graft material contained therein.

[0509] According to the embodiment described in the preceding paragraph, the present invention may be carried out by a method in which access is provided to a graft receiving area in a body, bone graft is placed into a hollow tube having a first end and a second end, the hollow tube, together with the bone graft, is arranged so that the first end of the hollow tube is at least adjacent to the graft receiving area and permits lateral or nearly lateral (in relation to the longitudinal axis of the hollow tube and plunger assembly) introduction of bone graft to the graft receiving area. This method prevents loss of bone graft due to improper or limited orientation of the integrated fusion cage and graft delivery device, and further allows a user to achieve insertion of a desired quantity of bone graft by way of the contoured plunger and hollow tube configuration described according to preferred embodiments herein.

[0510] The method of the present invention may also be carried out by providing a hollow tube having a first end and a second end, constructed so that it may receive a measurable quantity of bone graft, and so that the first end may be arranged at least adjacent to a bone graft receiving area, and so that bone graft can be delivered from the first end of the hollow tube through the second end of the hollow tube and eventually to the bone graft receiving area upon movement of the plunger in a generally downward direction through the hollow tube (i.e., in a direction from the first end to the second end). According to this embodiment, a graft retaining structure may also be provided for use in connection with the contoured edge of the plunger, such that the graft retaining structure is positioned between the contoured edge of the plunger and the bone graft, but which is adhered to the bone graft and remains at the graft receiving area following removal from the hollow tube. In one embodiment, the bone graft is provided in discrete packages or containers. Furthermore, this graft retaining structure may also be employed with another tool, such as a graft packer, which is employed either before or after the hollow tube is removed from the graft receiving area.

[0511] In another embodiment, the one or more plungers corresponding to the one or more hollow tubes are positioned with distal ends near the proximate end of the horizontal tube before use, said plungers having a detent to retain plunger in ready position without undesired movement before surgeon chooses which one or more plungers to extend through hollow horizontal tube and deliver bone graft material and/or desired material to the surgical area.

[0512] According to another embodiment of the present invention, a hollow tube and plunger assembly is provided in which the hollow tube and/or the plunger assembly is disposable. Alternatively, the tube may be made of a bio-compatible material which remains at least partially in the patient without impairing the final implantation. Thus, the hollow tube may be formed from a material that is resorbable, such as a resorbable polymer, and remain in the patient after implantation, so as not to interfere with the growth of the bone or stability of any bone graft or implant.

[0513] The current design preferably comprises a hollow tubular member comprising a rounded edge rectangular shaft, which may be filled or is pre-filled with grafting material. The loading is carried out by the plunger. The rectangular design is preferable as it allows the largest surface area device to be placed into the annulotomy site of a disk, but in other embodiments may be formed similar to conventional round shafts. The other preferred feature includes a laterally-mounted exit site for the graft material. The combination of this design feature allows direction-oriented dispersion of the graft material. This allows ejection of the graft material into an empty disk space as opposed to below the hollow tube, which would tend to impact the material and not allow its spread through a disk space.

[0514] Another feature of this design is that a rectangular design allows the user to readily determine the orientation of the device and thereby the direction of entry of the bone graft material into the surgical area. However, such a feature may be obtained alternatively through exterior markings or grooves on the exterior on the hollow tube. Such exterior grooves or markings would allow use of a range of cross-sections for the device, to include a square, circle, or oval while allowing the user to readily determine the orientation of the device relative to the direction of entry of the bone graft material into the surgical area.

[0515] A further feature of this design is that an anti-perforation footing or shelf is paced on the bottom of the hollow tube to prevent annular penetration and/or injury to the patient's abdomen or other anatomy adjacent the bone graft receiving area.

[0516] Another alternative embodiment to the design described herein includes a removable funnel attachment. This allows easy loading of the cannula with the funnel and with its removal easy visualization of the operating site without visual blockage through the microscope.

[0517] In another embodiment of the invention, all or some of the elements of the device or sections of all or some of the device may be disposable. Disposable medical devices are advantageous as they typically have reduced recurring and initial costs of manufacture.

[0518] In another embodiment of the device, the distal tip or end of the plunger device is composed of a different material to the rest of the plunger, so as the material at the distal end of the plunger is sponge-like or softer-than or more malleable than the rest of the plunger so as upon engagement with the interior distal end of the hollow tube, the distal end of the plunger substantially conforms to the interior configuration of the hollow tube. Similarly, the plunger distal end may be made of a material that is adaptable to substantially conform to the interior shape of the distal end of the hollow tube. Such configurations enable substantially all of the material contained within the plunger to be delivered to the targeted site.

[0519] Another alternative embodiment to the design described herein includes a navigation aid on one or more surfaces of the tubular body to permit surgeon to know how far the device has been inserted or to ensure proper alignment relative to a transverse bone graft delivery site (i.e. disc space). Such capability is particularly important when the patient or surgical area is not positioned immediately below the surgeon, or multiple procedures are being performed. A navigation aid allows more immediate and reliable locating of the surgical area for receiving of bone graft material. In one embodiment, the hollow tube is scored or marked or provides some affirmative indication, actively or passively, to the surgeon to indicate degree of delivery of the material, e.g. bone graft material, to the delivery site, and/or position of the plunger element. For example, the exterior of the hollow tube could be color-coded and/or provided with bars. In another embodiment, a computer and/or electro-mechanical sensor or device is used to provide feedback to the surgeon to indicate degree of delivery of the material, e.g. amount of cc's of bone graft material, to the delivery site, and/or position of the plunger element.

[0520] In another alternative embodiment to the design described herein, the plunger could include an activation device, which is often in a liquid or semi-liquid state, and that may be injected once the semi-solid portion of the morphogenic protein has been displaced by the movement of the plunger through the tubular body. That is, the plunger pushes the dry material, and once completed has a bulb or other device on the usable end to insert the liquid portion of the activating agent through the inner lumen within the plunger to evacuate the liquid from the plunger and out an opening at the non-usable end of the plunger so as to contact the dry material already inserted into the disc space).

[0521] In one embodiment of the device, all or portions of the device are manufactured using 3-D printing techniques. In another embodiment, all or portions of the device are made by injection molding techniques.

[0522] In one embodiment, the ratio of the surface area of the bottom tip of the plunger is approximately half the surface area of the two lateral openings at the distal portion of the hollow tube.

[0523] In one embodiment, the device includes a supplemental means of gripping the device, such as a laterally extending cylindrically-shaped handle that engages the hollow tube.

[0524] In one embodiment, the material inserted into the hollow tube is a non-Newtonian fluid. In one embodiment, the device is adapted to accept and deliver compressible fluids. In another embodiment, the device is adapted to accept and deliver non-compressible fluids.

[0525] In one embodiment, the upper portion of plunger is fitted with one or more protrusions, which extends from the surface of the plunger so as to engage the upper surface of the hollow tube, to prevent the plunger from engaging the distal interior portion of the hollow tube. In one embodiment, the upper portion of plunger is fitted with one or more protrusions to prevent the plunger from engaging the apex of the hollow tube distal interior ramp surface.

[0526] In one embodiment, the funnel attaches to the upper portion of the hollow tube by a bayonet connection. In one embodiment, the funnel attaches to the upper portion of the hollow tube by an interference fit. In one embodiment, the funnel attaches to the upper portion of the hollow tube

by a threaded connection. In one embodiment, the funnel attaches to the upper portion of the hollow tube by a slot/groove connection.

[0527] In one embodiment, the second end of hollow tube has one hollow tube distal opening. In one embodiment, the second end of hollow tube has two hollow tube distal openings located on opposite sides. In one embodiment, the second end of hollow tube has no more than two openings, the openings located on opposite sides.

[0528] In one embodiment, after bone graft material is delivered to a surgical site, a cavity approximately defined by the volume engaged by the device when inserted into the surgical site is left in the surgical site upon removal of the device from the surgical site. In one embodiment, the aforementioned cavity is then used as the site for insertion of a fusion cage.

[0529] The integrated fusion cage **60** with expandable cage feature provides a number of unique and innovative features not provided by conventional or traditional integrated fusion cages. For example, the integrated fusion cage with expandable cage feature of the disclosure is intentionally and deliberately designed to receive bone graft material (or any material suitable for use in surgical applications, as known to those skilled in the art) at its proximal end (ie the end generally facing the surgeon and/or the end opposite the end initially directed into a surgical site), such that the bone graft material flows into the fusion cage and also flows out from the fusion cage into the surgical site. Such features as the interior ramps of the fusion cage (e.g. located within the interior of the hollow tube, and/or on the front and/or rear blocks of the fusion cage) function to direct received bone graft material into the surgical site. Additionally, the features of the hollow tube and plunger wherein a greater volume of bone graft material may be reliably (e.g. not prone to blockage as is typical with most convention eg round hollow tubes or cannula systems) and readily delivered to a surgical site and/or a fusion cage are unique and not found in the prior art. Among other things, such features encourage improved surgical results by delivering more volume and coverage of bone graft material to the surgical site. Also, such features minimize gaps in bone graft coverage to include gaps between the fusion cage area and the surrounding surgical site. Also, the features of the one or more apertures of the fusion cage of the disclosure enable and encourage delivery of bone graft material, as received by the fusion cage, into the surrounding surgical site.

[0530] In contrast, conventional fusion cages, to include expandable fusion cages, do not provide such features and/or functions. For example, U.S. Pat. No. 8,852,242 to Morgenstern Lopez ("Lopez"), discloses a dilation introducer for orthopedic surgery for insertion of an intervertebral expandable fusion cage implant. The Lopez device does not allow receipt of bone graft material from its proximal end, or any end, in contrast to the disclosed fusion cage and fusion cage/bone graft delivery system. That is, the Lopez proximal end includes an array of components, all of which do not allow receipt of bone graft material. Furthermore, the Lopez device requires an elaborate array of components, e.g. upper side portion **240** of the upper body portion **202** and lower side portion **242** of the lower body portion **204**, which also block any egress of bone graft from the inside of the Lopez fusion cage once deployed. Also, the Lopez wedges occupy the entire interior of the cage; there are no ramps to direct graft from the interior to the disk space. In short, the

Lopez design is not made with bone graft delivery in mind, and indeed, cannot function to accept let alone deliver bone graft. Additionally, suggestions provided in the Lopez disclosure to deliver bone graft to the surgical site would not provide the integrated and complete fusion cage and surgical site bone graft delivery of the invention, e.g. the Lopez slot **918** of the Lopez lumen **916** and funnel assembly **910** at best provides limited delivery of bone graft material only before and after insertion of the Lopez fusion cage, and then only peripheral to the fusion cage. Also, it appears the Lopez device provides wedges **206** and **208** of similar if not identical interior ramp angles. In contrast, in certain embodiments of the present invention the interior wedged surfaces of the invention, i.e. front block ramp **226** and rear block ramp **236**, are not of the same configuration and/or shape, e.g. front block ramp **226** is of a curved profile and rear block ramp **236** is of a linear or straight-line profile. Among other things, the curved profile of the front block ramp **226** urges egress of bone graft as received by the fusion cage **60**.

[0531] In one embodiment of the fusion cage **60**, no anti-torque structures or components are employed. In one embodiment of the invention, the lateral sides of the fusion cage **60** are substantially open to, among other things, allow egress of bone graft material as received to the fusion cage. In one embodiment, the expansion screw **240** is configured with a locking mechanism, such that the fusion cage **60** may be locked at a set expansion state. In one embodiment, such a locking mechanism is provided through a toggle device operated at or on the installer/impactor handle **258**.

[0532] In one embodiment, the front block ramp **226** and rear block ramp **236** are identical and/or symmetrical.

[0533] In addition, it is contemplated that some embodiments of the fusion cage **60** can be configured to include side portions that project therefrom and facilitate the alignment, interconnection, and stability of the components of the fusion cage **60**.

[0534] Furthermore, complementary structures can also include motion limiting portions that prevent expansion of the fusion cage beyond a certain height. This feature can also tend to ensure that the fusion cage is stable and does not disassemble during use.

[0535] In some embodiments, the expansion screw **240** can facilitate expansion of the fusion cage **60** through rotation, longitudinal contract of a pin, or other mechanisms. The expansion screw **240** can also facilitate expansion through longitudinal contraction of an actuator shaft as proximal and distal collars disposed on inner and outer sleeves move closer to each other to in turn move the proximal and distal wedged block members closer together. It is contemplated that in other embodiments, at least a portion of the actuator shaft can be axially fixed relative to one of the proximal and distal wedge block members with the actuator shaft being operative to move the other one of the proximal and distal wedge members via rotational movement or longitudinal contraction of the pin.

[0536] Further, in embodiments wherein the engagement screw **240** is threaded, it is contemplated that the actuator shaft can be configured to bring the proximal and distal wedged block members closer together at different rates. In such embodiments, the fusion cage **60** could be expanded to a V-configuration or wedged shape. For example, the actuator shaft can comprise a variable pitch thread that causes longitudinal advancement of the distal and proximal wedged block members at different rates. The advancement of one of

the wedge members at a faster rate than the other could cause one end of the implant to expand more rapidly and therefore have a different height than the other end. Such a configuration can be advantageous depending on the intervertebral geometry and circumstantial needs.

[0537] In other embodiments, the implant **200** can be configured to include anti-torque structures. The anti-torque structures can interact with at least a portion of a deployment tool during deployment of the fusion cage **60** implant to ensure that the implant maintains its desired orientation. For example, when the implant is being deployed and a rotational force is exerted on the actuator shaft, the anti-torque structures can be engaged by a non-rotating structure of the deployment tool to maintain the rotational orientation of the implant while the actuator shaft is rotated. The anti-torque structures can comprise one or more inwardly extending holes or indentations on the rear wedged block member. However, the anti-torque structures can also comprise one or more outwardly extending structures.

[0538] According to yet other embodiments, the fusion cage **60** can be configured to include one or more additional apertures to facilitate osseointegration of the fusion cage **60** within the intervertebral space. The fusion cage **60** may contain one or more bioactive substances, such as antibiotics, chemotherapeutic substances, angiogenic growth factors, substances for accelerating the healing of the wound, growth hormones, antithrombogenic agents, bone growth accelerators or agents, and the like. Indeed, various biologics can be used with the fusion cage **60** and can be inserted into the disc space or inserted along with the fusion cage **60**. The apertures can facilitate circulation and bone growth throughout the intervertebral space and through the implant. In such implementations, the apertures can thereby allow bone growth through the implant and integration of the implant with the surrounding materials.

[0539] In one embodiment, the fusion cage **60** comprises an expandable cage configured to move a first surface vertically from a second surface by rotation of at least one screw that rotates without moving transversely with respect to either said first or second surface, said first plate and second plate having perimeters that overlap with each other in a vertical direction and that move along a parallel line upon rotation of the screw.

[0540] In one embodiment, the fusion cage **60** is stackable by any means known to those skilled in the art. For example, each upper plate **200** may be fitted with one or more notches on the lateral edges configured to fit with one or more protrusions on each lower plate **210**.

[0541] Surprisingly, while conventional practice assumed that the amount of material that would be required, let alone desired, to fill a prepared disc space with bone paste (or BMP, etc.) would be roughly equivalent to the amount of material removed from such space prior to inserting a cage, a present inventor discovered that far more bone graft material can be—and should preferably be—inserted into such space to achieve desired fusion results. The reasons why this basic under appreciation for the volume of bone graft necessary to achieve optimal fusion results vary, but the clinical evidence arrived at via practice of the present invention compellingly demonstrates that more than doubling of the amount of bone graft material (and in some cases increasing the amount by 200%, 300% or 400% or

more) than traditionally thought necessary or sufficient, is extremely beneficial to achieving desired results from fusion procedures.

[0542] The ramifications of this simple yet dramatic discovery (documented in part below) is part of the overall inventive aspect of the present invention, as it has been—to date—simply missed entirely by the practicing spine surgeons in the field. The prospect of reduced return surgeries, the reduction in costs, time, and physical suffering by patients, as well as the volume of legal complaints against surgeons and hospitals due to failed fusion results, is believed to be significant, as the evidence provided via use of the present invention indicates a vast reduction in the overall costs involved in both economic resources, as well as emotional capital, upon acceptance and wide-spread use of the present invention. Insurance costs should thus decrease as the present invention is adopted by the industry. While the costs of infusing increased amount of bone graft materials into the space of a patient's disc may at first appear to increase the costs of an individual operation, the benefits achieved thereby will be considerable, including the reduction of repeat surgeries to fix non-fused spines. Thus, regardless of the actual tools and devices employed to achieve the end result of attaining up to 100% more bone graft material being utilized in fusion operations, (as well as other surgeries where previously under-appreciated bone graft material delivery volumes have occurred) one important aspect of the present invention is directed to the appreciation of a previously unrecognized problem and the solution thereto, which forms part of the inventive aspects of the present invention described and claimed herein.

[0543] In one embodiment, at least twice the amount of disk material removed from a surgical site is replaced with bone graft material. In a preferred embodiment, at least three times the amount of disk material removed from a surgical site is replaced with bone graft material. In a most preferred embodiment, at least three and a half times the amount of disk material removed from a surgical site is replaced with bone graft material.

Experimental Results

[0544] The following experimental results are with respect to an apparatus and method for near-simultaneous and integrated delivery of bone graft material in a patient's spine. These results are sample results and are not intended to limit the invention.

Materials and Methods

[0545] During the time period from July 2010 through December 2012, a set of patients undergoing minimally invasive (MIS) transverse lumbar interbody fusion (T-LIF) at the L4-5 and/or L5-S1 levels were studied for disk material removed and BG delivered at each disk space during the surgical procedure. The diagnosis was spondylosis or spondylolisthesis in all patients. A total of 63 patients with an average age of 56 years were studied. There were 29 male and 34 female patients. Ninety-one disk spaces were analyzed. A single surgeon with the same surgical team performed all surgeries. The operations were carried out through a 22 mm cannula with microscopic control. The midline structures and spinous process attachments were left undisturbed. The disk space was debrided exhaustively using non-motorized, hand tools to bleeding subchondral

bone. The debrided disk material was measured in a volumetric syringe. Bone Graft (BG) material consisting of silicated tricalcium phosphate granules and hyaluronic acid powder were mixed in a 1:1 ratio and local bone graft and bone marrow aspirate concentrate were added together to form a slurry. The slurry was measured volumetrically. Disk space mobilization and distraction was carried out with serial impaction of distractor tools until appropriate disk height was achieved. Distraction ranged from 8 mm to 14 mm, with the 10 mm or 12 mm height being most commonly observed.

[0546] The BG delivery tool of this disclosure was used to apply the BG slurry to the disk space. The embodiment had a rectangular cross section with the same footprint as a small fusion cage (8 mm×12 mm). The tapered tip was placed into the debrided disk space under microscopic control to allow for direct visualization, followed by the application of a snap-on funnel for loading the BG. The BG slurry was then placed in the funnel and the slurry was pushed into the disk space with the plunger. The biportal design of the delivery tool directed the slurry into the lateral areas of the prepared disk space, leaving a natural void for the fusion cage once the tool was removed. Once the disk space was filled entirely, the site of insertion was inspected for any BG material, which might have escaped the confines of the disk space. This material was excluded in the final measurement to ensure an accurate calculation of BG delivery. Removal of the delivery tool provided an unobscured path for the fusion cage to be applied.

[0547] A polyether ether ketone, hollow interbody fusion cage of the appropriate size was then placed into the disk space. A minimally invasive, bilateral pedicle screw/rod system was applied prior to wound closure. Average blood loss for the procedures was 127 ml±75 ml.

[0548] A two-tailed student's t-test was used to determine if any significant difference existed between the volumes of disk material removed at L4-5 versus L5-S1. The null hypothesis was that no significant difference existed between samples. Significance was set at $p < 0.05$. The two-tailed t test was also used to determine whether a significant difference existed between volumes of BG delivery and disk material removed. The formula [(BG delivered+graft volume of the fusion cage)/disk material removed] was used to generate the ratio of BG delivery versus disk material removed.

[0549] In order to compare the volume of disk material removed during a T-LIF procedure with a complete, surgical discectomy, the volume of disk material removed during L5-S1 anterior lumbar discectomy was measured volumetrically. The L5-S1 disk was harvested and measured for patients undergoing either anterior fusion or total disk replacement. The material removed consisted of anterior and posterior annulus as well as complete nucleotomy, and represented more tissue (in terms of the annuli) than would be typically removed in a T-LIF procedure. There were 29 anterior L5-S1 discectomy patients. The age range, gender distribution and diagnosis were the same as the T-LIF patients.

[0550] All study patients were followed up with anterior/posterior radiographs and a physical examination at 4 weeks, 12 weeks, 26 weeks and 52 weeks post surgery. A visual analog scale (VAS) for pain was obtained at each visit and an Oswestry Disability Index (ODI) was completed preoperatively and at 26 weeks postoperatively.

Results

[0551] There were 58 L4-5 disk spaces and 33 L5-S1 disk spaces evaluated. The average volumes of disk material harvested from L4-5 and L5-S1 were $4.1 \text{ ml} \pm 2.2 \text{ ml}$ and $2.8 \text{ ml} \pm 1.9 \text{ ml}$, respectively. The p-value for the student's two-tailed t-test was equal to 0.01, revealing a significant difference in terms of disk material removed between L4-5 and L5-S1. The range of volume was less than 1 ml to 14.5 ml. The comparison between disk material removed and BG material inserted at L4-5 or at L5-S1 demonstrated a significant difference ($p < 0.001$).

[0552] BG volume applied to L4-5 was $9.8 \text{ ml} \pm 3.3 \text{ ml}$. At L5-S1 it was $8.6 \text{ ml} \pm 3.2 \text{ ml}$. The p-value for the student's two-tailed t-test was equal to 0.07, trending to a significant difference in bone graft applied between L4-5 and L5-S1. The combined average was $9.2 \text{ ml} \pm 3.0 \text{ ml}$. The volume of BG applied ranged from 4.5 ml to 19 ml. The formula of [(BG delivered+graft volume of the fusion cage)/disk material removed] generated a surprising result: The amount of disk material removed compared to the amount of BG placed in the disk space was not a 1:1 ratio, as would have been empirically expected. At L4-5 the ratio was 3.4 ± 2.2 and at L5-S1 it was 4.7 ± 2.7 , as shown in FIGS. 34A-B, respectively. This was statistically significant with a p-value of 0.02. With respect to the entire study, the ratio of BG inserted relative to disk material removed revealed that on average 3.7 ± 2.3 times as much BG was inserted into the disk space as disk material removed. This finding was even more dramatic with collapsed disk spaces where 1 ml of disk material harvest led to an average of $6.6 \text{ ml} \pm 0.9 \text{ ml}$ of BG delivery, as shown in FIGS. 35A-B. The volume of BG delivery was asymptotically related to the volume of disk material removed with 12.3 ml of disk material being delivered to a disk where 8.0 ml of disk was removed, as shown in FIGS. 35A-B.

[0553] The average volume of disk material removed during a T-LIF discectomy at L5-S1 was 3.2 ml and the average volume of disk material from the anterior L5-S1 discectomy was 8.1 ml. Dividing the average T-LIF volume by the average anterior discectomy (including annuli) volume revealed that on average 34% of the disk material was removed at the time of T-LIF at the L5-S1 disk space.

[0554] Because of the tapered tip of the BG delivery tool, it was possible to enter the most collapsed disk space without endplate injury. The delivery device did not jam with the application of the BG slurry. The removable funnel allowed direct visualization of the tool under the microscope without obscuring its tip during insertion. Because the delivery device applied BG out of its side portals, it provided a natural void for fusion cage insertion, and no cage jamming resulted during impaction. BG delivery using the described tool took a fraction of the time (less than 2 minutes) usually devoted to depositing BG to the disk space. There were no complications associated with the use of the BG delivery tool.

[0555] The average preoperative ODI measured 29 ± 9 and the postoperative value was 21 ± 8 . A significant difference was not detected with $p = 0.06$. The VAS similarly improved with pre-operative score measuring 7.5 ± 1.5 and postoperative score 4.0 ± 2.5 . The postoperative VAS was statistically significant relative to the corresponding preoperative value with $p < 0.05$.

Pseudoarthrosis developed in 7 disks in 4 patients (7.6%). The patients with 2-level pseudoarthrosis had a diagnosis of

hypothyroidism. This diagnosis was also present in one of the single level pseudoarthrosis patients. The remaining pseudoarthrosis patients did not have discernable risk factors (diabetes, tobacco consumption or obesity).

Discussion

[0556] There is substantial variation in fusion rates after T-LIF surgery with pseudoarthrosis rates varying from 23.1% to 2.9%. The reasons for the range of successful arthrodesis vary from surgical technique, including BG preparation and application, to the way in which a pseudoarthrosis is diagnosed—direct surgical exploration or by radiographic means. Reason would dictate that the volume of BG delivered to a prepared disk space would contribute positively to successful arthrodesis with inadequate grafting leading to pseudoarthrosis. Using hand tools and the goal of disk space debridement, a conservative estimate of 34% of disk removal was observed in this study at the L5-S1 level. This substantial difference represents the different goals of the procedures and provides a baseline for general disk space debridement for T-LIF procedures.

[0557] The statistically significant difference between the amount of disk material removed from L4-5 versus L5-S1 correlates with the commonly observed radiographic finding of disk height at L4-5 being greater than that of L5-S1. Likewise, BG delivery to L4-5 was greater relative to the L5-S1 disk space. Although direct volume of BG insertion was greater in L4-5 relative to L5-S1, the ratio (BG delivered/disk material removed) was higher at L5-S1 (4.7 ± 2.7) than at L4-5 (3.4 ± 2.2). This was a statistically significant difference ($p < 0.02$) and corresponds with the more collapsed disk spaces demonstrating a higher percentage of BG delivery (see FIGS. 34A-B).

[0558] On average, 3.7 times as much bone graft was applied to the debrided disk space relative to disk material removed. This is explained by the fact that the disk space was collapsed at the time of discectomy, and then distracted and mobilized during the preparation process to a distracted height. This suggests that relying on an empiric 1:1 ratio of disk removal to BG insertion grossly under-fills the disk space and would be an important contributor to pseudoarthrosis. This is an especially important consideration in the most collapsed disk spaces since distraction to appropriate height in a non-collapsed disk reduces the ratio to 8:12.3 (see FIG. 35A) or a 1:1.4 ratio.

[0559] The BG slurry used in this study consisted of a mixture of granular material and liquid. This combination of materials does not behave as a typical, Newtonian (non-compressible) fluid. A non-Newtonian fluid will exude its fluid component as it is compressed, and the residual granular BG material occludes a conventional, cylindrical BG delivery device.

[0560] The BG delivery tool in this study revealed a number of advantages in that it allowed for BG application in collapsed disc spaces due to its wedged tip, a process which is not possible with round-ended injection cannulas. The increased cross sectional footprint relative to a round cannula allowed considerably less friction of non-Newtonian fluid material through the cannula, resulting in an increase in the BG flow dynamics, and eliminating jamming due to BG impaction. It is estimated that changing the cross-sectional area from 8 mm×8 mm to 8 mm×12 mm improves the flow dynamics of a non-Newtonian fluid by 40%. The two sites for BG extrusion at the sides of the

cannula tip double the exit zone surface area, further decreasing the resistance to flow of the granular mixture. The removable funnel allowed direct visualization of the cannula as it was applied to the disk space without being obscured by the funnel. The biportal expression of the BG material allowed graft inoculation of all prepared areas of the disk space and left a void for the fusion cage. The applied BG delivery tool allowed refilling of the cannula without having to remove the device, resulting in decreased potential trauma to the adjacent nerve tissue.

[0561] The fusion rate in this study was 92.4% with three of the pseudoarthrosis patients having a diagnosis of hypothyroidism. This may be related to abnormalities in bone metabolism associated in patients with endocrinopathy. The other pseudoarthrosis patients did not have apparent risk factors. Postoperative pain scores and functional improvement correlated with progression to arthrodesis.

[0562] In summary, preparation of the disk spaces at L4-S1 can deliver 34% of the disk volume during debridement. BG delivery was on average 3.7 times the volume of disk removal with a relatively higher ratio of BG being delivered to the more collapsed disk spaces. A novel BG delivery device can be used to dispense a volume of BG to the disk space that is capable of filling the entire debrided area in an efficient and safe fashion. This should allow for maximization of arthrodesis potential, increase patient safety, and decrease operative time.

[0563] FIG. 75 is a perspective view of a bone graft delivery device 502 according to the prior art. The bone graft delivery device 502 comprises a first end 504 and a second end 516, with an elongate shaft 508 provided therebetween. The first end 504 comprises a funnel 512 for receiving material and providing the material to the elongate shaft 508. The second end 516 comprises an outlet aperture 510 through which bone graft material may exit the device and be provided to a disc space (for example). Bone graft delivery devices of the present disclosure, including the device shown in FIG. 75, are contemplated as comprising indicia 511, including indicia that is operable to indicate an extent of insertion of the second end 516 of the device into a surgical work site.

[0564] FIG. 76 is a cross-sectional view of a bone graft delivery device 512 provided in combination with a surgical work site 522. Specifically, a bone graft delivery device 512 is shown as providing a bone graft material 524 to an intervertebral space 522 within a human spine 520. The tool 502 is generally inserted into a patient from a lateral access site, and a second end of the delivery device 512 is provided within the intervertebral space to which bone graft material 524 is to be provided. FIG. 76 depicts a conventional end-dispensing cannula that ejects and injects bone graft material directly into the intended path of a fusion cage. The device and method of FIG. 76 does not distribute bone graft delivery material into the periphery of the prepared disc space and generally fails to achieve appropriate distribution of bone graft delivery material.

[0565] FIG. 77 is a plan view of a bone graft delivery device 530 according to one embodiment of the present disclosure. As shown, the device 530 comprises an elongate shaft 532 and a handle 534 extending substantially perpendicular thereto. The handle 534 comprises a user-interface means that extends away from the elongate shaft portion 532 of the device. The handle 534 is connected to the device proximal to a first end 538 of the device 530. In various

embodiments, the connection 536 between the handle 534 and the elongate shaft 532 comprises a permanent connection, such as a welded connection between the two components. In alternative embodiments, it is contemplated that the handle 534 is selectively detachable from the elongate shaft portion 532 of the device 530. For example, in some embodiments, it is contemplated that the handle 534 comprises a threaded connection for selectively attaching the handle 534 to the elongate shaft 532 of the tool 530. As further shown in FIG. 77, the device comprises a removable funnel member 540. The removable funnel 540 is operable to connect to the first end 538 of the device and is capable of facilitating the insertion of bone graft material to a patient via the elongate shaft 532 of the tool 530. The funnel 540 is operable to insert bone graft material into the elongate and generally thin shaft 532 by providing an expanded opening for a user to feed bone graft material into. The funnel 540 is provided as a removable device such that a user may remove the funnel 540 after bone graft material has been inserted and such that the funnel 540 does not obstruct a user's view of a surgical work site after the funnel is no longer needed.

[0566] FIG. 78 is a top plan view of a surgical work site and a bone graft delivery device 530 according to one embodiment of the present disclosure. As shown, the bone graft delivery device 530 comprises an extending handle 534 and the device 530 is provided in a surgical worksite 539. The surgical tool preferably comprises an ovoid internal cross-section 542 with an enhanced area. For illustrative purposes, a conventional tool's cross-section 540 is shown. Conventional devices with cross-sections represented by section 540 of FIG. 78 generally comprise an area of less than 50 mm², and specifically of approximately 38 mm². In contrast, tools and devices of the present disclosure comprise an internal area of at least approximately 70 mm² and preferably of at least 78 mm².

[0567] FIG. 79 is a detailed perspective view of a distal end of a bone graft delivery device 530. As shown, the device 530 comprises an elongate shaft 532 that terminates with a contoured distal end 544. As shown, the distal end of the device 544 comprises a closed end, and at least one aperture 546 is provided along a length of the shaft 532 for allowing egress of bone graft material to a surgical work site. The distal end 544 of the tool 530 preferably comprises a rounded or curved end to facilitate insertion into a workspace, including collapsed or restricted disc spaces. It is contemplated that the distal end 544 of the tool 530 is to be provided within a work site after the work site has been prepared and cleaned by additional components. However, it has been observed that even after clearing of a disc space (for example) by conventional tools and methods, some obstructions may still be present. It has been found that a rounded, curved, or pointed distal end 544 as shown in FIG. 79 eases insertion and prevents damage or injury to a patient.

[0568] Whereas conventional devices comprise an open distal end (see FIG. 75, for example), the closed and rounded distal end 544 of the present invention is further provided with at least one and preferably two or more apertures 546 on a lateral portion of the shaft 532 to facilitate egress of bone graft material from the device and to avoid injection of bone graft material directly into an intended path of insertion for a fusion cage.

[0569] FIG. 80 is an elevation view of a surgical access site, including a patient's spine 550 and a bone graft delivery device provided and extending into an intervertebral disc

space **545**. The elongate shaft **532** extends into a disc space **545** wherein the distal end of the device is provided between vertebrae. The device is preferably inserted far enough into the disc space that the aperture(s) **546** provided on lateral sides of the shaft **532** are also positioned within the disc space. Accordingly, after debridement of the disc space **545** through appropriate methods, new bone graft material may be inserted into the disc space **545** by providing the bone graft material through the elongate shaft **532** and ejecting the bone graft material through the apertures **546** into the disc space **545**. Although not shown in FIG. **80**, a fusion cage may be in the disc space **545** prior to and/or subsequent to injection of bone graft material.

[**0570**] FIG. **81** is a top plan view of a surgical site and an injection of bone graft material **552** according in accordance with methods and systems of one embodiment of the present disclosure. As shown, an elongate shaft **532** of a bone graft delivery device is provided and wherein a rounded or curved distal end **544** of the device extends into a surgical site which is shown as an intervertebral disc space of a patient's spine **550** in FIG. **81**. As shown in FIG. **81**, bone graft material **552** is provided to an intervertebral space by ejecting the material from first and second apertures **546** provided in side-walls of the elongate shaft **532** of the bone graft delivery tool. The tool and method of FIG. **81** provides for multiple ejection ports for delivery and enhanced distribution of bone graft material into a surgical site. The elongate shaft **532** of the device and associated apertures **546** are operable to provide a greater amount of bone graft material to a work space as compared to existing devices and methods by providing enhanced distribution, for example. As opposed to conventional methods and devices, bone graft delivery devices of the present disclosure avoid injection of bone graft material directly into the path or intended path of a cage (see FIG. **76**). Devices of the present disclosure provide for a sufficient amount of bone graft material is provided to a workspace and wherein a receiving area is provided that is operable to receive a fusion cage.

[**0571**] FIG. **82** is a top view of the surgical workspace according to FIG. **81**, and wherein the bone graft delivery tool has been removed after insertion or injection of the bone graft material **552**. As shown in FIG. **82**, removal of the bone graft delivery tool provides for an unobstructed path **554** and void space for subsequent insertion of a fusion cage (not shown in FIG. **82**). Annulotomy is performed as a step in the method(s) of intradiscal decompression and the resolution of disco radicular conflict as contemplated by various embodiments of the present disclosure. The bone graft material **552** is provided before, during, and/or after insertion of the appropriate fusion cage.

[**0572**] FIGS. **83-84** depict methods and devices for preparing a bone graft material **570** according to one embodiment of the present disclosure. Specifically, bone graft material **570** is partially prepared by providing the material **570** within a graduated syringe **560** and the bone graft material is compressed or compacted to form a desired and measured amount of bone graft material. The bone graft material **570** is thereafter prepared for insertion into a surgical workspace, including (but not limited to) an area of disc debridement in a surgical setting.

[**0573**] Methods and systems of the present disclosure provide for increased amounts of bone graft delivery material being delivered to a disc space, and therefore improve and expedite post-surgical recovery processes. In various

embodiments, it is contemplated that between approximately 2.5 mL and 5.7 mL of disc material is removed from a surgical site, and between approximately 6.2 mL and 12.2 mL of bone graft delivery material is provided to the same space. Complete filling of a prepared disc space and subsequent fusion and incorporation of bone graft delivery material is provided. Enhanced bone graft delivery is accomplished through various methods and devices of the present disclosure including, for example, lateral apertures or ports provided in a bone graft delivery device to inject or insert bone graft material without obstruction a path of a cage, and through enhanced cage systems wherein an interior volume of disc space can be increased. In a prepared, distracted disc space, a volume of a generally cylindrical space is increased and improved, increased amounts of bone graft delivery material is provided.

[**0574**] While various embodiment of the present disclosure have been described in detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present disclosure, as set forth in the following claims.

[**0575**] The foregoing discussion of the disclosure has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more embodiments for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the claimed disclosure requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment. Thus, the following claims are hereby incorporated into this Detailed Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

[**0576**] Moreover, though the present disclosure has included description of one or more embodiments and certain variations and modifications, other variations and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights which include alternative embodiments to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

What is claimed is:

1. A bone graft insertion device comprising:
 - a hollow tube having a length, a proximal end and a distal end, and an interior volume extending between the proximal end and the distal end;
 - the distal end of the hollow tube comprising a closed end;
 - at least one aperture provided proximal to the distal end of the hollow tube, wherein the at least one aperture is operable to transmit bone graft material from an interior of the hollow tube;
 - a plunger adapted for insertion within said hollow tube;
 - a positioning handle interconnected to the hollow tube, wherein the positioning handle is secured to the hollow

tube and wherein the positioning handle extends perpendicularly away from the hollow tube to provide a user-interface;

the proximal end of the hollow tube comprising a funnel that is operable to receive bone graft material, and wherein the funnel is selectively removable from the hollow tube;

wherein the hollow tube and the plunger are configured to deliver bone graft material to a graft receiving area through the at least one opening of the hollow tube.

2. The device of claim 1, wherein the at least one opening comprises first and second openings provided through side-walls of the hollow tube.

3. The device of claim 1, wherein the hollow tube comprises a ferrous material.

4. The device of claim 1, wherein the positioning handle is selectively removable from the hollow tube.

5. The device of claim 1, wherein the positioning handle is welded to the hollow tube.

6. A bone graft insertion device comprising:

a hollow tube having a length, a proximal end and a distal end, and an interior volume extending between the proximal end and the distal end, said distal end having at least one opening;

at least one aperture provided proximal to the distal end of the hollow tube, wherein the at least one aperture is operable to transmit bone graft material from the interior volume of the hollow tube;

a plunger adapted for insertion within the hollow tube;

a positioning handle interconnected to the hollow tube, wherein the positioning handle extends from the hollow tube to provide a user-interface;

the proximal end of the hollow tube comprising a funnel that is operable to receive bone graft material;

wherein said hollow tube and said plunger are configured to deliver bone graft material to a graft receiving area through one or more lateral openings near said distal end of said hollow tube.

7. The device of claim 6, wherein the at least one aperture comprises first and second apertures provided through side-walls of the hollow tube.

8. The device of claim 6, wherein the hollow tube comprises a ferrous material.

9. The device of claim 6, wherein the positioning handle is selectively removable from the hollow tube.

10. The device of claim 6, wherein the positioning handle is welded to the hollow tube.

11. The device of claim 6, wherein the distal end comprises at least one of a curved and a rounded tip.

12. The device of claim 6, wherein the funnel is selectively removable from the hollow tube.

13. A bone graft insertion device comprising:

a hollow tube having a length, a proximal end and a distal end, said hollow tube having an interior cross-section;

a plunger adapted for insertion within said hollow tube, said plunger having a distal end exterior surface that forming a substantially congruent fit with said hollow tube interior cross-section, said plunger having a distal tip contoured to conform to the distal end of said hollow tube; and

a positioning handle interconnected to the hollow tube, wherein the positioning handle extends away from the bone graft insertion device to provide a user-interface;

wherein said hollow tube and said plunger are configured to deliver bone graft material to a graft receiving area through one or more lateral openings provided proximal to the distal end of the hollow tube.

14. The device of claim 13, wherein the positioning handle is selectively detachable from the bone graft insertion device.

15. The device of claim 13, wherein the distal end comprises a closed end, and wherein the one or more lateral openings are operable to allow an egress of bone graft material from the device.

16. The device of claim 13, wherein the interior cross-section is rectangular.

17. The device of claim 13, wherein the distal end of the hollow tube comprises a tapered tip.

18. The device of claim 13, wherein the distal end exterior surface is of rectangular cross-section.

19. The device of claim 13, wherein the hollow tube comprises a metallic alloy.

20. The device of claim 13, further comprising a funnel configured to interconnect to the hollow tube.

* * * * *