



US 20200029961A1

(19) **United States**(12) **Patent Application Publication**
Scirica(10) **Pub. No.: US 2020/0029961 A1**(43) **Pub. Date: Jan. 30, 2020**(54) **SURGICAL INSTRUMENT HAVING A
PLASTIC SURFACE**(71) Applicant: **Covidien LP**, Mansfield, MA (US)(72) Inventor: **Paul Scirica**, Huntington, CT (US)(21) Appl. No.: **16/592,820**(22) Filed: **Oct. 4, 2019****Publication Classification**(51) **Int. Cl.****A61B 17/068** (2006.01)**A61B 17/072** (2006.01)**A61B 17/10** (2006.01)(52) **U.S. Cl.**CPC .. **A61B 17/068** (2013.01); **A61B 2017/00128**(2013.01); **A61B 17/105** (2013.01); **A61B****17/07207** (2013.01)**Related U.S. Application Data**


(60) Continuation of application No. 15/805,245, filed on Nov. 7, 2017, which is a continuation of application No. 14/643,589, filed on Mar. 10, 2015, now Pat. No. 9,814,461, which is a division of application No. 14/323,208, filed on Jul. 3, 2014, now Pat. No. 9,004,340, which is a division of application No. 13/545,034, filed on Jul. 10, 2012, now Pat. No. 8,770,458, which is a continuation of application No. 12/962,887, filed on Dec. 8, 2010, now Pat. No. 8,245,900, which is a division of application No. 12/198,948, filed on Aug. 27, 2008, now Pat. No. 7,866,525, which is a continuation-in-part of application No. 11/544,982, filed on Oct. 6, 2006, now Pat. No. 7,845,535.


(60) Provisional application No. 60/967,190, filed on Aug. 31, 2007.

(57)

ABSTRACT

A surgical instrument including a handle portion, a body portion, a movable handle, a tool assembly, a drive beam and a closure apparatus is disclosed. At least one of the closure apparatus and a contact surface of the tool assembly include a plastic surface. The body portion extends distally from the handle portion. The movable handle is located on the handle portion and is in mechanical cooperation with a drive member. The tool assembly includes an anvil, a cartridge assembly and a contact surface. The drive beam includes a proximal engagement portion and is configured to engage a portion of the drive member. The closure apparatus is configured to engage the contact surface of the tool assembly. At least a partial actuation of the movable handle moves the closure apparatus distally into engagement with the contact surface to approximate the anvil and the cartridge assembly.









FIG. 1A











FIG. 3









FIG. 3G




FIG. 4




FIG. 5








FIG. 6








FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15






FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27





FIG. 27b




FIG. 27c




FIG. 27d





FIG. 28



SURGICAL INSTRUMENT HAVING A PLASTIC SURFACE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 15/805,245, filed Nov. 7, 2017, which is a continuation of U.S. patent application Ser. No. 14/643,589, filed Mar. 10, 2015, now U.S. Pat. No. 9,814,461, which is a divisional of U.S. patent application Ser. No. 14/323,208, filed Jul. 3, 2014, now U.S. Pat. No. 9,004,340, which is a divisional of U.S. patent application Ser. No. 13/545,034, filed Jul. 10, 2012, now U.S. Pat. No. 8,770,458, which is a continuation of U.S. patent application Ser. No. 12/962,887, filed Dec. 8, 2010, now U.S. Pat. No. 8,245,900, which is a divisional of U.S. patent application Ser. No. 12/198,948, filed Aug. 27, 2008, now U.S. Pat. No. 7,866,525, which claims the benefit of, and priority to, U.S. Provisional Patent Application Ser. No. 60/967,190, filed Aug. 31, 2007, and is a continuation-in-part of U.S. patent application Ser. No. 11/544,982, filed Oct. 6, 2006, now U.S. Pat. No. 7,845,535. The entire contents of each of the above applications are hereby incorporated herein by reference.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to a surgical instrument and disposable loading unit including a plastic surface thereon. More particularly, the present disclosure relates to a surgical instrument which includes a plastic surface on at least one of a closure apparatus and a contact surface of a tool assembly.

2. Background of the Related Art

[0003] Surgical devices wherein tissue is first grasped or clamped between opposing jaw structure and then joined by surgical fasteners are well known in the art. In some instruments, a knife is provided to cut the tissue which has been joined by the fasteners. The fasteners are typically in the form of surgical staples but two part polymeric fasteners can also be utilized.

[0004] Instruments for this purpose may include two elongated members which are respectively used to capture or clamp tissue. Typically, one of the members carries a staple cartridge that houses a plurality of staples arranged in at least two lateral rows while the other member has an anvil that defines a surface for forming the staple legs as the staples are driven from the staple cartridge. In some instruments, the closure of the two elongated members, or tool assembly, is affected by actuation of a movable handle which moves a drive beam having a closure apparatus thereon into a contact surface of a tool assembly, thus approximating the members of the tool assembly. A large frictional force may be present between the closure apparatus and the contact surface of the tool assembly, thus possibly requiring a relatively large amount of force to be applied to the movable handle.

SUMMARY

[0005] In accordance with the present disclosure, a method of providing an insert having a low coefficient of friction on a closure member of a surgical device is disclosed which includes the steps of providing a closure member

having a flange portion and a vertical beam portion connected to the flange portion, providing a hole through the flange portion and forming in place a moldable material having a low coefficient of friction through the hole of the flange portion to cover at least a portion of an internal surface of the flange portion with the material. In one embodiment, the moldable material is plastic.

[0006] In one embodiment, the flange portion includes an upper flange portion and a lower flange portion which are interconnected by the vertical beam portion.

[0007] In one embodiment, the step of providing a hole includes the step of providing a hole through both the upper flange portion and the lower flange portion, and the step of injecting a moldable material includes the step of injecting a moldable material through each of the holes in the upper and lower flange portions.

[0008] In one embodiment, the internal surface of each of the upper and lower flange portions defines at least one recess and the moldable material is injected into the recesses through the holes.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Various embodiments of the presently disclosed surgical instrument are disclosed herein with reference to the drawings, wherein:

[0010] FIG. 1 is a side perspective view from the distal end of one embodiment of the presently disclosed surgical instrument with articulating tool assembly;

[0011] FIG. 1A is a side perspective view from the proximal end of a disposable loading unit (DLU) of the surgical instrument shown in FIG. 1 including the tool assembly;

[0012] FIG. 2 is a side perspective view of the distal end of mounting assembly and tool assembly, with parts separated, of the DLU of the surgical instrument shown in FIG. 1;

[0013] FIG. 3 is a side perspective view of the mounting assembly and the proximal body portion of the DLU shown in FIG. 1A with parts separated;

[0014] FIG. 3A is a side perspective view of a coupling member of the surgical instrument shown in FIG. 1;

[0015] FIG. 3B is a side perspective view of an upper mounting portion of the mounting assembly of the DLU of the surgical instrument shown in FIG. 1;

[0016] FIG. 3C is a side perspective view of a lower mounting portion of the mounting assembly of the DLU of the surgical instrument shown in FIG. 1;

[0017] FIG. 3D is a side perspective view from above the proximal body portion, the mounting assembly and the tool assembly of the DLU of the surgical instrument with the tool assembly in its non-articulated position;

[0018] FIG. 3E is a side perspective view from above the proximal body portion, the mounting assembly and the tool assembly shown in FIG. 3D with the tool assembly in an articulated position;

[0019] FIG. 3F is a side perspective view from below the proximal body portion, the mounting assembly and the tool assembly of the DLU of the surgical instrument with the tool assembly in its non-articulated position;

[0020] FIG. 3G is a side perspective view from below the proximal body portion, the mounting assembly and the tool assembly shown in FIG. 3F with the tool assembly in an articulated position;

[0021] FIG. 4 is a side cross-sectional view of the tool assembly of the DLU shown in FIG. 1A;

[0022] FIG. 5 is a top perspective view of the lock member actuator of the proximal body portion locking mechanism shown in FIG. 3;

[0023] FIG. 6 is a bottom perspective view of a locking member of the locking mechanism shown in FIG. 3;

[0024] FIG. 7 is a top view of the proximal end of the DLU proximal body portion shown in FIG. 1A with the locking mechanism in its locked position;

[0025] FIG. 8 is a cross-sectional view taken along section lines 8-8 of FIG. 7;

[0026] FIG. 9 is a top view of the proximal end of the DLU proximal body portion shown in FIG. 1A with the locking mechanism in its unlocked position;

[0027] FIG. 10 is a cross-sectional view taken along section lines 10-10 of FIG. 9;

[0028] FIG. 11 is a side perspective view of the DLU and surgical instrument shown in FIG. 1 prior to attachment of the DLU to the surgical instrument;

[0029] FIG. 12 is a top view of the proximal end of the DLU and the distal end of the surgical instrument shown in FIG. 11 prior to attachment to the distal end of the surgical instrument;

[0030] FIG. 13 is a top view of the proximal end of the DLU shown in FIG. 11 as the DLU is advanced linearly into the distal end of the surgical instrument;

[0031] FIG. 14 is a top view of the proximal end of the DLU and the distal end of the surgical instrument shown in FIG. 12 after the DLU has been advanced linearly but prior to locking the DLU to the surgical instrument;

[0032] FIG. 15 is a top view of the proximal end of the DLU and the distal end of the surgical instrument shown in FIG. 13 after the DLU has been advanced linearly and rotatably locked onto the surgical instrument;

[0033] FIG. 16 is a perspective view of a locking assembly for use with a surgical instrument in accordance with an embodiment of the present disclosure;

[0034] FIG. 17 is a perspective view of various components of the locking assembly of FIG. 16;

[0035] FIG. 18 is an enlarged perspective view of a portion of the locking assembly of FIGS. 16 and 17 illustrated with the articulating tool assembly in a non-articulated position;

[0036] FIG. 19 is an enlarged perspective view of a portion of the locking assembly of FIGS. 16-18 and including a link;

[0037] FIG. 20 is an enlarged perspective view of a portion of the locking assembly of FIGS. 16-19 illustrated with the articulating tool assembly in an articulated position;

[0038] FIG. 21 is an enlarged perspective view of another locking assembly for use with a surgical instrument in accordance with an embodiment of the present disclosure;

[0039] FIG. 22 is an enlarged bottom perspective view of the locking assembly of FIG. 21;

[0040] FIG. 23 is a perspective view of a drive beam having a plurality of layers and a closure apparatus in accordance with an embodiment of the present disclosure;

[0041] FIG. 24 is a perspective view of the drive beam and closure apparatus of FIG. 23 with parts separated;

[0042] FIG. 25 is a cross-sectional view of a portion of the drive beam and closure apparatus of FIGS. 23 and 24;

[0043] FIG. 26 is a cross-sectional view of a drive beam and a closure apparatus in accordance with an embodiment of the present disclosure;

[0044] FIG. 27 is a cross-sectional view of the drive beam and closure apparatus of FIG. 26;

[0045] FIG. 27a is a perspective view of a closure member in accordance with an embodiment of the present disclosure;

[0046] FIG. 27b is a cross-sectional view of the closure member shown in FIG. 27a taken along section lines 27b-27b of FIG. 27a;

[0047] FIG. 27c is a perspective view of the closure member shown in FIG. 27a prior to attachment of the insert;

[0048] FIG. 27d is a cross-sectional view of the closure member taken along section lines 27d-27d of FIG. 27c;

[0049] FIG. 28 is a perspective view of a tool assembly in accordance with an embodiment of the present disclosure; and

[0050] FIG. 29 is an assembly view of the tool assembly of FIG. 28.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0051] Embodiments of the presently disclosed surgical instrument and DLU will now be described in detail with reference to the drawings, in which like reference numerals designate identical or corresponding elements in each of the several views.

[0052] Referring to FIG. 1, surgical instrument 500 includes a handle portion 510, a body portion 512, and a disposable loading unit ("DLU") 16. Handle portion 510 includes a stationary handle 514 and a movable handle or trigger 516. Movable handle 516 is movable in relation to stationary handle 514 to advance a control rod 520 which projects from the distal end of body portion 512. Handle portion 510 and body portion 512 may be constructed in the manner disclosed in U.S. Pat. No. 6,330,965 which is hereby incorporated herein in its entirety by reference. Alternately, other surgical instruments can be used with DLU 16 to perform endoscopic surgical procedures.

[0053] Referring to FIGS. 1 and 1A, briefly, DLU 16 includes a tool assembly 17, a proximal body portion 200 and a mounting assembly 202. Body portion 200 has a proximal end adapted to releasably engage the distal end of a surgical instrument 500 (FIG. 11) in the manner to be discussed in detail below. Mounting assembly 202 is pivotally secured to a distal end of body portion 200 and is fixedly secured to a proximal end of tool assembly 17. Pivotal movement of mounting assembly 202 about an axis perpendicular to a longitudinal axis of body portion 200 affects articulation of tool assembly 17 between a non-articulated position in which the longitudinal axis of tool assembly 17 is aligned with the longitudinal axis of body portion 200 and an articulated position in which the longitudinal axis of tool assembly 17 is disposed at an angle to the longitudinal axis of body portion 200.

[0054] Referring to FIGS. 2-4, tool assembly 17 includes a cartridge assembly 18 and an anvil assembly 20. Anvil assembly 20 includes an anvil portion 28 having a plurality of staple deforming concavities 30 (FIG. 4) and a cover plate 32 secured to a top surface of anvil portion 28. Cover plate 32 and anvil portion 28 define a cavity 34 (FIG. 4) therebetween which is dimensioned to receive a distal end of a drive assembly 212 (FIG. 3). Cover plate 32 encloses the distal end of drive assembly 212 to prevent pinching of tissue during actuation of DLU 16. A longitudinal slot 38 extends through anvil portion 28 to facilitate passage of a retention flange 40 of drive assembly 212. A camming surface 42

formed on anvil portion 28 is positioned to engage a pair of cam members 40a supported on retention flange 40 of drive assembly 212 to effect approximation of the anvil and cartridge assemblies. A pair of pivot members 44 are formed. A pair of stabilizing members 50 engage a respective shoulder 52 formed on carrier 48 to prevent anvil portion 28 from sliding axially in relation to staple cartridge 54 as camming surface 42 is pivoted about pivot members 44.

[0055] Cartridge assembly 18 includes carrier 48 which defines an elongated support channel 56 which is dimensioned and configured to receive staple cartridge 54. Corresponding tabs 58 and slots 60 formed along staple cartridge 54 and elongated support channel 56, respectively, function to retain staple cartridge 54 at a fixed location within support channel 56. A pair of support struts 62 formed on staple cartridge 54 are positioned to rest on side walls of carrier 48 to further stabilize staple cartridge 54 within support channel 56. Carrier 48 has slots 46 for receiving pivot members 44 of anvil portion 28 and allowing anvil portion 28 to move between spaced and approximated positions.

[0056] Staple cartridge 54 includes retention slots 64 (FIG. 2) for receiving a plurality of staples or fasteners 66 and pushers 68. A plurality of laterally spaced apart longitudinal slots 70 extend through staple cartridge 54 to accommodate upstanding cam wedges 72 of an actuation sled 74 (FIG. 2). A central longitudinal slot 76 extends along substantially the length of staple cartridge 54 to facilitate passage of a knife blade 78 (FIG. 4). During operation of surgical stapler 10, drive assembly 212 abuts actuation sled 74 and pushes actuation sled 74 through longitudinal slots 70 of staple cartridge 54 to advance cam wedges 72 into sequential contact with pushers 68. Pushers 68 translate vertically along cam wedges 72 within fastener retention slots 64 and urge fasteners 66 from retention slots 64 into staple deforming cavities 30 (FIG. 4) of anvil assembly 20.

[0057] Referring to FIG. 3, mounting assembly 235 includes an upper mounting portion 236 and a lower mounting portion 238. A centrally located pivot member 284 extends from upper mounting portion 236 through a respective opening 246a formed in a first coupling member 246. Lower mounting portion 238 includes a bore 239 for receiving pivot member 284 (see FIG. 3F). Pivot member 284 extends through bore 239 and opening 247a of a second coupling member 247. Each of coupling members 246, 247 includes an interlocking proximal portion 246b, 247b configured to be received in grooves 290 formed in the distal end of an inner housing which is formed from upper and lower housing halves 250 and 252. Coupling members 246, 247 retain mounting assembly 235 and upper and lower housing halves 250 and 252 in a longitudinally fixed position in relation to each other while permitting pivotal movement of mounting assembly 235 in relation thereto.

[0058] Referring to FIGS. 3A-3C, each coupling member 246, 247 includes a cantilevered spring arm 246c which has a distal end 246d positioned to engage mounting assembly 235. More specifically, upper mounting portion 236 includes a top surface 236a which includes a recess 236b dimensioned to receive distal end 246d of spring arm 246c of a respective coupling member 246. Lower mounting portion 238 includes a bottom surface 238a having a pair of raised surfaces 238b which define a recess 238c which is dimensioned to receive spring arm 247c of a respective coupling

member 247. Alternatively, at least one recess may be formed in the proximal end of tool assembly 17.

[0059] As illustrated in FIGS. 3D-3G, when distal end of spring arms 246c, 247c of coupling members 246, 247 are positioned in recesses 236b and 238c of upper and lower mounting portions 236 and 238, respectively, spring arms 246c, 247c retain mounting assembly 235 in a non-articulated position. Spring arms 246c, 247c will retain mounting assembly 235 in its non-articulated position until a predetermined force sufficient to deflect spring arms 246c from recesses 236b and 238c is applied to effect articulation of mounting assembly 235 and tool assembly 17. When the predetermined force is applied to the mounting assembly 235 and tool assembly 17, spring arms 246c, 247c will spring or deflect outwardly from recesses 236b and 238c, as shown in FIGS. 3E and 3G, to permit pivotal movement of mounting assembly 235 (and, thus, tool assembly 17) in relation to the distal end of proximal body portion 200 of the DLU 16.

[0060] As discussed above, spring arms 246c and recesses 236b and 238c maintain tool assembly 17 in its non-articulated position until a predetermined force has been applied to mounting assembly 235 to disengage spring arms 246c, 247c from recesses 236b and 238c of mounting assembly 235. It is envisioned that the spring arms/recesses could be incorporated into any articulating surgical device including staplers, graspers (See FIG. 3H), powered sealing devices, e.g., RF sealing devices, etc. Further, although two spring arms/recesses are shown, a single spring arm can be provided. Moreover, the articulating tool assembly need not form part of a DLU but rather can be supported directly on the distal end of a surgical instrument. For example, the mounting assembly can be removably or irremovably secured to the tool assembly and secured directly to the distal end of a surgical instrument.

[0061] Upper housing half 250 and lower housing half 252 are contained within an outer sleeve 251 of body portion 200 (FIG. 3). Body portion 200 includes a cutout 251a dimensioned to receive a boss or projection 250a formed on upper housing half 250. The positioning of projection 250a within cutout 251a prevents axial and rotational movement of upper and lower housing halves 250 and 252 within outer sleeve 251 of body portion 200. In one embodiment, boss 250a has a substantially rectangular configuration having a greater axial dimension than lateral dimension. The greater axial dimension provides increased surface area for preventing rotation of upper and lower housing halves 250 and 252 within sleeve 251. A proximal portion 250b of boss 250a is ramped. Ramped proximal portion 250b allows sleeve 251 to be slid over boss 250a as upper and lower housing halves 250 and 252 are positioned within sleeve 251. It is envisioned that boss 250a may assume other configurations, e.g., circular, square, triangular, etc., and still achieve its intended function. Further, boss 250a can be repositioned anywhere along upper housing half 250 or, in the alternative, be positioned on lower housing half 252 or partly on each housing half 250 and 252.

[0062] The proximal end or insertion tip 193 of upper housing half 250 includes engagement nubs 254 for releasably engaging the distal end of a surgical instrument in a bayonet-type fashion (see FIGS. 1A and 7). Housing halves 250 and 252 define a channel 400 for slidably receiving axial drive assembly 212 therein. An articulation link 256 is dimensioned to be slidably positioned within a slot 402

formed between upper and lower housing halves 250 and 252. A pair of H-block assemblies 255 are positioned adjacent the distal end of housing portion 200 and adjacent the distal end of axial drive assembly 212 to prevent outward buckling and bulging of drive assembly 212 during articulation and firing of surgical stapling apparatus 10. Each H-block assembly 255 includes a flexible body 255a which includes a proximal end fixedly secured to body portion 200 and a distal end fixedly secured to mounting assembly 235 (FIG. 3).

[0063] A retention member 288 is supported on engagement section 270 of axial drive assembly 212. Retention member 288 includes a pair of fingers 288a which are releasably positioned within slots or recesses 252a formed in lower housing half 252. In operation, when SULU 16 is attached to a surgical instrument and axial drive assembly 212 is actuated by applying a predetermined force to an actuation member 516 of the surgical instrument 500 (FIG. 11), axial drive assembly 212 is advanced distally to move drive assembly 212 and retention member 288 distally. As retention member 288 is advanced distally, fingers 288a are forced from recesses 252a to provide an audible and tactile indication that the surgical instrument has been actuated. Retention member 288 is designed to prevent inadvertent partial actuation of DLU 16, such as during shipping, by maintaining axial drive assembly 212 at a fixed position within DLU 16 until a predetermined axial force has been applied to axial drive assembly 212.

[0064] Axial drive assembly 212 includes an elongated drive beam 266 including a distal working head 268 and a proximal engagement section 270. In one embodiment, drive beam 266 is constructed from multiple stacked sheets of material. Engagement section 270 includes a pair of resilient engagement fingers 270a and 270b which mountingly engage a pair of corresponding retention slots formed in drive member 272. Drive member 272 includes a proximal porthole 274 configured to receive distal end of a control rod 520 (FIG. 11) of a surgical instrument when the proximal end of DLU 16 is engaged with the body portion 512 of a surgical instrument 500.

[0065] Referring also to FIGS. 5-10, DLU 16 further includes a locking mechanism including a locking member 300 and a locking member actuator 302. Locking member 300 (FIG. 6) is rotatably supported within a longitudinal or axial slot 310 (FIG. 7) formed in a proximal portion of upper housing half 250 of body portion 200 of DLU 16. Locking member 300 is movable from a first position (FIGS. 7 and 8), in which locking member 300 maintains drive assembly 212 in a prefired position, to a second position (FIGS. 9 and 10), in which drive assembly 212 is free to move axially.

[0066] As illustrated in FIG. 6, locking member 300 includes semi-cylindrical body 312 which is slidably positioned within transverse slot 310 formed in upper housing half 250 of body portion 200. Body 312 includes a radially inwardly extending cam member 314 and a radially inwardly extending finger 316. Finger 316 is dimensioned to be slidably received within a notch or slot 270c (FIG. 3) formed in drive assembly 212. Engagement of finger 316 in notch 270c of drive assembly 212 prevents drive assembly 212 from moving linearly within body portion 200 and, thus, prevents actuation of DLU 16.

[0067] Referring to FIGS. 3, 5 and 7, a locking member actuator 302 is slidably positioned within an axial slot 320 (FIG. 7) formed in upper housing half 250 of body portion

200 of DLU 16. Actuator 302 includes a proximal abutment member 322, a distal spring guide 324, and a central cam slot 326. Axial slot 320 intersects transverse slot 310 such that cam member 314 of locking member 300 is slidably positioned within cam slot 326 of locking member actuator 302. A biasing member or spring 328 (FIG. 7) is positioned about spring guide 324 between a distal surface 330 of actuator 302 and a wall 332 (FIG. 7) defining the distal end of axial slot 320. Spring 328 urges actuator 302 to its retracted position within axial slot 320. In its retracted position, abutment member 322 is positioned on and extends radially outwardly of the proximal end of DLU 16 adjacent insertion tip 193 of proximal body portion 200 and cam slot tip 326 is positioned to locate cam member 314 such that finger 316 of lock member 300 is positioned within notch 270c of drive assembly 212.

[0068] FIGS. 11-15 illustrate DLU 16 and surgical instrument 500 prior to and during attachment of DLU 16 to surgical instrument 500. Prior to attachment of DLU 16 onto surgical instrument 500, spring 328 urges actuator 302 to its retracted position to move lock member 300 to its locked position as discussed above. When insertion tip 193 DLU 16 is linearly inserted into the open end 522 (FIG. 11) of the body portion 512 (FIG. 13) of a surgical instrument 500, nubs 254 move linearly through slots (not shown) formed in open end 522 of body portion 512. As nubs 254 pass through the slots, the proximal end 322a of abutment member 322, which is angularly offset from nubs 254, abuts a wall 276c defining the slots for receiving nubs 254. As DLU 16 is moved further into body portion 512, locking member actuator 302 is moved from its retracted position to its advanced position in the direction indicated by arrow "T" in FIG. 14. As actuator 302 is moved to its advanced position, lock member 300 is cammed in the direction indicated by arrow "U" in FIG. 14 from its locked position (FIG. 8) engaged with drive assembly 212 to its unlocked position (FIG. 10) to move finger 316 from notch 270c. The locking mechanism including locking member 300 and locking member actuator 302 prevents accidental or inadvertent advancement or manipulation of the drive member of DLU 16 such as during loading of DLU 16 onto a surgical instrument 500.

[0069] When DLU 16 has been moved linearly in relation to instrument 500 to a position wherein a proximal surface 530 of body portion 200 abuts inner surface 276c of body portion 512 (FIG. 15), DLU 16 can be rotated in relation to body portion 512 in a bayonet-type action to position nubs 254 within openings 536 of body portion 512 to lock DLU 16 onto body portion 512. It is envisioned that other coupling types besides bayonet couplings may be used to connect DLU 16 to instrument 500, e.g., spring detent or snap-fit couplings, friction fit couplings, interlocking members, threaded couplings etc.

[0070] In an embodiment of the present disclosure illustrated in FIGS. 16-20, a locking assembly 600 is illustrated for use with surgical instrument 500 and disposable loading unit 16 (see FIG. 1, for example). In the illustrated embodiments, locking assembly 600 includes a housing 602, a pusher 604, a rod 606, a slide 608, at least one spring 610, a cam finger 612, a pivot plate 614 having slots 616 and a link 618. Locking assembly 600 generally helps tool assembly 17 (see FIG. 1, for example) maintain its position during firing of surgical instrument 500.

[0071] Referring to FIGS. 16 and 17, a portion of locking assembly 600 is at least partially contained within a housing 602. FIG. 16 illustrates locking assembly 600 disposed in relation to housing 602, while FIG. 17 illustrates locking assembly 600 isolated from housing 602. In the illustrated embodiment of FIG. 17, pusher 604 is shown with rod 606 extending distally therefrom. Slide 608 extends distally from rod 606 and is in a slidable relationship therewith, thus allowing slide 608 to move axially with respect to rod 606. Spring 610 or pair of springs (not explicitly shown in this embodiment) distally biases slide 608 from rod 606.

[0072] Now referring to FIGS. 18-20, cam finger 612 and pivot plate 614 are illustrated. Cam finger 612 extends distally from slide 608 and pivot plate 614 may be disposed on mounting assembly 235 (see FIG. 3), for example. It is envisioned that pivot plate 614 may be disposed on or incorporated with a portion of tool assembly 17. A plurality of slots 616 (five slots 616 are illustrated) is disposed on pivot plate 614 and are sized to accept at least a portion of cam finger 612 therein. Upon different amounts of articulation of tool assembly 17 (including no substantial articulation) with respect to body portion 512 (see FIG. 1, for example), cam finger 612 is approximately aligned with an individual slot 616 of pivot plate 614. FIGS. 18 and 19 illustrate cam finger 612 substantially aligned with a center slot 616a (hidden from view in FIG. 19) and FIG. 20 illustrates cam finger 612 substantially aligned with a side slot 616b.

[0073] Link 618, illustrated in FIGS. 17 and 19, is in mechanical engagement with pivot plate 614 and cam finger 612. (In FIG. 18, the link has been removed.) Link 618 is illustrated having an opening 620 and a slot 622 (FIG. 19). Opening 620 is in a pivotal relationship with a boss 624 on pivot plate 614 and slot 622 is slidably engaged with cam finger 612. This relationship allows for articulation of pivot plate 614 with respect to body portion 512 and for longitudinal translation of slide 608 with respect to pivot plate 614.

[0074] In operation, upon at least a partial actuation of movable handle 516 (see FIG. 1, for example), pusher 604 is forced distally, e.g., via control rod 520 (see FIG. 11, for example), thus causing distal translation of cam finger 612 at least partially into a slot 616 of pivot plate 614. It is envisioned that actuating movable handle 516 to approximate cartridge assembly 18 and an anvil assembly 20 (see FIG. 1A, for example) also functions to translate cam finger 612 distally. In such an embodiment, when articulating tool assembly 17 is in place and clamped on tissue, further articulation cannot be accomplished (without releasing movable handle 516, for example). Thus, locking assembly 600 helps maintain articulating tool assembly 17 in position with respect to body portion 512, prior to emplacing staples into tissue, for example.

[0075] As discussed above, spring 610 distally biases slide 608 from rod 606. This biasing provided by spring 610 helps ensure cam finger 612 is not accidentally or prematurely dislodged from slot 616 of pivot plate 614, which may result in a significant amount of "play" therebetween. Additionally, the distal bias provided by spring 610 helps eliminate manufacturing tolerances and/or clearances that are present between slide 608 and pivot plate 614. It is also envisioned that at least a portion of cam finger 612 and/or slot 616 may be wedge-shaped to help reduce any unintended movement therebetween. In such an embodiment, a distal portion of

cam finger 612 and slot 616 would be narrower than a corresponding proximal portion.

[0076] In an embodiment of the present disclosure illustrated in FIGS. 21 and 22, a locking assembly 700 is illustrated for use with surgical instrument 500 and disposable loading unit 16 (see FIG. 1, for example). In the illustrated embodiment, locking assembly 700 includes an adapter 702, a pusher 704, a pivot 706, a biasing element (e.g., a pair of springs 708) and a link 710. Locking assembly 700 generally helps maintain tool assembly 17 in a predetermined position.

[0077] With reference to FIG. 21, adapter 702 of locking assembly 700 is generally housed within body portion 512 (see FIG. 1, for example) of surgical instrument 500 or within disposable loading unit 16. In the illustrated embodiment, pusher 704 is located distally of a pair of springs 708. Pusher 704 is distally biased via the pair of springs 708 towards pivot 706 of articulating tool assembly 17. A distal portion of pusher 704 includes a pusher mating surface 712 (FIG. 22) which is shaped and dimensioned to mate with a pivot mating surface 714 (FIG. 22) disposed adjacent a proximal portion of pivot 706. Link 710 is illustrated in mechanical cooperation with a portion of pusher 704 and pivotably connected to a portion of pivot 706, thus allowing articulating tool assembly 17 to move between its first position and its second position with respect to body portion 512. More specifically, link 710 includes an opening 711 that fits over a protrusion 707 of pivot 706, thus allowing pivotal movement therebetween. Further, link 710 is slidably engaged with a portion of adapter 702, thus allowing longitudinal movement therebetween.

[0078] Now referring to FIG. 22, pusher mating surface 712 is substantially flat along a majority of its length in this embodiment. Correspondingly, pivot mating surface 714 is also flat along a majority of its length in the illustrated embodiment. Thus, the distal bias of pusher 704 towards pivot 706 (in the direction of arrow A) via the pair of springs 708, helps maintain articulating tool assembly 17 in its first, non-articulated, position, as the biasing force helps articulating tool assembly 17 resist pivoting. While two springs 708 are illustrated, more or fewer springs 708 may be provided.

[0079] To pivot articulating tool 17 from its first, non-articulated position, the distal biasing force from pair of springs 708 must be overcome. Such a pivoting action, moves pusher 704 proximally (in the direction of arrow B) against the bias of pair of springs 708. It is also envisioned that pusher mating surface 714 includes detents (not explicitly shown in this embodiment) to help stabilize articulating jaw member 17 in selected articulated positions.

[0080] With continued reference to FIG. 22, pivot 706 includes a shelf 716 thereon. As shown in FIG. 22, shelf 716 overlaps at least a portion of pusher 704 when pusher mating surface 712 is in contact with pivot mating surface 714. Shelf 716 is situated and configured to help prevent tissue from being pinched between pusher 704 and pivot 706 when articulating tool assembly 17 is rotated and/or articulated.

[0081] In an embodiment of the present disclosure illustrated in FIGS. 23-25, a multi-layered drive beam 750 having a plurality of layers 750a-750e is illustrated and may be included in a disposable loading unit 16 (see FIG. 1, for example). A closure apparatus 760, such as an I-beam, is also illustrated. Closure apparatus 760 includes a horizontal portion 762 that is advanceable into camming surface 42 (or

other contact surface) to approximate tool assembly tool assembly 17, as described in detail above with reference to FIG. 2.

[0082] With reference to FIG. 24, multi-layered drive beam 750 having five layers 750a-750e is illustrated. It is envisioned and within the scope of the present disclosure that fewer or more layers may be used to form multi-layered drive beam 750. It is also envisioned that multi-layered drive beam 750 may replace drive beam 266 in other embodiments of this disclosure. Use of multi-layered drive beam 750 may provide increased strength and flexibility during use, specifically, for instance, while tool assembly 17 is in an articulated position.

[0083] A plurality of cutouts 770 is illustrated in FIGS. 23-25 which extend through each layer of multi-layered drive beam 750. Although the figures show between five and ten cutouts per layer of multi-layered drive beam 750, the exact number of cutouts 770 may be fewer than five, between five and ten, or greater than ten. Additionally, cutouts 770 of adjacent layers of drive beam 750 may or not align with each other. The use of cutouts 770 reduces cross-sectional dimensions of drive beam 750 and allows for bending force adjustment. While rectangular cutouts 770 are illustrated, the use of cutouts 770 having other regular or non-regular shapes is also contemplated.

[0084] The attachment of each layer 750a-750e of multi-layered drive beam 750 and the attachment to closure apparatus 760 are illustrated in FIG. 25. In the illustrated embodiment, an outer layer (750a or 750e of FIG. 24) is affixed to closure apparatus 760 in two locations (each location being indicated by numeral 780 in FIG. 25), via a pair of spot welds, for example. It is also envisioned that each outer layer 750a, 750e includes an aperture 776 that fits over a boss 778 protruding from closure apparatus 760. Each outer layer 750a, 750e is also affixed to an adjacent layer (e.g., 750b or 750d) in two locations (each location being indicated by numeral 781 in FIG. 25), possibly via a pair of spot welds. Further, each inner layer (e.g., 750b, 750c and 750d) is attached to an adjacent inner layer (for instance, 750b is attached to 750c; 750c is attached to 750b and 750d; and 750d is attached to 750c) in two locations, via spot welds, for example. While spot welding is disclosed as an attachment method, other methods for attaching each layer to each other and the outer layers to the closure apparatus are envisioned and within the scope of the present disclosure. The illustrated embodiments show attachment points 780 of inner layers adjacent closure apparatus 760, but it is envisioned and within the scope of the present disclosure that attachment points 780 are disposed in other locations on drive beam 750. Additionally, it is envisioned that at least one layer of drive beam 750 is made of a metal, such as stainless steel. Portions of drive beam 750 and/or closure apparatus 760 may also be made of or at least partially coated with a plastic material, as described below. Further, closure apparatus 790 may include a cutting surface 766 (FIG. 23) thereon for cutting tissue.

[0085] In an embodiment of the present disclosure illustrated in FIGS. 26 and 27, a closure apparatus 800 and a portion of drive beam 802 are shown. Closure apparatus and/or a contact surface (e.g., camming surface 42) of tool assembly 17 (see FIG. 2, for example) may include a plastic surface or plastic coating. In this embodiment, closure apparatus 800 is illustrated having a pair of caps 804 at least partially covering horizontal portions 806 of closure appa-

ratus 800. Caps 804 may be made of plastic in this embodiment. Such plastic surfaces disposed on closure apparatus 800 and/or contact surface of tool assembly 17 generally reduce the amount of friction therebetween vis-a-vis two metal surfaces. That is, a plastic to metal or a plastic to plastic interaction may create less friction than interaction between a pair of metal surfaces. This reduced amount of friction may correspond to a reduced firing force.

[0086] It is envisioned that a portion of closure apparatus 800, such as pair of caps 804, is made of plastic, overmolded with plastic or includes a plastic coating. Additionally, a contact surface of tool assembly 17, or at least a portion thereof, may also be made of plastic, be overmolded with plastic or include a plastic coating.

[0087] In an embodiment of the disclosure, closure apparatus 800 may include an I-shaped cross section, as illustrated in FIGS. 26 and 27. Additionally, closure apparatus 800 and drive beam 802 may be part of a disposable loading unit 16 and/or part of a surgical instrument 500 that is able to articulate. Further, drive beam 802 may include a single layer or a plurality of layers (as shown in FIG. 26) and at least a portion of drive beam 802 may be made of plastic. Still further, closure apparatus 800 may include a cutting surface 808 (FIG. 27) thereon for cutting tissue.

[0088] With continued reference to FIGS. 26 and 27, plastic cap 804 may include a reinforced section 810 which may increase the strength of closure apparatus 800 or may provide a stronger connection between cap 804 and horizontal portion 806 of closure apparatus 800. It is also envisioned that cap 804 may be removably attached to closure apparatus 800. In such an embodiment, cap 804 may be removed and replaced if any substantial wearing or damage occurs.

[0089] FIGS. 27a-27d illustrate an alternative embodiment of the presently disclosed closure member shown generally as 800'. As discussed above with respect to closure member 800, closure member 800' may include an I-shaped cross-section which includes an upper flange portion 802', a lower flange portion 804' and a vertical beam portion 806' which extends between upper flange portion 802' and lower flange portion 804'. Closure member 800' can be formed of metal, e.g., stainless steel, etc. Each of upper flange portion 802' and lower flange portion 804' includes an external surface 807' and an internal surface 808'. Each internal surface 808' includes a cutout or recess 810' (FIG. 27d) which is dimensioned to receive an insert 812' formed of a material having a low coefficient of friction. In one embodiment, insert 812' is formed of plastic although it is envisioned that other materials having a low coefficient of friction and the requisite strength characteristics may also be used to form insert 812'. As illustrated, insert 812' may extend slightly below the internal surface 808' of upper flange portion 802' and slightly above the internal surface 808' of lower flange portion 804'. Although inserts 812' are illustrated as extending along only a portion of the length of internal surfaces 808' of upper and lower flange portions 802' and 804', it is envisioned that inserts 812' may extend over the entire or substantially the entire length of internal surfaces 808'.

[0090] Vertical beam portion 806' includes a cutout 814' dimensioned to receive a drive beam (See, e.g., drive beam 802 in FIG. 27) and a knife blade 816'. Knife blade 816' can be secured to vertical beam portion 806', such as by welding, or machined directly therein. Similarly, the drive beam can

be welded to closure member **800'**, formed integrally therewith, or secured to closure member **800'** using other known fastening techniques.

[0091] Referring to FIGS. **27a** and **27c**, the distal edge **819'** of lower flange portion **804'** includes a chamfer or radiused edge **820'**. The distal edge **819'** is the edge that first engages tool assembly **17**. In one embodiment, radiused edge **820'** is spaced from insert **812'** and is positioned to effect approximation of the pivotable jaw of the stapling device. See FIG. **1**.

[0092] Referring to FIGS. **27c** and **27d**, in one embodiment insert **812'** (FIG. **27a**) is attached to upper flange portion **802'** and lower flange portion **804'** by forming the insert **812'** in place. This may be done using an injection molding process. In one embodiment of the process, a hole **822'** is drilled into and through upper and/or lower flange portions **802'** and **804'** such as to communicate with recesses **810'** of upper flange portion **802'** and lower flange portion **804'**. Each hole **822'** communicates from the external surface **806'** with both recesses **810'** on internal surface **808'** of upper or lower flange portions. Alternatively, two holes can be drilled through each of upper and lower flange portions **802'** and **804'**, with each hole communicating with one recess on one side of vertical beam portion **806'**. Next, closure member **800'** is positioned within a mold and mold material is injected through the hole **822'** into recesses **810'** to form inserts **812'**. The mold can be configured to provide any desired insert configuration. After the molding step, the insert or inserts **812'** can be machined or further shaped and the closure member **800'** can be machined or cleaned in a known manner to prepare closure member **800'** for use in a surgical device.

[0093] In an embodiment of the present disclosure illustrated in FIGS. **28** and **29**, a tool assembly **850** is illustrated. Tool assembly **850** of this embodiment includes a channel **852**, a first attachment member **860**, a second attachment member **870**, an anvil assembly **880**, a first attachment rod **890** and a second attachment rod **892**. First and second attachment rods **890**, **892** provide a strong connection facilitating the elements of tool assembly **850** to remain together.

[0094] Channel **852** includes an opening **854** (two openings are illustrated) adjacent its proximal end and first attachment member **860** includes a boss **862** (two bosses are illustrated) extending therefrom. Channel **852** is connectable to first attachment member by placing opening(s) **854** over boss(es) **862**, thus providing a pivotal connection therebetween. Although not explicitly illustrated in the present embodiment, channel **852** may house a plurality of surgical fasteners or a staple cartridge.

[0095] Anvil assembly **880** includes an anvil cover **882** and an anvil **886**. Anvil **886** is configured for mechanical engagement with anvil cover **882**, e.g., via a snap-fit connection. An aperture **884** extends at least partially through a portion of anvil cover **882**. Aperture **884** is configured to fit over a protrusion **872** disposed on second attachment member **870**, thereby providing a connection between anvil assembly **880** and second attachment member **870**. Additionally, anvil cover **882** includes at least one opening **888** extending at least partially therethrough in an embodiment of the disclosure. Opening **888** is configured to fit over boss **862** of first attachment member **860**. In such an embodiment, anvil assembly **880** may be pivoted with respect to first attachment member **860** and second attachment member **870**.

[0096] First attachment member **860** includes a first opening **864** and a second opening **866** extending therethrough. Second attachment member **870** also includes a first opening **874** and a second opening **876** extending therethrough (FIG. **29**). Further, first attachment member **860** and second attachment member **870** are in mechanical engagement, such that first openings **864**, **874** substantially align and second openings **866**, **876** substantially align.

[0097] To secure first attachment member **860** with second attachment member **870** (and thus channel **852** and anvil assembly **880**), first attachment rod **890**, or a portion thereof, is inserted through first openings **864** and **874**. To further secure the elements of tool assembly **850**, second attachment rod **892**, or a portion thereof, is inserted through second openings **866** and **876**. It is envisioned that first attachment rod **890** and/or second attachment rod **892** are rivets, such as two-part rivets that are tightenable.

[0098] In an embodiment of the disclosure, tool assembly **850** is part of a disposable loading unit, which may be able to articulate. Articulation of tool assembly **850** may be facilitated by pivotably attaching tool assembly **850** to a body portion of a surgical instrument via protrusion **874** extending from second attachment member **870** and a link (such as link **710** in FIG. **21**). Additionally, a method of assembling tool assembly **850**, as described above, is contemplated by the present disclosure.

[0099] It will be understood that various modifications may be made to the embodiments disclosed herein. For example, the above-described lock assembly may be incorporated into a variety of surgical instruments which include DLUs and is not limited to use on linear staplers. Further, the DLU may be configured to receive an insertion tip of surgical instrument in contrast to that disclosed. Therefore, the above description should not be construed as limiting, but merely as exemplifications of various embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

1-20. (canceled)

21. A method of manufacturing a surgical instrument, the method comprising:

providing a closure member having an upper flange portion and a lower flange portion arranged for engaging at least one jaw of the surgical instrument, the at least one jaw being made from a metallic material;

forming a hole through at least one of the upper and lower flange portions; and

injecting a material having a low coefficient of friction into the hole to form a surface on the at least one of the upper and lower flange portions having a low coefficient of friction that is positioned to engage the at least one jaw.

22. The method according to claim **21**, wherein providing the closure member includes the closure member having a vertical beam portion interconnecting the upper flange portion and the lower flange portion, the upper and lower flange portions having an internal surface and an external surface.

23. The method according to claim **22**, wherein forming the hole includes forming the hole such that the hole extends from the external surface to the internal surface of the at least one upper and lower flange portions, and injecting the material includes injecting the material at the external surface to the internal surface to form the surface having a low

coefficient of friction such that at least a portion of the internal surface of the at least one upper and lower flange portion.

24. The method according to claim **21**, wherein forming the hole includes drilling the hole.

25. The method according to claim **21**, wherein injecting the material includes the material having the low coefficient of friction is a plastic material.

26. The method according to claim **21**, wherein providing the closure member includes providing a recess in the internal surface of the at least one upper and lower flange portion.

27. The method according to claim **21**, further including machining the material after injecting the material into the hole.

28. A method of manufacturing a surgical instrument, the method comprising:

securing an anvil assembly to a cartridge assembly;
forming a closure apparatus from metal, the closure apparatus having a first portion;
securing a first plastic member having a low coefficient of friction to the first portion of the closure apparatus;
securing the closure apparatus to a distal portion of a drive beam; and

advancing the drive beam distally to move the first plastic member of the closure apparatus into engagement with a first contact surface of at least one of the anvil assembly or the cartridge assembly to move at least one of the anvil assembly or the cartridge assembly towards an approximated configuration.

29. The method according to claim **28**, wherein forming the closure apparatus includes forming metal into an I-shaped cross-section having an upper horizontal portion and a lower horizontal portion.

30. The method according to claim **29**, wherein securing the first plastic member to the first portion of the closure apparatus includes securing the first plastic member to the upper horizontal portion.

31. The method according to claim **30**, further comprising securing a second plastic member to the lower horizontal portion.

32. The method according to claim **29**, wherein securing the first plastic member to the first portion of the closure apparatus includes securing the first plastic member to the lower horizontal portion.

33. The method according to claim **28**, further comprising removing the first plastic member after securing the first plastic member.

34. The method according to claim **28**, further comprising forming the contact surface of the at least one of the anvil assembly or the cartridge assembly out of metal.

35. The method according to claim **34**, further comprising overmolding a plastic section on the contact surface of the at least one of the anvil assembly or the cartridge assembly to reduce friction with the first portion.

36. A method of manufacturing a surgical instrument, the method comprising:

forming a closure apparatus including a first portion formed from metal;

overmolding a plastic member having a low coefficient of friction onto the first portion of the closure apparatus; securing the closure apparatus to a distal portion of a drive beam;

advancing the drive beam distally to move the plastic member of the closure apparatus into engagement with a contact surface of at least one of an anvil assembly or a cartridge assembly to move at least one of the anvil assembly or the cartridge assembly towards an approximated configuration.

37. The method according to claim **29**, wherein forming the closure apparatus includes forming metal into an I-shaped cross-section having an upper horizontal portion and a lower horizontal portion.

38. The method according to claim **37**, wherein overmolding the plastic member on the first portion of the closure apparatus includes overmolding the plastic member on the upper horizontal portion.

39. The method according to claim **38**, further comprising overmolding the plastic member on the lower horizontal portion.

40. The method according to claim **37**, wherein overmolding the plastic member on the first portion of the closure apparatus includes overmolding the plastic member on the lower horizontal portion.

* * * * *