

(51) International Patent Classification:
D06F 39/00 (2006.01)(21) International Application Number:
PCT/EP2012/064514(22) International Filing Date:
24 July 2012 (24.07.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11176078.1 1 August 2011 (01.08.2011) EP(71) Applicant (for all designated States except US): **ELECTROLUX HOME PRODUCTS CORPORATION N.V.**
[BE/BE]; Raketstraat 40, B-1130 Brussels (BE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DEL POS, Maurizio** [IT/IT]; Electrolux Italia S.p.A., Via Revedole 83, I-33170 Pordenone (IT). **FAVARO, Daniele** [IT/IT]; Electrolux Italia S.p.A., Corso Lino Zanussi 30, I-33080 Porcia (PN) (IT). **ZATTIN, Andrea** [IT/IT]; Electrolux Italia S.p.A., Corso Lino Zanussi 30, I-33080 Porcia (IT).(74) Agents: **NARDONI, Andrea** et al.; Electrolux Italia S.p.A., Corso Lino Zanussi 30, I-33080 Porcia (PN) (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: LAUNDRY WASHING MACHINE




Fig. 6

(57) **Abstract:** Laundry washing machine (1) comprising an outer casing (2), a washing tub (3) arranged inside said casing (2) directly facing a laundry loading/unloading opening realized in a front wall (2a) of said casing (2), a rotatable drum arranged in axially rotating manner inside the washing tub (3) and structured for receiving the laundry to be washed, an detergent dispenser (9) which is housed inside the casing (2) between the washing tub (3) and the top wall (2d) of the casing (2) and is structured for feeding into the washing tub (3) a detergent, softener and/or other washing agent mixed with fresh water arriving from the water mains, and a water softening device (11) which is arranged inside the boxlike casing (2) and is structured for reducing the hardness degree of the fresh water supplied to the washing tub (3); the water softening device (11) in turn comprising a water-softening agent container (23) filled with a water softening agent able to reduce the hardness degree of the fresh water supplied to the washing tub (3), and a regeneration-agent reservoir (21) which is fluidly connected to said water-softening agent container (23) and is structured to receive a salt or other regeneration agent for performing a regeneration of the water softening function of said water softening agents; at least one among the water-softening agent container (23) and the regeneration-agent reservoir (21) being a stand-alone modular component-part (21, 23) which is provided with mechanical coupling means (21a, 23a) structured for allowing rigid fastening of said stand-alone modular component-part (21, 23) to the detergent dispenser (9).



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

LAUNDRY WASHING MACHINE

5 The present invention relates to a laundry washing machine.

 In particular, the present invention relates to a front-loading home laundry washing machine, to which the following description refers purely by way of example without this implying any loss of generality.

 As is known, currently marketed front-loading home laundry washing
10 machines generally comprise: a substantially parallelepiped-shaped boxlike outer casing structured for resting on the floor; a substantially bell-shaped washing tub which is suspended in floating manner inside the casing, directly facing a laundry loading/unloading through opening realized in the front wall of the casing; a substantially cylindrical elastically-deformable bellows, which connects the front
15 opening of the washing tub to the laundry loading/ unloading opening formed in the front wall of the casing; a porthole door which is hinged to the front wall of the casing to rotate to and from a closing position in which the door closes the laundry loading/unloading opening in the front wall of the casing for watertight sealing the washing tub; a substantially cylindrical, bell-shaped revolving drum structured for
20 housing the laundry to be washed, and which is housed inside the washing tub in axially rotating manner about its substantially horizontally-oriented longitudinal axis, and with its concavity facing the laundry loading/unloading opening; and finally an electrically-powered motor assembly which is structured for driving into rotation the revolving drum about its longitudinal axis inside the washing tub.

25 This type of home laundry washing machines is furthermore provided with a drawer detergent dispenser which is located inside the boxlike casing, immediately above the washing tub, and is structured for selectively feeding into the washing tub, according to the washing cycle manually-selected by the user via a control panel usually located on the front wall of the boxlike casing, a given amount of detergent,
30 softener and/or other washing agent suitably mixed with the fresh water arriving from the water mains, or even merely a given amount of fresh water arriving from

the water mains.

More specifically, the detergent dispenser generally comprises a detergent drawer which is fitted in manually extractable manner into a internal drawer housing whose entrance is located on front wall of the boxlike casing, above the porthole door. This detergent drawer is usually divided into a number of detergent compartments each of which is manually fillable with a corresponding detergent product, and the detergent dispenser furthermore comprises a drawer flush circuit which is structured to spill/pour a given amount of fresh water drawn from the water mains selectively and alternatively into each detergent compartment of the detergent drawer for flushing the detergent, softener or other washing agent out of the compartment and down into a funnel-shaped catchment basin which is realized on the bottom of the drawer housing and directly communicates with the inside of the washing tub via a drain duct.

As is known the hardness of the fresh water drawn from the water mains deeply negatively influences the cleaning efficiency of the detergents and softeners used in the washing cycle, thus the user is usually requested to considerably increase the amount of detergent and softener used in the washing cycle when the hardness degree of the tap water is too high.

To solve this problem the European patent application No. 1085118 discloses a front-loading home laundry washing machine provided with an internal water softening device capable of reducing, during each washing cycle, the hardness degree of the tap water used in the pre-washing and washing phases of the washing cycle. This water softening device uses ion-exchange resins to restrain calcium and magnesium ions (Ca^{++} and Mg^{++}) dissolved in the tap water channeled to the washing tub, and uses brine (i.e. salt water) to periodically regenerate these ion-exchange resins. Salt water, in fact, is able to remove from the ion-exchange resins the calcium and magnesium ions previously combined/fixed to said resins.

Unluckily integration of the salt reservoir on the back of the detergent drawer has brought to a very complicated detergent-dispenser structure with a consequent significant increase in the detergent dispenser overall production cost.

Another drawback associated to the arrangement of the salt reservoir on the

back of the detergent drawer is that the capacity of the salt reservoir is limited, and that the brine formed inside the salt reservoir may accidentally come out of the salt reservoir during normal extraction and insertion of the detergent drawer and form, on the bottom of the drawer housing, relevant salt deposits that, in long term, may
5 hinder extraction and insertion of the detergent drawer and/or impede the correct alignment of the salt reservoir with the resin container located immediately beneath said salt reservoir, with all problem concerned.

Last but not less important, the brine accidentally coming out of the salt reservoir may fall into the funnel-shaped catchment basin realized on the bottom of
10 the drawer housing. This catchment basin communicates with the upper portion of the washing tub, thus the brine may fall down onto the outer surface of the revolving drum that is generally made of metal, and therefore cause a quick rusting up of the revolving drum.

Aim of the present invention is to realize an internal water softening device
15 designed to eliminate the drawbacks referred above.

In compliance with the above aims, according to the present invention there is provided a laundry washing machine comprising an outer casing, a washing tub arranged inside said casing directly facing a laundry loading/unloading opening realized in a front wall of said casing, a rotatable drum arranged in axially rotating
20 manner inside the washing tub and structured for receiving the laundry to be washed, an detergent dispenser which is structured for supplying detergent into the washing tub, and a water softening device which is arranged inside the boxlike casing and is structured for reducing the hardness degree of the fresh water supplied to the washing tub; the water softening device in turn comprising a water-softening agent
25 container filled with a water softening agent able to reduce the hardness degree of the fresh water supplied to the washing tub, and a regeneration-agent reservoir structured to receive a salt or other regeneration agent for performing a regeneration of the water softening function of said water softening agents; wherein at least one among the water-softening agent container and the regeneration-agent reservoir is a stand-
30 alone modular component-part which is provided with mechanical coupling means structured for allowing rigid fastening of said stand-alone modular component-part to

the detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the detergent dispenser is provided with a first housing which extends inside the casing, and in that at least one among the water-softening agent container and the regeneration-agent reservoir is structured for being
5 rigidly fastened to the first housing of said detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the regeneration-agent reservoir of the water softening device is arranged beside the first housing of the detergent dispenser.

10 Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the regeneration-agent reservoir is arranged beside the first housing of the detergent dispenser, in a direction locally substantially parallel to the front wall of the casing.

Preferably, though not necessarily, the laundry washing machine is
15 furthermore characterized in that the regeneration-agent reservoir is provided with mechanical coupling means structured for allowing rigid fastening of the regeneration-agent reservoir to a sidewall of the first housing of said detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is
20 furthermore characterized in that the water-softening agent container is a stand-alone modular component-part which is provided with mechanical coupling means structured for allowing rigid fastening and fluidical connection of the water-softening agent container to the bottom of the regeneration-agent reservoir.

Preferably, though not necessarily, the laundry washing machine is
25 furthermore characterized in that said water-softening agent container is located beneath said regeneration-agent reservoir within a seat delimited by the lateral wall of the casing, the upper portion of the washing tub and the front wall of the casing.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water-softening agent container is a stand-alone
30 modular component-part which is provided with mechanical coupling means structured for allowing rigid fastening and fluidical connection of the water-softening

agent container to the detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the detergent dispenser is provided with complementary mechanical coupling means structured for engaging the mechanical
5 coupling means of said regeneration-agent reservoir and/or said water-softening agent container.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the detergent dispenser is exposed or exposable to the outside of the casing through the front wall of said casing.

10 Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said detergent dispenser comprises a detergent container which is fillable with a given quantity of detergent, softener and/or other washing agent, and is housed inside the casing into said first housing.

Preferably, though not necessarily, the laundry washing machine is
15 furthermore characterized in that said detergent container is movable inside said first housing so as to be at least partly extractable from the first housing through a first opening on the front wall of the casing.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the regeneration-agent reservoir of the water
20 softening device is exposed or exposable to the outside of the casing through the front wall of said casing.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the regeneration-agent reservoir comprises a regeneration-agent container which is fillable with a given quantity of regeneration
25 agents, and is housed inside the casing into a corresponding second housing or seat.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the detergent dispenser comprises also the second housing or seat of said regeneration-agent reservoir.

Preferably, though not necessarily, the laundry washing machine is
30 furthermore characterized in that said regeneration-agent container is movable inside said second housing or seat so as to be at least partly extractable from the second

housing or seat through a second opening on the front wall 8a) of the casing.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the displacement direction of the regeneration-agent container inside the second seat is locally substantially parallel to the displacement
5 direction of the detergent container inside the first seat.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said detergent container and said regeneration-agent container are able to jut out from the front wall of the casing while remaining locally substantially parallel to one another.

10 Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said water softening device furthermore comprises a water supply circuit which is structured for selectively spilling/pouring a given amount of fresh water into the regeneration-agent reservoir to at least partly dissolve the regeneration agents stored therein; the water-softening agent container
15 communicating with said regeneration agent reservoir for receive said solution of regeneration agents.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water supply circuit comprises electrically-controlled auxiliary valve means which are interposed between the water mains and
20 the regeneration-agent reservoir and are able to control/regulate the flow of fresh water towards the regeneration-agent reservoir.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized by also comprises electrically-controlled main valve means which are arranged between the detergent dispenser and the water mains, and are
25 able to control/regulate the flow of fresh water from the water mains towards the detergent dispenser and/or the washing tub.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water-softening agent container is arranged between the detergent dispenser and said main valve means.

30 Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water softening device is furthermore provided

with a first water drain line which is structured for selectively draining the brine or fresh water out of the resin container.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said first water drain line comprises an exhaust duct
5 which connects the bottom of the resin container either with the washing tub, with the drain sump or with the water filtering assembly of the laundry washing machine, and an on-off valve which is located along the exhaust duct for controlling the outflow of the brine or fresh water from the resin container.

Preferably, though not necessarily, the laundry washing machine is
10 furthermore characterized in that said detergent dispenser comprises: a detergent drawer which is inserted in manually extractable manner into a first drawer housing which extends inside the casing above the washing tub, starting from a front entrance or opening which is realized on the front wall of casing above the laundry loading/unloading opening; and a drawer flush circuit which is structured for
15 selectively spilling/pouring a given amount of fresh water arriving from the water mains into the detergent drawer for flushing the detergent, softener or other washing agent out of the detergent drawer and down into the bottom of the first drawer housing which communicates with the inside of the washing tub.

Preferably, though not necessarily, the laundry washing machine is
20 furthermore characterized in that the water-softening agent container is arranged between said main valve means and the drawer flush circuit of the detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the detergent drawer is provided with a number of
25 detergent compartments each fillable with a respective detergent product, and in that the drawer flush circuit comprises: a sprinkler head which is located inside the first drawer housing above the detergent drawer, and is provided with a number of shower-making portions each of which is aligned to a corresponding detergent compartment of the detergent drawer and is structured for feeding a shower of water
30 droplets by gravity only into said detergent compartment; and an hydraulic distributor assembly which is located upstream of the sprinkler head, and is

structured for channeling the fresh water arriving from the water mains selectively and alternatively into one of the shower-making portions of the sprinkler head.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water-softening agent container is arranged
5 between said valve means and said hydraulic distributor assembly, so as to be crossed by the fresh water directed to the inlet of said hydraulic distributor assembly.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the first drawer housing is substantially basin-shaped, and that the sprinkler head comprises a substantially flat first lid or cover
10 which is designed to close the top of the first drawer housing; said first lid or cover being divided into a number of shower-making portions, each of which is vertically aligned to a corresponding detergent compartment of the detergent drawer and is structured for receiving the fresh water from the hydraulic distributor assembly and for feeding a shower of water droplets only into the detergent compartment located
15 immediately beneath.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that said regeneration-agent reservoir comprises a salt drawer which is inserted in manually extractable manner into a second drawer housing which extends inside the casing, beside the detergent dispenser, starting
20 from a front entrance or opening which is realized on the front wall of casing above the laundry loading/ unloading opening.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the second drawer housing is substantially basin-shaped, and that the first lid or cover of the drawer flush circuit is designed to also
25 close the top of said second drawer housing.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the water supply circuit of the water softening device is at least partly integrated in said first lid or cover.

Preferably, though not necessarily, the laundry washing machine is
30 furthermore characterized in that the water supply circuit comprises a first water channel that extends within said first lid or cover and is fluidly connected to said

basin-shaped second drawer housing wherein it is fluidly connected to the salt drawer.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the said first water channel branches off from the
5 drawer flush circuit of the detergent dispenser.

Preferably, though not necessarily, the laundry washing machine is furthermore characterized in that the drawer flush circuit furthermore comprises a second water drain line that branches off from the hydraulic distributor assembly.

A non-limiting embodiment of the present invention will now be described,
10 by way of example, with reference to the accompanying drawings, in which:

- Figure 1 shows a perspective view of a front-loading, home laundry washing machine realized in accordance with the teachings of the present invention, with parts removed for clarity;
- Figure 2 is a lateral view of the Figure 1 home laundry washing machine
15 with parts removed for clarity;
- Figure 3 is a front view of the Figure 1 laundry washing machine with parts removed for clarity;
- Figure 4 is a perspective view of the top portion of the Figure 1 laundry washing machine in a first operating position;
- Figure 5 is a perspective view of the top portion of the Figure 1 laundry
20 washing machine in a second operating position;
- Figure 6 is a perspective view of the internal detergent dispenser and internal water softening device of the Figure 1 laundry washing machine;
- Figure 7 is a partly-exploded perspective view of the internal detergent
25 dispenser and internal water softening device shown in Figure 6, with parts removed for clarity;
- Figure 8 is a perspective view of some component parts of the internal detergent dispenser and water softening device shown in Figures 6 and 7;
- Figure 9 is a schematic view of the Figure 6 detergent dispenser and water
30 softening device;
- Figure 10 is a perspective view of an alternative embodiment of the internal

detergent dispenser and internal water softening device schematically shown in Figure 6, with parts removed for clarity;

- Figure 11 is a schematic view of the Figure 10 alternative embodiment of the internal detergent dispenser and water softening device of the Figure 6 laundry washing machine;
- Figure 12 is a perspective view of a second alternative embodiment of the internal detergent dispenser and internal water softening device shown in Figure 6, with parts removed for clarity;
- Figures 13 and 14 are respective schematic views of further alternative embodiments of the internal detergent dispenser and water softening device of the Figure 1 laundry washing machine;
- Figure 15 shows a perspective views of a further alternative embodiment of the internal water softening device of the Figure 1 laundry washing machine, with parts in section and parts removed for clarity;
- Figure 16 shows a perspective views of a further alternative embodiment of the internal water softening device of the Figure 1 laundry washing machine, with parts in section and parts removed for clarity; whereas
- Figures 17 and 18 show two perspective views of a further alternative embodiment of the internal water softening device of the Figure 1 laundry washing machine, with parts in section and parts removed for clarity.

With reference to Figures 1, 2 and 3, referral number 1 indicates as a whole a home laundry washing machine which comprises:

- a preferably, though not necessarily, substantially parallelepiped-shaped outer boxlike casing 2 which is structured for resting on the floor and is provided with a front wall 2a, two side walls 2b, and a rear wall 2c all preferably substantially vertically oriented, and a substantially horizontal top wall 2d;
- a preferably, though not necessarily, cylindrical, substantially bell-shaped hollow washing tub 3 which is arranged inside the casing 2 preferably suspended in floating manner via a suspension system preferably comprising a number of coil springs 4 and vibration dampers 5, directly

facing a laundry loading/unloading pass-through opening realized in the front wall 2a of boxlike casing 2;

- a substantially cylindrical, elastically-deformable bellows 6 which connects the front opening of washing tub 3 to the laundry loading/unloading opening formed in the front wall 2a of casing 2; and
- a substantially cylindrical, bell-shaped revolving drum (not shown) structured for housing the laundry to be washed, and which is housed in axially rotating manner inside the washing tub 3 so as to be able to freely rotate about its longitudinal reference axis.

In the example shown, in particular, the revolving drum is housed in axially rotating manner inside the washing tub 3 with its front opening directly faced/aligned to the laundry loading/unloading opening on the front wall 2a of casing 2, and the drum rotation axis is preferably arranged locally substantially coincident with the substantially horizontally-oriented longitudinal reference axis L of washing tub 3.

With reference to Figures 1, 2 and 3, the laundry washing machine 1 furthermore comprises:

- a porthole door 7 which is hinged to the front wall 2a of casing 2 to rotate about a preferably, though non necessarily, vertically-oriented reference axis to and from a closing position in which the peripheral border of the porthole door 7 rests completely on front wall 2a for closing the laundry loading/unloading opening and watertight sealing the washing tub 3;
- an electrically-powered motor assembly 8 which is structured for driving into rotation the revolving drum about its longitudinal reference axis inside the washing tub 3;
- a detergent dispenser 9 which is housed inside the casing 2, above the washing tub 3, so as to emerge from the front wall 2a of the boxlike casing 2 above the aforesaid laundry loading/ unloading opening, and is structured for selectively feeding into the washing tub 3, according to the selected washing cycle, a given amount of detergent, softener and/or other washing agent suitably mixed with the fresh water arriving from the water mains, or even simply a given amount of fresh water arriving from the water mains;

and

- an electrically-controlled on-off valve 10 which is arranged between the detergent dispenser 9 and the water mains, and is able to control/regulate the flow of fresh water from the water mains towards the detergent dispenser 9 and/or the washing tub 3.

In addition to the above, the laundry washing machine 1 is furthermore provided with an internal water softening device 11 which is arranged inside the boxlike casing 2 between the on-off valve 10 and the detergent dispenser 9 or even directly the washing tub 3, and is structured for selectively reducing, during each washing cycle, the hardness degree of the fresh water drawn from the water mains and channeled to the detergent dispenser 9 and/or directly to the washing tub 3.

This water softening device is preferably housed inside the boxlike casing 2 beside the detergent dispenser 9 in a direction preferably substantially horizontal and locally substantially parallel to the front wall 2a of casing 2, so that both detergent dispenser 9 and water softening device 11 are directly exposed or exposable on the outside of boxlike casing 2, one beside the other, so to be preferably independently accessible by the user at any moment.

With reference to Figures 1-5, in particular, the detergent dispenser 9 is arranged inside the casing 2 between the washing tub 3 and the top wall 2d of the casing 2, and is provided with a first loading inlet which is exposed or exposable to the outside on the front wall 2a of casing 2, above the laundry loading/unloading opening, and is suitable for loading the detergent, softener and/or other washing agent with the detergent dispenser 9.

In other words, the detergent dispenser 9 comprises a detergent container which is fillable with a given quantity of detergent, softener and/or other washing agent, and is housed inside casing 2 into a corresponding housing or seat, and the front wall 2a of casing 2 is provided with a corresponding pass-through opening through which the detergent container is accessible by the user.

In the example shown, in particular, the detergent dispenser 9 is located inside the boxlike casing 2, immediately above the washing tub 3, so that the inlet of detergent dispenser 9 is arranged on the front wall 2a of the casing 2, immediately

above the laundry loading/ unloading opening, and preferably beside an appliance control panel 12 that is arranged on the front wall 2a of casing 2 above the laundry loading/unloading opening and immediately beneath the top wall 2d of casing 2.

With reference to Figures 4-9, in the example shown, in particular, the detergent dispenser 9 comprises a detergent drawer 13 which is inserted in manually extractable manner into a drawer housing or seat 14 which extends substantially horizontally inside the boxlike casing 2, immediately above the washing tub 3, starting from a pass-through front entrance or opening 14a which is realized on the front wall 2a of casing 2 immediately above the laundry loading/unloading opening. The detergent drawer 13 of detergent dispenser 9 is therefore movable inside the drawer housing or seat 14 so as to be at least partly extractable from the drawer housing or seat 14 through the front entrance or opening 14a on the front wall 2a of casing 2.

The detergent dispenser 9 furthermore comprises a drawer flush circuit 15 which is structured for selectively spilling/pouring a given amount of fresh water arriving from the water mains via the on-off valve 10 into the detergent drawer 13 for flushing the detergent, softener or other washing agent out of the detergent drawer 13 and down into a funnel-shaped catchment basin which is formed on the bottom 14b of the drawer housing 14, and which communicates with the inside of washing tub 3 via a corresponding supply duct 16 preferably connected to the upper portion of the washing tub 3.

The water softening device 11 is preferably interposed between the on-off valve 10 and the drawer flush circuit 15 of detergent dispenser 9.

With reference to figures 1, 2, 4 and 5, in the example shown, in particular, the detergent drawer 13 is movable inside the drawer housing 14 in a displacement direction which is preferably substantially horizontally-oriented and also locally substantially perpendicular to the front wall 2a of casing 2.

Furthermore the detergent drawer 13 is preferably divided into a number of detergent compartments 13a (three in the example shown) each of which is manually fillable with a respective washing agent, and the drawer flush circuit 15 is structured for selectively spilling/ pouring the fresh water arriving from the water mains

selectively and alternatively into the various detergent compartments 13a of the detergent drawer 13 for flushing the detergent or softener out of the compartments 13a and down into the funnel-shaped catchment basin formed on the bottom 13b of the drawer housing 14.

5 The drawer flush circuit 15 is connected to the on-off valve 10 downstream of the water softening device 11, and is structured for spilling/ pouring the fresh water arriving from the water softening device 11 selectively and alternatively into one or more of the detergent compartments 13a of detergent drawer 13.

 With reference to Figures 6-9, in the example shown, in particular, the drawer
10 flush circuit 15 preferably comprises:

- a sprinkler head which associated to the drawer housing 14 so as to be located immediately above the detergent drawer 13 when the latter is completely inserted/recessed into the drawer housing 14, and which is provided with a number (three in the example shown) of shower-making portions/ sections
15 each of which is preferably substantially aligned to a corresponding detergent compartment 13a of the detergent drawer 13 and is structured for feeding a dense shower of water droplets by gravity into the detergent compartment 13a located immediately beneath; and preferably
- an electrically-controlled hydraulic distributor assembly 18 which is located
20 immediately upstream of the sprinkler head, i.e. between the sprinkler head and the on-off valve 10, and is structured for channeling the fresh water arriving from the on-off valve 10 selectively and alternatively towards the various shower-making sections/portions of the sprinkler head.

 More specifically, in the example shown, each shower-making
25 section/portion of the sprinkler head is preferably vertically aligned to a respective detergent compartment 13a of the detergent drawer 13, and is structured for feeding a dense shower of water droplets exclusively into the detergent compartment 13a located immediately beneath.

 With reference to Figures 6, 7 and 8, in the example shown, in particular, the
30 drawer housing 14 is preferably substantially basin-shaped, and the detergent dispenser 9 also comprises a preferably substantially flat, upper lid or cover 17 which

is designed to close the top of the drawer housing 14 so to be located immediately above the detergent drawer 13 when the latter is completely inserted/recessed into the drawer housing 14. The detergent container housing of detergent dispenser 9 is therefore preferably formed by the basin-shaped drawer housing 14 and upper lid or
5 cover 17.

The lid or cover 17 is furthermore preferably structured so as to incorporate the sprinkler head of the drawer flush circuit 15. In other words the lid or cover 17 on top of drawer housing 14 forms the sprinkler head of the drawer flush circuit 15 and is therefore divided into a number (three in the example shown) of shower-
10 making portions, each of which is vertically aligned to a corresponding detergent compartment 13a of the detergent drawer 13, and is structured for receiving the fresh water from the hydraulic distributor assembly 18 and for feeding a dense shower of water droplets by gravity exclusively into the detergent compartment 13a located immediately beneath.

The hydraulic distributor assembly 18, instead, preferably comprises a
15 rotatable water diverter 18a which is preferably recessed into the sprinkler lid or cover 17 in axially rotating manner; and an electric motor or other electrically-operated rotatable actuator 18b which is fixed sideways of the sprinkler lid or cover 17 and is mechanically connected to the central shaft of the rotatable water diverter
20 18a via a crank-rod mechanism, so to directly control/vary the angular position of the rotatable water diverter 18a.

With reference to Figures 7 and 9, the sprinkler lid or cover 17 has a first internal water channel 17a that connects the inlet of the rotatable water diverter 18a to the on-off valve 10, so to channel fresh water to the inlet of the rotatable water
25 diverter 18a; and a number of second water channels 17b each connecting a respective outlet of the rotatable water diverter 18a to a corresponding shower-making portion of the sprinkler lid or cover 17.

The fresh water from the water mains arrives to the inlet of the rotatable water diverter 18a and is selectively channeled/directed to one of the shower-making
30 portions of the sprinkler lid or cover 17 according to the angular position of the rotatable water diverter 18a.

As an alternative, the electric motor 18b could be connected to the central shaft of the rotatable water diverter 18a via a driving belt winded on a couple of pulleys mortised one to the drive shaft of electric motor 18b, and the other to the central shaft of the rotatable water diverter 18a.

5 In a different non-shown embodiment, the hydraulic distributor assembly 18 formed by the rotatable water diverter 18a and the electric motor 18b may be replaced by a number of electrically-controlled on-off valves each of which is interposed between the on-off valve 10 and a respective shower-making section/portion of the sprinkler head 17 for directly controlling the flow of fresh
10 water towards the corresponding shower-making section/portion of the sprinkler head 17.

With referenced to Figure 9, preferably, though not necessarily, the drawer flush circuit 15 also comprises a one-way valve 19 which is located immediately downstream of the on-off valve 10, i.e. between the on-off valve 10 and the inlet of
15 the rotatable water diverter 18a, and is structured to allow fresh water to only flow from the on-off valve 10 to the water diverter 18a of detergent dispenser 9 and not vice versa.

In addition the drawer flush circuit 15 is preferably also provided with a number of air-break assemblies 20 each located immediately downstream of a
20 corresponding water outlet of the rotatable water diverter 18a, i.e. along a corresponding second water channel 17b of the sprinkler lid or cover 17.

With reference to Figures 4-9, the water softening device 11, in turn, is preferably inserted/located between the on-off valve 10, or the one-way valve 19 if present, and the inlet of the hydraulic distributor assembly 18 of the drawer flush
25 circuit 15, so to be crossed by the fresh water flowing towards the hydraulic distributor assembly 18, and basically comprises: a water-softening agent container which is filled with a water softening agent able to reduce the hardness degree of the fresh water flowing through said water-softening agent container, and a regeneration-agent reservoir which is fluidly connected to said water-softening agent container
30 and is structured for receiving a given quantity of salt or other regeneration agent and is able to regenerate the water softening function of the water softening agents.

Both the water-softening agent container and the regeneration-agent reservoir are housed inside the casing 2, and the regeneration-agent reservoir is moreover preferably arranged inside the casing 2, beside the detergent dispenser 9 in a direction locally substantially parallel to the front wall 2a of casing 2, so that both
5 detergent dispenser 9 and the regeneration-agent reservoir of the water softening device 11 are directly exposed or exposable on the outside of boxlike casing 2, one beside the other, so to be preferably independently accessible by the user at any moment.

More specifically, the regeneration-agent reservoir of the water softening
10 device 11 is housed inside the casing 2 between the detergent dispenser 9 and one of the side walls 2b of casing 2, and is provided with a second independent inlet which is exposed or exposable to the outside of the boxlike casing 2 beside the inlet of detergent dispenser 9. This second independent inlet is suitable for loading the salt or other regeneration agents inside the regeneration-agent reservoir.

15 In other words, the regeneration-agent reservoir of the water softening device 11 comprises a regeneration-agent container which is fillable with a given quantity of regeneration agents and is housed inside the casing 2 into a corresponding second housing or seat, and the front wall 2a of casing 2 is provided with a corresponding second pass-through opening through which the regeneration-agent container is
20 accessible by the user.

In the example shown, in particular, this second independent inlet of the regeneration-agent reservoir of the water softening device 11 is preferably located on the front wall 2a of boxlike casing 2 immediately adjacent to the inlet of detergent dispenser 9.

25 With reference to Figures 1-5, in the example shown, in particular, the water softening device 11, and more specifically the regeneration-agent reservoir of the water softening device 11, is located inside the boxlike casing 2 preferably immediately beside the detergent dispenser 9, on the other side of the appliance control panel 12 that is arranged on the front wall 2a of casing 2 above the laundry
30 loading/unloading opening and immediately beneath the top wall 2d of casing 2.

With reference to Figures 6-9, in the example shown, in particular, the water

softening device 11 comprises:

- an outside-accessible regeneration-agent reservoir 21 which is structured for receiving a given amount (for example half a Kilo or one Kilo) of salt grains (Sodium Chloride) or similar regeneration chemical agent, and is housed
5 inside the boxlike casing 2 immediately beside the drawer housing 14 of detergent dispenser 9 in a direction substantially parallel to the front wall 2a of casing 2, so to emerge from a corresponding pass-through opening realized on the front wall 2a of the boxlike casing 2 immediately beside the entrance/front opening 14a of the drawer housing 14;
- 10 – a water supply circuit 22 which is structured for selectively spilling/pouring, on command, a given amount of fresh water into the regeneration-agent reservoir 21 so to at least partly dissolve the salt stored therein and form a given amount of brine (i.e. salt water); and
- 15 – a water-softening agent container 23 which is filled with a given amount of ion-exchange resins (not shown) capable to restrain the calcium and/or magnesium ions (Ca^{++} and Mg^{++}) dissolved in the fresh water flowing across the resin container 23, and which is interposed between the on-off valve 10, or the one-way valve 19 if present, and the detergent dispenser 9.

The resin container 23 is preferably interposed between the on-off valve 10,
20 or the one-way valve 19 if present, and the inlet of the rotatable water diverter 18a of the drawer flush circuit 15 so to be crossed by the fresh water flowing from the on-off valve 10 to the hydraulic distributor assembly 18.

The water supply circuit 22 is therefore structured for spilling/pouring a given amount of fresh water into the regeneration-agent reservoir 21 of water softening
25 device 11 to at least partly dissolve the salt or other regeneration agents stored therein.

The ion-exchange resins (not shown) stored into the resin container 23 instead form the water softening agents of the water softening device 11.

In the example shown, in particular, the resin container 23 is preferably
30 located inside the casing 2, immediately beneath the regeneration-agent reservoir 21 and immediately beside the upper portion of washing tub 3, so as to internally face

the front wall 2a of casing 2. Thus the resin container 23 is located below the drawer housing 14 of detergent dispenser 9.

The resin container 23 is preferably located within an approximately triangular pocket compartment or seat delimited by the sidewall 2b of the boxlike casing 2, the upper portion of the washing tub 3, the front wall 2a of casing 2, and the supply duct 16 connecting the drawer housing 14 to the washing tub 3.

With reference to Figure 7, the resin container 23 is provided as a completely stand-alone cartridge or similar modular component-part 23 which is provided with a mechanical coupling interface 23a structured for allowing rigid fastening and fluidical connection of the stand-alone modular component-part 23 directly to the bottom of the regeneration-agent reservoir 21.

This stand-alone modular component-part 23 is furthermore provided with two hydraulic connectors 23b, 23c structured for allowing fluidical connection of the resin container 23 in series to the water supply line that channels the fresh water from the on-off valve 10 to the inlet of the hydraulic distributor assembly 18.

A first hydraulic connector 23b directly communicates with the on-off valve 10 so as to allow the inflow of the fresh water into the resin container 23, whereas a second hydraulic connector 23c directly communicates with the hydraulic distributor assembly 18 so as to allow the outflow of the fresh water from the resin container 23 towards the inlet of the rotatable water diverter 18a.

The ion-exchange resins (not shown) are preferably, though not necessarily, confined, inside the resin container 23, into a water-permeable basket (not shown) whose volume is less than that of the resin container 23 so as to form an internal peripheral gap or interspace allowing free fresh-water circulation.

With reference to Figure 6, 7 and 8, likewise resin container 23, also salt reservoir 21 is preferably provided as a stand-alone modular component-part 21 which is provided with mechanical coupling means 21a structured for allowing rigid fastening of the salt reservoir 21 to the side of detergent dispenser 9. Detergent dispenser 9, in turn, is preferably provided with complementary mechanical coupling means structured for engaging the mechanical coupling means 21a of salt reservoir 21.

In the example shown, mechanical coupling means 21a preferably consist in snap-on locking means structured for rigidly fastening the salt reservoir 21 to the side of the drawer housing 14 of detergent dispenser 9.

Thus the water softening device 10 comprises at least one stand-alone
5 modular component-part 21, 23 which is structured for being rigidly connectable/attachable to the detergent dispenser 9, or preferably to the drawer housing 13 of detergent dispenser 9.

With reference to Figure 9, the water softening device 11 furthermore comprises: a one-way valve 24 which is interposed between the regeneration-agent
10 reservoir 21 and the resin container 23, and is structured to allow the brine contained in the regeneration-agent reservoir 21 to freely flow by gravity into the resin container 23, and to prevent the fresh water arriving into the resin container 23 from the on-off valve 10 to go up into the regeneration-agent reservoir 21; and preferably also water-hardness sensor means (not shown) structured to measure the hardness
15 degree of the fresh water coming out from the resin container 23 directed towards the detergent dispenser 9.

In the example shown, in particular, the water-hardness sensor means are able to communicate with an internal electronic central control unit (not shown) which controls all electrically-operated component parts of the laundry washing machine 1,
20 and is housed inside the boxlike casing 2, preferably on the back of control panel 12.

Preferably, though not necessarily, the water softening device 11 is finally provided with a water drain line 25 which is structured for selectively draining the brine or fresh water out of resin container 23 and preferably channelling said brine or fresh water directly into the washing tub 3, into the drain sump 26 that extends
25 downwards from the bottom of the washing tub 3, or into the water filtering assembly 27 that is interposed between the drain sump 26 of washing tub 3 and the suction of the water circulating pump 28 and of the water exhaust pump 29 which, in the example shown, are both preferably located on the bottom of the boxlike casing 2, or substantially directly into the water exhaust pump 29 which drains water or
30 washing liquor outside the machine.

In the example shown, in particular, the water drain line 25 preferably

comprises an exhaust duct 30 which directly connects the bottom of the resin container 23 either to the washing tub 3, to the drain sump 26 or to the water filtering assembly 27, or to water exhaust pump 29; and an electrically-controlled on-off valve 31 which is located along the exhaust duct 30 for controlling the outflow of the
5 brine or fresh water from the resin container 23.

With reference to Figures 5-9, the regeneration-agent reservoir 21 preferably comprises a salt drawer 32 which is inserted in manually extractable manner into a second drawer housing or seat 33 which extends substantially horizontally inside the boxlike casing 2, immediately beside the drawer housing 14 of detergent dispenser 9,
10 starting from a pass-through front entrance or opening 33a which is realized on the front wall 2a of casing 2 locally adjacent to the entrance/front opening 14a of the drawer housing 14 of detergent dispenser 9.

The salt drawer 32 of regeneration-agent reservoir 21 is therefore movable inside the drawer housing or seat 33 so as to be at least partly extractable from the
15 drawer housing or seat 33 through the front entrance or opening 33a on the front wall 2a of casing 2.

The displacement direction of the salt drawer 32 is furthermore preferably locally substantially parallel to the displacement direction of detergent drawer 13, thus detergent drawer 13 and salt drawer 32 are able to jut out from the front wall 2a
20 of casing 2 while remaining locally substantially parallel to one another.

With reference to Figure 8, the snap-on locking means 21a of salt reservoir 21 are preferably arranged on the lateral wall of drawer housing 33 so to allow quick and rigid fastening of the drawer housings 14 and 33 to one another.

In addition to the above, in the example shown the front panel 13f of the
25 detergent drawer 13 is preferably substantially handle-shaped and is preferably dimensioned so to completely cover, when the detergent drawer 13 is completely inserted into the drawer housing 14, both the entrance/front opening 14a of drawer housing 14 and the entrance/front opening 33a of drawer housing 33, so to completely hide both the detergent dispenser 9 and the water softening device 11.

30 The water supply circuit 22 of the water softening device 11 is structured for spilling/pouring the fresh water directly into the salt drawer 32 when the latter is

completely inserted into its drawer housing 33, and reservoir 21 preferably also comprises a substantially basin-shaped, water-permeable salt basket 34 which is fitted/recessed into the salt drawer 32 preferably in manually-removable manner, and is dimensioned for being manually fillable with said given amount of salt grains or
5 other water-softening chemical agent.

With reference to Figures 5 and 7, in the example shown, in particular, the bottom and/or at least one of sidewalls of the salt basket 34 have a meshed structure so as to allow the fresh water spilled/poured into the salt drawer 32 to freely reach and at least partly dissolve the salt grains located inside the salt basket 34 to form a
10 give amount of brine which is subsequently drained into the drawer housing 33 via a siphons assembly or discharge hopper or opening (not shown) incorporated in the salt drawer 32.

The brine accumulated on the bottom of the drawer housing 33, in turn, is subsequently drained/channelled into the resin container 23 via the one-way valve
15 24, when the hydrostatic pressure inside the resin container 23 allows the brine to flow by gravity within the resin container 23.

With reference to Figures 7 and 8, in the example shown, in particular, the drawer housing 33 of regeneration-agent reservoir 21 is preferably substantially basin-shaped similarly to drawer housing 14, and the snap-on locking means 21a are
20 preferably arranged on the sidewall of the basin-shaped drawer housing 33 that is directly faced the drawer housing 14 of detergent dispenser 9.

Furthermore, the bottom 33b of the drawer housing 33 is preferably shaped so as to form a funnel-shaped catchment basin 33b that directly communicates with the inside of resin container 23 via a large pass-through opening into which the one-way
25 valve 24 is preferably recessed. This pass-through opening is preferably upwardly closed by a protective grid which is dimensioned to prevent the salt grains from reaching and blocking the one-way valve 24.

With reference to Figure 7, the mechanical coupling interface 23a of the resin container 23, in turn, is preferably provided with an outwards-projecting connecting
30 sleeve or manifold which is structured/ dimensioned to couple in watertight manner with the pass-through opening on the bottom 33b of drawer housing 33, so as to put

the inside of resin container 23 in direct communication with the drawer housing 33 via the one-way valve 24.

As an alternative the one-way valve 24 may be recessed into the connecting sleeve or manifold 23a that protrudes upwards from the resin container 23.

5 With reference to Figures 7 and 8, the drawer housing 33 is preferably, though not necessarily, finally provided with a discharge hopper or opening 33c which is preferably located on a lateral wall of the drawer housing 33 and is structured to drain out of the funnel-shaped catchment basin 33b the brine that exceeds a predetermined maximum level.

10 With reference to Figures 7 and 8, the salt drawer 32, in turn, is preferably fixed to/supported by a longitudinal rail or telescopic runner 35 that is arranged into the drawer housing 33 locally substantially parallel to the preferably substantially horizontally-oriented insertion and extraction direction of the salt drawer 32, so as to allow the manual displacement of the salt drawer 32 in and out of the drawer housing
15 33. Preferably a push-pull mechanism 36 is also arranged into the drawer housing 33 to ease the manual insertion and extraction of salt drawer 32.

 With reference to Figures 6 and 7, the water supply circuit 22 of water softening device 11 instead comprises an additional electrically-controlled on-off valve 37 which is interposed between the water mains and the regeneration-agent
20 reservoir 21 and, similarly to on-off valve 10, is able to control/regulate the flow of fresh water towards the regeneration-agent reservoir 21; and an internal water channel which extends inside the drawer housing 33 and is fluidly connected to the salt drawer 32 so to channel the fresh water arriving from the on-off valve 37 directly into the salt drawer 32.

25 In the example shown, the water supply circuit 22 furthermore comprises a hosepipe 38 connecting the on-off valve 37 to the internal water channel (not shown) on drawer housing 33.

 Likewise to the drawer flush circuit 15, the water supply circuit 22 is preferably also provided with a corresponding one-way valve 39 which is located
30 immediately downstream of the on-off valve 37, i.e. between the on-off valve 37 and the internal water channel of drawer housing 33, and is structured to allow fresh

water to only flow from the on-off valve 37 to the internal water channel of drawer housing 33 and not vice versa.

The water softening device 11 preferably comprises a first hosepipe 40 directly connecting the on-off valve 10 to the hydraulic connector 23b of the resin container 23, and a second hosepipe 41 directly connecting the hydraulic connector 23c of the resin container 23 to the inlet of the internal water channel 17a of the sprinkler lid or cover 17.

With reference to Figure 6 and 7, in the example shown, in particular, the drawer housing 33 is substantially basin-shaped and the regeneration-agent reservoir 21 also comprises a preferably substantially flat lid or cover 42 which is designed to close exclusively the top of the basin-shaped drawer housing 33, so to be located immediately above the salt drawer 32 when the latter is completely inserted/recessed into the drawer housing 33. This lid or cover 42 furthermore is preferably arranged locally adjacent to the flat lid or cover 17 of detergent drawer 9.

The housing of the regeneration-agent container of water softening device 11 is therefore preferably formed by the basin-shaped drawer housing 33 and the corresponding upper lid or cover 42.

The internal water channel 42a of the water supply circuit 22 is preferably realized/integrated into the lid or cover 42.

With reference to Figure 9, in the example shown, the drawer flush circuit 15 preferably also comprises an auxiliary second water drain line 43 that branches off from a corresponding outlet of the hydraulic distributor assembly 18, and is structured for channeling the brine or fresh water arriving from the resin container 23 preferably, though not necessarily, directly into the washing tub 3, or into the drain sump 26, or into the water filtering assembly 27, or into pump 29.

In other words, one of the outlets of the rotatable water diverter 18a of drawer flush circuit 15 is preferably connected to an auxiliary water drain line 43 which preferably, though not necessarily, ends into the washing tub 3 or into the drain sump 26 or into the water filtering assembly 27, or into pump 29; and the electric motor 18b is preferably structured to selectively place/arrange the rotatable water diverter 18a in a position that allows to channel the brine or fresh water arriving from the

resin container 23 to the auxiliary water drain line 43 that, in turn, channels said brine or fresh water directly into the washing tub 3 or into the drain sump 26 or into the water filtering assembly 27, or into pump 29.

Alike water drain line 25, the auxiliary water drain line 43 of drawer flush
5 circuit 15 allows to selectively channel/drain out of the resin container 23 the brine or fresh water that fills said resin container.

With reference to Figure 6 and 9, in the example shown, in particular, the sprinkler lid or cover 17 preferably comprises a fourth internal water channel 17d which extends inside the sprinkler lid or cover 17 from a corresponding outlet of the
10 rotatable water diverter 18a of the drawer flush circuit 15 to the inlet of an auxiliary hosepipe 43 that extend towards the bottom of the boxlike casing 2 and ends directly into the washing tub 3 or into the drain sump 26 or into the water filtering assembly 27 or into the exhaust pump 29,.

Preferably to the auxiliary water drain line 43 may also comprise an air-break
15 assembly (not shown) arranged along the fourth internal water channel 17d of the sprinkler lid or cover 17.

General operation of home laundry washing machine 1 is clearly inferable from the above description. When the on-off valve 10 is opened the fresh water flows from the water mains to the hydraulic distributor assembly 18 of the drawer
20 flush circuit 15 that, according to the washing cycle, channels said fresh water to one of the shower-making sections/portions of the sprinkler lid or cover 17 for flushing the detergent, softener or other washing agent out of the corresponding detergent compartment 13a of the detergent drawer 13 and down into the washing tub 3 via the supply duct 16.

25 While flowing towards the drawer flush circuit 15, the fresh water flows through the resin container 23 wherein the ion-exchange resins reduce the hardness degree of the fresh water directed to the detergent drawer 13. The water-hardness sensor means monitor the hardness degree of the fresh water directed to the hydraulic distributor assembly 18 of the drawer flush circuit 15.

30 When determines that the ion-exchange resins inside the resin container 23 are no more able to reduce the hardness degree of the fresh water directed to the

detergent drawer 13, the electronic central control unit (not shown) of the laundry washing machine 1 performs, preferably immediately before the starting of the rinsing phase of the washing cycle (i.e. during the washing phase of the washing cycle), a regeneration process of the ion-exchange resins stored inside the resin container 23. Obviously the regeneration process may also take place during the
5 rinsing phase of the washing cycle.

During this regeneration process, the central control unit momentarily opens the on-off valve 37 so as to channel a given amount of fresh water into the regeneration-agent reservoir 21 via the water supply circuit 22.

10 When a sufficient amount of brine is formed inside the regeneration-agent reservoir 21, the central control unit arranges the hydraulic distributor assembly 18 so as to put the resin container 23 in direct communication with the auxiliary water drain line 43, and more or less at the same time it opens the on-off valve 31 of the water drain line 25 so as to drain the fresh water out of the resin container 23. Since
15 at that time the on-off valve 10 is closed, the drainage of the fresh water from the resin container 23 causes the drop of the hydrostatic pressure inside the resin container 23 and the consequent automatic opening of the one-way valve 24 that allows the brine to flow by gravity into the resin container 23, thus replacing the fresh water previously store therein.

20 The fresh water previously store in the resin container 23, instead, flows directly into the washing tub 3 or into the drain sump 26 or into the water filtering assembly 27, into pump 29, via the water drain line 25 and/or via the auxiliary water drain line 43.

When brine has completely filled the resin container 23 in place of the fresh
25 water previously store therein, the central control unit closes the on-off valve 31 of the water drain line 25 to restrain the brine inside the resin container 23 for a predetermined time interval generally sufficient to allow the brine to remove from the ion-exchange resins the calcium and magnesium ions previously combined/fixed to said resins.

30 Since in the example shown the rotatable water diverter 18a of drawer flush circuit 15 is located higher than the resin container 23 and the brine inside the resin

container 23 is at ambient pressure, there is no need for the electronic central control unit of the laundry washing machine 1 to change configuration of the rotatable water diverter 18a to prevent the brine from coming out of the resin container 23 via the auxiliary water drain line 43.

5 After the resin-regeneration interval has lapsed, the central control unit opens again the on-off valve 31 of the water drain line 25 to drain the brine out of the resin container 23 and, more or less at the same time, opens again the on-off valve 10 so that the pressurized fresh water of the water minas pushes the brine away from the resin container 23 and into either the washing tub 3 or the drain sump 26 or the water
10 filtering assembly 27 or pump 29, via the water drain line 25 and/or via the auxiliary water drain line 43.

 Finally, preferably after having closed again the on-off valves 10 and 31, the central control unit of the laundry washing machine activates the water exhaust pump 29 so to discharge the brine out of the laundry washing machine 1 preferably
15 together with the washing or rinsing water already stored on the bottom of the washing tub 3, and continues the washing cycle.

 In a less sophisticated embodiment, however, the electronic central control unit of the laundry washing machine 1 may be programmed to regenerate the ion-exchange resins stored in the resin container 23 after a given number of washing
20 cycles. In which case the water-hardness sensor means monitor are therefore unnecessary.

 This number of washing cycles may be decided by the user on the basis of an alleged hardness degree of the fresh water coming out from the water mains.

 The advantages resulting from the arrangement of the outside-accessible regeneration-agent reservoir 21 immediately beside the detergent dispenser 9 are
25 remarkable.

 First of all, the side by side modular structure of detergent dispenser 9 and water softening device 11 greatly simplifies the structure of detergent dispenser 9 with the consequent reduction of the detergent-dispenser overall production costs.

30 Furthermore the regeneration-agent reservoir 21 is directly accessible by the user on the front wall 2a of the boxlike casing 2, beside the detergent dispenser 9,

thus greatly simplifying the manual loading of the salt grains into the regeneration-agent reservoir 21.

Last but not less important, the brine is no more allowed to reach the revolving drum, thus avoiding the rusting up of this component part.

5 Clearly, changes may be made to the front-loading laundry washing machine 1 as described above without, however, departing from the scope of the present invention.

For example, with reference to Figures 10 and 11, in a much more sophisticated embodiment, the water softening device 11 lacks the on-off valve 37, 10 the one-way valve 39 and the lid or cover 42; and the sprinkler lid or cover 17 of detergent dispenser 9 is shaped/designed to additionally completely close also the top of drawer housing 33.

In other words the sprinkler lid or cover 17 closes both drawer housings 14 and 33, and the drawer housing 33 of salt reservoir 21 is structured for being 15 modularly connected to drawer housing 14 of detergent dispenser 9 and/or to the large lid or cover 17 of detergent dispenser 9. Thus the mechanical coupling means 21a are structured for allowing rigid fastening of the salt reservoir 21 to the sidewall of drawer housing 14 and/or to the sprinkler lid or cover 17 of detergent dispenser 9.

Furthermore the sprinkler lid or cover 17 preferably also incorporate the 20 water supply circuit 22 of water softening device 11.

With reference to Figures 10 and 11, in particular, the water supply circuit 22 of water softening device 11 preferably branches off from the drawer flush circuit 15 of detergent dispenser 9.

More specifically, in this embodiment the sprinkler lid or cover 17 that closes 25 both drawer housings 14 and 33 is preferably provided with a third internal water channel 17c which extends inside the sprinkler lid or cover 17 from a corresponding outlet of the rotatable water diverter 18a of the drawer flush circuit 15 and is fluidly connected to the salt drawer 32 so to channel the fresh water coming out of the rotatable water diverter 18a directly into the salt drawer 32.

30 The electric motor 18b of drawer flush circuit 15, in turn, is preferably structured to selectively place/ arrange the rotatable water diverter 18a in a position

that allows, when the brine is requested, to channel the fresh water arriving from the resin container 23 to the third internal water channel 17c of the sprinkler lid or cover 17.

In other words, the water supply circuit 22 comprises a water channel 17c that
5 branches off from a corresponding outlet of the water diverter 18a and is fluidly connected to the salt drawer 32, so as to feed water to the regeneration-agent reservoir 21 under control of the hydraulic distributor assembly 18.

Moreover in this embodiment the internal water channel 17a of sprinkler lid or cover 17 receives the fresh water directly from the on-off valve 10, and the resin
10 container 23 is preferably inserted/arranged along the internal water channel 17a that, inside the sprinkler lid or cover 17, channels the fresh water towards the inlet of the rotatable water diverter 18a. Thus the first and second hydraulic connectors 23b and 23c of resin container 23 are preferably structured for being connectable to the sprinkler lid or cover 17, along the internal water channel 17a of the lid or cover 17.

15 With reference to Figure 10, in particular, in this embodiment the sprinkler lid or cover 17 is preferably provided with two tubular appendixes 17a' and 17a'' that extend downwards, beside the drawer housing 33, up to reach and connect to the hydraulic connectors 23b and 23c of the resin container 23 located beneath the drawer housing 33. The tubular appendix 17a' connected to the hydraulic connector
20 23b forms the end portion of a first section of the internal water channel 17a directly communicating with the on-off valve 10; the tubular appendix 17a'' connected to the hydraulic connector 23c forms the starting portion of a second section of the internal water channel 17a directly communicating with the inlet of the rotatable water diverter 18a.

25 With reference to Figure 12, instead, in a less sophisticated embodiment of the water supply circuit 22, the sprinkler lid or cover 17 of detergent dispenser 9 still closes both drawer housings 14 and 33, but the internal water channel 17c of the sprinkler lid or cover 17, rather than communicating with an auxiliary outlet of the rotatable water diverter 18a of the drawer flush circuit 15, is again directly connected
30 to the electrically-controlled on-off valve 37 which controls/ regulates the flow of fresh water towards the internal water channel 17c of the sprinkler lid or cover 17.

In the example shown, in particular, on-off valve 10 and on-off valve 37 are preferably integrated into a valve assembly that comprises a third electrically-controlled on-off valve 210 that is connected to a hosepipe 211 that ends into the washing tub 3. This third on-off valve is able to control/regulate the flow of fresh
5 water from the water mains directly to the washing tub 3 bypassing the detergent drawer 9 and the waters softening device 11.

With reference to Figure 13, instead, the water softening device 11 lacks the water drain line 25, whereas the drawer flush circuit 15 of detergent dispenser 9 lacks the air-break assemblies 20 located along the internal water channels 17b, 17c and
10 17d of the sprinkler lid or cover 17 and instead comprises an air-break assembly 144 which is located along the internal water channel 17a of the sprinkler lid or cover 17, immediately upstream of the resin container 23, and preferably integrates a discharge hopper which, in turn, communicates with either the washing tub 3, the drain sump 26, the water filtering assembly 27 or pump 29, via a specific water drain line 145.
15 Thus the fresh water or brine exceeding the nominal capacity of the resin container 23 is allowed to come out from the resin container 23 via the air-break assembly 144 and be channeled directly into the washing tub 3 or into the drain sump 26 or into the water filtering assembly 27 or into pump 29 by the water drain line 145.

With reference to Figure 14, instead, the drawer flush circuit 15 of detergent
20 dispenser 9 lacks the air-break assemblies 20 located along the internal water channels 17b, 17c and 17d of the sprinkler lid or cover 17, and instead comprises a single air-break assembly 148 which is located along the internal water channel 17a of the sprinkler lid or cover 17, immediately upstream of the inlet of the rotatable water diverter 18a.

25 With reference to Figures 15 and 16, instead, the regeneration-agent reservoir 21 of the water softening device 11 may comprise a stand-alone modular salt container 132 which is permanently recessed/confined into a seat inside the boxlike casing 2, immediately beside the drawer housing or seat 14 of detergent dispenser 9. The stand-alone salt container 132 comprises mechanical coupling means (not
30 shown) structured for allowing rigid fastening of the salt reservoir 132 to the side of detergent dispenser 9, and is furthermore provided with a salt-loading mouth 132a

which is aligned to and engages a corresponding pass-through opening realized on the front wall 2a of casing 2, immediately beside the entrance/ front opening 14a of the drawer housing 14, so that the salt-loading mouth 132a is exposed or exposable onto the front wall 2a of cabinet 2.

5 In the Figures 15 embodiment, the regeneration-agent reservoir 21 furthermore comprises a telescopic loading hopper or slide 134 which is inserted in manually extractable manner into the salt-loading mouth 132a of the salt container 132. In the Figures 16 embodiment, the regeneration-agent reservoir 21 furthermore comprises screw plug 135 which is inserted/screwed into the salt-loading mouth 132a
10 in easily removable manner to seal preferably substantially in watertight manner the salt container 132.

With reference to Figures 17 and 18, instead, the regeneration-agent reservoir 21 of the water softening device 11 may comprise a stand-alone modular salt container 232 which is fixed in horizontally sliding manner onto the sidewall of the
15 drawer housing or seat 14 of detergent dispenser 9, so as to be able to freely slide inside the casing 2 in a direction d locally substantially parallel to the displacement direction of detergent drawer 13, towards and backwards a pass-through opening 232a realized on the front wall 2a of casing 2 immediately beside the entrance/front opening 14a of the drawer housing or seat 14.

20 The regeneration-agent reservoir 21 is furthermore provided with a salt-loading hopper 234 that protrudes from a lateral wall of the salt container 232 directly faced to the front wall 2a of casing 2, and is shaped/dimensioned to engage the pass-through opening 234a on the front wall 2a of the boxlike casing 2 so as to jut out from the front wall 2a of casing 2 beside the salt drawer 13 when the salt
25 container 232 is arranged at minimum distance from the front wall 2a of casing 2.

Furthermore, in a first non-shown embodiment the regeneration-agent reservoir 21 preferably lacks the removable basket 34, and the bottom and/or at least one of sidewalls of the salt drawer 32 have a water-permeable meshed structure, so as to form the brine directly on the bottom of the drawer housing 33.

30 Finally in a second non-shown embodiment the basin-shaped drawer housing 33 of regeneration-agent reservoir 21 is realized in one piece with the basin-shaped

drawer housing 14 of detergent dispenser 9, thus solely the resin container 23 consists in completely stand-alone modular component-part 23 which is provided with a mechanical coupling interface 23a structured for allowing rigid fastening and fluidical connection of the stand-alone modular component-part 23 directly to the
5 detergent dispenser 9.

In other words, in this embodiment the detergent container housing of detergent dispenser 9 is provided with two independent seats respectively housing the detergent drawer 13 and the other housing the salt drawer 32. The regeneration-agent reservoir 21 is therefore integrally formed with the detergent container housing
10 of detergent dispenser 9, and the resin container 23 is modularly connected to the bottom of the detergent container housing, preferably beneath the salt drawer 32.

CLAIMS

1. Laundry washing machine (1) comprising an outer casing (2), a washing tub (3) arranged inside said casing (2) directly facing a laundry loading/unloading opening realized in a front wall (2a) of said casing (2), a rotatable drum arranged in axially rotating manner inside the washing tub (3) and structured for receiving the laundry to be washed, an detergent dispenser (9) which is structured for supplying detergent into the washing tub (3), and a water softening device (11) which is arranged inside the boxlike casing (2) and is structured for reducing the hardness degree of the fresh water supplied to the washing tub (3);
- the water softening device (11) in turn comprising a water-softening agent container (23) filled with a water softening agent able to reduce the hardness degree of the fresh water supplied to the washing tub (3), and a regeneration-agent reservoir (21) structured to receive a salt or other regeneration agent for performing a regeneration of the water softening function of said water softening agents;
- the laundry washing machine (1) being **characterized in that** at least one among the water-softening agent container (23) and the regeneration-agent reservoir (21) is a stand-alone modular component-part (21, 23) which is provided with mechanical coupling means (21a, 23a) structured for allowing rigid fastening of said stand-alone modular component-part (21, 23) to the detergent dispenser (9).
2. Laundry washing machine according to Claim 1, characterized in that the detergent dispenser (9) is provided with a first housing (14) which extends inside the casing (2), and in that at least one among the water-softening agent container (23) and the regeneration-agent reservoir (21) is structured for being rigidly fastened to the first housing (14) of said detergent dispenser (9).
3. Laundry washing machine according to Claim 2, characterized in that the regeneration-agent reservoir (21) of the water softening device (11) is arranged beside the first housing (14) of the detergent dispenser (9).
4. Laundry washing machine according to Claim 3, characterized in that the regeneration-agent reservoir (21) is arranged beside the first housing (14) of the detergent dispenser (9), in a direction locally substantially parallel to the front wall (2a) of the casing (2).

5. Laundry washing machine according to Claim 3 or 4, characterized in that the regeneration-agent reservoir (21) is provided with mechanical coupling means (21a) structured for allowing rigid fastening of the regeneration-agent reservoir (21) to a sidewall of the first housing (14) of said detergent dispenser (9).

5 6. Laundry washing machine according to any one of the foregoing claims, characterized in that the water-softening agent container (23) is a stand-alone modular component-part (23) which is provided with mechanical coupling means (23a) structured for allowing rigid fastening and fluidical connection of the water-softening agent container (23) to the bottom of the regeneration-agent reservoir (21).

10 7. Laundry washing machine according to Claim 6, characterized in that said water-softening agent container (23) is located beneath said regeneration-agent reservoir (21) within a seat delimited by the lateral wall (2b) of the casing (2), the upper portion of the washing tub (3) and the front wall (2a) of the casing (2).

8. Laundry washing machine according to any one of the foregoing claims, 15 characterized in that the water-softening agent container (23) is a stand-alone modular component-part (23) which is provided with mechanical coupling means (23b, 23c) structured for allowing rigid fastening and fluidical connection of the water-softening agent container (23) to the detergent dispenser (9).

9. Laundry washing machine according to any one of the foregoing claims, 20 characterized in that the detergent dispenser (9) is provided with complementary mechanical coupling means structured for engaging the mechanical coupling means (21a) of said regeneration-agent reservoir (21) and/or said water-softening agent container (23).

10. Laundry washing machine according to any one of the foregoing claims, 25 characterized in that the detergent dispenser (9) is exposed or exposable to the outside of the casing (2) through the front wall (2a) of said casing (2).

11. Laundry washing machine according to Claim 10, characterized in that said detergent dispenser (9) comprises a detergent container (13) which is fillable with a given quantity of detergent, softener and/or other washing agent, and is housed inside 30 the casing (2) into said first housing (14).

12. Laundry washing machine according to Claim 11, characterized in that said

detergent container (13) is movable inside said first housing (14) so as to be at least partly extractable from the first housing (14) through a first opening (14a) on the front wall (2a) of the casing (2).

13. Laundry washing machine according to any one of the foregoing claims,
5 characterized in that the regeneration-agent reservoir (21) of the water softening device (11) is exposed or exposable to the outside of the casing (2) through the front wall (2a) of said casing (2).

14. Laundry washing machine according to any one of the foregoing claims,
characterized in that the regeneration-agent reservoir (21) comprises a regeneration-
10 agent container (32, 132, 232) which is fillable with a given quantity of regeneration agents, and is housed inside the casing (2) into a corresponding second housing or seat (33).

15. Laundry washing machine according to Claim 14, characterized in that the detergent dispenser (9) comprises also the second housing or seat (33) of said
15 regeneration-agent reservoir (21).

16. Laundry washing machine according to Claim 14 or 15, characterized in that said regeneration-agent container (32, 132, 232) is movable inside said second housing or seat (33) so as to be at least partly extractable from the second housing or seat (33) through a second opening (33a) on the front wall (2a) of the casing (2).



20 17. Laundry washing machine according to Claims 12 and 16, characterized in that the displacement direction of the regeneration-agent container (32, 132, 232) inside the second seat (33) is locally substantially parallel to the displacement direction of the detergent container (13) inside the first seat (14).

18. Laundry washing machine according to Claim 17, characterized in that said
25 detergent container (13) and said regeneration-agent container (32, 132, 232) are able to jut out from the front wall (2a) of the casing (2) while remaining locally substantially parallel to one another.

19. Laundry washing machine according to any one of the foregoing claims, characterized in that said water softening device (11) furthermore comprises a water
30 supply circuit (22) which is structured for selectively spilling/pouring a given amount of fresh water into the regeneration-agent reservoir (21) to at least partly dissolve the

regeneration agents stored therein; the water-softening agent container (23) communicating with said regeneration agent reservoir (21) for receive said solution of regeneration agents.

20. Laundry washing machine according to any one of the foregoing claims,
5 characterized in that the water-softening agent container (23) is arranged between the detergent dispenser (9) and main valve means (10).








Fig. 3






Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 11




Fig. 10




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16

