



(22) Date de dépôt/Filing Date: 1995/10/11

(41) Mise à la disp. pub./Open to Public Insp.: 1996/04/14

(45) Date de délivrance/Issue Date: 2003/09/23

(30) Priorité/Priority: 1994/10/13 (08/322,978) US

(51) Cl.Int.⁶/Int.Cl.⁶ F25B 49/02


(72) Inventeurs/Inventors:
ODEN, KENNETH W., US;
SELFIDGE, GLENN D., US

(73) Propriétaire/Owner:
ROYAL VENDORS, INC., US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : COMMANDE ELECTRONIQUE POUR SYSTEME DE REFRIGERATION

(54) Title: ELECTRONIC REFRIGERATION CONTROL SYSTEM



(57) Abrégé/Abstract:

The present invention is directed to a system and method for electronically controlling the refrigeration and/or heating of the product storage compartment in a vending machine. The system includes a temperature sensor for sensing the temperature in the product storage compartment, and a door sensor for sensing whether the door is open or closed. The control method

(57) Abrégé(suite)/Abstract(continued):

includes the steps of activating a defrost mode, which is a timed period with no heating or cooling activity, when the door to the vending apparatus is open. The defrost mode is also activated whenever the cooling element has been running continuously for several hours. Further, the control method includes a step of cycling the cooling element "on" whenever a predetermined high temperature is reached. When the cooling element is "off" for more than 6 hours and the predetermined high temperature has not been reached, the heater is turned "on" to prevent the products in the vending machine from freezing.

2160338

ABSTRACT OF THE DISCLOSURE

The present invention is direct to a system and method for electronically controlling the refrigeration and/or heating of the product storage compartment in a vending machine. The system includes a temperature sensor for sensing the temperature in the product storage compartment, and a door sensor for sensing whether the door is open or closed. The control method includes the steps of activating a defrost mode, which is a timed period with no heating or cooling activity, when the door to the vending apparatus is open. The defrost mode is also activated whenever the cooling element has been running continuously for several hours. Further, the control method includes a step of cycling the cooling element "on" whenever a predetermined high temperature is reached. When the cooling element is "off" for more than 6 hours and the predetermined high temperature has not been reached, the heater is turned "on" to prevent the products in the vending machine from freezing.

2160338

AN ELECTRONIC REFRIGERATION CONTROL SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention is directed to a system and method for electronically controlling the refrigeration and/or heating of the product storage compartment in a vending apparatus.

2. Related Art

10 Currently, vending machines have widespread application and utilization. Vending machines can be found not only, in restaurants and other eateries, but also both inside and outside such facilities as offices, recreation centers, hospitals, gasoline stations, and apartment complexes. Because of their location, vending machines often experience both high and low
15 levels of usage over a period of time. Further, such machines may be exposed to extremes of temperature and humidity for extended periods. Some vending machines are run for so long that ice and frost occur in the machines even though the products to be dispensed are warm.

20 When a vending machine is exposed to extremely cold temperatures, its cooling system should not be running continuously. In fact, prolonged periods of cold weather can freeze the products in the vending machine.

25 Moreover, when a vending machine door is open for loading or servicing, continuing to run the machine's compressor may cause problems in normal operation.

5 In the prior art, various types of systems have been proposed and implemented to optimize vending machine operation under varying conditions. For example, U.S. Patent No. 5,231,844 to Park discloses a refrigerator defrost control method in which the refrigerator is defrosted by comparing a sensor temperature in the refrigerator with a predetermined temperature during a defrost period. This defrost control method includes sensing the open/closed conditions of the refrigerator doors, and activating a defrost heater when the
10 doors are closed.

U.S. Patent No. 5,228,300 to Shim discloses an automatic refrigerator operation control method that includes controlling the temperature setting of a chamber; defrost cycling; and the operation of a compressor and fan motor according to the frequency of the door being opened and closed and to the open
15 time of the door.

U.S. Patent No. 5,046,324 to Otoh, et al. shows a defrosting controller for refrigeration systems. The controller determines a frost melting period from the measurements of the evaporator temperature during defrosting by means of an
20 evaporator temperature sensor.

U.S. Patent No. 4,932,217 to Meyer shows a process for controlling a heater; particularly, a defrost heater for refrigeration plants. In this process, the temperature of the

room to be heated is measured at intervals of time and in each case a measured temperature value is stored.

U.S. Patent No. 4,916,912 to Levine, et al. shows a heat pump with adaptive frost determination functions.

5 U.S. Patent No. 4,903,501 to Harl discloses a refrigerator air-control heated baffle.

U.S. Patent No. 4,850,198 to Helt, et al. discloses a refrigerator compressor control method involving momentarily energizing the compressor after extended off periods.

10 U.S. Patent No. 4,745,629 to Essig, et al. discloses an improved duty-cycle timer that provides a duty-cycle control signal having alternate "on" and "off" intervals of different logic states. In one embodiment of this invention, the duty-cycle timer controls operation of a refrigeration circuit
15 defrost mechanism.

U.S. Patent No. 3,518,841 to West, Jr. discloses a household refrigerator apparatus that includes an evaporator automatically defrostable through use of an electric heating element energized at varying timed intervals.

20 In comparison to the present invention, devices and systems known in the prior art, such as those discussed above, do not directly address or solve the problems to which the present invention is directed but rather suffer from those same problems and disadvantages. In particular, conventional refrigeration
25 control systems suffer from unnecessary compressor cycling when

the refrigeration system attempts to start before pressures have equalized in the evaporator and the condenser. Also, conventional control systems do not effectively maintain refrigerated compartment temperature when outside temperatures are extremely cold for extended periods. Instead, such systems remain unnecessarily idle, with the compressor off, for periods in excess of several hours, thereby allowing ambient conditions to determine the refrigerated compartment temperature. Even further, the conventional refrigeration control systems in the prior art do not provide service personnel any way to efficiently troubleshoot the vending machines.

SUMMARY OF THE INVENTION

One main object of the present invention is to provide a system and method for efficiently controlling the refrigeration system (i.e., the compressor and its related components) and heating element of a vending machine. In particular, a specific object of the present invention is to provide a system and method of controlling a vending machine so as to prevent both unnecessary cycling of the compressor and ineffective maintenance of the refrigerated compartment temperature under extreme operating conditions. The present invention includes specific features that are lacking in the teachings of the prior art.

2160338

5 The features of the present invention include the ability to activate a timed defrost mode with no heating or cooling activity, and the ability to use an electric heater to prevent products in the vending machine from freezing when outside temperatures are extremely low. Further, the present invention includes a logic test with temperature sensing to determine both ambient conditions and controlled cabinet temperature.

10 Another object of the present invention is to provide an electronic control system that allows service personnel to efficiently troubleshoot problems in the vending machine. In particular, the system provides service personnel an electronic memory that stores information on error conditions and a display for showing the cabinet temperature at the sensor location.

15 Overall, a main object of the present invention is to provide a system and method for controlling the temperature of a vending machine more efficiently and reliably.

BRIEF DESCRIPTION OF THE DRAWINGS

20 The invention is better understood by reading the following detailed description of the preferred embodiment with reference to accompanying drawing figures, in which like reference numerals refer to like elements throughout, and in which:

Figure 1 illustrates a circuit block diagram of one embodiment of the hardware implementation of the present invention;

Figure 2 illustrates a circuit block diagram of the controller of the first embodiment of the present invention as shown in Figure 1; and

Figures 3a - 3c together illustrate the logic diagram for the refrigeration control system of a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In describing preferred embodiments of present invention illustrated in the drawings, specific terminology is employed for the sake of clarity. The invention is not intended to be limited to the specific terminology so selected, however, and it is to be understood that each specific element includes all technical equivalents that operate in a similar manner to accomplish a similar purpose.

In one embodiment, the present invention as illustrated in Figure 1 is generally directed to a system 1 for controlling the operation of a cooling element 3 and a heater element 4 of a vending machine 2. In this embodiment, the cooling element 3 is based on a vapor compression refrigeration cycle comprising a refrigeration fluid compressor and its associated components, while the heater element 4 is a silicon sheet heater bonded to a metal mounting bracket. The heater element 4 also has a built-in independent over-temperature safety control. A temperature sensor 5 (for example, a National Semiconductor

LM34DZ precision Fahrenheit temperature sensor) senses the temperature in the refrigerated compartment 10 of the vending machine 2, and inputs a temperature signal to a controller 6. The controller 6 in this embodiment is based on a Motorola 68HC11E1 8-bit processor with one of its eight analog-to-digital inputs being used to receive signals from the temperature sensor 5.

As shown in Figure 2, the controller 6 is organized as a main controller 6a with a refrigeration control 6b and a heater element control 6c. In this preferred embodiment, the main controller 6a, refrigeration control 6b and heater element control 6c are implemented as the operating software of the controller 6. Thus, the controls 6a - 6c are, for example, first stored in ROM memory and then loaded into the RAM memory of a processor in the controller 6 when the controller 6 is first initialized. As will be explained below, the controller 6 also incorporates a memory 12 (for example, a SGS Thompson M27c512 64k x 8 bit EPROM) for storing the operating system of the controller 6, the parameters for various timers and temperatures used in the operation of the system, the status of various warning flags, as well as temperature readings made by the temperature sensor 5. A user interface 20 allows service personnel to access the controller, and thereby the memory 12, in order either to check the status of the warning flags or to change the operating parameters in the system. The user

2160338

interface can be a hand-held terminal (e.g., a laptop computer) that connects to the controller through a TTL level RS-232 port for DEX transmissions. A display 7 is used to show the temperature of the refrigerated compartment of the vending machine. The display 7 can be an alphanumeric display using LEDs, for example. A sensor 8 connected to the door 9 of the refrigerated compartment 10 is used to monitor the opening and closing of the door 9. The sensor 8 in this embodiment is a switch (e.g., a momentary contact switch) that is activate/deactivated depending on the opening/closing of the door 9.

The various timers 13 - 19, in this preferred embodiment, are also software implemented in that they constitute software logic routines that are accessed as required. Their parameters are initially stored in the memory 12, and the timers can be operated, as an example, based on the internal clock of the processor in the controller 6. The internal clock provides the base timing pulses which can then be counted and translated for the various timer operations.

In operation, the refrigeration control 6a cycles the refrigerated compartment of the vending machine between a refrigeration cut-in or high temperature and a refrigeration cut-out or low temperature. The refrigeration cut-in and cut-out temperatures can be set by the manufacturer to have a limited range of adjustability; both temperatures are then

5 stored in the memory 12. For example, the refrigeration cut-in temperature would be initially set to 41°F by the manufacturer, and be adjustable between 45°F and 39°F. On the other hand, the refrigeration cut-out temperature would be initially set at 29°F and be adjustable between 34°F and 24°F.

10 The heater element control 6b cycles between a heating cut-out or high temperature and a heating cut-in or low temperature. In the present embodiment, both the heating cut-out and cut-in temperatures are set by the manufacturer and are not adjustable; both temperatures also are stored in the memory 12. For example, the heating cut-out temperature would be set to 36°F, while the heating cut-in temperature would be set to 32°F.

15 The controller 6 is designed to produce five refrigeration and heating control modes for the vending machine. These modes are:

1. Defrost mode
2. Refrigeration mode with cooling element "off"
3. Refrigeration mode with cooling element "on"
4. Heating mode with heating element "off"
- 20 5. Heating mode with heating element "on"

The defrost mode, a main feature of the present invention, is a timed period of inactivity wherein no active heating or cooling is performed by the system. As illustrated in Figures 3a - 3c, when the door 9 of the vending machine 2 is opened

2160338

(Step 100), the door sensor 8 is activated and a door safety timer 14 begins running (Step 101) (e.g., for one hour) to signal that the door 9 is open. A first defrost timer 15 (Step 102) then starts to run (e.g., for 3.5 minutes) to monitor the defrost period. If the door 9 is closed before the first defrost timer 15 runs out, the main controller 6a will detect the door 9 being closed through the door sensor 8 (Step 105). At that point, the main controller 6a will activate the refrigeration control 6b to initiate a refrigeration mode with the cooling element 3 "off" (Step 107). If, however, the first defrost timer 15 runs out before the door 9 is closed, the main controller 6a will first detect whether the door 9 is in fact closed using the door sensor 8 (Step 105). If not, the door safety timer 14 is checked to determine if it too has run out (Step 109). If the door safety timer 14 has run out, the temperature sensor 5 is checked to determine if the temperature in the refrigerated compartment 10 is a predetermined amount (e.g., 3°) below the refrigeration cut-out temperature defined in the memory 12. If so, a "cold" error flag is set in the memory 12 to indicate that such a condition has occurred. After setting the "cold" error flag or if the temperature is not detected to be below the refrigeration cut-out temperature, control reverts to the refrigeration control 6b in the refrigeration mode with the cooling element 3 "off" within a preset time; for example, 30 seconds.

5 The operation of the door safety timer 14 is used to
monitor the door sensor 8. Should the door sensor 8 be
defective, the main controller 6a would automatically transfer
control to the refrigeration modes, starting with the mode
10 having the cooling element 3 "off." This would allow the main
controller 6a to monitor the temperature in the refrigerated
compartment 10. For example, if a defective door sensor 8 was
unable to detect the door 9 being open for an extended period of
time or if the defective door sensor 8 signaled that the door 9
15 was closed while in fact it was open, the main controller 6a
would revert control to the refrigeration modes in order to
prevent a significant loss in temperature. On the other hand,
if the defective sensor 8 instead signaled that the door 9 was
open while in fact it was closed, the main controller 6a
15 reverting control to the refrigeration control 6b in the
refrigeration mode with the cooling element "off" (Step 107)
would effectively ignore the erroneous signals and bypass the
defective sensor 8.

20 A second defrost timer 16 with a second defrost period can
be initiated when the cooling element 3 has been running
continuously for a predetermined time period (e.g., 4 hours).
As shown in Figure 3b and as will be explained below, the
refrigeration mode with the cooling element 3 "on" operates with
a cooling element "on" timer 18 (Step 121). In this embodiment,
25 that cooling element "on" timer 18 is set for four hours. If

the four hours run out, the second defrost timer 16 is activated (See Figure 3a) for, in this case, 18 minutes (Step 108). With the second defrost timer 16 activated, the second defrost period continues operation similar to the first defrost period. After that second defrost period is completed, control reverts to the refrigeration mode with the cooling element 3 "off."

In the two refrigeration modes, the cooling element 3 is cycled either "on" (Step 120) or "off" (Step 107). For the refrigeration mode with the cooling element "off," a cooling element "off" timer 17 is initiated in step 106 (e.g., 6 hours) and monitored (Step 117). During this time period, the refrigeration control 6b is constantly monitoring for the refrigeration cut-in temperature (Step 118) stored in the memory 12, and for the temperature of the refrigerated compartment 10 to reach the predetermined amount below the refrigeration cut-out temperature (Step 116) through the temperature sensor 7, as explained above. If the refrigeration cut-in temperature does occur as in Step 118, the refrigeration mode with the cooling element "on" operates as in Step 120. If the cooling element "off" timer 17 runs out without reaching the refrigeration cut-in temperature, the refrigeration control 6b will automatically assume that the outside ambient temperature is too low. Consequently, control will revert to the heater element control 6c with the heating mode having the heater element 4 "on" to prevent the products in the vending machine from freezing, and

the cooling element 3 from running when the outside ambient temperature is lower than the temperature of the refrigeration compartment 10.

As illustrated in Figure 3b, in the refrigeration mode with the cooling element "on" as in Step 120, the cooling element "on" timer 18 (Step 119) is initiated (e.g., 4 hours) during which the refrigeration control 6b constantly monitors for the refrigeration cut-out temperature (Step 122) defined in the memory 12. The temperature of the refrigerated compartment 10 when the cooling element 3 is activated is recorded, and a cooling timer 19 is initiated to record the length of time of the cooling element 3 running. If the cut-out temperature is reached, the refrigeration mode cycles the cooling element "off" with the first defrost period (e.g., 3.5 minutes) as in Step 102 initiating the first defrost timer 15. Effectively, after cycling in the refrigeration mode with the cooling element "on," the cooling element 3 is turned "off" and the first defrost period is initiated before returning to the refrigeration mode with the cooling element "off." If the cooling element "on" timer 18 runs out (Step 121), the refrigeration control 6b assumes that the heat exchanger 11 has developed ice and the second defrost timer 16 begins to run with the second defrost period (e.g., eighteen minutes) as in Step 108.

While monitoring for the refrigeration cut-out temperature, the refrigeration control 6b also compares the current

temperature of the refrigerated compartment 10 with the temperature measured when the cooling element 3 was activated and stored in the memory 12 (Step 125). In other words, the temperature at TIME 0 is the temperature of the refrigerated compartment when the cooling element 3 was initially turned "on." If the current temperature is less than the temperature at TIME 0, the refrigeration control 6b continues monitoring. If the current temperature is greater, the refrigeration control 6b determines if that condition of the temperature has lasted more than a predetermined time period stored in the memory 12 (e.g., thirty minutes) (Step 124) based on the cooling timer 19. If the predetermined time period has not been exceeded, the refrigeration control 6b returns to monitoring for the refrigeration cut-out temperature (Step 122). If the time period has been exceeded, a "not cooling" error flag is set in the memory 12 to produce a warning. Afterward, the refrigeration control 6b again returns to monitoring.

Also while monitoring for the refrigeration cut-out temperature, the refrigeration control 6b monitors the condition of the temperature sensor 5. This operation is intended to determine if any defects (e.g., a defective sensor, broken signal wires) exist in connection with the temperature sensor 5. If the temperature sensor 5 is detected to be "open" or not transmitting any signals (Step 127), a "sensor open" error flag is set in the memory 12 to generate a warning (Step 126). If

the temperature sensor 5 is not detected to be "open," or after the setting of the "sensor open" error flag, the refrigeration control 6b returns to monitoring the cooling element "on" timer 18 (Step 121).

5 In the two heating modes, an electric heating element 4 is cycled either "on" (Step 129) or "off" (Step 132). As shown in Figure 3c, in the heating mode with the heating element "on" (Step 129), the heating element control 6c constantly measures for the heater cut-out temperature (Step 130) defined in the
10 memory 12. If the heater cut-out temperature is reached, control transfers to the heating mode with the heating element "off"; the heater is turned "off" (Step 131).

 In the heating mode with the heating element "off," the heating element control 6c constantly monitors for the
15 predetermined heater cut-in temperature (Step 134) and a predetermined temperature (e.g., 50°F) that transfers control to the refrigeration mode with the cooling element "on" (Step 133). If the heater cut-in temperature is reached as in Step 134, the heating element control 6c cycles the heating element 4 in the
20 heating mode with the heating element "on" (Step 129). As noted in Figure 3c, no timers are utilized in either of the heating modes.

 Also illustrated in Figure 3a, Steps 110 through 114 embody the "power up" sequence of the vending machine 2. As shown,
25 when power is initiated (Step 100), the controller 6 monitors

whether the supply voltage received by the vending machine 2 is less than the power voltage requirement (e.g., 95 VAC) of the vending machine 2 (Step 110). If the power voltage requirement has been reached, the controller 6 continuously monitors it. If not, a power-up timer (e.g., 30 seconds) is initiated to allow the voltage level to build up (Step 111). During this timer period, the controller 6 continuously determines whether the power voltage requirement is reached (Step 112). If the required voltage is reached, the controller 6 then switches to monitoring (Step 110). If not, the controller 6 checks the power-up timer 13 if it has run out (Step 113). While the power-up timer 13 is still running, the controller 6 will revert back to monitoring the buildup of the supply voltage (Step 112). If the power-up timer 13 has run out, a "voltage" error flag warning is set (Step 114); afterward, the controller reverts to monitoring the supply voltage (Step 110).

By virtue of the logical operation of the present invention, unnecessary cycling on the cooling element and/or its related components is prevented. For example, if a cooling element based on a compressor is used, the compressor can be prevented from starting before the pressures in its evaporator and condenser have equalized by the timed defrost period. Further, the logical operation prevents the ineffective control of the temperature under extreme ambient temperature conditions.

2160338

The timed defrost period also eliminates the occurrence of evaporator icing when the vending machine products are warm.

5 Modifications and variations of the above-described
embodiments of the present invention are possible as appreciated
by those skilled in the art in light of the above teachings.
For example, the structure and operation of the controller 6,
such as the various timers, the refrigeration control, the
heater element control and the memory, can all be embodied not
only in hardware, but also in software. Instead of a cooling
10 system based on a refrigeration fluid compressor with an
evaporator and condenser, the present invention can also operate
using thermoelectric or absorption cooling cycles. Also, the
system can incorporate relay drivers and high-voltage relays
(for example, a ULN relay driver with a 74HC595 serial input-to-
15 parallel output shift register) in order to deliver the
necessary voltage and current levels to the cooling element and
heater element systems. Alternatively, the system can
incorporate power electronic circuits designed to handle such
high levels of power, in order to integrate the structure and
20 features of the invention in a more compact device. Also,
instead of interfacing using a user interface 20 to access the
memory 12, user controls (i.e., switches, a keypad) can be built
in with the controller 6 that could be used to signal the
controller to display the information from the memory 12 on the
25 display 7.

2160338

Consequently, it is therefore to be understood that, within the scope of the appending claims and their equivalence, the invention may be practiced otherwise than it is specifically described.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:**

1. A system for electronically controlling the
refrigeration and heating of a product storage compartment
5 of a vending machine having a door, the system comprising:

a temperature sensor sensing the temperature of the
storage compartment;

a door sensor detecting whether the door of the
vending machine is open or closed;

10 a cooling element for refrigerating the refrigerated
compartment;

a heater element for heating the refrigerated
compartment; and

an electronic controller connected to said temperature
15 sensor, door sensor, cooling element, and heater element,
said controller including

refrigeration control means for controlling
refrigeration of the storage compartment in at least one of
a refrigeration mode with said cooling element in an ON
20 state and a refrigeration mode with said cooling element in
an OFF state,

heating control means for controlling heating of the
storage compartment in at least one of a heating mode with
said heater element in an ON state and a heating mode with
25 said heater element in an OFF state, and

main control means for controlling defrosting of the storage compartment in a defrost mode with both said cooling element and said heater element in an OFF state, and for switching control between said refrigeration control means, said heating control means and said defrost mode based on signals from at least said temperature sensor and said door sensor.

2. A system for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 1, the system further comprising:

a user interface connected to said electronic controller to access control data from said electronic controller.

3. A system for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 1, wherein said main control means includes a door safety timer for monitoring when the door of the storage compartment is open and a defrost timer for monitoring a time of the defrost mode.

4. A system for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 1, wherein said refrigeration control means includes a cooling element OFF timer for monitoring a time of said cooling element being OFF, a cooling element ON timer for monitoring a time of said cooling element being ON and a cooling timer for monitoring a time of the temperature in the storage compartment dropping.

5. A system for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 1, wherein said main control means includes a memory for storing temperature control data and
5 timer data used in said main control means, said refrigeration control means and said heating control means, and error flag data generated by said electronic controller.

6. A system for electronically controlling the
10 refrigeration and heating of a product storage compartment as claimed in claim 5, the system further comprising:

a user interface connected to said electronic controller to access the temperature control data, timer data and error flag data from said memory of said
15 electronic controller.

7. A control circuit for electronically controlling the refrigeration and heating of a storage compartment of a vending machine, said vending machine having a door, a cooling element and a heater element, the circuit
20 comprising:

a temperature sensor sensing the temperature of the storage compartment;

a door sensor detecting whether the door of the vending machine is open;

25 a main controller connected to said temperature sensor, door sensor, cooling element, and heater element,

said main controller maintaining both the cooling element and the heater element in an OFF state;

a refrigeration controller connected to said main controller, said refrigeration controller controlling said
5 cooling element in one of an ON state and an OFF state;

a heating controller connected to said main controller, said heating controller controlling said heater element in one of an ON state and an OFF state; and

a memory for storing temperature control data and
10 timer data used in said main controller, said refrigeration controller, and said heating controller, and error flag data generated by said main controller, wherein said main controller further controls switching operation with one of said refrigeration controller and said heating controller
15 based on signals from at least said temperature sensor and said door sensor.

8. A control circuit for electronically controlling the refrigeration and heating of a storage compartment as claimed in claim 7, the circuit further comprising: a user
20 interface connected to said main controller to access the temperature control data, timer data, and error flag data from said memory.

9. A control circuit for electronically controlling the refrigeration and heating of a storage compartment as
25 claimed in claim 7, wherein said main controller includes a door safety timer for monitoring when the door of the storage compartment is open and a defrost timer for

23

monitoring a time of said cooling and heater elements being in an OFF state.

10. A control circuit for electronically controlling the refrigeration and heating of a storage compartment as
5 claimed in claim 7 wherein said refrigeration controller includes a cooling element OFF timer for monitoring a time of the cooling element being OFF, a cooling element ON timer for monitoring a time of the cooling element being ON and a cooling timer for monitoring a time of the
10 temperature in the storage compartment dropping.

11. A method for electronically controlling the refrigeration and heating of a product storage compartment in a vending apparatus, comprising the steps of:

sensing a temperature in the product storage
15 compartment;

determining whether the product storage compartment is open or closed; and

maintaining the product storage compartment in one of a defrost mode, a passive refrigeration mode, a passive
20 heating mode, an active refrigeration mode, and an active heating mode based on said sensing of the temperature and said determining whether the product storage compartment is open, wherein

said passive refrigeration mode includes monitoring a
25 refrigeration temperature of the product storage compartment, switching to said active heating mode when said passive refrigeration mode exceeds a passive

predetermined time period, and switching to said active refrigeration mode when the refrigeration temperature reaches a predetermined refrigeration cut-in temperature,

said active refrigeration mode includes refrigerating
5 the product storage compartment for an active predetermined time period, switching to said defrost mode when refrigerating the product storage compartment reaches a predetermined refrigeration cut-out temperature and switching to said defrost mode when refrigerating the
10 product storage compartment reaches the active predetermined time period,

said passive heating mode includes monitoring a heating temperature of the product storage compartment, switching to said active heating mode when the heating
15 temperature drops to a predetermined heating cut-in temperature and switching to said active refrigeration control when the heating temperature reaches the predetermined refrigeration cutin temperature,

said active heating mode includes heating the product
20 storage compartment and switching to said passive heating-mode when the heating temperature during the heating of the product storage compartment reaches a predetermined heating cut-out temperature, and

said defrost mode includes maintaining refrigeration
25 and heating control of the product storage compartment inactive for a predetermined defrost time period and switching to said passive refrigeration mode when the

predetermined defrost time period is reached and the product storage compartment is determined to be closed.

12. A method for electronically controlling the refrigeration and heating of a product storage compartment
5 as claimed in claim 11, wherein said defrost mode further includes maintaining the refrigeration and heating control of the product storage compartment inactive for a predetermined door-open safety time period and switching to said passive refrigeration mode when the predetermined
10 door-open safety time period is reached and the product storage compartment is determined to be open.

13. A method for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 11, wherein said passive refrigeration
15 mode further includes determining whether the temperature of the product storage compartment is lower than the predetermined refrigeration cut-out temperature by a predetermined difference, and setting a cold error flag warning when the temperature of the product storage
20 compartment is lower than the predetermined refrigeration cut-out temperature by the predetermined difference.

14. A method for electronically controlling the refrigeration and heating of a product storage compartment as claimed in claim 11, wherein said active refrigeration
25 mode further includes determining if a current temperature of the product storage compartment is less than a prior temperature, determining if the current temperature of the product storage compartment has been less than the prior temperature for a predetermined cooling time period, and

setting a not-cooling error flag warning when the current temperature of the product storage compartment is determined to having been less than the prior temperature for the predetermined cooling time period.

- 5 15. A method for electronically refrigerating and heating a product storage compartment in a vending apparatus which has a door, a cooling element and a heater, said method comprising the steps of:

sensing a temperature in the product storage
10 compartment;

determining whether the door of the vending apparatus is open or closed;

maintaining refrigeration and heating of the product storage compartment inactive for a first predetermined
15 defrost time period;

passively refrigerating the product storage compartment with the cooling element in an OFF state when the first predetermined defrost time period is reached and the product storage compartment is determined to be closed;
20 monitoring the temperature of the product storage compartment during said passive refrigerating for a passive predetermined time period;

actively refrigerating the product storage compartment with the cooling element in an ON state when the
25 temperature of the product storage compartment reaches a

27

predetermined refrigeration cut-in temperature for an active predetermined time period;

switching to maintaining refrigeration and heating of the product storage compartment inactive for the first
5 predetermined defrost time period when said active refrigerating of the product storage compartment reaches a predetermined refrigeration cut-out temperature;

switching to maintaining refrigeration and heating of the product storage compartment inactive for a second
10 predetermined defrost time period when said active refrigerating of the product storage compartment reaches the active predetermined time period;

actively heating the product storage compartment with the heater in an ON state when the passive predetermined
15 time period is reached;

passively heating the product storage compartment with the heater in an OFF state after actively heating the product storage compartment when the temperature of the product storage compartment reaches a predetermined heating
20 cut-out temperature;

monitoring the temperature of the product storage compartment during said passive heating;

actively heating the product storage compartment with the heater in the ON state when the temperature of the
25 product storage compartment drops to a predetermined heating cut-in temperature during said passive heating; and

actively refrigerating the product storage compartment with the cooling element in an ON state when the heating temperature reaches the predetermined refrigeration cut-in temperature during said passive heating.

- 5 16. A method for electronically refrigerating and heating a product storage compartment as claimed in claim 15, further comprising the steps of:

maintaining refrigeration and heating of the product storage compartment inactive for a predetermined door-open
10 safety time period if the door is determined to be open;
and

passively refrigerating the product storage compartment when the predetermined door-open safety time period is reached and the door is determined to be open.

- 15 17. A method for electronically refrigerating and heating a product storage compartment as claimed in claim 15, wherein said step of passively refrigerating includes determining whether the temperature of the product storage compartment is lower than the predetermined refrigeration cut-out
20 temperature by a predetermined difference, and setting a cold error flag warning when the temperature of the product storage compartment is lower than the predetermined refrigeration cut-out temperature by the predetermined difference.

- 25 18. A method for electronically refrigerating and heating a product storage compartment as claimed in claim 15, wherein said step of actively refrigerating includes determining if a current temperature of the product storage compartment is

29

less than a prior temperature, determining if the current temperature of the product storage compartment has been less than the prior temperature for a predetermined cooling time period, and setting a not-cooling error flag warning
5 when the current temperature of the product storage compartment is determined to having been less than the prior temperature for the predetermined cooling time period.

19. A method for refrigerating and heating a vending
10 machine having a storage compartment and a door, said method comprising the steps of:

sensing a temperature in the storage compartment;

sensing whether the door is open or closed;

maintaining refrigeration and heating of the storage
15 compartment inactive for a first predetermined defrost time period;

refrigerating the storage compartment for a predetermined refrigerating time period when the first predetermined defrost time period is reached and the
20 storage compartment is determined to be closed;

switching to maintaining refrigeration and heating of the storage compartment inactive for the first predetermined defrost time period when the temperature of the storage compartment during said refrigerating of the
25 storage compartment reaches a predetermined refrigeration cut-out temperature;

30

switching to maintaining refrigeration and heating of the storage compartment inactive for a second predetermined defrost time period when said refrigerating of the storage compartment reaches the predetermined refrigerating time
5 period;

heating the storage compartment when the temperature of the storage compartment drops to a predetermined heating-cut-in temperature and until a predetermined heating cut-out temperature is reached; and

10 switching to refrigerating the storage compartment after said heating when the temperature of the storage compartment reaches the predetermined refrigeration cut-in temperature.

20. A method for refrigerating and heating a vending
15 machine as claimed in claim 19, said method further comprising the steps of:

maintaining refrigeration and heating of the storage compartment inactive for a predetermined door-open safety time period if the door is determined to be open; and

20 refrigerating the storage compartment when the predetermined door-open safety time period is reached and the door is determined to be open.


21. A method for refrigerating and heating a vending machine as claimed in claim 19, wherein said step of
25 refrigerating includes determining whether the temperature of the storage compartment is lower than the predetermined refrigeration cut-out temperature by a predetermined

difference, and setting a cold error flag warning when the temperature of the storage compartment is lower than the predetermined refrigeration cut-out temperature by the predetermined difference.

- 5 22. A method for refrigerating and heating a vending machine as claimed in claim 19, wherein said step of refrigerating includes determining if a current temperature of the storage compartment is less than a prior temperature, determining if the current temperature of the
10 storage compartment has been less than the prior temperature for a predetermined cooling time period, and setting a not-cooling error flag warning when the current temperature of the storage compartment is determined to having been less than the prior temperature for the
15 predetermined cooling time period.


2160339

FIGURE 1



2160338

FIGURE 2



2160338




FIGURE 3a

2160338




FIGURE 3b

FIGURE 3c

