




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61B 17/04		A1	(11) International Publication Number: WO 00/59383
(43) International Publication Date: 12 October 2000 (12.10.00)			
(21) International Application Number: PCT/US00/08902			(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(22) International Filing Date: 4 April 2000 (04.04.00)			
(30) Priority Data: 09/286,484 5 April 1999 (05.04.99) US			Published <i>With international search report.</i>
(71) Applicant: STARION INSTRUMENTS, INC. [US/US]; 20665 4th St., Saratoga, CA 95070 (US).			
(72) Inventors: MOLLENAUER, Kenneth, H.; Starion Instruments, Inc., 20665 4th St., Saratoga, CA 95070 (US). KUCKLICK, Theodore; Starion Instruments, Inc., 20665 4th St., Saratoga, CA 95070 (US).			
(74) Agent: CROCKETT, K., David; Crockett & Crockett, Suite 400, 24012 Calle De La Plata, Laguna Hills, CA 92653 (US).			

(54) Title: SUTURE WELDING DEVICE



(57) Abstract

This invention is devices (1) for welding suture segments (in lieu of tying knots in sutures (41) applied during endoscopic surgery). The devices (1) provide for snaring loose suture ends (47, 48), and drawing the suture ends (47, 48) into a space between heating surfaces (19, 20), and provide for closing the heating surfaces (19, 20).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Suture Welding DeviceField of the Inventions

5 The devices described below relate to the field of surgical devices and methods, specifically to the field of endoscopic suturing techniques.

Background of the Inventions

Sutures and stitching are well known techniques for repairing body tissue after injury or surgery. Many types of 10 surgery, such as gall bladder removal, hernia repair, and even coronary bypass surgery can now be performed through the techniques of endoscopic surgery. Endoscopic surgery, also referred to as laparoscopic surgery, minimally invasive surgery, or bloodless surgery, is performed through small 15 incisions in the body with long slender cutting and grasping devices which can be inserted into the body through the small incisions. The devices have small working mechanisms on the distal end (the end of the instrument that is inserted into the body) and convenient handles and operating mechanisms (for 20 controlling the working mechanisms on the proximal end). Surgeons use endoscopic scalpels and scissors for cutting tissue, endoscopic graspers and forceps for grabbing and manipulating tissue, and endoscopic suture needles for stitching tissue. Stitching a surgical or traumatic wound 25 closed within an endoscopic work space requires quite a bit of manual dexterity and experience, and the final process of tying a knot in the stitching is very difficult.

Several devices have been suggested for assisting 30 surgeons in securing the loose ends of a suture during open surgery. Rather than assisting the surgeon to tie a knot, the

devices allow the surgeon to melt the two loose ends of the suture together or to create a melted mass on a single loose suture tip which prevents it from being withdrawn into the suture pathway. Zinnbauer, et al, Suture Cutting and

5 Cauterizing Method Using Radiant Heat, U.S. Patent 5,565,122 (Oct. 15, 1996), while not intended or adapted for endoscopic use, shows a device with jaws mounted at the distal end of a long neck, and a heating element over the jaws. When the jaws are laid against the skin, and the suture is place between the
10 jaws, the heating element is heated to melt the suture and leave a melted mass of suture material on the suture. The melted mass prevents the suture from being pulled into and through the suture line. Polonsky, Suture Fusing and Cutting Apparatus, U.S. Patent 4,662,068 (May 5, 1987) shows a pair of
15 forceps with heat fusing surfaces on the grasping surfaces of the jaws. The forceps are used to grab and twist two loose suture ends and melt them together to secure the stitching.

Summary

The devices and methods described below permit the
20 closure of stitches during endoscopic surgery. The devices are endoscopic tools capable of insertion into an endoscopic access port, such as a cannula, and include a long slender insertion rod with a handle and operating mechanism on the proximal end and a pair of grasping jaws on the distal end of
25 the rod. The grasping jaws are fitted with heating surfaces which can be heated to temperatures sufficient to melt suture. A snare comprised of a snare portion and a rod is housed within the insertion rod. The snare portion can be pushed out the distal end of the insertion rod and manipulated to snare a
30 length of suture and then pulled proximally into the insertion rod. The snare may be twisted to create a length of twisted-together suture. Because the snare is drawn into the insertion rod, the entrapped suture is pulled into the space

between the jaws where it can be grasped and melted by the jaws. This provides an easy way to get the suture between the jaws with limited movement of the insertion rod within the body and the endoscopic access port. The suture may be 5 tensioned as desired by the surgeon prior to melting by closing the jaws firmly on the suture while drawing the snare proximally, then closely the jaws tightly so that the suture is held in properly tensioned position while the weld is accomplished.

10 In one embodiment, the jaws can be scissor-like, having opposing grasping faces which meet to clamp the suture between the grasping faces. In another embodiment, the grasping faces are mounted on co-axially disposed tubes, where the tubes 15 rotate relative to the each other to bring the grasping faces together and close upon the suture.

A composite weldable suture is described below which is particularly useful in the creating of melted knots. The suture comprises a core, which melts at moderately high temperatures compared to a porous fiber cover, which melts at 20 a high temperature. When two strands of suture are pressed together and exposed to heat, as in the operation of the suture welding devices, the cores melt and seep through the fiber cover and fuse together. The presence of the fiber provides structural integrity to the suture which ensures that 25 the melted knot does not separate from the standing part of the suture.

Brief Description of the Drawings

Figure 1 illustrates a suture welding device for grabbing sutures within an endoscopic work space and fusing a knot in 30 the suture.

Figure 2 illustrates a proximal handle design which permits one handed operation of the suture welding device.

Figure 3 illustrates a step in the operation of the suture welding device of Figure 1.

5 Figure 4 illustrates a step in the operation of the suture welding device of Figure 1.

Figure 5 illustrates a step in the operation of the suture welding device of Figure 1.

10 Figures 6 and 7 illustrate variations on the snare used with the suture welding device.

Figure 8 illustrates a rotary embodiment of the suture welding device.

Figure 9 illustrates a step in the operation of the suture welding device of Figure 8.

15 Figure 10 is an illustration of the suture with a melttable component that may be used with the suture welding devices.

Detailed Description of the Inventions

Figure 1 illustrates a suture welding device 1. The welding device is comprised of a long insertion rod 2, with a distal end 3 and a proximal end 4. The distal end carries a pair of grasping jaws 5 and 6 mounted pivotably within the distal end and protruding from the distal end of the insertion rod. The proximal end is fitted with a handle assembly 7. A snare 8 including a snaring portion 9 mounted on the distal end of a snare rod 10 is slidably and rotatably disposed within the lumen 11 in the insertion rod 2. The snare also includes the handle 12 mounted on its proximal end. The snare exits out the distal end of the insertion rod, and as

illustrated exits through a port in the distal face **13** of the insertion rod. The snare provides a means for initially grasping loose suture ends and drawing the suture ends into close proximity to the jaws. The jaws provide a second means 5 for grasping the suture ends after they have been picked up by the snare.

The insertion rod may be any convenient length, typically 30 to 100 centimeters, and is preferably of small diameter about 2 mm to 2 cm to fit in standard endoscopic access 10 cannulas. The lumen of the insertion rod may also be configured to exit out the side-wall of the insertion rod, thereby directing the snare rod outwardly in a direction which is divergent from the long axis of the insertion rod. The snare portion **9** is comprised of two arcuate branches of 15 resilient metal or plastic, with each branch extending distally from the snare rod to curve first outwardly from the long axis of the snare rod and then inwardly toward the long axis of the snare rod to join together at their distal tips. The resilient branches may preferentially open upon exit from 20 the lumen, and be compressible into a narrow configuration upon withdrawal into the lumen. The grasping jaws mounted on the distal end of the insertion rod extend distally from the insertion rod. Each jaw **5** and **6** has a grasping face **17** and **18** which opposes the grasping face on the other jaw, and the jaws 25 may be closed to bring the grasping faces into contact or close proximity. The grasping face of each jaw includes resistive heating elements **19** and **20** which are connected to an appropriate power supply through electrical wires that run through the jaws and the insertion rod to electrical connector 30 **21** in the handle. The lower jaw **6** holds a suture cutting blade **22** aligned with blade channel **23** on the upper jaw **5**. The grasping faces may have a serrated, knurled or ridged surface to assist in holding the sutures. The handle assembly 7 may include any comfortable gripping structure such as a

pistol grip or scissor handle, a trigger **24** for operating the jaws, and a switch **25** for applying electrical power to the heating elements.

Figure 2 illustrates a proximal handle design which permits one handed operation of the suture welding device. The insertion rod **2** comprises a barrel which houses the snare **8** and the operating rod **26** for the jaws (which is pulled proximally to close the jaws). The handle assembly **7** is mounted on the proximal end **4** of the insertion rod. The snare **10** is fixed to a screw **27**, so that rotation of the screw results in rotation of the snare. The screw has high pitch threads, and slide yoke **28** engages the threads so the longitudinal movement of the slide yoke causes rotation of the screw and snare. When the trigger **29** and yoke are pulled distally, the **15** yoke eventually meets the stop plate **30** mounted on the proximal end of the screw, and further proximal movement of the trigger results in withdrawal of the snare loop **9** into the insertion rod. At this point, the jaws of the device are open, the snare has rotated to form a twist in any suture **20** segments ensnared in the snare loop, and the snare loop has been pulled into the insertion rod. Further proximal travel of the trigger and slide yoke will cause the yoke (and the stop plate) to engage the stop plate **31** which is fixed to the jaw operating rod **26**, and force the operating rod proximally, **25** thereby closing the jaws. The slide yoke is fixed to the trigger **24** through a slot in the handle assembly barrel **32** and the proximal end of the insertion rod. The trigger is slidably mounted in the handle assembly, and is biased to moved distally when not held or squeezed by the surgeon. The **30** bias may be provided with spring clips or spring loaded slides, or various other arrangements. When the jaws are closed upon the sutures, the surgeon may heat the heating elements by operating a push button switch **25**. While the device is illustrated with a grasper having two opposing jaws,

it may be constructed with three or more grasping jaws in mutually opposing relationship. Likewise, although the snare loop is illustrated as a two-armed snare, the snare may be constructed with three or more arms which may be used to 5 ensnare loose suture ends. Additionally, while the operation of the devices is illustrated with a typical suture structure which requires joining two standing parts of the suture structure, three or more standing parts may be joined in the melted "knot" created by the device.

10 Figures 3, 4 and 5 illustrate the use of the suture welding device. In Figure 3 the distal end of the insertion rod is illustrated in proximity to a surgical incision **40** which has been stitched with suture **41**. The suture **41** may be any fusible suture, including the suture described below in 15 reference to Figure 10. The suture segments may be referred to as the stitches **42**, the standing parts **43** and **44** (which are the lengths of suture remaining after the knot is welded), the welding portions **45** and **46** and the ends **47** and **48** (the ends are removed after the knot is welded). The snare loop **9** has 20 been extended distally from the lumen **11** in the insertion rod **2**, and has been manipulated by the surgeon to snare the ends **47** and **48**. Figure 4 illustrates that the snare and snare rod have been pulled proximally to draw the suture ends into the lumen **11**, drawing the welding portions **45** and **46** into the 25 space between the jaws. The snare rod has been rotated within the lumen to coil the fusing portions of the suture ends into a length of intertwined suture segments, referred to as the twist **49**. In Figure 5, the surgeon has closed the jaws upon the twist **49**. The surgeon ensures that enough suture has been 30 taken up in the twist so that the sutured incision is properly closed, tensioning the suture by a combination of pulling and twisting to draw the suture into the insertion rod. The suture may be tensioned as desired by the surgeon prior to melting by closing the jaws firmly on the suture while drawing the snare

proximally, then closely the jaws tightly so that the suture is held in properly tensioned position while the weld is accomplished. The surgeon then applies heating power to the heating elements in the jaws by operating the switch 25 in the handle. The heat fuses the weld portions of each suture into mass that firmly holds the standing parts together, just as would a well tied knot. The closure of the jaws also forces the blade through the suture ends to cut away any excessive length of suture above the weld. (The blade may be omitted where the suture used with the device is easily separable during welding, so the formation of the weld also results in separation of the standing part from the loose ends. A light tension on the loose ends during welding is sufficient to separate some sutures.) When the jaws are opened, the melted twist is released from the jaws and remains in place within the body, just as would the knot. The severed suture ends 47 and 48 may be withdrawn from the device by pulling the snare rod completely out of the proximal end of the suture welding device. The sutures may be inserted into the snare using other endoscopic instruments inserted into the endoscopic workspace through other access ports, and the manipulations necessary to grab the suture and weld it at the proper place may be monitored with endoscopic cameras which are commonly used to visualize endoscopic procedures.

Figures 6 and 7 illustrate variations of the snare that may be used with the suture welding device. In Figure 6, the snare is comprised of two diverging arms 50 extending from the snare rod and forming a Y together with the snare rod. The arms of the grasper may be closed upon withdrawal into the lumen of the insertion rod. The bosses 51 on the outer surface of each arm help urge the arms closed as they are impinged upon by the walls of the lumen. In Figure 7, the snare is comprised of an arcuate branch 52 extending distally from the snare rod and a partial arcuate branch 53 extending

proximally from the distal end of the first arcuate branch 52 back toward the snare rod. Many other embodiments of snares may be used.

Figure 8 illustrates a rotary embodiment of the suture welding device. The device comprises an insertion rod 2 with a distal end 3 and a proximal end 4. The outer tube **54** of the insertion rod houses an inner tube **55** which is rotatable within the outer tube. On the distal end of the inner tubes, heating anvil **56** and grasping surface **57** are formed from a radially extending boss. The inner and outer tubes have a small slot **58** which opens on the distal extremity of each tube. The slot defines longitudinally aligned slot wall **59** (visible in Figure 8) and an opposing slot wall **60** (visible in Figure 9) in the outer tube. A small notch **61** is located in the slot wall **59**, opposite to the heating anvil, to receive and locate the suture in relation to the heating anvil. The heating anvil is mounting on one edge of the slot of the inner tube, and extends radially outwardly from the center axis of the tube and into the slot of the outer tube. The grasping surface of the outer tube is disposed on the slot wall of the outer tube slot which opposes the anvil, so that rotation of the inner tube rotates the anvil into mating relationship with the grasping surface of the outer tube. The proximal end of the insertion rod 2 is fitted with a handle assembly **62** which enables rotation of the inner tube **55** to bring the grasping boss **56** into contact or close proximity with the matching grasping surface **57** within the longitudinally aligned slot on the outer tube. A snare 10 is slidably and rotatably disposed within the insertion rod 2, within a lumen **63** in the inner tube **55**. The snare 8 includes a snare structure 9 mounted on the distal end of the snare rod 10 and the handle 12 mounted on the distal end. The snare exits out the distal end of the insertion rod, and as illustrated exits through the open lumen of the inner tube. The snare is illustrated in the position

within the inner tube, indicating that the surgeon has operated the snare to snare the suture ends, leaving the standing parts 43 and 44 outside the tube, and placing the welding portions 45 and 46 within the slot between the anvil 5 and the grasping face. A cutting blade 64 is disposed on the inner edge of the heating anvil, and provides an easily accessible blade for cutting the suture ends from the weld. The handle assembly 62 includes a pistol grip with a trigger switch 65 which is operated by the surgeon to apply electrical 10 energy to the anvil. An aperture 66 through the proximal end of the barrel 2 and handle assembly accommodates a boss 67 which protrudes from the inner tube 55. The boss is fixed to the inner tube, so that the surgeon may push the boss downward to rotate the inner tube, and thereby close the grasping boss 15 56 upon the matching grasping surface 57 to grasp and melt the suture as described above.

Figure 9 illustrates a step in the operation of the rotating suture welding device of Figure 8. Again, the surgeon has tensioned the sutures as desired by pulling the 20 appropriate amount of suture into the insertion rod and/or twisting the suture weld portions together. Tensioning can be accomplished by twisting the standing parts of the suture and/or drawing the suture proximally in to the rod until the desired degree of tension is obtained. The surgeon has drawn 25 the suture end into the insertion rod, and has trapped the welding portions of the suture between the anvil 56 and the grasping surface 57 by rotating the inner tube relative to the outer tube. Closure of the anvil upon the grasping surface also results in closure of the blade 64 on the suture, 30 severing the suture ends from the weld portions. (Again, the blade may be omitted where the suture used with the device is easily separable during welding, so the formation of the weld combined with light tension on the loose ends of the suture results in separation of the standing part from the loose

ends.) The weld is made such that the standing portion is of appropriate tension. After the weld is complete, the suture ends may be removed by pulling the snare rod proximally from the device.

5 Figure 10 illustrates the suture with a melttable component that may be used with the suture welding devices. The suture **74** is comprised of a melttable core **75** covered by a melt-resistant porous sheath **76**. Upon application of heat sufficient to melt the core, the core material flows through 10 the porous sheath and flows into core material flowing from adjoining suture segments. The temperature is maintained below the melting point of the sheath material, so that the sheath does not melt and remains in tact so that the suture does not break or separate upon melting of the core.

15 Preferably, the core melts at temperatures above body temperature but below temperatures which would significantly damage surrounding body tissue, such as the range of 40°C to 270°C (these temperatures can be achieved briefly in the heating elements without causing harmful heating in the 20 surrounding body tissue). The porous sheath preferably melts at temperatures above the temperature range in which the core melts, preferably being melt resistant to temperatures exceeding the melting temperature of the core material. The core may be made of the following materials: polyethylene 25 (120°C), polypropylene, nylon (200°C), polyethylene terephthalate (255-270°C), polyester, polytetrafluoroethylene (PTFE) and ePTFE (Teflon®), polyglycolic acid, polyvinylidene, polylecaprone, polydioxanone, polyglectin, polygalactin, polyvinylidene fluoride and many other thermoplastics. The 30 porous sheath may be made of the materials such as silk, cotton, catgut, stainless steel, polyamide, PTFE, fluorinated ethylene propylene (FEP), and any one of the above-mentioned core materials that melts at a higher temperature than the selected core material. It should be appreciated that many

combinations of core and porous sheath materials can be achieved.

Thus, while the preferred embodiments of the devices and methods have been described in reference to the environment in 5 which they were developed, they are merely illustrative of the principles of the inventions. Other embodiments and configurations may be devised without departing from the spirit of the inventions and the scope of the appended claims.

We claim:

1. A device for securing a plurality of segments of suture together, said device comprising:

an insertion rod having a distal and a proximal end, said
5 distal end adapted to be inserted into an endoscopic
work space;

a first means for grasping the suture, said first means
being capable of snaring loose suture ends within an
endoscopic work space, said first means for grasping
10 suture being slidably disposed within the insertion rod
and being operable from the proximal end of the
insertion rod to grasp at least one segment of suture;

a second means for grasping the suture, said second means
being disposed near the distal end of the insertion
15 rod, said second means including means for heating the
suture.

2. The device of claim 1 wherein the second means for
grasping comprises:

a pair of grasping jaws disposed on the distal tip of the
20 insertion rod, said jaws being operable from the
proximal end of the insertion rod to open and close
upon a segment of suture.

3. The device of claim 2 wherein the means for heating the
suture comprises a heating element disposed on at least one of
25 the grasping jaws.

4. The device of claim 1 wherein the second grasping means
comprises:

a rotatable member within the insertion rod, said rotatable member having a distal end and a proximal end;

5 a slot on the distal tip of the insertion rod, said slot defining a longitudinally aligned slot wall;

a grasping boss protruding radially from the rotatable member and outwardly into the slot in the insertion rod, said boss defining a grasping surface opposing the longitudinally aligned slot wall;

10 said rotatable member being rotatable from the proximal end of the insertion rod to bring the grasping surface of the boss into close proximity with the longitudinally aligned slot wall.

5. A device for securing a plurality of segments of suture
15 together, said device comprising:

a barrel having a distal and a proximal end;

a first means for grasping the suture, said first means being capable of snaring loose suture ends, said first means for grasping suture being slidably disposed within the barrel and being operable from the proximal end of the barrel to grasp at least one segment of suture;

20 a second means for grasping the suture, said second means being disposed near the distal end of the barrel, said second means including means for heating the suture.

25

6. The device of claim 5 wherein the second means for grasping comprises:

a pair of grasping jaws disposed on the distal tip of the barrel, said jaws being operable from the proximal end

of the barrel to open and close upon a segment of suture.

7. The device of claim 5 wherein the means for heating the suture comprises a heating element disposed on at least one of 5 the grasping jaws.

8. The device of claim 5 wherein the second grasping means comprises:

a rotatable member within the barrel, said rotatable member having a distal end and a proximal end;

10 a slot on the distal tip of the barrel, said slot defining a longitudinally aligned slot wall;

a grasping boss protruding radially from the rotatable member and outwardly into the slot in the insertion rod, said boss defining a grasping surface opposing the 15 longitudinally aligned slot wall;

said rotatable member being rotatable from the proximal end of the barrel to bring the grasping surface of the boss into close proximity with the longitudinally aligned slot wall.

20 9. A device for securing a plurality of segments of suture together, said device comprising:

a first rod having a distal end for insertion into the body and a proximal end, said first rod having a lumen extending from the distal end to the proximal end;

25 a plurality of opposing grasping jaws mounted on the distal end of the insertion rod, said grasping jaws being operable from the proximal end of the insertion rod to open and close upon the segments of suture;

a heating element on at least one of the grasping jaws,
said heating element operable to apply heat to segments
of suture;

a snare having a distal end and a proximal end, and
5 having a snaring structure capable of snaring a segment
of suture, said snare being disposed within the lumen
of the first rod, said snare rod extending proximally
within the first rod and being operable from the
proximal end of the first rod to slide longitudinally
10 and rotate within the lumen of the first rod;

said snare being extendable from the distal end of the
first rod, and being retractable into the distal end of
the first rod so that any suture segments ensnared in
the snare are drawn into proximity of the grasping
15 jaws.

1/4





FIG. 1

2/4

FIG. 3





FIG. 4



3/4

FIG. 5




FIG. 6





FIG. 7



4/4

FIG. 8




FIG. 9





FIG. 10



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US00/08902

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :A61B 17/04

US CL :606/144

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 606/27, 28, 113, 139, 144, 148

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST BRS

Srch Terms: suture, welding

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,713,908 A (JAMEEL et al.) 03 February 1998, whole document.	1-9
A	US 5,759,188 A (YOON) 02 June 1998, whole document.	1-9

Further documents are listed in the continuation of Box C. See patent family annex.

"A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier document published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"&"	document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

02 JUNE 2000

Date of mailing of the international search report

21 JUN 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

JULIAN W. WOO

Telephone No. (703) 308-0421