



- (51) **International Patent Classification:** Not classified
- (21) **International Application Number:** PCT/IB2014/060706
- (22) **International Filing Date:** 14 April 2014 (14.04.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:** 13/875,226 1 May 2013 (01.05.2013) US
- (71) **Applicant:** **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, New York 10504 (US).
- (71) **Applicants (for MG only):** **IBM UNITED KINGDOM LIMITED** [GB/GB]; PO Box 41, North Harbour, North Harbour, Portsmouth Hampshire PO6 3AU (GB). **IBM (CHINA) INVESTMENT COMPANY LIMITED** [CN/CN]; 25/F, Pangu Plaza, No.27, Central North 4th Ring Road, Chaoyang District, Beijing 100101 (CN).
- (72) **Inventors:** **BISKEBORN, Robert, Glenn**; IBM Corporation, MD LRCA/013, 650 Harry Road, Almaden Research Center, San Jose, California 95120-6099 (US). **LO, Calvin, Shyhjong**; IBM Corporation, MD LRC/013, 650 Harry Road, Almaden Research Center, San Jose, California

95120-6099 (US). **HERGET, Philipp**; IBM Corporation, 650 Harry Road, Almaden Research Center, San Jose, California 95120-6099 (US).

(74) **Agent:** **WILLIAMS, Julian**; IBM United Kingdom Limited, Intellectual Property Law, Hursley Park, Winchester Hampshire SO21 2JN (GB).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) **Title:** MAGNETIC HEAD AND SYSTEM HAVING OFFSET ARRAYS




FIG. 10B

(57) **Abstract:** In one general embodiment, an apparatus includes at least two modules, each of the modules having an array of transducers, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in an intended direction of tape travel thereacross; and a mechanism for orienting the modules about an axis orthogonal to the plane in which the arrays reside to control a transducer pitch presented to a tape.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, **Published:**
KM, ML, MR, NE, SN, TD, TG).

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

MAGNETIC HEAD AND SYSTEM HAVING OFFSET ARRAYS

BACKGROUND

[0001] The present invention relates to data storage systems, and more particularly, this invention relates to a magnetic head and system implementing the same, where the head has offset arrays.

[0002] In magnetic storage systems, data is read from and written onto magnetic recording media utilizing magnetic transducers. Data is written on the magnetic recording media by moving a magnetic recording transducer to a position over the media where the data is to be stored. The magnetic recording transducer then generates a magnetic field, which encodes the data into the magnetic media. Data is read from the media by similarly positioning the magnetic read transducer and then sensing the magnetic field of the magnetic media. Read and write operations may be independently synchronized with the movement of the media to ensure that the data can be read from and written to the desired location on the media.

[0003] An important and continuing goal in the data storage industry is that of increasing the density of data stored on a medium. For tape storage systems, that goal has led to increasing the track and linear bit density on recording tape, and decreasing the thickness of the magnetic tape medium. However, the development of small footprint, higher performance tape drive systems has created various problems in the design of a tape head assembly for use in such systems.

[0004] In a tape drive system, magnetic tape is moved over the surface of the tape head at high speed. Usually the tape head is designed to minimize the spacing between the head and the tape. The spacing between the magnetic head and the magnetic tape is crucial so that the recording gaps of the transducers, which are the source of the magnetic recording flux, are in near contact with the tape to effect writing sharp transitions, and so that the read element is in near contact with the tape to provide effective coupling of the magnetic field from the tape to the read element.

[0005] The quantity of data stored on a magnetic tape may be increased by increasing the number of data tracks across the tape. More tracks are made possible by reducing feature sizes of the readers and writers, such as by using thin-film fabrication techniques and MR sensors. However, for various reasons, the feature sizes of readers and writers cannot be arbitrarily reduced, and so factors such as lateral tape motion transients and tape lateral expansion and contraction (e.g., perpendicular to the direction of tape travel) must be balanced with reader/writer sizes that provide acceptable written tracks and readback signals. One issue limiting areal density is misregistration caused by tape lateral expansion and contraction. Tape width can vary by up to about 0.1% due to expansion and contraction caused by changes in humidity, tape tension, temperature, aging etc. This is often referred to as tape dimensional stability (TDS).

[0006] If the tape is written in one environment and then read back in another, the TDS may prevent the spacing of the tracks on the tape from precisely matching the spacing of the reading elements during readback. In current products, the change in track spacing due to TDS is small compared to the size of the written tracks and is part of the tracking budget that is considered when designing a product. As the tape capacity increases over time, tracks are becoming smaller and TDS is becoming an increasingly larger portion of the tracking budget and this is a limiting factor for growing areal density.

BRIEF SUMMARY

[0007] An apparatus according to one embodiment includes at least two modules, each of the modules having an array of transducers, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in an intended direction of tape travel thereacross when the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to the intended direction of tape travel thereacross; and a mechanism for orienting the modules to control a transducer pitch presented to a tape.

[0008] An apparatus according to another embodiment includes at least two modules, each of the modules having an array of transducers, a drive mechanism for passing a magnetic medium over the modules; a mechanism for orienting the modules to control a transducer pitch presented to a tape; and a controller configured to control the mechanism for orienting the modules based on a state of expansion of the tape, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to an intended direction of tape travel thereacross, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in the intended direction of tape travel thereacross.

[0009] A computer program product for orienting a head includes a computer readable storage medium having program code embodied therewith. The program code is readable/executable by a controller to: determine, by the controller, a desired pitch for transducers for reading and/or writing to a magnetic tape; and cause a mechanism to orient a head to achieve the desired pitch, the head having at least two opposing modules generally aligned with each other in an intended direction of tape travel thereacross, positions of the two modules being fixed relative to each other, each module having an array of the transducers. An axis of each array is defined between opposite ends thereof. The array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in the intended direction of tape travel thereacross when the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to the intended direction of tape travel.

[0010] Any of these embodiments may be implemented in a magnetic data storage system such as a tape drive system, which may include a magnetic head, a drive mechanism for passing a magnetic medium (e.g., recording tape) over the magnetic head, and a controller electrically coupled to the magnetic head.

[0011] Other aspects and embodiments of the present invention will become apparent from the following detailed description, which, when taken in conjunction with the drawings, illustrate by way of example the principles of the invention.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0012] Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings in which:

FIG. 1A is a schematic diagram of a simplified tape drive system according to one embodiment.

FIG. 1B is a schematic diagram of a tape cartridge according to one embodiment.

FIG. 2 illustrates a side view of a flat-lapped, bi-directional, two-module magnetic tape head according to one embodiment.

FIG. 2A is a tape bearing surface view taken from Line 2A of FIG. 2.

FIG. 2B is a detailed view taken from Circle 2B of FIG. 2A.

FIG. 2C is a detailed view of a partial tape bearing surface of a pair of modules.

FIG. 3 is a partial tape bearing surface view of a magnetic head having a write-read-write configuration.

FIG. 4 is a partial tape bearing surface view of a magnetic head having a read-write-read configuration.

FIG. 5 is a side view of a magnetic tape head with three modules according to one embodiment where the modules all generally lie along about parallel planes.

FIG. 6 is a side view of a magnetic tape head with three modules in a tangent (angled) configuration.

FIG. 7 is a side view of a magnetic tape head with three modules in an overwrap configuration.

FIGS. 8A-8C are partial top-down views of one module of a magnetic tape head according to one embodiment.

FIGS. 9A-9C are partial top-down views of one module of a magnetic tape head according to one embodiment.

FIGS. 10A is a partial top-down view of an apparatus with two modules according to one embodiment.

FIGS. 10B is a diagram of the system having the apparatus of FIG. 10A.

FIGS. 10C is a partial top-down view of an apparatus with two modules according to one embodiment.

FIGS. 10D is a partial top-down view of a system with multiple sets of modules according to one embodiment.

FIG. 11 is a flow chart of a method according to one embodiment.

FIG. 12 is a partial top-down view of a magnetic head with three modules according to one embodiment.

DETAILED DESCRIPTION

[0013] The following description is made for the purpose of illustrating the general principles of the present invention and is not meant to limit the inventive concepts claimed herein. Further, particular features described herein can be used in combination with other described features in each of the various possible combinations and permutations.

[0014] Unless otherwise specifically defined herein, all terms are to be given their broadest possible interpretation including meanings implied from the specification as well as meanings understood by those skilled in the art and/or as defined in dictionaries, treatises, etc.

[0015] It must also be noted that, as used in the specification and the appended claims, the singular forms "a," "an" and "the" include plural referents unless otherwise specified.

[0016] The following description discloses several preferred embodiments of magnetic storage systems, as well as operation and/or component parts thereof.

[0017] In one general embodiment, an apparatus includes at least two modules, each of the modules having an array of transducers, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the array of a first of the modules is offset from the array of a second of the modules in a first

direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in an intended direction of tape travel thereacross when the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to the intended direction of tape travel thereacross; and a mechanism for orienting the modules to control a transducer pitch presented to a tape.

[0018] In another general embodiment, an apparatus includes at least two modules, each of the modules having an array of transducers, a drive mechanism for passing a magnetic medium over the modules; a mechanism for orienting the modules to control a transducer pitch presented to a tape; and a controller configured to control the mechanism for orienting the modules based on a state of expansion of the tape, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to an intended direction of tape travel thereacross, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in the intended direction of tape travel thereacross.

[0019] In yet another general embodiment, a computer program product for orienting a head includes a computer readable storage medium having program code embodied therewith. The program code is readable/executable by a controller to: determine, by the controller, a desired pitch for transducers for reading and/or writing to a magnetic tape; and cause a mechanism to orient a head to achieve the desired pitch, the head having at least two opposing modules generally aligned with each other in an intended direction of tape travel thereacross, positions of the two modules being fixed relative to each other, each module having an array of the transducers. An axis of each array is defined between opposite ends thereof. The array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in the intended direction of tape travel thereacross when the axes are oriented at an

angle greater than 0.2° relative to a line oriented perpendicular to the intended direction of tape travel.

[0020] FIG. 1A illustrates a simplified tape drive **100** of a tape-based data storage system, which may be employed in the context of the present invention. While one specific implementation of a tape drive is shown in FIG. 1A, it should be noted that the embodiments described herein may be implemented in the context of any type of tape drive system.

[0021] As shown, a tape supply cartridge **120** and a take-up reel **121** are provided to support a tape **122**. One or more of the reels may form part of a removable cartridge and are not necessarily part of the system **100**. The tape drive, such as that illustrated in FIG. 1A, may further include drive motor(s) to drive the tape supply cartridge **120** and the take-up reel **121** to move the tape **122** over a tape head **126** of any type. Such head may include an array of readers, writers, or both.

[0022] Guides **125** guide the tape **122** across the tape head **126**. Such tape head **126** is in turn coupled to a controller **128** via a cable **130**. The controller **128**, may be or include a processor and/or any logic for controlling any subsystem of the drive **100**. For example, the controller **128** typically controls head functions such as servo following, data writing, data reading, etc. The controller **128** may operate under logic known in the art, as well as any logic disclosed herein. The controller **128** may be coupled to a memory **136** of any known type, which may store instructions executable by the controller **128**. Moreover, the controller **128** may be configured and/or programmable to perform or control some or all of the methodology presented herein. Thus, the controller may be considered configured to perform various operations by way of logic programmed into a chip; software, firmware, or other instructions being available to a processor; etc. and combinations thereof.

[0023] The cable **130** may include read/write circuits to transmit data to the head **126** to be recorded on the tape **122** and to receive data read by the head **126** from the tape **122**. An actuator **132** controls position of the head **126** relative to the tape **122**.

[0024] An interface **134** may also be provided for communication between the tape drive **100** and a host (integral or external) to send and receive the data and for controlling the operation of the tape drive **100** and communicating the status of the tape drive **100** to the host, all as will be understood by those of skill in the art.

[0025] FIG. **1B** illustrates an exemplary tape cartridge **150** according to one embodiment. Such tape cartridge **150** may be used with a system such as that shown in FIG. **1A**. As shown, the tape cartridge **150** includes a housing **152**, a tape **122** in the housing **152**, and a nonvolatile memory **156** coupled to the housing **152**. In some approaches, the nonvolatile memory **156** may be embedded inside the housing **152**, as shown in FIG. **1B**. In more approaches, the nonvolatile memory **156** may be attached to the inside or outside of the housing **152** without modification of the housing **152**. For example, the nonvolatile memory may be embedded in a self-adhesive label **154**. In one preferred embodiment, the nonvolatile memory **156** may be a Flash memory device, ROM device, etc., embedded into or coupled to the inside or outside of the tape cartridge **150**. The nonvolatile memory is accessible by the tape drive and the tape operating software (the driver software), and/or other device.

[0026] By way of example, FIG. **2** illustrates a side view of a flat-lapped, bi-directional, two-module magnetic tape head **200** which may be implemented in the context of the present invention. As shown, the head includes a pair of bases **202**, each equipped with a module **204**, and fixed at a small angle α with respect to each other. The bases may be “U-beams” that are adhesively coupled together. Each module **204** includes a substrate **204A** and a closure **204B** with a thin film portion, commonly referred to as a “gap” in which the readers and/or writers **206** are formed. In use, a tape **208** is moved over the modules **204** along a media (tape) bearing surface **209** in the manner shown for reading and writing data on the tape **208** using the readers and writers. The wrap angle θ of the tape **208** at edges going onto and exiting the flat media support surfaces **209** are usually between about 0.1 degree and about 5 degrees.

[0027] The substrates **204A** are typically constructed of a wear resistant material, such as a ceramic. The closures **204B** made of the same or similar ceramic as the substrates **204A**.

[0028] The readers and writers may be arranged in a piggyback or merged configuration. An illustrative piggybacked configuration comprises a (magnetically inductive) writer transducer on top of (or below) a (magnetically shielded) reader transducer (e.g., a magnetoresistive reader, etc.), wherein the poles of the writer and the shields of the reader are generally separated. An illustrative merged configuration comprises one reader shield in the same physical layer as one writer pole (hence, "merged"). The readers and writers may also be arranged in an interleaved configuration. Alternatively, each array of channels may be readers or writers only. Any of these arrays may contain one or more servo track readers for reading servo data on the medium.

[0029] FIG. 2A illustrates the tape bearing surface 209 of one of the modules 204 taken from Line 2A of FIG. 2. A representative tape 208 is shown in dashed lines. The module 204 is preferably long enough to be able to support the tape as the head steps between data bands.

[0030] In this example, the tape 208 includes 4 to 22 data bands, e.g., with 8 data bands and 9 servo tracks 210, as shown in FIG. 2A on a one-half inch wide tape 208. The data bands are defined between servo tracks 210. Each data band may include a number of data tracks, for example 1024 data tracks (not shown). During read/write operations, the readers and/or writers 206 are positioned to specific track positions within one of the data bands. Outer readers, sometimes called servo readers, read the servo tracks 210. The servo signals are in turn used to keep the readers and/or writers 206 aligned with a particular set of tracks during the read/write operations.

[0031] FIG. 2B depicts a plurality of readers and/or writers 206 formed in a gap 218 on the module 204 in Circle 2B of FIG. 2A. As shown, the array of readers and writers 206 includes, for example, 16 writers 214, 16 readers 216 and two servo readers 212, though the number of elements may vary. Illustrative embodiments include 8, 16, 32, 40, and 64 active readers and/or writers 206 per array, and alternatively interleaved designs having odd numbers of reader or writers such as 17, 25, 33, etc. An illustrative embodiment includes 32 readers per array and/or 32 writers per array, where the actual number of transducer elements could be greater, e.g., 33, 34, etc. This allows the tape to travel more slowly, thereby

reducing speed-induced tracking and mechanical difficulties and/or execute fewer “wraps” to fill or read the tape. While the readers and writers may be arranged in a piggyback configuration as shown in FIG. **2B**, the readers **216** and writers **214** may also be arranged in an interleaved configuration. Alternatively, each array of readers and/or writers **206** may be readers or writers only, and the arrays may contain one or more servo readers **212**. As noted by considering FIGS. **2** and **2A-B** together, each module **204** may include a complementary set of readers and/or writers **206** for such things as bi-directional reading and writing, read-while-write capability, backward compatibility, etc.

[0032] FIG. **2C** shows a partial tape bearing surface view of complimentary modules of a magnetic tape head **200** according to one embodiment. In this embodiment, each module has a plurality of read/write (R/W) pairs in a piggyback configuration formed on a common substrate **204A** and an optional electrically insulative layer **236**. The writers, exemplified by the write head **214** and the readers, exemplified by the read head **216**, are aligned parallel to a direction of travel of a tape medium thereacross to form an R/W pair, exemplified by the R/W pair **222**.

[0033] Several R/W pairs **222** may be present, such as 8, 16, 32 pairs, etc. The R/W pairs **222** as shown are linearly aligned in a direction generally perpendicular to a direction of tape travel thereacross. However, the pairs may also be aligned diagonally, etc. Servo readers **212** are positioned on the outside of the array of R/W pairs, the function of which is well known.

[0034] Generally, the magnetic tape medium moves in either a forward or reverse direction as indicated by arrow **220**. The magnetic tape medium and head assembly **200** operate in a transducing relationship in the manner well-known in the art. The piggybacked MR head assembly **200** includes two thin-film modules **224** and **226** of generally identical construction.

[0035] Modules **224** and **226** are joined together with a space present between closures **204B** thereof (partially shown) to form a single physical unit to provide read-while-write capability by activating the writer of the leading module and reader of the trailing module aligned with the writer of the leading module parallel to the direction of tape travel relative

thereto. When a module **224**, **226** of a piggyback head **200** is constructed, layers are formed in the gap **218** created above an electrically conductive substrate **204A** (partially shown), e.g., of AlTiC, in generally the following order for the R/W pairs **222**: an insulating layer **236**, a first shield **232** typically of an iron alloy such as NiFe (–), CZT or Al-Fe-Si (Sendust), a sensor **234** for sensing a data track on a magnetic medium, a second shield **238** typically of a nickel-iron alloy (e.g., ~80/20 at% NiFe, also known as permalloy), first and second writer pole tips **228**, **230**, and a coil (not shown). The sensor may be of any known type, including those based on MR, GMR, AMR, tunneling magnetoresistance (TMR), etc.

[0036] The first and second writer poles **228**, **230** may be fabricated from high magnetic moment materials such as ~45/55 NiFe. Note that these materials are provided by way of example only, and other materials may be used. Additional layers such as insulation between the shields and/or pole tips and an insulation layer surrounding the sensor may be present. Illustrative materials for the insulation include alumina and other oxides, insulative polymers, etc.

[0037] The configuration of the tape head **126** according to one embodiment includes multiple modules, preferably three or more. In a write-read-write (W-R-W) head, outer modules for writing flank one or more inner modules for reading. Referring to FIG. 3, depicting a W-R-W configuration, the outer modules **252**, **256** each include one or more arrays of writers **260**. The inner module **254** of FIG. 3 includes one or more arrays of readers **258** in a similar configuration. Variations of a multi-module head include a R-W-R head (FIG. 4), a R-R-W head, a W-W-R head, etc. In yet other variations, one or more of the modules may have read/write pairs of transducers. Moreover, more than three modules may be present. In further approaches, two outer modules may flank two or more inner modules, e.g., in a W-R-R-W, a R-W-W-R arrangement, etc. For simplicity, a W-R-W head is used primarily herein to exemplify embodiments of the present invention. One skilled in the art apprised with the teachings herein will appreciate how permutations of the present invention would apply to configurations other than a W-R-W configuration.

[0038] FIG. 5 illustrates a magnetic head **126** according to one embodiment of the present invention that includes first, second and third modules **302**, **304**, **306** each having a

tape bearing surface **308**, **310**, **312** respectively, which may be flat, contoured, etc. Note that while the term “tape bearing surface” appears to imply that the surface facing the tape **315** is in physical contact with the tape bearing surface, this is not necessarily the case. Rather, only a portion of the tape may be in contact with the tape bearing surface, constantly or intermittently, with other portions of the tape riding (or “flying”) above the tape bearing surface on a layer of air, sometimes referred to as an “air bearing”. The first module **302** will be referred to as the “leading” module as it is the first module encountered by the tape in a three module design for tape moving in the indicated direction. The third module **306** will be referred to as the “trailing” module. The trailing module follows the middle module and is the last module seen by the tape in a three module design. The leading and trailing modules **302**, **306** are referred to collectively as outer modules. Also note that the outer modules **302**, **306** will alternate as leading modules, depending on the direction of travel of the tape **315**.

[0039] In one embodiment, the tape bearing surfaces **308**, **310**, **312** of the first, second and third modules **302**, **304**, **306** lie on about parallel planes (which is meant to include parallel and nearly parallel planes, e.g., between parallel and tangential as in FIG. 6), and the tape bearing surface **310** of the second module **304** is above the tape bearing surfaces **308**, **312** of the first and third modules **302**, **306**. As described below, this has the effect of creating the desired wrap angle α_2 of the tape relative to the tape bearing surface **310** of the second module **304**.

[0040] Where the tape bearing surfaces **308**, **310**, **312** lie along parallel or nearly parallel yet offset planes, intuitively, the tape should peel off of the tape bearing surface **308** of the leading module **302**. However, the vacuum created by the skiving edge **318** of the leading module **302** has been found by experimentation to be sufficient to keep the tape adhered to the tape bearing surface **308** of the leading module **302**. The trailing edge **320** of the leading module **302** (the end from which the tape leaves the leading module **302**) is the approximate reference point which defines the wrap angle α_2 over the tape bearing surface **310** of the second module **304**. The tape stays in close proximity to the tape bearing surface until close to the trailing edge **320** of the leading module **302**. Accordingly, read and/or write elements **322** may be located near the trailing edges of the outer modules **302**, **306**. These embodiments are particularly adapted for write-read-write applications.

[0041] A benefit of this and other embodiments described herein is that, because the outer modules **302**, **306** are fixed at a determined offset from the second module **304**, the inner wrap angle α_2 is fixed when the modules **302**, **304**, **306** are coupled together or are otherwise fixed into a head. The inner wrap angle α_2 is approximately $\tan^{-1}(\delta/W)$ where δ is the height difference between the planes of the tape bearing surfaces **308**, **310** and W is the width between the opposing ends of the tape bearing surfaces **308**, **310**. An illustrative inner wrap angle α_2 is in a range of about 0.5° to about 1.1° , though can be any angle required by the design.

[0042] Beneficially, the inner wrap angle α_2 may be set slightly less on the side of the module **304** receiving the tape (leading edge) than the inner wrap angle α_3 on the trailing edge, as the tape **315** rides above the trailing module **306**. This difference is generally beneficial as a smaller α_3 tends to oppose what has heretofore been a steeper exiting effective wrap angle.

[0043] Note that the tape bearing surfaces **308**, **312** of the outer modules **302**, **306** are positioned to achieve a negative wrap angle at the trailing edge **320** of the leading module **302**. This is generally beneficial in helping to reduce friction due to contact with the trailing edge **320**, provided that proper consideration is given to the location of the crowbar region that forms in the tape where it peels off the head. This negative wrap angle also reduces flutter and scrubbing damage to the elements on the leading module **302**. Further, at the trailing module **306**, the tape **315** flies over the tape bearing surface **312** so there is virtually no wear on the elements when tape is moving in this direction. Particularly, the tape **315** entrains air and so will not significantly ride on the tape bearing surface **312** of the third module **306** (some contact may occur). This is permissible, because the leading module **302** is writing while the trailing module **306** is idle.

[0044] Writing and reading functions are performed by different modules at any given time. In one embodiment, the second module **304** includes a plurality of data and optional servo readers **331** and no writers. The first and third modules **302**, **306** include a plurality of writers **322** and no readers, with the exception that the outer modules **302**, **306** may include optional servo readers. The servo readers may be used to position the head during reading

and/or writing operations. The servo reader(s) on each module are typically located towards the end of the array of readers or writers.

[0045] By having only readers or side by side writers and servo readers in the gap between the substrate and closure, the gap length can be substantially reduced. Typical heads have piggybacked readers and writers, where the writer is formed above each reader. A typical gap is 25-35 microns. However, irregularities on the tape may tend to droop into the gap and create gap erosion. Thus, the smaller the gap is the better. The smaller gap enabled herein exhibits fewer wear related problems.

[0046] In some embodiments, the second module **304** has a closure, while the first and third modules **302**, **306** do not have a closure. Where there is no closure, preferably a hard coating is added to the module. One preferred coating is diamond-like carbon (DLC).

[0047] In the embodiment shown in FIG. 5, the first, second, and third modules **302**, **304**, **306** each have a closure **332**, **334**, **336**, which extends the tape bearing surface of the associated module, thereby effectively positioning the read/write elements away from the edge of the tape bearing surface. The closure **332** on the second module **304** can be a ceramic closure of a type typically found on tape heads. The closures **334**, **336** of the first and third modules **302**, **306**, however, may be shorter than the closure **332** of the second module **304** as measured parallel to a direction of tape travel over the respective module. This enables positioning the modules closer together. One way to produce shorter closures **334**, **336** is to lap the standard ceramic closures of the second module **304** an additional amount. Another way is to plate or deposit thin film closures above the elements during thin film processing. For example, a thin film closure of a hard material such as Sendust or nickel-iron alloy (e.g., 45/55) can be formed on the module.

[0048] With reduced-thickness ceramic or thin film closures **334**, **336** or no closures on the outer modules **302**, **306**, the write-to-read gap spacing can be reduced to less than about 1 mm, e.g., about 0.75 mm, or 50% less than standard LTO tape head spacing. The open space between the modules **302**, **304**, **306** can still be set to approximately 0.5 to 0.6 mm, which in some embodiments is ideal for stabilizing tape motion over the second module **304**.

[0049] Depending on tape tension and stiffness, it may be desirable to angle the tape bearing surfaces of the outer modules relative to the tape bearing surface of the second module. FIG. 6 illustrates an embodiment where the modules **302**, **304**, **306** are in a tangent or nearly tangent (angled) configuration. Particularly, the tape bearing surfaces of the outer modules **302**, **306** are about parallel to the tape at the desired wrap angle α_2 of the second module **304**. In other words, the planes of the tape bearing surfaces **308**, **312** of the outer modules **302**, **306** are oriented at about the desired wrap angle α_2 of the tape **315** relative to the second module **304**. The tape will also pop off of the trailing module **306** in this embodiment, thereby reducing wear on the elements in the trailing module **306**. These embodiments are particularly useful for write-read-write applications. Additional aspects of these embodiments are similar to those given above.

[0050] Typically, the tape wrap angles may be set about midway between the embodiments shown in FIGS. 5 and 6.

[0051] FIG. 7 illustrates an embodiment where the modules **302**, **304**, **306** are in an overwrap configuration. Particularly, the tape bearing surfaces **308**, **312** of the outer modules **302**, **306** are angled slightly more than the tape **315** when set at the desired wrap angle α_2 relative to the second module **304**. In this embodiment, the tape does not pop off of the trailing module, allowing it to be used for writing or reading. Accordingly, the leading and middle modules can both perform reading and/or writing functions while the trailing module can read any just-written data. Thus, these embodiments are preferred for write-read-write, read-write-read, and write-write-read applications. In the latter embodiments, closures should be wider than the tape canopies for ensuring read capability. The wider closures will force a wider gap-to-gap separation. Therefore a preferred embodiment has a write-read-write configuration, which may use shortened closures that thus allow closer gap-to-gap separation.

[0052] Additional aspects of the embodiments shown in FIGS. 6 and 7 are similar to those given above.

[0053] A 32 channel version of a multi-module head **126** may use cables **350** having leads on the same pitch as current 16 channel piggyback LTO modules, or alternatively the connections on the module may be organ-keyboarded for a 50% reduction in cable span. Over-under, writing pair unshielded cables can be used for the writers, which may have integrated servo readers.

[0054] The outer wrap angles α_1 may be set in the drive, such as by guides of any type known in the art, such as adjustable rollers, slides, etc. For example, rollers having an offset axis may be used to set the wrap angles. The offset axis creates an orbital arc of rotation, allowing precise alignment of the wrap angle α_1 .

[0055] To assemble any of the embodiments described above, conventional u-beam assembly can be used. Accordingly, the mass of the resultant head can be maintained or even reduced relative to heads of previous generations. In other approaches, the modules may be constructed as a unitary body. Those skilled in the art, armed with the present teachings, will appreciate that other known methods of manufacturing such heads may be adapted for use in constructing such heads.

[0056] As noted above, tape lateral expansion and contraction present many challenges to increasing data track density on conventional products. Conventional products have attempted to compensate for tape lateral expansion and contraction by controlling tape width by tension and improving the characteristics of the media itself. However, these methods fail to fully cancel the tape lateral expansion and contraction, and actually lead to other problems, including tape stretch and media cost increases, respectively.

[0057] FIGS. **8A-8C** are intended to depict the effect of tape lateral expansion and contraction on transducer arrays position relative thereto, and are in no way intended to limit the invention. FIG. **8A** depicts a module **800** relative to the tape **802**, where the tape has a nominal width. As shown, the transducers **804** are favorably aligned with the data tracks **806** on the tape **802**. However, FIG. **8B** illustrates the effect of tape lateral contraction. As shown, contraction of the tape causes the data tracks to contract as well, and the outermost transducers **808** are positioned along the outer edges of the outer data tracks as a result.

Moreover, FIG. 8C depicts the effect of tape lateral expansion. Here expansion of the tape causes the data tracks to move farther apart, and the outermost transducers 808 are positioned along the inner edges of the outer data tracks as a result. If the tape lateral contraction is greater than that shown in FIG. 8B, or the tape lateral expansion is greater than that shown in FIG. 8C, the outermost transducers 808 will cross onto adjacent tracks, thereby causing the adjacent tracks to be overwritten during a writing operation and/or resulting in readback of the wrong track during a readback operation. Moreover, running effects, such as tape skew and lateral shifting may exacerbate such problems, particularly for tape having shingled data tracks.

[0058] Thus, it would be desirable to develop a tape drive system able to read and/or write tracks onto the tape in the proper position, regardless of the extent of tape lateral expansion and/or contraction at any given time. Various embodiments described and/or suggested herein overcome the foregoing challenges of conventional products, by orienting at least two modules of a tape drive system, such as by rotating, pivoting and/or tilting, thereby selectively altering the pitch of the transducers in their arrays, as will soon become apparent.

[0059] By selectively orienting a module, the pitch of the transducers on the module is thereby altered, preferably aligning the transducers with the tracks on a tape for a given tape lateral expansion and/or contraction. Tape contraction (shrinkage) can be dealt with by orienting a nominally non-offset head, but tape expansion (dilation) cannot. Thus, to accommodate both shrinkage and dilation about a “nominal,” the head must be statically positioned at a nominal angle of at least approximately 0.2° as will be explained below. Thereafter, smaller angular adjustments (e.g., about 1° or lower, but could be more) may be made to the already-oriented module in order to compensate for any variation of the tape lateral expansion and/or contraction, thereby keeping the transducers aligned with tracks on the tape.

[0060] FIGS. 9A-9C illustrate representational views of the effects of orienting a module having transducer arrays. It should be noted that the angles of orientation illustrated in FIGS.

9A-9C are an exaggeration (e.g., larger than would typically be observed), and are in no way intended to limit the invention.

[0061] Referring to FIG. **9A**, the module **900** is shown relative to the tape **902**, where the tape has a nominal width. As illustrated, the module **900** is oriented at an angle θ_{nom} such that the transducers **904** are favorably aligned with the data tracks **906** on the tape **902**. However, when the tape **902** experiences tape lateral contraction and/or expansion, the data tracks **906** on the tape contract and/or expand as well. As a result, the transducers on the module are no longer favorably aligned with the data tracks **906** on the tape **902**.

[0062] In FIG. **9B**, the tape **902** has experienced tape lateral contraction. Therefore, in a manner exemplified by FIG. **8B**, the transducers **904** on the module **900** of FIG. **9B** would no longer be favorably aligned with the data tracks **906** on the tape **902** if no adjustment were made. However, as alluded to above, smaller angular adjustments may be made to the already-oriented module **900** in order to compensate for tape lateral contraction. Therefore, referring again to FIG. **9B**, the angle of orientation $>\theta_{nom}$ of the module **900** is further positioned at an angle greater than θ_{nom} . By increasing the angle $>\theta_{nom}$ the effective width w_2 of the array of transducers decreases from the effective width w_1 illustrated in FIG. **9A**. This also translates to a reduction in the effective pitch between the transducers, thereby realigning the transducers along the contracted data tracks **906** on the tape **902** as shown in FIG. **9B**.

[0063] On the other hand, when the tape experiences tape lateral expansion, the data tracks on the tape expand as well. As a result, the transducers on the module would no longer be favorably aligned with the data tracks on the tape if no adjustments were made. With reference to FIG. **9C**, the tape **902** has experienced tape lateral expansion. As a result, further angular adjustments may be made to the angle of orientation of the module in order to compensate for the tape lateral expansion. Therefore, referring again to FIG. **9C**, the angle of orientation $<\theta_{nom}$ of the module **900** is reduced to an angle less than θ_{nom} . By decreasing the angle of orientation $<\theta_{nom}$ the effective width w_3 of the array of transducers **904** increases from the effective width w_1 illustrated in FIG. **9A**. Moreover, reducing the effective width of the array of transducers **904** also causes the effective pitch between the

transducers to be reduced, thereby realigning the transducers along the data tracks **906** on the tape **902**.

[0064] In a preferred approach, magnetic tape systems have two or more modules, each having an array of transducers, typically in a row. Depending on the desired embodiment, the additional rows of transducers may allow the system to read verify during the write process, but is not limited thereto. As mentioned above, the foregoing conventional challenges may be overcome, e.g., by rotating a given module about an axis orthogonal to the plane in which its array resides (e.g., parallel to the plane of the tape bearing surface), thereby selectively altering the pitch of the transducers in the array.

[0065] By providing a system that compensates for tape lateral expansion and/or contraction, various embodiments enable use of wider readers, resulting in a better signal to noise ratio (SNR), and/or smaller data tracks, resulting in a higher capacity per unit area of the media.

[0066] FIGS. **10A-10B** depict an apparatus **1000** for compensating for tape lateral expansion and/or contraction, in accordance with one embodiment. As an option, the present system **1000** may be implemented in conjunction with features from any other embodiment listed herein, such as those described with reference to the other FIGS. Of course, however, system **1000** and others presented herein may be used in various applications and/or in permutations which may or may not be specifically described in the illustrative embodiments listed herein. Further, the system **1000** presented herein may be used in any desired environment.

[0067] Referring to FIGS. **10A-10B**, the system **1000** includes modules **1002**, **1004**, each of which have an array **1006**, **1008** of transducers **1010**. The modules **1002**, **1004**, are preferably fixed relative to each other. In view of the present description, “fixed” is intended to mean constrained from a directional movement relative to each other such that the arrays of each maintain a fixed position relative to each other. According to various approaches, the modules may be fixed relative to each other by using rods, fasteners, adhesives, cables, wire, etc. Moreover, according to different embodiments, the modules are preferably fixed relative

to each other prior to being installed in the system **1000**, head, etc. depending on the desired embodiment. However, the modules are preferably selectively orientable (e.g., tiltable and/or rotatable) as a single structure about a pivot point while remaining fixed relative to each other, as will soon become apparent.

[0068] With continued reference to FIGS. **10A-10B**, the modules **1002**, **1004**, are preferably fixed such that the axes **1012**, **1013** of the arrays **1006**, **1008** are oriented about parallel to each other, respectively. As illustrated in FIGS. **10A-10B**, the axes **1012**, **1013** of each array of transducers are defined by the dashed lines that lie between opposite ends thereof, e.g., positioned farthest apart.

[0069] Referring now to FIG. **10A**, the array **1006** of a first module **1002** is offset from the array **1008** of a second module **1004** in a first direction parallel to the axis **1013** of the array **1008** of the second module **1004**. The modules **1002**, **1004** are also set to a nominal angle in the drive so that the transducers of the arrays are aligned along the data tracks **906** on a tape **902** having nominal tape lateral expansion.

[0070] With continued reference to FIG. **10A**, the arrays **1006**, **1008** of the transducers **1010** of the first and second modules are preferably offset such that the transducers **1010** of the first module **1002** are about aligned with the transducers **1010** of the second module **1004** in a direction **1020** of tape travel thereacross when the axes are oriented at an angle ϕ between greater than about 0.05° and about 45° . Preferably, the angle ϕ is between greater than about 0.2° and about 10° , and ideally between greater than about 0.25° and about 5° , relative to a line **1022** oriented perpendicular to the direction **1020** of tape travel.

[0071] In addition, the inventors have surprisingly and unexpectedly found that the various embodiments described below, and having the angle ϕ in the range between greater than about 0.2° and about 10° , enable writing and reading that does not steer the tape or cause media damage over the life of the tape. For example, the inventors expected the skiving edges of the modules to steer the tape laterally.

[0072] Angles of orientation greater than within the specified range (e.g., greater than about 10°) are undesirable as the higher angles cause steering of the tape when used. However, as described above, the angles of orientation within the specified range unexpectedly and unforeseeably did not result in steering of the tape. Moreover, it is more difficult to distinguish between tape lateral expansion and/or contraction and skew when angles of orientation of the modules is greater than within the specified range. This may cause difficulties when matching the dimensional conditions of the tape and/or orientation of the modules of the current operation to that of the previous operation (explained in further detail below). It should also be noted that the angle of orientation ϕ illustrated in FIG. 10A is exaggerated (e.g., larger than within the desired range), and is in no way intended to limit the invention.

[0073] Depending on the desired embodiment, the modules themselves may be offset to effect the shifting of the transducer arrays, e.g., as shown by the offset (**offset**) in FIG. 10B. Alternatively, the transducer arrays may be positioned on the respective module in a specified position to effect the offset while the modules themselves are not offset in the drive; or combinations thereof.

[0074] With continued reference to FIG. 10B, the system **1000** includes a mechanism **1014**, such as a tape dimensional instability compensation mechanism, for orienting the modules to control a transducer pitch presented to a tape. The tape dimensional instability compensation mechanism **1014** preferably allows for the orienting of the modules to be done while the modules are reading and/or writing. The tape dimensional instability compensation mechanism **1014** may be any known mechanism suitable for orienting the modules. Illustrative tape dimensional instability compensation mechanisms **1014** include worm screws, voice coil actuators, thermal actuators, piezoelectric actuators, etc.

[0075] A controller **1016** in one approach is configured to control the tape dimensional instability compensation mechanism **1014** based on a readback signal of the tape, e.g., servo signals, data signals, a combination of both, etc. In another approach, the dimensional conditions of the tape and/or orientation of the modules when the tape was written may be retrieved e.g., from a database, cartridge memory, etc., and the orientation may be set based

thereon to about match the transducer pitch of the current operation to that of the previous operation.

[0076] In various approaches, additional logic, computer code, commands, etc., or combinations thereof, may be used to control the tape dimensional instability compensation mechanism **1014** for adjusting the orientation of the modules based on a skew of the tape. Moreover, any of the embodiments described and/or suggested herein may be combined with various functional methods, depending on the desired embodiment.

[0077] FIG. **10C** depicts a variation of an apparatus as shown in FIG. **10A**, and like elements are numbered the same in both FIGS. Referring to FIG. **10C**, a spacer member **1050** extends between tape bearing surfaces of the modules. The spacer member **1050** may be recessed from a plane of the tape bearing surfaces, but is preferably coplanar therewith and/or otherwise forms a portion of the overall tape bearing surface of the head.

[0078] In one approach, the spacer member **1050** includes a magnetic shield **1052** for magnetically shielding the array of transducers from the second array of transducers. Such magnetic shield may be formed of any suitable material known in the art, such as NiFe, CoFe, etc. The magnetic shield may extend from the tape bearing surface, or some point therebelow, in a height direction (into the tape bearing surface), preferably for a distance that provides the desired shielding effect. For example, the shield may have a height similar to that of shields of the transducers.

[0079] FIG. **10D** depicts an alternate embodiment, similar to that of FIG. **10B**, but having two sets of modules, where each set may include two or more modules. Each set of modules is preferably independently orientable to set the angle of orientation. Each set may also be independently positionable for track following.

[0080] In one approach, the outer modules of each set may be configured for writing, and the inner modules configured for reading. Thus, in one illustrative use case, the writers on the outer module of one set may write while the readers of an inner module of the second set may read back the just-written track. In another illustrative use case, the writers on the

outer module of one set may write while the readers of an inner module of the same set may read back the just-written track.

[0081] FIG. 11 depicts a method **1100** for orienting modules having transducers, in accordance with one embodiment. Such method **1100** may be implemented by the controller of FIG. 10B. As an option, the present method **1100** may be implemented in conjunction with features from any other embodiment listed herein, such as those described with reference to the other FIGS. Of course, however, such method **1100** and others presented herein may be used in various applications and/or in permutations which may or may not be specifically described in the illustrative embodiments listed herein. Further, the method **1100** presented herein may be used in any desired environment.

[0082] Referring now to FIG. 11, the method **1100** includes determining a desired pitch for transducers for reading and/or writing to a magnetic tape as illustrated in operation **1102**. In one approach, the desired pitch may be determined by the state of the tape. An exemplary mechanism for establishing the proper pitch is to use the timing interval read by two servo readers to determine the state of the tape, e.g., contracted, expanded or nominal. Although a preferred mode is to use servo data, this is not absolutely required. Thus, it may be desirable to determine the state of the tape, e.g., by incorporating any of the approaches described and/or suggested herein and/or known processes, when determining the desired pitch. However, according to other approaches, the pitch may be determined using any approach described and/or suggested herein, or combinations thereof.

[0083] Method **1100** further includes orienting a head to achieve the desired pitch, the head having at least two opposing modules generally aligned with each other in a(n intended) direction of tape travel thereacross, positions of the two modules being fixed relative to each other, each module having an array of the transducers, where an axis of each array is defined between opposite ends thereof, where the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in a direction of tape travel thereacross when the

axes are oriented at an angle between greater than 0.2° and about 10° relative to a line oriented perpendicular to the direction of tape travel. See operation **1104**.

[0084] In another approach, steps **1102** and **1104** may be performed concurrently. For example, in one embodiment the proper transducer pitch may be based on data signals. One way to implement this is by first setting the transducer pitch at a nominal value by selecting a nominal angle, and then adjusting the orientation thereof to obtain a better readback quality across the read channels. The quality may be determined for example by finding the lowest error rate, best signal to noise level, etc.

[0085] As an option, the system may continue or periodically monitor the appropriate signals and adjust the orientation. Adjustments can be performed any time, such as during an initialization period prior to reading or writing user data, during readback or writing operations, etc.

[0086] Although two modules **1002**, **1004** are illustrated in FIGS. **10A-10B**, in other approaches, a system may include any number of modules e.g., at least two, at least three, at least four, a plurality, etc. depending on the desired embodiment. Referring to the illustrative embodiment depicted in FIG. **12**, which may be considered a modification of system **1000** of FIG. **10A**, the system **1200** shown may include a third module **1202** positioned between the first and second modules **1002**, **1004**. As shown, the array of transducers of the third module **1202** is preferably offset from the array of the first module **1002** in a first direction **1204**. Moreover, the extent of the offset t_1 of the array of the third module **1202** relative to the array of the first module **1002** is less than an extent of the offset t_2 of the array of the second module **1004** relative to the array of the first module **1002**.

[0087] According to different approaches, the first second and/or third modules **1002**, **1004**, **1202** may be used for data writing and/or data reading, depending on the desired embodiment. Thus, the system **1200** may serve as a write-read-write (WRW) device if the first and second modules **1002**, **1004** are designed for at least data writing and the third module **1202** is designed for at least data reading. As an option, the first and second modules

1002, **1004** may be designed for data writing and not for data reading, and/or the third module **1202** maybe designed for data reading and not for data writing.

[0088] In another approach, the system **1200** may serve as a read-write-read (RWR) device if the first and second modules **1002**, **1004** are designed for at least data reading and optionally not for data writing, while the third module **1202** is designed for at least data writing and optionally not for data reading. However, this is in no way meant to limit the invention; according to various other approaches, a third, fourth, fifth, etc. module may be positioned with any orientation relative to other modules of the system, depending on the desired embodiment.

[0089] With continued reference to FIG. **12**, according to one approach, the angle of orientation ϕ of the modules **1002**, **1202**, **1004** and distance y between the arrays may be used to calculate the offset x . As illustrated, the offset x is between the arrays of transducers of the modules in a direction parallel to their axes **1012**, **1206**, which may be calculated using Equation 1.

$$\tan(\phi) = x/y \quad \text{Equation 1}$$

[0090] Equation 1 can be rewritten into Equation 2.

$$y (\tan(\phi)) = x \quad \text{Equation 2}$$

[0091] Other known methods of calculating and/or assigning the offset x and distance y between the arrays of any of the modules may be used in other embodiments.

It will be clear that the various features of the foregoing systems and/or methodologies may be combined in any way, creating a plurality of combinations from the descriptions presented above.

[0092] As will be appreciated by one skilled in the art, aspects of the present invention may be embodied as a system, method or computer program product. Accordingly, aspects of the present invention may take the form of an entirely hardware embodiment, an entirely

software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as “logic,” a “circuit,” “module,” or “system.” Furthermore, aspects of the present invention may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

[0093] Any combination of one or more computer readable medium(s) may be utilized. The computer readable medium may be a computer readable signal medium or a non-transitory computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the non-transitory computer readable storage medium include the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a portable compact disc read-only memory (e.g., CD-ROM), a Blu-ray disc read-only memory (BD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a non-transitory computer readable storage medium may be any tangible medium that is capable of containing, or storing a program or application for use by or in connection with an instruction execution system, apparatus, or device.

[0094] A computer readable signal medium may include a propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electro-magnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium that is not a non-transitory computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device, such as an electrical connection having one or more wires, an optical fibre, etc.

[0095] Program code embodied on a computer readable medium may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fibre cable, RF, etc., or any suitable combination of the foregoing.

[0096] Computer program code for carrying out operations for aspects of the present invention may be written in any combination of one or more programming languages, including an object oriented programming language such as Java, Smalltalk, C++ or the like and conventional procedural programming languages, such as the "C" programming language or similar programming languages. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer, for example through the Internet using an Internet Service Provider (ISP).

[0097] Aspects of the present invention are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

[0098] These computer program instructions may also be stored in a computer readable medium that can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions stored in the computer

readable medium produce an article of manufacture including instructions which implement the function/act specified in the flowchart and/or block diagram block or blocks.

[0099] The computer program instructions may also be loaded onto a computer, other programmable data processing apparatus, or other devices to cause a series of operational steps to be performed on the computer, other programmable apparatus or other devices to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart(s) and/or block diagram block or blocks.

[00100] It will be further appreciated that embodiments of the present invention may be provided in the form of a service deployed on behalf of a customer.

[00101] While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of an embodiment of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

CLAIMS

1. An apparatus, comprising:
at least two modules, each of the modules having an array of transducers, wherein the at least two modules are fixed relative to each other, wherein an axis of each array is defined between opposite ends thereof, wherein the axes of the arrays are oriented about parallel to each other, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in an intended direction of tape travel thereacross when the axes are oriented at an angle greater than 0.2° relative to a line oriented perpendicular to the intended direction of tape travel thereacross; and
a mechanism for orienting the modules to control a transducer pitch presented to a tape.
2. An apparatus as recited in claim 1, wherein only two modules are present.
3. An apparatus as recited in claim 1, wherein a third one of the modules is positioned between the first and second modules, wherein the array of the third module is offset from the array of the first module in the first direction, wherein an extent of the offset of the array of the third module relative to the array of the first module is less than an extent of the offset of the array of the second module relative to the array of the first module.
4. An apparatus as recited in claim 3, wherein the first and second modules are configured for data writing and are not configured for data reading, wherein the third module is configured for data reading and is not configured for data writing.
5. An apparatus as recited in claim 3, wherein the first and second modules are configured for data reading and are not configured for data writing, wherein the third module is configured for data writing and is not configured for data reading.

6. An apparatus as recited in claim 1, further comprising a controller configured to control the mechanism for orienting the modules based on a state of expansion of the tape.
7. An apparatus as recited in claim 1, further comprising a controller configured to control the mechanism for orienting the modules based on a skew of the tape.
8. An apparatus as recited in claim 1, further comprising a drive mechanism for passing a magnetic medium over the modules.
9. An apparatus as recited in claim 1, further comprising a spacer member extending between tape bearing surfaces of an adjacent pair of the at least two modules, the spacer member including a magnetic shield for magnetically shielding the array of transducers on one of the modules from the array of transducers on the other module.
10. An apparatus as recited in claim 1, further comprising a second set of at least two second modules generally aligned with the at least two modules in the intended direction of tape travel, each of the second modules having an array of transducers, wherein the at least two second modules are fixed relative to each other; and
further comprising a second mechanism for orienting the second modules to control a transducer pitch presented to a tape.
11. An apparatus, as recited in claim 1, comprising:
a drive mechanism for passing a magnetic medium over the modules; and
a controller configured to control the mechanism for orienting the modules based on a state of expansion of the tape.
12. A computer program product for orienting a head, the computer program product comprising a computer readable storage medium having program code embodied therewith, the program code readable/executable by a controller to:
determine, by the controller, a desired pitch for transducers for reading and/or writing to a magnetic tape; and

cause a mechanism to orient a head to achieve the desired pitch, the head having at least two opposing modules generally aligned with each other in an intended direction of tape travel thereacross, positions of the two modules being fixed relative to each other, each module having an array of the transducers, wherein an axis of each array is defined between opposite ends thereof, wherein the array of a first of the modules is offset from the array of a second of the modules in a first direction parallel to the axis of the array of the second module such that the transducers of the first module are about aligned with the transducers of the second module in the intended direction of tape travel thereacross when the axes are oriented at an angle between greater than 0.2° and about 10° relative to a line oriented perpendicular to the intended direction of tape travel.

13. The computer program product as recited in claim 12, further comprising program code for determining a state of the tape, the desired pitch being determined based on the state of the tape.

14. A computer program product as recited in claim 12, wherein the head has only two modules.

15. A computer program product as recited in claim 12, wherein the head has three modules, a third one of the modules being positioned between the first and second modules, wherein the array of the third module is offset from the array of the first module in the first direction, wherein an extent of the offset of array of the third module relative to the array of the first module is less than an extent of the offset of the array of the second module relative to the array of the first module.

1/14




FIG. 1A




FIG. 1B




FIG. 2




FIG. 2A




FIG. 2B






FIG. 2C






FIG. 5




FIG. 6

7/14




FIG. 7

8/14




FIG. 8A




FIG. 8B

9/14




FIG. 8C




FIG. 9A

10/14




FIG. 9B








FIG. 9C

11/14



12/14



13/14




FIG. 11




FIG. 12