US00D528020S

(12) **United States Design Patent** (10) **Patent No.: US D528,020 S**
Brown et al. (45) **Date of Patent: ** Sep. 12, 2006**

(54) **PROCESS DEVICE**

(75) Inventors: **Gregory C. Brown**, Chanhassen, MN (US); **George C. Hausler**, Maple Grove, MN (US)

(73) Assignee: **Rosemount Inc.**, Eden Prairie, MN (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/204,502**

(22) Filed: **Apr. 29, 2004**

(51) **LOC (8) Cl.** **10-04**
(52) **U.S. Cl.** **D10/46**
(58) **Field of Classification Search** D14/299; D10/46, 102; 73/718, 861.02, 861.03, 861.22, 73/861.24, 861.52
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,883,489	A	*	4/1959	Eadie, Jr. et al.	335/148
3,612,851	A	*	10/1971	Fowler	362/30
D225,743	S	*	1/1973	Seltzer	D10/102
4,370,890	A	*	2/1983	Frick	73/718
5,094,109	A		3/1992	Dean et al.	
D331,370	S	*	12/1992	Williams	D10/46
D345,107	S	*	3/1994	Williams	D10/46
5,495,769	A	*	3/1996	Broden et al.	73/718
5,554,809	A	*	9/1996	Tobita et al.	73/700
5,851,083	A		12/1998	Palan	
5,872,494	A		2/1999	Palan et al.	
5,954,526	A		9/1999	Smith	
6,079,276	A	*	6/2000	Frick et al.	73/718
6,295,875	B1		10/2001	Frick et al.	

OTHER PUBLICATIONS

"Wireless Instrumentation, Multi–Input Field Unit", by Accutech, 2 pgs., Dec. 2003.

"Wireless Management Toolkit XYR 5000", by Honeywell International Inc., Phoenix, Arizona, 3 pgs., Oct. 2003.

"Wireless Analog Input Transmitters XYR 5000", by Honeywell International Inc., Phoenix, Arizona, 4 pgs., Oct. 2003.

* cited by examiner

Primary Examiner—Paula A. Greene
(74) *Attorney, Agent, or Firm*—Westman, Champlin & Kelly, P.A.

(57) **CLAIM**

The ornamental design for a process device, as shown and described.

DESCRIPTION

FIG. **1** is a front elevational view of a process device showing my new design;

FIG. **2** is a right side elevation view of a first embodiment;

FIG. **3** is a rear elevation view of a first embodiment;

FIG. **4** is a left side elevation view of a first embodiment;

FIG. **5** is a top plan view of a first embodiment;

FIG. **6** is a bottom plan view of a first embodiment;

FIG. **7** is a perspective view of a first embodiment;

FIG. **8** is a front elevational view of a second embodiment of a process device showing my new design;

FIG. **9** is a right side elevation view of a second embodiment;

FIG. **10** is a rear elevation view of a second embodiment;

FIG. **11** is a left side elevation view of a second embodiment;

FIG. **12** is a top plan view of a second embodiment;

FIG. **13** is a bottom plan view of a second embodiment; and,

FIG. **14** is a perspective view of a second embodiment.

The broken lines are for illustrative purposes only and forms no part of the claimed design.

1 Claim, 14 Drawing Sheets






IN EXPLOSIVE ATMOSPHERE
-WARNING-
ROSEMOUNT
KEEP TIGHT WHEN CIRCUIT ALIVE

Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7


IN EXPLOSIVE ATMOSPHERE
-WARNING-
- ROSEMOUNT -
KEEP TIGHT WHEN CIRCUIT ALIVE

Fig. 8



Fig. 9



Fig. 10



Fig. 11



Fig. 12



Fig. 13



Fig. 14