

(12) **United States Patent
Parks**

(10) **Patent No.: US 11,053,772 B2**
(45) **Date of Patent: Jul. 6, 2021**

(54) **METHODS AND SYSTEMS FOR
PREVENTING HYDROSTATIC HEAD
WITHIN A WELL**

(71) Applicant: **Vertice Oil Tools**, Missouri City, TX (US)
(72) Inventor: **Stephen Parks**, Houston, TX (US)
(73) Assignee: **Vertice Oil Tools Inc.**, Missouri City, TX (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/162,559**

(22) Filed: **Jan. 29, 2021**

(65) **Prior Publication Data**

US 2021/0148187 A1 May 20, 2021

Related U.S. Application Data

(63) Continuation of application No. PCT/US2020/013611, filed on Jan. 15, 2020, which is a continuation of application No. 16/571,112, filed on Sep. 14, 2019, now Pat. No. 10,662,734.

(51) **Int. Cl.**
E21B 33/128 (2006.01)
E21B 33/127 (2006.01)

(52) **U.S. Cl.**
CPC **E21B 33/1285** (2013.01); **E21B 33/127** (2013.01); **E21B 33/128** (2013.01)

(58) **Field of Classification Search**
CPC .. E21B 33/127; E21B 33/1208; E21B 33/128; E21B 33/126; E21B 33/1285
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,640,893 B1 *	11/2003	Rummel		E21B 33/1208	166/187
6,843,315 B2	1/2005	Coronado			
7,306,033 B2 *	12/2007	Gorrara		E21B 33/127	166/187
7,588,077 B2 *	9/2009	Harper		E21B 33/1212	166/191
7,669,653 B2	3/2010	Craster			
9,863,208 B2 *	1/2018	Martin		F16J 15/08	
10,006,257 B2 *	6/2018	Logan		E21B 17/00	
10,060,222 B2 *	8/2018	Saltel		E21B 33/127	
10,125,567 B2 *	11/2018	Martin		E21B 33/1292	
10,662,734 B1 *	5/2020	Parks		E21B 33/127	
2006/0042801 A1 *	3/2006	Hackworth		E21B 33/13	166/387
2007/0089877 A1 *	4/2007	Corre		E21B 33/1277	166/187
2008/0251250 A1 *	10/2008	Brezinski		E21B 43/103	166/179
2012/0125619 A1 *	5/2012	Wood		E21B 43/267	166/308.1

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO-2005088064 A1 * 9/2005 E21B 43/105


Primary Examiner — Daniel P Stephenson

(74) *Attorney, Agent, or Firm* — Pierson IP, PLLC

(57) **ABSTRACT**

A tool with a deformable element that is configured to flex across an annulus based on a force being applied to an inner surface of the deformable element. The deformable element may be configured to be positioned within a chamber that is covered by a first rupture disc. The deformable element may include seals, flex joints, and a body.

22 Claims, 8 Drawing Sheets



(56)


References Cited

U.S. PATENT DOCUMENTS

2012/0312555	A1*	12/2012	Caminari	E21B 23/00
				166/381
2014/0196887	A1	7/2014	Hallundbæk	
2015/0090439	A1*	4/2015	VanLue	E21B 33/134
				166/118
2016/0053568	A1*	2/2016	Saltel	E21B 23/06
				166/179
2016/0102522	A1	4/2016	Martin	
2017/0211348	A1*	7/2017	Buyers	E21B 33/1216

* cited by examiner

FIG. 1







FIG. 3






FIGURE 4




FIGURE 5

FIG. 6




FIG. 7





FIG. 8



1

METHODS AND SYSTEMS FOR PREVENTING HYDROSTATIC HEAD WITHIN A WELL

BACKGROUND INFORMATION

Field of the Disclosure

Examples of the present disclosure relate to a deformable element that is configured to seal across an annulus by deformation. More specifically, embodiments include a deformable element that is configured to flex across an annulus responsive to being introduced to pressure force.

Background

Directional drilling is the practice of drilling non-vertical wells. Horizontal wells tend to be more productive than vertical wells because they allow a single well to reach multiple points of the producing formation across a horizontal axis without the need for additional vertical wells. This makes each individual well more productive by being able to reach reservoirs across the horizontal axis. While horizontal wells are more productive than conventional wells, horizontal wells are costlier.

Conventionally, casings can be run all way to the surface which adds an extra cost of casing length. Other methods can include hanging the casing just above the horizontal or deviated section using a packer, a liner hanger, combination of both. Although this can be a cheaper method, it is still expensive and increases operational complexity. Alternative methods include running the casing all the way to the surface, then intervening with mechanical or chemical cuts to sever the casing at a point above the horizontal section. However, this provides uncertainty of a shape and condition of the severed portion for re-entry purposes.

Furthermore, in re-frac applications or casing in casing applications, the original casing can have existing perforations that are connecting to the reservoir. This may cause pressure to be depleted due to production, and a conventional packer to isolate top sections of the liner may be required to prevent hydrostatic head from acting on uncured cement. This causes the liner to drop/move and expose the original perforations to new treating pressure. However, conventional packers require significant size/real estate to compensate for the piston needed to activate them.

Accordingly, needs exist for systems and methods associated with a deformable element that is configured to flex across an annulus based on a pressure being applied to an inner surface of the deformable element.

SUMMARY

Embodiments disclosed herein describe systems and methods for a tool with a deformable element that is configured to flex across an annulus based on a pressure being applied to an inner surface of the deformable element. This may eliminate the need for a significant increase in the outside diameter or decrease of the inner diameter of the tool, which may allow embodiments to occupy smaller spaces while maximizing the internal diameter through the tool. The deformable element may be configured to be positioned within a chamber that is covered by a first rupture disc. The deformable element may include seals, flex joints, and a body. In other embodiments, the rupture disc may be replaced with check valve or any other temporarily barrier.

2

The seals may be positioned on a proximal and distal end of an inner surface of the body against an outer surface of the tool. The inner surface of the tool may be partial seals configured to limit communication from an area between the inner surface of the body and the rest of the chamber without forming an atmospheric chamber, which can be also accomplished through the installation of check valve. In embodiments, the seal positioned on proximal or the distal end may be a complete seal.

The flex joints may be indentations, grooves, etc. positioned on an outer surface of the deformable element extending towards the inner surface. The flex joints may be configured to create weak points where the deformable element may flex outward across the annulus, which may allow the deformable element to bend but not break. The flex joints may be positioned between the seals. In other embodiments, the flex joints may be outside of the seals, positioned closer to the ends of the deformable element.

The body of the deformable element may extend from a first flex joint to a second flex joint, and include two tapered portions and a stem, wherein the stem is positioned between the two tapered portions. The tapered portions may be configured to increase and decrease, the diameter across the body to reduce the diameter across the stem, respectively. This may allow for stem to move from a first position that is in parallel to a central axis of the tool, to a second position that is bowed, flexed, etc. outward across the annulus. The outer surface of the body of the deformable element may be coupled with a compressible, resilient, high tensile strength materials, such as rubber. In other embodiments, the deformable element may not be coupled with any other materials.

In embodiments, responsive to the first rupture disc that isolates the chamber from the inner diameter of the tool being removed, the inner surface of the body may receive a force from the initial rupture and from fluid flowing through the inner diameter of the tool. This may cause the stem to bow outward to increase a distance from the outer diameter of the tool to the inner surface of the body, which may form a seal across the annulus. In embodiments, responsive to decreasing the force against the inner surface of the body, the stem may no longer bow outward and be reset in the direction that is in parallel to the central axis of the tool. In other embodiments, responsive to flexing the stem across the annulus, the stem may not fully retract even if the force is no longer being applied to the inner surface of the body due to reaching the plastic yield of the material which makes the stem permanently in a flex position.

These, and other, aspects of the invention will be better appreciated and understood when considered in conjunction with the following description and the accompanying drawings. The following description, while indicating various embodiments of the invention and numerous specific details thereof, is given by way of illustration and not of limitation. Many substitutions, modifications, additions or rearrangements may be made within the scope of the invention, and the invention includes all such substitutions, modifications, additions or rearrangements.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present invention are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

FIG. 1 depicts a tool, according to an embodiment.

FIG. 2 depicts a tool, according to an embodiment.

FIG. 3 depicts a tool, according to an embodiment.

FIG. 4 depicts a method for using a tool, according to an embodiment.

FIG. 5 depicts a method for using a tool, according to an embodiment.

FIG. 6 depicts a tool, according to an embodiment.

FIG. 7 depicts a tool, according to an embodiment.

FIG. 8 depicts a tool, according to an embodiment.

Corresponding reference characters indicate corresponding components throughout the several views of the drawings. Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of various embodiments of the present disclosure. Also, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present disclosure.

DETAILED DESCRIPTION

In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one having ordinary skill in the art that the specific detail need not be employed to practice the present invention. In other instances, well-known materials or methods have not been described in detail in order to avoid obscuring the present invention.

FIG. 1 depicts a tool **100** for sealing an annulus, according to an embodiment. Tool **100** may be used in connection with further elements, as described in U.S. Ser. No. 16/423,367 filed on May 28, 2019, and U.S. Pat. No. 10,400,521 granted on Sep. 3, 2019, which are hereby incorporated by reference in its entirety. More specifically, tool **100** may be configured to seal across an annulus before/after an upper sub-assembly **105** is decoupled from a lower sub-assembly **110** and/or before an inner diameter of tool **100** is in communication with the annulus outside of tool **100**. Tool **100** may include upper sub assembly **105** and lower sub assembly **110**, which may be configured to be run in hole as an integral unit, and decoupled from each other. Lower sub-assembly **110** may include a first rupture disc **120**, deformable element **130**, outer surface **140**, and second rupture disc **150**.

First rupture disc **120** may be positioned between an inner diameter of lower sub-assembly **110** and a housing of deformable element **130**. First rupture disc **120** may be configured to be removed after a pressure differential across first rupture disc **120** is greater than a first pressure threshold. In further embodiments, rupture disc **120** may be formed of dissolvable materials or any other temporarily element that are configured to be removed after a predetermined amount of time, temperature, and/or being interfaced with fluids, etc.

Deformable element **130** may be a device formed of rigid materials, such as metal, that is configured to move from a first mode to a second mode. Deformable element **130** may be a continuous piece of ductile material that is configured to be plastically inflated/deformed. Deformable element **130** may be configured to move between the first mode and the second mode after first rupture disc **120** has been removed, and responsive to fluid creating a force on an inner surface of deformable element **130**. The sudden pressure from rupture disc **120** and the flowing fluid may create a force against the inner surface of deformable element that is radial

from the inner diameter of the tool towards the inner surface of casing. In the first mode, deformable element **130** may be configured to extend in a direction substantially in parallel to a central axis of lower sub-assembly **110**. In the second mode, the middle of the deformable element **130** may be configured to flex, bow, etc. outward to seal/choke across an annulus while the ends of the deformable element **130** remain parallel to a central axis of lower sub-assembly **110**. Furthermore, in the second mode a distance between the outer surface **140** of lower sub-assembly **110** and the inner surface of deformable element **130** may increase. In the second mode, the distance between the outer surface **140** of the lower sub assembly **110** and the inner diameter of the original casing it run through may decrease. In further embodiments, Deformable element **130** may be formed of a single material, such as steel, or a combination of materials coupled together. The plurality of materials may be coupled together to allow variation in material properties, such as strength, ductility, or to allow flex points at desired locations based on the mechanical properties of the materials at different locations.

Second rupture disc **150** may be positioned between the inner diameter of lower sub-assembly and the annulus. Second rupture disc **150** may be configured to be removed after a pressure differential across second rupture disc **150** is greater than a second pressure threshold, wherein the second pressure threshold is greater than the first pressure threshold. As such, communication to the annulus through a chamber housing second rupture disc **150** may be formed after both first rupture disc **120** and second rupture disc **150** are removed. In further embodiments, second rupture disc **150** may be formed of dissolvable materials that are configured to be removed after a predetermined amount of time, being interfaced with fluids, etc.

FIG. 2 depicts deformable element **130** in a first mode, according to an embodiment. As depicted in FIG. 2, in the first mode, an outer surface of deformable element **130** may be positioned away from an inner surface of casing **210**. Accordingly, in the first mode, fluid may flow between the outer surface of deformable element **130** and casing **210** without restriction. Deformable element **130** may include seals **220**, **222**, flex joints **230**, **232**, and a body **250**.

The seals **220**, **222** may be positioned on a proximal and distal end of an inner surface of the body **250**, and be positioned against an outer surface of the tool. The seals **220**, **222** may be partial seals configured to limit communication from an area between the inner surface of the body **250** and the rest of the annulus without forming an atmospheric chamber. In embodiments, a first seal **220** positioned on proximal or the distal end may be a partial seal, while a second seal **222** positioned on the opposite end of body **250** may be a complete seal.

The flex joints **230**, **232** may be indentations, grooves, etc. positioned on an outer surface of deformable element **130** extending towards the inner surface of deformable element **130**. Flex joints **230**, **232** may be configured to be weak points where deformable element **130** may flex outward across the annulus, which may allow deformable element **130** to bend, yield or deform but not break. In embodiments, flex joints **230**, **232** may be positioned between seals **220**, **222**. In further embodiments, flex joints **230**, **232** may be symmetrical in shape, with a substantially "U-Shape." The shape of flex joints **230**, **232** may further control the flexing of body **250**. In other embodiments, the seals **220**, **222** may be positioned between the flex joints **230**, **232**.

Body **250** may include two tapered portions **240**, **242** positioned between flex joints **230**, **232**, and a stem **252**

5

positioned between tapered portions **240**, **242**. Tapered portions **240**, **242** may decrease a diameter across the metal body **250** to control the flexing of body **250** at stem **252**. Due to the decrease in diameter across stem **252** versus that of tapered portions **240**, **242**, stem **252** may flex more outward than the rest of body **250**. In embodiments, weep holes **260**, **262**, check valves, or one-way valves may be positioned through body **250**. The valves may be configured to allow communication from the inner surface of body **250** and the annulus, while limiting communication from the annulus to the inner surface of body **250**. This may assist in not forming an atmospheric chamber between the inner surface of body **250** and first rupture disc **120**. In embodiments, body **250** may have a substantially planar inner surface when run in hole, wherein the inner surface of body **250** may be configured to be position adjacent to an outer surface of a mandrel before body **250** is deformed. Before being deformed, an outer surface of body **250** may have a concave curvature. Once body **250** is deformed, the outer surface of body **250** may have a convex curvature.

In other embodiments, elastic material **253** may be coupled, mounted, glued, etc. to an outer surface of the stem **252**, elastic material **253** may extend between tapered portions **240**, **242**. Elastic material **253** may be a rubber, Teflon or any other elastic material that has the ability to deform and seal gaps. FIG. **3** depicts deformable element **130** in a second mode, according to an embodiment. In embodiments, responsive to the first rupture disc being removed, the inner surface of deformable element **130** may be configured to interface with fluid flow, pressure, or both within the inner diameter of the chamber, which may cause a force against the inner surface of deformable element **130**. This force may cause deformable element **130** to flex outward, the flex, bow or deformation may be permanent if it exceeds the max yield strength of deformable element **130**.

As depicted in FIG. **3**, when the force is applied to the inner surface of deformable element **130**, body **250** may begin to flex at the weak points created by flex joints **230**, **232**, and continue to flex at an increasing angle along tapered portions **240**, **242**. This may allow the outer surface of body **250** to be positioned adjacent to casing **210**. In other embodiment body **250** outer diameter may be coupled to a rubber, elastic element, this may allow body **250** to flex less and allow the outer surface of stem **252** or elastic element **253** to contact the casing **210**, which may form a seal across the annulus.

FIG. **4** depicts a method **400** for deforming a tool, according to an embodiment. The operations of method **400** presented below are intended to be illustrative. In some embodiments, method **400** may be accomplished with one or more additional operations not described, and/or without one or more of the operations discussed. Additionally, the order in which the operations of method **400** are illustrated in FIG. **4** and described below is not intended to be limiting.

At operation **410**, pressure within a tool may be increased by flowing fluid within a tool.

At operation **420**, responsive to the pressure increasing within the tool, the force created by the fluid flowing, the pressure across a first rupture disc being greater than a first pressure differential, etc., the first rupture disc may be removed.

At operation **430**, the fluid may flow through a chamber housing the first rupture disc and interact with an inner surface of a deformable element.

At operation **440**, responsive to the fluid interacting with the inner surface of the deformable element, the deformable element may flex at flex joints and across tapered portions of

6

the deformable element. By controlling the diameter across the deformable element at various locations, the outward flex of the deformable element may be controlled to flex but not break, wherein the deformable element may flex across an annulus such that an outer surface of the deformable element is positioned adjacent to inner diameter of casing.

At operation **450**, the pressure within the tool may further increase.

At operation **460**, responsive to the pressure within the tool increasing further, a second rupture disc may be removed. This may allow communication through a housing initially holding the second rupture disc, wherein the communication is allowed between an inner diameter of the tool and the annulus.

FIG. **5** depicts a method **500** for deforming a tool, according to an embodiment. The operations of method **400** presented below are intended to be illustrative. In some embodiments, method **500** may be accomplished with one or more additional operations not described, and/or without one or more of the operations discussed. Additionally, the order in which the operations of method **500** are illustrated in FIG. **5** and described below is not intended to be limiting.

At operation **510**, a tool may be positioned downhole within a cased hole or an open hole. The cased hole may be positioned downhole within a geological formation that has already produced, and includes fractures that are created by a perforation gun. In other embodiment the geological formation may be not produced at the time of position the tool.

At operation **520**, cement may be pumped through the tool, followed by a wiper plug. This may force the cement to fill up an annulus positioned between an outer diameter of the tool and an inner diameter of the cased hole. However, there may be a hydrostatic head creating a pressure on an upper surface of the cement that is not cured. Without any further forces impacting the cement, this hydrostatic head may force the well to drink and move the cement downhole, which may not allow the cement to be cured at desired locations.

At operation **530**, a deformable element may expand across the annulus at a location above an upper surface of the cement. By expanding the deformable element, the deformable element may create a sufficient enough force to isolate the annulus above from the annulus below, which prevents the hydrostatic head from acting on the cement head or set packers, it may be necessary to deform existing materials at a kickoff point to form the seal to limit the real estate required for elements in a narrower casing.

At operation **540**, the cement below the deformable element may cure. By expanding the deformable element above the upper surface of the cement in a refracturing operation, the cement may not drop downhole due to the hydrostatic head applying forces against the upper surface of the cement.

FIG. **6** depicts a deformable body **600**, according to an embodiment. Elements depicted in FIG. **6** may be described above, and for the sake of brevity a further description of these elements is omitted.

As depicted in FIG. **6** deformable body **600** may include an asymmetric flex joint **605**. Flex joint **605** may include two asymmetrical curves **620**, **630** with a lower sidewall that is tapered **610**. This may allow for the deformation of deformable body **600** to occur at lower stresses in a given direction than when compared to a symmetrical flex joint **605**.

FIG. **7** depicts a system **700** configured to deform across an annulus to contact an inner surface of casing **710**, according to an embodiment. Elements depicted in FIG. **7**

7

may be described above, and for the sake of brevity a further description of these elements is omitted. System **700** may include a retaining body **720** and a deformable element **705**.

Retaining body **720** may include a seal **740** and ledge **730**, wherein ledge **730** may be an outcrop, projection etc. In embodiments, seal **740** may be configured to be positioned adjacent to an outer diameter of a tool, while ledge **730** may be positioned away from the outer diameter of the tool. An end **707** of a deformable element **705** may be configured to be positioned between ledge **730** and the outer diameter of the tool, and be secured to ledge **730** and the outer diameter of the tool. Responsive to the inner surface of deformable element **705** receiving a force to deform, deformable element **705** may flex outward to seal across the annulus to be positioned adjacent to casing **710**. When flexed across the annulus, the end **707** of deformable body **705** may remain positioned between ledge **730** and the outer diameter of the tool.

FIG. **8** depicts a system **800** configured to deform across an annulus to contact an inner surface of casing, according to an embodiment. Elements depicted in FIG. **8** may be described above, and for the sake of brevity a further description of these elements is omitted. System **800** may include a deformable element **810**, rupture disc **815**, mandrel **820** with ledge **825**, seals **830**, and ports **840**.

Deformable element **810** may be configured to be positioned within mandrel **820**, wherein at least a portion of the upper surface of deformable element **810** is exposed to an annulus. This portion of the upper surface of the deformable element may be configured to flex across the annulus to seal the annulus. The ends of deformable element **810** may be configured to be encompassed and secured in place by mandrel **820** and the ledge **825** of mandrel.

Seals **830** may be positioned between the lower surface of deformable element **810** and mandrel **820**, wherein seals **830** may be configured to limit communication between the inner diameter of system **800** and a lower surface of deformable element **810**. In other embodiments, the seals may be configured on the deformable element **810**, the ledge **825** or next to the element proximal end and distal end.

Ports **840** may be configured to allow communication from an inner diameter of system **800** towards a lower surface of deformable element **810**. The communication may assist in flexing deformable element **810** across the annulus after rupture disc **815** is removed. In other embodiment that rupture disc may be replaced with a hole.

Reference throughout this specification to “one embodiment”, “an embodiment”, “one example” or “an example” means that a particular feature, structure or characteristic described in connection with the embodiment or example is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment”, “in an embodiment”, “one example” or “an example” in various places throughout this specification are not necessarily all referring to the same embodiment or example. Furthermore, the particular features, structures or characteristics may be combined in any suitable combinations and/or sub-combinations in one or more embodiments or examples. In addition, it is appreciated that the figures provided herewith are for explanation purposes to persons ordinarily skilled in the art and that the drawings are not necessarily drawn to scale.

Although the present technology has been described in detail for the purpose of illustration based on what is currently considered to be the most practical and preferred implementations, it is to be understood that such detail is solely for that purpose and that the technology is not limited to the disclosed implementations, but, on the contrary, is

8

intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present technology contemplates that, to the extent possible, one or more features of any implementation can be combined with one or more features of any other implementation.

The invention claimed is:

1. A downhole tool configured to be used in zonal isolation operations comprising:

a deformable element with a stem configured to move from a first mode to a second mode, wherein in a first mode the stem has a first outside diameter and in the second mode the stem is permanently deformed to have a second outside diameter, the second outside diameter being larger than the first outside diameter, wherein in the first mode an inner surface of the stem is not flexed and in the second mode the inner surface of the stem is flexed to create a convex bend;

a tapered slope increasing a diameter across the deformable element from a center the stem towards an end of the deformable element, wherein a thickness associated with the center of the stem is smaller than that of the tapered slope, wherein the center of the stem is positioned closer to a central axis of the downhole tool than an outer surface of the tapered slope.

2. The downhole tool of claim **1**, wherein in the first mode the inner surface of the stem extends in a direction in parallel to a central axis of the downhole tool.

3. The downhole tool of claim **1**, further comprising: indentations extending from an outer surface of the deformable element towards an inner surface of the deformable element positioned closer to a central axis of the downhole tool than the outer surface of the deformable element;

an elastic material positioned on the outer surface of the deformable element.

4. The downhole tool of claim **1**, wherein the tapered slope includes two angled ends.

5. The downhole tool of claim **1**, wherein the tapered slope is positioned between the end of the deformable element and the center of the stem.

6. The downhole tool of claim **1**, further comprising: a retaining body with a ledge, wherein the end is configured to be positioned between a tool mandrel and the ledge.

7. The downhole tool of claim **1**, further comprising: a hole configured to expose the internal diameter of the deformable element to an inner diameter of the downhole tool.

8. A method associated with a downhole tool configured to be used in zonal isolation operations, the method comprising:

moving a deformable element with a stem from a first mode to a second mode, wherein in a first mode the stem has a first outside diameter and in the second mode the stem is permanently deformed to have a second outside diameter, the second outside diameter being larger than the first outside diameter, wherein in the first mode an inner surface of the stem is not flexed and in the second mode the inner surface of the stem is flexed to create a convex bend;

forming a tapered slope that increases a diameter across the deformable element from a center the stem towards an end of the deformable element, wherein a thickness associated with the center of the stem is smaller than that of the tapered slope, wherein the center of the stem

9

is positioned closer to a central axis of the downhole tool than an outer surface of the tapered slope.

9. The method of claim 8, wherein in the first mode the inner surface of the stem extends in a direction in parallel to a central axis of the downhole tool.

10. The method of claim 8, further comprising:

forming indentations extending from an outer surface of the deformable element towards the inner surface of the deformable element, the inner surface of the deformable element positioned closer to a central axis of the downhole tool than the outer surface of the deformable element;

positioning an elastic material positioned on the outer surface of the deformable element.

11. The method of claim 8, wherein the tapered slope includes two angled ends.

12. The method of claim 8, wherein the tapered slope is positioned between the end of the deformable element and the center of the stem.

13. The method of claim 8, further comprising:

positioning the end between a tool mandrel and a ledge.

14. The method of claim 8, further comprising:

forming a hole to expose the internal diameter of the deformable element to an inner diameter of the downhole tool.

15. A downhole tool configured to be used in zonal isolation operations comprising:

a deformable element with a stem configured to move from a first mode to a second mode, wherein in a first mode the stem has a first length and in the second mode the stem is permanently deformed to have a second length, the second length being shorter than the first length, wherein in the first mode an inner surface of the stem is not flexed and in the second mode the inner surface of the stem is flexed to create a convex bend;

10

a flex joint extending from an outer surface of the body towards the inner surface of the stem, the inner surface of the stem positioned closer to a central axis of the downhole tool than the outer surface of the stem; and a tapered slope increasing a diameter across the body from a center the stem towards ends of the deformable element, wherein a thickness associated with the center of the stem is smaller than that of the tapered slope, wherein the center of the stem is positioned closer to a central axis of the downhole tool than an outer surface of the tapered slope.

16. The downhole tool of claim 15, wherein in the first mode the inner surface of the stem extends in a direction in parallel to a central axis of the downhole tool.

17. The downhole tool of claim 16, further comprising: an elastic material positioned on the outer surface of the deformable element.

18. The downhole tool of claim 17, further comprising: a sealing surface positioned between the deformable element and a tool mandrel, wherein the deformable element is a separate element from the tool mandrel.

19. The downhole tool of claim 17, wherein the ends of the deformable element has a maximum thickness of the deformable element.

20. The downhole tool of claim 16, wherein the tapered slope includes two angled ends.

21. The downhole tool of claim 16, wherein the tapered slope is positioned between the end of the deformable element and the center of the stem.

22. The downhole tool of claim 16, further comprising: a retaining body with a ledge, wherein the end is configured to be positioned between a tool mandrel and the ledge.

* * * * *