



(51) International Patent Classification:

A61L 31/02 (2006.01) *A61B 17/04* (2006.01)
A61L 31/10 (2006.01) *A61B 17/064* (2006.01)
A61L 31/14 (2006.01) *A61B 17/115* (2006.01)
A61B 17/072 (2006.01) *A61B 17/00* (2006.01)
A61B 17/11 (2006.01) *A61B 17/06* (2006.01)
A61B 90/00 (2016.01)

(21) International Application Number:

PCT/US2016/046312

(22) International Filing Date:

10 August 2016 (10.08.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

14/836,375 26 August 2015 (26.08.2015) US

(71) Applicant: **ETHICON ENDO-SURGERY, LLC**
[US/US]; #475 Street C, Los Frailes Industrial Park,
Guaynabo, Puerto Rico 00969 (US).(72) Inventors: **ECKERT, Chad E.**; 4545 Creek Road, Cincinnati, Ohio 45242 (US). **HARRIS, Jason L.**; 4545 Creek Road, Cincinnati, Ohio 45242 (US). **SWAYZE, Jeffrey S.**; 4545 Creek Road, Cincinnati, Ohio 45242 (US). **SHELTON, IV, Frederick E.**; 4545 Creek Road, Cincinnati, Ohio 45242 (US). **MORGAN, Jerome R.**; 4545 Creek Road, Cincinnati, Ohio 45242 (US).(74) Agents: **SHIRTZ, Joseph F.** et al.; Johnson & Johnson, One Johnson & Johnson Plaza, New Brunswick, New Jersey 08933 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))

(54) Title: STAPLES COMPRISING A COVER

(57) Abstract: A staple cartridge assembly including staples is disclosed herein. The staples comprise features which improve the biocompatibility and/or bioabsorption of the staples. The staples are comprised of a magnesium alloy, for example. The magnesium alloy can also include zinc. In certain instances, a bioabsorbable polymer is coated on part of, but not all of, the staple. Portions of the staple that are not coated by the bioabsorbable polymer will be absorbed at a first rate while portions of the staple that are coated by the bioabsorbable polymer will be absorbed at a slower rate. In various instances, the tips of the magnesium staples are coated with magnesium nitride and/or any other suitable material which can increase the hardness of the staples. In certain instances, the staples are coated in silver. In some instances, the staples include one or more apertures defined therein.

**WO 2017/034804 A1**

TITLE**STAPLES COMPRISING A COVER****BACKGROUND**

[0001] The present invention relates to surgical instruments and, in various embodiments, to surgical stapling and cutting instruments and staple cartridges for use therewith.

[0002] A stapling instrument can include a pair of cooperating elongate jaw members, wherein each jaw member can be adapted to be inserted into a patient and positioned relative to tissue that is to be stapled and/or incised. In various embodiments, one of the jaw members can support a staple cartridge with at least two laterally spaced rows of staples contained therein, and the other jaw member can support an anvil with staple-forming pockets aligned with the rows of staples in the staple cartridge. Generally, the stapling instrument can further include a pusher bar and a knife blade which are slidable relative to the jaw members to sequentially eject the staples from the staple cartridge via camming surfaces on the pusher bar and/or camming surfaces on a wedge sled that is pushed by the pusher bar. In at least one embodiment, the camming surfaces can be configured to activate a plurality of staple drivers carried by the cartridge and associated with the staples in order to push the staples against the anvil and form laterally spaced rows of deformed staples in the tissue gripped between the jaw members. In at least one embodiment, the knife blade can trail the camming surfaces and cut the tissue along a line between the staple rows.

[0003] The foregoing discussion is intended only to illustrate various aspects of the related art in the field of the invention at the time, and should not be taken as a disavowal of claim scope.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] Various features of the embodiments described herein are set forth with particularity in the appended claims. The various embodiments, however, both as to organization and methods of operation, together with advantages thereof, may be understood in accordance with the following description taken in conjunction with the accompanying drawings as follows:

[0005] FIG. 1 is a perspective view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;

[0006] FIG. 2 is a side elevation view of the staple of FIG. 1;

- [0007] FIG. 3 is a top view of the staple of FIG. 1;
- [0008] FIG. 4 is a cross-sectional view of the staple of FIG. 1 taken along line 4-4 in FIG. 3;
- [0009] FIG. 5 is a perspective view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;
- [0010] FIG. 6 is a side elevation view of the staple of FIG. 5;
- [0011] FIG. 7 is a side elevation view of a staple for use with surgical stapling instrument in accordance with at least one embodiment;
- [0012] FIG. 8 is a side elevation view of the staple of FIG. 7 in a formed configuration;
- [0013] FIG. 9 is a top view of the staple of FIG. 7 in the formed configuration of FIG. 8;
- [0014] FIG. 10 is a side elevation view of the staple of FIG. 7 in a formed configuration and a partial cross-sectional view of an anvil of a surgical stapling instrument;
- [0015] FIG. 11 is a perspective view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;
- [0016] FIGS. 11A-11C are cross-sections of portions of the staple of FIG. 11;
- [0017] FIG. 12 is a perspective view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;
- [0018] FIG. 13 is a side elevation view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;
- [0019] FIG. 14 is a partial top view of a formed staple configuration comprising a plurality of staples in accordance with at least one embodiment;
- [0020] FIG. 15 is a perspective view of a staple for use with a surgical stapling instrument in accordance with at least one embodiment;
- [0021] FIG. 16 is a partial cross-sectional view of an anvil illustrating a portion of the staple of FIG. 15 being formed from an unformed configuration to a formed configuration;
- [0022] FIG. 17 is an elevation view of the staple of FIG. 15 in a formed configuration;
- [0023] FIG. 18 includes side views of multiple staple tips in accordance with at least one embodiment;
- [0024] FIG. 19 is a bottom view of a staple in accordance with at least one embodiment and forming pockets of an anvil according to a first arrangement;
- [0025] FIG. 20 is partial cross-sectional view of an anvil pocket of FIG. 19 taken along line 20-20 in FIG. 19;

- [0026] FIG. 21 is a bottom view of the staple and the forming pockets of FIG. 19 according to a second arrangement;
- [0027] FIG. 22 is a bottom view of the staple and the forming pockets of FIG. 19 according to a third arrangement;
- [0028] FIG. 23 is a bottom view of the staple of FIG. 19 and forming pockets in accordance with at least one embodiment;
- [0029] FIG. 24 is a partial cross-sectional view of an anvil pocket of FIG. 23 taken along line 24-24 in FIG. 23;
- [0030] FIG. 25 is a bottom view of the staple of FIG. 19 and forming pockets in accordance with at least one embodiment;
- [0031] FIG. 26 is a bottom view of the staple of FIG. 19 and forming pockets in accordance with at least one embodiment;
- [0032] FIG. 27 is a partial perspective view of a staple leg in accordance with at least one embodiment;
- [0033] FIG. 27A is a partial cross-sectional end view of the staple leg of FIG. 27;
- [0034] FIG. 27B is a partial longitudinal cross-section of the staple leg of FIG. 27;
- [0035] FIG. 28 is a perspective view of a portion of a staple strip manufactured with progressive die stamping;
- [0036] FIG. 28A is a partial cross-sectional view of the portion of the staple strip of FIG. 28 taken along line 28A-28A in FIG. 28;
- [0037] FIG. 28B is a partial cross-sectional view of the portion of the staple strip of FIG. 28 taken along line 28B-28B in FIG. 28;
- [0038] FIG. 28C is a partial perspective view of a sled configured to engage the staple strip of FIG. 28;
- [0039] FIG. 29 is a perspective view of a portion of a staple strip manufactured with progressive die stamping in accordance with at least one embodiment;
- [0040] FIG. 30 is a bottom perspective view of the staple strip of FIG. 29;
- [0041] FIG. 31 is a partial cross-sectional view of a staple cartridge and staples in accordance with at least one embodiment;
- [0042] FIG. 32 is a perspective view of a staple cartridge assembly in accordance with at least one embodiment;

- [0043] FIG. 33 is a top plan view of the staple cartridge assembly of FIG. 32;
- [0044] FIG. 34 is a detail view of a distal end of the staple cartridge assembly of FIG. 32;
- [0045] FIG. 35 is a partial cross-sectional perspective view of a staple cartridge assembly in accordance with at least one embodiment illustrating staples being ejected from the staple cartridge assembly by a firing member;
- [0046] FIG. 36 is a partial exploded view of the staple cartridge assembly of FIG. 35;
- [0047] FIG. 37 is a partial cross-sectional view of the staple cartridge assembly of FIG. 35 illustrating a staple being deformed against an anvil by the firing member;
- [0048] FIG. 38 is a partial plan view of a staple positioned in a staple cavity of the staple cartridge assembly of FIG. 35;
- [0049] FIG. 39 is a partial perspective view of a staple being lifted by the firing member of the staple cartridge of FIG. 35;
- [0050] FIG. 40 is a bottom perspective view of the staple of FIG. 39;
- [0051] FIG. 41 is a diagram illustrating the staple of FIG. 39 in a level position;
- [0052] FIG. 42 is a diagram illustrating the staple of FIG. 39 in a crooked position;
- [0053] FIG. 43 is a cross-sectional plan view of a staple cavity configured to guide a staple in accordance with at least one embodiment;
- [0054] FIG. 44 is a cross-sectional perspective view of a staple cartridge assembly positioned in a jaw of a surgical stapling instrument in accordance with at least one embodiment illustrating a firing member positioned in a cartridge body of the staple cartridge assembly;
- [0055] FIG. 45 is a partial cross-sectional perspective view of the staple cartridge assembly of FIG. 44 illustrating a retention feature configured to hold the firing member in the cartridge body when the staple cartridge assembly is not positioned in the jaw of the surgical stapling instrument;
- [0056] FIG. 46 is a partial cross-sectional exploded view of the staple cartridge assembly of FIG. 44;
- [0057] FIG. 47 is a partial cross-sectional end view of the staple cartridge assembly of FIG. 44;
- [0058] FIG. 48 is a partial cross-sectional perspective view of the staple cartridge assembly of FIG. 44 illustrating a retention feature configured to releasably hold the staple cartridge assembly in the jaw of the surgical stapling instrument;
- [0059] FIG. 49 is a partial plan view of a staple positioned in a staple cavity of a staple cartridge assembly in accordance with at least one embodiment;

- [0060] FIG. 50 is a detail view of a retention feature configured to releasably hold the staple in the staple cartridge assembly of FIG. 49;
- [0061] FIG. 51 is a partial cross-sectional elevational view of a staple cartridge assembly in accordance with at least one embodiment;
- [0062] FIG. 52 is a perspective view of a staple in accordance with at least one embodiment;
- [0063] FIG. 53 is a bottom perspective view of the staple of FIG. 52;
- [0064] FIG. 54 is a front elevational view of the staple of FIG. 52;
- [0065] FIG. 55 is a side elevational view of the staple of FIG. 52;
- [0066] FIG. 56 is a bottom view of the staple of FIG. 52;
- [0067] FIG. 57 is a perspective view of a firing member of a staple cartridge assembly in accordance with at least one embodiment comprising alignment channels;
- [0068] FIG. 58 is a diagram illustrating the firing member of FIG. 57 and a staple positioned in a staple cavity of a staple cartridge assembly;
- [0069] FIG. 59 is a diagram illustrating the firing member of FIG. 57 aligning the staple of FIG. 58 within the staple cavity of FIG. 58;
- [0070] FIG. 60 is a perspective view of the firing member of FIG. 57 and staples arranged in two longitudinal rows;
- [0071] FIG. 61 is a partial cross-sectional view of an alignment channel of the firing member of FIG. 57 and a portion of the staple of FIG. 58;
- [0072] FIG. 62 is a partial cross-sectional perspective view of the staple cartridge assembly of FIG. 58;
- [0073] FIG. 63 is a partial exploded view of the staple cartridge assembly of FIG. 58;
- [0074] FIG. 64 is a partial bottom cross-sectional perspective view of the staple cartridge assembly of FIG. 58;
- [0075] FIG. 65 is a partial perspective view of projections extending from a deck surface of a staple cartridge assembly in accordance with at least one alternative embodiment;
- [0076] FIG. 66 is a partial perspective view of projections extending from a deck surface of a staple cartridge assembly in accordance with at least one alternative embodiment;
- [0077] FIG. 67 is a bottom perspective view of a cartridge body of a staple cartridge assembly;
- [0078] FIG. 68 is a bottom view of the cartridge body of FIG. 67;

- [0079] FIG. 69 is a bottom perspective view of the cartridge body of the staple cartridge assembly of FIG. 32;
- [0080] FIG. 70 is a bottom view of the cartridge body of FIG. 32;
- [0081] FIG. 71 is a diagram illustrating the cartridge body of FIG. 67 to an alternative embodiment of a cartridge body;
- [0082] FIG. 72 is a partial top plan view of a staple cartridge assembly in accordance with at least one embodiment;
- [0083] FIG. 73 is a partial perspective view of the staple cartridge of FIG. 32;
- [0084] FIG. 74 is a cross-sectional view of the staple cartridge of FIG. 32 and the anvil of FIG. 37 illustrating certain staples in an unfired position and certain staples in a fired position;
- [0085] FIG. 75 illustrates the staples of the staple cartridge of FIG. 32 deformed to three different heights;
- [0086] FIG. 76 illustrates the staples of the staple cartridge of FIG. 32 implanted in the tissue of a patient;
- [0087] FIG. 77 illustrates a staple of the staple cartridge of FIG. 32 being deformed;
- [0088] FIG. 78 is a perspective view of a staple in accordance with at least one embodiment;
- [0089] FIG. 79 is a cross-sectional view of the staple of FIG. 78;
- [0090] FIG. 80 is a perspective view of a staple assembly in accordance with at least one embodiment;
- [0091] FIG. 81 is an elevational view of the staple assembly of FIG. 80;
- [0092] FIG. 82 is a perspective view of an implantable staple adjunct;
- [0093] FIG. 83 is a cross-sectional view of the staple adjunct of FIG. 82;
- [0094] FIG. 84 is a partial perspective view of a staple assembly including the staple adjunct of FIG. 82;
- [0095] FIG. 85 illustrates the staple assembly of FIG. 84 implanted into tissue;
- [0096] FIG. 86 is a perspective view of a staple in accordance with at least one embodiment illustrated in a deformed configuration;
- [0097] FIG. 87 is a plan view of a circular cartridge body comprising a plurality of the staple assemblies of FIG. 84 in accordance with at least one embodiment;
- [0098] FIG. 88 illustrates the spacing of the staples of FIG. 35 in unstretched tissue;
- [0099] FIG. 89 illustrates the spacing of the staples of FIG. 35 in stretched tissue;

[0100] FIG. 90 is a perspective view of a staple in accordance with at least one embodiment;

[0101] FIG. 91 illustrates the staple of FIG. 90 implanted into tissue;

[0102] FIG. 92 illustrates the staple of FIG. 90 after being partially dissolved;

[0103] FIG. 93 is a cross-sectional perspective view of a portion of a circular surgical stapler in accordance with at least one embodiment;

[0104] FIG. 94 is a partial cross-sectional perspective view of the circular surgical stapler of FIG. 93;

[0105] FIG. 95 is a partial perspective view of the circular surgical stapler of FIG. 93;

[0106] FIG. 96 is a partial exploded perspective view of a circular surgical stapler in accordance with at least one embodiment;

[0107] FIG. 97 is a partial perspective view of the circular surgical stapler of FIG. 96 illustrating staples in a preloaded position;

[0108] FIG. 98 is a partial perspective view of the circular surgical stapler of FIG. 96;

[0109] FIG. 99 is an end view of a circular surgical stapling configuration in accordance with at least one embodiment;

[0110] FIG. 100 is an end view of a circular surgical stapling configuration in accordance with at least one embodiment;

[0111] FIG. 101 is partial cross-sectional view of a colon stapled with a circular stapling instrument disclosed herein;

[0112] FIG. 102 is a partial perspective view of a curved stapler in accordance with at least one embodiment;

[0113] FIG. 103 is a partial exploded view of the curved stapler of FIG. 102;

[0114] FIG. 104 is a partial perspective view of the curved stapler of FIG. 102;

[0115] FIG. 105 is a partial perspective view of a curved stapler in accordance with at least one embodiment; and

[0116] FIG. 106 is a partial perspective view of the curved stapler of FIG. 105.

[0117] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate various embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[0118] The Applicant of the present application owns the following U.S. Patent Applications that were filed on even date herewith and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. _____, entitled SURGICAL STAPLES FOR MINIMIZING STAPLE ROLL; Attorney Docket No. END7687USNP/150127;
- U.S. Patent Application Serial No. _____, entitled SURGICAL STAPLES COMPRISING FEATURES FOR IMPROVED FASTENING OF TISSUE; Attorney Docket No. END7678USNP/150118;
- U.S. Patent Application Serial No. _____, entitled SURGICAL STAPLES COMPRISING HARDNESS VARIATIONS FOR IMPROVED FASTENING OF TISSUE; Attorney Docket No. END7727USNP/150298;
- U.S. Patent Application Serial No. _____, entitled SURGICAL STAPLE STRIPS FOR PERMITTING VARYING STAPLE PROPERTIES AND ENABLING EASY CARTRIDGE LOADING; Attorney Docket No. END7680USNP/150120;
- U.S. Patent Application Serial No. _____, entitled SURGICAL STAPLING CONFIGURATIONS FOR CURVED AND CIRCULAR STAPLING INSTRUMENTS; Attorney Docket No. END7682USNP/150122;
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY WITHOUT A BOTTOM COVER; Attorney Docket No. END7679USNP/150119;
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY COMPRISING STAPLE CAVITIES FOR PROVIDING BETTER STAPLE GUIDANCE; Attorney Docket No. END7681USNP/150121;
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY INCLUDING STAPLE GUIDES; Attorney Docket No. END7685USNP/150125;
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY COMPRISING STAPLE ALIGNMENT FEATURES ON A FIRING MEMBER; Attorney Docket No. END7688USNP/150128;
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY COMPRISING VARIOUS TISSUE COMPRESSION GAPS AND STAPLE FORMING GAPS; Attorney Docket No. END7684USNP/150124;

- U.S. Patent Application Serial No. _____, entitled STAPLES CONFIGURED TO SUPPORT AN IMPLANTABLE ADJUNCT; Attorney Docket No. END7686USNP/150126; and
- U.S. Patent Application Serial No. _____, entitled STAPLE CARTRIDGE ASSEMBLY INCLUDING FEATURES FOR CONTROLLING THE ROTATION OF STAPLES WHEN BEING EJECTED THEREFROM; Attorney Docket No. END7683USNP/150123.

[0119] Applicant of the present application also owns the following patent applications that were filed on December 23, 2013 and which are each incorporated by reference herein in their respective entireties:

- U.S. Patent Application Serial No. 14/138,554, entitled SURGICAL INSTRUMENTS WITH ARTICULATABLE SHAFT ARRANGEMENTS;
- U.S. Patent Application Serial No. 14/138,465, entitled SURGICAL STAPLES AND STAPLE CARTRIDGES;
- U.S. Patent Application Serial No. 14/138,474, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH SEPARATE AND DISTINCT CLOSING AND FIRING SYSTEMS;
- U.S. Patent Application Serial No. 14/138,485 entitled SURGICAL CUTTING AND STAPLING INSTRUMENTS WITH INDEPENDENT JAW CONTROL FEATURES;
- U.S. Patent Application Serial No. 14/138,475, entitled SURGICAL STAPLES AND STAPLE CARTRIDGES;
- U.S. Patent Application Serial No. 14/138,481, entitled SURGICAL STAPLES AND METHODS FOR MAKING THE SAME;
- U.S. Patent Application Serial No. 14/138,489 entitled SURGICAL STAPLES, STAPLE CARTRIDGES AND SURGICAL END EFFECTORS;
- U.S. Design Patent Application Serial No. 29/477,488, entitled SURGICAL FASTENER;
- U.S. Patent Application Serial No. 14/138,505 entitled FASTENER CARTRIDGE COMPRISING AN EXTENDABLE FIRING MEMBER;
- U.S. Patent Application Serial No. 14/138,518 entitled FASTENER CARTRIDGE COMPRISING A FIRING MEMBER CONFIGURED TO DIRECTLY ENGAGE AND EJECT FASTENERS FROM THE FASTENER CARTRIDGE;
- U.S. Patent Application Serial No. 14/138,530 entitled FASTENER CARTRIDGE COMPRISING A FIRING MEMBER INCLUDING FASTENER TRANSFER SURFACES;

- U.S. Patent Application Serial No. 14/138,507, entitled MODULAR SURGICAL INSTRUMENTS;
- U.S. Patent Application Serial No. 14/138,497, entitled SURGICAL CUTTING AND STAPLING INSTRUMENTS WITH ARTICULATABLE END EFFECTORS; and
- U.S. Patent Application Serial No. 14/138,516, entitled SURGICAL CUTTING AND STAPLING METHODS.

[0120] Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. Well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. The reader will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and illustrative. Variations and changes thereto may be made without departing from the scope of the claims.

[0121] The terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has" and "having"), "include" (and any form of include, such as "includes" and "including") and "contain" (and any form of contain, such as "contains" and "containing") are open-ended linking verbs. As a result, a surgical system, device, or apparatus that "comprises," "has," "includes" or "contains" one or more elements possesses those one or more elements, but is not limited to possessing only those one or more elements. Likewise, an element of a system, device, or apparatus that "comprises," "has," "includes" or "contains" one or more features possesses those one or more features, but is not limited to possessing only those one or more features.

[0122] The terms "proximal" and "distal" are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term "proximal" referring to the portion closest to the clinician and the term "distal" referring to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as "vertical", "horizontal", "up", and "down" may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0123] Various exemplary devices and methods are provided for performing laparoscopic and minimally invasive surgical procedures. However, the reader will readily appreciate that the various methods and devices disclosed herein can be used in numerous surgical procedures and applications including, for example, in connection with open surgical procedures. As the present Detailed Description proceeds, the reader will further appreciate that the various instruments disclosed herein can be inserted into a body in any way, such as through a natural orifice, through an incision or puncture hole formed in tissue, etc. The working portions or end effector portions of the instruments can be inserted directly into a patient's body or can be inserted through an access device that has a working channel through which the end effector and elongated shaft of a surgical instrument can be advanced.

[0124] A staple, or fastener, disclosed herein is configured for use with a surgical stapling instrument. Discussed in greater detail below, the staple is removably stored in a staple cavity of a staple cartridge. The staple cartridge comprises a sled configured to receive a firing actuation from the surgical stapling instrument which imparts a force on the staple to eject the staple from the staple cavity. When the staple is ejected, or driven, out of the staple cavity by the sled, the staple undergoes a deformation process where the staple forms into a fired configuration from an unfired configuration. The staple forms into the fired configuration when the staple contacts corresponding forming pockets of an anvil of the surgical stapling instrument.

[0125] Various staples disclosed herein comprise a flat-formed staple which can be cut and/or stamped from a sheet of material, for example. The sheet of material can be metallic and can comprise stainless steel and/or titanium, for example. In at least one instance, outlines can be traced, etched, and/or cut into the sheet of material which are machined and/or laser cut to form the staples into a manufactured shape.

[0126] The staples comprise a pair of staple legs and a staple base portion, or crown, from which the staple legs extend. Each staple leg comprises a staple tip, or piercing portion, which is configured to pierce the tissue and contact a corresponding forming pocket of the anvil of the surgical stapling instrument. The staple legs are configured to change shape to achieve a formed configuration to fasten the tissue. The staple base portion defines a first plane and the staple legs define a second plane which is laterally offset from but at least substantially parallel to the first plane. Embodiments are envisioned where the first and second planes are not parallel.

[0127] The flat-formed staple 100 depicted in FIGS. 1-4 comprises a proximal staple leg 110, a distal staple leg 120, and a staple base portion 130. The staple 100 further comprises vertical transition portions, or bends, 118, 128 and lateral transition portions, or bends, 116, 126. The vertical transition portions 118, 128 bend, or extend, the legs 110, 120 vertically, or upward, from the staple base portion 130. The lateral transition portions 116, 126 extend the staple legs 110, 120 laterally outward, or at least substantially perpendicularly with respect to the staple base portion 130. The staple legs 110, 120 define a first plane and the staple base portion 130 defines a second plane. Together, the vertical transition portions 118, 128 and the lateral transition portions 116, 126 permit the staple legs 110, 120 to be laterally offset and parallel with respect to the staple base portion 130. Stated another way, the first plane is offset from and at least substantially parallel to the second plane. In FIGS. 1-4, the first plane is offset in the negative Y direction. Other staples may be used in conjunction with a plurality of staples 100 where the other staples comprise a first plane which is offset in the positive Y direction. The use of both types of staples permits staple rows to be nested, or interwoven, where staple legs of neighboring rows may be at least substantially aligned and/or share a common longitudinal axis. In various instances, the staple rows can be nested to provide denser staple rows.

[0128] The proximal staple leg 110 and the distal staple leg 120 comprise staple tips 112, 122 and corners 114, 124, respectively. The tips 112, 122 are configured to pierce tissue and contact a forming pocket of an anvil of a surgical stapling instrument. The tips 112, 122 contact the anvil when the staple 100 receives a driving force to eject the staple 100 from a corresponding staple cavity in the staple cartridge. The tips 112, 122 and/or legs 110, 120 of the staple 100 will then begin forming from an unfired configuration to a fired configuration. The proximal staple leg 120 further comprises a leading engagement foot 117 comprising a chamfered surface, or edge, 119. As the sled contacts the staple 100 upon the sled's distal translation, a feature of the sled can engage the leading engagement foot 117 to aid in preventing longitudinal staple roll, or rotation, for example. The engagement foot 117 can comprise a push point that is configured to be pushed on to load the staple 100 into a staple cartridge.

[0129] Since the staple 100 is a flat-formed staple, the staple legs 110, 120, tips 112, 122, and/or other portions of the staple 100 can be further developed, or worked, after being stamped from a flat, or at least substantially flat, stock. Further developing the staple 100 can provide specific properties creating and/or altering preferential bending planes, toughness, and/or elasticity, for

example. Traditional wire-formed staples comprise desirable properties advantageous for surgical fastening and can be implemented with the staple 100. Methods for constructing the corners 114, 124 and/or tips 112, 122, for example, may include any suitable process including cold working, for example. A specific process may include coining by working the corners 114, 124 into a rounded, angled, oblique, and/or parabolic profile, for example. The staple tips 112, 122 can also be worked using similar methods to provide an adequate tip configured to pierce tissue and form against a corresponding forming pocket of the anvil.

[0130] The staple base portion 130 comprises an inclined drive surface 132, a final drive surface 131, and a distal wall 133. In various embodiments, the staple 100 is supported in a staple cartridge by a pan where the final drive surface 131 is configured to rest on the pan. In various other embodiments where a staple cartridge is pan-less, the final drive surface does not rest on a pan, rather, the final drive surface comprises an initial position residing above a bottom surface of the pan-less staple cartridge. This would allow a bottom surface of the sled and the bottom surface of the pan-less staple cartridge to be at least substantially flush as the sled translates through the cartridge. The drive surface 132 of each staple base portion 130 is configured to receive the driving force F_s from the sled of the surgical stapling instrument. When the sled translates distally through the staple cartridge, the sled contacts the drive surface 132 to lift the staple 100 out of the cartridge and, in addition, contact the final drive surface 131 to form the staple 100 into its fired configuration.

[0131] The distal wall 133 acts as a distal-most wall of the staple base portion 130 and is positioned proximal of the distal staple leg 120 resulting in a lack of any portion of the staple base portion 130 underneath the distal staple leg 120. Having a greater amount of mass in the base portion 130 of the staple 100 increases the ability of the staple 100 to resist rotational motion caused by the moment M_s applied by the sled. Increasing the moment of inertia of the staple base portion 130 increases the ability to resist rotational motion. As a result, a greater torque, or larger moment, would be required to cause longitudinal staple roll.

[0132] The staple base portion 130 further comprises a top surface, or compression surface, 136 comprising a proximal surface 139, an intermediate surface 138, and a distal surface 137. The proximal surface 139 is angled, or slanted, upward toward the proximal leg 110. The distal surface 137 is angled, or slanted, upward toward the distal leg 120. The intermediate surface 138 is at least substantially parallel to the final drive surface 131. This valley-like configuration limits the stress

concentration of tissue captured near the transition portions 118, 128, 116, 126 where the legs 110, 120 extend from the staple base portion 130. In various embodiments, these surfaces 137, 138, 139 can be curved to create a concave surface. In traditional staples, when formed, the connections where the legs meet the staple base produce locations responsible for highly localized tissue stress. This is especially true in the event that such a traditional staple buckles, or is crushed, or flattened, rather than formed into a true “B” configuration.

[0133] In various embodiments, the dynamics of the staple 100 are predictable when ejected from a staple cartridge. As the staple 100 is ejected from its corresponding staple cavity, a driving force F_S from the sled generates a moment M_S . One preventive measure for preventing staple roll includes increasing the moment of inertia of the staple 100, discussed above, which is configured to prevent, as illustrated in FIG. 2, longitudinal roll, or rotation of the staple. In the event that the staple 100 rolls longitudinally in the distal direction, or, in other words, rotates counterclockwise about the Y axis, outer, longitudinal staple leg surfaces 115, 125 of the staple 100 will contact the guide surfaces, or sidewalls, of the staple cartridge. This contact produces corresponding reaction forces F_{C1} and F_{C2} . More particularly, as the staple 100 is driven out of the staple cavity and rotated about the Y axis, the wall 115 of the proximal staple leg 110 contacts a proximal sidewall of the staple cartridge producing a reaction force F_{C2} which acts upon the staple leg 110 below the center of mass. The wall 125 of the distal staple leg 120 contacts a distal sidewall of the staple cartridge producing a reaction force F_{C1} which acts upon the staple leg 120 above the center of mass. Both reaction forces, F_{C1} and F_{C2} , contribute to a reactional moment M_{RC} to counteract, or balance, the applied moment M_S acting on the staple 100. The reaction forces discussed herein may be distributed loads acting upon a surface area of each of the staple legs 110, 120.

[0134] The moment of inertia of the staple 100 is also configured to prevent, as illustrated in FIG. 4, lateral roll, or rotation of the staple 100. The staple base portion 130 comprises a notch 134 defined in the top surface 136 on a side of the staple base portion 130 closest to the legs 110, 120. The notch 134 contributes to the predictability of the dynamics of the staple 100 before formation and upon formation when ejected from the staple cartridge. For example, referring primarily to FIG. 4, the notch 134 is configured to induce rotation of the staple 100 toward a particular cavity sidewall. In the event that the staple 100 rolls laterally, or, in other words, rotates in the direction of the applied moment M_S , outer, lateral staple leg walls 111, 121 of the staple 100 will contact the guide surfaces, or sidewalls, of the staple cartridge producing corresponding reaction forces F_{C1} and

F_{C2} . For example, as the staple 100 is driven out of the staple cavity and rotated in the direction of the applied moment M_S , the walls 111, 121 of the staple legs 110, 120 contact a corresponding sidewall of the staple cartridge producing a reaction force F_{C1} which act upon the staple legs 110, 120 above the center of mass. An outer lateral wall 135 of the staple base portion 130 contacts another corresponding sidewall of the staple cartridge producing a reaction force F_{C2} which acts upon the staple base portion 130 below the center of mass. Reaction forces F_{C1} and F_{C2} produce a reactional moment M_{RC} to counteract, or balance, the applied moment M_S acting on the staple 100 from the sled. The reaction forces discussed herein may be distributed loads acting upon a surface area of each of the staple legs 110, 120 and the staple base portion 130. In various embodiments, the staple 100 is encouraged to roll laterally in the direction of the applied moment M_S to control which walls of the staple cavity are going to be contacted for staple guidance as the staple 100 is ejected from the staple's 100 corresponding staple cavity.

[0135] FIGS. 5 and 6 illustrate a wire-formed staple 200 comprising staple legs 210 and a staple base portion 230. The staple legs 210 are offset and bent at a substantially ninety degree angle from the staple base portion 230. The staple legs 210 reside in a first plane which is at least substantially perpendicular to a second plane defined by the staple base portion 230 and the bend portions 220 of the staple legs 210.

[0136] FIGS. 7-10 illustrate a staple 300 comprising a proximal staple leg 310, a distal staple leg 320, and a staple base portion, or crown, 330 having a drive surface 332. The staple legs 310, 320 extend from the staple base portion 330 and each staple leg 310, 320 comprises a laterally outward bend portion and an upward bend portion. The laterally outward bend portions of the staple legs bend the staple legs laterally outward with respect to the staple base portion. The upward bend portions of the staple legs bend the staple legs vertically with respect to the staple base portion. The staple 300 comprises a first zone 331 comprising a first hardness, second zones 311, 321 comprising a second hardness, and third zones 312, 322 comprising a third hardness. Embodiments are envisioned where the staple 300 comprises more or less zones than depicted. Varying certain properties, such as the hardness, of different portions of the staple 300 can provide greater control and predictability when forming the staple against corresponding forming pockets such as forming pockets 341 of anvil 340, for example. The first hardness of the first zone 331 may be greater than that of the second hardness of the second zones 311, 321. In many instances, it is desirable to have ductile staple legs 310, 320 capable of permanently changing shape without fracture or, in other

words, having staple legs 310, 320 with a high plasticity, while having a staple base portion 330 that supports the staple legs 310, 320 and comprises a hardness greater than the staple legs 310, 320, for example. A greater hardness would increase the staple base portion's 330 ability to resist deformation upon the application of an external and/or internal force, such as a force from the staple legs upon being compressed against the anvil, for example.

[0137] Metal working different portions of the staples disclosed herein can comprise several advantages. One of these advantages may include being able to prevent crushing, or buckling, of the staple legs during formation and, instead, encourage the staple legs to deform in a desired configuration as a result of the contact with the corresponding forming pockets.

[0138] The staple 300 may be formed into any desired formation. In an unformed configuration, the staple legs 310, 320 define a first plane P_1 and the staple base portion 330 defines a second plane P_2 . Shown in FIGS. 9 and 10 is an example of a formation of the staple 300 in which the staple legs 310, 320 are formed laterally toward the second plane P_2 . Variations in hardness of certain zones and/or portions of the staple 300 can be responsible for providing directional encouragement when contacting the forming pockets 341. Embodiments are envisioned where the staple legs 310, 320 are formed in a direction laterally away from the second plane P_2 .

[0139] FIGS. 11-11C depict a staple 400 comprising staple legs 410 and a staple base portion 430 formed from a flat sheet of material. The staple base portion 430 comprises a rectangular cross-sectional profile 431 and the staple legs comprise a round cross-sectional profile 411. Having round staple legs 410 that extend from a staple base portion 430 having the rectangular cross-sectional profile 431 can provide a staple base portion and staple legs with no preferential bending planes. The staple 400 comprises bend portions 420 where the staple legs 410 extend from the staple base portion 430. The bend portions 420 comprise a substantially square cross-sectional profile 421. The square profile 421 and the rectangular profile 431 of the bend portions 420 and the staple base portion 430, respectively, provide a stiff connection and backbone to the round staple legs 410. The round staple legs 410 eliminate preferential bending planes that staple legs with a square, rectangular, or any shape with vertices or a non-uniform shape, cross-sections could have.

[0140] FIG. 12 depicts a staple 500 in accordance with at least one embodiment comprising a proximal staple leg 510, a distal staple leg 520, and a staple base portion 530 from which the staple legs 510, 520 extend. The proximal staple leg 510 is bent laterally outward from the staple base portion 530 in a first direction. The distal staple leg 520 is bent laterally outward from the staple

base portion in a second direction. The first direction is opposite the second direction. The staple base portion 530 defines a first plane and the staple legs 510, 520 define a second plane which intersects the first plane. One advantage of having the staple legs 510, 520 bent in opposite directions can help prevent lateral roll by counteracting the applied sled moment on each side of the staple base portion 530. This results in an S-shaped configuration and requires complimentary forming pockets.

[0141] A staple 600 is depicted in FIG. 13 comprising a proximal leg 610, a distal leg 620, and a staple base portion 630 having a drive surface 632. The distal leg 620 is longer than the proximal leg 610 resulting in an offset contact timing of the tips 611, 621 of the staple legs 610, 620 against the forming pockets of the anvil. In various embodiments, the distal leg may comprise a tip that comprises an initial pre-bent configuration to aid in the forming process when initially contacting the anvil. This pre-formed tip 621 would require less compressive force than the staple tip 611 to begin deformation against the anvil. Having the longer staple leg, in this case the distal staple leg 620, contact the anvil before the shorter, or proximal, staple leg, 610 may require the staple tip 621 of the longer leg 620 to have, to a certain degree, a pre-formed tip before the tip 611 is deformed.

[0142] FIG. 14 illustrates an arrangement 700 of formed staples 711, 721. The staples 711 are arranged in a first row 710 and the staples 721 are arranged in a second row 720 which is adjacent to the first row 710. The staples 711, 712 may be similar to that of the staple 600 illustrated in FIG. 13 discussed above. The staples 711 comprise laterally opposing legs 713, 715. The staples 721 comprise laterally opposing legs 723, 725. The laterally opposing legs 713, 715 each comprise tips configured to contact forming pockets of an anvil at contact points 713c, 715c, respectively. The laterally opposing legs 723, 725 also each comprise tips configured to contact forming pockets of an anvil at contact points 723c, 725c, respectively. The laterally opposing legs 713, 715 each form inwardly toward the staple base portion from which they extend. The laterally opposing legs 723, 725 also each form inwardly toward the staple base portion from which they extend.

[0143] The staple rows 710, 720 are interwoven such that the contact points 723c, 713c are in substantial alignment. Such an arrangement allows for a more densely arranged staple row configuration in a staple cartridge and/or a more densely arranged forming pocket configuration on an anvil. Also, intersecting purchase planes may provide for a higher quality purchase and a larger area of purchase coverage in the tissue. The intersecting purchase planes may guarantee that anything captured between the staple rows and the forming pockets is guaranteed to be adequately

fastened. This can help when stapling smaller vessels and/or not easily visible vessels that, in conventional staple arrangements, may navigate staple row separations resulting in less than adequate fastening.

[0144] FIGS. 15-17 depict a staple 800 comprising staple legs 810, 820 and a staple base portion 830 having a drive surface 832. The staple legs 810, 820 comprise tips 842 configured to contact forming pockets of an anvil, such as forming pocket 861 of the anvil 860, for example. The staple tips 842 comprise a piercing tip, or portion, 842T, a curling surface 842S, and a concave cutout portion 842C. The piercing tip 842T is configured to pierce the tissue T upon ejection from the staple cartridge and, once in contact with the forming pocket 861 of the anvil 860, deform within the forming pocket 861. Deformation of the staple tip 842 is encouraged into a certain formation by utilizing the predictable deformability of the concave cutout portion 842C. The curling surface 842S of the staple tip 842 is configured to curl, or deform, from a piercing position 812A, to an intermediate formed position 812B, and to a non-piercing position 812C. Once the staple tip 842 has deformed completely, the piercing tip 842T is shielded, or isolated, from the tissue T by the curling surface 842S. This prevents further piercing of the tissue T after the tip 842 pierces the tissue upon ejection. This arrangement also prevents further injury and/or unwanted irritation that a piercing tip that is exposed after the initial piercing could possibly inflict. Preventing further piercing of the tissue T after the legs are formed also lessens the chance of the staple 800 being pulled through the tissue T. The curling surface 842S acts as a shield configured to shield the piercing tip 842T from the tissue T.

[0145] FIG. 18 depicts multiple examples of different types of staple tips 871, 872, 873, 874, and 875 that can be employed with any suitable surgical staple such as the staples disclosed herein. Staple tip 871 comprises a triangular shape with an at least substantially flat face. Staple tip 872 comprises a face with a varying contour. Staple tip 873 comprises a rocket-like shape. Staple tip 874 comprises a nub-like profile. The nub-like profile may be substantially dull, for example. Staple tip 875 comprises a pencil-sharpened profile.

[0146] In various embodiments, the staple tips disclosed herein may comprise a material different than that of the staple to which the staple tip is connected in order to make deforming in the fashion desired easier, however, the staple tip material can still be strong enough to prevent unfolding of the staple tip after fastening tissue.

[0147] Surgical staples can be encouraged to form into a desired configuration by changing the shape, size, configuration, and/or other aspects of the forming pockets configured to form the staples. FIG. 19 depicts forming pockets 911, 921 configured to form a staple 900. The staple 900 comprises staple legs 901, 902, staple tips 910, 920, and a staple base 930, wherein the staples legs 901, 902 extend from the staple base 930. The staple 900 is configured to contact and form against the corresponding forming pockets 911, 921. The forming pocket 911 comprises a forming channel surface 917 configured to receive a corresponding tip 910 and encourage the tip 910 to form in a direction P1. Shown in FIG. 20, the forming pocket 911 comprises lateral valley-like surfaces 915 and longitudinal valley-like surfaces 913 configured to funnel, or catch, the tip 910 of the staple in the event of minor misalignment upon contact. The staple 900, staple leg 901, and/or staple tip 910 may be driven off target with respect to the forming channel surface 917 upon ejection from the cartridge. The valley-like surfaces permit longitudinal and lateral roll of the staple. Although illustrated as concave surfaces, the valley surfaces may be convex or flat, for example.

[0148] The forming pocket 921 comprises a forming channel surface 927 configured to receive a corresponding tip 920 of the staple 900 and encourage the tip 920 to form in a direction D1. The direction D1 is opposite the direction P1 and, as shown in FIG. 19, illustrates an instance in which the staple legs are formed toward each other and at least substantially parallel to the staple base 930. Other embodiments are envisioned where the directions D1, P1 direct the corresponding staple legs in opposite directions but outward with respect to each other. The forming pocket 921 further comprises lateral valley-like surfaces 925 and longitudinal valley like surfaces 923 configured to funnel, or catch, the tip 920 of the staple 900 in the event of minor misalignment upon contact. The staple 900, staple leg 902, and/or staple tip 920 may be driven off target with respect to the forming channel surface 927 upon ejection from the cartridge.

[0149] In various embodiments, the longitudinal valley-like surfaces may comprise two separate valley surfaces. The two separate valley surfaces may comprise an initial valley surface nearest the intended point of contact for the corresponding staple tip. The initial valley surface may comprise a larger range of misalignment protection than the other of the separate valley surfaces. The initial valley surface may comprise a larger width and/or height than the other of the separate valley surfaces, for example.

[0150] FIG. 21 depicts another arrangement of the staple pockets 911, 921 discussed above. However, the staple pockets 911, 921 in the illustrated arrangement are configured to direct the

staple tips inward toward the staple base 130. The leg 901 and tip 910 are configured to be formed in direction P2. The leg 902 and tip 920 are configured to be formed in direction D2. The directions P2, D2 are transverse. Other embodiments are envisioned where the directions P2, D2 direct the corresponding staple legs and tips away from the staple base, or outward.

[0151] FIG. 22 depicts yet another arrangement of the staple pockets 911, 921 discussed above. The staple pockets 911, 921 in the illustrated arrangement are configured to form the corresponding staple legs 901, 902 and tips 910, 920 in opposite directions where one of the staple legs 902 is directed toward the staple base 930 and one of the staple legs 901 is directed away from the staple base 930. The leg 901 and tip 910 are configured to form in direction P3. The leg 902 and tip 920 are configured to form in direction D3. The directions P3, D3 are at least substantially parallel. Other embodiments are envisioned where the directions P3, D3 are not parallel.

[0152] FIGS. 23 and 24 depict another embodiment of forming pockets comprising forming pockets 1011, 1021 configured to deform the staple 900. The forming pockets 1011, 1021 comprise an ear-like shape providing nested pockets. This type of arrangement can save space on the staple forming surface of an anvil to allow for more staple pockets and, as a result, more staples in a staple cartridge in a lesser amount of space. The forming pocket 1011 comprises a forming channel surface 1017 configured to receive the corresponding tip 910 and encourage the tip 910 to form in a curved direction P4. Shown in FIG. 24, the forming pocket 1011 comprises a first valley-like, curved surface 1015A and a second valley-like, curved surface 1015B configured to funnel, or catch, the tip 910 of the staple in the event of minor misalignment during contact. The staple 900, staple leg 901, and/or staple tip 910 may be driven off target with respect to the forming channel surface 917 upon ejection from its staple cavity. The valley-like surfaces permit some longitudinal and lateral roll of the staple. Although illustrated as concave surfaces, the valley surfaces may be convex or flat, for example.

[0153] The forming pocket 1021 comprises a forming channel surface 1027 configured to receive the corresponding tip 920 of the staple 900 and encourage the tip 920 to form in a direction D4.

FIG. 23 illustrates an instance in which the staple legs 901, 902 are formed toward each other with one staple leg 901 formed away from the staple base 930 and one staple leg 902 formed toward the staple base 930. Other embodiments are envisioned where the directions P4, D4 direct the corresponding staple legs 901, 902 in opposite directions but outward with respect to each other. The forming pocket 1021 comprises a first valley-like, curved surface 1025A and a second valley-

like, curved surface 1025B configured to funnel, or catch, the tip 920 of the staple 900 in the event of minor misalignment before and/or during contact.

[0154] FIG. 25 depicts yet another embodiment of forming pockets comprising anvil forming pockets 1111, 1121 configured to deform corresponding staple legs 901, 902 and tips 910, 920 toward the staple base 930. The forming pockets 1111, 1121 are trapezoidal in shape and can be nested with other similar forming pockets using less space on a forming surface of an anvil. The forming pockets 1111, 1121 are configured to form the staple legs 901, 902 and tips 910, 920 in directions P5, D5, respectively.

[0155] FIG. 26 depicts yet another embodiment of forming pockets comprising anvil forming pockets 1211, 1221 configured to deform corresponding staple legs 901, 902 and tips 910, 920 in directions P6, D6, respectively. The forming pockets 1111, 1121 are triangular in shape and can be nested with each other comprising an even more compact forming pocket arrangement on an anvil of a surgical stapling instrument.

[0156] Referring now to FIGS. 27-27B, a staple leg 1300 is depicted. The staple leg 1300 comprises a substantially round staple tip with a substantially square staple leg and a staple leg body portion 1301. The staple leg 1300 comprises hardened corners formed using a coining process, for example, where the corners 1303A, 1303B, 1303C, and 1303D were rounded in order to create preferential bending planes. Stated another way, the staple leg 1300 comprises a cross-sectional profile configured to encourage the staple leg 1300 to bend in a certain direction due to the corner hardening upon contact with an anvil. The corners 1303A, 1303B, 1303C, and 1303D may vary in hardness from one corner to the next, or, may comprise two corners with a first hardness and the other two corners with a second hardness. The corners 1303A, 1303B, 1303C, and 1303D may be coined to provide different radial profiles on the same staple leg. For example, the corner 1303A comprises a radial profile with a radius R_A greater than the radius R_B of the radial profile of corner 1303B shown in FIG. 27B.

[0157] Portions of the staples disclosed herein may be hardened at various times of the manufacturing process with any suitable means. For example, hardening process may include bronzing, chemical vapor deposition, physical vapor deposition, laser surface treatment, thermal oxidation, ion nitriding, and/or solid state diffusion, for example. Other portions of the staples may be prevented from being hardened by these processes. Other portions of the staples may be locally

annealed, such as the staple tips, for example. Increasing hardness in certain areas can increase the force required to uniform the staples after the staples have assumed a fired configuration.

[0158] FIGS. 28-28C depict a staple 1400 and a sled 1460 in accordance with at least one embodiment. The staple 1400 comprises staple legs 1410, 1420, a staple base portion 1430 from which the staple legs 1410, 1420 extend, a drive surface 1432, and a bottom surface 1431. The staple legs 1410, 1420 extend from the staple base portion 1430 in a plane which is a parallel and offset with respect to a plane defined by the staple base portion 1430. The staple 1400 is made with progressive die stamping utilizing a base strip 1450 and a connector portion 1451. Although only a single staple 1400 is shown, a plurality of staples 1400 are attached to the base strip 1450. The connector portion 1451 connects the staple 1400, specifically the staple base portion 1430, to the base strip 1450. The connector portion 1451 comprises a discontinuity, or notch, 1453 configured to permit the staples 1400 to detach from the strip 1450. In at least one instance, the sled 1460 comprises release portions, or striking portions, 1461. The release portions 1461 of the sled 1460 are configured to engage the discontinuities 1453, or connector portions 1451, to separate, break, and/or shear, the staples 1400 from the base strip 1450 and permit the staples to be ejected from their staple cavities by the sled 1460.

[0159] Embodiments are envisioned where the base strip 1450 comprises alignment features such as holes, for example, which engage corresponding alignment features on a staple cartridge. Such alignment features may comprise protrusions, for example, that align with the alignment features of the base strip 1450. In various instances, a person loading the staples into the cartridge could align the staples with the staple cavities and/or align the alignment features before pushing the staples into the staple cavities. Certain embodiments are envisioned in which the staple cartridge comprises engagement features configured to engage the discontinuities 1453 when the strip assemblies are loaded into the staple cartridge. The engagement features allow the staples 1400 to be separated from the strip 1450 when the staples 1400 are loaded into a staple cartridge instead of when the staples 1400 are fired. Manufacturing staples using progressive die stamping can permit staples to have different crown sizes, shapes, and/or configurations as well as staple leg sizes, shapes, and/or configurations. Another advantage of using progressive die stamping technology may include the ability to alter the spacing of the rows of staples in which the staples are aligned.

[0160] FIGS. 29 and 30 depict another embodiment of a strip 1500 of staples 1501 made with progressive die stamping. The strip 1500 of staples 1501 comprises a base strip 1550, a connector

portion 1551, and staples 1501. Each staple 1501 comprises, one, a staple base portion 1530 comprising a bottom surface 1531 and, two, staple legs 1510 extending from the staple base portion 1530. The connector portion 1551 attaches the bottom surface 1531 of the staple base portion 1530 to the base strip 1550. The staple legs are bent up from the staple base portion 1530 such that the legs 1510 reside in a plane which is offset and at least substantially parallel to a plane defined by the staple base portion 1530. In the illustrated embodiment, the staple legs 1510 are bent in a direction opposite to that of the connector portion 1551. Bending the legs 1510 and the connector portions 1551 in this manner can permit a more dense staple row arrangement. The connector portions 1551 can comprise a discontinuity enabling the staples 1501 to be released from the base strip 1550 upon loading the staples 1501 into a staple cartridge and/or firing the staples 1501 from the staple cartridge as discussed in the previous embodiment.

[0161] FIG. 31 depicts a plurality of staples 1601 and a cross-sectional view of a portion of a staple cartridge 1650 in accordance with at least one embodiment. The staples 1601 are removably stored within corresponding staple cavities 1651 of the staple cartridge 1650. The staple cartridge 1650 comprises a deck surface 1653 and staple leg supports 1655. The staples 1601 comprise, one, staple legs 1610 which each comprise a staple tip 1611 and, two, a staple base portion 1630 from which the staple legs 1610 extend. Each staple 1601 comprises a pre-load configuration, a loaded configuration, and a fired configuration where the staple 1601 is ejected from the staple cartridge 1650 and formed against corresponding forming pockets of an anvil. The staple legs 1610 are bent outwardly with respect to the staple base portions 1630 in the pre-load configuration. The staple legs 1610 are biased against sidewalls of the corresponding staple cavity 1651 in the loaded configuration and define a first distance X between the tips 1611 of the staple legs 1610. In the pre-load configuration, the distance between the staple tips 1611 of the staple legs 1610 is greater than X . This biasing force helps support the staples 1601 in the staple cartridge 1650.

[0162] A staple cartridge 2000 is illustrated in FIGS. 32-34. The staple cartridge assembly 2000 comprises a cartridge body 2010. The cartridge body 2010 is positionable in and removable from a jaw of a surgical stapling instrument. As a result, the staple cartridge 2000 is replaceable; however, other embodiments are envisioned in which the staple cartridge 2000 is not replaceable. The cartridge body 2010 comprises a proximal end 2011, a distal end 2012, and a deck 2014 extending between the proximal end 2011 and the distal end 2012. The deck 2014 is configured to support the tissue of a patient when the tissue is compressed against the deck 2014.

[0163] The cartridge body 2010 further comprises a plurality of staple cavities 2020 defined therein. The staple cavities 2020 are arranged in six longitudinal rows extending between the proximal end 2011 and the distal end 2012; however, any suitable arrangement of staple cavities 2020 can be utilized. A staple, such as staple 2130 (FIG. 40), for example, is removably stored in each staple cavity 2020. As discussed in greater detail below, the staples are ejected from the staple cavities 2020 by a firing member when the firing member is moved from the proximal end 2011 of the cartridge body 2010 toward the distal end 2012.

[0164] Further to the above, the staples are moved from an unfired position to a fired position by the firing member. The firing member lifts the staples toward an anvil, such as anvil 2190 (FIG. 37), for example, to deform the staples between an unfired, undeformed configuration and a fired, deformed configuration. The cartridge body 2010 further comprises a longitudinal slot 2013 defined therein. The slot 2013 is configured to receive the staple firing member and/or a tissue cutting member therein when the staples are ejected from the staple cavities 2020.

[0165] In various embodiments, further to the above, the staples do not protrude above the deck 2014 until they are moved toward the anvil by the firing member. Such embodiments may frequently utilize small staples. In other embodiments, the legs of the staples protrude above the deck 2014 when the staples are in their unfired positions. In at least one such embodiment, the cartridge body 2010 further comprises projections 2050 extending from the deck 2014. The projections 2050 extend the staple cavities 2020 above the deck 2014 and guide the staples toward the anvil when the staples are being ejected from the staple cartridge 2000. In such embodiments, the staples may not extend above the projections 2050 until they are moved toward the anvil by the firing member.

[0166] Referring primarily to FIG. 34, the projections 2050 do not extend around the entirety of the staple cavities 2020. A first projection 2050 is positioned adjacent a first end of each cavity 2020 and a second projection 2050 is positioned adjacent a second end of each cavity 2020. Each first projection 2050 extends around a first staple leg guide 2022 of a staple cavity 2020 and each second projection 2050 extends around a second staple leg guide 2023 of the staple cavity 2020. Each first projection 2050 provides a proximal bracket which can control and guide the proximal leg of a staple and each second projection 2050 provides a distal bracket which can control and guide the distal leg of the staple. The first projection 2050 of each staple cavity 2020 is not symmetrical with respect to the first end of the staple cavity 2020 and does not extend around the

entirety of the first end of the cavity 2020. Similarly, the second projection 2050 of each staple cavity 2020 is not symmetrical with respect to the second end of the staple cavity 2020 and does not extend around the entirety of the second end of the cavity 2020. The first projection 2050 and the second projection 2050 comprise mirror images of one another and are symmetrically arranged with respect to the center of each staple cavity 2020; however, any suitable arrangement of projections could be utilized.

[0167] As illustrated in FIGS. 32-34, the cartridge body 2010 comprises steps 2014' and steps 2014'' which extend upwardly from the deck 2014. More specifically, the steps 2014' extend upwardly from the deck 2014 and the steps 2014'' extend upwardly from the steps 2014'. As a result, the steps 2014'' may apply a larger compressive pressure to the tissue than the steps 2014' and, similarly, the steps 2014' may apply a larger compressive pressure to the tissue than the deck 2014. The steps 2014' and 2014'' comprise staggered longitudinal plateaus; however, the steps 2014' and 2014'' may comprise any suitable configuration. Moreover, further to the above, the projections 2050 extending from the steps 2014'' extend above the projections 2050 extending from the steps 2014' and, similarly, the projections 2050 extending from the steps 2014' extend above the projections 2050 extending from the deck 2014. Stated another way, the projections 2050 extending from the deck 2014, the steps 2014', and the steps 2014'' are staggered.

[0168] A staple cartridge 2100 is illustrated in FIGS. 35-38. The staple cartridge assembly 2100 comprises a cartridge body 2110 and is similar to the staple cartridge assembly 2000 and/or the other staple cartridges disclosed herein in many respects. The cartridge body 2110 comprises a deck 2114, a plurality of staple cavities 2120a, and a plurality of staple cavities 2120b. The staple cavities 2120a are similar to the staple cavities 2120b in many respects. For instance, the staple cavities 2120a and 2120b both comprise a central slot 2121 having a proximal end and a distal end, a proximal staple leg guide 2122 extending laterally from the proximal end of the central slot 2121, and a distal staple leg guide 2123 extending laterally from the distal end of the central slot 2121. That said, the staple cavities 2120a and the staple cavities 2120b are oriented in different directions. More particularly, the staple leg guides 2122, 2123 of the staple cavities 2120a extend toward the staple cavities 2120b and, similarly, the staple leg guides 2122, 2123 of the staple cavities 2120b extend toward the staple cavities 2120a; however, any suitable arrangement can be utilized.

[0169] A staple 2130a is positioned in each staple cavity 2120a and a staple 2130b is positioned in each staple cavity 2120b. The staples 2130a and the staples 2130b are similar in many respects.

For instance, each staple 2130a comprises a base, or crown, 2131, a proximal leg 2132 extending from a proximal end of the base 2131, and a distal leg 2133 extending from a distal end of the base 2131. That said, the staples 2130a, 2130b are adapted in a manner to fit within the staple cavities 2120a, 2120b, respectively. For example, when the staples 2130a are positioned in the staple cavities 2120a and the staples 2130b are positioned in the staple cavities 2120b, the legs 2132, 2133 of the staples 2130a extend toward the staples 2130b and the legs 2132, 2133 of the staples 2130b extend toward the staples 2130a; however, other arrangements are possible.

[0170] Further to the above, the proximal legs 2132 of the staples 2130a, 2130b are positioned within the staple leg guides 2122 when the staples 2130a, 2130b are stored in the staple cavities 2120a, 2120b, respectively. Similarly, the distal legs 2133 of the staples 2130a, 2130b are positioned within the staple leg guides 2123 when the staples 2130a, 2130b are stored in the staple cavities 2120a, 2120b, respectively. Moreover, the bases 2131 of the staples 2130a, 2130b are positioned in the central slots 2121 of the staple cavities 2120 when the staples 2130a, 2130b are stored in the staple cavities 2120a, 2120b, respectively. Referring primarily to FIG. 35, the tips of the staple legs 2132, 2133 extend above the deck 2114 of the cartridge body 2110 when the staples 2130a, 2130b are in their unfired positions. That said, the tips of the staple legs 2132 are at least partially surrounded by proximal projections 2152 extending from the deck 2114 and the tips of the staple legs 2133 are at least partially surrounded by distal projections 2153 extending from the deck 2114. The proximal projections 2152 extend around the proximal staple leg guides 2122, but they do not extend around the proximal ends of the central slots 2121. Similarly, the distal projections 2153 extend around the distal staple leg guides 2123, but they do not extend around the distal ends of the central slots 2121.

[0171] Turning now to FIG. 38, each proximal projection 2152 comprises a first portion 2154 which extends around a proximal side of the proximal guide slot 2122 and a second portion 2155 which extends around a lateral side of the proximal guide slot 2122. The proximal projection 2152 does not extend around a distal side of the proximal guide slot 2122; however, it is envisioned that the proximal projection 2152 can extend around the distal side of the proximal guide slot in alternative embodiments. Similarly, each distal projection 2153 comprises a first portion which extends around a distal side of the distal guide slot 2123 and a second portion which extends around a lateral side of the distal guide slot 2123. The distal projection 2153 does not extend around a proximal side of the distal guide slot 2123; however, it is envisioned that the distal projection 2153

can extend around the proximal side of the distal guide slot in alternative embodiments. In any event, the arrangement depicted in FIG. 38 protects the staple legs 2132, 2133 when the staples 2130a, 2130b are in their unfired positions and, in addition, guide the staples 2130a, 2130b as the staples are being fired. Such an arrangement also appropriately controls the flow of tissue relative to the deck 2114 of the cartridge body 2110.

[0172] Referring again to FIG. 38, the staple cavities 2120a and the staples 2130a are sized and configured such that clearance gaps are provided between the staples 2130a and the staple cavities 2120a. For example, a clearance gap 2156 is present between the proximal leg 2132 of a staple 2130b and the proximal sidewall of the proximal guide slot 2122 and, similarly, a clearance gap 2158 is present between the proximal leg 2132 of the staple 2130b and the distal sidewall of the proximal guide slot 2122. In addition, a clearance gap 2157 is present between the lateral side of the proximal leg 2132 and the lateral sidewall of the proximal guide slot 2122. Similar gaps can be found between the distal leg 2133 and the distal guide slot 2123. Lateral clearance gaps 2126, 2127 can also be provided between the base 2131 of the staple 2130b and the lateral sides of the central slot 2121. Such clearance gaps may be transient and the staple may contact one or more of the sidewalls nonetheless.

[0173] A staple cartridge 2200 is illustrated in FIG. 43. The staple cartridge 2200 is similar to the staple cartridges 2000, 2100 and the other staple cartridges disclosed herein in many respects. The staple cartridge 2200 comprises a cartridge body 2210 including staple cavities 2220 defined therein. Each of the staple cavities 2220 has a staple, such as staple 2130, for example, removably stored therein. Each staple cavity 2220 comprises a first guide slot 2222 configured to guide the leg 2132 of the staple 2130, a second guide slot 2223 configured to guide the leg 2133 of the staple 2130, and a central slot 2221. The guide slots 2222 and 2223 extend laterally from the central slot 2221 and the central slot 2221 includes an intermediate guide 2225 configured to guide the base 2131 of the staple 2130. The first guide slot 2222 is sized and configured such that the staple leg 2132 is closely received in a corner of the first guide slot 2222. Similarly, the second guide slot 2223 is sized and configured such that the staple leg 2133 is closely received in a corner of the second guide slot 2223. The intermediate guide 2225 is sized and configured to limit the lateral movement of the staple 2130 within the staple cavity 2220. Moreover, the intermediate guide 2225 is sized and configured to hold the staple legs 2132 and 2133 in the staple leg guide slots 2222 and 2223, respectively.

[0174] As discussed above, the intermediate guide 2225 is sized and configured to hold the staple legs 2132 and 2133 against the sidewalls of the guide slots 2222 and 2223, respectively. Such an arrangement creates lateral reaction forces, indicated as force vectors LT in FIG. 43, between the lateral sidewalls of the cavity 2220 and the staple 2130. Such lateral reaction forces generate friction forces between the sidewalls of the cavity 2220 and the staple 2130 when the staple 2130 is ejected from the cavity 2220. It should be understood that friction forces are a function of the surface area in which they are applied and, as such, the intermediate guide 2225 does not extend along the entire length of the central slot 2221. That said, the intermediate guide 2225 has a longitudinal length which is sufficient to control the orientation of the staple 2130 within the cavity 2220. Moreover, the intermediate guide 2225 has a sufficient vertical length sufficient to control the orientation of the staple 2130 during the firing stroke of the staple 2130. In at least one instance, the guide 2225 extends along the entire vertical depth of the cavity 2220.

[0175] The intermediate guide 2225 is flat and is configured to interface with a flat surface defined on the lateral side of the base 2131 of the staple 2130; however, any suitable arrangement could be utilized. In certain alternative embodiments, the intermediate guide 2225 comprises a resilient biasing member configured to apply a lateral biasing force to the base 2131 of the staple 2130, for example. In at least one instance, the resilient biasing member could comprise a cantilever spring, for example.

[0176] The staple cavity 2220 does not include a lateral guide positioned opposite the lateral intermediate guide 2225. In fact, a clearance gap 2229 is present between a lateral sidewall 2228 and the staple 2130.

[0177] Further to the above, referring again to FIG. 43, the staple 2130 is not positioned in the ends of the central slot 2221. More particularly, the central slot 2221 of the cavity 2220 comprises a proximal end 2226 and a distal end 2227 and the staple 2130 does not extend into either the proximal end 2226 or the distal end 2227. Rather, clearance gaps are present between the ends 2226, 2227 and the staple 2130. Such clearance gaps extend between the ends 2226, 2227 and the intermediate guide 2225. As a result, the ends 2226, 2227 of the staple cavity 2220 do not control the longitudinal position of the staple 2130. Instead, the staple leg guides 2222, 2223 control the longitudinal position of the staple 2130. In fact, the legs 2132 and 2133 of the staple 2130 can be biased inwardly by the staple leg guides 2222 and 2223, respectively. Such an arrangement creates longitudinal reaction forces, indicated as force vectors LG in FIG. 43.

[0178] As a result of the above, the staple cavity 2220 comprises three control points, or positions, in which the staple cavity 2220 controls the orientation of the staple 2130. These control points comprise discrete control positions with clearance gaps defined therebetween. Stated another way, the guides 2222, 2223, and 2225 triangulate the control of the staple 2130. Alternative embodiments are envisioned which comprise more than three control points. In any event, the control points provided by the staple leg guides 2222 and 2223 are defined in a first control plane. An intermediate control point provided by the intermediate guide 2225 is defined in a second control plane. The first control plane and the second control plane are parallel; however, alternative embodiments are envisioned in which the first control plane and the second control plane are not parallel. Moreover, the first control plane is aligned with, or adjacent to, the staple legs 2132 and 2133 of the staple 2130 and the second control plane is aligned with, or adjacent to, the base 2131 of the staple 2130.

[0179] A staple cartridge 2700 is illustrated in FIG. 65. The staple cartridge 2700 comprises a cartridge body 2710 which includes a deck 2714 and a plurality of staple cavities 2220 defined in the deck 2714. Similar to the cartridge body 2110, the cartridge body 2710 includes projections 2752 and 2753 which extend above the deck 2714. The projections 2752 at least partially surround the staple leg guides 2222 of the staple cavities 2220 and the projections 2753 at least partially surround the staple leg guides 2223 of the staple cavities 2220. Similar to projections 2152, 2153, the projections 2752, 2753 each include an outside portion 2754 and a lateral portion 2755. The outside portions 2754 are positioned longitudinally with respect to the staple leg guides 2222 and 2223 while the lateral portions 2755 are positioned laterally with respect to the staple leg guides 2222 and 2223. Unlike the projections 2152, 2153, the projections 2752, 2753 each include an inner portion 2756 which are positioned longitudinally with respect to the staple leg guides 2222 and 2223. The inner portions 2756 are connected to the lateral portions 2755 and the lateral portions 2755 are connected to the outside portions 2754. Similar to the above, the projections 2752, 2753 extend the staple cavities 2220 above the deck 2714.

[0180] A staple cartridge 2800 is illustrated in FIG. 66. The staple cartridge 2800 comprises a cartridge body 2810 which includes a deck 2814 and a plurality of staple cavities 2220 defined in the deck 2814. Similar to the cartridge body 2110, the cartridge body 2810 includes projections 2152, 2153 which extend above the deck 2114. As outlined above, the projections 2152 at least partially surround the staple leg guides 2222 of the staple cavities 2220 and the projections 2753 at

least partially surround the staple leg guides 2223 of the staple cavities 2220. Moreover, the cartridge body 2810 includes inner projections 2856 which are positioned longitudinally with respect to the staple leg guides 2222 and 2223. The inner projections 2856 are not connected to the projections 2152, 2153.

[0181] Referring again to FIG. 35, the staples 2130 are driven between unfired positions and fired positions by a firing member, such as sled 2140, for example. The sled 2140 comprises wedges 2145 which are configured to directly engage the staples 2130 and lift the staples 2130 toward an anvil, such as anvil 2190, for example, as illustrated in FIG. 37. The sled 2140 comprises a wedge 2145 for each longitudinal row of staples 2130; however, the sled 2140 may have any suitable number of wedges 2145. Each wedge 2145 comprises an angled drive surface 2141 which slides under the staples 2130 as the sled 2140 is advanced from the proximal end of the staple cartridge 2100 toward the distal end of the staple cartridge 2100. The base 2131 of each staple 2130 comprises an angled drive surface 2135 which is directly contacted by a drive surface 2141. Stated another way, each staple 2130 comprises its own integrally-formed driver having a drive surface 2135. The staples 2130 are comprised of metal and, as a result, the integrally-formed driver is also comprised of metal. That said, the staples disclosed herein can be comprised of any suitable material.

[0182] Further to the above, each drive surface 2141 comprises an initial, or distal, portion 2142, a second, or intermediate, portion 2143, and a third, or apex, portion 2144. The initial portion 2142 extends at a first angle and provides an initial contact point for the sled 2140 against a staple 2130 as the sled 2140 is moved distally. As the initial portion 2142 slides under the staple 2130, the staple 2130 is lifted upwardly within the staple cavity 2120. As the sled 2140 continues to move distally, the intermediate portion 2143 comes into contact with the staple 2130. The intermediate portion 2143 extends at a second angle which is different than the first angle. The first angle can be steeper than the second angle when it is desirable for there to be a quick initial upward displacement of the staple 2130 whereas the first angle can be shallower than the second angle when it is desirable to provide a gradual initial upward displacement of the staple 2130. In either event, the staple 2130 contacts the anvil 2190 while the staple 2130 is being lifted upwardly by the intermediate portion 2143, as illustrated in FIG. 37; however, alternative embodiments are envisioned in which the staple 2130 contacts the anvil 2190 when the staple 2130 is being lifted upwardly by the initial portion 2142. In either event, the proximal leg 2132 of the staple 2130

contacts a proximal forming pocket 2192 defined in the anvil 2190 and the distal leg 2133 contacts a distal forming pocket 2193 defined in the anvil 2190. The forming pockets 2192 and 2193 are configured to bend the legs 2132 and 2133 inwardly to deform the staple 2130 and capture the tissue of a patient within the staple 2130. The apex 2144 of the drive surface 2141 slides under the staple 2130 to finish the forming process. The apex 2144 can comprise a peak of the drive surface 2141, a flat surface, and/or a surface which extends at a third angle which is different than the first angle and/or the second angle.

[0183] In various instances, each drive surface 2141 can comprise a portion which trails, or is positioned proximal to, the apex 2144 of the drive surface 2141. Such a trailing portion can be lower than the apex 2144, for example. Moreover, such a trailing portion can provide for a gradual decrease in forming pressure in the staples 2130, for example.

[0184] Turning now to FIG. 39, the staple 2130 further includes a foot 2134 which extends downwardly from the proximal leg 2132. When the staple 2130 is in its proper orientation in its staple cavity 2120, as illustrated in FIG. 41, the foot 2134 is not contacted by the sled 2140. In such instances, an alignment plateau 2146 of the sled 2140 passes under the foot 2134. When the staple 2130 is not in its proper orientation in its staple cavity 2120, as illustrated in FIG. 42, the sled 2140 can contact the staple 2130 and re-orient the staple 2130. For the purpose of comparison, an improperly oriented staple 2130 and a properly oriented staple 2130' are both illustrated in FIG. 42. The sled 2140 comprises an angled alignment ramp 2148 which is configured to contact the foot 2134 and rotate the staple 2130 into its proper orientation. After the alignment ramp 2148 has properly oriented the staple 2130, the alignment plateau 2146 can slide underneath the foot 2134. As can be appreciated from FIG. 39, the alignment ramp 2148, the alignment plateau 2146, and the foot 2134 are arranged in an alignment plane which is aligned with the forming plane of the legs 2132 and 2133 of the staple 2130. The alignment plane is adjacent to a lifting plane which includes the forming surface 2141 of the sled 2140 and the base 2131 of the staple 2130.

[0185] A staple cartridge assembly 2300 is illustrated in FIGS. 44-48. The staple cartridge assembly 2300 is similar to the staple cartridge 2000, 2100, 2200, and the other staple cartridges disclosed herein in many respects. The staple cartridge 2300 comprises a cartridge body 2310 and sleds 2340 which are configured to eject staples removably stored in the cartridge body 2310. Similar to sled 2140, sleds 2340 comprise staple forming ramps 2145. The ramps 2145 are slidably positioned in longitudinal slots 2115 defined in the cartridge body 2110 which are aligned with the

lifting portions, or planes, of the staples. Notably, as discussed in greater detail below, the slots 2115 have an open end defined in the bottom 2316 of the cartridge body 2310.

[0186] Further to the above, the staple cartridge assembly 2300 does not include a cover extending around the bottom 2316 of the cartridge body 2310. Referring primarily to FIG. 48, the cartridge body 2310 is directly positioned against the jaw 2180 of the stapling instrument. In embodiments where a staple cartridge is not readily removable from the jaw of a stapling instrument and not readily replaceable with another staple cartridge, the absence of a bottom cover is not necessarily problematic as the jaw 2180 can prevent the staples from falling out of the bottom of the staple cavities 2120 and/or the sleds 2340 from falling out of the bottom of the longitudinal slots 2115. The staple cartridge assembly 2300 is, however, replaceable and, even though it does not include a bottom cover, the staple cartridge assembly 2300 includes features which keep the staples and the sleds 2340 from falling out of the bottom 2316 of the cartridge body 2310, which are described in greater detail further below. Such features could be adapted to any of the staple cartridges disclosed herein.

[0187] Referring primarily to FIGS. 45-47, the cartridge body 2310 includes retention features configured to hold the sleds 2340 therein. For example, the cartridge body 2310 includes proximal retention features 2317 which are configured to hold the sleds 2340 in the longitudinal slots 2115 when the sleds 2340 are in their proximal, or unfired, positions. The sleds 2340 are in their unfired positions when the staple cartridge assembly 2300 is inserted, or loaded, into the jaw 2180 and, as a result, the proximal retention features 2317 retain the sleds 2340 in the cartridge body 2310 when the cartridge assembly 2300 is being handled by a clinician. Each retention feature 2317 includes an angled surface 2318 and a shoulder 2319. Each sled 2340 includes a corresponding recess 2348 configured to receive an angled surface 2318 and, in addition, a corresponding shoulder 2349 which can be aligned with and/or contact a shoulder 2319 of the retention feature 2317. When the sleds 2340 are inserted into the slots 2115, referring to FIG. 46, the ramps 2145 and/or the sidewalls of the cartridge 2310 can flex to permit the sleds 2340 to slide relative to the angled surfaces and then resiliently snap back to their original positions once the shoulders 2349 of the sleds 2340 have become aligned with the shoulders 2319 of the cartridge body 2310, as illustrated in FIG. 45. The retention features 2317 are also configured to prevent the sleds 2340 from sliding proximally out of the longitudinal slots 2115.

[0188] As a result of the above, the proximal retention features 2317 prevent the sleds 2340 from falling out of the cartridge body 2310 when a clinician is handling the staple cartridge assembly 2300. When the sleds 2340 are advanced distally to fire the staples, the sleds 2340 are no longer aligned with the proximal retention features 2317. At such point, however, the staple cartridge assembly 2300 is already in the jaw 2180 and sled retention features are no longer needed. That said, the cartridge body 2310 can include additional retention features which can hold the sleds 2340 in the cartridge body 2310 regardless of the position of the sleds 2340. Such retention features could be configured to hold the sleds 2340 in the cartridge body 2310 when the sleds 2340 are in their distal, or fully fired, positions, for example.

[0189] Further to the above, the staples of the staple cartridges disclosed herein can include one or more features configured to hold the staples in the staple cavities of the staple cartridge. Turning now to FIGS. 49 and 50, a staple 2330 includes a base 2331 and one or more staple legs 2332 extending from the base 2331. The staple 2330 is removably stored in a staple cavity 2320 in the cartridge body 2310, for example. The base 2331 comprises a protrusion 2338 extending therefrom which is engaged with a sidewall of the staple cavity 2320. The interaction between the protrusion 2338 and the staple cavity sidewall keeps the staple 2330 from falling out of the bottom 2316 of the cartridge body 2310. The interaction between the protrusion 2338 and the staple cavity sidewall comprises an interference fit; however, such an interference fit does not prevent the sleds 2340 from ejecting the staples 2330 from the staple cavities 2320. The protrusion 2338 can be formed in the base 2331 during a stamping process, for example. The stamping process can form the protrusion 2338 by creating a dent 2337 in the opposite side of the base 2331. The staple cavity 2320 includes a vertical groove 2328 which is aligned with the protrusion 2338. The groove 2328 increases the contact area between the sidewall of the staple cavity 2320 and the protrusion 2338. In addition, the groove 2328 can control the orientation of the staple 2330 within the staple cavity 2320. Alternative embodiments are envisioned which do not comprise the groove 2328.

[0190] In addition to or in lieu of the above, the staples stored in the staple cartridges disclosed herein can include staple legs which are resiliently engaged with the sidewalls of their staple cavities. Turning now to FIG. 51, a staple 2430 can include a base 2431 and staple legs 2432 and 2433 extending from the base 2431. The staples 2430 are similar to the staples 2130, 2330, and/or the other staples disclosed herein in many respects. A staple cartridge body 2410, for example, can include a plurality of staple cavities 2120 defined therein and a staple 2430 positioned in each staple

cavity 2120. FIG. 51 depicts a staple 2430 positioned inside a cavity 2120 and a staple 2430 positioned outside a staple cavity 2120 of the cartridge body 2430. When the staples 2430 are not positioned in the staple cavities 2120, the staple legs 2432, 2433 do not extend in parallel directions; rather, they extend outwardly away from each other. When the staples 2430 are positioned in the staple cavities 2120, they are flexed inwardly by the sidewalls of the staple cavities 2120. Stated another way, the staple legs 2432, 2433 are resiliently biased against the sidewalls of the staple cavities and, owing to this biased engagement, the staples 2430 are inhibited from falling out of the bottom 2436 of the cartridge body 2410. As illustrated in FIG. 51, the distance between the staple legs 2432, 2433 when the staples 2130 are positioned in the staple cavities 2120 is X while the distance between the staple legs 2432, 2433 when the staples 2130 are not positioned in the staple cavities is larger than X.

[0191] In various embodiments, a cartridge body can include one or more shoulders which are configured to keep the staples stored therein from falling out of the bottom of the cartridge body. The shoulders can at least partially extend underneath the staples.

[0192] In certain embodiments, the cartridge body of a staple cartridge assembly can be comprised of plastic and can be formed during an injection molding process, for example. The injection mold can include two halves which are movable toward and away from each other. The interface between the injection mold halves is often called a parting line and it is frequent that flashing, or seepage of the plastic between the mold halves, can occur at the parting line. In at least one embodiment, the parting line of an injection mold can be defined at the interfaces between the deck of the staple cartridge and the staple cavities defined in the deck. As a result of the above, plastic flashing can occur around the perimeter of the staple cavities. Such flashing can releasably hold the staples in the staple cartridge.

[0193] Referring again to FIG. 48, the cartridge body 2310 is configured to directly engage the jaw 2180. The jaw 2180 comprises one or more retention shoulders 2315 defined therein. The cartridge body 2310 comprises corresponding retention shoulders 2187 which co-operate with the retention shoulders 2315 to releasably retain the cartridge body 2310 in the jaw 2180. The cartridge body 2310 and/or the jaw 2180 further comprise ramp surfaces 2314 which are configured to facilitate the insertion of the cartridge body 2310 into the jaw 2180. As a result of the above, the cartridge body 2310 can have a snap-fit relationship with the jaw 2180. The snap-fit relationship

can be overcome by prying the cartridge body 2310 out of the jaw 2180 such that the staple cartridge assembly 2300 can be replaced.

[0194] A staple 2530 is illustrated in FIGS. 52-56. The staple 2530 is similar to the staples 2130, 2330, 2340, and/or the other staples disclosed herein in many respects. The staple 2530 comprises a base 2531 and legs 2532 and 2533 extending from the base 2531. The staple 2530 also includes a projection 2538 extending upwardly from the base 2531. The projection 2538 is aligned with the staple driving plane which includes the base 2531 and is not aligned with tissue capture plane including the staple legs 2532 and 2533. The projections 2538 can compress the tissue outside of the staple capture plane.

[0195] A staple cartridge assembly 2600 is illustrated in FIGS. 57-64. The staple cartridge 2600 comprises a cartridge body 2610 including a plurality of staple cavities 2220 defined therein. The staple cartridge 2600 further comprises a staple 2530 positioned in each staple cavity 2220 and sleds 2640 configured to eject the staples 2530 from the staple cavities 2220. The sleds 2640 are similar to the sleds 2140 in many respects. Each sled 2640 comprises a plurality of ramps 2645 wherein each ramp 2645 comprises a drive surface 2641 configured to slide under the staples 2530 and lift the staples 2530 within the staple cavities 2220. Each drive surface 2641 includes an inclined surface 2643 bounded by lateral sidewalls 2649 which define a guide channel that aligns the staples 2530 with respect to the drive surfaces 2641 and/or the staple cavities 2220. The guide channel is configured to receive the bases 2531 of the staples 2530 between the sidewalls 2649 and orient the staples 2530 laterally as the sled 2640 is advanced distally. Such lateral re-alignment is apparent upon comparing FIGS. 58 and 59. Referring again to FIGS. 52-56, each staple 2530 comprises a guide feature 2139 defined on the bases 2531 thereof. The guide feature 2139 of each staple 2530 comprises a curved end, for example, which is configured to interact with the lateral sidewalls 2649 of the guide channels and adjust the lateral position of the staples 2530. In various other embodiments, the guide features 2139 can comprise any suitable configuration.

[0196] In addition to or in lieu of the above, referring primarily to FIG. 60, the sleds 2640 comprise guide channels 2646 which are configured to receive the downwardly depending feet 2134 of the staples 2530 and orient the staples 2530 with respect to the drive surfaces 2641 and/or the staple cavities 2220. Each guide channel 2646 comprises a ramp portion 2648 and lateral sidewalls. The guide channels 2646 are configured to receive the bases 2531 of the staples 2530 between the sidewalls of the channels 2646 and orient the staples 2530 laterally as the sled 2640 is advanced

distally. Referring primarily to FIG. 61, each foot 2134 comprises lead-in, or beveled, surfaces 2137 which are configured to interact with the sidewalls of the channels 2646 to guide the staples 2530 into the channels 2646. That said, the feet 2134 can comprise any suitable geometry which facilitates the entry of the staples 2530 into the channels 2646. The reader should appreciate that, as the staples 2530 are driven upwardly within the staple cavities 2220 by the drive surfaces 2641, the feet 2134 of the staples 2530 lift out of the channels 2646. By the time that the staples 2530 are being formed by the apexes 2644 of the drive surfaces 2641, the feet 2134 are no longer positioned in the channels 2646.

[0197] Referring primarily to FIGS. 58, 59, and 64, the channels 2646 can also align the sleds 2640 with respect to the cartridge body 2610. More particularly, the cartridge body 2610 further comprises longitudinal rails 2616 extending downwardly into the channels 2646. The rails 2616 are closely received in the channels 2646 to limit or prevent lateral movement between the sleds 2640 and the cartridge body 2610 while permit the longitudinal movement of the sleds 2640 needed to fire the staples 2530 as outlined above. The foot 2134 of each staple 2530 is configured to properly orient the staple 2530 within its staple cavity 2220 in the event that the staple 2530 is misoriented within the staple cavity 2220.

[0198] The arrangements disclosed herein allow for a staple cartridge to be more compact than previous staple cartridges. Among other things, the staple cartridges disclosed herein that do not utilize staple drivers between the firing member and the staples, i.e., driverless staple cartridges, allow the staple cartridges to have a shorter overall height. Similarly, the staple cartridges that do not include a bottom cover also allow the staple cartridges to have a shorter overall height.

Driverless staple cartridges can also allow smaller staple cavities to be utilized. Turning now to FIGS. 67 and 68, a cartridge body 2910 includes staple cavities 2920 and a longitudinal slot 2013 defined therein. FIGS. 67 and 68 show the bottom 2916 of the cartridge body 2910 and the bottom openings of the staple cavities 2920. The reader should appreciate that the staple cavities 2920 are sized and configured to receive staple drivers for driving the staples out of the cartridge body 2910. Turning now to FIGS. 69 and 70 which depicts the bottom 2016 of the cartridge body 2010, the staple cavities 2020 of the cartridge body 2010 are smaller than the staple cavities 2920. As the reader will recall, drivers are not positioned in the staple cavities 2020 and, as a result, the size of the staple cavities 2020 can be reduced. FIG. 71 compares the bottom 2916 of the cartridge body 2910 to the bottom 3016 of an alternative embodiment of a cartridge body 3010. As can be seen in

FIG. 71, the cartridge body 3010 includes longitudinal rows of staple cavities 3020 which are much narrower than the longitudinal rows of staple cavities 2920. In various instances, such narrower staple cavities can permit the center lines of the longitudinal rows of staple cavities to be closer to one another. Turning now to FIG. 72, a staple cartridge body 3110 includes longitudinal rows of staple cavities 3120a, 3120b, and 3120c defined in a deck 3114 of the cartridge body 3110 which are positioned closer together than would be permitted in embodiments which use staple drivers to lift the staples within the cartridge body.

[0199] The various embodiments of the staple cartridge assemblies disclosed herein can have any suitable number of staples and/or any suitable size of staples. In certain instances, all of the staples stored in the staple cartridge assembly 2000 (FIG. 73) have the same, or at least substantially the same, size. Referring to FIG. 77, each staple 2130 in the staple cartridge 2000 comprises an unformed, or unfired, overall height H1 defined between the bottom of the base 2131 and the tips of the staple legs 2132, 2133. Similarly, each staple 2130 comprises a tissue capture area defined between the top of the base 2131 and the tips of the staple legs 2132, 2133 which has the same height H2 when the staples 2130 are in their unformed height.

[0200] In contrast to the above, a first group of staples stored in the staple cartridge 2000 can have a first unformed height H1 and a second group of staples can have a second unformed height H1 which is different than the first unformed height H1. Also in contrast to the above, a first group of staples stored in the staple cartridge 2000 can have a first tissue capture height H2 and a second group of staples can have a second tissue capture height H2 which is different than the first tissue capture height H2.

[0201] The first group of staples can be positioned in a first longitudinal row of staple cavities 2120 while the second group of staples can be positioned in a second longitudinal row of staple cavities 2120. In at least one instance, the first row of staple cavities 2120 can be adjacent the knife slot 2013 in the step 2014' of the cartridge body 2010 while the second row of staple cavities 2120 can be adjacent the first row of staple cavities 2120 in the step 2014' of the cartridge body 2010. In at least one such instance, the first unformed height H1 is shorter than the second unformed height H1, for example.

[0202] Further to the above, a third group of staples stored in the staple cartridge 2000 can have a third unformed height H1 which is different than the first unformed height H1 and/or the second unformed height H1. The third group of staples can be positioned in a third longitudinal row of

staple cavities 2120. In at least one instance, the third row of staple cavities 2120 can be adjacent the second row of staple cavities 2120 in the deck 2014 of the cartridge body 2010. In at least one such instance, the second unformed height H1 is shorter than the third unformed height H1, for example. In addition to or in lieu of the above, the third group of staples can have a third tissue capture height H2 which is larger than the second tissue capture height H2.

[0203] In various embodiments, the first group of staples, the second group of staples, and/or the third group of staples can be deformed to the same overall formed height. Alternatively, the first group of staples can be deformed to a first formed height, the second group of staples can be deformed to a second formed height, and/or the third group of staples can be deformed to a third formed height. In such instances, the first group of staples can apply a larger pressure to the tissue than the second group of staples and, similarly, the second group of staples can apply a larger pressure to the tissue than the third group of staples.

[0204] Turning now to FIGS. 74-76, staples having the same unformed height can be deformed to different formed heights. For example, a first longitudinal row of staples, represented by staples 2130'', can be deformed to a first formed height, a second longitudinal row of staples, represented by staples 2130', can be deformed to a second formed height, and/or a third row of staples, represented by staples 2130, can be deformed to a third formed height. The first formed height is shorter than the second formed height, and the second formed height is shorter than the third formed height, for example. In such instances, the first group of staples can apply a larger pressure to the tissue than the second group of staples and, similarly, the second group of staples can apply a larger pressure to the tissue than the third group of staples.

[0205] A staple 3230 is illustrated in FIGS. 78 and 79. The staple 3230 comprises a base, or crown, 3231, a first leg 3232 extending from the base 3231, and a second leg 3233 extending from the base 3231. Similar to the base 2131 of the staple 2130, the base 3231 of the staple 3230 includes an inclined drive surface defined in a drive plane. Unlike staple 2130, however, the first leg 3232 and the second leg 3233 define a staple forming plane which is transverse to, or non-parallel to, the drive plane.

[0206] The staple 3230 further includes a platform 3238 extending from the base 3231. The platform 3238 is integrally formed with the base 3231 and has been folded over such that the platform 3238 extends laterally from the base 3231. The platform 3238 is not directly connected to the legs 3232, 3233. Instead, gaps 3237 are present between the platform 3238 and the legs 3232,

3233. In various other embodiments, the platform 3238 is directly connected to the first leg 3232 and/or the second leg 3233. The platform 3238 extends in a plane, i.e., a support plane, which is transverse to the drive plane and the staple forming plane; however, the platform 3238 can extend in any suitable direction. The platform 3238 is flat, or at least substantially flat; however, the platform 3238 can comprise any suitable shape.

[0207] In certain embodiments, the platforms 3238 of the staples 3230 can contact the tissue being stapled when the staples 3230 are implanted into the tissue. The wider platform 3238 can reduce the possibility of the staples 3230 tearing through the tissue.

[0208] In various embodiments, a staple cartridge assembly comprises a cartridge body including a deck and staple cavities defined in the deck. The staple cartridge assembly further comprises staples 3230 removably stored in the staple cavities and, in addition, an implantable layer positioned over the deck. The implantable layer can comprise any suitable adjunct such as a tissue thickness compensator and/or a buttress material, for example. A tissue thickness compensator can compensate for variations in the thickness of the tissue being stapled. The implantable layer can be comprised of a woven material and/or a non-woven material, for example.

[0209] Further to the above, the platforms 3238 of the staples 3230 can abut the layer when the staples 3230 are implanted into the tissue. In such instances, the platforms 3238 support the layer. Similar to the above, the platforms 3238 can also reduce the possibility of the staples 3230 tearing through the layer. The platforms 3238 of the staples 3230 and the layer can form a co-operative system which distributes the forces, stresses, and/or strains being applied to the tissue over a larger area.

[0210] The staple 3230 is formed from a flat sheet of material utilizing a stamping process. During the stamping process, material is removed from the sheet to create the general shape of the staple 3230. The first leg 3232 is bent in a first direction and the second leg 3233 is bent in a second direction; however, both the first leg 3232 and the second leg 3233 can be bent in any suitable direction by a die utilizing a single line of action. The platform 3238 is bent in the same direction as the first leg 3232 during the stamping process, and/or a different stamping process. In certain instances, the platform 3238 can be created utilizing the same single line of action that creates the legs 3232 and 3233. In other instances, the platform 3238 can be created utilizing a second line of action which is transverse or orthogonal to the first line of action.

[0211] Turning now to FIG. 86, a staple 3630 comprises a base, or crown, 3631, and legs 3632 and 3633 extending from the base 3631. Similar to the staple 3230, the staple 3630 further comprises a platform 3638 extending from the base 3631. The reader should appreciate that the platform 3238 of the staple 3230 and the platform 3638 of the staple 3630 can increase the moment of inertia, or stiffness, of the staples. The staple 3630 comprises a relief, or flex, slot 3637 in the base 3631 which decreases the stiffness of the staple 3630, for example. Additionally, or alternatively, a relief slot could be provided in the platform 3638. In any event, more than one relief slot could be utilized to provide the desired stiffness of the staple 3630. Moreover, such relief slots could be adapted to any of the staples disclosed herein.

[0212] In addition to or in lieu of the above, turning now to FIGS. 80 and 81, a staple assembly 3330 comprises a staple 3230 and an implantable adjunct 3370 attached to the staple 3230. The adjunct 3370 comprises a first end including a first aperture 3372 configured to receive the first leg 3232 of the staple 3230 and a second aperture 3373 configured to receive the second leg 3233. As a result, the adjunct 3370 is tethered to the staple legs 3232, 3233 and the movement of the adjunct 3370 relative to the staple 3230 is constrained.

[0213] Further to the above, the adjunct 3370 comprises a resilient portion 3371 which extends over the platform 3238 of the staple 3230. A gap 3377 is present between the resilient portion 3371 of the adjunct 3370 and the platform 3238 of the staple 3230 when the staple assembly 3330 is stored in a staple cartridge. When the staple assembly 3330 is ejected from the staple cartridge, the staple legs 3232, 3233 of the staples 3230 penetrate the tissue being stapled and the resilient portion 3371 of the adjunct 3370 comes into contact with the tissue. The resilient portion 3371 is configured to flex, deflect, and/or displace downwardly toward the platform 3238 when the adjunct 3370 comes into contact with the tissue. The resilient portion 3371 can apply a biasing force to the tissue when the tissue is captured within the staple 3230. The movement of the resilient portion 3371 is at least partially constrained by the platform 3238.

[0214] In addition to or in lieu of the above, turning now to FIG. 84, a staple assembly 3430 comprises a staple 3630 and an implantable adjunct 3470 attached to the staple 3230. The adjunct 3470 comprises a first end including a first aperture 3472 configured to receive the first leg 3632 of the staple 3630 and a second aperture 3473 configured to receive the second leg 3633. As a result, the adjunct 3470 is tethered to the staple legs 3632, 3633 and the movement of the adjunct 3470 relative to the staple 3630 is constrained.

[0215] Further to the above, the adjunct 3470 comprises a resilient portion 3471 which extends over the platform 3638 of the staple 3630. Very little, if any, gap is present between the resilient portion 3471 of the adjunct 3470 and the platform 3638 of the staple 3630 when the staple assembly 3430 is stored in a staple cartridge. When the staple assembly 3430 is ejected from the staple cartridge, the staple legs 3632, 3633 of the staple 3630 penetrate the tissue being stapled and the resilient portion 3471 of the adjunct 3470 comes into contact with the tissue. Referring to FIG. 85, the resilient portion 3471 is configured to flex, deflect, and/or displace downwardly toward the platform 3638 when the adjunct 3470 comes into contact with the tissue. The resilient portion 3471 can apply a biasing force to the tissue when the tissue is captured within the staple 3630. The movement of the resilient portion 3471 is at least partially constrained by the platform 3638.

[0216] Referring primarily to FIGS. 82 and 83, the resilient portion 3471 of the adjunct 3470 comprises an enclosure. The enclosure is sealed and includes at least one material therein. In various instances, the material comprises a medicament. The medicament is released from the enclosure when the enclosure is ruptured. The enclosure can rupture when the staple assembly 3430 is implanted in the tissue or after a period of time. The adjunct 3470 is comprised of any suitable biocompatible material and, when the biocompatible material comprises a bioabsorbable material, the adjunct 3470 can be absorbed *in situ*. After a sufficient amount of the adjunct 3470 has been absorbed, the medicament can be released from the adjunct 3470. In various alternative embodiments, an adjunct comprises two separate enclosures. In at least one such embodiment, a first enclosure can contain a first medicament and a second enclosure can contain a second medicament. The first medicament can mix with the second medicament when the enclosures have been ruptured.

[0217] Further to the above, the material in the chamber of the resilient portion 3471 can be selected for its mechanical properties such as its elasticity, for example, and can provide the resilient portion 3471 with desirable properties to apply a sufficient biasing force to the tissue. In at least one instance, it may be desirable for the resilient portion 3471 to have mechanical properties which closely resemble that of patient tissue. In other instances, it may be desirable for the resilient portion 3471 to have a stiffness less than the stiffness of patient tissue, for example. Such embodiments may provide a suitable constriction of blood flow within the tissue. In some instances, it may be desirable for the resilient portion 3471 to have a stiffness which is less than the

stiffness of the base 3631 but greater than the stiffness of the patient tissue, for example. Such embodiments may provide strain relief to the tissue.

[0218] The adjuncts 3370, 3470 can be comprised of a woven material and/or a non-woven material. In at least one instance, the adjuncts 3370, 3470 comprise shells which are comprised of a woven material and/or a non-woven material. The adjuncts 3370, 3470 can be comprised of PGA and/or PLA, for example. In at least one instance, the adjuncts 3370, 3470 comprise shells which are comprised of PGA and/or PLA, for example.

[0219] The adjuncts 3370, 3470 are configured to be attached to a single staple. Stated another way, each adjunct 3370, 3470 are only attached to one staple. Such adjuncts can be referred to as pledgets. Alternative embodiments are envisioned in which two or more staples are connected by an adjunct.

[0220] Turning now to FIGS. 88 and 89, the various staples disclosed herein, such as staples 2130, for example, can be implanted into the tissue of a patient in longitudinal rows. Two longitudinal rows of staples 2130 are depicted in FIGS. 88 and 89. In various instances, the tissue may stretch in various directions, such as longitudinally, for example. The longitudinal stretch of tissue T is depicted in FIG. 89. As can be seen in FIG. 89, the rows of staples 2130 can stretch along with the tissue T. In such instances, the gaps between the staples 2130 can increase. This gap increase is readily apparent when comparing the unstretched gap distance X1 (FIG. 88) to the stretched gap distance X2 (FIG. 89). The staples 2130 in a third longitudinal row can be positioned and arranged such that they are aligned with or co-extensive with the gaps whether or not the gaps are stretched (X2) or unstretched (X1). Such concepts could be readily adapted to circular and/or curved staple rows, for example.

[0221] Turning now to FIG. 87, a circular cartridge body 3510, for example, can utilize the staple assemblies 3430. The cartridge body 3510 comprises a plurality of staple cavities 3520 arranged in circular, concentric rows. As illustrated in FIG. 87, each staple cavity includes a staple assembly 3430 positioned therein; however, any suitable staple could be utilized.

[0222] The staples disclosed herein can be comprised of any suitable material. In various instances, the staples are comprised of stainless steel and/or titanium, for example. In certain instances, the staples disclosed herein are comprised of magnesium. The entire disclosures of COMPARISON OF THE EFFECTS OF Mg-6Zn AND Ti-3Al-2.5V ALLOYS ON TGF- β /TNF- α /VEGF/b-FGF IN THE HEALING OF THE INTESTINAL TRACT IN VIVO, *Biomed. Mater.* 9

(2014) 025011, by Yan *et al.*; COMPARISON OF THE EFFECTS OF Mg-6Zn AND TITANIUM ON INTESTINAL TRACT IN VIVO, *J. Mater. Sci.: Mater. Med.*, by Yan *et al.* which published online on March 20, 2013; EVALUATION OF THE SOFT TISSUE BIOCOMPATIBILITY OF MgCa0.8 AND SURGICAL STEEL 316L IN VIVO: A COMPARATIVE STUDY IN RABBITS, *Biomed. Eng. OnLine* 2010 9:63, by Erdmann *et al.*; INVESTIGATION OF THE MECHANICAL AND DEGRADATION PROPERTIES OF Mg-Sr AND Mg-Zn-Sr ALLOYS FOR USE AS POTENTIAL BIODEGRADABLE IMPLANT MATERIALS, *J. Mech. Behavior of Biomed. Mat.* 7 (2012) 87-95, by Brar *et al.*; Mg-Zr-Sr ALLOYS AS BIODEGRADABLE IMPLANT MATERIALS, *Acta Biomaterialia* 8 (2012) 3177-3188, by Li *et al.*; ON THE BIODEGRADABILITY, MECHANICAL BEHAVIOR, AND CYTOTOXICITY OF AMORPHOUS $\text{Mg}_{72}\text{Zn}_{23}\text{Ca}_5$ AND CRYSTALLINE $\text{Mg}_{70}\text{Zn}_{23}\text{Ca}_5\text{Pd}_2$ ALLOYS AS TEMPORARY IMPLANT MATERIALS, *Soc. Biomat.*, by Pellicer *et al.*, which published online on August 28, 2012, are incorporated by reference herein. In at least one instance, the staples are comprised of a magnesium alloy including zinc and/or silver, for example. Staples including alloys of magnesium and zinc increase the healing performance of tissue. Staples including silver provide anti-microbial benefits. Staples including all three alloys provide a synergistic dynamic.

[0223] Staples comprised of magnesium, including those comprised of a magnesium alloy, can be treated to improve the hardness of the staples. In various instances, a magnesium nitride coating is applied to the magnesium staples. The magnesium nitride coating is applied the entirety of the magnesium staples in certain instances while, in other instances, the magnesium nitride coating is applied to only portions of the magnesium staples. For instance, it may be desirable to coat only the staple legs and/or the tips of the staple legs in magnesium nitride as the staple legs need to have a sufficient hardness to penetrate the tissue. In at least one such instance, a mask can be applied to the remainder of the magnesium staple when the magnesium nitride coating is applied to the staple legs. The magnesium nitride coating can be created by introducing the magnesium staples to a nitrogen-rich environment at an elevated temperature and/or pressure, for example.

[0224] In addition to or in lieu of the above, one or more surfaces of the magnesium staples can include a coating including carbon.

[0225] In addition to or in lieu of the above, other surface hardening techniques could be utilized. For example, the magnesium staples could be hardened using a laser hardening process and/or a

plasma discharge hardening process. In at least one instance, a KERONITE ceramic surface treatment, by Keronite International, can be applied to the staples.

[0226] As discussed above, certain portions of the magnesium staples may undergo a hardening process while other portions of the magnesium staples may not undergo a hardening process. In some instances, certain portions of the magnesium staples can be hardened to a first hardness while other portions of the magnesium staples can be hardened to a second hardness which is different than the first hardness. The portions of the magnesium staples having a lower hardness will elude magnesium, zinc, and/or silver ions, for example, faster than the portions of the magnesium staples having a higher hardness.

[0227] In addition to or in lieu of the above, magnesium staples, including those comprised of a magnesium alloy, can be at least partially covered in a coating including silver. In at least one instance, the silver coating can include ionized silver, for example. In certain instances, an electroplating process can be utilized to apply the silver coating to the magnesium staples. In various instances, the entirety of the magnesium staples are covered in a silver coating. In at least one instance, a portion, or portions, of the magnesium staples are masked during the electroplating process such that the masked portions are not coated, or at least substantially coated, in silver.

[0228] In addition to or in lieu of the above, the staples disclosed herein can be coated, or at least partially coated, in an anti-microbial coating. Such a coating can comprise triclosan, for example. In at least one instance, the triclosan is mixed in an absorbable polymer coating. In certain instances, the coating can comprise LAE intermixed with sodium stearate, for example. The entire disclosure of WO 2012013577 A1, entitled COMPOSITION FOR COATING MEDICAL DEVICES CONTAINING LAE AND A POLYCATIONIC AMPHOTERIC POLYMER, by Gaffar *et al.*, is incorporated by reference herein.

[0229] Turning now to FIGS. 90-92, a staple 3730 comprises a metal frame and a coating 3739 on less than the entirety of the metal frame. The metal frame includes the staple 2130 and is comprised of magnesium and/or a magnesium alloy, for example. The coating 3739 includes a bioabsorbable polymer; however, the coating 3739 can comprise any suitable material. The coating 3739 extends around the legs 2132, 2133 of the metal frame 2130. More specifically, the coating 3739 spirals around each of the legs 2132, 2133; however, any suitable arrangement of the coating 3739 could be utilized. The coating 3739 also covers the transitions, or corners, between the legs 2132, 2133 and the base, or crown, 2131 of the metal frame 2130. The coating 3739 could also cover a portion

of the base 2131. In various instances, the coating 3739 can be strategically applied to areas of the metal frame 2130 that are inherently susceptible to faster bioabsorption, such as the bends, edges, and/or corners of the metal frame 2130, for example. In any event, a portion of the metal frame 2130 is covered by the coating 3739 while a portion of the metal frame 2130 is exposed.

[0230] The magnesium, or magnesium alloy, metal frame 2130 is bioabsorbable. Referring primarily to FIG. 91, the portions of the metal frame 2130 that are not covered by the coating 3739 are directly exposed to the body when implanted, and, thus, immediately subjected to the body's natural absorption process. The portions of the metal frame 2130 that are covered by the coating 3739 are not directly exposed to the body, at least not initially, when implanted. The coating 3739 protects, or at least somewhat protects, the portions of the metal frame 2130 that it covers and delays the bioabsorption of such portions. Over time, referring primarily to FIG. 92, the unprotected portions of the metal frame 2130 will bioabsorb, leaving behind the portions of the metal frame 2130 that are protected by the coating 3739. The coating 3739 can substantially encapsulate the portions of the metal frame 2130 that it covers, at least until the coating 3739 itself is bioabsorbed and/or until the metal frame 2130 has sufficiently broken apart. At such point, the portions of the metal frame 2130 that the coating 3739 once protected are exposed and can be bioabsorbed by the body.

[0231] The bioabsorbable polymer of the coating 3739 can be comprised of PGA and/or PLA, for example; however, the coating 3739 can be comprised of any suitable material including, but not limited to, bioabsorbable polymers and non-bioabsorbable polymers. In certain instances, the coating 3739 comprises a non cross-linked polymer, for example. Such a polymer can cause the coating 3739 to swell and encapsulate any sharp edges of the metal frame 2130 that are created when the metal frame 2130 deteriorates.

[0232] In various embodiments, the coating 3739 can be arranged in a grid, mesh, and/or lattice arrangement on the metal frame 2130. In such an embodiment, the metal frame 2130 can be exposed in the openings in the grid which can allow the metal frame 2130 to be bioabsorbed in such openings. As the metal frame 2130 begins to deteriorate, the latticed coating 3739 can act as a net or cage and hold the fragments of the metal frame 2130 together, for example, at least until the coating 3739 is bioabsorbed.

[0233] The coating 3739 can be applied to the metal frame 2130 in any suitable manner. In at least one instance, the coating 3739 can be sprayed onto the metal frame 2130 such that the coating

3739 is applied in a random manner which creates random openings through which the metal frame 2130 can be bioabsorbed. In certain other instances, the coating 3739 can be applied to the metal frame 2130 in a pattern. In at least one such instance, the pattern can include a dot-matrix pattern having islands of coating surrounded by exposed portions of the metal frame 2130.

[0234] In certain alternative embodiments, a staple can include two or more coatings. In at least one such instance, a first coating can be bioabsorbed at a first rate and a second coating can be bioabsorbed at a second rate to expose different portions of the metal frame 2130 at different times during the healing process, for example. Such staples can still have uncovered portions; however, it is contemplated that every portion of a staple could be covered by at least one or more coatings.

[0235] The therapeutic benefits provided by the materials disclosed herein are a function of the surface area of the staples that is exposed to the patient's body. Staples having a larger surface area may deliver such therapeutic benefits faster than staples having a smaller surface area. That said, staples having a smaller surface area may provide such therapeutic benefits over a longer period of time. Nonetheless, the surface area of the staples disclosed herein can be increased by introducing apertures into the staples. For instance, one or more apertures, or through holes, can be created in the base, or crown, 2131 of the staple 2130, for example. The through holes can permit tissue to grow through the staple 2130 and improve the assimilation of the staple 2130 into the body.

[0236] In at least one embodiment, further to the above, the coating 3739 is not positioned in the apertures as the coating 3739 would reduce the available surface absorption area of the staple 2130. However, if delaying the bioabsorption of these staple portions is desired, the apertures in the staple 2130 could be filled, or at least partially filled, with the coating 3739. As discussed above, the coating 3739 can be configured to delay the absorption of the underlying metal frame; however, any suitable coating could be utilized. For example, a coating on the metal frame could encourage tissue ingrowth into the structure of the staple. In at least one such instance, the coating comprises small micropillars that create a porous and/or prickly interaction with the tissue.

[0237] In various embodiments, further to the above, a suture, or string, can extend through the apertures defined in the staples. Such a suture can tether the staples together. In various instances, the suture is threaded through the apertures while the staples are positioned in the staple cartridge. In other instances, the suture is threaded through the apertures after the staples have been implanted into the tissue. In at least one embodiment, the suture is positioned in a groove defined in the deck of the staple cartridge and the staples each comprise a slot or hook defined therein which is

configured to catch the suture as the staples are being deployed. In any event, the suture can be pulled to gather the stapled tissue together, such as in a purse-string tissue gathering technique, for example.

[0238] In various embodiments, the staples disclosed herein can comprise barbs. In at least one instance, barbs are defined on the staple leg such that the barbs engage a layer that is implanted with the tissue. Such barbs can reduce relative movement between the layer and the staples. In certain embodiments, barbs are defined on the base of the staple. Such barbs can grip a layer of tissue positioned adjacent the implanted staples.

[0239] A circular surgical stapler 5000 is depicted in FIGS. 93-95. The circular surgical stapler 5000 comprises a frame assembly 5020 comprising an attachment portion 5021 configured to operably couple an anvil to the circular surgical stapler 5000. The circular surgical stapler 5000 further comprises a knife member 5040 configured to incise tissue captured by the circular surgical stapler 5000, a surgical staple cartridge 5010 which removably stores a plurality of staples 5051 therein, and a pusher assembly, or driver, 5030 configured to eject the staples 5051 out of the staple cartridge 5010. The surgical staple cartridge 5010 comprises a cartridge deck 5013 and a plurality of staple cavities 5011 defined in the cartridge deck 5013 which removably store the staples 5051. The staples 5051 are similar to the staples discussed in greater detail herein, however, any suitable staple may be used. The staples 5051 comprise staple legs in a plane which is offset from a plane defined by the staple base portion.

[0240] Referring primarily to FIG. 95, the staple cavities 5011 of the staple cartridge 5010 comprise an inner row of staple cavities 5011A, an intermediate row of staple cavities 5011B, and an outer row of staple cavities 5011C. Staple row spacing may include any suitable spacing; however, nested rows may be closer together than non-nested rows. The intermediate row of staple cavities 5011B is positioned radially outward with respect to the inner row of staple cavities 5011A. The outer row of staple cavities 5011C is positioned radially outward with respect to the intermediate row of staple cavities 5011B. The staple cavities 5011A in the inner row comprise an orientation which orients the staple legs of the staples 5051 stored therein such that the staple legs extend radially outward with respect to the staple base. The intermediate row of staple cavities 5011B and the outer row of staple cavities 5011C comprise an orientation which orients the staple legs of the staples 5051 stored therein such that the staple legs extend radially inward with respect to the staple bases.

[0241] The staple cavities 5011A in the inner row define a plurality of first gaps therebetween having a distance A. The intermediate row of staple cavities 5011B define a plurality of second gaps with a distance B. The outer row of staple cavities 5011C define a plurality of third gaps with a distance C. The distance A is less than the distances B and C. The distance B is greater than the distance A but less than the distance C. The distance C is greater than the distances A and B. The cavities 5011 are arranged such that the first gaps comprise a distance which is greater than the distances of the second gaps and/or the third gaps. The cavities 5011 are arranged such that the third gaps comprise a distance which is less than the distances of the first gaps and/or the second gaps. Embodiments are envisioned where there are no gaps associated with one or more rows of staple cavities.

[0242] The intermediate row of staple cavities 5011B are arranged such that the cavities 5011B overlap the first gaps defined by the inner row of staple cavities 5011A in order to compensate for the lack of tissue ligation in the first gaps. The outer row of staple cavities 5011C are arranged such that the cavities 5011C overlap the second gaps defined by the intermediate row of staple cavities 5011B in order to compensate for the lack of tissue ligation in the second gaps. Overlapping these fastening gaps with such an arrangement increases the ligation ability of the circular surgical stapler 5000. This arrangement also permits the fastened tissue to flex upon fastening. Conventional arrangements utilize greater quantities of staples in the intermediate and/or outer rows in order to increase ligation efficiency; however, such conventional arrangements can limit tissue flexibility after fastening.

[0243] FIGS. 96-98 illustrate a circular surgical stapler 5100 in accordance with at least one embodiment. The circular surgical stapler 5100 comprises a frame assembly 5120 comprising an attachment portion configured to operably couple an anvil to the circular surgical stapler 5100. The circular surgical stapler 5100 further comprises a knife member 5140 configured to incise tissue captured by the circular surgical stapler 5100, a surgical staple cartridge 5110 which removably stores a plurality of staples 5151 therein, and a pusher assembly, or driver, 5130 configured to eject the staples 5151 out of the staple cartridge 5110. The pusher assembly 5130 comprises an inner row of staple drivers 5130A, an intermediate row of staple drivers 5130B, and an outer row of staple drivers 5130C. The surgical staple cartridge 5110 comprises a cartridge deck 5113 and a plurality of staple cavities 5111 defined in the cartridge deck 5113 which removably store the staples 5151 therein. The surgical staple cartridge 5110 further comprises a plurality of deck

features, or staple supports, or guides, 5115 configured to support, guide, and/or control the staples 5151 when the staples 5151 are ejected from the staple cartridge 5110. The deck features, or cavity extenders, 5115 can have a multitude of purposes such as aiding in the gripping of tissue intermediate the anvil and the staple cartridge 5110 and/or storing, releasing, and delivering a medicament to tissue captured with the stapler 5100, for example.

[0244] The staple cavities 5111 of the staple cartridge 5110 are similar to the staple cavities 5011 in many respects. The staple cavities 5111 comprise an inner row of staple cavities 5111A, an intermediate row of staple cavities 5111B, and an outer row of staple cavities 5111C. The deck features 5115 comprise a plurality of first deck features 5115A, a plurality of second deck features 5115B, and a plurality of third deck features 5115C. Each first deck feature 5115A comprises an intermediate portion 5116 and two outer portions 5117 to define a T-configuration. The intermediate portion 5116 sits between two staple cavities 5111A and extends from the deck 5113 to guide and/or support neighboring staple legs. The outer portions 5117 branch off of the intermediate portion 5116 in at least substantially opposite directions and extend from the deck 5113 to guide and/or support a portion of a staple base. Combining deck features for more than one cavity in such a manner can save space on the cartridge deck 5113.

[0245] Each second deck feature 5115B and each third deck feature 5115C comprise an intermediate portion 5118 and two outer portions 5119 to define a cavity-surrounding configuration. The intermediate portion 5118 extends from the deck 5113 to guide and/or support staple bases of staples removably stored in the intermediate row of staple cavities 5111B and the outer row of staple cavities 5111C. The two outer portions 5119 branch off from the intermediate portion 5118 to support the staple legs that extend from the staple base that the intermediate portion 5118 is guiding and/or supporting.

[0246] FIG. 99 illustrates a circular stapling configuration 5200 for use with a circular surgical stapler in accordance with at least one embodiment. The circular stapling configuration 5200 is an arrangement of staples employable with a circular staple cartridge. A circular staple cartridge employing the circular stapling configuration 5200 comprises corresponding staple cavities to removably store the staples discussed herein. The circular stapling configuration 5200 comprises a plurality of staples 5210 comprising an inner row of staples 5213, an intermediate row of staples 5215, and an outer row of staples 5217. Each staple 5213 is orientated such that its staple legs face outward toward the outer row of staples 5217. Each staple 5215 is orientated such that its staple

legs face inward toward the inner row of staples 5113. Each staple 5217 is orientated such that its staple legs face outward away from the inner row of staples 5213 and the intermediate row of staples 5215. Each staple row may reside a certain distance from each other staple row and/or the cutting member to better control blood flow and/or predict tissue behavior at certain points within the stapled tissue.

[0247] The outer row of staples 5217 comprise different characteristics than the inner and/or intermediate row of staples 5213, 5215. For example, in various instances, the outer row of staples 5217 are formed into a larger “B” formation resulting in a greater capture volume and/or taller staple forming height to alleviate high tissue compression near the outer row of staples 5217. A larger B formation may also improve blood flow toward the inner rows. In various instances, the outer row of staples 5217 comprise a greater resistance to unfolding by utilizing a larger staple crown, staple leg widths, and/or staple leg thicknesses.

[0248] The quantity of staples used in each row of staples can vary in a circular and/or linear surgical staple cartridge. The outer row of staples 5217 comprise a first quantity, the intermediate row of staples 5215 comprise a second quantity, and the inner row of staples 5213 comprise a third quantity. FIG. 99 illustrates a scenario where the first quantity is equal to the second quantity, but, greater than the third quantity. In various embodiments, the first quantity, the second quantity, and the third quantity are different. In various embodiments, the first quantity is greater than the second quantity and the second quantity is greater than the third quantity.

[0249] Varying staple crown widths between staple rows can provide an effective and/or efficient stapling arrangement. For example, each outer row staple 5217 comprises a staple crown having a width that is greater than the crown width of each inner row staple 5213 and each intermediate row staple 5215. The staple crown of each outer row staple 5217 is bent laterally in order have a larger crown width staple while maintaining the compact circular stapling arrangement. Some embodiments are envisioned where the crown of each outer row staple 5217 is curved. One advantage of bending or curving the crown of the outer row staples 5217 can include being able to nest the outer row staples 5217 closer to the intermediate row staples 5215 and the inner row staples 5213, for example. Each outer row staple 5217 spans a plurality of gaps defined between the inner row staples 5213 and/or the intermediate row staples 5215. Each intermediate row staple 5215 spans, overlaps, or covers each gap defined between the inner row of staples 5213.

[0250] In various embodiments the gaps defined by the inner row staples 5213 can be varied based on the radial position of the row of inner staples. For example, a row of inner staples having a diameter much less than the diameter of the intestine being stapled may comprise much larger gaps between the inner row staples to provide radial flexibility, and/or expansion. A row of inner staples having a diameter less than, but closer to, the diameter of the intestine being stapled may comprise smaller gaps between the inner row staples because, in this instance, vast expansion and/or flexibility may not be necessary.

[0251] FIG. 100 illustrates a circular stapling configuration 5300 for use with a circular surgical stapler in accordance with at least one embodiment. The circular stapling configuration 5300 is an arrangement of staples employable with a circular staple cartridge. A circular staple cartridge employing the circular stapling configuration 5300 comprises corresponding staple cavities to removably store the staples discussed herein. The circular stapling configuration 5300 comprises a plurality of staples 5310 comprising inner row staples 5313A, 5313B, intermediate row staples 5315C, 5315D, and outer row staples 5317E, 5317F. Each staple 5313A, 5313B is orientated such that the staple legs thereof face outward toward the outer row staples 5317E, 5317F. Each staple 5315C, 5315D is orientated such that the staple legs thereof face inward toward the inner row staples 5313A, 5313B. Each staple 5317E, 5317F is orientated such that the staple legs thereof face outward away from the inner row staples 5313A, 5313B and the intermediate row staples 5315C, 5315D. Embodiments are envisioned where various staples within the same row face opposite directions. Embodiments are envisioned where every staple in every row faces the same direction. Embodiments are envisioned where the inner row staples face inward, the intermediate row staples face outward, and the outer row staples face inward, for example.

[0252] Varying staple crown widths between and within staple rows can also provide an effective and/or efficient stapling arrangement. For example, the inner row staples 5313A, 5313B each comprise a different crown width, the intermediate row staples 5315C, 5315D each comprise a different crown width, and the outer row staples 5317E, 5317F each comprise a different crown width. In various embodiments, the crown widths of each staple 5313A, 5313B, 5315C, 5315D, 5317E, and 5317F are all different. Embodiments are envisioned where crown widths of certain staples in one row are equal to crown widths of certain staples in another row. The inner row staples define a stretch zone labeled SZ. The stretch zone SZ can comprise a gap defined between the staples 5313A, for example. The stretch zone SZ permits the stapled tissue to flex.

[0253] The circular surgical staplers, circular staple cartridges, and/or circular stapling configurations may be employed in a colectomy procedure, for example. FIG. 101 illustrates an example of a part of a colectomy procedure where two portions of intestine are joined providing a new pathway, or passage, 5400 for the digestive system. One portion of intestine T_1 comprises an inner wall 5410 and a second portion of intestine T_2 comprises an inner wall 5420. The intestine portions T_1 and T_2 are stapled with inner staples 5401, intermediate staples 5403, and outer staples 5405. The intestine portions T_1 and T_2 are incised creating a new passage P-P for digestive material to pass. The incision creates cut portions 5411 and 5421 of the intestine portions T_1 and T_2 . The change in diameter between the inner walls 5410, 5420 of the intestine portions T_1 and T_2 and the cut portions 5411, 5421 can, in some cases, constrict, or narrow, the passage P-P making it difficult for digestive material to pass. It can be desirable to have flexibility of the staple portion starting with the inner staples 5401. One method for providing flexibility utilizes staple gaps defined between staples in the various rows in which the staples are arranged. Another method for providing flexibility utilizes larger sized staples with larger staple crowns. In various instances, gaps between the staples and staple rows permit flexibility of the stapled portion allowing digestive material to pass more easily. In various instances, different size staples permit tissue flexibility.

[0254] FIGS. 102-104 depict a curved stapling instrument 5500 in accordance with at least one embodiment configured to capture, incise, and staple tissue. The curved stapling instrument 5500 comprises a frame assembly 5510, a staple cartridge 5520, and an anvil 5530. Upon receiving a first actuation force, the staple cartridge 5520 is driven toward the anvil 5530 to capture tissue therebetween. The curved stapling instrument 5500 further comprises a knife assembly 5540 comprising a cutting member 5541 configured to incise the tissue captured between the staple cartridge 5520 and the anvil 5530. The staple cartridge 5520 comprises a deck 5527 comprising a cutting slot 5521 configured to receive the cutting member 5541, a plurality of staple cavities 5523A and 5523B, and a plurality of staples 5560 removably stored within the staple cavities 5523A, 5523B. The curved stapling instrument 5500 further comprises a driver assembly 5550 comprising a plurality of staple drivers 5551 configured to drive the staples 5560 toward the anvil 5530 upon the application of a second actuation force. The second actuation force is responsible for lifting the driver assembly 5550 and the knife assembly 5540 vertically relative to the curved stapling instrument 5500 in order to incise and staple the tissue.

[0255] The staple cartridge 5520 further comprises a plurality of deck features 5525 extending from the deck 5527. Embodiments are envisioned where the deck features 5525 are separate portions configured to be attached to the deck 5527. The deck features 5525 can be extensions of the staple cavities 5523A, 5523B in order to support, guide, and/or control the staples 5560 while loading the staples 5560 into the cartridge 5520, while housing, or supporting, the staples 5560 before ejecting the staples 5560, and/or while ejecting the staples 5560 from the cartridge 5520. A single deck feature 5525 supports two different staple legs of neighboring staples. The deck features 5525 can comprise multiple support walls configured to support one or more sides, faces, and/or edges of each staple leg. Embodiments are envisioned where the deck features 5525 on the outer staple rows, rows furthest from the slot, only correlate with every other staple cavity in each outer row. Staple features may increase in density the closer to the incision the staple features are positioned.

[0256] FIGS. 105 and 106 depict a curved stapling instrument 5600 in accordance with at least one embodiment configured to capture, incise, and staple tissue. The curved stapling instrument 5600 comprises a frame assembly 5610, a staple cartridge 5620, and an anvil 5630. Upon receiving a first actuation force, the staple cartridge 5620 is driven toward the anvil 5630 to capture tissue therebetween. The curved stapling instrument 5600 further comprises a knife assembly comprising a cutting member configured to incise the tissue captured between the staple cartridge 5620 and the anvil 5630. The staple cartridge 5620 comprises a deck 5627 comprising a cutting slot 5621 configured to receive the cutting member, a plurality of staple cavities 5623, and a plurality of staples 5660 removably stored within the staple cavities 5623. The curved stapling instrument 5600 further comprises a driver assembly 5650 comprising a plurality of staple drivers 5651 configured to drive the staples 5660 toward the anvil 5630 upon the application of a second actuation force. The second actuation force is responsible for lifting the driver assembly 5650 and the knife assembly vertically relative to the curved stapling instrument 5600 in order to incise and staple the tissue.

[0257] The staple cartridge 5620 further comprises a plurality of deck features 5625 extending from the deck 5627. Embodiments are envisioned where the deck features 5625 are separate portions configured to be attached to the deck 5627. The deck features 5625 can be extensions of the staple cavities 5623 in order to support, guide, and/or control the staples 5660 while loading the staples 5660 into the cartridge 5620, while housing, or supporting, the staples 5660 before ejecting

the staples 5660, and/or while ejecting the staples 5660 from the cartridge 5620. The deck features 5625 can comprise multiple support walls configured to support one or more sides, faces, and/or edges of each staple leg. The deck features 5625 extend from at least one of the staple leg walls and at least one of the staple base walls of the staple cavities.

[0258] The staple drivers 5651 comprise a flat profile which is at least substantially the same as the bottom profile of the staples 5660. Having similar, or the same, profiles permits an adequate force distribution by the staple drivers 5651 over the staple base portions of the staples 5660. When being formed against the anvil 5630, the similar profiles between the drivers 5651 and the staples 5660 prevents the staples 5660 becoming misaligned.

[0259] *Examples*

Example 1 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a longitudinal slot defined in the deck extending from the proximal end toward the distal end and staple cavities, wherein the staple cavities are arranged in longitudinal rows. Each staple cavity comprises a top opening defined in the deck, a bottom opening, a proximal end, a distal end, and a staple cavity sidewall extending between the proximal end and the distal end. The staple cartridge assembly further comprises staples removably stored in the staple cavities, wherein each staple comprises a proximal leg, a distal leg, a base extending between the proximal leg and the distal leg, and a retention projection extending from the base, wherein the retention projections of the staples are engaged with the staple cavity sidewalls to prevent the staples from falling out of the bottom openings of the staple cavities.

Example 2 - The staple cartridge assembly of Example 1, further comprising a sled movable from the proximal end toward the distal end to eject the staples through the top openings of the staple cavities.

Example 3 - The staple cartridge assembly of Example 2, wherein the cartridge body further comprises a bottom surface defined opposite the deck, a longitudinal channel defined in the bottom surface, wherein at least a portion of the sled is slidably positioned in the longitudinal channel, and a retention portion configured to prevent the sled from falling out of the longitudinal channel through the bottom surface.

Example 4 - The staple cartridge assembly of Example 3, wherein the sled is movable between a proximal position and a distal position during a firing stroke, wherein the retention portion is

engaged with the sled when the sled is in the proximal position, and wherein the retention portion is not engaged with the sled when the sled is in the distal position.

Example 5 - The staple cartridge assembly of Examples 1, 2, 3, or 4, wherein the staple cartridge assembly does not comprise a cover extending around the bottom surface of the cartridge body.

Example 6 - The staple cartridge assembly of Examples 1, 2, 3, 4, or 5, wherein the cartridge body comprises at least one snap-fit feature configured to directly engage the surgical stapler.

Example 7 - The staple cartridge assembly of Examples 3, 4, or 5, wherein the sled directly engages the staples, and wherein the staple cartridge assembly does not comprise drivers positioned intermediate the sled and the staples.

Example 8 - The staple cartridge assembly of Examples 1, 2, 3, 4, 5, 6, or 7, wherein each staple is stamped from a sheet of material, wherein the proximal leg, the distal leg, and the base of each the staple are formed in a staple plane, and wherein the retention projection extends laterally from the staple plane.

Example 9 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a bottom portion, a longitudinal slot defined in the deck extending from the proximal end toward the distal end, a longitudinal channel defined in the bottom portion, and staple cavities, wherein each staple cavity comprises a top opening defined in the deck and a bottom opening defined in the bottom portion. The staple cartridge assembly further comprises staples removably stored in the staple cavities, a sled slidably positioned in the longitudinal channel, wherein the sled is movable from the proximal end toward the distal end to eject the staples through the top openings of the staple cavities, and a retention portion configured to prevent the sled from falling out of the longitudinal channel through the bottom portion.

Example 10 - The staple cartridge assembly of Example 9, wherein the sled is movable between a proximal position and a distal position during a firing stroke, wherein the retention portion is engaged with the sled when the sled is in the proximal position, and wherein the retention portion is not engaged with the sled when the sled is in the distal position.

Example 11 - The staple cartridge assembly of Examples 9 or 10, wherein the staple cartridge assembly does not comprise a cover extending around the bottom portion of the cartridge body.

Example 12 - The staple cartridge assembly of Examples 9, 10, or 11, wherein the sled directly engages the staples, and wherein the staple cartridge assembly does not comprise drivers positioned intermediate the sled and the staples.

Example 13 - A staple cartridge assembly for use with a surgical stapler, wherein the surgical stapler includes a jaw configured to receive the staple cartridge assembly, and wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a bottom portion, wherein the staple cartridge assembly does not comprise an enclosure extending around the bottom portion, a longitudinal slot defined in the deck extending from the proximal end toward the distal end, a longitudinal channel defined in the bottom portion, and staple cavities, wherein each the staple cavity comprises a top opening defined in the deck and a bottom opening defined in the bottom portion. The staple cartridge assembly further comprises staples removably stored in the staple cavities, a sled slidably positioned in the longitudinal channel, wherein the sled is movable from the proximal end toward the distal end to eject the staples through the top openings of the staple cavities during a firing stroke, and means for preventing the sled from falling out of the longitudinal channel through the bottom portion.

Example 14 - The staple cartridge assembly of Example 13, wherein the sled directly engages the staples during the firing stroke.

Example 15 - The staple cartridge assembly of Examples 13 or 14, further comprising means for preventing the staples from falling out of the staple cavities through the bottom openings.

Example 16 - A staple cartridge assembly for use with a surgical stapler, wherein the surgical stapler includes a jaw configured to receive the staple cartridge assembly, and wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a bottom portion, wherein the staple cartridge assembly does not comprise an enclosure extending around the bottom portion, and staple cavities, wherein each the staple cavity comprises a top opening defined in the deck and a bottom opening defined in the bottom portion. The staple cartridge assembly further comprises staples removably stored in the staple cavities, wherein the cartridge body includes shelves integrally formed with the cartridge body that prevent the staples from falling out of the staple cavities through the bottom openings.

Example 17 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a longitudinal slot defined in the deck extending from the proximal end toward the distal end, and a

staple cavity. The staple cavity comprises a top opening defined in the deck, a bottom opening, a proximal guide, a distal guide, a sidewall extending between the proximal guide and the distal guide, and an intermediate guide extending inwardly from the sidewall. The staple cartridge assembly further comprises a staple removably stored in the staple cavity including a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, and a base extending between the proximal leg and the distal leg, wherein the intermediate guide is positioned to guide the base and hold the proximal leg in the proximal guide and the distal leg in the distal guide.

Example 18 - The staple cartridge assembly of Example 17, wherein the staple cavity further comprises a proximal cavity end proximal to the proximal guide and a distal cavity end distal to the distal guide.

Example 19 - The staple cartridge assembly of Example 18, wherein the staple is not positioned in the proximal cavity end and the distal cavity end.

Example 20 - The staple cartridge assembly of Examples 18 or 19, wherein a first clearance gap is present between the staple base, the intermediate guide, and the distal cavity end, and wherein a second clearance gap is present between the staple base, the intermediate guide, and the proximal cavity end.

Example 21 - The staple cartridge assembly of Examples 17, 18, 19, or 20, wherein the base comprises a flat guide surface interfaced with the intermediate guide.

Example 22 - The staple cartridge assembly of Examples 17, 18, 19, 20, or 21, wherein the cartridge body further comprises a plurality of the staple cavities, and wherein the staple cartridge assembly further comprises a plurality of the staples positioned in the staple cavities.

Example 23 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, or 22, wherein the proximal guide, the distal guide, and the intermediate guide triangulate the control of the staple as the staple is ejected from the staple cavity.

Example 24 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22 or 23, wherein the proximal guide and the distal guide extend above the deck.

Example 25 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, or 24, wherein the intermediate guide extends above the deck.

Example 26 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, 24, or 25, wherein the proximal leg and the distal leg of the staple define a leg plane, wherein the base comprises a drive surface in a drive plane, and wherein the drive plane is offset from the leg plane.

Example 27 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, 24, 25, or 26, wherein the proximal leg and the distal leg are pinched toward each other by the proximal guide and the distal guide.

Example 28 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, or 27, wherein the intermediate guide comprises a resilient biasing member engaged with the base configured to push the proximal leg into the proximal guide and the distal leg into the distal guide.

Example 29 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, or 28, wherein the intermediate guide is positioned closer to the distal guide than the proximal guide.

Example 30 - The staple cartridge assembly of Examples 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, or 28, wherein the intermediate guide is positioned equidistant between the distal guide and the proximal guide.

Example 31 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a longitudinal slot defined in the deck extending from the proximal end toward the distal end, and a staple cavity. The staple cavity comprises a top opening defined in the deck, a bottom opening, a proximal guide, a distal guide, and a sidewall extending between the proximal guide and the distal guide. The staple cartridge assembly further comprises a staple removably stored in the staple cavity including a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, wherein the proximal leg and the distal leg define a leg plane, and wherein the proximal leg and the distal leg are pinched toward each other by the proximal guide and the distal guide, and a base extending between the proximal leg and the distal leg, wherein the base comprises a drive surface in a drive plane, and wherein the drive plane is offset from the leg plane.

Example 32 - The staple cartridge assembly of Example 31, wherein the leg plane is parallel to the drive plane.

Example 33 - The staple cartridge assembly of Examples 31 or 32, wherein the cartridge body further comprises a plurality of the staple cavities, and wherein the staple cartridge assembly further comprises a plurality of the staples positioned in the staple cavities.

Example 34 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal end, a distal end, a deck, a longitudinal slot defined in the deck extending from the proximal end toward the distal end, and a staple cavity. The staple cavity comprises a top opening defined in the deck, a bottom opening, a proximal guide, a distal guide, a sidewall extending between the proximal guide and the distal end guide, and an intermediate guide extending inwardly from the staple cavity sidewall. The staple cartridge assembly further comprises a staple removably stored in the staple cavity including a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, and a base extending between the proximal leg and the distal leg, wherein the proximal guide, the distal guide, and the intermediate guide triangulate the control of the staple as the staple is ejected from the staple cavity.

Example 35 - The staple cartridge assembly of Example 34, wherein the cartridge body further comprises a plurality of the staple cavities, and wherein the staple cartridge assembly further comprises a plurality of the staples positioned in the staple cavities.

Example 36 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal cartridge end, a distal cartridge end, a deck, a longitudinal knife slot defined in the deck extending from the proximal cartridge end toward the distal cartridge end, and a staple cavity. The staple cavity comprises a top opening defined in the deck, a proximal cavity end, a distal cavity end, a proximal guide, a distal guide, wherein the proximal guide and the distal guide extend above the deck, and a cavity slot extending between the proximal cavity end and the distal cavity end, wherein the proximal guide and the distal guide extend laterally with respect to the cavity slot. The staple cartridge assembly further comprises a staple removably stored in the staple cavity including a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, and a base extending between the proximal leg and the distal leg, wherein the base is positioned in the cavity slot.

Example 37 - The staple cartridge assembly of Example 36, wherein the proximal guide and the distal guide extend toward the knife slot.

Example 38 - The staple cartridge assembly of Example 36, wherein the proximal guide and the distal guide extend away from the knife slot.

Example 39 - The staple cartridge assembly of Examples 36, 37, or 38, wherein the proximal guide comprises a proximal bracket.

Example 40 - The staple cartridge assembly of Example 39, wherein the proximal bracket does not extend around the proximal cavity end.

Example 41 - The staple cartridge assembly of Examples 39 or 40, wherein the cavity slot is defined by a longitudinal axis, and wherein the proximal bracket is not aligned with the longitudinal axis.

Example 42 - The staple cartridge assembly of Examples 36, 37, 38, 39, 40, or 41, wherein the distal guide comprises a distal bracket.

Example 43 - The staple cartridge assembly of Example 42, wherein the distal bracket does not extend around the distal cavity end.

Example 44 - The staple cartridge assembly of Examples 42 or 43, wherein the cavity slot is defined by a longitudinal axis, and wherein the distal bracket is not aligned with the longitudinal axis.

Example 45 - The staple cartridge assembly of Examples 36, 37, 38, 39, 40, 41, 42, 43, or 44, wherein the proximal leg and the distal leg define a staple leg plane, wherein the base comprises a drive surface in a drive plane offset from the staple leg plane, wherein the proximal guide and the distal guide are aligned with the staple plane, and wherein the proximal guide and the distal guide are not aligned with the drive plane.

Example 46 - The staple cartridge assembly of Examples 36, 37, 38, 39, 40, 41, 42, 43, or 44, wherein the proximal leg and the distal leg define a staple leg plane, wherein the base comprises a drive surface in a drive plane offset from the staple leg plane, and wherein the proximal guide and the distal guide define a bracket plane aligned with the staple leg plane.

Example 47 - The staple cartridge assembly of Examples 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, or 46, wherein the cartridge body further comprises a plurality of the staple cavities, and wherein the staple cartridge assembly further comprises a plurality of the staples positioned in the staple cavities.

Example 48 - The staple cartridge assembly of Examples 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, or 47, wherein a portion of the proximal guide that extends above the deck comprises a staple cavity extender, and wherein a portion of the distal guide that extends above the deck comprises a staple cavity extender

Example 49 - A staple cartridge assembly for use with a surgical stapler, wherein the staple cartridge assembly comprises a cartridge body including a proximal cartridge end, a distal cartridge end, a deck, and a staple cavity. The staple cavity includes a proximal cavity end, a distal cavity end, a proximal guide extending above and below the deck, a distal guide extending above and

below the deck, and a connecting slot extending between the proximal cavity end and the distal cavity end, wherein the proximal guide and the distal guide extend laterally with respect to the connecting slot. The staple cartridge assembly further comprises a staple removably stored in the staple cavity comprising a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, and a base extending between the proximal leg and the distal leg, wherein the base is positioned in the cavity slot.

Example 50 - The staple cartridge assembly of Example 49, wherein the cartridge body further comprises a plurality of the staple cavities, and wherein the staple cartridge assembly further comprises a plurality of the staples positioned in the staple cavities.

Example 51 - The staple cartridge assembly of Examples 49 or 50, wherein the portion of the proximal guide that extends above the deck comprises a staple cavity extender, and wherein the portion of the distal guide that extends above the deck comprises a staple cavity extender

Example 52 - A fastener cartridge assembly for use with a surgical fastening instrument, wherein the fastener cartridge assembly comprises a cartridge body comprising a proximal cartridge end, a distal cartridge end, a deck, and a fastener pocket. The fastener pocket comprises a proximal pocket end, a distal pocket end, a proximal guide, a distal guide, a proximal pocket extender, wherein the proximal pocket extender extends above the deck, a distal pocket extender, wherein the proximal pocket extender extends above the deck, and a pocket opening extending between the proximal pocket end and the distal pocket end, wherein the proximal guide and the distal guide extend laterally with respect to the pocket opening. The fastener cartridge assembly further comprises a fastener removably stored in the fastener pocket comprising a proximal leg positioned within the proximal guide, a distal leg positioned within the distal guide, and a base extending between the proximal leg and the distal leg, wherein the base is positioned in the pocket opening.

Example 53 - The fastener cartridge assembly of Example 52, wherein the cartridge body further comprises a plurality of the fastener pockets, and wherein the fastener cartridge assembly further comprises a plurality of the fasteners positioned in the fastener pockets.

Example 54 - A staple cartridge assembly for use with a surgical instrument, the staple cartridge assembly comprising a cartridge body including a proximal end, a distal end, a deck, and staple cavities defined in the deck. The staple cartridge assembly further comprises staples removably positioned in the staple cavities and a firing member comprising a channel aligned with the staples, wherein the channel comprises a first lateral sidewall and a second lateral sidewall, and wherein the

channel is configured to receive the staples between the first lateral sidewall and the second lateral sidewall.

Example 55 - The staple cartridge assembly of Example 54, wherein the channel is defined on an inclined surface of the firing member.

Example 56 - The staple cartridge assembly of Examples 54 or 55, wherein the channel comprises a ramp portion configured to lift the staples within the staple cavities during a firing stroke of the firing member and an apex portion configured to form the staples against an anvil of the surgical instrument to a final formed height.

Example 57 - The staple cartridge assembly of Example 56, wherein the channel comprises a trailing portion positioned proximally with respect to the apex portion, and wherein the apex portion is positioned above the trailing portion.

Example 58 - The staple cartridge assembly of Examples 54, 55, 56, or 57, wherein the firing member comprises a sled including a plurality of wedges, and wherein the channel is defined on one of the wedges.

Example 59 - The staple cartridge assembly of Examples 54, 55, 56, 57, or 58, wherein the firing member further comprises a ramp configured to initially lift the staples within the staple cavities and guide the staples into the channel.

Example 60 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, or 59, wherein the channel comprises a mouth portion and a longitudinal portion, wherein the mouth portion provides a lead-in to the longitudinal portion, and wherein the mouth portion is wider than the longitudinal portion.

Example 61 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, 59, or 60, wherein the staples are received within the channel without a staple driver positioned between the staples and the channel.

Example 62 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, 59, 60, or 61, wherein the first lateral sidewall is parallel to the second lateral sidewall.

Example 63 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, 59, 60, or 61, wherein the first lateral sidewall is not parallel to the second lateral sidewall.

Example 64 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, 59, 60, or 61, wherein the first lateral sidewall and the second lateral are angled with respect to each other to create a staple entry lead-in.

Example 65 - The staple cartridge assembly of Examples 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, or 64, wherein the channel comprises a first channel, and wherein the firing member further comprises a second channel configured to receive the staples.

Example 66 - The staple cartridge assembly of Example 65, wherein each staple comprises a drive portion configured to enter the first channel, and a forming portion configured to enter the second channel.

Example 67 - The staple cartridge assembly of Examples 65 or 66, wherein the first channel extends at an angle relative to the second channel.

Example 68 - The staple cartridge assembly of Examples 65, 66, or 67, wherein the first channel and the second channel are parallel to one another in a first region and non-parallel to one another in a second region.

Example 69 - The staple cartridge assembly of Examples 65, 66, 67, or 68, wherein the second channel is configured to receive the staples before the first channel as the firing member is advanced toward the distal end.

Example 70 - A staple cartridge assembly for use with a surgical instrument, the staple cartridge assembly comprising a cartridge body comprising a deck and staple cavities defined in the deck, staples removably positioned in the staple cavities, and a firing member comprising a ramp configured to directly engage the staples and a rail extending from the ramp configured to orient the staples relative to the ramp.

Example 71 - The staple cartridge assembly of Example 70, wherein the rail comprises a first rail, and wherein the firing member further comprises a second rail extending from the ramp configured to orient the staples relative to the ramp.

Example 72 - The staple cartridge assembly of Example 71, wherein the first rail is parallel to the second rail.

Example 73 - A staple cartridge assembly for use with a surgical stapling instrument including an anvil, wherein the anvil includes forming pockets, and wherein the staple cartridge assembly comprises a cartridge body comprising a proximal end, a distal end, a deck, and staple cavities defined in the deck. The staple cartridge assembly comprises staples removably positioned in the staple cavities, wherein each staple comprises a staple driving portion and a staple forming portion, and a firing member comprising a first guide channel aligned with the staple driving portions of the staples and a second guide channel aligned with the staple forming portions of the staples, wherein

the first guide channel and the second guide channel are configured to co-operatively align the staples with the staple forming pockets of the anvil when the firing member is moved toward the distal end.

Example 74 - A staple cartridge assembly comprising a cartridge body including a deck, a first longitudinal row of staple cavities, and a second longitudinal row of staple cavities. The staple cartridge assembly further comprises a plurality of first staples, wherein each first staple is removably stored in the first longitudinal row of staple cavities, and wherein each first staple comprises a unitary structure including a first base including a first drive surface and a first staple leg extending from the first base and including a first tip, wherein a first unformed distance is defined between the first drive surface and the first tip, a plurality of second staples, wherein each second staple is removably stored in the second longitudinal row of staple cavities, and wherein each second staple comprises a unitary structure including a second base including a second drive surface and a second staple leg extending from the second base and including a second tip, wherein a second unformed distance is defined between the second drive surface and the second tip which is different than the first unformed distance, and a firing member configured to directly engage the first staples and the second staples.

Example 75 - The staple cartridge assembly of Example 74, wherein the first staples and the second staples are formed from a sheet of metal.

Example 76 - The staple cartridge assembly of Examples 74 or 75, wherein each first base includes a first tissue supporting surface, wherein a first tissue capture distance is defined between the first tissue supporting surface and the first tip, wherein each second base includes a second tissue supporting surface, wherein a second tissue capture distance is defined between the second tissue supporting surface and the second tip, and wherein the first tissue capture distance is different than the second tissue capture distance.

Example 77 - The staple cartridge assembly of Examples 74, 75, or 76, wherein the deck comprises a first deck height along the first longitudinal row of staple cavities and a second deck height along second the longitudinal row of staple cavities which is different than the first deck height.

Example 78 - The staple cartridge assembly of Example 77, wherein the cartridge body further comprises a longitudinal slot configured to receive a cutting member, wherein the first longitudinal row of staple cavities is adjacent the longitudinal slot, wherein the second longitudinal row of staple

cavities is adjacent the first longitudinal row of staple cavities, and wherein the second deck height is shorter than the first deck height.

Example 79 - The staple cartridge assembly of Examples 74, 75, 76, 77, or 78, wherein the cartridge body further comprises a longitudinal slot configured to receive a cutting member, wherein the first longitudinal row of staple cavities is adjacent the longitudinal slot, and wherein the second longitudinal row of staple cavities is adjacent the first longitudinal row of staple cavities.

Example 80 - The staple cartridge assembly of Examples 74, 75, 76, 77, 78, or 79, wherein the first unformed distance is shorter than the second unformed distance.

Example 81 - The staple cartridge assembly of Examples 74, 75, 76, 77, 78, 79, or 80, further comprising an anvil configured to deform the staples.

Example 82 - The staple cartridge assembly of Example 81, wherein the anvil is configured to deform the first staples to a first deformed height and the second staples to a second deformed height which is different than the first deformed height.

Example 83 - The staple cartridge assembly of Examples 81 or 82, wherein the cartridge body is movable toward the anvil to clamp tissue between the anvil and the deck of the cartridge body.

Example 84 - The staple cartridge assembly of Examples 81, 82, or 83, wherein the anvil is movable toward the cartridge body to clamp tissue between the anvil and the deck of the cartridge body.

Example 85 - The staple cartridge assembly of Examples 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, or 84, further comprising staple cavity extenders extending from the deck.

Example 86 - The staple cartridge assembly of Examples 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, or 85, further comprising an implantable layer positioned over the deck.

Example 87 - A staple cartridge assembly comprising a cartridge body comprising a deck, a first longitudinal row of staple cavities, and a second longitudinal row of staple cavities. The staple cartridge assembly further comprises a plurality of first staples, wherein each first staple is removably stored in the first longitudinal row of staple cavities, and wherein each first staple comprises a unitary structure including a first base including a first drive surface and a first tissue supporting surface and a first staple leg extending from the first base including a first tip, wherein a first tissue capture distance is defined between the first tissue supporting surface and the first tip, a plurality of second staples, wherein each second staple is removably stored in the second longitudinal row of staple cavities, and wherein each second staple comprises a unitary structure

including a second base including a second drive surface and a second tissue supporting surface and a second staple leg extending from the second base including a second tip, wherein a second tissue capture distance is defined between the second tissue supporting surface and the second tip which is different than the first tissue capture distance, and a firing member configured to directly engage the first staples and the second staples.

Example 88 - The staple cartridge assembly of Example 87, wherein the deck comprises a first deck height along the first longitudinal row of staple cavities and a second deck height along second the longitudinal row of staple cavities which is different than the first deck height.

Example 89 - The staple cartridge assembly of Example 88, wherein the cartridge body further comprises a longitudinal slot configured to receive a cutting member, wherein the first longitudinal row of staple cavities is adjacent the longitudinal slot, wherein the second longitudinal row of staple cavities is adjacent the first longitudinal row of staple cavities, and wherein the second deck height is shorter than the first deck height.

Example 90 - The staple cartridge assembly of Examples 87, 88, or 89, further comprising an anvil configured to deform the staples.

Example 91 - The staple cartridge assembly of Example 90, wherein the anvil is configured to deform the first staples to a first deformed height and the second staples to a second deformed height which is different than the first deformed height.

Example 92 - The staple cartridge assembly of Examples 90 or 91, wherein the cartridge body is movable toward the anvil to clamp tissue between the anvil and the deck of the cartridge body.

Example 93 - A staple cartridge assembly comprising a cartridge body comprising a first longitudinal row of staple cavities and a second longitudinal row of staple cavities, a plurality of first staples removably stored in the first longitudinal row of staple cavities, wherein each first staple is comprised of stamped metal and includes an integrally-formed metal driver, a plurality of second staples removably stored in the second longitudinal row of staple cavities, wherein each second staple is comprised of stamped metal and includes an integrally-formed metal driver, and means for forming the first staples to a first deformed height and the second staples to a second deformed height, wherein the first deformed height is different than the second deformed height.

Example 94 - A staple cartridge assembly comprising a staple cartridge body including a deck and staple cavities defined in the deck, staples removable stored in the staple cavities, wherein each staple comprises a base, a leg extending from the base, and a platform extending laterally from the

base, and an implantable layer positioned over the deck, wherein the platforms of the staples are configured to abut the layer when the staples are implanted into the tissue of a patient.

Example 95 - The staple cartridge assembly of Example 94, wherein each staple is stamped from a sheet of material, wherein the base defines a base plane, and wherein the platform is folded out of the base plane.

Example 96 - The staple cartridge assembly of Examples 94 or 95, wherein the implantable layer comprises a woven material.

Example 97 - The staple cartridge assembly of Examples 94, 95, or 96, wherein the implantable layer comprises a non-woven material.

Example 98 - The staple cartridge assembly of Examples 94, 95, 96, or 97, further comprising a retention member extending from the leg adjacent the base, wherein the retention member is configured to engage the implantable layer when staples are implanted into the tissue of a patient.

Example 99 - The staple cartridge assembly of Examples 94, 95, 96, 97, or 98, wherein the platform is flat.

Example 100 - The staple cartridge assembly of Examples 94, 95, 96, 97 98, or 99, wherein the platform is not directly attached to the leg.

Example 101 - A staple cartridge assembly comprising a staple cartridge body including a deck and staple cavities defined in the deck, staples removable stored in the staple cavities, wherein each staple comprises a crown, a first leg and a second leg extending from the crown, and a platform extending laterally from the crown, and an implantable layer positioned over the deck, wherein the platforms of the staples are configured to support the layer when the staples are implanted into the tissue of a patient.

Example 102 - The staple cartridge assembly of Example 101, wherein each staple is stamped from a sheet of material, wherein the crown defines a crown plane, and wherein the platform is folded out of the crown plane.

Example 103 - The staple cartridge assembly of Examples 101 or 102, wherein the implantable layer comprises a woven material.

Example 104 - The staple cartridge assembly of Examples 101, 102, or 103, wherein the implantable layer comprises a non-woven material.

Example 105 - The staple cartridge assembly of Examples 101, 102, 103, or 104, further comprising a retention member extending from the leg adjacent the crown, wherein the retention member is configured to engage the implantable layer when staples are implanted into the tissue of a patient.

Example 106 - The staple cartridge assembly of Examples 101, 102, 103, 104, or 105, wherein the platform is flat.

Example 107 - The staple cartridge assembly of Examples 101, 102, 103, 104, 105, or 106, wherein each staple comprises a compliant adjunct positioned adjacent the crown.

Example 108 - The staple cartridge assembly of Example 107, wherein the compliant adjunct extends between the first leg and the second leg.

Example 109 - The staple cartridge assembly of Examples 107 or 108, wherein the compliant adjunct is attached to the first leg and the second leg.

Example 110 - The staple cartridge assembly of Examples 107, 108, or 109, wherein the compliant adjunct comprises a first aperture and a second aperture, wherein the first leg extends through the first aperture, and wherein the second leg extends through the second aperture.

Example 111 - The staple cartridge assembly of Examples 107, 108, 109, or 110, wherein the compliant adjunct comprises a cavity and at least one medicament positioned in the cavity.

Example 112 - The staple cartridge assembly of Examples 107, 108, 109, 110, or 111, wherein the compliant adjunct comprises a compressible enclosure.

Example 113 - A staple cartridge assembly comprising a staple cartridge body including a deck and staple cavities defined in the deck, and staples removably stored in the staple cavities, wherein each staple comprises a crown, a first leg and a second leg extending from the crown, a platform extending laterally from the crown, and a compliant adjunct positioned adjacent the crown.

Example 114 - The staple cartridge assembly of Example 113, wherein the compliant adjunct extends between the first leg and the second leg.

Example 115 - The staple cartridge assembly of Examples 113 or 114, wherein the compliant adjunct is attached to the first leg and the second leg.

Example 116 - The staple cartridge assembly of Examples 113, 114, or 115, wherein the compliant adjunct comprises a first aperture and a second aperture, wherein the first leg extends through the first aperture, and wherein the second leg extends through the second aperture.

Example 117 - The staple cartridge assembly of Examples 113, 114, 115, or 116, wherein the compliant adjunct comprises a cavity and at least one medicament positioned in the cavity.

Example 118 - The staple cartridge assembly of Examples 113, 114, 115, 116, or 117, wherein the compliant adjunct comprises a compressible enclosure.

Example 119 - A staple cartridge assembly comprising a cartridge body including a deck and a plurality of staple cavities defined in the deck, and a plurality of staples stored in the staple cavities, wherein each staple comprises a first portion comprised of an alloy including zinc and magnesium and a second portion comprised of an absorbable polymer, wherein the second portion is disposed on the first portion, and wherein the second portion covers less than the entirety of the first portion.

Example 120 - The staple cartridge assembly of Example 119, wherein the first portion comprises a base and a staple leg extending from the base, and wherein the second portion extends around the staple leg in a spiral pattern.

Example 121 - The staple cartridge assembly of Examples 119 or 120, wherein the second portion is coated on the first portion in a dot-matrix pattern.

Example 122 - The staple cartridge assembly of Examples 119, 120, or 121, wherein the first portion comprises a base and a staple leg extending from the base, wherein a corner is defined between the base and the staple leg, and wherein the second portion covers the corner.

Example 123 - The staple cartridge assembly of Examples 119, 120, 121, or 122, wherein the absorbable polymer comprises a non-crosslinked polymer.

Example 124 - The staple cartridge assembly of Examples 119, 120, 121, 122, or 123, wherein the second portion is coated on the first portion in a mesh pattern.

Example 125 - The staple cartridge assembly of Examples 119, 120, 121, 122, 123, or 124, wherein the first portion comprises a base and a staple leg extending from the base, wherein the staple leg comprises a tissue penetrating tip, and wherein the staple further comprises magnesium nitride disposed on the tip.

Example 126 - The staple cartridge assembly of Examples 119, 120, 121, 122, 123, 124, or 125, wherein the staple further comprises a coating of ionized silver on at least part of the first portion that is not coated by the second portion.

Example 127 - The staple cartridge assembly of Examples 119, 120, 121, 122, 123, 124, 125, or 126, further comprising at least one aperture in the first portion.

Example 128 - A staple cartridge assembly comprising a cartridge body including a deck and a plurality of staple cavities defined in the deck and a plurality of staples stored in the staple cavities, wherein each staple comprises a metal frame comprised of a magnesium alloy and an absorbable

polymer coated on the metal frame, wherein the absorbable polymer does not cover every portion of the metal frame.

Example 129 - A staple cartridge assembly comprising a cartridge body including a deck and a plurality of staple cavities defined in the deck, and a plurality of staples stored in the staple cavities, wherein each staple comprises a metal frame comprised of a magnesium alloy, wherein the metal frame comprises a base and a leg extending from the base, and wherein the leg comprises a tissue penetrating tip, and a magnesium nitride coating on the tip.

Example 130 - The staple cartridge assembly of Example 129, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the absorbable polymer does not cover every portion of the metal frame.

Example 131 - The staple cartridge assembly of Examples 129 or 130, wherein each staple further comprises a coating comprising silver on at least a portion of the metal frame.

Example 132 - A staple cartridge assembly comprising a cartridge body including a deck and a plurality of staple cavities defined in the deck, and a plurality of staples stored in the staple cavities, wherein each staple comprises a metal frame comprised of a magnesium alloy, wherein the metal frame comprises a base and a leg extending from the base, and wherein the leg comprises a tissue penetrating tip, and a coating comprising silver on at least a portion of the metal frame.

Example 133 - The staple cartridge assembly of Example 132, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the absorbable polymer does not cover every portion of the metal frame.

Example 134 - The staple cartridge assembly of Examples 132 or 133, further comprising a magnesium nitride coating on the tip.

Example 135 - A staple cartridge assembly comprising a cartridge body including a deck and a plurality of staple cavities defined in the deck, and a plurality of staples stored in the staple cavities, wherein each staple comprises a metal frame comprised of a magnesium alloy, wherein the metal frame comprises a base and a leg extending from the base, and wherein the leg comprises tissue penetrating tip, and an aperture defined in the metal frame.

Example 136 - The staple cartridge assembly of Example 135, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the absorbable polymer does not cover every portion of the metal frame.

Example 137 - The staple cartridge assembly of Example 135, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the absorbable polymer is not positioned in the aperture.

Example 138 - The staple cartridge assembly of Example 135, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the absorbable polymer is positioned in the aperture.

Example 139 - The staple cartridge assembly of Example 135, wherein each staple further comprises an absorbable polymer coated on the metal frame, and wherein the aperture is filled with the absorbable polymer.

Example 140 - A staple cartridge assembly for stapling tissue comprising a cartridge body including a proximal end, a distal end, and a plurality of staple cavities, a plurality of staples positioned in the staple cavities, wherein each staple comprises a base a leg extending from the base, wherein the leg comprises a tip configured to penetrate the tissue, and a foot extending from the base, and a firing member configured to eject the staples from the staple cavities, wherein the firing member is configured to contact the foot of any staple that is misoriented within its staple cavity prior to ejecting the misoriented staple from its staple cavity.

Example 141 - The staple cartridge assembly of Example 140, wherein the firing member comprises a firing ramp configured to contact the bases of the staples to drive the staples out of the staple cavities and an alignment ramp configured to contact the feet of the staples if the staples are misoriented.

Example 142 - The staple cartridge assembly of Examples 140 or 141, wherein the firing member further comprises a firing channel aligned with the firing ramp, wherein the firing channel is configured to receive the bases of the staples, and an alignment channel aligned with the alignment ramp, wherein the alignment channel is configured to receive the feet of the staples once the staples are properly oriented.

Example 143 - The staple cartridge assembly of Examples 141 or 142, wherein the alignment ramp extends distally with respect to the firing ramp such that the alignment ramp can contact the feet of the staples before the firing ramp contacts the bases of the staples.

Example 144 - The staple cartridge assembly of Examples 140 ,141, 142, or 143, wherein the foot of the staple is positioned proximally with respect to the base of the staple.

Example 145 - The staple cartridge assembly of Examples 140, 141, 142, 143, or 144, wherein the firing member is not configured to contact the feet of the staples if the staples are properly oriented within the staple cavities.

Example 146 - A staple cartridge assembly for stapling tissue comprising a cartridge body comprising a proximal end and a distal end, and a plurality of staple cavities, wherein each staple cavity comprises a top opening, a proximal wall, and a distal wall. The staple cartridge assembly further comprises a firing member and a plurality of staples positioned in the staple cavities, wherein each staple comprises a base, a proximal leg extending from the base, a distal leg extending from the base, and center of mass defined in the base, wherein the distal wall provides a distal reaction force to the staple above the center of mass and the proximal wall provides a proximal reaction force to the staple below the center of mass wherein the staple is lifted toward the top opening by the firing member. The staple cartridge assembly further comprises a firing member configured to eject the staples from the staple cavities, wherein the firing member is configured to contact the foot of any staple that is misoriented within its staple cavity prior to ejecting the misoriented staple from its staple cavity.

Example 147 - The staple cartridge assembly of Example 146, wherein the base defines a drive plane, and wherein the proximal leg and the distal leg are not in the drive plane.

Example 148 - The staple cartridge assembly of Examples 146 or 147, wherein the proximal leg and the distal leg are offset laterally from the center of mass of the staple.

Example 149 - The staple cartridge assembly of Examples 146, 147, or 148, wherein the distal wall applies the distal reaction force to the distal leg and the proximal wall applies the proximal reaction force to the proximal leg.

Example 150 - The staple cartridge assembly of Example 147, wherein the proximal leg extends to a first side of the drive plane and the distal leg extends to a second side of the drive plane.

Example 151 - The staple cartridge assembly of Examples 146, 147, 148, 149, or 150, wherein the base comprises a notch defined therein configured to shift the center of mass of the staple toward a side of the staple cavity.

Example 152 - A staple cartridge assembly for stapling tissue comprising a cartridge body including a proximal end, a distal end, and a plurality of staple cavities. The staple cartridge assembly further comprises a plurality of staples positioned in the staple cavities, wherein each staple comprises a base defining a drive plane and a leg extending from the base, wherein the leg extends to a side of

the drive plane, a firing member configured to eject the staples from the staple cavities, and means for reducing the rotation of the staples within the staple cavities when the firing member is driving the staples out of the staple cavities.

Example 153 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of staples removably stored in the staple cavities, wherein each staple comprises a staple base portion which defines a first plane, a center of mass located within the staple base portion, a first staple leg extending from the staple base portion, and a second staple leg extending from the staple base portion, wherein the first staple leg and the second staple leg define a second plane which is offset and at least substantially parallel to the first plane.

Example 154 - The surgical staple cartridge of Example 153, wherein the first staple leg and the second staple leg are configured to form toward the staple base portion.

Example 155 - The surgical staple cartridge of Examples 153 or 154, wherein the staple base portion comprises a compression surface comprising a contour configured to limit tissue compression.

Example 156 - The surgical staple cartridge of Examples 153, 154, or 155, wherein the staple base portion comprises a bottom surface, and wherein the first staple leg further comprises an engagement foot elevated above the bottom surface.

Example 157 - The surgical staple cartridge of Examples 153, 154, 155, or 156, wherein the staple base portion comprises an inner wall and a top surface, wherein the inner wall and the top surface comprise a cutout configured to cause the staple base portion to lean toward the staple legs.

Example 158 - The surgical staple cartridge of Examples 153, 154, 155, 156, or 157, wherein the first staple leg extends higher than the second staple leg.

Example 159 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, or 158, wherein the staple base portion comprises a rectangular cross-sectional profile.

Example 160 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, or 159, wherein the first staple leg and the second staple leg comprise a substantially round cross-sectional profile.

Example 161 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, or 160, wherein the first staple leg and the second staple leg comprise coined corners.

Example 162 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, 160, or 161, wherein the first staple leg is proximal the second staple leg, wherein the staple base portion comprises a distal wall, and wherein the distal wall is proximal to the second staple leg.

Example 163 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, 160, 161, or 162, wherein the first staple leg comprises a first height and the second staple leg comprises a second height different than the first height.

Example 164 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, or 163, wherein the first staple leg and the second staple leg each comprise a staple tip configured to form against corresponding forming pockets of an anvil, wherein the corresponding forming pockets comprise a valley and a forming surface, and wherein the valley is configured to funnel the staple tips toward the forming surface.

Example 165 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, or 164, wherein the first staple leg and the second staple leg are configured to form against corresponding forming pockets, wherein the corresponding forming pockets are configured to form the first staple leg in a first direction and the second staple leg in a second direction, and wherein the first direction is opposite and at least substantially parallel to the second direction.

Example 166 - The surgical staple cartridge of Example 165, wherein the first direction points away from the staple base portion, and wherein the second direction points toward the staple base portion.

Example 167 - The surgical staple cartridge of Examples 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, or 166, wherein the first staple leg and the second staple leg are configured to form against corresponding forming pockets, wherein the corresponding forming pockets are configured to form the first staple leg in a first curved direction and the second staple leg in a second curved direction.

Example 168 - A surgical staple comprising a staple base portion defining a first plane, a first staple leg extending at least substantially perpendicular from the staple base portion, and a second staple leg extending at least substantially perpendicular from the staple base portion, wherein the first staple leg and the second staple leg define a second plane, wherein the first plane and the second plane intersect.

Example 169 - A surgical staple cartridge comprising a plurality of the surgical staple of Examples 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, or 168, wherein the surgical staples are arranged in a plurality of woven rows.

Example 170 - The surgical staple of Examples 168 or 169, wherein the staple is configured to form into an S-shape configuration.

Example 171 - A surgical staple comprising a staple base portion comprising a bottom surface which defines a bottom plane, a center of mass located within the staple base portion, and a first staple leg and a second staple leg extending from the staple base portion and defining a staple leg plane which is offset and at least substantially parallel to the staple base portion, wherein the first staple leg comprises an engagement foot elevated above the bottom plane.

Example 172 - The surgical staple of Example 171, wherein the engagement foot is laterally offset with respect to the staple base portion.

Example 173 - A surgical staple cartridge for use with a surgical stapler including an anvil to staple tissue, wherein the anvil comprises a plurality of forming pockets, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of staples removably stored within the staple cavities, wherein each staple comprises a base and a staple leg extending from the base, wherein the staple leg comprises a staple tip comprising a piercing portion, wherein the piercing portion is configured to puncture tissue and deform against the forming pocket of the anvil, and wherein the piercing portion is configured to deform into a nested configuration such that the piercing tip is isolated from the tissue.

Example 174 - The surgical staple cartridge of Example 173, wherein the nested configuration comprises a hook configuration configured to prevent the surgical staple from pulling through the tissue.

Example 175 - The surgical staple cartridge of Examples 173 or 174, wherein the staple tip further comprises a cutout portion configured to receive the piercing portion when the piercing portion is deformed.

Example 176 - The surgical staple cartridge of Example 175, wherein the cutout portion is concave.

Example 177 - The surgical staple cartridge of Examples 175 or 176, wherein each staple comprises another staple leg extending from the base, wherein the another staple leg comprises another staple tip comprising another cutout portion, and wherein the cutout portion and the another cutout portion face each other.

Example 178 - The surgical staple cartridge of Examples 173, 174, 175, 176, or 177, wherein the staple tip further comprises a curling surface configured to ride against a corresponding forming pocket of the anvil.

Example 179 - The surgical staple cartridge of Examples 173, 174, 175, 176, 177, or 178, wherein each staple comprises another staple leg, wherein the staple leg and the another staple leg define a first plane, wherein the staple base defines a second plane, and wherein the first plane and the second plane are laterally offset from each other.

Example 180 - A surgical staple for use with a surgical stapler including an anvil, wherein the anvil comprises a forming pocket, the surgical staple comprising a staple base portion and a staple leg extending from the staple base portion, wherein the staple leg comprises a staple tip, and wherein the staple tip comprises a piercing tip configured to contact the forming pocket to deform the staple leg and a cutout portion, wherein the piercing tip is configured to curl in toward the cutout portion upon contact with the forming pocket such that the staple tip assumes a non-piercing configuration.

Example 181 - The surgical staple of Example 180, wherein the non-piercing configuration comprises a hook configuration configured to prevent the surgical staple from pulling through the tissue.

Example 182 - The surgical staple of Examples 180 or 181, wherein the cutout portion is configured to receive the piercing tip when the staple tip is deformed.

Example 183 - The surgical staple of Examples 180, 181, or 182, wherein the cutout portion is concave.

Example 184 - The surgical staple of Examples 180, 181, 182, or 183, wherein the staple tip further comprises a deformable surface configured to form against the forming pocket of the anvil.

Example 185 - A surgical staple cartridge for use with a surgical stapler including an anvil, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of flat-formed staples removably stored within the staple cavities, wherein each staple comprises a staple base portion and a staple leg extending from the base portion, wherein the staple leg comprises a staple tip comprising a rounded profile and a piercing portion.

Example 186 - The surgical staple cartridge of Example 185, wherein the rounded profile is attained by a cold working process.

Example 187 - The surgical staple cartridge of Examples 185 or 186, wherein the staple tip comprises a coined portion.

Example 188 - The surgical staple cartridge of Examples 185, 186, or 187, wherein the staple tip further comprises a deformable surface configured to form against a forming pocket of the anvil.

Example 189 - The surgical staple cartridge of Examples 185, 186, 187, or 188, wherein the staple tip comprises a first hardness, and wherein the staple leg comprises a second hardness different than the first hardness.

Example 190 - The surgical staple cartridge of Example 189, wherein the first hardness is greater than the second hardness.

Example 191 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of staples removably stored within the staple cavities, wherein each staple comprises a staple base and a pair of staple legs extending from the staple base, wherein each staple leg comprises a staple tip, wherein the staple legs comprise a first zone comprising a first hardness, and wherein the staple tips comprise a second zone comprising a second hardness which is different than the first hardness.

Example 192 - The surgical staple cartridge of Example 191, wherein the second hardness is greater than the first hardness.

Example 193 - The surgical staple cartridge of Example 191, wherein the second hardness is less than the first hardness.

Example 194 - The surgical staple cartridge of Examples 191, 192, or 193, wherein the staple base comprises a third zone comprising a third hardness different than the first hardness and the second hardness.

Example 195 - The surgical staple cartridge of Examples 191, 192, 193, or 194, wherein the staple legs comprise corner portions that are coined to the first hardness.

Example 196 - The surgical staple cartridge of Example 195, wherein the corner portions provide a preferential bending plane.

Example 197 - The surgical staple cartridge of Examples 191, 192, 193, 194, 195, or 196, wherein the first zone comprises a first ductility, and wherein the second zone comprises a second ductility which is less than the first ductility.

Example 198 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of staples removably stored within the staple cavities, wherein each staple comprises a staple base, a pair of staple legs extending from the staple base, a first zone comprising a first hardness, and a second zone comprising a second hardness which is different than the first hardness.

Example 199 - The surgical staple cartridge of Example 198, wherein the first zone is hardened using a first method and the second zone is hardened using a second method different than the first method.

Example 200 - The surgical staple cartridge of Example 198, wherein only one of the first zone and the second zone is hardened by a hardening method.

Example 201 - The surgical staple cartridge of Examples 198, 199, or 200, wherein each staple further comprises bend portions intermediate the staple legs and the staple base, and wherein the bend portions comprise the first zone and the staple base comprises the second zone.

Example 202 - The surgical staple cartridge of Examples 198, 199, 200, or 201, wherein the staple base comprises the first zone and the staple legs comprise the second zone.

Example 203 - The surgical staple cartridge of Examples 198, 199, 200, 201, or 202, wherein the staple legs are not hardened and the staple base is hardened such that the staple legs are encouraged to assume a formed configuration and such that the staple base is configured to avoid plastic deformation.

Example 204 - The surgical staple cartridge of Examples 198, 199, 200, 201, 202, or 203, wherein each staple leg comprises a transition portion extending from the staple base and a vertical leg portion extending from the transition portion, and wherein the staple base comprises the first zone and the vertical leg portion comprises the second zone.

Example 205 - A surgical staple configured to be removably stored within a surgical staple cartridge in an unfired configuration, the surgical staple comprising a non-uniform hardness profile, wherein the staple comprises a first zone having a first hardness and a second zone having a second hardness, wherein the first zone is hardened to the first hardness when the staple is in a pre-load configuration, and wherein the second zone is hardened to the second hardness when the staple is in the pre-load configuration.

Example 206 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a plurality of staples removably stored within the staple cavities, wherein each staple comprises a staple base, wherein the staple base defines a first zone comprising a first hardness, a plurality of bend portions extending from the staple base, wherein the bend portions define a second zone comprising a second hardness, and staple legs extending from the bend portions, wherein each staple leg defines a third zone comprising a third hardness different than the first hardness.

Example 207 - The surgical staple cartridge of Example 206, wherein the first hardness is greater than the third hardness.

Example 208 - The surgical staple cartridge of Example 206, wherein the first hardness is greater than the second hardness and the third hardness.

Example 209 - The surgical staple cartridge of Examples 206, 207, or 208, wherein each staple leg comprises a staple tip defining a fourth zone comprising a fourth hardness which is less than the third hardness.

Example 210 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a sled, a cartridge body, a plurality of staple cavities, and a strip of staples removably stored within the staple cavities, wherein the strip of staples comprises a plurality of staples, a strip, and a plurality of connector portions joining the staples to the strip, wherein the connector portions are configured to release the staples from the strip.

Example 211 - The surgical staple cartridge of Example 210, wherein each connector portion comprises a discontinuity configured to encourage the separation of the staples from the strip.

Example 212 - The surgical staple cartridge of Example 210, wherein each connector portion comprises a discontinuity configured to encourage the separation of the staple from the strip when the strip of staples is loaded into the cartridge body.

Example 213 - The surgical staple cartridge of Examples 210 or 211, wherein the sled is configured to separate the plurality of staples from the strip by breaking the connector portions when the sled is translated through the staple cartridge.

Example 214 - The surgical staple cartridge of Examples 210, 211, 212, or 213, wherein each staple comprises a pair of outwardly biasing staple legs configured to engage the cartridge body and hold the strip of staples in the surgical staple cartridge.

Example 215 - The surgical staple cartridge of Examples 210, 211, 212, 213, or 214, wherein the cartridge body comprises a bottom, and wherein the strip of staples is configured to be loaded into the bottom of the cartridge body.

Example 216 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, or 215, wherein the plurality of staples are arranged in a first row and a second row, and wherein the strip is joined to the staples in the first row and the second row.

Example 217 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, 215, or 216, wherein the plurality of staples comprises a first group of staples having a first configuration and a second group of staples having a second configuration different than the first configuration.

Example 218 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, 215, 216, or 217, wherein the connector portion comprises a peened portion.

Example 219 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, 215, 216, 217, or 218, wherein the sled comprises striking portions configured to break the connector portions.

Example 220 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, 215, 216, 217, 218, or 219, wherein the staples comprise a chamfered surface configured to engage the sled when the sled is translated through the cartridge body.

Example 221 - The surgical staple cartridge of Examples 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, or 220, wherein the strip comprise alignment features configured to engage corresponding alignment features on the cartridge body.

Example 222 - A surgical staple cartridge for use with a surgical stapling instrument, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities, and a strip of staples removably stored within the cartridge body, the strip of staples comprising a plurality of staples, a strip, and a plurality of connector portions joining the staples to the strip, wherein the connector portions are engageable to release the staples from the strip, and wherein the staples, the strip, and the connector portions are metal.

Example 223 - The surgical staple cartridge of Example 222, wherein the plurality of staples comprises a first plurality of staples comprising a first crown width and a second plurality of staples comprising a second crown width which is different than the first crown width.

Example 224 - The surgical staple cartridge of Examples 222 or 223, wherein the plurality of staples comprises a first group of staples comprising staple legs defining a first height and a second group of staples comprising staple legs defining a second height different than the first height.

Example 225 - The surgical staple cartridge of Example 222, wherein the strip of staples comprises a uniform composition.

Example 226 - The surgical staple cartridge of Examples 222, 223, 224, or 225, wherein the strip comprises alignment features configured to engage corresponding alignment features on the cartridge body.

Example 227 - The surgical staple cartridge of Example 222, 223, 224, 225, or 226, further comprising a second strip of staples comprising a plurality of second staples, a second strip, and a plurality of second connector portions joining the second staples to the second strip, wherein the plurality of staples are arranged in a plurality of rows defining a first row spacing, wherein the plurality of second staples are arranged in a plurality of second rows defining a second row spacing, and wherein the first row spacing and the second row spacing are different.

Example 228 - A metal strip of surgical staples configured for use with a surgical staple cartridge, the metal strip of surgical staples comprising a plurality of staples, a ribbon, and a plurality of connector portions joining the staples to the ribbon.

Example 229 - The metal strip of surgical staples of Example 228, wherein the connector portions comprise a discontinuity notch.

Example 230 - A surgical staple cartridge for use with a circular stapler, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities defined in the cartridge body, and a plurality of staples removably stored within the staple cavities, the plurality of staples comprising an inner row of staples comprising a quantity of first staples, wherein each first staple comprises a first staple crown defining a first staple crown width, an intermediate row of staples positioned radially outward with respect to the inner row of staples, wherein the intermediate row of staples comprises a quantity of second staples, and wherein each second staple comprises a second staple crown defining a second staple crown width, and an outer row of staples positioned radially outward with respect to the intermediate row of staples, wherein the outer row of staples comprises a quantity of third staples, wherein each third staple comprises a third staple crown defining a third staple crown width, and wherein one of the first staple crown width, the second staple crown width, and the third staple crown width is different than another of the first staple crown width, the second staple crown width, and the third staple crown width.

Example 231 - The surgical staple cartridge of Example 230, wherein the inner row of staples defines a plurality of first gaps between the first staples, and wherein the second staples of the intermediate row of staples overlap the first gaps.

Example 232 - The surgical staple cartridge of Example 231, wherein the intermediate row of staples defines a plurality of second gaps between the second staples, wherein the second gaps are larger than the first gaps, and wherein the third staples of the outer row of staples overlap the second gaps.

Example 233 - The surgical staple cartridge of Examples 231 or 232, wherein the third staples of the outer row of staples also overlap the first gaps.

Example 234 - The surgical staple cartridge of Example 230, wherein the inner row of staples defines a plurality of first gaps between the first staples, wherein the intermediate row of staples defines a plurality of second gaps between the second staples, wherein the second staples overlap the first gaps, and wherein the first gaps and the second gaps are at least substantially equal.

Example 235 - The surgical staple cartridge of Example 230, wherein the inner row of staples defines a plurality of first gaps between the first staples, wherein the intermediate row of staples defines a plurality of second gaps between the second staples, wherein each first gap defines a first distance, and wherein each second gap defines a second distance which is less than the first distance.

Example 236 - The surgical staple cartridge of Examples 230, 231, 232, 233, 234, or 235, wherein the first staple crown width is less than the second staple crown width.

Example 237 - The surgical staple cartridge of Examples 230, 231, 232, 233, 234, or 235, wherein the first staple crown width is at least substantially equal to the second staple crown width.

Example 238 - The surgical staple cartridge of Examples 230, 231, 232, 233, 234, 235, 236, or 237, wherein the third staple crown width is greater than the first staple crown width and the second staple crown width.

Example 239 - A surgical staple cartridge for use with a circular stapler, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities defined in the cartridge body, and a plurality of staples removably stored within the staple cavities, the plurality of staples comprising an inner row of staples comprising a first quantity of first staples, wherein each first staple comprises a first staple crown defining a first staple crown width, an intermediate row of staples positioned radially outward with respect to the inner row of staples, wherein the intermediate row of staples comprises a second quantity of second staples, and wherein each second staple comprises a second staple crown defining a second staple crown width, and an outer row of staples positioned radially outward with respect to the intermediate row of staples, wherein the outer row of staples comprises a third quantity of third staples, wherein each third staple comprises a third staple crown defining a third staple crown width, wherein one of the first staple crown width, the second staple crown width, and the third staple crown width is different than another of the first staple crown width, the second staple crown width, and the third staple crown width, and wherein one of the first quantity,

the second quantity, and the third quantity is different than another of the first quantity, the second quantity, and the third quantity.

Example 240 - The surgical staple cartridge of Example 239, wherein the second quantity is less than the first quantity.

Example 241 - The surgical staple cartridge of Examples 239 or 240, wherein the second quantity is less than the third quantity.

Example 242 - The surgical staple cartridge of Examples 239, 240, or 241, wherein the plurality of staple cavities comprises a plurality of non-uniform cavity extenders.

Example 243 - The surgical staple cartridge of Examples 239, 240, 241, or 242, wherein each first staple of the inner row of staples comprises a pair of staple legs extending radially outward from each first staple crown.

Example 244 - The surgical staple cartridge of Examples 239, 240, 241, 242, or 243, wherein each second staple of the intermediate row of staples comprises a pair of staple legs extending radially inward from each second staple crown.

Example 245 - The surgical staple cartridge of Examples 239, 240, 241, 242, 243, or 244, wherein each third staple of the outer row of staples comprises a pair of staple legs extending radially inward from each third staple crown.

Example 246 - A surgical staple cartridge for use with a surgical stapler, the surgical staple cartridge comprising a cartridge body, a plurality of staple cavities defined in the cartridge body, and a plurality of staples removably stored within the staple cavities, the plurality of staples comprising an inner row of staples comprising a first quantity of first staples, wherein each first staple comprises a first staple crown defining a first staple crown width, an intermediate row of staples positioned outward with respect to the inner row of staples, wherein the intermediate row of staples comprises a second quantity of second staples, and wherein each second staple comprises a second staple crown defining a second staple crown width, and an outer row of staples positioned outward with respect to the intermediate row of staples, wherein the outer row of staples comprises a third quantity of third staples, wherein each third staple comprises a third staple crown defining a third staple crown width, and wherein one of the first staple crown width, the second staple crown width, and the third staple crown width is different than another of the first staple crown width, the second staple crown width, and the third staple crown width.

Example 247 - The surgical staple cartridge of Example 246, wherein one of the first quantity, the second quantity, and the third quantity is different than another of the first quantity, the second quantity, and the third quantity.

Example 248 - The surgical staple cartridge of Example 246, wherein the first quantity and the second quantity are equal.

Example 249 - The surgical staple cartridge of Examples 246, 247, or 248, wherein the inner row of staples defines a plurality of first gaps between the first staples, wherein the intermediate row of staples defines a plurality of second gaps between the second staples, wherein each first gap defines a first distance, and wherein each second gap defines a second distance which is less than the first distance.

[0260] The entire disclosures of:

U.S. Patent No. 5,403,312, entitled ELECTROSURGICAL HEMOSTATIC DEVICE, which issued on April 4, 1995;

U.S. Patent No. 7,000,818, entitled SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, which issued on February 21, 2006;

U.S. Patent No. 7,422,139, entitled MOTOR-DRIVEN SURGICAL CUTTING AND FASTENING INSTRUMENT WITH TACTILE POSITION FEEDBACK, which issued on September 9, 2008;

U.S. Patent No. 7,464,849, entitled ELECTRO-MECHANICAL SURGICAL INSTRUMENT WITH CLOSURE SYSTEM AND ANVIL ALIGNMENT COMPONENTS, which issued on December 16, 2008;

U.S. Patent No. 7,670,334, entitled SURGICAL INSTRUMENT HAVING AN ARTICULATING END EFFECTOR, which issued on March 2, 2010;

U.S. Patent No. 7,753,245, entitled SURGICAL STAPLING INSTRUMENTS, which issued on July 13, 2010;

U.S. Patent No. 8,393,514, entitled SELECTIVELY ORIENTABLE IMPLANTABLE FASTENER CARTRIDGE, which issued on March 12, 2013;

U.S. Patent Application Serial No. 11/343,803, entitled SURGICAL INSTRUMENT HAVING RECORDING CAPABILITIES; now U.S. Patent No. 7,845,537;

U.S. Patent Application Serial No. 12/031,573, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT HAVING RF ELECTRODES, filed February 14, 2008;

U.S. Patent Application Ser. No. 12/031,873, entitled END EFFECTORS FOR A SURGICAL CUTTING AND STAPLING INSTRUMENT, filed February 15, 2008, now U.S. Patent No. 7,980,443;

U.S. Patent Application Serial No. 12/235,782, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT, now U.S. Patent No. 8,210,411;

U.S. Patent Application Serial No. 12/249,117, entitled POWERED SURGICAL CUTTING AND STAPLING APPARATUS WITH MANUALLY RETRACTABLE FIRING SYSTEM, now U.S. Patent No. 8,608,045;

U.S. Patent Application Serial No. 12/647,100, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT WITH ELECTRIC ACTUATOR DIRECTIONAL CONTROL ASSEMBLY, filed December 24, 2009; now U.S. Patent No. 8,220,688;

U.S. Patent Application Ser. No. 12/893,461, entitled STAPLE CARTRIDGE, filed September 29, 2012, now U.S. Patent No. 8,733,613;

U.S. Patent Application Ser. No. 13/036,647, entitled SURGICAL STAPLING INSTRUMENT, filed February 28, 2011, now U.S. Patent No. 8,561,870;

U.S. Patent Application Serial No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Patent No. 9,072,535;

U.S. Patent Application Serial No. 13/524,049, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING A FIRING DRIVE, filed on June 15, 2012; now U.S. Patent No. 9,101,358;

U.S. Patent Application Serial No. 13/800,025, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on March 13, 2013, now U.S. Patent Application Publication No. 2014/0263551;

U.S. Patent Application Serial No. 13/800,067, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on March 13, 2013, now U.S. Patent Application Publication No. 2014/0263552;

U.S. Patent Application Publication No. 2007/0175955, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT WITH CLOSURE TRIGGER LOCKING MECHANISM, filed January 31, 2006; and

U.S. Patent Application Publication No. 2010/0264194, entitled SURGICAL STAPLING INSTRUMENT WITH AN ARTICULATABLE END EFFECTOR, filed April 22, 2010, now U.S. Patent No. 8,308,040, are hereby incorporated by reference herein.

[0261] Although the various embodiments of the devices have been described herein in connection with certain disclosed embodiments, many modifications and variations to those embodiments may be implemented. Also, where materials are disclosed for certain components, other materials may be used. Furthermore, according to various embodiments, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to perform a given function or functions. The foregoing description and following claims are intended to cover all such modification and variations.

[0262] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[0263] By way of example only, aspects described herein may be processed before surgery. First, a new or used instrument may be obtained and when necessary cleaned. The instrument may then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument may then be placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation may kill bacteria on the instrument and in the container. The sterilized instrument may then be stored in the sterile container. The sealed container may keep the instrument sterile until it is opened in a medical facility. A device also may be sterilized using any other technique known in the art, including but not limited to beta or gamma radiation, ethylene oxide, plasma peroxide, or steam.

[0264] While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles.

[0265] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.


WHAT IS CLAIMED IS:

1. A staple cartridge assembly, comprising:
 - a cartridge body, comprising:
 - a deck; and
 - a plurality of staple cavities defined in said deck;
 - a plurality of staples stored in said staple cavities, wherein each said staple comprises:
 - a first portion comprised of an alloy including zinc and magnesium; and
 - a second portion comprised of an absorbable polymer, wherein said second portion is disposed on said first portion, and wherein said second portion covers less than the entirety of said first portion.
2. The staple cartridge assembly of Claim 1, wherein said first portion comprises a base and a staple leg extending from said base, and wherein said second portion extends around said staple leg in a spiral pattern.
3. The staple cartridge assembly of Claim 1, wherein said second portion is coated on said first portion in a dot-matrix pattern.
4. The staple cartridge assembly of Claim 1, wherein said first portion comprises a base and a staple leg extending from said base, wherein a corner is defined between said base and said staple leg, and wherein said second portion covers said corner.
5. The staple cartridge assembly of Claim 1, wherein said absorbable polymer comprises a non-crosslinked polymer.
6. The staple cartridge assembly of Claim 1, wherein said second portion is coated on said first portion in a mesh pattern.
7. The staple cartridge assembly of Claim 1, wherein said first portion comprises a base and a staple leg extending from said base, wherein said staple leg comprises a tissue penetrating tip, and wherein said staple further comprises magnesium nitride disposed on said tip.

8. The staple cartridge assembly of Claim 1, wherein said staple further comprises a coating of ionized silver on at least part of said first portion that is not coated by said second portion.
9. The staple cartridge assembly of Claim 1, further comprising at least one aperture in said first portion.
10. A staple cartridge assembly, comprising:
a cartridge body, comprising:
a deck; and
a plurality of staple cavities defined in said deck; and
a plurality of staples stored in said staple cavities, wherein each said staple comprises:
a metal frame comprised of a magnesium alloy; and
an absorbable polymer coated on said metal frame, wherein said absorbable polymer does not cover every portion of said metal frame.
11. A staple cartridge assembly, comprising:
a cartridge body, comprising:
a deck; and
a plurality of staple cavities defined in said deck; and
a plurality of staples stored in said staple cavities, wherein each said staple comprises:
a metal frame comprised of a magnesium alloy, wherein said metal frame comprises a base and a leg extending from said base, and wherein said leg comprises a tissue penetrating tip;
and
a magnesium nitride coating on said tip.
12. The staple cartridge assembly of Claim 11, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said absorbable polymer does not cover every portion of said metal frame.

13. The staple cartridge assembly of Claim 11, wherein each said staple further comprises a coating comprising silver on at least a portion of said metal frame.
14. A staple cartridge assembly, comprising:
a cartridge body, comprising:
a deck; and
a plurality of staple cavities defined in said deck; and
a plurality of staples stored in said staple cavities, wherein each said staple comprises:
a metal frame comprised of a magnesium alloy, wherein said metal frame comprises a base and a leg extending from said base, and wherein said leg comprises a tissue penetrating tip;
and
a coating comprising silver on at least a portion of said metal frame.
15. The staple cartridge assembly of Claim 13, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said absorbable polymer does not cover every portion of said metal frame.
16. The staple cartridge assembly of Claim 13, further comprising a magnesium nitride coating on said tip.
17. A staple cartridge assembly, comprising:
a cartridge body, comprising:
a deck; and
a plurality of staple cavities defined in said deck; and
a plurality of staples stored in said staple cavities, wherein each said staple comprises:
a metal frame comprised of a magnesium alloy, wherein said metal frame comprises a base and a leg extending from said base, and wherein said leg comprises tissue penetrating tip;
and
an aperture defined in said metal frame.

18. The staple cartridge assembly of Claim 17, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said absorbable polymer does not cover every portion of said metal frame.
19. The staple cartridge assembly of Claim 17, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said absorbable polymer is not positioned in said aperture.
20. The staple cartridge assembly of Claim 17, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said absorbable polymer is positioned in said aperture.
21. The staple cartridge assembly of Claim 17, wherein each said staple further comprises an absorbable polymer coated on said metal frame, and wherein said aperture is filled with said absorbable polymer.



2/66




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

4/66




FIG. 7




FIG. 8

5/66




FIG. 9




FIG. 10

6/66




FIG. 11




FIG. 11A




FIG. 11B




FIG. 11C

7/66




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 18

10/66




FIG. 16




FIG. 17

11/66




FIG. 19




FIG. 20




FIG. 21

12/66




FIG. 22




FIG. 23




FIG. 24

13/66




FIG. 25




FIG. 26





FIG. 27



15/66




FIG. 28

16/66




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 29




FIG. 30

18/66





FIG. 31






FIG. 33

20/66




FIG. 34

21/66




FIG. 35

22/66




FIG. 3

23/66




FIG. 37

24/66




FIG. 38

25/66




FIG. 39




FIG. 40

26/66




FIG. 41




FIG. 42

27 / 66




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48

30/66




FIG. 49




FIG. 50

31/66






FIG. 51

32/66



33/66




FIG. 54




FIG. 55




FIG. 56

34/66




FIG. 59

FIG. 58





FIG. 57



36/66




FIG. 62




FIG. 63

37/66






FIG. 64






FIG. 67




FIG. 68

40/66




FIG. 69






FIG 70



42/66




FIG. 73

43/66




FIG. 74

44/66




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79

47/66




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85

50/66




FIG. 86

51/66




FIG. 87




FIG. 88




FIG. 89

53/66




FIG. 90




FIG. 91






FIG. 92



56 / 66




FIG. 95




FIG. 96

58/66




FIG. 97

59/66




FIG. 98




FIG. 99




FIG. 100

61/66




FIG. 101

62/66




FIG. 102




FIG. 103

64/66




FIG. 104

65/66




FIG. 105

66/66




FIG. 106

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2016/046312

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61L31/02 A61L31/10 A61L31/14 A61B17/072 A61B17/11
A61B90/00 A61B17/04 A61B17/064 A61B17/115 A61B17/00
A61B17/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2006/052824 A1 (RANSICK MARK H [US] ET AL) 9 March 2006 (2006-03-09) claims 1-21	1-21
A	WO 2007/125532 A2 (BIOMAGNESIUM SYSTEMS LTD [IL]; AGHION ERNEST ELIYAHU [IL]; ARNON AMIR) 8 November 2007 (2007-11-08) pages 21, 29-3; claim 1	1-21
A	US 2012/241492 A1 (SHELTON IV FREDERICK E [US] ET AL) 27 September 2012 (2012-09-27) paragraph [0396]; claims 1-8	1-21



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 November 2016

Date of mailing of the international search report

21/11/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Schneider, Aurore

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/046312

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2006052824	A1	09-03-2006	NONE
WO 2007125532	A2	08-11-2007	AU 2007245256 A1 08-11-2007
		BR PI0710355 A2 09-08-2011	
		CA 2645737 A1 08-11-2007	
		CN 101484599 A 15-07-2009	
		EP 2021522 A2 11-02-2009	
		JP 2009535504 A 01-10-2009	
		KR 20080113280 A 29-12-2008	
		US 2009081313 A1 26-03-2009	
		WO 2007125532 A2 08-11-2007	
US 2012241492	A1	27-09-2012	EP 2644119 A2 02-10-2013
			EP 2644123 A1 02-10-2013
			EP 2644125 A2 02-10-2013
			EP 2653115 A1 23-10-2013
			US 2012241492 A1 27-09-2012
			US 2013256367 A1 03-10-2013
			US 2013256368 A1 03-10-2013
			US 2013256369 A1 03-10-2013
			US 2013256380 A1 03-10-2013
			US 2016192929 A1 07-07-2016
			WO 2013148766 A2 03-10-2013
			WO 2013148825 A1 03-10-2013
			WO 2013148827 A2 03-10-2013
			WO 2013148828 A2 03-10-2013