



(12) **United States Patent**
Feldstein

(10) **Patent No.:** **US 10,920,491 B2**
(45) **Date of Patent:** **Feb. 16, 2021**

(54) **SHADING AND LIGHTING CONTROL USING A CONTROL NETWORK**

(71) Applicant: **Crestron Electronics, Inc.**, Rockleigh, NJ (US)
(72) Inventor: **George Feldstein**, Rockleigh, NJ (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/292,508**
(22) Filed: **Mar. 5, 2019**

(65) **Prior Publication Data**
US 2019/0203532 A1 Jul. 4, 2019

Related U.S. Application Data
(60) Division of application No. 15/047,251, filed on Feb. 18, 2016, now Pat. No. 10,358,869, which is a division of application No. 14/306,685, filed on Jun. 17, 2014, now Pat. No. 9,267,327, and a continuation of application No. 14/306,656, filed on Jun. 17, 2014, now Pat. No. 9,366,082.

(51) **Int. Cl.**
E06B 9/68 (2006.01)
H04L 12/28 (2006.01)
(52) **U.S. Cl.**
CPC **E06B 9/68** (2013.01); **H04L 12/283** (2013.01); **H04L 12/2816** (2013.01); **E06B 2009/6809** (2013.01); **G05B 2219/25011** (2013.01); **G05B 2219/2642** (2013.01); **G05B 2219/2653** (2013.01); **H04L 2012/285** (2013.01)
(58) **Field of Classification Search**
CPC E06B 9/68; E06B 9/72; E06B 2009/6809; H04L 49/405; H04L 12/2816; G05B 15/02; G05B 19/06; G05B 2219/2653
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

5,372,172 A 12/1994 Homer
5,523,668 A 6/1996 Feldstein
6,771,044 B1 8/2004 Vinciguerra
6,983,783 B2 1/2006 Carmen, Jr. et al.
(Continued)


OTHER PUBLICATIONS
"A Methodology for Detailed Calculation of Illuminance Levels and Light Dimming Factors in a Room with Motorized Blinds Integrated in an Advanced Window", Tzempelikos, A., Thesis, Concordia University, Montreal, Quebec, Canada, 2001, National Library of Canada, 0-612-59299-5.
(Continued)

Primary Examiner — Bitew A Dinke

(57) **ABSTRACT**

A control system is disclosed that includes a room controller transmitting signals to both a shade control network and a light control network, directing that motorized roller shades and dimmable lights be set to desired intensity levels. The control system further includes an intelligent hub that provides a trickle-charge re-charge current via power-over-Ethernet cables to batteries associated with each of the motorized roller shades for re-charging the batteries, thereby eliminating power supplies being installed within walls. The intelligent hub provides for communication with the room controller based on streaming protocol and with the shade control network based on event-based protocol. A computer running user interface software may be connected to the system to facilitate programming.

12 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,085,627 B2 * 8/2006 Bamberger H04L 12/2829
700/277

7,389,806 B2 6/2008 Kates

7,950,827 B2 5/2011 Veskovic

8,179,061 B1 * 5/2012 Liao E06B 9/68
318/16

9,267,327 B2 * 2/2016 Feldstein G05B 11/01

9,366,082 B2 * 6/2016 Feldstein G05B 11/01

9,812,901 B2 11/2017 Descarries

9,860,071 B2 1/2018 Bodo

10,202,801 B2 * 2/2019 Feldstein H04L 12/00

10,358,869 B2 * 7/2019 Feldstein H04L 12/2816

2004/0250964 A1 * 12/2004 Carmen, Jr. H05B 47/10
160/120

2005/0110416 A1 * 5/2005 Veskovic E06B 9/32
315/149

2005/0131554 A1 * 6/2005 Bamberger H04L 12/2803
700/19

2005/0288823 A1 12/2005 Hesse et al.

2006/0165097 A1 7/2006 Caveney

2006/0185799 A1 * 8/2006 Kates E06B 9/32
160/5

2008/0092075 A1 * 4/2008 Jacob H05B 47/18
715/771

2008/0136261 A1 * 6/2008 Mierta H05B 47/185
307/40

2008/0260363 A1 * 10/2008 Carmen H02P 7/29
388/811

2009/0301672 A1 * 12/2009 Veskovic E06B 9/32
160/405

2010/0188009 A1 * 7/2010 Bull H02J 3/00
315/246

2010/0244709 A1 * 9/2010 Steiner H05B 47/11
315/158

2011/0035061 A1 * 2/2011 Altonen G05D 23/1919
700/278

2011/0265958 A1 * 11/2011 Skinner E06B 9/322
160/127

2012/0001487 A1 * 1/2012 Pessina H05B 47/105
307/31

2012/0025802 A1 * 2/2012 Carmen H05B 45/37
323/320

2012/0050596 A1 * 3/2012 Feldstein G05B 15/02
348/311

2012/0053731 A1 * 3/2012 Feldstein E06B 9/42
700/275

2012/0125543 A1 * 5/2012 Chambers E06B 9/307
160/5

2012/0193035 A1 * 8/2012 Malekpour E06B 9/68
160/5

2012/0261078 A1 * 10/2012 Adams E06B 9/32
160/6

2014/0076508 A1 * 3/2014 Mullet B23B 3/00
160/310

2014/0132475 A1 * 5/2014 Bhutani H01Q 9/42
343/866

2014/0145511 A1 * 5/2014 Renzi E06B 9/68
307/84

2014/0156079 A1 * 6/2014 Courtney G05B 15/02
700/275

2014/0305602 A1 * 10/2014 Kirby E06B 9/72
160/310

2015/0048924 A1 * 2/2015 Feldstein G07C 9/27
340/5.51

2015/0107788 A1 * 4/2015 Mullet A47H 5/0325
160/405

2015/0130641 A1 5/2015 Rahman et al.

2015/0286938 A1 * 10/2015 Blair G06F 30/20
706/11

2015/0295411 A1 * 10/2015 Courtney H05B 47/155
700/295

2015/0368967 A1 * 12/2015 Lundy E06B 9/68
160/5

2016/0017656 A1 * 1/2016 Adreon E06B 9/68
160/7

2016/0040478 A1 * 2/2016 Lundy E06B 9/68
700/275

2016/0047164 A1 * 2/2016 Lundy E06B 9/68
160/5

2017/0172333 A1 * 6/2017 Mullet A47H 1/02

OTHER PUBLICATIONS

“Active Load Management with Advanced Window Wall System; Research and Industry Perspectives,” Lee, E., et al., Lawrence Berkeley National Laboratory, University of California, Jun. 1, 2002, <http://escholarship.org/uc/item/5rv2v5wg>.

“Integrated Performance of an Automated Ventilation Blind/Electric Lighting System in a Full-Scale Private Office,” Lee, E. S., et al., Lawrence Berkeley National Laboratory, University of California, 1998-09.

“A Comprehensive Approach to Integrated Envelope and Lighting Systems for New Commercial Buildings,” Lee, E. S., et al., Lawrence Berkeley National Laboratory, University of California, 1994-05.

“Perspectives on Advanced Facades with Dynamic Glazings and Integrated Lighting Controls,” Selkowitz, S. E., et al., Presented at CISBAT 2003 Innovations in Building Envelopes and Environmental Systems, International Conferences on Solar Energy in Building, Oct. 8, 2003, Ecole Polytechnique Federale de Lausanne, Lausanne, Switzerland.

Nov. 18, 2015_NOA.

Oct. 12, 2015_Resp_NFOA.

Jun. 10, 2015_OA.

Feb. 24, 2015_Resp_Restr_Requirement.

Aug. 11, 2014_Preliminary_Amendment.

Feb. 2, 2015_RR.

May 13, 2016_Response_to_Amendment_Under_Rule_312.

Feb. 12, 2016_NoticeofAllowanceANDCorrectDrawings.

May 30, 2018_Office_Action.

Aug. 10, 2018_Response.

NPL_06_Proc_Doc.

NPL_07_Proc_Doc.

NPL_08_Proc_Doc.

NPL_09_Proc_Doc.

NPL_10_Proc_Doc.

NPL_11_Proc_Doc.

NPL_12_Proc_Doc.

NPL_13_Proc_Doc.

* cited by examiner




FIG. 1
(Prior Art)




FIG. 2
(Prior Art)




FIG. 3
(Prior Art)




FIG. 4




FIG. 5




FIG. 6




FIG. 8





FIG. 9




FIG. 10




FIG. 11

1200




FIG. 12




FIG. 13

1400
↙




FIG. 14

SHADING AND LIGHTING CONTROL USING A CONTROL NETWORK

PRIORITY INFORMATION

The present Application is a divisional Application of U.S. Non-provisional patent application Ser. No. 15/047,251 (Client Matter No. CP00302-02), filed 18 Feb. 2016, which is a Divisional Application to U.S. Non-provisional patent application Ser. No. 14/306,685 (Client Matter No. CP00302-01), filed 17 Jun. 2014, and U.S. Non-provisional patent application Ser. No. 15/047,251 (Client Matter No. CP00302-02) is a Continuation Application to U.S. Non-provisional patent application Ser. No. 14/306,656 (Client Matter No. CP00302-00), filed 17 Jun. 2014, the entire contents of all of which are expressly incorporated herein by reference.

BACKGROUND OF THE INVENTION

Technical Field

Aspects of the embodiments relate to an integrated home automation system that includes centralized control for controlling motorized shades in a residential home.

Background Art

It is known to control the operation of a motorized shade or drapery by transmitting command signals to the motorized shade or drapery from a control system, thereby, directing the motor to move the shade or drape. Shades move in a vertical direction and wrap around a roller tube while drapes move in a horizontal direction. One known example of a control system that operates motorized screens, drapes, and curtains is illustrated in a 1989-1999 catalog published by Crestron Electronics, Inc.

Furthermore, one skilled in the art of network control system design would recognize that there is no difference between the type of commands used to control shades, lighting, slide projectors, and other pieces of interfacing equipment. Certain of prior art patents, such as U.S. Pat. No. 7,085,627 (“the ‘627 Patent”), assigned to Lutron Electronics Inc., purport to distinguish between various subsystems that could be used in all overall home automation system, such as a “lighting system,” a “shade network,” and a “security system.” However, these patents are typically written from the aspect of a company that specializes in one of the subsystems (i.e. Lutron Electronics, Inc. specializes in lighting) and not from the point of view of a company specializing in control systems (i.e. AMX, Control4, Crestron, or Savant).

It would have been apparent to one skilled in the art of computer network technology that there are no basic network design features (i.e. physical layer, baud rate or network topology) that would be different based on whether a network was used to control residential shades, residential lighting, or other residential systems. So, regardless of certain representations made in the ‘627 patent there simply has not been any difference between shade control communication networks and lighting control networks.

FIG. 1 illustrates a conventional shade system **100** that includes motorized roller shade (shade) **106** that is used to cover window **108**. Shade **106** includes flexible shade fabric **104** that is windingly received onto rotatably supported roller tube **102**. Shade **106** also includes an electric motor (not shown) that drivingly engages roller tube **102** in order

to rotate roller tube **102**. It is known to control such shade **106** from a centralized location as part of an overall home automation system.

Referring now to FIG. 2, it would have been clear to a network designer, since at least the late 1980’s, that there are several basic network topologies available for interconnecting various computer-controlled devices, such as for example, interconnecting the various devices of a home automation system. Several different network topologies are shown in FIG. 2, and described below.

In bus network topology **202**, each node is connected to a single cable **203**. A signal from a source node travels in both directions to all nodes connected on the bus cable **203** until it finds the intended recipient node. In all the network topologies shown in FIG. 2, the central, source, or hub node, is shown as the solid, shaded circle, and the attached nodes (which generally represent computers, or in the case of a home automation system, microcontrollers), are shown as the empty, un-shaded circles. In bus network topology **202**, if the intended recipient address, for a particular data packet, does not match any address of a node connected to the bus, then that data packet is ignored. Alternatively, if the intended recipient address matches the address of a node connected to the bus, then that data packet is accepted at that node. Since bus topology **202** consists of only one cable **203**, it is rather inexpensive to implement when compared to other network topologies. However, the low cost of implementing the technology is offset by the high cost of managing the network. Such cost is partially related to the cost of adding other nodes (or computers), which includes running the bus (cable **203**) to the new node and/or a bus-feed to the existing main bus. Additionally, since only one cable is utilized, it can be a single point of failure that takes down the entire network. In terms of home (or commercial) automation systems, additional limitations can include that only a limited amount of power can be transferred to devices on bus network **202** from the central node. If additional nodes are added that require additional power, a new power supply could be required, but there is a limit as to how much power can be transferred over conventional cabling for bus network topology **202**.

In local area networks where star network topology (star network) **204** is used, each node is connected to a central hub with a point-to-point connection. Star network **204** does not necessarily have to resemble a star to be classified as a star network, but all of the nodes on star network **204** must be connected to the one central hub. All traffic that traverses star network **204** passes through the central hub, and as such, the central hub acts as a signal repeater. The star topology is considered the easiest topology to design and implement. An advantage of star network **204** is the simplicity of adding additional nodes. The primary disadvantage of star network **204** is that the hub represents a single point of failure; if it fails, no communications can take place (whereas in bus network **202**, a non-source node (the one or more unshaded nodes) can take over as the source node). In terms of automation systems, star network **204** can transfer larger amounts of power, because each interconnecting cable only has to handle the power that its end node requires (i.e., one cable does not carry all of the current for the entire network), although a new power supply at some point might be required. However, each time a new node is added, the cable must be “home-runned” back to the central (or source) node, which can be costly.

Another local area network is daisy-chain network topology (daisy-chain network) **206**. In daisy-chain network **206**, it is fairly easy and straightforward to add more computers

into the network by daisy-chaining, or connecting each computer in series to the next. If a message is intended for a computer partway down the line, each system bounces it along in sequence until it reaches the destination. A daisy chain network can take two basic forms: linear and ring. In terms of automation systems, daisy chain network **206** is also problematic in terms of power because all of the power needs to be transferred through one cable, similarly to bus network **202**; thus, there are practical limitations as to the number of devices that can be attached and/or the total power that can be provided. If additional power is required in nodes further down the line in the daisy chain, then local transformers or other power supplies could be necessary to provide the additional power.

A linear topology in a daisy chain network **206** puts a two-way link between one computer and the next. By connecting the computers at each end, a ring topology can be formed. An advantage of the ring topology is that the number of transmitters and receivers can be cut in half, since a message will eventually loop all of the way around. When a node sends a message, the message is processed by each computer in the ring. If the ring breaks at a particular link then the transmission can be sent via the reverse path thereby ensuring that all nodes are always connected in the case of a single failure.

Tree network topology (tree network) **208** is also shown in FIG. 2. The topology of tree network **208** is based on a hierarchy of nodes. The highest level of any tree network consists of a single, or 'root' node **210** (i.e., the solid circle of tree network **208**). Root node **210** is connected either to a single (or, more commonly, multiple) node(s) **212** in the level below by point-to-point links (note that root node **210** is connected first to first lower level node **212a**, and then first lower level node **212a** is connected to first lower level node **212b**, and so on). These first lower level nodes **212** are also connected to a single or multiple second lower level nodes **214** in the next level down. Tree networks **208** are not constrained to any number of levels, but as tree networks **208** are a variant of bus network **202** topology, they are prone to crippling network failures should a connection in a higher level of nodes fail/suffer damage (i.e., if first lower level node **212a** failed, everything would essentially fail as root node **210** is then cut off from all of the other nodes). Each node in the network has a specific, fixed number of nodes connected to it at the next lower level in the hierarchy ("lower" referring to levels away from root node **210**; the first lower level including first lower level nodes **212**, the next lower level including second lower level nodes **214**, and so on), this number being referred to as the 'branching factor' of the tree.

While tree networks **208** are capable in terms of data throughput, in terms of power distribution, tree networks **208** suffer from the same limitations as bus network **202** and daisy chain network **206** in that all of the power must be transferred by the first cable from the central node; further, because of the nature of the "tree" like growth, there is no way of knowing in advance how much power each branch might ultimately have to transfer. If additional power is required in nodes further down the branches of the "tree," then local transformers or other power supplies could be necessary to provide the additional power.

The last network topology to be discussed in regard to FIG. 2 is mesh network **216**, which is a network topology in which each node (called a mesh node) relays data for the entire network. All nodes cooperate in the distribution of data in mesh network **216**. Mesh network **216** typically has a self-healing capability that enables data rerouting when

one node breaks down or a connection goes bad. As a result, mesh network **216** is typically quite reliable, as there is often more than one path between a source and a destination in mesh network **216**. Although mostly used in wireless situations (shown as dashed lines), the "mesh network" concept is also applicable to wired networks (solid lines) and software interaction. Mesh networks **216** are applicable to data only, as power cannot be effectively be transferred wirelessly.

Mesh networks **216** can be designed using a flooding technique or a routing technique. When using a routing technique, the message is propagated along a path, by hopping from one node to the next node until the destination is reached. To ensure all its paths' availability, a routing network must allow for continuous connections and reconfiguration around broken or blocked paths using self-healing algorithms. A flooding technique is one in which the message is transmitted to all of the nodes of mesh network **216**. The attractiveness of the flooding technology lies in its high reliability and simplicity. As those of skill in the art can appreciate, there is no need for sophisticated routing techniques since there is no routing. No routing means no network management, no need for self-discovery, no need for self-repair, and, because the message is the payload, no overhead for conveying routing tables or routing information.

A mesh network whose nodes are all connected to each other is a fully connected network. A fully connected network can be costly, as either a wired connection is required between each node (or computer) or a wireless interface needs to be installed. Of course, the wireless interface can save wiring costs, but can also prove to be less reliable (and slower) under some conditions, as those of skill in the art can appreciate.

Attention is now directed to FIG. 3. FIG. 3 illustrates a conventional automated combined shading and lighting control network system (control system) **300** that is suitable for use in, among other places, a hotel suite, for controlling motorized roller shades, lighting, televisions, among other devices. It is known by those of skill in the art to provide a centralized control system that provides both lighting and shading control functions. Such a centralized system is shown in FIG. 3.

Control system **300** includes room controller **302**, set top box **304**, television **306**, bus **308** (which can be RS-485, or Cresnet®), interface units (IUs) **310**, transformers **312**, light dimmers **314**, keypads **316**, and shades **106**. Bus **308** is typically capable of carrying 24 VDC. Those of skill in the art can appreciate that other devices, not shown, can also be included in control system **300**. For example, room controller **302** can also be directly connected to, or indirectly connected to (through other routers (not shown)), wide area network (WAN) **322**, such as the Internet. In addition, IUs **310** can be wall mountable for the case of local and remote control of shades **106**, desk mounted, or located elsewhere. Room controller **302** can also be connected to IU **310** for controlling shades **106**, and can also be connected to light dimmers **314** (which are typically wall-mountable) for controlling the dimmable lighting loads. Room controller **302** and transformers **312** are further provided for controlling motorized roller shades **106** by controlling the motors therein to position shades and drapes. An early example of such a centralized control system is "The Creston New Generation Total Control System", circa 1998. In some configurations, IUs **310** also provide signals, typically in digital form (although they can also generate analog signals) to control a collection of one or more relays that provide

power and control signals to the motors in motorized roller shades **106**. The relays can be controlled by bus **308** so that power can be forwarded to motorized roller shades **106** from transformers **312**, alone with control signals that are delivered by bus **308**.

Room controller **302** can transmit command signals to light dimmer **314** for directing that the dimmable loads be set to particular intensity levels that can range from between 0 and 100 percent. Likewise, room controller **302** can also transmit command signals directing that the motorized shades be set to various positions that can range from between fully closed and fully open. Control system **300** can further include microprocessors at each of motorized roller shades **106** in IUs **310** that are connected to the network for transmitting control signals and for storage of a database including network-related information. However, it is also known to those of skill in the art that some control systems **300** do not include processors in any of IU's **310** and/or motorized roller shades **106**.

Control system **300** is programmable such that preset shade positions for shades **106** can be stored in control system **300** for subsequent selection by a user by actuation of a preset actuator provided by IU **310**. Control system **300** is also programmed to address other devices connected to the network with a unique identifier to provide for network communication between the devices and to provide for centralized control of shades **106**. The "other devices" can include television **306**, set top box **304**, as well as light dimmer **314** and keypad **316** (which can used to enter a code to unlock a door, or a card swipe, that can read a magnetic strip, also to unlock the door). Control system **300** is also programmed to assign the electronic drive unit (EDU) **326** of each of shades **106** of control system **300** to one of the wall-mountable IUs **310** for control of its respective EDU **326** from the wall-mountable IU **310**. Note also that for each shade **106** there is a transformer **312** that provides the necessary voltages/power to motorized roller shade **106** via control of its respective IU **310**. It is to be noted that the EDUs are relatively simple devices in this example and do no more than receive command signals from IUs **310**, and transfer the data/commands as needed.

It has also been attempted in the prior art for shade **106** to mimic a light dimmer setting wherein, for example, a dimmer setting of 50% would be equivalent to opening a motorized window shade half-way. This leads, however, to obvious drawbacks in that the outdoor ambient light varies according many factors including season of the year and cloud cover.

It is known by those of skill in the art that connecting either shades or lighting controls to a network is not complicated using any one of several network protocols, such as, but not limited to, Crestron's "Cresnet®", Power over Ethernet, Zigbee, among others. However, it is also known to those of skill in the art that while any one of several network topologies can be used, as discussed above, each has problems associated with them. Furthermore, it is also known by those of skill in the art that conveying power to motorized roller shades, as shown and described in reference to FIG. 3, can involve the separate installation of in-the-wall mountable transformers **312** that presents a host of separate issues. First, there is the construction costs, and damage done to walls. Even if transformers **312** are not wall mounted, they still must be put somewhere, and they are relatively inefficient, generate heat, as well as electrical noise.

Thus, there is a need for a hybrid star and linked network with power storage capability at each node in order to

provide desirable characteristics for a home, office, or hotel suite automation system that includes control of shades, audio speakers, among other devices.

SUMMARY OF THE INVENTION

It is to be understood that both the general and detailed descriptions that follow are explanatory only and are not restrictive of the embodiments.

According to one aspect of the embodiments, a shade control system includes a plurality of drive units each having a motor adapted for moving an associated shade member, and a plurality of drive unit controllers each capable of generating command signals for directing at least one of the drive units to move the associated shade member. The shade control system also includes a communication bus to which each of the drive units and drive unit controllers is connected in a common arrangement such that each one of the drive units and drive unit controllers can communicate with every other drive unit and drive unit controllers.

According to a further aspect of the embodiments, the shade member associated with each drive member is a shade fabric wound onto a roller tube. The drive unit controllers preferably include at least one keypad controller having an open limit actuator and a close limit actuator for generating command signals for moving the associated shade fabric of at least one of the drive units to a predetermined open limit position and a predetermined close limit position. The keypad controller preferably includes a raise actuator and a lower actuator for generating command signals for moving the associated shade fabric of at least one of the drive units through raise and lower position adjustments.

DISCLOSURE OF INVENTION

According to a first aspect of the embodiments, a method for controlling lights and shades is provided, the method comprising transmitting controls signals from a room controller to one or more devices, wherein said control signals represent a desired intensity level setting, receiving the transmitted control signals at the one or more devices, transferring power to a first set of said one or more devices via a power-over-Ethernet (PoE) cable, and converting said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices. According to the first aspect of the embodiments, the step of converting comprises converting a first set of said control signals representing an intensity level setting of a shade such that the motorized roller shades changes a shade position of said shade to match the desired intensity level setting, and converting a second set of said control signals representing an intensity level setting of a dimmable light such that dimmable light controls changes a dimming setting of said dimmable light.

According to the first aspect of the embodiments, the step of converting said first set of control signals comprises transmitting a sequence of control signals to the motorized roller shades such that said motorized shade moves said shade in a series of substantially evenly timed steps of substantially equal distance to simulate a relatively slowly moving shade compared to a normal rate of driven movement for the motorized roller shade, and wherein a motor speed for the at least one motorized shade is variable and wherein the method further comprises transmitting a signal

concurrently with the intensity level directing the at least one motorized shade to move to the associated shade position at a desired speed.

Still further according to the first aspect of the embodiments, the step of transmitting comprises transmitting said control signals from said room controller to an intelligent hub, wherein said control signals further include database information, and forwarding said controls signals from said intelligent hub to a first of one or more motorized roller shades via said PoE cable, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of the at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor. According to the first aspect of the embodiments, said step of transferring power comprises transmitting a trickle-charge re-charging current from said intelligent hub to said first set of said one or more devices over said PoE cable, wherein said set of said one or more devices includes motorized roller shades, and wherein said PoE cable is connected between said intelligent hub and each electronic data unit of each at least one or more motorized roller shades in a daisy chain fashion.

According to the first aspect of the embodiments, said electronic drive unit further includes control electronics, and wherein said control electronics includes an input interface, and an output interface, and wherein said input interface is configured to receive control signals, database information, and trickle-charge re-charging current from either a preceding electronic drive unit or intelligent hub via said PoE cable, and wherein said output interface is configured to transmit control signals, database information, and trickle-charge re-charging current to a subsequent electronic drive unit via said PoE cable.

According to the first aspect of the embodiments, said electronic drive unit further comprises a relay switch network configured to cause electrical power to selectively by-pass said electrical drive unit, and wherein said relay switch network is further configured to selectively allow one or more batteries in one or more different respective motorized roller shades to draw re-charging power from said battery in said motorized roller shade associated with said electrical drive unit.

Still further according to the first aspect of the embodiments, the motorized roller shade further comprises a shade, and a hem bar located at a bottom of said shade, wherein said hem bar includes one or more small batteries electrically connected to each other and said battery of said motorized roller shade, and wherein said small batteries are configured to provide a trickle-charge re-charging current to said battery of said motorized roller shade.

According to a second aspect of the embodiments, a method is provided for controlling lights and shades, the method comprising transmitting controls signals from a room controller to one or more devices, wherein said control signals represent a desired intensity level setting, receiving the transmitted control signals at the one or more devices, transferring power to a first set of said one or more devices from a transformer via a power cable, and converting said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices.

According to the second aspect of the embodiments, the step of converting comprises converting a first set of said control signals representing an intensity level setting of a shade such that the motorized roller shades changes a shade

position of said shade to match the desired intensity level setting, and converting a second set of said control signals representing an intensity level setting of a dimmable light such that dimmable light controls changes a dimming setting of said dimmable light, wherein the step of converting said first set of control signals includes transmitting a sequence of control signals to the motorized roller shades such that said motorized shade moves said shade in a series of substantially evenly timed steps of substantially equal distance to simulate a relatively slowly moving shade compared to a normal rate of driven movement for the motorized roller shade, and further wherein a motor speed for the at least one motorized shade is variable; and wherein the method further comprises transmitting a signal concurrently with the intensity level directing the at least one motorized shade to move to the associated shade position at a desired speed.

Still further according to the second aspect of the embodiments, the step of transmitting comprises transmitting said control signals from said room controller to a mesh network gateway, wherein said control signals further include database information, and forwarding said controls signals wirelessly from said mesh network gateway to each of said one or more motorized roller shades, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of said at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor.

According to the second aspect of the embodiments, the step of transferring power comprises transmitting a trickle-charge re-charging current from said transformer to a first one of said motorized roller shades over said power cable, and wherein a PoE cable is connected between each electronic data unit of each at least one or more motorized roller shades in a daisy chain fashion, and wherein said electronic drive unit further includes control electronics, and wherein said control electronics includes an input interface, and an output interface, and wherein said input interface is configured to receive control signals, database information, and trickle-charge re-charging current from a preceding electronic drive unit, if so connected, via said PoE cable, and wherein said output interface is configured to transmit control signals, database information, and trickle-charge re-charging current to a subsequent electronic drive unit via said PoE cable.

According to the second aspect of the embodiments, said electronic drive unit further comprises a relay switch network configured to cause electrical power to selectively by-pass said electrical drive unit, and wherein said relay switch network is further configured to selectively allow one or more batteries in one or more different respective motorized roller shades to draw re-charging power from said battery in said motorized roller shade associated with said electrical drive unit. According to the second aspect of the embodiments, the motorized roller shade further comprises a shade, and a hem bar located at a bottom of said shade, wherein said hem bar includes one or more small batteries electrically connected to each other and said battery of said motorized roller shade, and wherein said small batteries are configured to provide a trickle-charge re-charging current to said battery of said motorized roller shade.

According to a third aspect of the embodiments, a method for controlling lights and motorized roller shades is provided, the method comprising providing a programmable room controller adapted to store preset intensity levels in a

database of information for devices connected to the room controller, connecting the room controller to a lighting control network including at least one dimmable light, connecting the room controller to a shade control network that includes at least one motorized roller shade, programming the room controller to store preset intensity levels for the dimmable lights of the lighting control network in the database of information, programming the programmable room controller to store a preset intensity level for the at least one motorized roller shade of the shade control network in the database of information, transferring power to said shade control network via a PoE cable from an intelligent hub, and transmitting a portion of the database of information that includes the preset intensity level for the at least one motorized roller shade of the shade control network from the room controller to the shade control network, wherein the shade control network is configured to convert the preset intensity levels into preset shade positions.

According to the third aspect of the embodiment, the method further comprises connecting a keypad to the room controller, wherein the keypad is configured to transmit a command signal to the room controller regarding a selected preset intensity level for the at least one motorized shade of the shade control network in response to a user input, transmitting the command signal regarding the selected intensity level from the room controller to the shade control network; and directing the at least one motorized roller shade to move to the preset shade position associated with the selected intensity level.

According to the third aspect of the embodiments, a motor speed of a motor of the at least one motorized roller shade of the shade control network is variable and the method further comprises programming the room controller to store a desired motor speed associated with the preset intensity level for the at least one motorized roller shade of the shade control network in the database of information for directing the motorized roller shade to move to the associated preset shade position at the desired motor speed, and transmitting the motor speed with the associated preset intensity level to the shade control network in the portion of the database of information that includes the preset intensity level for the at least one motorized roller shade of the shade control network.

According to a fourth aspect of the embodiments, a method for controlling at least one motorized roller shade is provided, the method comprising providing a shade control network including at least one motorized roller shade, wherein each motorized roller shade is configured to transmit feedback information regarding shade position or other condition associated with a shade to the shade control network, providing a room controller connected to the shade control network for controlling the motorized roller shades of the shade control network, wherein the room controller is configured to receive the feedback information from the shade control network regarding the condition or position of the motorized roller shades, providing an intelligent hub connected to the room controller and the shade control network, the intelligent hub configured to store feedback information from the shade control network in memory for independent transmission to the room controller, and wherein said intelligent hub is further configured to transfer power to a first one of said motorized roller devices via a PoE cable, and transmitting feedback information from the motorized roller shades of the shade control system to the intelligent hub, and storing the feedback information for the motorized roller shades in a memory of the intelligent hub.

According to the fourth aspect of the embodiments, the method further comprises providing a timing device in the room controller for associating the shade position for the motorized roller shades to the time of day, transmitting shade position information from the motorized roller shades to the intelligent hub, retrieving the time of day from the timing device, storing the shade position information for the motorized roller shades and the associated time information in memory at the intelligent hub, transmitting the shade position information for the motorized roller shades and the associated time information from the intelligent hub to the room controller, creating a time-based macro program for directing the motorized roller shades of the shade control network to move to given positions at certain times of day based on the information transmitted to the room controller from the intelligent hub, and executing the time-based macro program.

According to the fourth aspect of the embodiments, the method further comprises providing a link between the room controller and the intelligent hub configured to transmit information in cycled packets of information based on a streaming protocol, and transmitting feedback information regarding the motorized roller shades of the shade control network from the intelligent hub to the room controller in a sequential manner using the streaming protocol such that any packet of information transmitted to the room controller that includes feedback information includes feedback information associated with only one of the motorized roller shades.

According to a fifth aspect of the embodiments, a method for controlling a shade control network including at least one motorized roller shade is provided, the method comprising providing a room controller having memory storage capability and an actuator, connecting the room controller to a motorized roller shade that includes a rotatably supported roller tube and a flexible shade fabric woundly received by the roller tube, programming the room controller to store in memory a first preset value associated with a first shade position and a second preset value associated with a second shade position, transferring power to a first one of said motorized roller shades via a PoE cable from an intelligent hub, and moving the motorized roller shade to the first preset shade position in response to an actuation of the actuator, and moving the motorized roller shade to the second preset shade position in response to a subsequent actuation of the actuator.

According to the fifth aspect of the embodiments, the motorized roller shade is toggled between the first and second shade positions in response to actuation of the actuator, the room controller includes a visual indicator located adjacent the actuator to provide a visual indication of the shade position to which the motorized roller shade is toggled to, and the room controller is programmed to set the first shade position by default to either a fully-opened shade position, or a fully-closed shade position.

According to a sixth aspect of the embodiments, a method is provided for programming a shade control network that includes at least one motorized roller shade, the shade control system including a communication network connected to each motorized roller shade, the method comprising connecting a computer having user interface capability to the communication network of the shade control network, transmitting at least a portion of a database of information regarding the shade control network from the computer to the shade control system, transferring power to said shade control network from an intelligent hub via a PoE cable, and

storing the portion of the database of information received by the shade control network in a memory in the shade control network.

According to the sixth aspect of the embodiments, each of the motorized roller shades of the shade control network has memory storage capability, and the method further comprises connecting the computer to a room controller and the shade control network, transmitting substantially all of the database of information regarding the shade control network from the computer to the room controller, transmitting at least a portion of the database of information from the room controller to each of the motorized roller shades, storing the portion of the database of information in memory at each of the motorized roller shades of the shade control network, transmitting an acknowledgement of receipt of the database portion from each of the motorized roller shades to the room controller, and transmitting a report from the room controller to the computer regarding acknowledgement by the at least one motorized roller shade.

According to the sixth aspect of the embodiments, the programming method further comprises connecting said intelligent hub to the communication network of the shade control system to facilitate transfer of information with the shade control network, and connecting said room controller to said intelligent hub, wherein said room controller is part of an integrated control system, and said room controller is configured to control at least one other control system including a lighting control network in addition to the shade control network. Still further according to the sixth aspect of the embodiments, the programming method further comprises connecting a plurality of intelligent hubs to a plurality of shade control network, each shade control network including at least one motorized roller shade, and a communication network connected to each of the motorized roller shades, wherein said communication network includes a PoE cable, and an electronic data unit, and connecting the room controller to each of the intelligent hubs.

According to the sixth aspect of the embodiments, the programming method still further comprises directing the shade control network to move the motorized roller shades in a sequential manner in response to a series of user inputs to provide for unique identification of the motorized roller shades by the shade control network, directing the shade control network to move the motorized roller shades of the shade control network to provide for visual identification of a particular shade among a reduced number of shades in a first subset of shades, and further reducing the number of shades in subsequent subsets by repeating the step of directing the shade control network to move the motorized shades with respect to subsequent subsets until a subset is formed that includes only the particular motorized shade to provide for unique identification of the particular motorized shade by the shade control network, wherein half of the shades of a given subset are moved to form the next subset of shades including the particular shade.

According to the sixth aspect of the embodiments, the shade control network further includes at least one intelligent hub connected to the communication network, the at least one intelligent hub having memory storage capability for storage of database information regarding the shade control network, the method further comprising transmitting at least a portion of the database of information to each of the intelligent hubs of the shade control network, and storing the portion of the database of information in memory at each of the intelligent hubs of the shade control network.

According to a seventh aspect of the embodiments, a system for controlling lights and shades is provided, com-

prising: a room controller adapted to transmit controls signals to one or more devices, wherein said control signals represent a desired intensity level setting, and wherein the one or more devices are adapted to receive the transmitted control signals; and a power cable adapted to transfer power to a first set of said one or more devices from a transformer, and wherein the one or more devices are further adapted to convert said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of said at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor, and wherein said electronic drive unit further comprises a relay switch network configured to cause electrical power to selectively by-pass said electrical drive unit, and wherein said relay switch network is further configured to selectively allow one or more batteries in one or more different respective motorized roller shades to draw re-charging power from said battery in said motorized roller shade associated with said electrical drive unit.

According to the seventh aspect of the embodiments, the one or more devices are further adapted to convert a first set of said control signals representing an intensity level setting of a shade such that the motorized roller shades changes a shade position of said shade to match the desired intensity level setting, and the one or more devices are further adapted to convert a second set of said control signals representing an intensity level setting of a dimmable light such that said dimmable light control signals change a dimming setting of said dimmable light, wherein the conversion of said first set of control signals includes transmitting a sequence of control signals to the motorized roller shades such that said motorized shade moves said shade in a series of substantially evenly timed steps of substantially equal distance to simulate a relatively slowly moving shade compared to a normal rate of driven movement for the motorized roller shade, and further wherein a motor speed for the at least one motorized shade is variable, and wherein the transmission of the sequence of control signals includes transmitting a signal concurrently with the intensity level directing the at least one motorized shade to move to the associated shade position at a desired speed.

According to the seventh aspect of the embodiments, the transmission of the sequence of control signals further includes a transmission of said control signals from said room controller to a mesh network gateway, wherein said control signals further include database information, and a forwarding of said controls signals wirelessly from said mesh network gateway to each of said one or more motorized roller shades.

According to the seventh aspect of the embodiments, the transformer is further adapted to transmit a trickle-charge re-charging current from said transformer to a first one of said motorized roller shades over said power cable, and wherein a power-over-Ethernet (PoE) cable is connected between each electronic data unit of each at least one or more motorized roller shades in a daisy chain fashion.

According to the seventh aspect of the embodiments, said electronic drive unit further includes control electronics, and wherein said control electronics includes an input interface, and an output interface, and wherein said input interface is configured to receive control signals, database information, and trickle-charge re-charging current from a preceding

electronic drive unit, if so connected, via said PoE cable, and wherein said output interface is configured to transmit control signals, database information, and trickle-charge re-charging current to a subsequent electronic drive unit via said PoE cable.

According to the seventh aspect of the embodiments, said motorized roller shade further comprises: a shade; and a hem bar located at a bottom of said shade, wherein said hem bar includes one or more small batteries electrically connected to each other and said battery of said motorized roller shade, and wherein said small batteries are configured to provide a trickle-charge re-charging current to said battery of said motorized roller shade.

According to an eighth aspect of the embodiments, a system for controlling lights and shades is provided, comprising: a room controller adapted to transmit control signals to one or more devices, wherein said control signals represent a desired intensity level setting, and wherein the one or more devices are adapted to receive the transmitted control signals; and a power cable adapted to transfer power to a first set of said one or more devices from a transformer, and wherein the one or more devices are further adapted to convert said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of said at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor, and wherein said motorized roller shade further comprises a shade; and a hem bar located at a bottom of said shade, wherein said hem bar includes one or more small batteries electrically connected to each other and said battery of said motorized roller shade, and wherein said small batteries are configured to provide a trickle-charge re-charging current to said battery of said motorized roller shade.

According to the eighth aspect of the embodiments, the one or more devices are further adapted to convert a first set of said control signals representing an intensity level setting of a shade such that the motorized roller shades changes a shade position of said shade to match the desired intensity level setting, and the one or more devices are further adapted to convert a second set of said control signals representing an intensity level setting of a dimmable light such that said dimmable light control signals change a dimming setting of said dimmable light, wherein the conversion of said first set of control signals includes transmitting a sequence of control signals to the motorized roller shades such that said motorized shade moves said shade in a series of substantially evenly timed steps of substantially equal distance to simulate a relatively slowly moving shade compared to a normal rate of driven movement for the motorized roller shade, and further wherein a motor speed for the at least one motorized shade is variable, and wherein the transmission of the sequence of control signals includes transmitting a signal concurrently with the intensity level directing the at least one motorized shade to move to the associated shade position at a desired speed.

According to the eighth aspect of the embodiments, the transmission of the sequence of control signals further includes a transmission of said control signals from said room controller to a mesh network gateway, wherein said control signals further include database information, and a

forwarding of said controls signals wirelessly from said mesh network gateway to each of said one or more motorized roller shades.

According to the eighth aspect of the embodiments, the transformer is further adapted to transmit a trickle-charge re-charging current from said transformer to a first one of said motorized roller shades over said power cable, and wherein a power-over-Ethernet (PoE) cable is connected between each electronic data unit of each at least one or more motorized roller shades in a daisy chain fashion.

According to the eighth aspect of the embodiments, said electronic drive unit further includes control electronics, and wherein said control electronics includes an input interface, and an output interface, and wherein said input interface is configured to receive control signals, database information, and trickle-charge re-charging current from a preceding electronic drive unit, if so connected, via said PoE cable, and wherein said output interface is configured to transmit control signals, database information, and trickle-charge re-charging current to a subsequent electronic drive unit via said PoE cable.

According to the eighth aspect of the embodiments, said electronic drive unit further comprises: a relay switch network configured to cause electrical power to selectively by-pass said electrical drive unit, and wherein said relay switch network is further configured to selectively allow one or more batteries in one or more different respective motorized roller shades to draw re-charging power from said battery in said motorized roller shade associated with said electrical drive unit.

The aspects of the embodiments described herein seek to overcome or at least ameliorate one or more of several problems, including but not limited to providing an efficient system of networked motorized roller shades.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and features of the embodiments will become apparent and more readily appreciated from the following description of the embodiments with reference to the following figures. Different aspects of the embodiments are illustrated in reference figures of the drawings. It is intended that the embodiments and figures disclosed herein are to be considered to illustrative rather than limiting. The components in the drawings are not necessarily drawn to scale, emphasis instead being placed upon clearly illustrating the principles of the aspects of the embodiments. In the drawings, like reference numerals designate corresponding parts throughout the several views.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 illustrates a conventional motorized roller shade covering a window.

FIG. 2 illustrates various conventional computer data network topologies that may be suitable for connecting residential networks, such as shading, lighting, or combined shading and lighting devices.

FIG. 3 illustrates a conventional automated combined shading and lighting control network system that is suitable for use in, among other places, a hotel suite, for controlling motorized roller shades, lighting, televisions, among other devices.

FIG. 4 illustrates a shading control network comprising motorized shades including electronic drive units configured in a daisy-chain network topology according to an embodiment.

FIG. 5 illustrates a block diagram of the electronic drive unit of FIG. 4 and certain components thereof according to an embodiment.

FIG. 6 illustrates a lighting control network comprising light dimmers and keypads configured in a mesh network topology and suitable for use within an overall home automation system according to an embodiment.

FIG. 7 illustrates a combined shading and lighting room automation control system that includes a shade control network configured in a daisy-chain network topology, a light control network configured in a mesh network, and an intelligent hub configured in a star network according to an embodiment.

FIG. 8 illustrates a partial view of a combined shading and lighting room automation control system similar to that of the system of FIG. 7 that includes a shading control network configured in a daisy-chain network topology, a lighting control network configured in a mesh network, and an intelligent hub configured in a star network according to a further embodiment.

FIG. 9 illustrates a block diagram of an electronic drive unit of FIG. 8 and certain components thereof according to an embodiment.

FIG. 10 is a flowchart of a method for controlling motorized roller shades by transmitting intensity levels from a room controller to one or more of a plurality of motorized roller shades according to an embodiment.

FIG. 11 is a flowchart of a method for storing preset intensity levels at one or more of a plurality of motorized roller shades according to an embodiment.

FIG. 12 is a flowchart of a method for controlling one or more of a plurality of motorized roller shades by transmitting a “set to preset” command from a room controller to at least one of the plurality of the motorized roller shades according to an embodiment.

FIG. 13 is a flowchart of a method for toggling the position of at least one or a plurality of motorized roller shades between two preset positions in response to an actuation of a shade preset actuator according to an embodiment.

FIG. 14 is a flowchart of a method for visually identifying a particular motorized roller shade out of a plurality of motorized roller shades by the “wiggle” method according to an embodiment.

LIST OF REFERENCE NUMBERS FOR THE MAJOR ELEMENTS IN THE DRAWINGS

The following is a list of the major elements in the drawings in numerical order.

- 102 Roller Tube
- 104 Shade Fabric
- 106 Motorized Roller Shade (Shade)
- 108 Window
- 202 Bus Network Topology
- 204 Star Network Topology
- 206 Daisy-chain Network Topology
- 208 Tree Network Topology
- 210 Root Node
- 212 First Lower Level Node
- 214 Second Lower Level Node
- 216 Mesh Network Topology
- 300 Combined Shading and Lighting Control Network System
- 302 Room Controller
- 304 Set-top Box
- 306 Television

- 308 Bus (RS-485/Cresnet)
- 310 Interface Unit
- 312 Transformer
- 314 Light Dimmer
- 316 Keypad
- 318 Infra-red Signals
- 320 Ethernet (CAT5) Cable
- 322 Wide Area Network (WAN)/Local Area Network (LAN)
- 324 Lighting
- 326 Electronic Data Unit
- 400 Shading Control Network (Control Network)
- 402 Room Controller With Integrated Display (House Controller)
- 404 Intelligent Hub
- 406 Power-Over Ethernet Cable
- 408 Electronic Drive Unit
- 410 Room Controller Integrated Display
- 412 Power-over-Ethernet Power Supply
- 414 Computer, Laptop, Tablet, Server, Personal Computer (PC)
- 416 Universal Serial Bus (USB) Cable
- 502 Elongated Motor
- 504 Bearing
- 506 Battery
- 508 Control Electronics
- 510 Input Communication/Power Interface (Input Interface)
- 512 Output Communication/Power Interface (Output Interface)
- 514 Relay/Switch Network
- 600 Wireless Lighting Control Network (Lighting Control Network)
- 602 Zigbee Gateway
- 604 Motion Sensor
- 606 Wireless Light Dimmer
- 608 Wireless Keypad
- 610 Speakers
- 700 Combined Shading and Lighting Room Automation Control System (Room Automation System)
- 702 Wi-Fi Gateway
- 704 Hotel Room Controller (Room Controller)
- 706 Wireless Smoke Detector
- 708 Wireless Door Lock
- 710 Intelligent Hub (PoE and Zigbee)
- 712 Wide Area Network (WAN)
- 714 Lighting System (Lights)
- 716 Shade Control Network
- 718 Light Control Network
- 720 Timing Device (Time Clock)
- 800 Room Automation System (Second)
- 802 Transformer
- 804 Electronic Data Unit (Zigbee Network Node)
- 806 Power Cable
- 808 Hem Bar
- 810 Small Battery
- 812 Trickle Charge Connector
- 814 Shade Control Network (Mesh and Daisy Chain; of Room Automation System 800)
- 902 Relay Network
- 904 Control Electronics (with Relay Network 902)

DETAILED DESCRIPTION OF THE INVENTION

The embodiments are described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the inventive concept are shown. In the drawings, the size and relative sizes of layers and regions

may be exaggerated for clarity. Like numbers refer to like elements throughout. The embodiments may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the inventive concept to those skilled in the art. The scope of the embodiments is therefore defined by the appended claims. The detailed description that follows is written from the point of view of a control systems company, so it is to be understood that generally the concepts discussed herein are applicable to various subsystems and not limited to only a particular controlled device or class of devices, such as motorized roller shades.

Reference throughout the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with an embodiment is included in at least one embodiment of the embodiments. Thus, the appearance of the phrases “in one embodiment” or “in an embodiment” in various places throughout the specification is not necessarily referring to the same embodiment. Further, the particular feature, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

Attention is now directed towards FIG. 4, which illustrates shading control network **400** that comprises motorized shades that include electronic drive units (EDUs) **408** configured in a star and daisy-chain network topology according to an embodiment. Shading control network **400** illustrates shades **106a-d** (though those of skill in the art can appreciate that there can be more motorized shades, or less, and that four is simply a convenient number of shades to use for purposes of illustration only), where each of shades **106a-d** includes corresponding electronic drive unit **408a-d**, respectively.

Shading control system **400** further includes intelligent hub **404** and is configured in a star and daisy-chain mixed network topology. Intelligent hub **404** can be considered to be the “root node” and room controller **402** and first electronic data unit (EDU) **408a** are the star nodes. The rest of the EDUs **408b-d** are thereafter attached in a daisy-chain fashion to first EDU **408a**. According to an embodiment, intelligent hub **404** provides electrical power to each node attached to it, either in the star network topology, or in the daisy chain network topology. The providing of electrical power by the Ethernet connections can be referred to as a PoE network. For example, room controller **402** with integrated display **410** receives its electrical power from intelligent hub **404**. According to an embodiment, when using PoE network protocols, the supplied electrical power can be 48 VDC, 12.95 watts maximum. As those of skill in the art can appreciate, these voltage and power levels are but examples, and not meant to be taken in a limiting manner; other voltages and/or power levels can be used dependent upon the circumstances and applications. Those of ordinary skill in the art can appreciate that networks that supply electrical power to devices, such as a PoE network providing power to motorized roller shades **106** are not typically configured in daisy-chain topology **206** but are instead configured in star topology **204**.

However, it is known to those of skill in the art that PoE provides only a limited amount of power. The limited amount of power available from PoE power supply **412** (about 12.95 watts) is not enough to drive even four motorized roller shades **106a-d** simultaneously, let alone a dozen that could be in a large room. However, according to embodiments, it can be demonstrated that each of motorized

roller shades **106a-d** can operate at a very low duty cycle; that is, instead of continuously operating, shades **106** are typically in motion less than 5% of the time (i.e. less than 3 minutes per hour). According to further embodiments, this means that it is possible to put power storage, such as battery **506** (shown in FIG. 5), at each shade **106** and still keep the power draw requirements below the maximum capability of PoE power supply **412**.

With a daisy-chain network topology including power storage at each node (i.e., batteries **506** at each of motorized roller shades **106a-d**), it is possible to conveniently wire each of motorized roller shades **106** in the daisy chain fashion, since each motorized roller shade **106** does not require “home run” wiring (i.e., wiring that goes from the respective motorized roller shade **106** to intelligent hub **404**) back to a central node as it would with a star network topology. Also, supplying power over the same wiring as the data network eliminates the need to provide a dedicated electrical supply for power alone to each motorized roller shade **106**. Those of skill in the art of residential home wiring can appreciate the disadvantage and additional work that would ensue if house mains AC power (e.g. 115 VAC) would have to be provided at each motorized roller shade **106**.

As described above, shading control network **400** can be used not only in or as part of a home automation system, but can also be part of a much larger, integrated hotel suite. As those of skill in the art can appreciate, such a configuration can include additional devices to control, can be wired to larger networks such as a local area network (LAN), wide area network (WAN), or even the internet. The hotel suite configuration is described in greater detail in regard to FIGS. 6 and 7, below. In such a configuration the room side of intelligent hub **404** can be connected to room controller **402**, as well as Wi-Fi gateway and a Zigbee gateway **62**. It is known to those skilled in the art that the Wi-Fi and Zigbee wireless communication protocols conform to IEEE 802.11 and IEEE 802.14, respectively.

Attention is now directed to FIG. 5, which illustrates EDU **408** of FIG. 4 and certain components thereof according to an embodiment. As discussed above in the description of FIG. 4, one of the aspects of the embodiments is a daisy-chained topology shading network using PoE protocols. According to a further embodiment, the use of PoE is facilitated by providing power storage at each of the network nodes, namely electronic drive units **408a-d**, which correspond to each of the four controlled shades **106a-d**. According to one non-limiting aspect of the embodiments, power storage can be in the form of battery **506**.

Each electronic drive unit **408** includes an elongated motor **502** rotatably driving a bearing **504**. Bearing **504** is notched about its outer periphery to facilitate engagement between bearing **504** and an interior of roller tube **102** (shown in FIG. 1) in which elongated motor **502** is received. Each electronic drive unit **408** further includes battery **506** and control electronics **508** that are attached to motor **502** opposite bearing **504** such that control electronics **508** are positioned adjacent an end of roller tube **102**.

Control electronics **508** of electronic drive unit **408** includes a microprocessor capable of monitoring the operation of elongated motor **502** to track the position of the associated shade fabric **104** as it is raised and lowered with respect to roller tube **102**. Control electronics **508** also controls elongated motor **502** to adjust the position of shade fabric **104** in accordance with instructions from intelligent hub **404**.

Each of electronic drive units **408** further includes input communications/power interface (input interface) **510**, and output communications/power interface (output interface) **512**. According to a further embodiment, each of the input and output interfaces **510**, **512** can be an RJ45 type connector capable of receiving/transmitting not only control/data signals over an Ethernet cable, but can receive/feed-forward external power via PoE network wiring (PoE cables **406**). As those of skill in the art can appreciate, the use of one type of connector or another is substantially immaterial, other than the connector must meet the minimum required electrical requirements for the transmission/reception of Ethernet data, and PoE. According to an embodiment, input and output interfaces **510**, **512** respectively, provide a PoE wiring connection to provide power and communications transmissions for EDU **408**, and according to another aspect of the embodiments, the provided power is used by control electronics **508** to trickle-charge battery **506**.

According to further embodiments, input interface **508b** receives power and data from a preceding EDU **408a**, or intelligent hub **710**, and output interface **508b** feeds the power and data forward to a next motorized roller shade **106c**/EDU **408c** (i.e., power and data are transmitted from intelligent hub **710** to first motorized roller shade **106a**/EDU **408a**/input interface **510a**, which then transmits the same power and data lines via output interface **512a** and PoE cables **406** to second motorized roller shade **106b**/EDU **408b**/input interface **510b**).

According to a further embodiment, relays can be included in control electronics **508**, such as one or more relay or switch (relay) networks **514**. Relay network **514** provides the capability of switching power received by PoE cable **406** from a first EDU **408** to subsequent EDU **408'** as needed by battery **506**. If, for example, it is determined that one or more batteries **506** needs recharging, then during quiet times, when no operation of motorized roller shades **106** is expected or anticipated, power can be provided by PoE cable **406** to the particular battery **506** in need of recharging, and any other EDUs connected thereto via PoE cable **406** can be completely disconnected from PoE cable **406** thereby directing all the available re-charging current that can be carried by PoE cable **406** to the particular battery or batteries **506** that need to be recharged. If instructions are received by any of room controller **704** and intelligent hub **710**, the recharging can be interrupted, relays re-configured to allow power to flow again to the electronics within all of control electronics **508**, and operation of room automation system **700** can proceed. According to further aspects of the embodiments, one or more batteries **506** of room automation system **700** can be recharged at substantially the same time.

According to a further embodiment, relay network **514** can also be used to extract energy stored in a first battery **506** and use it to charge a second battery **506**. As those of skill in the art can appreciate, a battery that has been discharged will lose potential, or battery voltage, and a second battery at a higher potential or voltage can be used to transfer energy stored in it to the first one that is more discharged. Once the battery voltages are about the same, transfer of energy and re-charging will stop. As those of skill in the art can further appreciate, there can be instances wherein a first battery will lose its capacity to recharge fully over time, and will therefore discharge to a lower voltage state faster than other batteries, and will need to be re-charged more often. According to an embodiment, this mode of re-charging batteries **506** through the use of relay network **514** can be referred to as a "vampire mode" of re-charging.

Referring back to FIG. 4, according to an aspect of the embodiments, intelligent hub **404** acts as an interface between EDUs **408** of respective shades **106** and a home automation system that includes certain components, such as room controller **402**. As those of skill in the art can appreciate, home automation systems can be quite complex, including, but not limited to, the control of audio and video distribution, lighting, shades and drapes, heating/ventilation/air conditioning (HVAC), and security subsystems, among other devices. As shown in FIG. 4, intelligent hub **404** resides between room controller **402** (which can be referred to more generally as simply "house controller") and motorized roller shades **106**. Intelligent hub **404**, and the components attached thereto, are substantially configured in a star topology; however each shade **106** is wired back to intelligent hub **404** in a daisy-chain topology and intelligent hub **404** provides power to each of shades **106**, using for example, PoE. Those of skill in the art can appreciate that other devices, such as audio speakers, can also be connected to PoE intelligent hub **404** and "home-runned" back to this hub.

Control electronics **508** for shade **106** also acts as a communications hub, rebroadcasting data received from house controller **402** to other shades **106** that are daisy-chained together using PoE cable **406**. Further, each control electronics **508** of respective shades **106** receives and transmits back to house controller **402** data received from motorized roller shades further down the daisy-chain line. For example, as shown in FIG. 4, control electronics **508d** of EDU **408d** of shade **106d** sends data pertaining to motorized roller shade **106d** to control electronics **508c** of EDU **408c** of shade **106c**, which then sends the data pertaining to shade **106d** to control electronics **508b** of EDU **408b** of shade **106b**, and so on back to house controller **402**, through to intelligent hub **404**. This allows longer lengths of wire (PoE cable **406**) to be used since the data/command signals are essentially received, amplified, and re-transmitted at each EDU **408**.

Communication from downstream shades **106** back to house controller **402** are handled on a first-to-respond basis, i.e. the first link to receive data is assigned as the input, and the data received is broadcast out to all other links including house controller **402**. Once communication has ceased, the link is relinquished, and the link waits for data to come in from any other shade **106** or control network **400** subsystem. Additionally, communication faults on a shade link **406**, such as a short-to-ground, can be detected and isolated, preventing a failed shade device from suppressing communications elsewhere on control network **400**. Failures such as this can occur due to a miswire of data lines, failure of transceiver hardware, or improper operation of communication software within shade **106**.

Control electronics **508** of each shade **106** further provides for basic manual user controls to cause its respective shade **106** to open and close, or to be raised and lowered. This allows control by a user of the system prior to addressing and programming control network **400**, or in the event of a failure of control network **400**. Control electronics **508** of each shade **106** further provides a diagnostic feature to detect wiring faults. The diagnostic test can be initiated by the installer from a test button, or initiated remotely, via the internet, or local network control. Shades **106** downstream can be queried and the voltage levels of their response analyzed and stored. A data table can be built of all shades **106** (or other devices that might be controlled by house controller **402**) that pass or fail the test(s), and store the voltage levels in a manner that is known to those of skill in

the art. The results of the test can be displayed on integrated display **410** of house controller **402**, or through use of light emitting diodes (LED) (or other visual indicators) at control electronics **508**, and still further by wiggling shades **106** up and down to indicate success of the test. Shades that do not move can be considered to have failed the test. The cause of the failure can be indicated in the form of an LED blink pattern, or displayed in different ways on integrated display **410**. The results can also be received and stored by house controller **402** and/or intelligent hub **404**, and can further be transmitted to an external computer **414** (which can also be referred to as a personal computer (PC), and which further includes a server, laptop, tablet, or other portable/non-portable computer device that includes one or more processors, and other equipment/devices known by those of skill in the art) connected by universal serial bus (USB) cable **416** or other means (e.g., wireless 802.11 or other transmission protocols).

According to further embodiments, control electronics **508** provides the ability to report its own status to control network **400**. The status reported can include information such as blown fuses, communication faults, the identification (ID) or serial number of the shade **106** connected to the respective control electronic **508**, power consumption of control electronics **508**, power consumption of motor **502**, and battery **506** statistics (e.g., current voltage, maximum and minimum charged/discharged voltage, number of charge/discharge cycles, among other battery statistical data).

FIG. 6 depicts a lighting control network **600** comprising light dimmers **606** and keypads **608** configured in a mesh network topology and suitable for use within an home automation system according to an embodiment. Not shown, but understood to be included, are lighting loads **324**. Lighting control network **600** can be used in conjunction with control network **400** in a home environment, hotel environment, or other commercial space, as discussed in greater detail below. Lighting control network **600** further includes Zigbee gateway **602** (which is essentially a low-power, low-data rate wireless modem/router) and motion sensors **604**.

As discussed above, mesh networks are wireless networks that allow devices to communicate between the device and a central hub (Zigbee gateway **602**), and between the device and one or more other devices in such a manner as to have substantially complete data transmission redundancy. In this manner, communications capability is very robust, as there are inherently several paths in which the data/commands that are desired to be communicated can do so. Thus, in the configuration shown in FIG. 6, which, as those of skill in the art can appreciate, contains only a few devices to illustrate the principles of operation, communications can exist between Zigbee gateway **602** and keypad **608a** and light dimmer **606a**. Light dimmer **606a** can communicate to either or both keypad **608a** and light dimmer **606b**, Zigbee gateway **602**, and speakers **610**; keypad **608b** can communicate to both keypad **608a** and motion sensor **604**. If any one of the devices exhibits a failure, because of the redundancy built into the lighting control network **600** using mesh network technology, the commands/data can still at least try a second path to arrive at their proper destination. Also shown in FIG. 6 are speakers **610**, which can also communicate with Zigbee gateway **602**.

As those of skill in the art can appreciate, lighting control system **600** with use of mesh network technology can encompass many other devices. In that case, instead of having each device being capable of communicating with

two devices, multiple devices—three, four, or even more—can be communicated with by each device. Of course, providing for wireless communications over multiple redundant paths can increase costs, but it does make the system more robust, and also allows for higher data throughput.

FIG. 7 depicts combined shading and lighting room automation control system (room automation system) **700** that includes a shading control network configured in a daisy-chain network topology, a lighting control network configured in a mesh network, and an intelligent hub configured in a star network, for use as a system suitable for control of a hotel suite, or one or more rooms in a private suite according to an embodiment. Room automation system **700** incorporates control network **400**, which includes PoE interconnections between intelligent hub **404** and EDUs **408** of each or shades **106**. In addition, intelligent hub **710** is connected via PoE cables **406** to Wi-Fi gateway **702**, which allows for communications to PC **414** wirelessly (which can be, as those of skill in the art can appreciate, personal computers/laptops or a central server), or to PC **414** via a wired connection (USB cable **416**, or via WAN **712**). In this manner, a user can use their PC **414**, with specialized software or other applications (Apps) to control the shading and lighting within the room, wherever the room is located (hotel, home, or other commercial space). Intelligent hub **710** is substantially similar to that of intelligent hub **404**, the main difference being, according to embodiments, that intelligent hub **710** contains additional software/programming capabilities not present in intelligent hub **404** that make it capable of communicating with room controller **704**, Wi-Fi gateway **702**, WAN **712**, and Zigbee gateway **602**, and controlling room automation system **700**.

Intelligent hub **710** is further connected via PoE cables **406** to room controller **704**, and WAN **710**. Room controller **704** is connected, via infrared communications, to set-top box **304** and television **306**, and is further connected to all of the other devices within the room as shown in FIG. 7 through either a wired connection, i.e., PoE cable **406** (including, for example, EDU **408**), or through a wireless connection, via Zigbee gateway **602**. As those of skill in the art can appreciate, other wireless means exist for communicating in a fashion similar to Zigbee, but few provide the combination of affordability and performance. Room controller **704** provides the main interface according to an embodiment between external control systems, such as front desk control system in a hotel environment, and the individual systems/devices within the room as shown in FIG. 7. Room controller **704** can further include a timing function, i.e., timing device **720**, for use in setting and executing stored settings and pre-programmed functions and operations. In addition, as discussed in greater detail below, keypad **608** can assume at least some of the functions of room controller **704**, and so in some circumstances can be interchangeable. However, for purposes of this discussion, reference will only be made to room controller **704** as being capable of controlling all of the devices within the room shown in FIG. 7, and further the only device capable of bi-directional communications with external control systems per Wi-Fi gateway **702** and WAN **712**.

WAN **712** allows for interconnection to other servers and computers (not shown) that, especially in use in a commercial and/or hotel environment, allows for remote monitoring and/or control of the operations of room automation system **700**. For purposes of example only, if room automation system **700** was located in a large meeting hall, for example a large convention center, then it could be advantageous to remotely monitor and/or control operations therein as such

rooms are very expensive to rent or lease, and the control of the lights, shades and other similar apparatus can be very important not only to the occupants but the owners in terms of security, energy costs, and other concerns.

In terms of a home environment, WAN **712** and Wi-Fi gateway **702** allows for interconnection with the internet that allows for remote monitoring and/or control by a user or owner. Such remote operational capabilities provides for enhanced security, and conservation of resources. A user or owner can even control lighting and shades **106** by an App on their cell phone (e.g., 3G/4G (long term evolution (LTE) “smart phone”) or other remote, personal communications devices; such operation can make it look like one or more people are in the house, when in reality the owners/occupants could be hundreds or thousands of miles away. To effectuate such command and control, intelligent hub **710** can be connected to Zigbee gateway **602**.

As those of skill in the art can appreciate, Zigbee gateway **602** is but just one of a plurality of devices that can be used for low power, low data rate communications between intelligent hub **710** and shading/lighting and other types of devices **604**, **606**, **608**, **610**, **706**, and **708**. Each of these will be discussed in turn.

Through use of room controller **704**, a user can be notified of detection of a person via motion sensor **604**, or, room automation system can be programmed to turn on certain one or more lights if detection of a person and/or movement occurs. This, of course, can provide additional security. If it is thought that no one should be in the room, then additional security measures can be taken, again via programming of room automation system **700**, to alert an alarm company as well as the owner or user.

Through use of room controller **704**, an owner/operator can control lights via light dimmer **606**. Light dimmer **606**, as discussed in regard to FIG. 6, can communicate wirelessly with Zigbee gateway **602**, and receive/send commands/data there-between. This allows the owner/operator to control the lighting instantaneously, or via a programmed setting (i.e., turn the lights on full at 5:15 PM, then dim them at 10:30 PM, then turn them off at 02:00 AM, and so on).

Room controller **704** and intelligent hub **710** can also communicate via PoE cable **406** and wirelessly via Zigbee gateway **602** to wireless keypad (keypad) **608**. Keypads **608** can be used for many different applications, and can be both inside and outside a room. Keypad **608** can be used to receive a code that allows entrance into a room through use of door lock **708**; or keypad **608** can receive a temperature setting from an owner/occupant and have that information transferred to room controller **704** (which can then transfer that information to a combined heating/air conditioning unit (not shown)); keypad **608** can also receive notifications from the owner/occupant as to what lights to illuminate, and at what brightness setting, and also open or close shades **106**. As those of skill in the art can appreciate, there are numerous other uses of keypad **608** that are made easier and more productive via use of wireless communications with Zigbee gateway **602**, intelligent hub **710**, and room controller **704**.

Smoke detectors (hereinafter generally referred to as “detectors”); the detectors can be smoke, fire, carbon monoxide, pathogen(s), nuclear, and other bio-hazard type detectors) **706**, while not generally requiring or providing much user interface or controllability, can communicate to room controller **704** via wireless communications through Zigbee gateway **602**, and can further communicate to a central control/monitoring system (not shown) that would be interested in the event of any one or more of the different types of detections. In addition, the same systems can communi-

cate with detectors **706** to ascertain their state of readiness, and to provide false alarms to test the responsiveness of personal in different buildings and/or rooms.

Wireless door lock (door lock) **708** can receive wireless commands from intelligent hub **710** that have been transferred to it via either/both WAN **712** and Wi-Fi **702**; these commands can originate from a central control system, such as front desk in a hotel environment, and which provide control information such as a resettable lock combination (i.e., a resettable code), or to accept a certain programmed key card that are now ubiquitously used in hotels. Door lock can receive the encoded information from a programmable key card via keypad **608**, or can receive a universal override code that might allow the management of the hotel facility to open any door. Further, door lock **708** can report failed attempt (and successful ones) to enter the room.

Embodiments regarding how the above-described constructions can used to program room automation system **700** will now be discussed in greater detail. In general, the programming of motorized roller shades **106**, as well as other components of room automation system **700** will include addressing each component of room automation system **700**. The programming of room automation system **700** can also include setting open and close limits for each of electronic drive units (EDUs) **408** and assigning one or more EDUs **408** to respective room controllers **704** (it can be the case that in larger environments there could be multiple room controllers **704**).

For proper operation of the above-described room automation system **700**, each component included in room automation system **700** must be given a unique address identifier to distinguish the components of room automation system **700** from each other. As described above, room automation system **700** utilizes a communication network in which all of the system components are connected to either a common communications bus, PoE cable **406**, or wirelessly via Zigbee gateway **602**. The use of PoE cable **406** provides for “soft addressing” of the system components in which a unique address can be automatically assigned to each component when a user enters a “system configuration mode.” As will be described below, the system configuration mode is used to address components and to assign EDUs **408** to room controllers **704**. The system configuration mode can also be activated from any one of keypads **608**, or from an alternate device or control system linked to room automation system **700** through Wi-Fi gateway **702** and/or WAN **712**. However, as discussed above, in fulfillment of the dual purposes of clarity and brevity, reference shall only be made to system configuration with use of room controller **704**.

Aspects of the embodiments provide for automatic addressing of system components, which results in each of the components having a unique address identifier associated with it. As those of the skill in the art can appreciate, however, the identifiers need not be assigned by room automation system **700** according to any particular series or pattern and could, for example, be accomplished by random numbering. It is only required that the address identifiers be unique such that room automation system **700** can distinguish one component of room automation system **700** from another.

Room automation system **700** according to embodiments provides for addressing of system components from room controllers **704** as follows. Room controller **704** is placed in “system configuration mode” by pressing and holding one or more pre-defined buttons, or via some other means. Following engagement of the system configuration mode button(s), an indicator will show that room controller **704** is ready to

begin addressing room automation system **700**. Another button or key (one of skill in the art appreciate that these are but non-limiting examples, and that many different means are available, e.g., “soft keys” on a touch screen display, all of which should be considered within the aspects of the embodiments, for starting and starting different processes within room controller **704** and room automation system **700**; in fulfillment of the dual purposes of clarity and brevity, reference shall be made from hereon in only to “buttons”) is pressed to initiate automatic addressing by room controller **704** that then assigns a unique identifying address to each component of room automation system **700**.

While the system components are being addressed by room controller **704**, an indicator will show that each of the devices found are being addressed. When each device has been addressed, another indicator can show that the actions have been completed. This indicates that addressing is complete and that the “system configuration mode” can be exited, such as by pressing another button, or the same as was pressed to enter system configuration mode. According to further embodiments, room automation system **700** can also be configured to provide for exiting of the system configuration mode automatically once configuration has been completed.

In addition to providing a visual indication of various programming stages, indicators are available that show that room controller **704** also provides a confirmation of correct wiring of the room. Automatic addressing of the components of the shades can also be initiated via room controller **704** as follows. Pressing and holding a close limit button of room controller **704** for several seconds, for example, will place room controller **704** in a “ready to address” mode. Addressing of the shade system components by room controller **704** is then initiated by pressing another button, in this case, an adjustment button.

Control of the shades by room controller **704** according to embodiments is also programmable to set an “open limit” position and a “close limit” position for each of EDUs **408**. These limits determine how far the associated shade fabric **104** will travel when its respective EDU **408** is directed to drive shade fabric **104** to the full open or full close positions. The shade limit positions can be set for EDU **408** using room controller **704** as follows. Pressing an open limit button of room controller **704** actuates a “set open limit” for that EDU **408** and an adjustment button room controller **704** can then be used to move the associated shade fabric **104** to the desired full open position. With shade fabric **104** in the desired position, the user presses and holds an open limit button. An indicator will then show that the current position for the EDU **408** has been stored by room controller **704** as the open limit for that particular EDU and shade fabric **104**. In a similar fashion, a close limit button of room controller **704** provides for setting the desired close limit position using adjustment buttons in a “set close limit mode” for the respective EDU **408**. According to further embodiments, the open and close limits of different motorized roller shades **106** can also be set using the room’s respective keypad **608** in a manner similar to that of room controller **704**.

As described above, room automation system **700** according to embodiments utilizes a communication network in which each component of room automation system **700** is connected to one or more communications buses, as shown in FIG. 7. The physical communications’ connections facilitates configuration, or reconfiguration, of room automation system **700** during various programming stages including system addressing, setting of EDU **408** limit positions and assignment of EDUs **408** to keypads **608**. Construction of

the communication network according to the embodiments described herein provides for troubleshooting and reporting of operational errors that may occur. As described above, signals directing control electronics **508** of electronic drive units **408** to move the associated shade fabrics **104** will be transmitted to EDUs **408** from room controller **704** at various times during operation and configuration of room automation system **700**. In the event that an EDU **408** fails to move the associated motorized roller shade **106** in response to such a command, room controller **704** can be arranged to diagnose and report various failures or conditions that may be responsible. For example, room controller **704** could be arranged to check such a failing EDU **408** for hardware conditions including stalling of motor **502**, overheating of motor **502**, duty cycle and software problems including corrupted position data.

According to further embodiments, room controller **704** can be interrogated following failure of EDU **408** to respond for any systemic conditions, such as excess number of devices or duplication of component addresses for example. Following diagnosis of an EDU **408** failure to respond, room automation system **700** provided for error reporting to room controller **704** from which the command signal originated. Error reporting at the originating device can be achieved by various types of display(s), using various combination of on/off or flash rate lighting conditions of LEDs of the originating device. According to further embodiments, keypad **608** and/or room controller **704** can be modified to include a display (e.g., a liquid crystal display (LCD), LED display, among others) to report numbered codes at an originating device.

Room controller **704** according to embodiments has been described herein for configuring and operating multiple motorized roller shades **106** having internal motors **502** driving roller tube **102**. Different aspects of the embodiments, however, are not so limited and can be used in other applications. For example, room controller **704** can be used to control shade rollers having external motors driving roller tubes. According to further embodiments, room controller **704** can also be applied to configure and operate other motor driven window treatments including roman shades and draperies, for example.

Room automation system **700** according to embodiments facilitates configuration of the different system components, in the manner described above for example for addressing, limit setting, and assignment. The communication network room automation system **700** also facilitates modification of an established network as described below, to facilitate replacement of a device or combination of multiple networks without requiring loss of programming for the established network.

As described above, room automation system **700** includes multiple motorized roller shades **106** each including EDU **408** connected to a rotatably supported roller tube **102** that windingly receives a flexible shade fabric **104**. Room automation system **700** can also include other devices such as keypads **608** and room controllers **704** that can control EDUs **408** of motorized roller shades **106**. Room controllers **704** control assigned motorized roller shades **106** by directing EDUs **408** to raise or lower the associated shade fabric **104** to a desired shade position or, alternatively, to move shade fabric **104** to a preset shade position stored in a memory. During initialization of room automation system **700** each room controller **704** is associated with one or more EDUs **408**. This process is known as EDU assignment.

EDUs **408** of motorized roller shades **106**, and room controller **704**, of room automation system **700** are inter-

connected by PoE cables **406** and/or Zigbee wireless communications. PoE cables **406** provide for transmission of signals and power between intelligent hub **710** (which receives commands/data from room controller **704**) and EDUs **408** for control of motorized roller shades **106** and for communication of network-related information.

The components and devices of the room automation system **700** are preferably interconnected such that each component or device can communicate with every other component or device on the network. A suitable shade network for use in the integrated control system according to embodiments is shown and described in regard to FIGS. 4-7. Each of EDUs **408** and room controller **704** can have memory storage capability to provide for storage at the respective device(s) of a database of information including network related information such as device addresses and EDU assignments, for example. As those of skill in the art can appreciate, it is not a requirement according to the embodiments to have such memory storage, but each device of room automation system **700** can be adapted for memory storage. According to further embodiments, room automation system **700** can further include one or more centralized devices capable of memory storage for storage of network related information at those locations instead of at EDUs **408** or room controller **704** of room automation system **700**. In addition to motorized roller shades **106** and room controller **704**, room automation system **700** can also further include other devices connected to room controller **704**.

The term “fully-opened” as used herein should be understood as referring to a position for a motorized shading treatment that provides a minimum of light blockage for shading area, such as defined by a window for example, for which the shading treatment provides shading. The term “fully-closed” as used herein should be understood as referring to position for the motorized shading treatment that provides for maximum light blockage for the shading area by the shading treatment. In a similar manner, relative terms such as “half-opened” or “partially opened” should be understood in relation to the “fully-opened” or “fully-closed” positions for the shading treatment.

The lighting system of room automation system **700** includes dimmable loads, such as lamps, or lighting **714**. In a manner similar to the motorized roller shades **106**, the dimmable loads of lighting system **714** are interconnected in a network arrangement that provides for receipt of required power by the dimmable loads for lighting system **714**. Lighting system **714** can also include light dimmers **606**, each adapted for controlling one or more dimmable loads of lighting system **714**. The use of room controller **704** and light dimmers **606** in room automation system **700** facilitates optional programming and operation of the motorized roller shades **106** and lights. According to further embodiments, integrated control of both motorized roller shades **106** and lights **714** controlled by light dimmer **606** from a centralized location is provided for by room automation system **700** as further discussed below.

Room automation system **700** includes room controller **704**. As shown in FIG. 7, room controller **704** is connected to motorized roller shades **106** and other devices via PoE cable **406** via intelligent hub **710** and Zigbee gateway **602**, and is adapted for integrated control of all of the devices shown in FIG. 7. Room automation system **700** also includes keypads **608** connected to room automation system **700** for controlling either motorized roller shades **106** or the dimmable loads of lighting system **714** via light dimmers **606** from a single convenient location, such as a wall-mounted location for example.

Room controller **704** functions to transmit control signals, input at one of keypads **608**, for example, to lighting system **714** and to direct lighting system **714** to modify the current delivered by dimmers **606**. The current for the dimmable loads is set by room controller **704** and/or light dimmer **606** to a particular intensity level ranging between about 0 to about 100 percent in response to the command signal from room controller **704**. The intensity levels for the dimmable loads of lighting system **714** can be raised and lowered by a user to a desired level or, alternatively, can be set to a preset intensity level programmed into room automation system **700** for the dimmable load.

Although not shown in detail, room controller **704** can include raise and lower actuators for respectively increasing or decreasing the intensity level for a dimmable load of lighting system **714** or for raising or lowering shade fabric **104** of motorized roller shade **106** in room automation system **700**. Room controller **704** further can include a plurality of preset actuators for directing motorized roller shades **106** or the dimmable loads respectively, assigned to the actuator to a preset intensity level (or equivalent shade position) that has been programmed into room controller **704**. Room controller **704** can also include visual indicators such as LEDs. The LEDs provide a visual feedback, for indicating to a user whether a dimmable load of the lighting system is on or off, for example, or whether motorized roller shade **106** is in a first or second preset position as described below in greater detail.

As described above, room controller **704** works within room automation system **700**, and is configured to direct EDUs **408** of motorized roller shades **106** to raise or lower associated shade fabrics **104** to a desired shade position or to move motorized roller shades **106** to a preset shade position that has been programmed into memory storage. Room controller **704**, as described in the preceding paragraphs, is adapted to direct signals representing intensity level, appropriate in use of lighting system **714** for controlling a dimmable load. To provide for control of motorized roller shades **106**, commands representing intensity level can be converted into a shade position value more appropriate to a shade control system. Room controller **704** is further configured according to embodiments to convert the intensity level values transmitted from room controller **704**, in response to user inputs, into shade position values such that an intensity level of about zero (0) percent is equivalent to a shade in a fully-closed position and an intensity level of about 100 percent is equivalent to a shade in a fully-opened position. In this manner, existing lighting control systems **714** can be modified into the an integrated control system as embodied by room automation system **700**/room controller **704** capable of controlling motorized roller shades **106** and lights with only limited changes to the existing lighting system **714** being required.

As can be appreciated by those of skill in the art, keypads **608**, light dimmers **606**, lighting system **714**, motion sensors **604**, detectors **706**, and room controller **704**, can all be wall-mountable for installation in a convenient location that facilitates access to the different components of room automation system **700** by a user. According to further embodiments, however, those of skill in the art can appreciate that room automation system **700** can also include hand held infrared transmitters (not shown) generating infrared signals for receipt by an infrared receiver connected to different components of room automation system **700** including, but not limited to, set top box **304**, television **306**, keypads **608**, light dimmers **606**, lighting system **714**, and room controller **704**.

Those of skill in the art can appreciate that room controller **704** can be connected to PC **414** via Wi-Fi gateway **702** and/or WAN **712**, as shown in FIG. 7. Connection of PC **414** to room controller **704** can also be accomplished via an interface through intelligent hub as shown in FIG. 7 through USB cable **416**, or directly to room controller **704** by second USB cable **416**. Connecting PC **414** to intelligent hub **710** provides for programming and control efficiencies through the use of graphical user interface (GUI) software running on PC **414**. Such GUI software provides for screen displays and user selection prompts to facilitate system programming and other functions such as system diagnosis features for troubleshooting problems and installing new systems. Although PC **414**, and the GUI software loaded thereon, may also facilitate normal operation of room controller **704** following installation or maintenance of room automation system **700**, it is not required. According to additional embodiments, PC **414** can be connected to room controller **704** directly solely for the purpose of programming room controller **704** with the necessary information to provide for subsequent operation of room automation system **700** via room controller **704**. Following completion of the required programming of room controller **704**, therefore, PC **414** can be disconnected from room controller **704** for normal operation of room automation system **700** without PC **414**.

In room automation system **700**, room controller **704** can further include memory storage of system related information and for directing command signals relating to intensity levels to lighting **714** and motorized roller shades **106**. As described above, PC **414** can be used to operate room automation system **700**. PC **414** can be permanently included in room automation system **700** for use of the processor and memory storage capabilities of PC **414** instead of including room controller **704**, according to further embodiments. The use of a separate room controller **704**, as shown in several figures, however, provides for a more robust and durable construction for room automation system **700**.

According to further embodiments, room automation system **700** can further include time clock **720** that is associated with room controller **704**. Association of time clock **720** with room controller **704** provides for storage of time-based information in memory of room controller **704** regarding the position or condition of motorized roller shades **106** and the dimmable loads of lighting system **714**. For motorized roller shades **106**, for example, room controller **704** can store information regarding shade position of a given motorized roller shade **106** at a given time of day. Such time-based information regarding the motorized rollers shades **106** can then be used to create a macro program for directing all of, or only part of the set of motorized roller shades **106** to automatically move the given motorized roller shade **106** to certain shade positions at different times of day based on the historical time-based information stored in memory by room controller **704**. Once the macro program has been created, a user in a residential setting for example could activate the program, when leaving on a vacation, to provide for automatic control of motorized roller shades **106** to mimic occupied use of the residence in accordance with the historical time-based information regarding motorized rollers shades **106** stored in memory by room controller **704**.

As briefly discussed above, room controller **704** of room automation system **700** can also be connected to a security system for the home or facility in which the room automation system is installed. Room controller **704** can also be programmed to set all of the dimmable loads of lighting system **714** to full intensity or to flash them rapidly, in response to an alert

signal transmitted to room controller **704** by the security system. Room automation system **700** can also be programmed to move all of the motorized roller shades **106** to a fully-opened position, thereby maximizing the effect produced in an alert mode by the dimmable loads of the lighting system **714**. Room automation system **700** can alternatively be programmed to move all or part of motorized roller shades **106** to their fully-opened positions and then to cycle between the fully-opened position and a partially closed position to provide an additional alert signal.

As shown in FIG. 7, room automation system **700** further includes intelligent hub **710** connected between room controller **704** and all of the other devices within the room or area controller by room automation system **700**. Intelligent hub **710** further includes a buffer to store feedback information from motorized roller shades **106** regarding the position or condition of the motorized roller shades **106**. The storage of the feedback information from motorized roller shades **106** by the buffer facilitates independent operation of motorized roller shades **106** from lighting system **714** for continued operation of either in the event of a failure of room controller **704**, for example.

The inclusion of intelligent hub **710** having a buffer also facilitates conversion of an existing lighting control system into room automation system **700** capable of controlling lights and shades. In such a lighting control network system, such as that provided by Crestron's Cresnet®, a streaming protocol communication system can be utilized. In a communication system based on streaming protocol, packets of information are periodically transmitted between interconnected components. This form of communication is contrasted to an event-based protocol system of communication in which information is transmitted in response to an event, such as an input command via a keypad controller or feedback information following action by a component in response to a command (e.g., a motorized shade confirms movement in response to a command or indicates a failure condition).

A streaming protocol system provides for more flexibility in configuration of a control system, such as room automation system **700**. This is particularly desirable in control systems where relatively inexpensive devices are controlled, such as in lighting control systems for example, because network information can be transmitted from a centralized location without the need for memory storage at each device. The buffer capabilities of intelligent hub **710** provides for modification of an existing lighting control system that uses a streaming protocol communication, to add a shade control system adapted to communicate based on an event-based protocol, with limited changes to the lighting control system being required.

According to further embodiments, there may be occasions where it is desirable to link a first established room automation system **700a** with a second room automation system **700b** separately established from first room automation system **700a**. Such a situation could occur, for example, during construction or remodeling of a facility. The separately established room automation systems **700a,b** can include separately addressed devices. Such a situation creates the possibility that a merger of the previously separate room automation systems **700a,b** could result in multiple sets of devices sharing a common device address. To resolve the address conflict in conventional control systems, reprogramming of the conflicting devices, or of the entire system, is required. Reprogramming can be a time-consuming task, particularly where reprogramming of an entire system is required.

FIG. 8 illustrates a partial view of combined shading and lighting room automation control system (room automation system) **800** similar to that of the system of FIG. 7 that includes shade control network **814** configured in a combined mesh and daisy-chain network topology, light control network **718** configured in a mesh network, and intelligent hub **710** configured in a star network according to a further embodiment. FIG. 9 illustrates a block diagram of an electronic drive unit of FIG. 8 and certain components thereof according to an embodiment. While similar, there are substantive differences between room automation system **700** and room automation system **800** according to embodiments. One such different is wall transformer **802**, which provides motor and battery re-charging power to motor **502** and battery **506**, respectively, of EDU **804** (which, as its number implies, is different from EDU **408**).

In the embodiment illustrated in FIG. 8 (in which many of the components that do not have substantive differences with like components of FIG. 7 have been omitted in fulfillment of the dual purposes of clarity and brevity), EDU **804**, shown in greater detail in FIG. 9, includes relay switch network **902**, and control electronics **904** (which, as its number implies, is different from control electronics **508**). Control electronics **904** includes relay switch **902** that provides for additional functionality in regard to power distribution than is present in control electronics **508** as shown in FIGS. 5 and 7.

As shown in FIG. 8, transformer **802**, through power cable **806**, provides the sole means of power to all of motorized roller shades **106** according to an embodiment. Relay switch network **902** provides the means for directing the flow of power to motorized roller shades **106** according to a further embodiment. That is, the power from transformer **802** can be directed through relay switch network **902** to re-charge battery **506** of motorized roller shade **106** directly via power cable **806**, which eliminates the need to run PoE cable **406** from intelligent hub **710** to the first EDU. Further, relay switch **902** can shunt power away from one or more of control electronics **904** should it be necessary to re-charge one or more batteries **506**; this prevents any current from being used by any one or more of control electronics **904** when one or more batteries **506** needs to be recharged, as discussed above. In addition, relay switch **902** allows one or more batteries **506** to re-charge each other as discussed above in the “vampire-mode” of recharging. The configuration of FIG. 8 and room automation system **800** is different than that of room automation system **700** as shown in FIG. 7 in that power to motorized roller shades **106** in room automation system **700** is provided by PoE cables **406** directly from intelligent hub **710**, as discussed above.

According to still a further embodiment, room automation system **800** includes additional features over that of room automation system **700**: hem bars **808** contain small batteries **810**, and trickle charge connectors **812** for trickle-charge re-charging of batteries **506** according to an embodiment. Small batteries **810** can be located in hem bars **808**. As those of skill in the art can appreciate, hem bars **808** are used in shades and draperies to provide a place to store a weight that keeps shades **104** substantially still in the presence of light drafts, such as what might be caused by air conditioning air currents, or heating air currents, or when the shades and/or drapes are moved. Specially fabricated hem bars **808** can be made to contain small batteries **810** and relay network **902** can be programmed and/or manipulated such that a small trickle-charge re-charging current can be provided via trickle charge connection **812** to one or more of batteries **506**. According to further embodiments, small batteries **810**

can themselves be standard alkaline cells, or rechargeable cells, such as AA rechargeable cells, or they can be specially designed and fabricated battery packs made up of rechargeable cells such as those used in the camcorder, laptop, and cell phone industries. According to further embodiments, hem bar **808** and its components and functionality can also be implemented in room automation system **700**.

According to a further embodiment, EDU **804** differs from previously presented EDU **408** in that it incorporates a Zigbee mesh network node, so that a first PoE cable **406** does not need to be connected to it from intelligent hub **710**, yet intelligent hub **710** and room controller **704** (as well as other devices connected to WAN **712** and/or Wi-Fi gateway **702**) can and do control it via Zigbee gateway **602**.

As those of skill in the art can further appreciate, and as discussed above, room automation system **800** includes any and all of the components as shown and described in reference to room automation system **700** in FIG. 7. Further, any and all of the operations and functionality described above, including but not limited to automatic addressing, remote monitoring and control, user of Zigbee gateway **602**, programming, confirmation of correct wiring, configuration and reconfiguration of devices, interrogation and error reporting, memory storage of different devices, use of system configuration mode, use of time clock, connection to security system, use of streaming protocols and Cresnet®, and linking to similar room automation systems **800** (i.e., **800a** linked to **800b** linked to **800c**, and so on), exist in and can be used in a similar manner in room automation system **800** as in regard to room automation system **700** according to further aspects of the embodiments.

As those of skill in the art can appreciate, a plurality of methods can be used for control of motorized roller shades **106**, lighting **714**, and the other devices by room automation systems **700** and **800** (according to further aspects of the embodiments, as discussed above, all of the functionality of the devices shown in room automation system **700** can be used in a substantially similar manner as in room automation system **800**; therefore, in order to improve readability, and in fulfillment of the dual purposes of clarity and brevity, further discussion in regard to the methods of FIGS. 10-14 apply equally to room automation system **800** as in regard to room automation system **700**, and therefore it will not be necessary to call out room automation system **800** in the following discussions). In controlling motorized roller shades **106** and lighting **714**, it can be convenient to organize and/or define some of the components of FIGS. 6 and 7 as separate networks. Therefore, according to an embodiment, a shade control network **716** can be defined as comprising Wi-Fi gateway **702**, WAN **712**, room controller **704**, PoE cables **406**, and motorized roller shades **106** (and all of its constituent components, as shown in FIG. 5). Furthermore, according to another aspect of the embodiments, a light control network **718** can be defined as comprising Wi-Fi gateway **702**, WAN **712**, room controller **704**, Zigbee gateway **602**, light dimmers **606**, and lighting **714**. In addition, according to another aspect of the embodiments, keypads **608**, and motion sensors **604** can be considered to be part of both shade control network **716** and light control network **718**. In regard to room automation system **800**, shade control network **814** is substantially similar to shade control network **716**, but does not include PoE cable **406** between intelligent hub **710** and first motorized shade **106a**, and does include transformer **802**. According to a further aspect of the embodiments, light control network **718** is substantially similar for both room automation systems **700** and **800**.

As described above, room controller **704** can be programmable according to an embodiment for memory storage of preset intensity levels for motorized roller shades **106**. According to one method of control, room controller **704** can be programmed to store in memory therein the preset intensity levels for the dimmable loads of lighting system **714** and for motorized roller shades **106**. One such method of control is discussed in regard to the method flowchart of FIG. **10**.

FIG. **10** is a flowchart of method **1000** for control of motorized roller shades **106** by transmitting intensity levels from room controller **704** to motorized roller shade **106**. In response to actuation of a shade preset actuator on room controller **704** (at step **1002**), room controller **704** transmits the preset intensity level to motorized roller shade **106** (at step **1004**). The intensity level is received by the associated motorized roller shade **106** and converted to a shade position (at step **1006**). Motorized roller shade **106** then directs its EDU **408** to move shade fabric **104** to the shade position equivalent to the intensity level transmitted by room controller **704** (at step **1008**).

According to a further embodiment, the preset information could first be transmitted to each of the motorized roller shades **106**, as part of programming of room automation system **700**. As described above, each of motorized roller shades **106** includes control electronics **508** as part of its respective EDU **408**. Control electronics **508**, in addition to controlling recharging of batter **506** and receipt of commands from intelligent hub **710**, and transmission of data thereto as well, further can incorporate memory for storing settings, and other information, as needed.

FIG. **11** is a flowchart of method **1100** for storage of preset intensity levels at motorized roller shades **106**. Using room controller **704** having GUI software, a user can be prompted to enter desired preset intensity levels for each of the motorized roller shades **106** of at step **1102**. A database of preset intensities is then compiled by room controller **704** using the GUI software in room controller **705** (at step **1104**) and transmitted by room controller **704** to intelligent hub **710** (at step **1106**) for storage in memory at each of motorized roller shades **106** (at step **1108**). According to a further embodiment, instead of entering the preset intensity levels in room controller **704**, PC **414** can be used to enter and transmit the levels to room controller **704**.

FIG. **12** is a flowchart of method **1200** for control of motorized roller shade **106** by transmitting a "set to preset" command from room controller **704** to each of motorized roller shades **106**. According to this aspect of the embodiments, subsequent actuation of a preset actuator on room controller **704** (at step **1202**) causes room controller **704** to transmit a "set to preset" command (at step **1204**). This differs from method **1000** shown in FIG. **10**, in which a signal representing the actual intensity level is transmitted to motorized roller shade **106** by room controller **704** based on database information stored in memory at room controller **704**. According to method **1200**, the "set to preset" command is transferred to motorized roller shade **106** (at step **1206**) that accesses the database of information stored at motorized roller shade **106** to determine the intensity level associated with the "set to preset" command (at step **1208**). Motorized roller shade **106** then converts the intensity level to an equivalent shade position and directs its EDU **408** to move shade fabric **104** to the equivalent shade position (at step **1210**). Transmitting a "set to preset" command provides for reduction in the total communication time because the same "set to preset" command can be sent to each of motorized roller shades **106** rather than sending multiple

signals to each motorized roller shade **106** including the intensity level associated with the preset.

While memory storage at each of motorized roller shades **106** can be beneficial, it is not required. It is within the scope of the aspects of the embodiments, for example, that the database of information that is compiled by the GUI software and delivered to motorized roller shades **106** by room controller **704** (at step **1106** of FIG. **11**) could, instead, be stored in one or more storage devices centrally located with respect to room automation system **700**.

The shade preset actuators of room controller **704** can be used to control motorized roller shades **106** using a toggling functionality as follows. It is known for lighting control systems, for example, to use toggling functionality to switch a dimmable lighting load between first and second intensity levels by actuation of a preset button. A processor associates the first and second intensity levels for the dimmable lighting loads with first and second states toggled by the preset button. Actuation of the preset button toggles the states between the first and second states. The processor sets the dimmable lighting load to one of the first and second intensity levels depending on the state of the preset button.

In lighting systems the first preset intensity level is typically set by default to zero and the second preset intensity level to a desired non-zero intensity. The states associated with the first and second preset intensity levels are, therefore, referred to as the "off" and "on" states. FIG. **13** is a flowchart of method **1300** for toggling the position of motorized roller shade **106** between two preset positions in response to an actuation of a shade preset actuator (at step **1302**). In room control system **700**, room controller **704** can be programmed to toggle motorized roller shade **106** between first and second preset shade positions (at steps **1306** and **1308**, respectively) depending on first and second states (determined at decision step **1304**) by toggling one of the shade preset actuators of room controller **704**. For the first, or "off" state, room controller **704** can be programmed to set the associated shade position to a fully-opened shade position by default, or alternatively to a fully-closed shade position. Room controller **704** can then toggle motorized roller shade **106** between the first shade position (i.e., the default "off" shade position) and a second preset position stored in memory for motorized roller shade **106** in response to actuation of the shade preset actuator. The ability to toggle between two preset positions can be desirable for a variety of reasons including, for example, privacy concerns, lighting factors, or facilitating view from a window.

EDUs **408** for motorized roller shades **106** can typically be adapted to drive associated roller tubes **102** at one set rate of speed. Room automation system **700**, however, can be adapted to direct motorized roller shade **106** to move shade fabric **104** in a stepped manner that simulates a relatively slowly, but continuously, moving shade **106**. This can be accomplished by room controller **704** transmitting, in periodic fashion, a sequence of intensity levels that increase or decrease in substantially equal steps with each intensity level that is transmitted. That is, a second intensity level is greater (or smaller) by a predetermined amount in intensity than the first, and the third is greater (or smaller) than the second by the same predetermined amount, and so on. If the duration of each step, as well as the duration of intervening period between steps, is sufficiently short, the resulting movement of the shade will appear to be continuous but slower than that provided by a shade being normally driven by an EDU **408** between two shade positions. Including PC

414 running GUI software greatly simplifies programming of room controller 704 to direct stepped movement of motorized roller shades 106.

Instead of simulating a reduced motor speed using stepped movement at normal speed, the motor speed for motorized roller shade 106 can be reduced by variation in the voltage applied to motor 502 of motorized roller shade 106. In response to a motor speed command from room controller 704, a microprocessor in EDU 408 for motorized roller shade 106 could apply appropriate voltage associated with the motor speed command by varying the duty cycle of a pulse width modulated drive signal applied to motor 502. Control of motor speed for a motorized window roller shade in this manner is described in greater detail in U.S. Pat. Nos. 6,100,659 and 6,497,267. Motor speed for motorized roller shades 106 can also be controlled based on other characteristics such as frequency of a driving signal, for example.

Room automation system 700, according to an embodiment, can be programmed to address motorized roller shades 106 such that a unique identifier is associated by room automation system 700 with each motorized roller shade 106. PC 414, as described above, has a GUI interface can be used to facilitate addressing of motorized roller shades 106 to room automation system 700 in accordance with method 1400. FIG. 14 is a flowchart of method 1400 for visually identifying a particular motorized roller shade 106 by the “wobble” method. According to method 1400, a user can enter a shade system addressing mode (at step 1402) in the GUI software by actuation of a keystroke at PC 414 or through a GUI selection prompted by room controller 704. Room controller 704 then directs one of motorized roller shades 106 to raise and lower its shade fabric 104 over a short distance (i.e., to “wobble” shade fabric 104 at step 1404). The wobbling of shade fabric 104 provides a visual means of identifying a particular motorized roller shade 106 within room automation system 700.

In method step 1406, method 1400 generates and displays a user prompting screen, with a specific message. The message is shown in FIG. 14 at decision step 1408: “Is Desired Shade Wobbling?” If “No” is selected by the user at decision step 1408 (“No” path from decision step 1408), room controller 704 directs another motorized roller shade 106 to “wobble” its respective shade fabric 104 (at step 1410) and again prompts the user to select “Yes” or “No” (at step decision step 1408). This procedure is repeated until the shade fabric 104 of the desired motorized roller shade 106 is wobbled room controller 704 (via operation of method 1400) and “Yes” is selected by the user at decision step 1408.

According to a further aspect of the embodiments, another method exists for visually identifying a particular motorized roller shade 106 in a shade addressing programming mode, wherein a subset of motorized roller shades 106 initially includes all of the motorized roller shades 106. According to an embodiment, room controller 704 can direct one half of the motorized shades 106 of the current subset to move to a fully-opened position and the other half of the subset to a fully-closed position. The user is then prompted by the GUI software to select “opened” or “closed” to identify the position of the desired motorized roller shade 106. The process is then repeated with the selected subset half becoming a new subset of motorized roller shades 106 and room controller 704 moving half of motorized roller shades 106 of the new subset to fully-opened and half to fully-closed. This procedure is repeated until the desired motorized roller shade 106 is the only motorized roller shade 106 in the subset.

The method just described in the previous paragraph, in which half of the motorized roller shades 106 of the subset are moved to fully-opened and half are moved to fully-closed provides a binary system of visually identifying a particular motorized roller shade 106. According to further embodiments, however, a binary system is not required. Room automation system 700 can be adapted, for example, to direct to move 1/N of the motorized roller shades 106 of the current subset to one of N shade positions. For example, motorized roller shades 106 in a current subset of shades 106 can be divided into quarters that are respectively moved to fully-opened, fully-closed, one-quarter raised and three-quarter raised positions. Those of skill in the art can appreciate that other sizes of “divisions” or “groupings” of motorized roller shades 106 are within the scope of the embodiments, and the above examples are just that and not to be taken in a limiting manner.

The following is a list of the acronyms used in the specification in alphabetical order.

3G Third Generation
 4G Fourth Generation
 EDU Electronic Drive Unit
 GUI Graphical User Interface
 HVAC Heating/Ventilation/Air Conditioning
 ID Identification Number
 IEEE Institute of Electrical and Electronics Engineers
 IU Interface Unit
 LAN Local Area Network
 LCD Liquid Crystal Display
 LAN Local Area Network
 LED Light Emitting Diode
 LTE Long Term Evolution
 PC Personal Computer
 PoE Power-over-Ethernet
 USB Universal Serial Bus
 VAC Volts, Alternating Current
 VDC Volts, Direct Current
 WAN Wide Area Network

The disclosed embodiments provide a system, software, and a method for controlling motorized roller shades, lighting, and providing power-over-Ethernet to the motorized roller shades. It should be understood that this description is not intended to limit the embodiments. On the contrary, the embodiments are intended to cover alternatives, modifications, and equivalents, which are included in the spirit and scope of the embodiments as defined by the appended claims. Further, in the detailed description of the embodiments, numerous specific details are set forth to provide a comprehensive understanding of the claimed embodiments. However, one skilled in the art would understand that various embodiments may be practiced without such specific details.

Although the features and elements of aspects of the embodiments are described being in particular combinations, each feature or element can be used alone, without the other features and elements of the embodiments, or in various combinations with or without other features and elements disclosed herein.

This written description uses examples of the subject matter disclosed to enable any person skilled in the art to practice the same, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the subject matter is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims.

37

The above-described embodiments are intended to be illustrative in all respects, rather than restrictive, of the embodiments. Thus the embodiments are capable of many variations in detailed implementation that can be derived from the description contained herein by a person skilled in the art. No element, act, or instruction used in the description of the present application should be construed as critical or essential to the embodiments unless explicitly described as such. Also, as used herein, the article "a" is intended to include one or more items.

All United States patents and applications, foreign patents, and publications discussed above are hereby incorporated herein by reference in their entireties.

What is claimed is:

1. A system for controlling lights and shades, comprising:
 - a room controller adapted to transmit control signals to one or more devices, wherein said control signals represent a desired intensity level setting, and wherein the one or more devices are adapted to receive the transmitted control signals; and
 - a power cable adapted to transfer power to a first set of said one or more devices from a transformer, and wherein the one or more devices are further adapted to convert said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of said at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor, and wherein said electronic drive unit further comprises
 - a relay switch network configured to cause electrical power to selectively by-pass said electrical drive unit, and wherein said relay switch network is further configured to selectively allow one or more batteries in one or more different respective motorized roller shades to draw re-charging power from said battery in said motorized roller shade associated with said electrical drive unit.
2. The system according to claim 1, wherein the one or more devices are further adapted to convert a first set of said control signals representing an intensity level setting of a shade such that the motorized roller shades changes a shade position of said shade to match the desired intensity level setting, and the one or more devices are further adapted to convert a second set of said control signals representing an intensity level setting of a dimmable light such that said dimmable light control signals change a dimming setting of said dimmable light, wherein the conversion of said first set of control signals includes transmitting a sequence of control signals to the motorized roller shades such that said motorized shade moves said shade in a series of substantially evenly timed steps of substantially equal distance to simulate a relatively slowly moving shade compared to a normal rate of driven movement for the motorized roller shade, and further wherein
- a motor speed for the at least one motorized shade is variable, and wherein

38

the transmission of the sequence of control signals includes transmitting a signal concurrently with the intensity level directing the at least one motorized shade to move to the associated shade position at a desired speed.

3. The system according to claim 1, wherein the transmission of the sequence of control signals further includes
 - a transmission of said control signals from said room controller to a mesh network gateway, wherein said control signals further include database information, and
 - a forwarding of said control signals wirelessly from said mesh network gateway to each of said one or more motorized roller shades.
4. The system according to claim 3, wherein the transformer is further adapted to transmit a trickle-charge re-charging current from said transformer to a first one of said motorized roller shades over said power cable, and wherein a power-over-Ethernet (PoE) cable is connected between each electronic data unit of each at least one or more motorized roller shades in a daisy chain fashion.
5. The system according to claim 3, wherein said electronic drive unit further includes control electronics, and wherein said control electronics includes an input interface, and an output interface, and wherein said input interface is configured to receive control signals, database information, and trickle-charge re-charging current from a preceding electronic drive unit, if so connected, via said PoE cable, and wherein said output interface is configured to transmit control signals, database information, and trickle-charge re-charging current to a subsequent electronic drive unit via said PoE cable.
6. The system according to claim 5, wherein said motorized roller shade further comprises:
 - a shade; and
 - a hem bar located at a bottom of said shade, wherein said hem bar includes one or more small batteries electrically connected to each other and said battery of said motorized roller shade, and wherein said small batteries are configured to provide a trickle-charge re-charging current to said battery of said motorized roller shade.
7. A system for controlling lights and shades, comprising:
 - a room controller adapted to transmit control signals to one or more devices, wherein said control signals represent a desired intensity level setting, and wherein the one or more devices are adapted to receive the transmitted control signals; and
 - a power cable adapted to transfer power to a first set of said one or more devices from a transformer, and wherein the one or more devices are further adapted to convert said control signals to effectuate said desired intensity level setting, and wherein said one or more devices includes motorized roller shades and dimmable lighting devices, wherein each of said one or more motorized roller shades includes a respective electronic data unit for each of said at least one motorized roller shades, and wherein each of said electronic drive units includes an elongated motor, and a battery, and further wherein said battery is configured to provide operating power to said elongated motor, and wherein said motorized roller shade further comprises

a shade; and
 a hem bar located at a bottom of said shade,
 wherein said hem bar includes one or more
 small batteries electrically connected to each
 other and said battery of said motorized roller
 shade, and wherein said small batteries are
 configured to provide a trickle-charge re-charg-
 ing current to said battery of said motorized
 roller shade.

8. The system according to claim 7, wherein
 the one or more devices are further adapted to convert a
 first set of said control signals representing an intensity
 level setting of a shade such that the motorized roller
 shades changes a shade position of said shade to match
 the desired intensity level setting, and the one or more
 devices are further adapted to
 convert a second set of said control signals representing
 an intensity level setting of a dimmable light such that
 said dimmable light control signals change a dimming
 setting of said dimmable light, wherein the conversion
 of said first set of control signals includes
 transmitting a sequence of control signals to the motor-
 ized roller shades such that said motorized shade moves
 said shade in a series of substantially evenly timed
 steps of substantially equal distance to simulate a
 relatively slowly moving shade compared to a normal
 rate of driven movement for the motorized roller shade,
 and further wherein
 a motor speed for the at least one motorized shade is
 variable, and wherein
 the transmission of the sequence of control signals
 includes transmitting a signal concurrently with the
 intensity level directing the at least one motorized
 shade to move to the associated shade position at a
 desired speed.

9. The system according to claim 7, wherein
 the transmission of the sequence of control signals further
 includes

a transmission of said control signals from said room
 controller to a mesh network gateway, wherein said
 control signals further include database information,
 and
 a forwarding of said controls signals wirelessly from
 said mesh network gateway to each of said one or
 more motorized roller shades.

10. The system according to claim 9, wherein
 the transformer is further adapted to transmit a trickle-
 charge re-charging current from said transformer to a
 first one of said motorized roller shades over said
 power cable, and wherein
 a power-over-Ethernet (PoE) cable is connected between
 each electronic data unit of each at least one or more
 motorized roller shades in a daisy chain fashion.

11. The system according to claim 9, wherein
 said electronic drive unit further includes control elec-
 tronics, and wherein said control electronics includes
 an input interface, and an output interface, and wherein
 said input interface is configured to receive control
 signals, database information, and trickle-charge re-
 charging current from a preceding electronic drive
 unit, if so connected, via said PoE cable, and wherein
 said output interface is configured to transmit control
 signals, database information, and trickle-charge re-
 charging current to a subsequent electronic drive unit
 via said PoE cable.

12. The system according to claim 11, wherein said
 electronic drive unit further comprises:
 a relay switch network configured to cause electrical
 power to selectively by-pass said electrical drive unit,
 and wherein
 said relay switch network is further configured to
 selectively allow one or more batteries in one or
 more different respective motorized roller shades to
 draw re-charging power from said battery in said
 motorized roller shade associated with said electrical
 drive unit.

* * * * *