



(12) **United States Patent**
Chang et al.

(10) **Patent No.:** **US 11,046,249 B2**
(45) **Date of Patent:** **Jun. 29, 2021**

(54) **MOVABLE CARRIER AUXILIARY SYSTEM AND VEHICLE ELECTRONIC REAR-VIEW MIRROR**

(58) **Field of Classification Search**
CPC B60R 1/00; B60R 1/12; B60R 2001/1215; B60R 1/06; B60R 1/04; G02B 13/0035; (Continued)

(71) Applicant: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO., LTD.**, Taichung (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(72) Inventors: **Yeong-Ming Chang**, Taichung (TW); **Chien-Hsun Lai**, Taichung (TW); **Yao-Wei Liu**, Taichung (TW)

7,543,946 B2* 6/2009 Ockerse B60R 1/088 250/216
7,859,737 B2* 12/2010 McCabe B60R 1/12 359/265

(73) Assignee: **ABILITY OPTO-ELECTRONICS TECHNOLOGY CO., LTD.**, Taichung (TW)

(Continued)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 101535087 A 9/2009
TW 201806803 A 3/2018

Primary Examiner — Susan E. Hodges

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(21) Appl. No.: **16/506,677**

(57) **ABSTRACT**

(22) Filed: **Jul. 9, 2019**

A movable carrier auxiliary system includes a first transparent assembly, a second transparent assembly, an electro-optic medium layer, a transparent electrode, a reflective layer, a transparent conductive layer, an electrical connector, a control member, and an optical image capturing module. A gap is formed between the second transparent assembly and the first transparent assembly. The electro-optic medium layer is disposed in the gap. The transparent electrode is disposed between the first transparent assembly and the electro-optic medium layer. The electro-optic medium layer is disposed between the first transparent assembly and the at least one reflective layer. The transparent conductive layer is disposed between the electro-optic medium layer and the at least one reflective layer. The electrical connector is electrically connected to the electro-optic medium layer, and transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer.

(65) **Prior Publication Data**

US 2020/0215973 A1 Jul. 9, 2020

(30) **Foreign Application Priority Data**

Jan. 7, 2019 (TW) 108100589

(51) **Int. Cl.**

B60R 1/00 (2006.01)

G02B 13/00 (2006.01)


(Continued)

(52) **U.S. Cl.**

CPC **B60R 1/00** (2013.01); **B60R 1/04** (2013.01); **B60R 1/06** (2013.01); **B60R 1/12** (2013.01);

(Continued)

30 Claims, 14 Drawing Sheets



- (51) **Int. Cl.** *1/13439* (2013.01); *G02F 1/133553* (2013.01);
G02B 9/00 (2006.01) *G02F 1/155* (2013.01); *G02F 1/157* (2013.01);
H04N 7/18 (2006.01) *G02F 1/169* (2019.01)
G02B 9/64 (2006.01)
G02B 9/60 (2006.01)
G02B 9/34 (2006.01)
G02B 9/16 (2006.01)
B60R 1/04 (2006.01)
B60R 1/12 (2006.01)
B60R 1/06 (2006.01)
G02B 9/62 (2006.01)
G02F 1/1343 (2006.01)
G02F 1/1335 (2006.01)
G02F 1/155 (2006.01)
G02F 1/157 (2006.01)
G02F 1/169 (2019.01)
- (52) **U.S. Cl.**
 CPC *G02B 9/16* (2013.01); *G02B 9/34*
 (2013.01); *G02B 9/60* (2013.01); *G02B 9/62*
 (2013.01); *G02B 9/64* (2013.01); *G02B*
13/004 (2013.01); *G02B 13/0035* (2013.01);
G02B 13/0045 (2013.01); *H04N 7/181*
 (2013.01); *B60R 2001/1215* (2013.01); *G02F*
- (58) **Field of Classification Search**
 CPC *G02B 9/62*; *G02B 9/60*; *G02B 13/0045*;
G02B 9/34; *G02B 13/004*; *G02B 9/16*;
G02B 9/64; *H04N 7/181*; *G02F 1/169*;
G02F 1/133553; *G02F 1/157*; *G02F*
1/13439; *G02F 1/155*
 USPC 348/148
 See application file for complete search history.
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
 2009/0015736 A1* 1/2009 Weller B60R 1/12
 349/11
 2015/0283945 A1* 10/2015 Krebs B60R 1/088
 349/58
 2018/0050641 A1* 2/2018 Lin B60R 1/12
 2019/0275945 A1* 9/2019 Chang B60R 1/088
 2020/0057251 A1* 2/2020 Chang H04N 5/2254
 * cited by examiner




FIG.1A




FIG.1B




FIG.1C




FIG.1D




FIG.1E




FIG.1F




FIG. 1G




FIG.1H




FIG.2A




FIG.2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG.7B

MOVABLE CARRIER AUXILIARY SYSTEM AND VEHICLE ELECTRONIC REAR-VIEW MIRROR

BACKGROUND OF THE INVENTION

Technical Field

The present invention generally relates to a movable carrier auxiliary system, and more particularly to a displaying system which could show changes in color and transparency.

Description of Related Art

With frequent commercial activities and the rapid expansion of transportation logistics, people are more dependent on the mobile vehicle such as car or motorcycle. At the same time, drivers are paying more and more attention to the protection of their lives and property when driving, and therefore, in addition to the performance and the comfort of the mobile vehicle, it is also considered whether the mobile vehicle to be purchased provides sufficient safety guards or auxiliary devices. Under this trend, in order to increase the safety of vehicles, automobile manufacturers or vehicle equipment design manufacturers have developed various driving safety protection devices or auxiliary devices, such as rearview mirrors, driving recorders, a panoramic image instant displaying of blind vision areas, a global positioning system that records the driving path at any time, and etc.

In addition, with the rapid development of digital cameras and computer visions in daily life, the digital cameras have been applied to driving assistance systems, hoping to reduce the accident rate of traffic accidents through the application of artificial intelligence.

Take a conventional rearview mirror as an example, when a driver changes lanes or turns, most of the conventional rearview mirror is used to observe and determine the presence or absence of objects outside of the vehicle. However, most of the rearview mirrors have limitations and disadvantages in use under certain driving conditions. For example, when driving at night, the driver's pupil is in an enlarged state in the dark environment just like the shutter of the camera for providing more optical signals to the optic nerve. In such a state, the driver's eyes are extremely sensitive to sudden light. Usually, the rearview mirror reflects the front light from the overtaking or subsequent vehicles, which causes the driver to have a visual dizziness, so that the driver's visual ability will be rapidly reduced in an instant, increasing the driver's reaction time that front obstacles become visible.

Therefore, how to effectively control the light reflectivity and penetration rate of the rearview mirror to reduce the light entering the driver's eyes so as to improve the driver's visual dizziness and to improve driving safety is one of the important problems to be solved.

BRIEF SUMMARY OF THE INVENTION

The present invention provides a movable carrier auxiliary system which is a vehicle electronic rear-view mirror as an example and includes a first transparent assembly, a second transparent assembly, an electro-optic medium layer, at least one transparent electrode, at least one reflective layer, and at least one transparent conductive layer. The electro-optic medium layer is disposed between the first transparent assembly and the second transparent assembly.

The transparent electrode could be disposed between the first transparent assembly and the electro-optic medium layer. The electro-optic medium layer could be disposed between the first transparent assembly and the reflective layer. The transparent electrode could be disposed between the electro-optic medium layer and the reflective layer. In this way, when the electro-optic medium layer is enabled by applying an external voltage or current, the optical properties of the electro-optic medium layer in the visible wavelength range (e.g. light transmittance, light reflectivity, or absorbance) could produce stable reversible change, thereby enabling color and transparency changes.

When an intensity of the external light is too strong to affect the driver's eyes, the external light is absorbed by the electro-optic medium layer to be in a matt state after the light beam reaches the electro-optic medium layer, so that the vehicle electronic rearview mirror is switched to an anti-glare mode. On the other hand, when the electro-optic medium layer is disabled, the electro-optic medium layer is transparent. At this time, the external light passes through the electro-optic medium layer to be reflected by the reflective layer, so that the vehicle electronic rear-view mirror is switched to a mirror mode.

In addition, in an embodiment, the movable carrier auxiliary system of the present invention could further include at least one displaying device and an optical image capturing module, wherein the image capturing module is electrically connected to the displaying device, and captures and projects an environmental image signal to the displaying device. The optical image capturing systems has at least one lens group, wherein the at least one lens group includes at least two lenses having refractive power. The lens group uses structural size design and combination of refractive powers, convex and concave surfaces of at least two optical lenses (the convex or concave surface in the disclosure denotes the geometrical shape of an image-side surface or an object-side surface of each lens on an optical axis) to reduce the size and increase the quantity of incoming light of the optical image capturing module, thereby the optical image capturing module could have a better amount of light entering therein and could improve imaging total pixels and imaging quality for image formation.

In an embodiment, the movable carrier auxiliary system of the present invention further includes at least one displaying device for displaying an environmental image signal and a third transparent assembly disposed on the second incidence surface, wherein the third transparent assembly includes a third incidence surface and a third exit surface. The image enters the third transparent assembly via the third incidence surface, and is emitted to the second incidence surface from the third exit surface.

In an embodiment, the first transparent assembly has a surface away from the second transparent assembly. An external light enters the vehicle electronic rear-view mirror via the surface, and the vehicle electronic rear-view mirror reflects the external light, so that the external light leaves the vehicle electronic rear-view mirror via the surface. A reflectance of the vehicle electronic rear-view mirror for reflecting the external light is more than 35%.

In an embodiment, the first transparent assembly is adhered to the second incidence surface via an optical adhesive, and the optical adhesive forms an optical adhesion layer.

In an embodiment, the vehicle electronic rear-view mirror includes an auxiliary reflective layer disposed between the reflective layer and the second transparent assembly.

In an embodiment, a material of the reflective layer could be selected from a material containing cerium oxide, or could be a material which is conductive selected from a group consisting of at least one of silver (Ag), copper (Cu), aluminum (Al), titanium (Ti), chromium (Cr), molybdenum (Mo) or its alloy, or could be a transparent conductive material.

In an embodiment, a material of the auxiliary reflective layer could be selected from a material containing cerium oxide, or a group consisting of chromium (Cr), titanium, and molybdenum, or an alloy thereof, or could be a transparent conductive material.

In an embodiment, the second transparent assembly is disposed between the transparent conductive layer and the reflective layer.

In an embodiment, a material of the transparent conductive layer could be at least one material selected from a group consisting of indium tin oxide (ITO), indium zinc oxide (IZO), Al-doped ZnO (AZO), or Fluorine-doped tin oxide.

In an embodiment, the displaying device is adapted to emit an image light, wherein the image light passes through the vehicle electronic rear-view mirror and leaves the vehicle electronic rear-view mirror via the surface. A reflectance of the vehicle electronic rear-view mirror for reflecting the external light could be more than 40%, and a penetration rate of the vehicle electronic rear-view mirror for the image light is greater than 15%.

In an embodiment, the electro-optic medium layer is selected from an electrochromic layer, a polymer dispersed liquid crystal (PDLC) layer, or a suspended particle device (SPD) layer.

In an embodiment, the optical image capturing systems has at least one lens group, wherein the at least one lens group includes at least two lenses having refractive power and satisfies: $1.0 \leq f/\text{HEP} \leq 10.0$; $0 \text{ deg} < \text{HAF} \leq 150 \text{ deg}$; and $0.9 \leq 2(\text{ARE}/\text{HEP}) \leq 2.0$, wherein f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

In an embodiment, the lens group satisfies: $0.9 \leq \text{ARS}/\text{EHD} \leq 2.0$, wherein for any surface of any lens, ARS is a profile curve length measured from a start point where the optical axis passes therethrough, along a surface profile thereof, and finally to an end point of the maximum effective half diameter thereof; EHD is a maximum effective half diameter thereof.

In an embodiment, the lens group satisfies: $\text{PLTA} \leq 100 \mu\text{m}$; $\text{PSTA} \leq 100 \mu\text{m}$; $\text{NLTA} \leq 100 \mu\text{m}$; $\text{NSTA} \leq 100 \mu\text{m}$; $\text{SLTA} \leq 100 \mu\text{m}$; $\text{SSTA} \leq 100 \mu\text{m}$; and $|\text{TDT}| < 250\%$, wherein HOI is a maximum height for image formation perpendicular to the optical axis on an image plane of the at least one lens group; PLTA is a transverse aberration at 0.7 HOI in a positive direction of a tangential ray fan aberration after the longest operation wavelength passing through an edge of the entrance pupil; PSTA is a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; NLTA is a transverse aberration at 0.7 HOI in a negative direction of the tangential ray fan aberration after the longest operation wavelength passing

through the edge of the entrance pupil; NSTA is a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; SLTA is a transverse aberration at 0.7 HOI of a sagittal ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil; SSTA is a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; TDT is a TV distortion for image formation in the optical image capturing module.

In an embodiment, the lens group includes four lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, and a fourth lens in order along an optical axis from an object side to an image side. The lens group satisfies: $0.1 \leq \text{InTL}/\text{HOS} \leq 0.95$, wherein HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fourth lens.

In an embodiment, the lens group includes five lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, and a fifth lens in order along an optical axis from an object side to an image side. The lens group satisfies: $0.1 \leq \text{InTL}/\text{HOS} \leq 0.95$, wherein HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fifth lens.

In an embodiment, the lens group includes six lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens in order along an optical axis from an object side to an image side. The lens group satisfies: $0.1 \leq \text{InTL}/\text{HOS} \leq 0.95$, wherein HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the sixth lens.

In an embodiment, the lens group includes seven lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens in order along an optical axis from an object side to an image side. The lens group satisfies: $0.1 \leq \text{InTL}/\text{HOS} \leq 0.95$, wherein HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the seventh lens.

In an embodiment, the lens group includes more than seven lenses having refractive power.

In an embodiment, the optical image capturing system has at least two lens groups, wherein each of the lens groups includes at least two lenses having refractive power.

In an embodiment, the displaying device includes at least one of a LCD, a LED, an OLED, a plasma projection element, a digital projection element, and a liquid crystal display module.

In an embodiment, the electrical connector includes at least one of a flexible circuit board, a copper foil, and an electric wire.

In an embodiment, further including an image sensing device electrically connected to the at least one control member for sensing an environment brightness inside of the movable carrier, wherein the at least one control member controls a brightness of the at least one displaying device according to the environment brightness.

In an embodiment, when the environment brightness decreases, the brightness of the image decreases, while when the environment brightness rises, the brightness of the image rises.

The lens parameter related to a length or a height in the lens:

A maximum height for image formation of the optical image capturing module is denoted by HOI. A height of the optical image capturing module (i.e., a distance between an object-side surface of the first lens and an image plane on an optical axis) is denoted by HOS. A distance from the object-side surface of the first lens to the image-side surface of the seventh lens is denoted by InTL. A distance from the first lens to the second lens is denoted by IN12 (instance). A central thickness of the first lens of the optical image capturing module on the optical axis is denoted by TP1 (instance).

The lens parameter related to a material in the lens:

An Abbe number of the first lens in the optical image capturing module is denoted by NA1 (instance). A refractive index of the first lens is denoted by Nd1 (instance).

The lens parameter related to a view angle of the lens:

A view angle is denoted by AF. Half of the view angle is denoted by HAF. A major light angle is denoted by MRA.

The lens parameter related to exit/entrance pupil in the lens:

An entrance pupil diameter of the optical image capturing module is denoted by HEP. For any surface of any lens, a maximum effective half diameter (EHD) is a perpendicular distance between an optical axis and a crossing point on the surface where the incident light with a maximum viewing angle of the optical image capturing module passing the very edge of the entrance pupil. For example, the maximum effective half diameter of the object-side surface of the first lens is denoted by EHD11, the maximum effective half diameter of the image-side surface of the first lens is denoted by EHD12, the maximum effective half diameter of the object-side surface of the second lens is denoted by EHD21, the maximum effective half diameter of the image-side surface of the second lens is denoted by EHD22, and so on. In the optical image capturing module, a maximum effective diameter of the image-side surface of the lens closest to the image plane is denoted by PhiA, which satisfies the condition: $\text{PhiA}=2*\text{EHD}$. If the surface is aspherical, a cut-off point of the largest effective diameter is the cut-off point containing the aspheric surface. An ineffective half diameter (IHD) of any surface of one single lens refers to a surface segment between cut-off points of the maximum effective half diameter of the same surface extending in a direction away from the optical axis, wherein said a cut-off point is an end point of the surface having an aspheric coefficient if said surface is aspheric. In the optical image capturing module, a maximum diameter of the image-side surface of the lens closest to the image plane is denoted by PhiB, which satisfies the condition: $\text{PhiB}=2*(\text{maximum effective half diameter EHD}+\text{maximum ineffective half diameter IHD})=\text{PhiA}+2*(\text{maximum ineffective half diameter IHD})$.

In the optical image capturing module, a maximum effective diameter of the image-side surface of the lens closest to the image plane (i.e., the image space) could be also called optical exit pupil, and is denoted by PhiA. If the optical exit

pupil is located on the image-side surface of the third lens, then it is denoted by PhiA3; if the optical exit pupil is located on the image-side surface of the fourth lens, then it is denoted by PhiA4; if the optical exit pupil is located on the image-side surface of the fifth lens, then it is denoted by PhiA5; if the optical exit pupil is located on the image-side surface of the sixth lens, then it is denoted by PhiA6, and so on. A pupil magnification ratio of the optical image capturing module is denoted by PMR, which satisfies the condition:

$$\text{PMR}=\text{PhiA}/\text{HEP}.$$

The lens parameter related to an arc length of the shape of a surface and a surface profile:

For any surface of any lens, a profile curve length of the maximum effective half diameter is, by definition, measured from a start point where the optical axis of the belonging optical image capturing module passes through the surface of the lens, along a surface profile of the lens, and finally to an end point of the maximum effective half diameter thereof. In other words, the curve length between the aforementioned start and end points is the profile curve length of the maximum effective half diameter, which is denoted by ARS. For example, the profile curve length of the maximum effective half diameter of the object-side surface of the first lens is denoted by ARS11, the profile curve length of the maximum effective half diameter of the image-side surface of the first lens is denoted by ARS12, the profile curve length of the maximum effective half diameter of the object-side surface of the second lens is denoted by ARS21, the profile curve length of the maximum effective half diameter of the image-side surface of the second lens is denoted by ARS22, and so on.

For any surface of any lens, a profile curve length of a half of the entrance pupil diameter (HEP) is, by definition, measured from a start point where the optical axis of the belonging optical image capturing module passes through the surface of the lens, along a surface profile of the lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis. In other words, the curve length between the aforementioned start point and the coordinate point is the profile curve length of a half of the entrance pupil diameter (HEP), and is denoted by ARE. For example, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the first lens is denoted by ARE11, the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the first lens is denoted by ARE12, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the second lens is denoted by ARE21, the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the second lens is denoted by ARE22, and so on.

The lens parameter related to a depth of the lens shape:

A displacement from a point on the object-side surface of the sixth lens, which is passed through by the optical axis, to a point on the optical axis, where a projection of the maximum effective semi diameter of the object-side surface of the sixth lens ends, is denoted by InRS61 (the depth of the maximum effective semi diameter). A displacement from a point on the image-side surface of the sixth lens, which is passed through by the optical axis, to a point on the optical axis, where a projection of the maximum effective semi diameter of the image-side surface of the seventh lens ends, is denoted by InRS62 (the depth of the maximum effective semi diameter). The depth of the maximum effective semi

diameter (sinkage) on the object-side surface or the image-side surface of any other lens is denoted in the same manner.

The lens parameter related to the lens shape:

A critical point C is a tangent point on a surface of a specific lens, and the tangent point is tangent to a plane perpendicular to the optical axis and the tangent point cannot be a crossover point on the optical axis. Following the above description, a distance perpendicular to the optical axis between a critical point C51 on the object-side surface of the fifth lens and the optical axis is HVT51 (instance), and a distance perpendicular to the optical axis between a critical point C52 on the image-side surface of the fifth lens and the optical axis is HVT52 (instance). A distance perpendicular to the optical axis between a critical point C61 on the object-side surface of the sixth lens and the optical axis is HVT61 (instance), and a distance perpendicular to the optical axis between a critical point C62 on the image-side surface of the sixth lens and the optical axis is HVT62 (instance). A distance perpendicular to the optical axis between a critical point on the object-side or image-side surface of other lenses is denoted in the same manner.

The object-side surface of the seventh lens has one inflection point IF711 which is nearest to the optical axis, and the sinkage value of the inflection point IF711 is denoted by SGI711 (instance). A distance perpendicular to the optical axis between the inflection point IF711 and the optical axis is HIF711 (instance). The image-side surface of the seventh lens has one inflection point IF721 which is nearest to the optical axis, and the sinkage value of the inflection point IF721 is denoted by SGI721 (instance). A distance perpendicular to the optical axis between the inflection point IF721 and the optical axis is HIF721 (instance).

The object-side surface of the seventh lens has one inflection point IF712 which is the second nearest to the optical axis, and the sinkage value of the inflection point IF712 is denoted by SGI712 (instance). A distance perpendicular to the optical axis between the inflection point IF712 and the optical axis is HIF712 (instance). The image-side surface of the seventh lens has one inflection point IF722 which is the second nearest to the optical axis, and the sinkage value of the inflection point IF722 is denoted by SGI722 (instance). A distance perpendicular to the optical axis between the inflection point IF722 and the optical axis is HIF722 (instance).

The object-side surface of the seventh lens has one inflection point IF713 which is the third nearest to the optical axis, and the sinkage value of the inflection point IF713 is denoted by SGI713 (instance). A distance perpendicular to the optical axis between the inflection point IF713 and the optical axis is HIF713 (instance). The image-side surface of the seventh lens has one inflection point IF723 which is the third nearest to the optical axis, and the sinkage value of the inflection point IF723 is denoted by SGI723 (instance). A distance perpendicular to the optical axis between the inflection point IF723 and the optical axis is HIF723 (instance).

The object-side surface of the seventh lens has one inflection point IF714 which is the fourth nearest to the optical axis, and the sinkage value of the inflection point IF714 is denoted by SGI714 (instance). A distance perpendicular to the optical axis between the inflection point IF714 and the optical axis is HIF714 (instance). The image-side surface of the seventh lens has one inflection point IF724 which is the fourth nearest to the optical axis, and the sinkage value of the inflection point IF724 is denoted by SGI724 (instance). A distance perpendicular to the optical axis between the inflection point IF724 and the optical axis is HIF724 (instance).

An inflection point, a distance perpendicular to the optical axis between the inflection point and the optical axis, and a sinkage value thereof on the object-side surface or image-side surface of other lenses is denoted in the same manner.

The lens parameter related to an aberration:

Optical distortion for image formation in the optical image capturing module is denoted by ODT. TV distortion for image formation in the optical image capturing module is denoted by TDT. Further, the range of the aberration offset for the view of image formation may be limited to 50%-100% field. An offset of the spherical aberration is denoted by DFS. An offset of the coma aberration is denoted by DFC.

The present invention provides a movable carrier auxiliary system which is a vehicle electronic rear-view mirror as an example and includes a first transparent assembly, a second transparent assembly, an electro-optic medium layer, at least one transparent electrode, at least one reflective layer, and at least one transparent conductive layer. The first transparent assembly has a first incidence surface and a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface. The second transparent assembly is disposed on the first exit surface, and includes a second incidence surface and a second exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly. The image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface. The electro-optic medium layer is disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second transparent assembly. The transparent electrode is disposed between the first transparent assembly and the electro-optic medium layer. The electro-optic medium layer could be disposed between the first transparent assembly and the reflective layer. The transparent conductive layer is disposed between the electro-optic medium layer and the at least one reflective layer. The electrical connector is electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer. The control member is electrically connected to the at least one electrical connector, wherein when a brightness of the image exceeds a certain brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer.

The present invention provides a movable carrier auxiliary system which is a vehicle electronic rear-view mirror as an example and includes a first transparent assembly, a second transparent assembly, an electro-optic medium layer, at least one transparent electrode, at least one reflective layer, at least one transparent conductive layer, at least one displaying device and at least one optical image capturing module. The first transparent assembly has a first incidence surface and a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface. The second transparent assembly is disposed on the first exit surface, and includes a second incidence surface and a second exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly. The image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface. The electro-optic medium layer is disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second trans-

parent assembly. The transparent electrode is disposed between the first transparent assembly and the electro-optic medium layer. The electro-optic medium layer could be disposed between the first transparent assembly and the reflective layer. The transparent conductive layer is disposed between the electro-optic medium layer and the at least one reflective layer. The electrical connector is electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer. The control member is electrically connected to the at least one electrical connector, wherein when a brightness of the image exceeds a certain brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer. The image capturing module is electrically connected to the displaying device, and captures and projects an environmental image signal to the displaying device. The optical image capturing systems has at least one lens group, wherein the at least one lens group includes at least two lenses having refractive power and satisfies: $1.0 \leq f/HEP \leq 10.0$; $0 \text{ deg} < HAF \leq 150 \text{ deg}$; and $0.9 \leq 2(ARE/HEP) \leq 2.0$, wherein f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

In an embodiment, the movable carrier auxiliary system is a vehicle electronic rear-view mirror.

In an embodiment, a brightness of the displaying device is greater than 1000 nits, and the displaying device exhibits an image with high dynamic range (HDR).

In an embodiment, further including a signal input device electrically coupled to the displaying device for sending a heterogeneous signal that is not from the optical image capturing system to the displaying device for numerical or graphical presentation.

In an embodiment, the signal input device is a tire pressure detector.

In an embodiment, the movable carrier auxiliary system is disposed on a transport which is a vehicle as an example. The movable carrier auxiliary system further includes a plurality of optical image capturing systems respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle, wherein the external image signal captured by each of the optical image capturing systems could be transmitted to the displaying device, and could be instantly and simultaneously presented to the driver for different viewing directions in a non-overlapping manner or in an image butting manner.

In an embodiment, the movable carrier auxiliary system further includes at least one at least one movable detector and a plurality of optical image capturing systems respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle, wherein when the movable carrier is in a state of shutting down the power system and stopping driving, the movable detector starts to continuously detect whether the movable carrier is collided

or vibrated. If the movable carrier is bumped or vibrated, the movable detector starts the video modules to instantly record.

In an embodiment, the movable carrier auxiliary system further includes a switch controller and two optical image capturing systems, wherein one of the optical image capturing systems is disposed on a front position of the movable carrier, and another one thereof is disposed on a rear position of the movable carrier. When the movable carrier is on a reverse mode, the monitor could display a rear image of the movable carrier and instantly record the video.

In an embodiment, the movable carrier auxiliary system further includes an information communication device, wherein the information communication device is adapted to communicate with a default contact person or organization.

In an embodiment, the movable carrier auxiliary system further includes a driving setter and a biological identification device, wherein the driving setter is electrically connected to the biological identification device. When a specific driver enters the movable carrier and faces the biological identification device, an identification could be performed and the driving setter is started. The driving setter controls the movable carrier according to parameters preset by an individual driver.

The present invention provides a vehicle electronic rear-view mirror which includes a first transparent assembly, a second transparent assembly, an electro-optic medium layer, at least one transparent electrode, at least one reflective layer, at least one transparent conductive layer, at least one displaying device and at least one optical image capturing module. The first transparent assembly has a first incidence surface and a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface. The second transparent assembly is disposed on the first exit surface, and includes a second incidence surface and a second exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly. The image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface. The electro-optic medium layer is disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second transparent assembly. The transparent electrode is disposed between the first transparent assembly and the electro-optic medium layer. The electro-optic medium layer could be disposed between the first transparent assembly and the reflective layer. The transparent conductive layer is disposed between the electro-optic medium layer and the at least one reflective layer. The electrical connector is electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer. The control member is electrically connected to the at least one electrical connector, wherein when a brightness of the image exceeds a certain brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer. The image capturing module is electrically connected to the displaying device, and captures and projects an environmental image signal to the displaying device. The optical image capturing systems has at least one lens group, wherein the at least one lens group includes at least two lenses having refractive power and satisfies: $1.0 \leq f/HEP \leq 10.0$; $0 \text{ deg} < HAF \leq 150 \text{ deg}$; and $0.9 \leq 2(ARE/HEP) \leq 2.0$, wherein f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of

the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

The length of the contour curve of any surface of a single lens in the range of the maximum effective radius affects the surface correction aberration and the optical path difference between the fields of view. The longer the profile curve length, the better the ability to correct the aberration, but at the same time It will increase the difficulty in manufacturing, so it is necessary to control the length of the profile curve of any surface of a single lens within the maximum effective radius, in particular to control the profile length (ARS) and the surface within the maximum effective radius of the surface. The proportional relationship (ARS/TP) between the thicknesses (TP) of the lens on the optical axis. For example, the length of the contour curve of the maximum effective radius of the side surface of the first lens object is represented by ARS11, and the thickness of the first lens on the optical axis is TP1, and the ratio between the two is ARS11/TP1, and the maximum effective radius of the side of the first lens image side. The length of the contour curve is represented by ARS12, and the ratio between it and TP1 is ARS12/TP1. The length of the contour curve of the maximum effective radius of the side of the second lens object is represented by ARS21, the thickness of the second lens on the optical axis is TP2, the ratio between the two is ARS21/TP2, and the contour of the maximum effective radius of the side of the second lens image. The length of the curve is represented by ARS22, and the ratio between it and TP2 is ARS22/TP2. The proportional relationship between the length of the profile of the maximum effective radius of any surface of the remaining lenses in the optical imaging system and the thickness (TP) of the lens on the optical axis to which the surface belongs, and so on. The optical image capturing module of the present invention satisfies: $0.9 \leq \text{ARS}/\text{EHD} \leq 2.0$.

The optical image capturing module has a maximum image height HOI on the image plane vertical to the optical axis. A transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by PLTA; a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by PSTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by NLTA; a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by NSTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil is denoted by SLTA; a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil is denoted by SSTA. The optical image capturing module of the present invention satisfies:

$\text{PLTA} \leq 100 \mu\text{m}$; $\text{PSTA} \leq 100 \mu\text{m}$; $\text{NLTA} \leq 100 \mu\text{m}$; $\text{NSTA} \leq 100 \mu\text{m}$; $\text{SLTA} \leq 100 \mu\text{m}$; $\text{SSTA} \leq 100 \mu\text{m}$; $|\text{TDT}| < 250\%$; $0.1 \leq \text{InTL}/\text{HOS} \leq 0.95$; and $0.2 \leq \text{InS}/\text{HOS} \leq 1.1$.

For visible light spectrum, the values of MTF in the spatial frequency of 110 cycles/mm at the optical axis, 0.3 field of view, and 0.7 field of view on an image plane are respectively denoted by MTFQ0, MTFQ3, and MTFQ7. The optical image capturing module of the present invention satisfies:

$\text{MTFQ0} \geq 0.2$; $\text{MTFQ3} \geq 0.01$; and $\text{MTFQ7} \geq 0.01$.

For any surface of any lens, the profile curve length within a half of the entrance pupil diameter (HEP) affects the ability of the surface to correct aberration and differences between optical paths of light in different fields of view. With longer profile curve length, the ability to correct aberration is better. However, the difficulty of manufacturing increases as well. Therefore, the profile curve length within a half of the entrance pupil diameter (HEP) of any surface of any lens has to be controlled. The ratio between the profile curve length (ARE) within a half of the entrance pupil diameter (HEP) of one surface and the thickness (TP) of the lens, which the surface belonged to, on the optical axis (i.e., ARE/TP) has to be particularly controlled. For example, the profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the first lens is denoted by ARE11, the thickness of the first lens on the optical axis is TP1, and the ratio between these two parameters is ARE11/TP1; the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the first lens is denoted by ARE12, and the ratio between ARE12 and TP1 is ARE12/TP1. The profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface of the second lens is denoted by ARE21, the thickness of the second lens on the optical axis is TP2, and the ratio between these two parameters is ARE21/TP2; the profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface of the second lens is denoted by ARE22, and the ratio between ARE22 and TP2 is ARE22/TP2. For any surface of other lenses in the optical image capturing system, the ratio between the profile curve length of a half of the entrance pupil diameter (HEP) thereof and the thickness of the lens which the surface belonged to is denoted in the same manner.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The present invention will be best understood by referring to the following detailed description of some illustrative embodiments in conjunction with the accompanying drawings, in which

FIG. 1A is a perspective schematic view of a first structural embodiment of the present invention;

FIG. 1B is a simplified sectional view, showing the short side of the first structural embodiment of the present invention;

FIG. 1C is a perspective schematic view of a second structural embodiment of the present invention;

FIG. 1D is a simplified sectional view, showing the short side of the second structural embodiment of the present invention;

FIG. 1E is a perspective schematic view of a third structural embodiment of the present invention;

FIG. 1F is a simplified sectional view, showing the short side of the third structural embodiment of the present invention;

FIG. 1G is a perspective schematic view of a fourth structural embodiment of the present invention;

13

FIG. 1H is a simplified sectional view, showing the short side of the fourth structural embodiment of the present invention;

FIG. 2A is a schematic diagram of a first optical embodiment of the present invention;

FIG. 2B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the first optical embodiment of the present application;

FIG. 3A is a schematic diagram of a second optical embodiment of the present invention;

FIG. 3B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the second optical embodiment of the present application;

FIG. 4A is a schematic diagram of a third optical embodiment of the present invention;

FIG. 4B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the third optical embodiment of the present application;

FIG. 5A is a schematic diagram of a fourth optical embodiment of the present invention;

FIG. 5B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the fourth optical embodiment of the present application;

FIG. 6A is a schematic diagram of a fifth optical embodiment of the present invention;

FIG. 6B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the fifth optical embodiment of the present application;

FIG. 7A is a schematic diagram of a sixth optical embodiment of the present invention; and

FIG. 7B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the sixth optical embodiment of the present application;

DETAILED DESCRIPTION OF THE INVENTION

A movable carrier auxiliary system of the present invention includes a structural design and an optical design, wherein structural embodiments will be described first.

A movable carrier auxiliary system which is a vehicle electronic rear-view mirror **0100** as an example according to a first structural embodiment of the present invention is illustrated in FIG. 1A. FIG. 1B is a simplified sectional view of FIG. 1A seen from a right shorter lateral side. The vehicle electronic rear-view mirror **0100** could be disposed on a transport which is a vehicle as an example to assist in the driving of the vehicle or to provide information about driving. More specifically, the vehicle electronic rear-view mirror **0100** could be an inner rear-view mirror disposed inside of the vehicle or could be an outer rear-view mirror disposed outside of the vehicle, which are used to assist the driver in understanding the location of other vehicles. However, this is not a limitation of the present invention. In addition, the transport is not limited to be a vehicle, but could be other types of vehicles, such as land, water, air transport, and etc.

The vehicle electronic rear-view mirror **0100** is assembled in a casing **0110**, wherein the casing **0110** has an opening (not shown). More specifically, the opening of the casing **0110** overlaps with a reflective layer **0190** of the vehicle

14

electronic rear-view mirror **0100** (shown in FIG. 1B). In this way, an external light could be transmitted to the reflective layer **0190** located inside of the casing **0110** through the opening, so that the vehicle electronic rear-view mirror **0100** functions as a mirror. When the driver drives the vehicle and faces the opening, for example, the driver could see the external light reflected by the vehicle electronic rear-view mirror **0100**, thereby knowing the position of the rear vehicle.

Referring to FIG. 1B, the vehicle electronic rear-view mirror **0100** includes a first transparent assembly **0120** and a second transparent assembly **0130**, wherein the first transparent assembly **0120** faces the driver, and the second transparent assembly **0130** is disposed on a side away from the driver. More specifically, the first transparent assembly **0120** and the second transparent assembly **0130** are translucent substrates, wherein a material of the translucent substrates could be glass for example. However, the material of the translucent substrates is not a limitation of the present invention. In other embodiments, the material of the translucent substrates could be plastic, quartz, PET substrate, or other applicable materials, wherein the PET substrate has the advantages of low cost, easy manufacture, and extremely thinness, in addition to packaging and protection effects.

In the current structural embodiment, the first transparent assembly **0120** includes a first incidence surface **0122** and a first exit surface **0124**, wherein an incoming light image from the rear of the driver enters the first transparent assembly **0120** via the first incidence surface **0122**, and is emitted via the first exit surface **0124**. The second transparent assembly **0130** includes a second incidence surface **0132** and a second exit surface **0134**, wherein the second incidence surface **0132** faces the first exit surface **0124**, and a gap is formed between the second incidence surface **0132** and the first exit surface **0124** by an adhesive **0114**. After the incoming light image being emitted via the first exit surface **0124**, the incoming light image enters the second transparent assembly **0130** via the second incidence surface **0132**, and is emitted via the second exit surface **0134**.

An electro-optic medium layer **0140** is disposed in the gap between the first exit surface **0124** of the first transparent assembly **0120** and the second incidence surface **0132** of the second transparent assembly **0130**. At least one transparent electrode **0150** is disposed between the first transparent assembly **0120** and the electro-optic medium layer **0140**. The electro-optic medium layer **0140** is disposed between the first transparent assembly **0120** and at least one reflective layer **0190**. A transparent conductive layer **0160** is disposed between the first transparent assembly **0120** and the electro-optic medium layer **0140**. Another transparent conductive layer **0160** is disposed between the second transparent assembly **0130** and the electro-optic medium layer **0140**. An electrical connector **0170** is electrically connected to the transparent conductive layer **0160**, and another electrical connector **0170** is electrically connected to the transparent electrode **0150**, thereby to transmit electrical energy to the electro-optic medium layer **0140** to change a transparency of the electro-optic medium layer **0140**. When a brightness of the incoming light image exceeds a certain brightness (e.g. a strong headlight from the rear of the vehicle), an image sensing device which is a glare sensor **0112** as an example electrically connected to a control member **0180** receives the light energy and convert it into a signal, and the control member **0180** determines whether the brightness of the incoming light image exceeds a predetermined brightness, and if a glare is generated, the electrical energy is provided to the electro-optic medium layer **0140** by the electrical

connector **0170** to generate an anti-glare performance. If the external light image is too strong, it will cause glare effect and affect the driver's eyes, thus endangering driving safety. More specifically, when an environment brightness inside of the movable carrier sensed by the image sensing device decreases, a brightness of the incoming light image decreases, while when the environment brightness rises, the brightness of the incoming light image rises. In an embodiment, the electrical connector could include at least one of a flexible circuit board, a copper foil, and an electric wire.

In addition, the transparent electrode **0150** and the reflective layer **0190** could respectively cover entire surface of the first transparent assembly **0120** and entire surface of the second transparent assembly **0130**. However, this is not a limitation of the present invention. In the current structural embodiment, a material of the transparent electrode **0150** could be selected from metal oxides such as indium tin oxide, indium zinc oxide, aluminum tin oxide, aluminum zinc oxide, indium antimony zinc oxide, other suitable oxides, or a stacked layer of at least two of the foregoing oxides. Moreover, a material of the reflective layer **0190** could be selected from a material containing cerium oxide, or could be a material which is conductive selected from a group consisting of at least one of silver (Ag), copper (Cu), aluminum (Al), titanium (Ti), chromium (Cr), molybdenum (Mo) or its alloy, or could be a transparent conductive material. However, the material of the transparent electrode **0150** and the material of the reflective layer **0190** are not a limitation of the present invention. In other embodiments, the material of the transparent electrode **0150** and the material of the reflective layer **0190** could be other types of materials.

The electro-optic medium layer **0140** could be made of an organic material or an inorganic material. However, this is not a limitation of the present invention. In the current structural embodiment, the electro-optic medium layer **0140** could be an electrochromic material. The electro-optic medium layer **0140** is disposed between the first transparent assembly **0120** and the second transparent assembly **0130** and is disposed between the first transparent assembly **0120** and the reflective layer **0190**. More specifically, the transparent electrode **0150** is disposed between the first transparent assembly **0120** and the electro-optic medium layer **0140** (i.e., electrochromic material layer). In a structural embodiment, the reflective layer **0190** could be disposed between the second transparent assembly **0130** and the electro-optic medium layer **0140**. In other embodiments, the electro-optic medium layer could be a polymer dispersed liquid crystal (PDLC) layer or a suspended particle device (SPD) layer. In addition, in the current structural embodiment, the vehicle electronic rear-view mirror **0100** further includes an adhesive **0114** located between the first transparent assembly **0120** and the second transparent assembly **0130** and surrounding the electro-optic medium layer **0140**. The electro-optic medium layer **0140** is co-packaged by the adhesive **0114**, the first transparent assembly **0120**, and the second transparent assembly **0130**.

In the current structural embodiment, the transparent conductive layer **0160** is disposed between the electro-optic medium layer **0140** and the reflective layer **0190**. More specifically, the transparent conductive layer **0160** could be used as an anti-oxidation layer of reflective layer **0190**, so that the electro-optic medium layer **0140** could be prevented from being in contact with the reflective layer **0190**, thereby preventing the reflective layer **0190** being corroded by organic materials, providing the vehicle electronic rear-view mirror **0100** of the current structural embodiment a longer

service life. In addition, the electro-optic medium layer **0140** is co-packaged by the adhesive **0114**, the transparent electrode **0150**, and the transparent conductive layer **0160**. In the current structural embodiment, the transparent conductive layer **0160** contains at least one material selected from a group consisting of indium tin oxide (ITO), indium zinc oxide (IZO), Al-doped ZnO (AZO), or Fluorine-doped tin oxide.

In the current structural embodiment, the vehicle electronic rear-view mirror **0100** could optionally provide with the electrical connector **0170**. For instance, in a structural embodiment, a conducting wire or a conducting structural is electrically connected to the transparent electrode **0150** and the reflective layer **0190**, so that the transparent electrode **0150** and the reflective layer **0190** could be electrically connected to the at least one control member **0180**, which provides a driving signal, via the conducting wire or the conducting structural, thereby to drive the electro-optic medium layer **0140**.

When the electro-optic medium layer **0140** is enabled, the electro-optic medium layer **0140** would undergo an electro-chemical redox reaction and change its energy level to be in a dimming state. When an external light passes through the opening of the casing **0110** and reaches the electro-optic medium layer **0140**, the external light would be absorbed by the electro-optic medium layer **0140** which is in the dimming state, so that the vehicle electronic rear-view mirror **0100** is switched to an anti-glare mode. On the other hand, when the electro-optic medium layer **0140** is disabled, the electro-optic medium layer **0140** is transparent. At this time, the external light passing through the opening of the casing **0110** passes through the electro-optic medium layer **0140** to be reflected by the reflective layer **0190**, so that the vehicle electronic rear-view mirror **0100** is switched to a mirror mode.

More specifically, the first transparent assembly **0120** has the first incidence surface **0122** which is away from the second transparent assembly **0130**. For instance, an external light from the rear vehicles enters the vehicle electronic rear-view mirror **0100** via the first incidence surface **0122**, and the vehicle electronic rear-view mirror **0100** reflects the external light, so that the external light leaves the vehicle electronic rear-view mirror **0100** via the first incidence surface **0122**. In addition, eyes of the vehicle driver could receive the external light reflected by the vehicle electronic rear-view mirror **0100** to know the position of other vehicles behind. Moreover, the reflective layer **0190** could have the optical properties of partial penetration and partial reflection by selecting a suitable material and design a proper film thickness.

A movable carrier auxiliary system which is a vehicle electronic rear-view mirror **0100** as an example according to a second structural embodiment of the present invention is illustrated in FIG. 1C. FIG. 1D is a simplified sectional view of FIG. 1C seen from a right shorter lateral side. The difference between the first structural embodiment and the second structural embodiment is that the vehicle electronic rear-view mirror **0100** according to the second structural embodiment could optionally include an auxiliary reflective layer **0192** disposed between the reflective layer **0190** and the first transparent assembly **0120**. In an embodiment, the auxiliary reflective layer **0192** could be disposed between the transparent conductive layer **0160** and the second transparent assembly **0130**. More specifically, the auxiliary reflective layer **0192** is disposed between the reflective layer **0190** and the second transparent assembly **0130**, and is adapted to assist in adjusting an optical penetration reflection.

tion property of the entire vehicle electronic rear-view mirror **0100**. For example, an external light enters the vehicle electronic rear-view mirror **0100** via the first incidence surface **0122**, and the vehicle electronic rear-view mirror **0100** reflects the external light, so that the external light leaves the vehicle electronic rear-view mirror **0100** via the first incidence surface **0122**. In the current structural embodiment, in order to provide the driver an image light with sufficient brightness, a reflectance of the vehicle electronic rear-view mirror **0100** for reflecting the external light could be more than 35%, and a penetration rate of the vehicle electronic rear-view mirror **0100** for the image light could be, for example, greater than 15%. In addition, the auxiliary reflective layer **0192** could also be used as an adhesive layer between the reflective layer **0190** and the second transparent assembly **0130**, which could facilitate the reflective layer **0190** to be attached to the second transparent assembly **0130**. In the current structural embodiment, the auxiliary reflective layer **0192** includes at least one material selected from a group consisting of chromium (Cr), titanium (Ti), and molybdenum (Mo), or an alloy thereof, or could also include other types of materials, thereby to adjust the optical penetration reflection property of the entire vehicle electronic rear-view mirror **0100**. For instance, the material of the auxiliary reflective layer **0192** could be selected from a group consisting of at least one of chromium, titanium, aluminum, molybdenum, and silver, or an alloy thereof, or could include cerium oxide or a transparent conductive material. Moreover, the material of the auxiliary reflective layer **0192** could be indium tin oxide or other metal oxides. However, the material of the auxiliary reflective layer is not limited by the materials as exemplified above.

A movable carrier auxiliary system which is a vehicle electronic rear-view mirror **0100** as an example according to a third structural embodiment of the present invention is illustrated in FIG. 1E. FIG. 1F is a simplified sectional view of FIG. 1E seen from a right shorter lateral side. The difference between the first structural embodiment and the third structural embodiment is that the movable carrier auxiliary system **100** according to the third structural embodiment includes at least one monitor **0200** disposed on a side of the second transparent assembly **0130** away from the first transparent assembly **0120**. For instance, in a structural embodiment, the at least one monitor **0200** is disposed on the second exit surface **0134** of the second transparent assembly **0130** away from the first transparent assembly **0120**. In addition, the monitor **0200** is adapted to emit an image light, wherein the image light passes through the vehicle electronic rear-view mirror **0100** and leaves the vehicle electronic rear-view mirror **0100** via the first incidence surface **0122**. Since the reflective layer **0190** has the optical properties of partial penetration and partial reflection, an image light emitted by the monitor **0200** could pass through the reflective layer **0190**, allowing the user to see an internal image displayed by the monitor **0200**. In the current structural embodiment, a size and an outer contour of the monitor **0200** are approximately the same as the first transparent assembly **0120** (i.e., a full screen). In addition, the monitor **0200** could be a streaming media for providing a driving information or a road condition information to the driver, that is, all visible areas of the vehicle electronic rear-view mirror **0100** according to the current structural embodiment could simultaneously provide the external light from other vehicles behind and the image light from the monitor **0200** to the driver, thereby to achieve a good driving assistance performance. Moreover, the size and the outer contour of the monitor **0200** could be designed to be smaller

than the first transparent assembly **0120** to meet specific requirements, so that only a specific visible area on first transparent assembly **0120** could observe the image light from the monitor **0200**. In the current structural embodiment, the monitor **0200** could be a liquid crystal display (LCD) for example, or could be other types of monitor such as organic light-emitting diode (OLED) monitor. However, the monitor is not a limitation of the present invention.

A movable carrier auxiliary system which is a vehicle electronic rear-view mirror **0100** as an example according to a fourth structural embodiment of the present invention is illustrated in FIG. 1G. FIG. 1H is a simplified sectional view of FIG. 1G seen from a right shorter lateral side. The difference between the third structural embodiment and the fourth structural embodiment is that the movable carrier auxiliary system **100** according to the fourth structural embodiment includes at least one video module disposed on a side of the second transparent assembly **0130** away from the first transparent assembly **0120** and facing a forward direction of the movable carrier for example, and being electrically coupled to the monitor **0200**. When an external image of the movable carrier needs to be captured, at least one control member **0180** could be electrically connected to the video module **0300** through a first signal transmission line **0310** and activated, and then an external image signal of the movable carrier captured by the video module **0300** could be transmitted to the monitor **0200** via a second signal transmission line **0320**, thereby to provide an instant driving information or a real-time traffic information to the driver.

In the current structural embodiment, the monitor **0200** could be a screen with a high dynamic range (HDR), which could show brightness with more obvious light and shade color transition, closer to a real situation seen by the human eye. In order to achieve a condition with a sufficient light compared with the external environment of the movable carrier, the monitor **0200** could be a screen with a brightness exceeding 1000 nits (most preferable), or with a brightness exceeding 4000 nits (second preferable), thereby the driver could clearly observe the driving information or the road condition information presented by the monitor **0200** within the movable carrier.

In the current structural embodiment, there is further a signal input device (not shown) electrically coupled to the displaying device, wherein the signal input device is adapted to send a heterogeneous signal that is not from the optical image capturing system to the display device for numerical or graphical presentation. The signal input device could be a tire pressure detector (TPMS) for example, so that an internal tire pressure of the movable carrier could be detected and instantly converted into a digital signal, wherein the digital signal is transmitted to the display device to be displayed in a numerical or graphical manner, thereby to help the driver to grasp the movable carrier and achieve a warning effect.

In a structural embodiment, the movable carrier auxiliary system includes a plurality of video modules **0300** (not shown), wherein each of the video modules **0300** is disposed on different positions of the movable carrier auxiliary system. For instance, if the movable carrier is a vehicle, the video modules **0300** could be respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle, wherein the external image signal captured by each of the video modules **0300** could be transmitted to the monitor **0200**, and could be instantly and simultaneously presented to the driver for different viewing directions in a non-overlapping manner or in an image butting manner.

In a structural embodiment, the movable carrier auxiliary system further includes at least one movable detector (not shown) and a plurality of video modules (not shown), wherein each of the video modules is disposed on different positions of the movable carrier auxiliary system (not shown). For instance, if the movable carrier is a vehicle, the video modules could be respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle. When the movable carrier is in a state of shutting down the power system and stopping driving, the movable detector starts to continuously detect whether the movable carrier is collided or vibrated. If the movable carrier is bumped or vibrated, the movable detector starts the video modules to instantly record, thereby to help the driver record collision events for on-site restoration and gathers the evidence.

In a structural embodiment, the movable carrier auxiliary system further includes a switch controller and two video modules **0300** (not shown), wherein one of the video modules **0300** is disposed on a front position of the movable carrier, and another one thereof is disposed on a rear position of the movable carrier. When the movable carrier is on a reverse mode, the monitor **0020** could display a rear image of the movable carrier and instantly record the video, thereby assisting the driver to avoid the rear collision event of the movable carrier.

In a structural embodiment, the movable carrier auxiliary system further includes an information communication device (not shown), wherein the information communication device is adapted to communicate with a default contact person or organization, so that when the driver encounters a specific event such as a traffic accident, the driver could notify somebody and seek an assistance through the information communication device to avoid an expansion of personal property damage.

In a structural embodiment, the movable carrier auxiliary system further includes a driving setter and a biological identification device (not shown), wherein the driving setter is electrically connected to the biological identification device. When a specific driver enters the movable carrier and faces the biological identification device, an identification could be performed and the driving setter is started. The driving setter controls the movable carrier according to parameters preset by an individual driver, thereby assisting the driver to quickly complete the corresponding setting of the movable carrier usage habit and effectively control the movable carrier.

Moreover, a maximum diameter of an image-side surface of a lens of the lens group closest to the image plane is denoted by Φ_{iB} , and a maximum effective diameter of the image-side surface of the lens of the lens group L closest to the image plane (i.e., the image space) could be also called optical exit pupil, and is denoted by Φ_{iA} .

In order to keep small in size and provide high imaging quality, the optical image capturing module of the current embodiment satisfies: $0 \text{ mm} < \Phi_{iA} \leq 17.4 \text{ mm}$. Preferably, the optical image capturing module of the current embodiment satisfies: $0 \text{ mm} < \Phi_{iA} \leq 13.5 \text{ mm}$.

Furthermore, the optical embodiments will be described in detail as follow. The optical image capturing module could work in three wavelengths, including 486.1 nm, 587.5 nm, and 656.2 nm, wherein 587.5 nm is the main reference wavelength and is the reference wavelength for obtaining the technical characters. The optical image capturing module could also work in five wavelengths, including 470 nm, 510 nm, 555 nm, 610 nm, and 650 nm wherein 555 nm is the

main reference wavelength, and is the reference wavelength for obtaining the technical characters.

The optical image capturing module of the present invention satisfies $0.5 \leq \Sigma PPR / |\Sigma NPR| \leq 15$, and a preferable range is $1 \leq \Sigma PPR / |\Sigma NPR| \leq 3.0$, where PPR is a ratio of the focal length f of the optical image capturing module to a focal length f_p of each of lenses with positive refractive power; NPR is a ratio of the focal length f of the optical image capturing module to a focal length f_n of each of lenses with negative refractive power; ΣPPR is a sum of the PPRs of each positive lens; and ΣNPR is a sum of the NPRs of each negative lens. It is helpful for control of an entire refractive power and an entire length of the optical image capturing module.

The optical image capturing module further includes an image sensor provided on the image plane. The optical image capturing module of the present invention satisfies $HOS/HOI \leq 50$ and $0.5 \leq HOS/f \leq 150$, and a preferable range is $1 \leq HOS/HOI \leq 40$ and $1 \leq HOS/f \leq 140$, where HOI is a half of a diagonal of an effective sensing area of the image sensor, i.e., the maximum image height, and HOS is a height of the optical image capturing module, i.e. a distance on the optical axis between the object-side surface of the first lens and the image plane. It is helpful for reduction of the size of the optical image capturing module for use in compact cameras.

The optical image capturing module of the present invention is further provided with an aperture to increase image quality.

In the optical image capturing module of the present invention, the aperture could be a front aperture or a middle aperture, wherein the front aperture is provided between the object and the first lens, and the middle is provided between the first lens and the image plane. The front aperture provides a long distance between an exit pupil of the optical image capturing module and the image plane, which allows more elements to be installed. The middle could enlarge a view angle of view of the optical image capturing module and increase the efficiency of the image sensor. The optical image capturing module satisfies $0.1 \leq InS/HOS \leq 1.1$, where InS is a distance between the aperture and the image surface. It is helpful for size reduction and wide angle.

The optical image capturing module of the present invention satisfies $0.1 \leq \Sigma TP / InTL \leq 0.9$, where $InTL$ is a distance between the object-side surface of the first lens and the image-side surface of the sixth lens, and ΣTP is a sum of central thicknesses of the lenses on the optical axis. It is helpful for the contrast of image and yield rate of manufacture and provides a suitable back focal length for installation of other elements.

The optical image capturing module of the present invention satisfies $0.001 \leq |R1/R2| \leq 25$, and a preferable range is $0.01 \leq |R1/R2| \leq 12$, where $R1$ is a radius of curvature of the object-side surface of the first lens, and $R2$ is a radius of curvature of the image-side surface of the first lens. It provides the first lens with a suitable positive refractive power to reduce the increase rate of the spherical aberration.

The optical image capturing module of the present invention satisfies $-7 < (R11 - R12) / (R11 + R12) < 50$, where $R11$ is a radius of curvature of the object-side surface of the sixth lens, and $R12$ is a radius of curvature of the image-side surface of the sixth lens. It may modify the astigmatic field curvature.

The optical image capturing module of the present invention satisfies $IN12/f \leq 60$, where $IN12$ is a distance on the optical axis between the first lens and the second lens. It may correct chromatic aberration and improve the performance.

The optical image capturing module of the present invention satisfies $IN56/f \leq 3.0$, where IN56 is a distance on the optical axis between the fifth lens and the sixth lens. It may correct chromatic aberration and improve the performance.

The optical image capturing module of the present invention satisfies $0.1 \leq (TP1+IN12)/TP2 \leq 10$, where TP1 is a central thickness of the first lens on the optical axis, and TP2 is a central thickness of the second lens on the optical axis. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

The optical image capturing module of the present invention satisfies $0.1 \leq (TP6+IN56)/TP5 \leq 15$, where TP5 is a central thickness of the fifth lens on the optical axis, TP6 is a central thickness of the sixth lens on the optical axis, and IN56 is a distance between the fifth lens and the sixth lens. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

The optical image capturing module of the present invention satisfies $0.1 \leq TP4/(IN34+TP4+IN45) < 1$, where TP2 is a central thickness of the second lens on the optical axis, TP3 is a central thickness of the third lens on the optical axis, TP4 is a central thickness of the fourth lens on the optical axis, IN34 is a distance on the optical axis between the third lens and the fourth lens, IN45 is a distance on the optical axis between the fourth lens and the fifth lens, and InTL is a distance between the object-side surface of the first lens and the image-side surface of the seventh lens. It may fine tune and correct the aberration of the incident rays layer by layer, and reduce the height of the optical image capturing module.

The optical image capturing module satisfies $0 \text{ mm} \leq HVT61 \leq 3 \text{ mm}$; $0 \text{ mm} < HVT62 \leq 6 \text{ mm}$; $0 \leq HVT61/HVT62$; $0 \text{ mm} \leq SGC61 \leq 0.5 \text{ mm}$; $0 \text{ mm} < SGC62 \leq 2 \text{ mm}$; and $0 < |SGC62|/(|SGC62|+TP6) \leq 0.9$, where HVT61 a distance perpendicular to the optical axis between the critical point C61 on the object-side surface of the sixth lens and the optical axis; HVT62 a distance perpendicular to the optical axis between the critical point C62 on the image-side surface of the sixth lens and the optical axis; SGC61 is a distance on the optical axis between a point on the object-side surface of the sixth lens where the optical axis passes through and a point where the critical point C61 projects on the optical axis; SGC62 is a distance on the optical axis between a point on the image-side surface of the sixth lens where the optical axis passes through and a point where the critical point C62 projects on the optical axis. It is helpful to correct the off-axis view field aberration.

The optical image capturing module satisfies $0.2 \leq HVT62/HOI \leq 0.9$, and preferably satisfies $0.3 \leq HVT62/HOI \leq 0.8$. It may help to correct the peripheral aberration.

The optical image capturing module satisfies $0 \leq HVT62/HOS \leq 0.5$, and preferably satisfies $0.2 \leq HVT62/HOS \leq 0.45$. It may help to correct the peripheral aberration.

The optical image capturing module of the present invention satisfies $0 < SGI611/(SGI611+TP6) \leq 0.9$; $0 < SGI621/(SGI621+TP6) \leq 0.9$, and it is preferable to satisfy $0.1 \leq SGI611/(SGI611+TP6) \leq 0.6$; $0.1 \leq SGI621/(SGI621+TP7) \leq 0.6$, where SGI611 is a displacement on the optical axis from a point on the object-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the closest to the optical axis, projects on the optical axis, and SGI621 is a displacement on the optical axis from a point on the image-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the image-side surface, which is the closest to the optical axis, projects on the optical axis.

The optical image capturing module of the present invention satisfies $0 < SGI612/(SGI612+TP6) \leq 0.9$; $0 < SGI622/(SGI622+TP6) \leq 0.9$, and it is preferable to satisfy $0.1 \leq SGI612/(SGI612+TP6) \leq 0.6$; $0.1 \leq SGI622/(SGI622+TP6) \leq 0.6$, where SGI612 is a displacement on the optical axis from a point on the object-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the second closest to the optical axis, projects on the optical axis, and SGI622 is a displacement on the optical axis from a point on the image-side surface of the sixth lens, through which the optical axis passes, to a point where the inflection point on the object-side surface, which is the second closest to the optical axis, projects on the optical axis.

The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF611| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF621| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF611| \leq 3.5 \text{ mm}$; $1.5 \text{ mm} \leq |HIF621| \leq 3.5 \text{ mm}$, where HIF611 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the closest to the optical axis, and the optical axis; HIF621 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the closest to the optical axis, and the optical axis.

The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF612| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF622| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF622| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF612| \leq 3.5 \text{ mm}$, where HIF612 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the second closest to the optical axis, and the optical axis; HIF622 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the second closest to the optical axis, and the optical axis.

The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF613| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF623| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF623| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF613| \leq 3.5 \text{ mm}$, where HIF613 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the third closest to the optical axis, and the optical axis; HIF623 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the third closest to the optical axis, and the optical axis.

The optical image capturing module of the present invention satisfies $0.001 \text{ mm} \leq |HIF614| \leq 5 \text{ mm}$; $0.001 \text{ mm} \leq |HIF624| \leq 5 \text{ mm}$, and it is preferable to satisfy $0.1 \text{ mm} \leq |HIF624| \leq 3.5 \text{ mm}$; $0.1 \text{ mm} \leq |HIF614| \leq 3.5 \text{ mm}$, where HIF614 is a distance perpendicular to the optical axis between the inflection point on the object-side surface of the sixth lens, which is the fourth closest to the optical axis, and the optical axis; HIF624 is a distance perpendicular to the optical axis between the inflection point on the image-side surface of the sixth lens, which is the fourth closest to the optical axis, and the optical axis.

In an embodiment, the lenses of high Abbe number and the lenses of low Abbe number are arranged in an interlaced arrangement that could be helpful for correction of aberration of the optical image capturing module.

An equation of aspheric surface is

$$z = ch^2/[1 + \{1 + (k+1)c^2h^2\}^{0.5}] + A4h^4 + A6h^6 + A8h^8 + A10h^{10} + A12h^{12} + A14h^{14} + A16h^{16} + A18h^{18} + A20h^{20} + \quad (1)$$

where z is a depression of the aspheric surface; k is conic constant; c is reciprocal of the radius of curvature; and $A4$, $A6$, $A8$, $A10$, $A12$, $A16$, $A18$, and $A20$ are high-order aspheric coefficients.

In the optical image capturing module, the lenses could be made of plastic or glass. The plastic lenses may reduce the weight and lower the cost of the optical image capturing module, and the glass lenses may control the thermal effect and enlarge the space for arrangement of the refractive power of the optical image capturing module. In addition, the opposite surfaces (object-side surface and image-side surface) of the first to the seventh lenses could be aspheric that could obtain more control parameters to reduce aberration. The number of aspheric glass lenses could be less than the conventional spherical glass lenses, which is helpful for reduction of the height of the optical image capturing module.

When the lens has a convex surface, which means that the surface is convex around a position, through which the optical axis passes, and when the lens has a concave surface, which means that the surface is concave around a position, through which the optical axis passes.

The optical image capturing module of the present invention could be applied in a dynamic focusing optical image capturing module. It is superior in the correction of aberration and high imaging quality so that it could be allied in lots of fields.

The optical image capturing module of the present invention could further include a driving module to meet different demands, wherein the driving module could be coupled with the lenses to move the lenses. The driving module could be a voice coil motor (VCM), which is used to move the lens for focusing, or could be an optical image stabilization (OIS) component, which is used to lower the possibility of having the problem of image blurring which is caused by subtle movements of the lens while shooting.

To meet different requirements, at least one lens among the first lens to the seventh lens of the optical image capturing module of the present invention could be a light filter, which filters out light of wavelength shorter than 500 nm. Such effect could be achieved by coating on at least one surface of the lens, or by using materials capable of filtering out short waves to make the lens.

To meet different requirements, the image plane of the optical image capturing module in the present invention could be either flat or curved. If the image plane is curved (e.g., a sphere with a radius of curvature), the incidence angle required for focusing light on the image plane could be decreased, which is not only helpful to shorten the length of the optical image capturing module (TTL), but also helpful to increase the relative illuminance.

We provide several optical embodiments in conjunction with the accompanying drawings for the best understanding. In practice, the optical embodiments of the present invention could be applied to other structural embodiments.

First Optical Embodiment

As shown in FIG. 2A and FIG. 2B, wherein a lens group of an optical image capturing module **10** of a first optical embodiment of the present invention is illustrated in FIG. 2A, and FIG. 2B shows curve diagrams of longitudinal spherical aberration, astigmatic field, and optical distortion of the optical image capturing module in the order from left to right of the first optical embodiment. The optical image capturing module **10** of the first optical embodiment includes, along an optical axis from an object side to an

image side, a first lens **110**, an aperture **100**, a second lens **120**, a third lens **130**, a fourth lens **140**, a fifth lens **150**, a sixth lens **160**, an infrared rays filter **180**, an image plane **190**, and an image sensor **192**.

The first lens **110** has negative refractive power and is made of plastic. An object-side surface **112** thereof, which faces the object side, is a concave aspheric surface, and an image-side surface **114** thereof, which faces the image side, is a concave aspheric surface. The object-side surface **112** has two inflection points. A profile curve length of the maximum effective half diameter of the object-side surface **112** of the first lens **110** is denoted by ARS11, and a profile curve length of the maximum effective half diameter of the image-side surface **114** of the first lens **110** is denoted by ARS12. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **112** of the first lens **110** is denoted by ARE11, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **114** of the first lens **110** is denoted by ARE12. A thickness of the first lens **110** on the optical axis is denoted by TP1.

The first lens satisfies $SGI111 = -0.0031$ mm; $|SGI111| / (|SGI111| + TP1) = 0.0016$, where a displacement on the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the object-side surface **112**, which is the closest to the optical axis, projects on the optical axis, is denoted by SGI111, and a displacement on the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the image-side surface **114**, which is the closest to the optical axis, projects on the optical axis is denoted by SGI121.

The first lens **110** satisfies $SGI112 = 1.3178$ mm; $|SGI112| / (|SGI112| + TP1) = 0.4052$, where a displacement on the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the object-side surface **112**, which is the second closest to the optical axis, projects on the optical axis, is denoted by SGI112, and a displacement on the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to a point where the inflection point on the image-side surface **114**, which is the second closest to the optical axis, projects on the optical axis is denoted by SGI122.

The first lens **110** satisfies $HIF111 = 0.5557$ mm; $HIF111 / HOI = 0.1111$, where a displacement perpendicular to the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF111, and a displacement perpendicular to the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF121.

The first lens **110** satisfies $HIF112 = 5.3732$ mm; $HIF112 / HOI = 1.0746$, where a displacement perpendicular to the optical axis from a point on the object-side surface **112** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the second closest to the optical axis is denoted by HIF112, and a displacement perpendicular to the optical axis from a point on the image-side surface **114** of the first lens **110**, through which the optical axis passes, to the inflection point, which is the second closest to the optical axis is denoted by HIF122.

The second lens 120 has positive refractive power and is made of plastic. An object-side surface 122 thereof, which faces the object side, is a convex aspheric surface, and an image-side surface 124 thereof, which faces the image side, is a convex aspheric surface. The object-side surface 122 has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface 122 of the second lens 120 is denoted by ARS21, and a profile curve length of the maximum effective half diameter of the image-side surface 124 of the second lens 120 is denoted by ARS22. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface 122 of the second lens 120 is denoted by ARE21, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface 124 of the second lens 120 is denoted by ARS22. A thickness of the second lens 120 on the optical axis is denoted by TP2.

The second lens 120 satisfies $SGI211=0.1069$ mm; $|SGI211|/(|SGI211|+TP2)=0.0412$; $SGI221=0$ mm; $|SGI221|/(|SGI221|+TP2)=0$, where a displacement on the optical axis from a point on the object-side surface 122 of the second lens 120, through which the optical axis passes, to a point where the inflection point on the object-side surface 122, which is the closest to the optical axis, projects on the optical axis, is denoted by SGI211, and a displacement on the optical axis from a point on the image-side surface 124 of the second lens 120, through which the optical axis passes, to a point where the inflection point on the image-side surface 124, which is the closest to the optical axis, projects on the optical axis is denoted by SGI221.

The second lens 120 satisfies $HIF211=1.1264$ mm; $HIF211/HOI=0.2253$; $HIF221=0$ mm; $HIF221/HOI=0$, where a displacement perpendicular to the optical axis from a point on the object-side surface 122 of the second lens 120, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF211, and a displacement perpendicular to the optical axis from a point on the image-side surface 124 of the second lens 120, through which the optical axis passes, to the inflection point, which is the closest to the optical axis is denoted by HIF221.

The third lens 130 has negative refractive power and is made of plastic. An object-side surface 132, which faces the object side, is a concave aspheric surface, and an image-side surface 134, which faces the image side, is a convex aspheric surface. The object-side surface 132 has an inflection point, and the image-side surface 134 has an inflection point. The object-side surface 122 has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface 132 of the third lens 130 is denoted by ARS31, and a profile curve length of the maximum effective half diameter of the image-side surface 134 of the third lens 130 is denoted by ARS32. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface 132 of the third lens 130 is denoted by ARE31, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface 134 of the third lens 130 is denoted by ARS32. A thickness of the third lens 130 on the optical axis is denoted by TP3.

The third lens 130 satisfies $SGI311=-0.3041$ mm; $|SGI311|/(|SGI311|+TP3)=0.4445$; $SGI321=-0.1172$ mm; $|SGI321|/(|SGI321|+TP3)=0.2357$, where SGI311 is a displacement on the optical axis from a point on the object-side surface 132 of the third lens 130, through which the optical axis passes, to a point where the inflection point on the object-side surface 132, which is the closest to the optical axis, projects on the optical axis, and SGI321 is a displacement

on the optical axis from a point on the image-side surface 134 of the third lens 130, through which the optical axis passes, to a point where the inflection point on the image-side surface 134, which is the closest to the optical axis, projects on the optical axis.

The third lens 130 satisfies $HIF311=1.5907$ mm; $HIF311/HOI=0.3181$; $HIF321=1.3380$ mm; $HIF321/HOI=0.2676$, where HIF311 is a distance perpendicular to the optical axis between the inflection point on the object-side surface 132 of the third lens 130, which is the closest to the optical axis, and the optical axis; HIF321 is a distance perpendicular to the optical axis between the inflection point on the image-side surface 134 of the third lens 130, which is the closest to the optical axis, and the optical axis.

The fourth lens 140 has positive refractive power and is made of plastic. An object-side surface 142, which faces the object side, is a convex aspheric surface, and an image-side surface 144, which faces the image side, is a concave aspheric surface. The object-side surface 142 has two inflection points, and the image-side surface 144 has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface 142 of the fourth lens 140 is denoted by ARS41, and a profile curve length of the maximum effective half diameter of the image-side surface 144 of the fourth lens 140 is denoted by ARS42. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface 142 of the fourth lens 140 is denoted by ARE41, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface 144 of the fourth lens 140 is denoted by ARE42. A thickness of the fourth lens 140 on the optical axis is TP4.

The fourth lens 140 satisfies $SGI411=0.0070$ mm; $|SGI411|/(|SGI411|+TP4)=0.0056$; $SGI421=0.0006$ mm; $|SGI421|/(|SGI421|+TP4)=0.0005$, where SGI411 is a displacement on the optical axis from a point on the object-side surface 142 of the fourth lens 140, through which the optical axis passes, to a point where the inflection point on the object-side surface 142, which is the closest to the optical axis, projects on the optical axis, and SGI421 is a displacement on the optical axis from a point on the image-side surface 144 of the fourth lens 140, through which the optical axis passes, to a point where the inflection point on the image-side surface 144, which is the closest to the optical axis, projects on the optical axis.

The fourth lens 140 satisfies $SGI412=-0.2078$ mm; $|SGI412|/(|SGI412|+TP4)=0.1439$, where SGI412 is a displacement on the optical axis from a point on the object-side surface 142 of the fourth lens 140, through which the optical axis passes, to a point where the inflection point on the object-side surface 142, which is the second closest to the optical axis, projects on the optical axis, and SGI422 is a displacement on the optical axis from a point on the image-side surface 144 of the fourth lens 140, through which the optical axis passes, to a point where the inflection point on the image-side surface 144, which is the second closest to the optical axis, projects on the optical axis.

The fourth lens 140 further satisfies $HIF411=0.4706$ mm; $HIF411/HOI=0.0941$; $HIF421=0.1721$ mm; $HIF421/HOI=0.0344$, where HIF411 is a distance perpendicular to the optical axis between the inflection point on the object-side surface 142 of the fourth lens 140, which is the closest to the optical axis, and the optical axis; HIF421 is a distance perpendicular to the optical axis between the inflection point on the image-side surface 144 of the fourth lens 140, which is the closest to the optical axis, and the optical axis.

The fourth lens 140 satisfies $HIF412=2.0421$ mm; $HIF412/HOI=0.4084$, where HIF412 is a distance perpen-

dicular to the optical axis between the inflection point on the object-side surface **142** of the fourth lens **140**, which is the second closest to the optical axis, and the optical axis; HIF422 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **144** of the fourth lens **140**, which is the second closest to the optical axis, and the optical axis.

The fifth lens **150** has positive refractive power and is made of plastic. An object-side surface **152**, which faces the object side, is a convex aspheric surface, and an image-side surface **154**, which faces the image side, is a convex aspheric surface. The object-side surface **152** has two inflection points, and the image-side surface **154** has an inflection point. A profile curve length of the maximum effective half diameter of the object-side surface **152** of the fifth lens **150** is denoted by ARS51, and a profile curve length of the maximum effective half diameter of the image-side surface **154** of the fifth lens **150** is denoted by ARS52. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **152** of the fifth lens **150** is denoted by ARE51, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **154** of the fifth lens **150** is denoted by ARE52. A thickness of the fifth lens **150** on the optical axis is denoted by TP5.

The fifth lens **150** satisfies $SGI511=0.00364$ mm; $SGI521=-0.63365$ mm; $|SGI511|/(|SGI511|+TP5)=0.00338$; $|SGI521|/(|SGI521|+TP5)=0.37154$, where SGI511 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the closest to the optical axis, projects on the optical axis, and SGI521 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the closest to the optical axis, projects on the optical axis.

The fifth lens **150** satisfies $SGI512=-0.32032$ mm; $|SGI512|/(|SGI512|+TP5)=0.23009$, where SGI512 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the second closest to the optical axis, projects on the optical axis, and SGI522 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the second closest to the optical axis, projects on the optical axis.

The fifth lens **150** satisfies $SGI513=0$ mm; $SGI523=0$ mm; $|SGI513|/(|SGI513|+TP5)=0$; $|SGI523|/(|SGI523|+TP5)=0$, where SGI513 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is the third closest to the optical axis, projects on the optical axis, and SGI523 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the third closest to the optical axis, projects on the optical axis.

The fifth lens **150** satisfies $SGI514=0$ mm; $SGI524=0$ mm; $|SGI514|/(|SGI514|+TP5)=0$; $|SGI524|/(|SGI524|+TP5)=0$, where SGI514 is a displacement on the optical axis from a point on the object-side surface **152** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the object-side surface **152**, which is

the fourth closest to the optical axis, projects on the optical axis, and SGI524 is a displacement on the optical axis from a point on the image-side surface **154** of the fifth lens **150**, through which the optical axis passes, to a point where the inflection point on the image-side surface **154**, which is the fourth closest to the optical axis, projects on the optical axis.

The fifth lens **150** further satisfies $HIF511=0.28212$ mm; $HIF521=2.13850$ mm; $HIF511/HOI=0.05642$; $HIF521/HOI=0.42770$, where HIF511 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the closest to the optical axis, and the optical axis; HIF521 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the closest to the optical axis, and the optical axis.

The fifth lens **150** further satisfies $HIF512=2.51384$ mm; $HIF512/HOI=0.50277$, where HIF512 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the second closest to the optical axis, and the optical axis; HIF522 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the second closest to the optical axis, and the optical axis.

The fifth lens **150** further satisfies $HIF513=0$ mm; $HIF513/HOI=0$; $HIF523=0$ mm; $HIF523/HOI=0$, where HIF513 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the third closest to the optical axis, and the optical axis; HIF523 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the third closest to the optical axis, and the optical axis.

The fifth lens **150** further satisfies $HIF514=0$ mm; $HIF514/HOI=0$; $HIF524=0$ mm; $HIF524/HOI=0$, where HIF514 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **152** of the fifth lens **150**, which is the fourth closest to the optical axis, and the optical axis; HIF524 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **154** of the fifth lens **150**, which is the fourth closest to the optical axis, and the optical axis.

The sixth lens **160** has negative refractive power and is made of plastic. An object-side surface **162**, which faces the object side, is a concave surface, and an image-side surface **164**, which faces the image side, is a concave surface. The object-side surface **162** has two inflection points, and the image-side surface **164** has an inflection point. Whereby, the incident angle of each view field entering the sixth lens **160** could be effectively adjusted to improve aberration. A profile curve length of the maximum effective half diameter of the object-side surface **162** of the sixth lens **160** is denoted by ARS61, and a profile curve length of the maximum effective half diameter of the image-side surface **164** of the sixth lens **160** is denoted by ARS62. A profile curve length of a half of the entrance pupil diameter (HEP) of the object-side surface **162** of the sixth lens **160** is denoted by ARE61, and a profile curve length of a half of the entrance pupil diameter (HEP) of the image-side surface **164** of the sixth lens **160** is denoted by ARS62. A thickness of the sixth lens **160** on the optical axis is denoted by TP6.

The sixth lens **160** satisfies $SGI611=-0.38558$ mm; $SGI621=0.12386$ mm; $|SGI611|/(|SGI611|+TP6)=0.27212$; $|SGI621|/(|SGI621|+TP6)=0.10722$, where SGI611 is a displacement on the optical axis from a point on the object-side surface **162** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the

object-side surface **162**, which is the closest to the optical axis, projects on the optical axis, and SGI621 is a displacement on the optical axis from a point on the image-side surface **164** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the image-side surface **164**, which is the closest to the optical axis, projects on the optical axis.

The sixth lens **160** satisfies $SGI612 = -0.47400$ mm; $|SGI612|/(|SGI612|+TP6) = 0.31488$; $SGI622 = 0$ mm; $|SGI622|/(|SGI622|+TP6) = 0$, where SGI612 is a displacement on the optical axis from a point on the object-side surface **162** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the object-side surface **162**, which is the second closest to the optical axis, projects on the optical axis, and SGI622 is a displacement on the optical axis from a point on the image-side surface **164** of the sixth lens **160**, through which the optical axis passes, to a point where the inflection point on the image-side surface **164**, which is the second closest to the optical axis, projects on the optical axis.

The sixth lens **160** further satisfies $HIF611 = 2.24283$ mm; $HIF621 = 1.07376$ mm; $HIF611/HOI = 0.44857$; $HIF621/HOI = 0.21475$, where HIF611 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the closest to the optical axis, and the optical axis; HIF621 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the closest to the optical axis, and the optical axis.

The sixth lens **160** further satisfies $HIF612 = 2.48895$ mm; $HIF612/HOI = 0.49779$, where HIF612 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the second closest to the optical axis, and the optical axis; HIF622 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the second closest to the optical axis, and the optical axis.

The sixth lens **160** further satisfies $HIF613 = 0$ mm; $HIF613/HOI = 0$; $HIF623 = 0$ mm; $HIF623/HOI = 0$, where HIF613 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the third closest to the optical axis, and the optical axis; HIF623 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the third closest to the optical axis, and the optical axis.

The sixth lens **160** further satisfies $HIF614 = 0$ mm; $HIF614/HOI = 0$; $HIF624 = 0$ mm; $HIF624/HOI = 0$, where HIF614 is a distance perpendicular to the optical axis between the inflection point on the object-side surface **162** of the sixth lens **160**, which is the fourth closest to the optical axis, and the optical axis; HIF624 is a distance perpendicular to the optical axis between the inflection point on the image-side surface **164** of the sixth lens **160**, which is the fourth closest to the optical axis, and the optical axis.

The infrared rays filter **180** is made of glass and is disposed between the sixth lens **160** and the image plane **190**. The infrared rays filter **180** gives no contribution to the focal length of the optical image capturing module.

The optical image capturing module **10** of the first optical embodiment has the following parameters, which are $f = 4.075$ mm; $f/HEP = 1.4$; $HAF = 50.001$ degrees; and $\tan(HAF) = 1.1918$, where f is a focal length of the lens group; HAF is a half of the maximum field angle; and HEP is an entrance pupil diameter.

The parameters of the lenses of the first optical embodiment are $f1 = -7.828$ mm; $|f/f1| = 0.52060$; $f6 = -4.886$; and $|f1| > f6$, where $f1$ is a focal length of the first lens **110**; and $f6$ is a focal length of the sixth lens **160**.

The first optical embodiment further satisfies $|f2| + |f3| + |f4| + |f5| = 95.50815$; $|f1| + |f6| = 12.71352$ and $|f2| - |f3| + |f4| + |f5| > |f1| + |f6|$, where $f2$ is a focal length of the second lens **120**, $f3$ is a focal length of the third lens **130**, $f4$ is a focal length of the fourth lens **140**, $f5$ is a focal length of the fifth lens **150**.

The optical image capturing module **10** of the first optical embodiment further satisfies $\Sigma PPR = f/f2 + f/f4 + f/f5 = 1.63290$; $\Sigma NPR = |f/f1| + |f/f3| + |f/f6| = 1.51305$; $\Sigma PPR / |\Sigma NPR| = 1.07921$; $|f/f2| = 0.69101$; $|f/f3| = 0.15834$; $|f/f4| = 0.06883$; $|f/f5| = 0.87305$; and $|f/f6| = 0.83412$, where PPR is a ratio of a focal length f of the optical image capturing module to a focal length f_p of each of the lenses with positive refractive power; and NPR is a ratio of a focal length f of the optical image capturing module to a focal length f_n of each of lenses with negative refractive power.

The optical image capturing module **10** of the first optical embodiment further satisfies $InTL + BFL = HOS$; $HOS = 19.54120$ mm; $HOI = 5.0$ mm; $HOS/HOI = 3.90824$; $HOS/f = 4.7952$; $InS = 11.685$ mm; $InTL/HOS = 0.9171$; and $InS/HOS = 0.59794$, where $InTL$ is a distance between the object-side surface **112** of the first lens **110** and the image-side surface **164** of the sixth lens **160**; HOS is a height of the image capturing system, i.e. a distance between the object-side surface **112** of the first lens **110** and the image plane **190**; InS is a distance between the aperture **100** and the image plane **190**; HOI is a half of a diagonal of an effective sensing area of the image sensor **192**, i.e., the maximum image height; and BFL is a distance between the image-side surface **164** of the sixth lens **160** and the image plane **190**.

The optical image capturing module **10** of the first optical embodiment further satisfies $\Sigma TP = 8.13899$ mm; and $\Sigma TP / InTL = 0.52477$, where ΣTP is a sum of the thicknesses of the lenses **110-160** with refractive power. It is helpful for the contrast of image and yield rate of manufacture and provides a suitable back focal length for installation of other elements.

The optical image capturing module **10** of the first optical embodiment further satisfies $|R1/R2| = 8.99987$, where $R1$ is a radius of curvature of the object-side surface **112** of the first lens **110**, and $R2$ is a radius of curvature of the image-side surface **114** of the first lens **110**. It provides the first lens **110** with a suitable positive refractive power to reduce the increase rate of the spherical aberration.

The optical image capturing module **10** of the first optical embodiment further satisfies $(R11 - R12)/(R11 + R12) = 1.27780$, where $R11$ is a radius of curvature of the object-side surface **162** of the sixth lens **160**, and $R12$ is a radius of curvature of the image-side surface **164** of the sixth lens **160**. It may modify the astigmatic field curvature.

The optical image capturing module **10** of the first optical embodiment further satisfies $\Sigma PP = f2 + f4 + f5 = 69.770$ mm; and $f5/(f2 + f4 + f5) = 0.067$, where ΣPP is a sum of the focal lengths f_p of each lens with positive refractive power. It is helpful to share the positive refractive power of a single lens to other positive lenses to avoid the significant aberration caused by the incident rays.

The optical image capturing module **10** of the first optical embodiment further satisfies $\Sigma NP = f1 + f3 + f6 = -38.451$ mm; and $f6/(f1 + f3 + f6) = 0.127$, where ΣNP is a sum of the focal lengths f_n of each lens with negative refractive power. It is helpful to share the negative refractive power of the sixth

lens 160 to the other negative lens, which avoids the significant aberration caused by the incident rays.

The optical image capturing module 10 of the first optical embodiment further satisfies $IN12=6.418$ mm; $IN12/f=1.57491$, where $IN12$ is a distance on the optical axis between the first lens 110 and the second lens 120. It may correct chromatic aberration and improve the performance.

The optical image capturing module 10 of the first optical embodiment further satisfies $IN56=0.025$ mm; $IN56/f=0.00613$, where $IN56$ is a distance on the optical axis between the fifth lens 150 and the sixth lens 160. It may correct chromatic aberration and improve the performance.

The optical image capturing module 10 of the first optical embodiment further satisfies $TP1=1.934$ mm; $TP2=2.486$ mm; and $(TP1+IN12)/TP2=3.36005$, where $TP1$ is a central thickness of the first lens 110 on the optical axis, and $TP2$ is a central thickness of the second lens 120 on the optical axis. It may control the sensitivity of manufacture of the optical image capturing module and improve the performance.

The optical image capturing module 10 of the first optical embodiment further satisfies $TP5=1.072$ mm; $TP6=1.031$ mm; and $(TP6+IN56)/TP5=0.98555$, where $TP5$ is a central thickness of the fifth lens 150 on the optical axis, $TP6$ is a central thickness of the sixth lens 160 on the optical axis, and $IN56$ is a distance on the optical axis between the fifth lens 150 and the sixth lens 160. It may control the sensitivity of manufacture of the optical image capturing module and lower the total height of the optical image capturing module.

The optical image capturing module 10 of the first optical embodiment further satisfies $IN34=0.401$ mm; $IN45=0.025$ mm; and $TP4/(IN34+TP4+IN45)=0.74376$, where $TP4$ is a central thickness of the fourth lens 140 on the optical axis; $IN34$ is a distance on the optical axis between the third lens 130 and the fourth lens 140; $IN45$ is a distance on the optical axis between the fourth lens 140 and the fifth lens 150. It may help to slightly correct the aberration caused by the incident rays and lower the total height of the optical image capturing module.

The optical image capturing module 10 of the first optical embodiment further satisfies $InRS51=-0.34789$ mm; $InRS52=-0.88185$ mm; $|InRS51|/TP5=0.32458$; and $|InRS52|/TP5=0.82276$, where $InRS51$ is a displacement from a point on the object-side surface 152 of the fifth lens 150 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the object-side surface 152 of the fifth lens 150 ends; $InRS52$ is a displacement from a point on the image-side surface 154 of the fifth lens 150 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the image-side surface 154 of the fifth lens 150 ends; and $TP5$ is a central thickness of the fifth lens 150 on the optical axis. It is helpful for manufacturing and shaping of the lenses and is helpful to reduce the size.

The optical image capturing module 10 of the first optical embodiment further satisfies $HVT51=0.515349$ mm; and

$HVT52=0$ mm, where $HVT51$ is a distance perpendicular to the optical axis between the critical point on the object-side surface 152 of the fifth lens 150 and the optical axis; and $HVT52$ is a distance perpendicular to the optical axis between the critical point on the image-side surface 154 of the fifth lens 150 and the optical axis.

The optical image capturing module 10 of the first optical embodiment further satisfies $InRS61=-0.58390$ mm; $InRS62=0.41976$ mm; $|InRS61|/TP6=0.56616$; and $|InRS62|/TP6=0.40700$, where $InRS61$ is a displacement from a point on the object-side surface 162 of the sixth lens 160 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the object-side surface 162 of the sixth lens 160 ends; $InRS62$ is a displacement from a point on the image-side surface 164 of the sixth lens 160 passed through by the optical axis to a point on the optical axis where a projection of the maximum effective semi diameter of the image-side surface 164 of the sixth lens 160 ends; and $TP6$ is a central thickness of the sixth lens 160 on the optical axis. It is helpful for manufacturing and shaping of the lenses and is helpful to reduce the size.

The optical image capturing module 10 of the first optical embodiment satisfies $HVT61=0$ mm; and $HVT62=0$ mm, where $HVT61$ is a distance perpendicular to the optical axis between the critical point on the object-side surface 162 of the sixth lens 160 and the optical axis; and $HVT62$ is a distance perpendicular to the optical axis between the critical point on the image-side surface 164 of the sixth lens 160 and the optical axis.

The optical image capturing module 10 of the first optical embodiment satisfies $HVT51/HOI=0.1031$. It is helpful for correction of the aberration of the peripheral view field of the optical image capturing module.

The optical image capturing module 10 of the first optical embodiment satisfies $HVT51/HOS=0.02634$. It is helpful for correction of the aberration of the peripheral view field of the optical image capturing module.

The second lens 120, the third lens 130, and the sixth lens 160 have negative refractive power. The optical image capturing module 10 of the first optical embodiment further satisfies $NA6/NA2 \leq 1$, where $NA2$ is an Abbe number of the second lens 120; $NA3$ is an Abbe number of the third lens 130; and $NA6$ is an Abbe number of the sixth lens 160. It may correct the aberration of the optical image capturing module.

The optical image capturing module 10 of the first optical embodiment further satisfies $|TDT|=2.124\%$; $|ODT|=5.076\%$, where TDT is TV distortion; and ODT is optical distortion.

The optical image capturing module 10 of the first optical embodiment further satisfies $LS=12$ mm; $\Phi A=2*(EHD62)=6.726$ mm, where $EHD62$ is a maximum effective half diameter of the image-side surface 164 of the sixth lens 160.

The parameters of the lenses of the first optical embodiment are listed in Table 1 and Table 2.

TABLE 1

f = 4.075 mm; f/HEP = 1.4, HAF = 50.000 deg							
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)	
0	Object plane	plane					
1	1 st lens	-40.99625704	plastic	1.515	56.55		-7.828
2		4.555209289					

TABLE 1-continued

f = 4.075 mm; f/HEP = 1.4, HAF = 50.000 deg						
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
3	Aperture plane	0.495				
4	2 nd lens	5.333427366	plastic	1.544	55.96	5.897
5		-6.781659971				
6	3 rd lens	-5.697794287	plastic	1.642	22.46	-25.738
7		-8.883957518				
8	4 th lens	13.19225664	plastic	1.544	55.96	59.205
9		21.55681832				
10	5 th lens	8.987806345	plastic	1.515	56.55	4.668
11		-3.158875374				
12	6 th lens	-29.46491425	plastic	1.642	22.46	-4.886
13		3.593484273				
14	Infrared rays filter	plane		1.517	64.13	
15		plane				
16	Image plane	plane				

Reference wavelength (d-line): 555 nm; the position of blocking light: the effective half diameter of the clear aperture of the first surface is 5.800 mm; the effective diameter of the clear aperture of the third surface is 1.570 mm; the effective diameter of the clear aperture of the fifth surface is 1.950 mm.

TABLE 2

Coefficients of the aspheric surfaces							
Surface	1	2	3	4	5	6	8
k	4.310876E+01	-4.707622E+00	2.616025E+00	2.445397E+00	5.645686E+00	-2.117147E+01	-5.287220E+00
A4	7.054243E-03	1.714312E-02	-8.377541E-03	-1.789549E-02	-3.379055E-03	-1.370959E-02	-2.937377E-02
A6	-5.233264E-04	-1.502232E-04	-1.838068E-03	-3.657520E-03	-1.225453E-03	6.250200E-03	2.743532E-03
A8	3.077890E-05	-1.359611E-04	1.233332E-03	-1.131622E-03	-5.979572E-03	-5.854426E-03	-2.457574E-03
A10	-1.260650E-06	2.680747E-05	-2.390895E-03	1.390351E-03	4.556449E-03	4.049451E-03	1.874319E-03
A12	3.319093E-08	-2.017491E-06	1.998555E-03	-4.152857E-04	-1.177175E-03	-1.314592E-03	-6.013661E-04
A14	-5.051600E-10	6.604615E-08	-9.734019E-04	5.487286E-05	1.370522E-04	2.143097E-04	8.792480E-05
A16	3.380000E-12	-1.301630E-09	2.478373E-04	-2.919339E-06	-5.974015E-06	-1.399894E-05	-4.770527E-06
Surface	9	10	11	12	13		
k	6.200000E+01	-2.114008E+01	-7.699904E+00	-6.155476E+01	-3.120467E-01		
A4	-1.359965E-01	-1.263831E-01	-1.927804E-02	-2.492467E-02	-3.521844E-02		
A6	6.628518E-02	6.965399E-02	2.478376E-03	-1.835360E-03	5.629654E-03		
A8	-2.129167E-02	-2.116027E-02	1.438785E-03	3.201343E-03	-5.466925E-04		
A10	4.396344E-03	3.819371E-03	-7.013749E-04	-8.990757E-04	2.231154E-05		
A12	-5.542899E-04	-4.040283E-04	1.253214E-04	1.245343E-04	5.548990E-07		
A14	3.768879E-05	2.280473E-05	-9.943196E-06	-8.788363E-06	-9.396920E-08		
A16	-1.052467E-06	-5.165452E-07	2.898397E-07	2.494302E-07	2.728360E-09		

The figures related to the profile curve lengths obtained based on Table 1 and Table 2 are listed in the following table:

First optical embodiment (Reference wavelength (d-line): 555 nm)						
ARE	1/2(HEP)	ARE value	ARE-1/2(HEP)	2(ARE/HEP) %	TP	ARE ITP (%)
11	1.455	1.455	-0.00033	99.98%	1.934	75.23%
12	1.455	1.495	0.03957	102.72%	1.934	77.29%
21	1.455	1.465	0.00940	100.65%	2.486	58.93%
22	1.455	1.495	0.03950	102.71%	2.486	60.14%
31	1.455	1.486	0.03045	102.09%	0.380	391.02%
32	1.455	1.464	0.00830	100.57%	0.380	385.19%
41	1.455	1.458	0.00237	100.16%	1.236	117.95%
42	1.455	1.484	0.02825	101.94%	1.236	120.04%
51	1.455	1.462	0.00672	100.46%	1.072	136.42%
52	1.455	1.499	0.04335	102.98%	1.072	139.83%
61	1.455	1.465	0.00964	100.66%	1.031	142.06%
62	1.455	1.469	0.01374	100.94%	1.031	142.45%

-continued

First optical embodiment (Reference wavelength (d-line): 555 nm)						
ARS	EHD	ARS value	ARS-EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	5.800	6.141	0.341	105.88%	1.934	317.51%
12	3.299	4.423	1.125	134.10%	1.934	228.70%
21	1.664	1.674	0.010	100.61%	2.486	67.35%
22	1.950	2.119	0.169	108.65%	2.486	85.23%
31	1.980	2.048	0.069	103.47%	0.380	539.05%
32	2.084	2.101	0.017	100.83%	0.380	552.87%
41	2.247	2.287	0.040	101.80%	1.236	185.05%
42	2.530	2.813	0.284	111.22%	1.236	227.63%
51	2.655	2.690	0.035	101.32%	1.072	250.99%
52	2.764	2.930	0.166	106.00%	1.072	273.40%
61	2.816	2.905	0.089	103.16%	1.031	281.64%
62	3.363	3.391	0.029	100.86%	1.031	328.83%

The detail parameters of the first optical embodiment are listed in Table 1, in which the unit of the radius of curvature, thickness, and focal length are millimeter, and surface 0-16 indicates the surfaces of all elements in the system in sequence from the object side to the image side. Table 2 is the list of coefficients of the aspheric surfaces, in which k indicates the taper coefficient in the aspheric curve equation, and A1-A20 indicate the coefficients of aspheric surfaces from the first order to the twentieth order of each aspheric surface. The following optical embodiments have similar diagrams and tables, which are the same as those of the first optical embodiment, so we do not describe it again. The definitions of the mechanism component parameters of the following optical embodiments are the same as those of the first optical embodiment.

Second Optical Embodiment

As shown in FIG. 3A and FIG. 3B, an optical image capturing module 20 of the second optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 210, a second lens 220, a third lens 230, an aperture 200, a fourth lens 240, a fifth lens 250, a sixth lens 260, a seventh lens 270, an infrared rays filter 280, an image plane 290, and an image sensor 292.

The first lens 210 has negative refractive power and is made of glass. An object-side surface 212 thereof, which faces the object side, is a convex spherical surface, and an image-side surface 214 thereof, which faces the image side, is a concave spherical surface.

The second lens 220 has negative refractive power and is made of glass. An object-side surface 222 thereof, which faces the object side, is a concave spherical surface, and an image-side surface 224 thereof, which faces the image side, is a convex spherical surface.

The third lens 230 has positive refractive power and is made of glass. An object-side surface 232, which faces the object side, is a convex spherical surface, and an image-side surface 234, which faces the image side, is a convex spherical surface.

The fourth lens 240 has positive refractive power and is made of glass. An object-side surface 242, which faces the object side, is a convex spherical surface, and an image-side surface 244, which faces the image side, is a convex spherical surface.

The fifth lens 250 has positive refractive power and is made of glass. An object-side surface 252, which faces the object side, is a convex aspherical surface, and an image-side surface 254, which faces the image side, is a convex aspherical surface.

The sixth lens 260 has negative refractive power and is made of glass. An object-side surface 262, which faces the object side, is a concave spherical surface, and an image-side surface 264, which faces the image side, is a concave spherical surface. Whereby, the incident angle of each view field entering the sixth lens 260 could be effectively adjusted to improve aberration.

The seventh lens 270 has negative refractive power and is made of glass. An object-side surface 272, which faces the object side, is a convex surface, and an image-side surface 274, which faces the image side, is a convex surface. It may help to shorten the back focal length to keep small in size, and may reduce an incident angle of the light of an off-axis field of view and correct the aberration of the off-axis field of view.

The infrared rays filter 280 is made of glass and is disposed between the seventh lens 270 and the image plane 290. The infrared rays filter 280 gives no contribution to the focal length of the optical image capturing module 20.

The parameters of the lenses of the second optical embodiment are listed in Table 3 and Table 4.

TABLE 3

f = 4.7601 mm; f/HEP = 2.2; HAF = 95.98 deg							
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)	
0	Object	1E+18					
1	1 st lens	47.71478323	4.977	glass	2.001	29.13	
2		9.527614761	13.737				
3	2 nd lens	-14.88061107	5.000	glass	2.001	29.13	
4		-20.42046946	10.837				
5	3 rd lens	182.4762997	5.000	glass	1.847	23.78	
6		-46.71963608	13.902				

TABLE 3-continued

f = 4.7601 mm; f/HEP = 2.2; HAF = 95.98 deg						
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
7	Aperture	1E+18				
8	4 th lens	28.60018103	4.095	glass	1.834	37.35
9		-35.08507586	0.323			
10	5 th lens	18.25991342	1.539	glass	1.609	46.44
11		-36.99028878	0.546			
12	6 th lens	-18.24574524	5.000	glass	2.002	19.32
13		15.33897192	0.215			
14	7 th lens	16.13218937	4.933	glass	1.517	64.20
15		-11.24007	8.664			
16	Infrared rays filter	1E+18	1.000	BK_7	1.517	64.2
17		1E+18	1.007			
18	Image plane	1E+18	-0.007			

Reference wavelength (d-line): 555 nm

TABLE 4

Coefficients of the aspheric surfaces							
Surface	1	2	3	4	5	6	8
k	0.000000E+00						
A4	0.000000E+00						
A6	0.000000E+00						
A8	0.000000E+00						
A10	0.000000E+00						
A12	0.000000E+00						
Surface	9	10	11	12	13	14	15
k	0.000000E+00						
A4	0.000000E+00						
A6	0.000000E+00						
A8	0.000000E+00						
A10	0.000000E+00						
A12	0.000000E+00						

An equation of the aspheric surfaces of the second optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

The exact parameters of the second optical embodiment based on Table 3 and Table 4 are listed in the following table:

Second optical embodiment (Reference wavelength: 555 nm)					
f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.3764	0.0478	0.1081	0.2458	0.2354	0.6208
f/f7	ΣPPR	ΣNPR	ΣPPR/ ΣNPR	IN12/f	IN67/f
0.3495	1.3510	0.6327	2.1352	2.8858	0.0451
f1/f2	f2/f3	(TP1 + IN12)/TP2		(TP7 + IN67)/TP6	
0.1271	2.2599	3.7428		1.0296	
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
81.6178	70.9539	13.6030	0.3451	-113.2790	84.4806
HVT11	HVT12	HVT21	HVT22	HVT31	HVT32

-continued

Second optical embodiment (Reference wavelength: 555 nm)					
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
HVT61	HVT62	HVT71	HVT72	HVT72/HOI	HVT72/HOS
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
PhiA					HOI
11.962 mm					6 mm
					InTL/HOS
					0.8693
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
0.060 mm	-0.005 mm	0.016 mm	0.006 mm	0.020 mm	-0.008 mm

The figures related to the profile curve lengths obtained based on Table 3 and Table 4 are listed in the following table:

Second optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE-1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	1.082	1.081	-0.00075	99.93%	4.977	21.72%
12	1.082	1.083	0.00149	100.14%	4.977	21.77%
21	1.082	1.082	0.00011	100.01%	5.000	21.64%
22	1.082	1.082	-0.00034	99.97%	5.000	21.63%
31	1.082	1.081	-0.00084	99.92%	5.000	21.62%
32	1.082	1.081	-0.00075	99.93%	5.000	21.62%
41	1.082	1.081	-0.00059	99.95%	4.095	26.41%
42	1.082	1.081	-0.00067	99.94%	4.095	26.40%
51	1.082	1.082	-0.00021	99.98%	1.539	70.28%
52	1.082	1.081	-0.00069	99.94%	1.539	70.25%
61	1.082	1.082	-0.00021	99.98%	5.000	21.63%
62	1.082	1.082	0.00005	100.00%	5.000	21.64%
71	1.082	1.082	-0.00003	100.00%	4.933	21.93%
72	1.082	1.083	0.00083	100.08%	4.933	21.95%

ARS	EHD	ARS value	ARS-EHD	(ARS/EHD) %	TP	ARS/TP (%)
11	20.767	21.486	0.719	103.46%	4.977	431.68%
12	9.412	13.474	4.062	143.16%	4.977	270.71%
21	8.636	9.212	0.577	106.68%	5.000	184.25%
22	9.838	10.264	0.426	104.33%	5.000	205.27%
31	8.770	8.772	0.003	100.03%	5.000	175.45%
32	8.511	8.558	0.047	100.55%	5.000	171.16%
41	4.600	4.619	0.019	100.42%	4.095	112.80%
42	4.965	4.981	0.016	100.32%	4.095	121.64%
51	5.075	5.143	0.067	101.33%	1.539	334.15%
52	5.047	5.062	0.015	100.30%	1.539	328.89%
61	5.011	5.075	0.064	101.28%	5.000	101.50%
62	5.373	5.489	0.116	102.16%	5.000	109.79%
71	5.513	5.625	0.112	102.04%	4.933	114.03%
72	5.981	6.307	0.326	105.44%	4.933	127.84%

The results of the equations of the second optical embodiment based on Table 3 and Table 4 are listed in the following table:

The fourth lens **340** has negative refractive power and is made of plastic. An object-side surface **342**, which faces the object side, is a concave aspheric surface, and an image-side

Values related to the inflection points of the second optical embodiment (Reference wavelength: 555 nm)							
HIF111	0	HIF111/HOI	0	SGI111	0	SGI111 /(SGI111 + TP1)	0

Third Optical Embodiment

As shown in FIG. 4A and FIG. 4B, an optical image capturing module **30** of the third optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens **310**, a second lens **320**, a third lens **330**, an aperture **300**, a fourth lens **340**, a fifth lens **350**, a sixth lens **360**, a seventh lens **370**, an infrared rays filter **380**, an image plane **390**, and an image sensor **392**.

The first lens **310** has negative refractive power and is made of glass. An object-side surface **312** thereof, which faces the object side, is a convex spherical surface, and an image-side surface **314** thereof, which faces the image side, is a concave spherical surface.

The second lens **320** has negative refractive power and is made of glass. An object-side surface **322** thereof, which faces the object side, is a concave spherical surface, and an image-side surface **324** thereof, which faces the image side, is a convex spherical surface.

The third lens **330** has positive refractive power and is made of plastic. An object-side surface **332** thereof, which faces the object side, is a convex aspheric surface, and an image-side surface **334** thereof, which faces the image side, is a convex aspheric surface. The image-side surface **334** has an inflection point.

surface **344**, which faces the image side, is a concave aspheric surface. The image-side surface **344** has an inflection point.

The fifth lens **350** has positive refractive power and is made of plastic. An object-side surface **352**, which faces the object side, is a convex aspheric surface, and an image-side surface **354**, which faces the image side, is a convex aspheric surface.

The sixth lens **360** has negative refractive power and is made of plastic. An object-side surface **362**, which faces the object side, is a convex aspheric surface, and an image-side surface **364**, which faces the image side, is a concave aspheric surface. The object-side surface **362** has an inflection point, and the image-side surface **364** has an inflection point. It may help to shorten the back focal length to keep small in size. Whereby, the incident angle of each view field entering the sixth lens **360** could be effectively adjusted to improve aberration.

The infrared rays filter **380** is made of glass and is disposed between the sixth lens **360** and the image plane **390**. The infrared rays filter **390** gives no contribution to the focal length of the optical image capturing module **30**.

The parameters of the lenses of the third optical embodiment are listed in Table 5 and Table 6.

TABLE 5

f = 2.808 mm; f/HEP = 1.6; HAF = 100 deg

Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
0	Object	1E+18				
1	1 st lens	71.398124	7.214	glass	1.702	41.15
2		7.117272355	5.788			-11.765
3	2 nd lens	-13.29213699	10.000	glass	2.003	19.32
4		-18.37509887	7.005			-4537.460
5	3 rd lens	5.039114804	1.398	plastic	1.514	56.80
6		-15.53136631	-0.140			7.553
7	Aperture	1E+18	2.378			
8	4 th lens	-18.68613609	0.577	plastic	1.661	20.40
9		4.086545927	0.141			-4.978
10	5 th lens	4.927609282	2.974	plastic	1.565	58.00
11		-4.551946605	1.389			4.709
12	6 th lens	9.184876531	1.916	plastic	1.514	56.80
13		4.845500046	0.800			-23.405
14	Infrared rays filter	1E+18	0.500	BK_7	1.517	64.13
15		1E+18	0.371			
16	Image plane	1E+18	0.005			

Reference wavelength (d-line): 555 nm; the position of blocking light: none.

TABLE 6

Coefficients of the aspheric surfaces

Surface	1	2	3	4	5	6	8
k	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	1.318519E-01	3.120384E+00	-1.494442E+01
A4	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	6.405246E-05	2.103942E-03	-1.598286E-03
A6	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	2.278341E-05	-1.050629E-04	-9.177115E-04
A8	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-3.672908E-06	6.168906E-06	1.011405E-04
A10	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	3.748457E-07	-1.224682E-07	-4.919835E-06

Surface	9	10	11	12	13
k	2.744228E-02	-7.864013E+00	-2.263702E+00	-4.206923E+01	-7.030803E+00
A4	-7.291825E-03	1.405243E-04	-3.919567E-03	-1.679499E-03	-2.640099E-03
A6	9.730714E-05	1.837602E-04	2.683449E-04	-3.518520E-04	-4.507651E-05
A8	1.101816E-06	-2.173368E-05	-1.229452E-05	5.047353E-05	-2.600391E-05
A10	-6.849076E-07	7.328496E-07	4.222621E-07	-3.851055E-06	1.161811E-06

An equation of the aspheric surfaces of the third optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

The exact parameters of the third optical embodiment based on Table 5 and Table 6 are listed in the following table:

Third optical embodiment (Reference wavelength: 555 nm)

f/f1	f/f2	f/f3	f/f4	f/f5	f/f6
0.23865	0.00062	0.37172	0.56396	0.59621	0.11996

ΣPPR	ΣNPR	ΣPPR/ ΣNPR	IN12/f	IN56/f	TP4/(IN34 + TP4 + IN45)
1.77054	0.12058	14.68400	2.06169	0.49464	0.19512

-continued

Third optical embodiment (Reference wavelength: 555 nm)

f1/f2	f2/f3	(TP1 + IN12)/TP2	(TP6 + IN56)/TP5
0.00259	600.74778	1.30023	1.11131

HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
42.31580	40.63970	10.57895	0.26115	-122.32700	93.33510

HVT51	HVT52	HVT61	HVT62	HVT62/HOI	HVT62/HOS
0	0	2.22299	2.60561	0.65140	0.06158

TP2/TP3	TP3/TP4	InRS61	InRS62	InRS61 /TP6	InRS62 /TP6
50	55	60	65		

-continued

Third optical embodiment (Reference wavelength: 555 nm)					
7.15374	2.42321	-0.20807	-0.24978	0.10861	0.13038
PhiA					HOI
6.150 mm					4 mm
					InTL/HOS
0.9604					
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
0.014 mm	0.002 mm	-0.003 mm	-0.002 mm	0.011 mm	-0.001 mm

The figures related to the profile curve lengths obtained based on Table 5 and Table 6 are listed in the following table:

Third optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.877	0.877	-0.00036	99.96%	7.214	12.16%
12	0.877	0.879	0.00186	100.21%	7.214	12.19%
21	0.877	0.878	0.00026	100.03%	10.000	8.78%
22	0.877	0.877	-0.00004	100.00%	10.000	8.77%
31	0.877	0.882	0.00413	100.47%	1.398	63.06%
32	0.877	0.877	0.00004	100.00%	1.398	62.77%
41	0.877	0.877	-0.00001	100.00%	0.577	152.09%
42	0.877	0.883	0.00579	100.66%	0.577	153.10%
51	0.877	0.881	0.00373	100.43%	2.974	29.63%
52	0.877	0.883	0.00521	100.59%	2.974	29.68%
61	0.877	0.878	0.00064	100.07%	1.916	45.83%
62	0.877	0.881	0.00368	100.42%	1.916	45.99%
ARS	EHD	ARS value	ARS - EHD	(ARS/EHD)%	TP	ARS/TP (%)
11	17.443	17.620	0.178	101.02%	7.214	244.25%
12	6.428	8.019	1.592	124.76%	7.214	111.16%
21	6.318	6.584	0.266	104.20%	10.000	65.84%
22	6.340	6.472	0.132	102.08%	10.000	64.72%
31	2.699	2.857	0.158	105.84%	1.398	204.38%
32	2.476	2.481	0.005	100.18%	1.398	177.46%
41	2.601	2.652	0.051	101.96%	0.577	459.78%
42	3.006	3.119	0.113	103.75%	0.577	540.61%
51	3.075	3.171	0.096	103.13%	2.974	106.65%
52	3.317	3.624	0.307	109.24%	2.974	121.88%
61	3.331	3.427	0.095	102.86%	1.916	178.88%
62	3.944	4.160	0.215	105.46%	1.916	217.14%

The results of the equations of the third optical embodiment based on Table 5 and Table 6 are listed in the following table:

Values related to the inflection points of the third optical embodiment (Reference wavelength: 555 nm)							
HIF321	2.0367	HIF321/HOI	0.5092	SGI321	-0.1056	$ SGI321 /(SGI321 + TP3)$	0.0702
HIF421	2.4635	HIF421/HOI	0.6159	SGI421	0.5780	$ SGI421 /(SGI421 + TP4)$	0.5005
HIF611	1.2364	HIF611/HOI	0.3091	SGI611	0.0668	$ SGI611 /(SGI611 + TP6)$	0.0337
HIF621	1.5488	HIF621/HOI	0.3872	SGI621	0.2014	$ SGI621 /(SGI621 + TP6)$	0.0951

Fourth Optical Embodiment

As shown in FIG. 5A and FIG. 5B, an optical image capturing module 40 of the fourth optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 410, a second lens 420, an aperture 400, a third lens 430, a fourth lens 440, a fifth lens 450, an infrared rays filter 470, an image plane 480, and an image sensor 490.

The first lens 410 has negative refractive power and is made of glass. An object-side surface 412 thereof, which faces the object side, is a convex spherical surface, and an image-side surface 414 thereof, which faces the image side, is a concave spherical surface.

The second lens 420 has negative refractive power and is made of plastic. An object-side surface 422 thereof, which faces the object side, is a concave aspheric surface, and an image-side surface 424 thereof, which faces the image side, is a concave aspheric surface. The object-side surface 422 has an inflection point.

The third lens 430 has positive refractive power and is made of plastic. An object-side surface 432 thereof, which faces the object side, is a convex aspheric surface, and an image-side surface 434 thereof, which faces the image side, is a convex aspheric surface. The object-side surface 432 has an inflection point.

The fourth lens 440 has positive refractive power and is made of plastic. An object-side surface 442, which faces the object side, is a convex aspheric surface, and an image-side surface 444, which faces the image side, is a convex aspheric surface. The object-side surface 442 has an inflection point.

The fifth lens 450 has negative refractive power and is made of plastic. An object-side surface 452, which faces the object side, is a concave aspheric surface, and an image-side surface 454, which faces the image side, is a concave aspheric surface. The object-side surface 452 has two inflection points. It may help to shorten the back focal length to keep small in size.

The infrared rays filter 470 is made of glass and is disposed between the fifth lens 450 and the image plane 480. The infrared rays filter 470 gives no contribution to the focal length of the optical image capturing module 40.

The parameters of the lenses of the fourth optical embodiment are listed in Table 7 and Table 8.

TABLE 7

f = 2.7883 mm; f/HEP = 1.8; HAF = 101 deg

Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)
0	Object	1E+18	1E+18			
1	1 st lens	76.84219	6.117399	glass	1.497	81.61
2		12.62555	5.924382			
3	2 nd lens	-37.0327	3.429817	plastic	1.565	54.5
4		5.88556	5.305191			
5	3 rd lens	17.99395	14.79391			
6		-5.76903	-0.4855	plastic	1.565	58
7	Aperture	1E+18	0.535498			
8	4 th lens	8.19404	4.011739	plastic	1.565	58
9		-3.84363	0.050366			
10	5 th lens	-4.34991	2.088275	plastic	1.661	20.4
11		16.6609	0.6			
12	Infrared rays filter	1E+18	0.5	BK_7	1.517	64.13
13		1E+18	3.254927			
14	Image plane	1E+18	-0.00013			

Reference wavelength (d-line): 555 nm.

TABLE 8

Coefficients of the aspheric surfaces

Surface	1	2	3	4	5	6	8
k	0.000000E+00	0.000000E+00	0.131249	-0.069541	-0.324555	0.009216	-0.292346
A4	0.000000E+00	0.000000E+00	3.99823E-05	-8.55712E-04	-9.07093E-04	8.80963E-04	-1.02138E-03
A6	0.000000E+00	0.000000E+00	9.03636E-08	-1.96175E-06	-1.02465E-05	3.14497E-05	-1.18559E-04
A8	0.000000E+00	0.000000E+00	1.91025E-09	-1.39344E-08	-8.18157E-08	-3.15863E-06	1.34404E-05
A10	0.000000E+00	0.000000E+00	-1.18567E-11	-4.17090E-09	-2.42621E-09	1.44613E-07	-2.80681E-06
A12	0.000000E+00						

Surface	9	10	11
k	-0.18604	-6.17195	27.541383
A4	4.33629E-03	1.58379E-03	7.56932E-03
A6	-2.91588E-04	-1.81549E-04	-7.83858E-04
A8	9.11419E-06	-1.18213E-05	4.79120E-05
A10	1.28365E-07	1.92716E-06	-1.73591E-06
A12	0.000000E+00	0.000000E+00	0.000000E+00

45

-continued

An equation of the aspheric surfaces of the fourth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

The exact parameters of the fourth optical embodiment based on Table 7 and Table 8 are listed in the following table:

Fourth optical embodiment (Reference wavelength: 555 nm)

f/f1	f/f2	f/f3	f/f4	f/f5	f1/f2
0.08902	0.32019	0.28029	0.53121	0.56045	3.59674

ΣPPR	ΣNPR	ΣNPR	IN12/f	IN45/f	f2/f3
1.4118	0.3693	3.8229	2.1247	0.0181	0.8754

50

Fourth optical embodiment (Reference wavelength: 555 nm)

TP3/(IN23 + TP3 + IN34)	(TP1 + IN12)/TP2	(TP5 + IN45)/TP4
0.73422	3.51091	0.53309

55

HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
46.12590	41.77110	11.53148	0.23936	-125.266	99.1671

60

HVT41	HVT42	HVT51	HVT52	HVT52/HOI	HVT52/HOS
0.00000	0.00000	0.00000	0.00000	0.00000	0.00000

65

TP2/TP3	TP3/TP4	InRS51	InRS52	InRS51 /TP5	InRS52 /TP5
0.23184	3.68765	-0.679265	0.5369	0.32528	0.25710

-continued

Fourth optical embodiment (Reference wavelength: 555 nm)					
PhiA	HOI				
5.598 mm	4 mm				
InTL/HOS					
0.9056					
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
-0.011 mm	0.005 mm	-0.010 mm	-0.003 mm	0.005 mm	-0.00026 mm

The figures related to the profile curve lengths obtained based on Table 7 and Table 8 are listed in the following table:

Fourth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.775	0.774	-0.00052	99.93%	6.117	12.65%
12	0.775	0.774	-0.00005	99.99%	6.117	12.66%
21	0.775	0.774	-0.00048	99.94%	3.430	22.57%
22	0.775	0.776	0.00168	100.22%	3.430	22.63%
31	0.775	0.774	-0.00031	99.96%	14.794	5.23%
32	0.775	0.776	0.00177	100.23%	14.794	5.25%
41	0.775	0.775	0.00059	100.08%	4.012	19.32%
42	0.775	0.779	0.00453	100.59%	4.012	19.42%
51	0.775	0.778	0.00311	100.40%	2.088	37.24%
52	0.775	0.774	-0.00014	99.98%	2.088	37.08%

ARS	EHD	ARS value	ARS - EHD	(ARS/EHD)%	TP	ARS/TP (%)
11	23.038	23.397	0.359	101.56%	6.117	382.46%
12	10.140	11.772	1.632	116.10%	6.117	192.44%
21	10.138	10.178	0.039	100.39%	3.430	296.74%
22	5.537	6.337	0.800	114.44%	3.430	184.76%
31	4.490	4.502	0.012	100.27%	14.794	30.43%
32	2.544	2.620	0.076	102.97%	14.794	17.71%
41	2.735	2.759	0.024	100.89%	4.012	68.77%
42	3.123	3.449	0.326	110.43%	4.012	85.97%
51	2.934	3.023	0.089	103.04%	2.088	144.74%
52	2.799	2.883	0.084	103.00%	2.088	138.08%

The results of the equations of the fourth optical embodiment based on Table 7 and Table 8 are listed in the following table:

Values related to the inflection points of the fourth optical embodiment (Reference wavelength: 555 nm)							
HIF211	6.3902	HIF211/HOI	1.5976	SGI211	-0.4793	$ SGI211 /(SGI211 + TP2)$	0.1226
HIF311	2.1324	HIF311/HOI	0.5331	SGI311	0.1069	$ SGI311 /(SGI311 + TP3)$	0.0072
HIF411	2.0278	HIF411/HOI	0.5070	SGI411	0.2287	$ SGI411 /(SGI411 + TP4)$	0.0539
HIF511	2.6253	HIF511/HOI	0.6563	SGI511	-0.5681	$ SGI511 /(SGI511 + TP5)$	0.2139
HIF512	2.1521	HIF512/HOI	0.5380	SGI512	-0.8314	$ SGI512 /(SGI512 + TP5)$	0.2848

Fifth Optical Embodiment

As shown in FIG. 6A and FIG. 6B, an optical image capturing module 50 of the fifth optical embodiment of the present invention includes, along an optical axis from an object side to an image side, an aperture 500, a first lens 510, a second lens 520, a third lens 530, a fourth lens 540, an infrared rays filter 570, an image plane 580, and an image sensor 590.

The first lens 510 has positive refractive power and is made of plastic. An object-side surface 512, which faces the object side, is a convex aspheric surface, and an image-side surface 514, which faces the image side, is a convex aspheric surface. The object-side surface 512 has an inflection point.

The second lens 520 has negative refractive power and is made of plastic. An object-side surface 522 thereof, which faces the object side, is a convex aspheric surface, and an image-side surface 524 thereof, which faces the image side, is a concave aspheric surface. The object-side surface 522 has two inflection points, and the image-side surface 524 has an inflection point.

The third lens 530 has positive refractive power and is made of plastic. An object-side surface 532, which faces the object side, is a concave aspheric surface, and an image-side surface 534, which faces the image side, is a convex aspheric surface. The object-side surface 532 has three inflection points, and the image-side surface 534 has an inflection point.

The fourth lens 540 has negative refractive power and is made of plastic. An object-side surface 542, which faces the object side, is a concave aspheric surface, and an image-side surface 544, which faces the image side, is a concave aspheric surface. The object-side surface 542 has two inflection points, and the image-side surface 544 has an inflection point.

The infrared rays filter 570 is made of glass and is disposed between the fourth lens 540 and the image plane 580. The infrared rays filter 570 gives no contribution to the focal length of the optical image capturing module 50.

The parameters of the lenses of the fifth optical embodiment are listed in Table 9 and Table 10.

TABLE 9

f = 1.04102 mm; f/HEP = 1.4; HAF = 44.0346 deg							
Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)	
0	Object	1E+18	600				
1	Aperture	1E+18	-0.020				
2	1 st lens	0.890166851	0.210	plastic	1.545	55.96	1.587
3		-29.11040115	-0.010				
4		1E+18	0.116				
5	2 nd lens	10.67765398	0.170	plastic	1.642	22.46	-14.569
6		4.977771922	0.049				
7	3 rd lens	-1.191436932	0.349	plastic	1.545	55.96	0.510
8		-0.248990674	0.030				
9	4 th lens	-38.08537212	0.176	plastic	1.642	22.46	-0.569
10		0.372574476	0.152				
11	1E+18	0.210	BK_7	1.517	64.13		1E+18
12	1E+18	0.185					1E+18
13	1E+18	0.005					1E+18

Reference wavelength (d-line): 555 nm; the position of blocking light: the effective half diameter of the clear aperture of the fourth surface is 0.360 mm.

TABLE 10

Coefficients of the aspheric surfaces						
Surface	2	3	5	6	7	8
k	-1.106629E+00	2.994179E-07	-7.788754E+01	-3.440335E+01	-8.522097E-01	-4.735945E+00
A4	8.291155E-01	-6.401113E-01	-4.958114E+00	-1.875957E+00	-4.878227E-01	-2.490377E+00
A6	-2.398799E+01	-1.265726E+01	1.299769E+02	8.568480E+01	1.291242E+02	1.524149E+02
A8	1.825378E+02	8.457286E+01	-2.736977E+03	-1.279044E+03	-1.979689E+03	-4.841033E+03
A10	-6.211133E+02	-2.157875E+02	2.908537E+04	8.661312E+03	1.456076E+04	8.053747E+04
A12	-4.719066E+02	-6.203600E+02	-1.499597E+05	-2.875274E+04	-5.975920E+04	-7.936887E+05
A14	0.000000E+00	0.000000E+00	2.992026E+05	3.764871E+04	1.351676E+05	4.811528E+06
A16	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-1.329001E+05	-1.762293E+07
A18	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	3.579891E+07
A20	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	0.000000E+00	-3.094006E+07

Surface	9	10
k	-2.277155E+01	-8.039778E-01
A4	1.672704E+01	-7.613206E+00
A6	-3.260722E+02	3.374046E+01
A8	3.373231E+03	-1.368453E+02
A10	-2.177676E+04	4.049486E+02
A12	8.951687E+04	-9.711797E+02
A14	-2.363737E+05	1.942574E+03
A16	3.983151E+05	-2.876356E+03
A18	-4.090689E+05	2.562386E+03
A20	2.056724E+05	-9.943657E+02

An equation of the aspheric surfaces of the fifth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

The exact parameters of the fifth optical embodiment based on Table 9 and Table 10 are listed in the following table:

Fifth optical embodiment (Reference wavelength: 555 nm)					
InRS41	InRS42	HVT41	HVT42	ODT %	TDT %
-0.07431	0.00475	0.00000	0.53450	2.09403	0.84704
f/f1	f/f2	f/f3	f/f4	f1/f2	f2/f3
0.65616	0.07145	2.04129	1.83056	0.10890	28.56826

-continued

Fifth optical embodiment (Reference wavelength: 555 nm)						
ΣPPR	ΣNPR	ΣPPR/ ΣNPR	ΣPP	ΣNP	f1/ΣPP	
2.11274	2.48672	0.84961	-14.05932	1.01785	1.03627	
f4/ΣNP	IN12/f	IN23/f	IN34/f	TP3/f	TP4/f	
1.55872	0.10215	0.04697	0.02882	0.33567	0.16952	
InTL	HOS	HOS/HOI	InS/HOS	InTL/HOS	ΣTP/InTL	
1.09131	1.64329	1.59853	0.98783	0.66410	0.83025	
(TP1 + IN12)/TP2	(TP4 + IN34)/TP3	TP1/TP2	TP3/TP4	IN23/(TP2 + IN23 + TP3)		
65						

-continued

Fifth optical embodiment (Reference wavelength: 555 nm)					
1.86168	0.59088	1.23615	1.98009	0.08604	
InRS41/ TP4	InRS42/ TP4	HVT42/ HOI	HVT42/ HOS	InTL/ HOS	
0.4211	0.0269	0.5199	0.3253	0.6641	
PhiA					HOI
1.596 mm					1.028 mm
PSTA	PLTA	NSTA	NLTA	SSTA	SLTA
-0.029 mm	-0.023 mm	-0.011 mm	-0.024 mm	0.010 mm	0.011 mm

The results of the equations of the fifth optical embodiment based on Table 9 and Table 10 are listed in the following table:

Values related to the inflection points of the fifth optical embodiment (Reference wavelength: 555 nm)						
HIF111	0.28454	HIF111/HOI	0.27679	SGI111	0.04361	SGI111 /(SGI111 + TP1) 0.17184
HIF211	0.04198	HIF211/HOI	0.04083	SGI211	0.00007	SGI211 /(SGI211 + TP2) 0.00040
HIF212	0.37903	HIF212/HOI	0.36871	SGI212	-0.03682	SGI212 /(SGI212 + TP2) 0.17801
HIF221	0.25058	HIF221/HOI	0.24376	SGI221	0.00695	SGI221 /(SGI221 + TP2) 0.03927
HIF311	0.14881	HIF311/HOI	0.14476	SGI311	-0.00854	SGI311 /(SGI311 + TP3) 0.02386
HIF312	0.31992	HIF312/HOI	0.31120	SGI312	-0.01783	SGI312 /(SGI312 + TP3) 0.04855
HIF313	0.32956	HIF313/HOI	0.32058	SGI313	-0.01801	SGI313 /(SGI313 + TP3) 0.04902
HIF321	0.36943	HIF321/HOI	0.35937	SGI321	-0.14878	SGI321 /(SGI321 + TP3) 0.29862
HIF411	0.01147	HIF411/HOI	0.01116	SGI411	-0.00000	SGI411 /(SGI411 + TP4) 0.00001
HIF412	0.22405	HIF412/HOI	0.21795	SGI412	0.01598	SGI412 /(SGI412 + TP4) 0.08304
HIF421	0.24105	HIF421/HOI	0.23448	SGI421	0.05924	SGI421 /(SGI421 + TP4) 0.25131

The figures related to the profile curve lengths obtained based on Table 9 and Table 10 are listed in the following table:

Fifth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.368	0.374	0.00578	101.57%	0.210	178.10%
12	0.366	0.368	0.00240	100.66%	0.210	175.11%
21	0.372	0.375	0.00267	100.72%	0.170	220.31%
22	0.372	0.371	-0.00060	99.84%	0.170	218.39%
31	0.372	0.372	-0.00023	99.94%	0.349	106.35%
32	0.372	0.404	0.03219	108.66%	0.349	115.63%
41	0.372	0.373	0.00112	100.30%	0.176	211.35%
42	0.372	0.387	0.01533	104.12%	0.176	219.40%

ARS	EHD	ARS value	ARS - EHD	(ARS/EHD)%	TP	ARS/TP (%)
11	0.368	0.374	0.00578	101.57%	0.210	178.10%
12	0.366	0.368	0.00240	100.66%	0.210	175.11%
21	0.387	0.391	0.00383	100.99%	0.170	229.73%
22	0.458	0.460	0.00202	100.44%	0.170	270.73%
31	0.476	0.478	0.00161	100.34%	0.349	136.76%

-continued

Fifth optical embodiment (Reference wavelength: 555 nm)						
32	0.494	0.538	0.04435	108.98%	0.349	154.02%
41	0.585	0.624	0.03890	106.65%	0.176	353.34%
42	0.798	0.866	0.06775	108.49%	0.176	490.68%

Sixth Optical Embodiment

As shown in FIG. 7A and FIG. 7B, an optical image capturing module 60 of the sixth optical embodiment of the present invention includes, along an optical axis from an object side to an image side, a first lens 610, an aperture 600, a second lens 620, a third lens 630, an infrared rays filter 670, an image plane 680, and an image sensor 690.

The first lens 610 has positive refractive power and is made of plastic. An object-side surface 612, which faces the object side, is a convex aspheric surface, and an image-side surface 614, which faces the image side, is a concave aspheric surface.

The second lens 620 has negative refractive power and is made of plastic. An object-side surface 622 thereof, which faces the object side, is a concave aspheric surface, and an image-side surface 624 thereof, which faces the image side, is a convex aspheric surface. The image-side surface 624 has an inflection point.

The third lens 630 has positive refractive power and is made of plastic. An object-side surface 632, which faces the object side, is a convex aspheric surface, and an image-side surface 634, which faces the image side, is a concave aspheric surface. The object-side surface 632 has two inflection points, and the image-side surface 634 has an inflection point.

The infrared rays filter 670 is made of glass and is disposed between the third lens 630 and the image plane 680. The infrared rays filter 670 gives no contribution to the focal length of the optical image capturing module 60.

The parameters of the lenses of the sixth optical embodiment are listed in Table 11 and Table 12.

TABLE 11

f = 2.41135 mm; f/HEP = 2.22; HAF = 36 deg

Surface	Radius of curvature (mm)	Thickness (mm)	Material	Refractive index	Abbe number	Focal length (mm)	
0	Object	1E+18	600				
1	1 st lens	0.840352226	0.468	plastic	1.535	56.27	2.232
2		2.271975602	0.148				
3	Aperture	1E+18	0.277				
4	2 nd lens	-1.157324239	0.349	plastic	1.642	22.46	-5.221
5		-1.968404008	0.221				
6	3 rd lens	1.151874235	0.559	plastic	1.544	56.09	7.360
7		1.338105159	0.123				
8	Infrared rays filter	1E+18	0.210	BK7	1.517	64.13	
9		1E+18	0.547				
10	Image plane	1E+18	0.000				

Reference wavelength (d-line): 555 nm; the position of blocking light: the effective half diameter of the clear aperture of the first surface is 0.640 mm.

TABLE 12

Coefficients of the aspheric surfaces

Surface	1	2	4	5	6	7
k	-2.019203E-01	1.528275E+01	3.743939E+00	-1.207814E+01	-1.276860E+01	-3.034004E+00
A4	3.944883E-02	-1.670490E-01	-4.266331E-01	-1.696843E+00	-7.396546E-01	-5.308488E-01
A6	4.774062E-01	3.857435E+00	-1.423859E+00	5.164775E+00	4.449101E-01	4.374142E-01
A8	-1.528780E+00	-7.091408E+01	4.119587E+01	-1.445541E+01	2.622372E-01	-3.111192E-01
A10	5.133947E+00	6.365801E+02	-3.456462E+02	2.876958E+01	-2.510946E-01	1.354257E-01
A12	-6.250496E+00	-3.141002E+03	1.495452E+03	-2.662400E+01	-1.048030E-01	-2.652902E-02
A14	1.068803E+00	7.962834E+03	-2.747802E+03	1.661634E+01	1.462137E-01	-1.203306E-03
A16	7.995491E+00	-8.268637E+03	1.443133E+03	-1.327827E+01	-3.676651E-02	7.805611E-04

An equation of the aspheric surfaces of the sixth optical embodiment is the same as that of the first optical embodiment, and the definitions are the same as well.

The exact parameters of the sixth optical embodiment based on Table 11 and Table 12 are listed in the following table:

Sixth optical embodiment (Reference wavelength: 555 nm)

f1/f1	f1/f2	f1/f3	f2/f2	f2/f3	TP1/TP2
1.08042	0.46186	0.32763	2.33928	1.40968	1.33921
ΣPPR	ΣNPR	ΣPPR/ΣNPR	IN12/f	IN23/f	TP2/TP3
1.40805	0.46186	3.04866	0.17636	0.09155	0.62498
TP2/(IN12 + TP2 + IN23)	(TP1 + IN12)/TP2	(TP3 + IN23)/TP2			
0.35102	2.23183	2.23183			
HOS	InTL	HOS/HOI	InS/HOS	ODT %	TDT %
2.90175	2.02243	1.61928	0.78770	1.50000	0.71008
HVT21	HVT22	HVT31	HVT32	HVT32/HOI	HVT32/HOS

40

-continued

Sixth optical embodiment (Reference wavelength: 555 nm)

0.00000	0.00000	0.46887	0.67544	0.37692	0.23277
PhiA					HOI
2.716 mm					1.792 mm
					InTL/HOS
					0.6970
PLTA	PSTA	NLTA	NSTA	SLTA	SSTA
-0.002	0.008	0.006	-0.008	-0.007	0.006
mm	mm	mm	mm	mm	mm

45

50

55

60

65

The results of the equations of the sixth optical embodiment based on Table 11 and Table 12 are listed in the following table:

Values related to the inflection points of the sixth optical embodiment (Reference wavelength: 555 nm)

HIF221	0.5599	HIF221/HOI	0.3125	SGI221	-0.1487	$ SGI221 /(SGI221 + TP2)$	0.2412
HIF311	0.2405	HIF311/HOI	0.1342	SGI311	0.0201	$ SGI311 /(SGI311 + TP3)$	0.0413
HIF312	0.8255	HIF312/HOI	0.4607	SGI312	-0.0234	$ SGI312 /(SGI312 + TP3)$	0.0476
HIF321	0.3505	HIF321/HOI	0.1956	SGI321	0.0371	$ SGI321 /(SGI321 + TP3)$	0.0735

The figures related to the profile curve lengths obtained based on Table 11 and Table 12 are listed in the following table:

Sixth optical embodiment (Reference wavelength: 555 nm)						
ARE	1/2(HEP)	ARE value	ARE - 1/2(HEP)	2(ARE/HEP) %	TP	ARE/TP (%)
11	0.546	0.598	0.052	109.49%	0.468	127.80%
12	0.500	0.506	0.005	101.06%	0.468	108.03%
21	0.492	0.528	0.036	107.37%	0.349	151.10%
22	0.546	0.572	0.026	104.78%	0.349	163.78%
31	0.546	0.548	0.002	100.36%	0.559	98.04%
32	0.546	0.550	0.004	100.80%	0.559	98.47%

ARS	EHD	ARS value	ARS - EHD	(ARS/EHD)%	TP	ARS/TP (%)
11	0.640	0.739	0.099	115.54%	0.468	158.03%
12	0.500	0.506	0.005	101.06%	0.468	108.03%
21	0.492	0.528	0.036	107.37%	0.349	151.10%
22	0.706	0.750	0.044	106.28%	0.349	214.72%
31	1.118	1.135	0.017	101.49%	0.559	203.04%
32	1.358	1.489	0.131	109.69%	0.559	266.34%

The optical image capturing module of the present invention could be one of a group consisting of an electronic portable device, an electronic wearable device, an electronic monitoring device, an electronic information device, an electronic communication device, a machine vision device, and a vehicle electronic device. In addition, the optical image capturing module of the present invention could reduce the required mechanism space and increase the visible area of the screen by using different lens groups with different number of lens.

It must be pointed out that the embodiments described above are only some embodiments of the present invention. All equivalent structures which employ the concepts disclosed in this specification and the appended claims should fall within the scope of the present invention.

What is claimed is:

1. A movable carrier auxiliary system, comprising:

- a first transparent assembly, comprising:
 - a first incidence surface; and
 - a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface;
- a second transparent assembly disposed on the first exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly; the second transparent assembly comprising:
 - a second incidence surface; and
 - a second exit surface, wherein the image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface;
- an electro-optic medium layer disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second transparent assembly;

at least one transparent electrode disposed between the first transparent assembly and the electro-optic medium layer;

at least one reflective layer directly disposed on the second exit surface of the second transparent assembly, wherein the electro-optic medium layer is disposed between the first transparent assembly and the at least one reflective layer;

at least one transparent conductive layer disposed between the electro-optic medium layer and the at least one reflective layer;

at least one electrical connector electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer;

at least one control member electrically connected to the at least one electrical connector;

at least one displaying device for displaying an environmental image signal; and

at least one optical image capturing module for capturing and projecting the environmental image signal to the at least one displaying device,

wherein the at least one optical image capturing module has at least one lens group; the at least one lens group comprises at least two lenses having refractive power and satisfies:

$$1.0 \leq f/HEP \leq 10.0;$$

$$0 \text{ deg} \leq HAF \leq 150 \text{ deg}; \text{ and}$$

$$0.9 \leq 2(ARE/HEP) \leq 2.0,$$

where f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis, and

wherein when a brightness of the image exceeds a pre-determined brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer.

2. The movable carrier auxiliary system of claim 1, wherein the movable carrier auxiliary system is a vehicle electronic rear-view mirror.

3. The movable carrier auxiliary system of claim 1, wherein the electro-optic medium layer is selected from an electrochromic layer, a polymer dispersed liquid crystal (PDLC) layer, or a suspended particle device (SPD) layer.

4. The movable carrier auxiliary system of claim 1, wherein a material of the reflective layer is selected from a material containing cerium oxide, or is a material which is

conductive and is selected from a group consisting of at least one of silver, copper, aluminum, titanium, chromium, molybdenum or its alloy, or is a transparent conductive material.

5. The movable carrier auxiliary system of claim 1, wherein a material of the transparent conductive layer includes at least one material selected from a group consisting of indium tin oxide (ITO), indium zinc oxide (IZO), Al-doped ZnO (AZO), or Fluorine-doped tin oxide.

6. The movable carrier auxiliary system of claim 1, wherein the first transparent assembly is adhered to the second incidence surface via an optical adhesive, and the optical adhesive forms an optical adhesion layer.

7. The movable carrier auxiliary system of claim 1, wherein the at least one lens group satisfies:

$$0.9 \leq ARS/EHD \leq 2.0;$$

wherein for any surface of any lens, ARS is a profile curve length measured from a start point where the optical axis passes therethrough, along a surface profile thereof, and finally to an end point of the maximum effective half diameter thereof; EHD is a maximum effective half diameter thereof.

8. The movable carrier auxiliary system of claim 1, wherein the at least one lens group satisfies:

$$PLTA \leq 100 \mu\text{m};$$

$$PSTA \leq 100 \mu\text{m};$$

$$NLTA \leq 100 \mu\text{m};$$

$$NSTA \leq 100 \mu\text{m};$$

$$SLTA \leq 100 \mu\text{m};$$

$$SSTA \leq 100 \mu\text{m}; \text{ and}$$

$$|TDT| < 250\%;$$

where HOI is a maximum height for image formation perpendicular to the optical axis on an image plane of the at least one lens group; PLTA is a transverse aberration at 0.7 HOI in a positive direction of a tangential ray fan aberration after the longest operation wavelength passing through an edge of the entrance pupil; PSTA is a transverse aberration at 0.7 HOI in the positive direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; NLTA is a transverse aberration at 0.7 HOI in a negative direction of the tangential ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil; NSTA is a transverse aberration at 0.7 HOI in the negative direction of the tangential ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; SLTA is a transverse aberration at 0.7 HOI of a sagittal ray fan aberration after the longest operation wavelength passing through the edge of the entrance pupil; SSTA is a transverse aberration at 0.7 HOI of the sagittal ray fan aberration after the shortest operation wavelength passing through the edge of the entrance pupil; TDT is a TV distortion for image formation in the optical image capturing module.

9. The movable carrier auxiliary system of claim 1, wherein the at least one lens group comprises four lenses having refractive power, which are constituted by a first lens,

a second lens, a third lens, and a fourth lens in order along an optical axis from an object side to an image side; the at least one lens group satisfies:

$$0.1 \leq \ln TL/HOS \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fourth lens.

10. The movable carrier auxiliary system of claim 1, wherein the at least one lens group comprises five lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, and a fifth lens in order along an optical axis from an object side to an image side; the at least one lens group satisfies:

$$0.1 \leq \ln TL/HOS < 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the fifth lens.

11. The movable carrier auxiliary system of claim 1, wherein the at least one lens group comprises six lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens in order along an optical axis from an object side to an image side; the at least one lens group satisfies:

$$0.1 \leq \ln TL/HOS \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the sixth lens.

12. The movable carrier auxiliary system of claim 1, wherein the at least one lens group comprises seven lenses having refractive power, which are constituted by a first lens, a second lens, a third lens, a fourth lens, a fifth lens, a sixth lens, and a seventh lens in order along an optical axis from an object side to an image side; the at least one lens group satisfies:

$$0.1 \leq \ln TL/HOS \leq 0.95;$$

where HOS is a distance in parallel with the optical axis between an object-side surface of the first lens and an image plane of the at least one lens group; InTL is a distance in parallel with the optical axis from the object-side surface of the first lens to an image-side surface of the seventh lens.

13. The movable carrier auxiliary system of claim 1, wherein the at least one displaying device comprises at least one of a LCD, a LED, an OLED, a plasma projection element, a digital projection element, and a liquid crystal display module.

14. The movable carrier auxiliary system of claim 1, wherein the electrical connector comprises at least one of a flexible circuit board, a copper foil, and an electric wire.

15. The movable carrier auxiliary system of claim 1, wherein the movable carrier auxiliary system is disposed on a movable carrier, and further comprises an image sensing device electrically connected to the at least one control member for sensing an environment brightness inside of the

59

movable carrier, wherein the at least one control member controls a brightness of the at least one displaying device according to the environment brightness.

16. The movable carrier auxiliary system of claim 15, wherein when the environment brightness decreases, the brightness of the image decreases, while when the environment brightness rises, the brightness of the image rises.

17. A movable carrier auxiliary system, comprising:

a first transparent assembly, comprising:

a first incidence surface; and

a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface;

a second transparent assembly disposed on the first exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly; the second transparent assembly comprising:

a second incidence surface; and

a second exit surface, wherein the image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface;

an electro-optic medium layer disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second transparent assembly;

at least one transparent electrode disposed between the first transparent assembly and the electro-optic medium layer;

at least one reflective layer directly disposed on the second exit surface of the second transparent assembly, wherein the electro-optic medium layer is disposed between the first transparent assembly and the at least one reflective layer;

at least one transparent conductive layer disposed between the electro-optic medium layer and the at least one reflective layer;

at least one electrical connector electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer;

at least one control member electrically connected to the at least one electrical connector, wherein when a brightness of the image exceeds a predetermined brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer;

at least one displaying device for displaying an environmental image signal; and

at least one optical image capturing module for capturing and projecting the environmental image signal to the at least one displaying device, wherein the at least one optical image capturing module has at least one lens group; the at least one lens group comprises at least two lenses having refractive power and satisfies:

$$1.0 \leq f/HEP \leq 10.0;$$

$$0 \text{ deg} < HAF < 150 \text{ deg}; \text{ and}$$

$$0.9 \leq 2(ARE/HEP) \leq 2.0;$$

where f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any

60

surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

18. The movable carrier auxiliary system of claim 17, wherein the movable carrier auxiliary system is a vehicle electronic rear-view mirror.

19. The movable carrier auxiliary system of claim 17, wherein a brightness of the at least one displaying device is greater than 1000 nits, and the at least one displaying device exhibit an image with high dynamic range (HDR).

20. The movable carrier auxiliary system of claim 17, further comprising a signal input device electrically coupled to the at least one displaying device for sending a heterogeneous signal that is not from the optical image capturing system to the at least one displaying device for numerical or graphical presentation.

21. The movable carrier auxiliary system of claim 20, wherein the signal input device is a tire pressure detector.

22. The movable carrier auxiliary system of claim 17, wherein the movable carrier auxiliary system is disposed on a movable carrier which is a vehicle, and further comprises a plurality of optical image capturing systems respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle, wherein the external image signal captured by each of the optical image capturing systems could be transmitted to the displaying device, and could be instantly and simultaneously presented to the driver for different viewing directions in a non-overlapping manner or in an image butting manner.

23. The movable carrier auxiliary system of claim 17, wherein the movable carrier auxiliary system is disposed on a movable carrier which is a vehicle, and further comprises at least one at least one movable detector and a plurality of optical image capturing systems respectively disposed on the left/right rear-view mirrors, on the front/rear bumpers, or between the front windshield and the rear windshield inside of the vehicle, wherein when the movable carrier is in a state of shutting down the power system and stopping driving, the movable detector starts to continuously detect whether the movable carrier is collided or vibrated; once the movable carrier is bumped or vibrated, the movable detector starts the video modules to instantly record.

24. The movable carrier auxiliary system of claim 17, further comprising a switch controller and two optical image capturing systems, wherein the movable carrier auxiliary system is disposed on a movable carrier; one of the optical image capturing systems is disposed on a front position of the movable carrier, and another one thereof is disposed on a rear position of the movable carrier; when the movable carrier is on a reverse mode, the monitor could display a rear image of the movable carrier and instantly record the video.

25. The movable carrier auxiliary system of claim 17, further comprising an information communication device, wherein the information communication device is adapted to communicate with a default contact person or organization.

26. The movable carrier auxiliary system of claim 17, further comprising a driving setter and a biological identification device, wherein the driving setter is electrically connected to the biological identification device; the movable carrier auxiliary system is disposed on a movable carrier, wherein when a specific driver enters the movable carrier and faces the biological identification device, an identification is performed and the driving setter is started;

61

the driving setter controls the movable carrier according to parameters preset by an individual driver.

27. A vehicle electronic rear-view mirror, comprising:

a first transparent assembly, comprising:
a first incidence surface; and

a first exit surface, wherein an image enters the first transparent assembly via the first incidence surface, and is emitted via the first exit surface;

a second transparent assembly disposed on the first exit surface, wherein a gap is formed between the second transparent assembly and the first transparent assembly; the second transparent assembly comprising:

a second incidence surface; and

a second exit surface, wherein the image is emitted to the second transparent assembly from the first exit surface and is emitted via the second exit surface;

an electro-optic medium layer disposed in the gap formed between the first exit surface of the first transparent assembly and the second incidence surface of the second transparent assembly;

at least one transparent electrode disposed between the first transparent assembly and the electro-optic medium layer;

at least one reflective layer directly disposed on the second exit surface of the second transparent assembly, wherein the electro-optic medium layer is disposed between the first transparent assembly and the at least one reflective layer;

at least one transparent conductive layer disposed between the electro-optic medium layer and the at least one reflective layer;

at least one electrical connector electrically connected to the electro-optic medium layer, wherein the at least one electrical connector transmits an electrical energy to the electro-optic medium layer to change a transparency of the electro-optic medium layer;

at least one control member electrically connected to the at least one electrical connector, wherein when a brightness of the image exceeds a predetermined certain brightness, the at least one control member controls the at least one electrical connector to supply the electrical energy to the electro-optic medium layer;

at least one displaying device for displaying an environmental image signal; and

at least one optical image capturing module for capturing and projecting the environmental image signal to the at least one displaying device,

62

wherein the at least one optical image capturing module has at least one lens group; the at least one lens group comprises at least two lenses having refractive power and satisfies:

$1.0 \leq f/HEP \leq 10.0;$

$0 \text{ deg} < HAF \leq 150 \text{ deg};$ and

$0.9 \leq 2(ARE/HEP) \leq 2.0,$

where f is a focal length of the at least one lens group; HEP is an entrance pupil diameter of the at least one lens group; HAF is a half of a maximum field angle of the at least one lens group; ARE is a profile curve length measured from a start point where an optical axis of the at least one lens group passes through any surface of one of the at least two lenses, along a surface profile of the corresponding lens, and finally to a coordinate point of a perpendicular distance where is a half of the entrance pupil diameter away from the optical axis.

28. The vehicle electronic rear-view mirror of claim 27, wherein the electro-optic medium layer is selected from an electrochromic layer, a polymer dispersed liquid crystal (PDLC) layer, or a suspended particle device (SPD) layer.

29. The vehicle electronic rear-view mirror of claim 27, wherein the at least one lens group satisfies:

$0.9 \leq ARS/EHD \leq 2.0;$

wherein for any surface of any lens, ARS is a profile curve length measured from a start point where the optical axis passes therethrough, along a surface profile thereof, and finally to an end point of the maximum effective half diameter thereof; EHD is a maximum effective half diameter thereof.

30. The vehicle electronic rear-view mirror of claim 27, further comprising an aperture, wherein the optical image capturing module further satisfies:

$0.2 \leq InS/HOS \leq 1.1;$

where InS is a distance on the optical axis between the aperture and an image plane of the at least one lens group; HOS is a distance in parallel with the optical axis between an object-side surface of one of the at least two lenses of the at least one lens group furthest from the image plane and the image plane.

* * * * *