

(43) International Publication Date
27 October 2016 (27.10.2016)

(51) International Patent Classification:

B01D 35/143 (2006.01) **B05B 12/02** (2006.01)
B05B 1/18 (2006.01) **E03C 1/02** (2006.01)
B05B 12/00 (2006.01) **E03C 1/04** (2006.01)

(21) International Application Number:

PCT/US2016/027714

(22) International Filing Date:

15 April 2016 (15.04.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/149,877 20 April 2015 (20.04.2015) US

(71) Applicant: **CHEN, Chung-Chin** [US/US]; Bacon & Thomas, PLLC, 625 Slaters Lane, 4th Flr., Alexandria, Virginia 22314 (US).

(72) Inventors; and

(71) Applicants : **CAI, Ying Lin** [CN/CN]; No. 6, Lane 2, Zhan Li Xia Street, Ronggui Boulevard, Shunde District, Foshan City, Guangdong, 528303 (CN). **HSU, Chao Fou**; 9Fl., No. 16, Lane 417, Huangshing Rd., Sanmin Chiu, Kaohsiung, Kaohsiung City, 807 (TW).(74) Agent: **URCIA, Benjamin Edward**; Bacon & Thomas, PLLC, 625 Slaters Lane, 4th Flr., Alexandria, Virginia 22314 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: HAND-HELD SHOWER HEAD CAPABLE OF MEASURING AND SUGGESTING REPLACEMENT OF FILTERING CORE HANDLE




FIG. 26

(57) Abstract: A hand-held shower head capable of measuring and suggesting replacement of filtering core handle includes a lower shell, an upper shell, a battery mount, a signal circuit device and a water flow measuring unit containing an impeller shaft, a magnetic element and a supporter. The water flow measuring unit and impeller shaft are disposed in a lower handle filter cartridge mounting section of the lower shell while the battery mount and a battery contained therein are disposed in an upper handle filter cartridge mounting section of the upper shell, and both the lower and upper handle filter cartridge mounting sections about the handle filter cartridge to provide an even overall weight distribution.

Title**HAND-HELD SHOWER HEAD CAPABLE OF MEASURING AND SUGGESTING REPLACEMENT OF FILTERING CORE HANDLE**

This application claims the benefit of provisional U.S. Patent Application number
5 62/149,877, filed April 20, 2015, and incorporated herein by reference.

Field Of The Present Invention

The present invention relates to a hand-held shower head capable of measuring and suggesting replacement of a filtering core handle. According to a preferred embodiment, the filtering core handle includes a water flow measuring unit and impeller shaft disposed
10 to abut a handle filter cartridge such that the shower head has a move even, less top heavy overall weight distribution than a prior handheld showerhead with filter replacing pre-alarm device.

Background Of The Invention

The inventor's U.S. Patent No. 7,468,127, issued January 6, 2005, and entitled
15 "Hand-Held Shower Head with Filter Replacing Pre-Alarm Assembly," disclosed a first generation of a showerhead series, the most recent upgrade of which was disclosed in a family of patent applications of the inventor entitled "Hand Held Shower Head with Filter Replacing Pre-Alarm Assembly" and including Taiwan Patent Appl. No. 101129129, Mainland China Patent Appl. No. 201210425572.5, U.S. Patent Appl. Ser. No. 13/729,063
20 and U.S. Patent Publication No. 2014/0042240, UK Patent Appl. No. 1308734.11308734.1, German Patent Appl. No. 102013108371.4, Japanese Patent No. 5594615, and Korean Patent No. 10-147159, The foregoing patents and pending patent applications entitled "Hand Held Shower Head with Filter Replacing Pre-Alarm

Assembly” disclose a showerhead shell **100**, an internal lid **70**, an impeller **80**, a hood **90**, a detachable alerting pod **200** and a signal circuit device **300**, in which

the showerhead shell **100** is a plastic hollow casing extruded into unitary piece having a shelf **103** that encompasses an obverse side **101** with a set of peripheral male threads **120** and a reverse side **102** to form an integral body. The showerhead shell **100** has a handle butt **104** having a tapered periphery and from which a tube having threads **106** extends to connect with corresponding threads of a handle filter cartridge **60**. A hollow water entry **105** extends through the handle butt **104**, and a receptacle **107** is formed in an interior of the obverse side **101**. A water exit bore base **109** and an impeller well **108** with an impeller hub notch **110** extend inwardly into an interior bottom surface of the receptacle **107**, and a water inlet channel **111** is formed to communicate between the hollow water entry **105** in the handle butt **104** and an adjacent side of the impeller well **108**, while a water outlet channel **112** is formed to communicate between the water exit bore base **109** and the other side of the impeller well **108** (as indicated by the dotted line portion shown in **FIG. 3**). A round recess socket **113** extends inwardly into the reverse side **102** of the shelf **103** to receive a detachable alerting pod **200** such that a terminal latching notch **114** is created in the distal internal wall (shown on the left in the main and enlarged views of **FIG. 2**) of the recess socket **113** while a snap latching arm **115** extends from the proximal internal wall (shown on the right side in **FIG. 2**) of the recess socket **113**. In addition, a finger guiding groove **116** extends into the top surface of the handle butt **104** abutting the rim of the reverse side **102**.

An internal lid **70**, which is a planiform disk tightly attached on the bottom side of the receptacle **107** in the showerhead shell **100**, has an inward surface **71** facing toward the

obverse side **101** of the showerhead shell **100**, an impeller hub notch **72** formed therein to correspond with the impeller hub notch **110** of the impeller well **108**, a water outlet **73** formed therein to correspond with the water exit bore base **109** of the receptacle **107** in the showerhead shell **100**, and a plurality of screw holes **74** extending through the internal lid
5 **70** at a periphery thereof such that the screw holes **74** spread around the impeller hub notch **72** and water outlet **73**.

An impeller **80**, which is a cylindrical profile body with plural radially extending curved vanes, has two central protruding hubs **81** coaxially disposed at a respective top side and bottom side thereof, and a magnetic element **82** embedded in the top cut of one
10 vane such that the impeller **80** is freely rotatable in the impeller well **108** by means of the two central protruding hubs **81** being mated with the impeller hub notch **110** of the impeller well **108** and the impeller hub notch **72** of the internal lid **70** respectively (as shown in **FIG. 14**).

A hood **90**, which is a plastic disk extruded into a unitary piece, is provided with
15 female threads **91** that extend around a bottom rim of the hood and a plurality of water spray holes **92** spread over the surface thereof so that the female threads **91** can mate with the male threads **120** on the obverse side **101** of the showerhead shell **100** by screwing engagement, so that the water spray holes **92** enable the water in the receptacle **107** on the obverse side **101** of the showerhead shell **100** to jet out.

20 The alerting pod **200**, which is a plastic capsule made by high frequency or ultrasonic fusion of a plastic transparent lid **201** and a plastic mounting cavity **202** to form a hermetically watertight integral body to be embedded into the round recess socket **113** of the reverse side **102** of the showerhead shell **100** for accommodating the signal circuit

device **300** therein (as shown in **FIGS. 10** and **11**). Alerting pod **200** has a terminal latching projection **203** created on a heading rim of the alerting pod (left in **FIGS. 1** and **8**) while a snap latching notch **204** is formed on the rear rim of the alerting pod (right in **FIG. 8**), and two passive recharging electrodes **205** are firmly inset in an internal bottom wall of the mounting cavity **202**, with each individual end of the two passive recharging electrodes **205** protruding out of the mounting cavity **202** (as shown on the lower side in the enlarged view in **FIG. 8**).

The signal circuit device **300**, which is contained in the alerting pod **200**, includes a microprocessor **301**, an LCD display circuit **302** electrically connected to the microprocessor **301** with its location near the transparent lid **201**, a rechargeable battery **303** electrically connected to the microprocessor **301**, and a magnetic reed switch **304** securely inset on the internal bottom side of the mounting cavity **202** (as shown in **FIG. 7**) such that the rechargeable battery **303** is connected with the passive recharging electrode **205** of the alerting pod **200** via a pair of wires **W** (as shown on the lower side of the enlarged view in **FIG. 8**).

Assembly steps for the shower head of **FIGS. 1** to **8** are illustrated in **FIGS. 9** to **16**, as follows:

a. Align the protruding hub **81** (upper side in **FIG. 9**) of the impeller **80** having magnetic element **82** in one vane with the impeller hub notch **110** of the impeller well **108** in the obverse side **101** of the showerhead shell **100**, and then put the protruding hub **81** into the impeller hub notch **110** so that the magnetic element **82** of the impeller **80** faces toward the recess socket **113** of the showerhead shell **100** (as shown in **FIG. 9**).

b. Attach the inward surface **71** of the internal lid **70** against the top surface of the receptacle **107** in the showerhead shell **100** so that the impeller hub notch **72** of the internal lid **70** sleeves over the other protruding hub **81** of the impeller **80** (lower side in **FIG. 10**), drive every self-tapping screw **S** into the internal bottom wall of the receptacle
5 **107** via corresponding screw hole **74** of the internal lid **70** respectively so that the internal lid **70** is closely attached with the top surface of the receptacle **107** to allow the impeller **80** to freely rotate in the impeller well **108** (as shown in **FIG. 11**).

c. Mate the female threads **91** on the hood **90** with the male threads **120** on the obverse side **101** of the showerhead shell **100** by screwing engagement to complete the
10 assembly for the obverse side **101** of the showerhead shell **100** (as shown in **FIG. 12**).

d. Align and mate the terminal latching projection **203** in the mounting cavity **202** of the alerting pod **200** with the terminal latching notch **114** in the recess socket **113** of the reverse side **102** of the showerhead shell **100** (as shown in **FIG. 13** and in the left upper enlarged view of **FIG. 14**) so that the bottom side of the snap latching notch **204** in the
15 mounting cavity **202** will contact with the top side of the snap latching projection **115** in the recess socket **113** (right side of the upper enlarged view shown in **FIG. 14**). Then, thoroughly latch the snap latching notch **204** in the mounting cavity **202** with the snap latching projection **115** of the recess socket **113** by forcibly applying downward force **F1** over the transparent lid **201** (enlarged view shown in **FIG. 15**) so that the terminal latching
20 projection **203** in the mounting cavity **202** also fully latches with the terminal latching notch **114** in the recess socket **113** simultaneously (enlarged view shown in **FIG. 16**) to complete the assembly for the alerting pod **200** and showerhead shell **100**. Thus, the overall assembly steps in the shower head of **FIGS. 1 to 8** are finished.

For operation of the shower head of **FIGS. 1 to 8**, please further refer to **FIGS. 17 to 19**. Prior to operating the shower head, first screw the handle filter cartridge **60** with the tubular threads **106** on the handle butt **104** of the showerhead shell **100**, and then connect a detachable water pipe **P** to the handle filter cartridge **60** (as shown in **FIG. 17**).

5 Once the shower head is hooked up, the tap water enters into the impeller well **108** sequentially via the handle filter cartridge **60**, the water entry **105** in the handle butt **104**, and the water inlet channel **111**, to drive the impeller **80** rotate. Then, the tap water in the impeller well **108** flows out of the water outlet **73** in the internal lid **70** sequentially via the water outlet channel **112** and the water exit bore base **109**. Finally, the tap water is jetted

10 out of the water spray holes **92** in the hood **90** (as shown in **FIGS. 18 and 19**). For each rotation of the impeller **80** driven by the running water, the magnetic element **82** thereof simultaneously switches the magnetic reed switch **304** in the alerting pod **200** one time to induce a switching signal, which is relayed to the microprocessor **301** in the signal circuit device **300** for being processed to generate accumulation data at certain preset intervals for

15 further transmission to the LCD display circuit **302** for displaying a related quantity of water flow thereon in accordance with following formula:

quantity of water flow (Q) = cross sectional area (A) times flow velocity (V)

The foregoing quantity of water flow (Q) shown in the LCD display circuit **302** is the accumulated quantity of water that has flowed through the handle filter cartridge **60**,

20 which relates to the total quantity of water flow used during the overall service life of the handle filter cartridge **60**. Moreover, the foregoing quantity of water flow (Q) is pre-stored in the microprocessor **301**. Thereby, a user of the shower head can get real time statistical data of the total filtered water quantity that has flowed through handle filter cartridge **60** by simply looking at the LCD display circuit **302** via the transparent lid **201** of

the alerting pod **200**. Once the total filtered water quantity that has flowed through handle filter cartridge **60** reaches (or nearly reaches) a predetermined critical value for the rated service life time of the specific handle filter cartridge **60**, the microprocessor **301** will send an alerting signal with current data of the total filtered water quantity to the LCD display circuit **302** for reminding the user that it is time to replace the handle filter cartridge **60** in order to ensure good quality of the handle filter cartridge **60** and the water filtered thereby. Therefore, the user can avoid the harmful consequences to health caused by unclean water, which occurs as a result of missing the replacement time and continuing to use the ineffective handle filter cartridge **60**.

For replacing or recharging the handle filter cartridge **60**, please further refer to **FIGS. 20 to 25**. The hand held shower head with filter replacing pre-alarm device of shown in **FIGS. 20 TO 25** further includes a battery recharging mount **400**, which includes a battery recharging cavity **401** with a pair of active recharging electrodes **402** to securely contact the corresponding pair of protruding ends of the passive recharging electrodes **205** in the mounting cavity **202** of the alerting pod **200**, for performing a recharging operation on the rechargeable battery **303** in the alerting pod **200**. The profile of the battery recharging cavity **401** is arranged to resemble, but is slightly bigger than, the profile of the mounting cavity **202** in the alerting pod **200** to adequately accommodate the mounting cavity **202** therein for performing the recharging operation on the rechargeable battery in the alerting pod (as shown in **FIGS. 24 and 25**).

The power of the rechargeable battery **303** in the alerting pod **200** might run out when the handle filter cartridge **60** has been replaced several times. In that event, to replace or recharge the handle filter cartridge **60**, first lift the marginal edge of the

transparent lid **201** in the alerting pod **200** by hooking one finger along the finger guiding groove **116** in the reverse side **102** of the showerhead shell **100** (as shown in **FIG. 20**), and then applying an upward force **F2** on the mounting cavity **202** (as shown in **FIG. 21**) until the snap latching notch **204** of the alerting pod **200** releases the snap latching projection **115** in the recess socket **113** of the showerhead shell **100** (as shown on the right upper side of the enlarged view in **FIG. 21**). Second, continuously apply an upward force **F2** on the mounting cavity **202**, the entire alerting pod **200** will fully detach from the recess socket **113** in the reverse side **102** of the showerhead shell **100** (as shown in **FIGS. 22** and **23**). Finally, insert the detached alerting pod **200** into the battery recharging cavity **401** of the battery recharging mount **400**, at which time the rechargeable battery **303** in the alerting pod **200** will be properly recharged (as shown in **FIGS. 24** and **25**).

The prior art handheld showerhead with filter-replacement pre-alarm device does achieve the expected effects after having been practically tested many times. However, some issues remain, such as uneven top-heavy weight distribution, accelerated aging fatigue, and unnecessary purchase waste, as described below.

1. Uneven top-heavy weight distribution:

Please refer to **FIGS. 1, 7, 17** and **18**. In the prior art handheld showerhead with filter replacing pre-alarm device shown therein, some components such as rechargeable battery **303** and magnetic reed switch **304** with related parts are inserted into the alerting pod **200** of the showerhead shell **100**, while some components such as impeller **80** and internal lid **70** with related parts are inserted into the impeller well **108** of the showerhead shell **100** so that the bulky showerhead shell **100** becomes heavier at the top than the slender handle of the handle filter cartridge **60** at the bottom. On the other hand, in the

conventional market-available handheld shower head with built-in filter but not pre-alarm device, there is no such disadvantage that the bulky showerhead shell **100** is heavier at the top than the slender handle of the handle filter cartridge **60** at the bottom. Accordingly, the showerhead set with the pre-alarm device can become a heavy burden for younger or older users, causing their arms to ache when using the showerhead set. Moreover, the top-heavy showerhead set can easily fall to the floor during a shower due to the uneven weight distribution. Consequently, the components in the showerhead set not only may have a shortened service life, but can also quickly malfunction with respect to the water quantity measurement and pre-alarm functions.

10 2. Accelerated aging fatigue:

 Please refer to **FIGS. 22 to 25**. To carry out recharging of the rechargeable battery **303** in the prior art hand held shower head with filter-replacement pre-alarm device, the alerting pod **200** must be taken off from the round docking socket **113** of the showerhead shell **100** and reinserted into the round recess socket **113** of the showerhead shell **100**. By frequently repeating such a recharging operation, damage to the snap latching projection **115** in the round recess socket **113** of the showerhead shell **100** will be hastened by aging fatigue. Consequently, the round recess socket **113** of the showerhead shell **100** will not have a shortened service life, but the user will be obliged to replace the integral showerhead shell **100** prematurely.

20 3. Unnecessary purchase waste:

 Please refer to **FIGS. 8 and 24**. If the user wants to recharge the rechargeable battery **303** in the prior art hand held shower head with filter-replacement pre-alarm device, the rechargeable battery **303** must be taken off from the alerting pod **200** of the

showerhead shell **100** and reinserted into the battery recharging cavity **401** of the battery recharging mount **400** so that the active recharging electrode **402** can electrically connect with the passive recharging electrode **205** of the mounting cavity **202**. As a result, both the active recharging electrode **402** and passive recharging electrode **205** will inevitably rust
5 because of exposure to ambient moisture, so that a bad electrical connection between active recharging electrode **402** and passive recharging electrode **205** will happen sooner or later. The bad electrical connection between active recharging electrode **402** and passive recharging electrode **205** will not only shorten the service life but also oblige the user to prematurely replace the integral showerhead shell **100**.

10 All of the above-described drawbacks aforesaid are harmful to the promotion of the prior art handheld showerhead with filter-replacement pre-alarm device because those drawbacks not only cause extra expense in that the user must frequently replace the filter cartridge, but also reduce motivation for the user to continuously use the product in the first place. In addressing those issues, the inventor of the present invention has diligently
15 researched and developed a new contrivance to overcome the foregoing issues, resulting the present invention.

Summary Of The Invention

According to a preferred embodiment of the present invention, the problem of unequal weight distribution in a hand-held shower head capable of measuring and
20 suggesting replacement of a filtering core handle is addressed by providing a showerhead with an integral lower shell, upper shell and handle containing a handle filter cartridge, an integral battery mount and battery lid with an embedded button-shaped battery, a signal circuit device, a transparent cover, a spray hood, as well as a water flow measuring unit

containing an impeller shaft in axial flow mode, an inducting magnet and a supporter in axial flow mode. The water flow measuring unit and impeller shaft are disposed in a lower handle filter cartridge mounting section of the showerhead lower shell while the battery mount and button-shaped battery are disposed in an upper handle filter cartridge mounting section of the showerhead upper shell, and both the lower and upper handle filter cartridge mounting sections abut the handle filter cartridge such that the overall weight distribution of the showerhead is more even than that of the prior art handheld showerhead with filter-replacement pre-alarm device. Accordingly, the issue of uneven top-heavy weight distribution and resulting harmful effects incurred in the prior art handheld showerhead with filter-replacement pre-alarm device are all eliminated.

The problem of cumbersome battery replacement is also solved, in a preferred embodiment of the present invention, providing a battery lid that can be taken off the battery mount during replacement of a button-shaped battery by simply inserting a coin into the rotatable notch of the battery lid, and turn the battery lid to let the integral battery lid together with button-shaped battery be taken out of the battery mount of the showerhead upper shell, the reverse steps being subsequently performed upon replacement of the used battery by a new button-shaped battery. As a result, some of the drawbacks incurred during recharging procedures in the prior art, which result from repeated detaching of the alerting pod from the groove base in the back side of the showerhead shell and reinserting the alerting pod back into the groove base in the back side of the showerhead shell, can be eliminated.

Brief Description Of The Drawings

FIG. 1 is an exploded cross sectional view of a conventional hand held shower head with filter-replacement pre-alarm assembly.

FIG. 2 is a cross sectional view taken against the section line 2-2 from previous FIG. 1.

5 **FIG. 3** is a cross sectional view taken against the section line 3-3 from previous FIG. 2.

FIG. 4 is a cross sectional view taken against the section line 4-4 from previous FIG. 1.

10 **FIG. 5** is a cross sectional view taken against the section line 5-5 from previous FIG. 1.

FIG. 6 is a cross sectional view taken against the section line 6-6 from previous FIG. 1.

FIG. 7 is a perspective exploded view for an alerting pod in the conventional hand held shower head with filter replacing pre-alarm assembly”.

15 **FIG. 8** is a cross sectional view taken against the section line of 8-8 from previous FIG. 1.

FIG. 9 is a first assembly illustrating view of the conventional hand held shower head with filter replacing pre-alarm assembly.

20 **FIG. 10** is a second assembly illustrating view of the conventional hand held shower head with filter replacing pre-alarm assembly.

FIG. 11 is a third assembly illustrating view of the conventional hand held shower head with filter replacing pre-alarm assembly.

FIG. 12 is a fourth assembly illustrating view of the conventional hand held shower head with filter replacing pre-alarm assembly.

FIG. 13 is a first coupling illustrating view of an alerting pod with a showerhead shell in the conventional hand held shower head with filter replacing pre-alarm assembly.

5 **FIG. 14** is a second coupling illustrating view of the alerting pod with a showerhead shell in the conventional hand held shower head with filter replacing pre-alarm assembly.

FIG. 15 is a third coupling illustrating view of the alerting pod with a showerhead shell in the conventional hand held shower head with filter replacing pre-alarm assembly.

10 **FIG. 16** is a fourth coupling illustrating view of the alerting pod with a showerhead shell in the conventional hand held shower head with filter replacing pre-alarm assembly.

FIG. 17 is a perspective view showing assembly of a handle filter cartridge to a hand-held shower head capable of measuring and suggesting replacement of the filter
15 according to a preferred embodiment of the present invention.

FIG. 18 is a cross sectional view taken against the section line 18-18 from previous FIG. 17.

FIG. 19 is a cross sectional view taken against the section line 19-19 from previous FIG. 18.

20 **FIG. 20** is a first illustrative view showing lifting of the transparent lid of an alerting pod from a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 21 is a second illustrative view showing the lifting of the transparent lid of the alerting pod from a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 22 is a third illustrative view showing the lifting of the transparent lid of the alerting pod from a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 23 is a fourth illustrative view showing the lifting of the transparent lid of the alerting pod from a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 24 is a perspective schematic view showing detaching of the alerting pod from a battery charger mount of a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 25 is a perspective schematic view showing inserting of the alerting pod into a battery charger mount of a showerhead shell in the conventional handheld shower head with filter replacing pre-alarm device.

FIG. 26 is an exploded perspective view of a showerhead of the first exemplary embodiment of the present invention.

FIG. 27 is a cross sectional view taken against the section line 27-27 from previous FIG. 26.

FIG. 28 is a cross sectional view taken against the section line 28-28 from previous FIG. 26.

FIG. 29 is a cross sectional view taken against the section line 29-29 from previous FIG. 26.

FIG. 30 is a lateral view of a battery lid in the first exemplary embodiment of the present invention.

5 **FIG. 31** is a cross sectional view taken against the section line 31-31 from previous FIG. 26.

FIG. 32 is a perspective view of a water flow measuring unit in the first exemplary embodiment of the present invention.

10 **FIG. 33** is a cross sectional view taken against the section line 33-33 from previous FIG. 32.

FIG. 34 is a cross sectional view taken against the section line 34-34 from previous FIG. 32.

FIG. 35 is a perspective view of an impeller shaft in axial flow mode in the first exemplary embodiment of the present invention.

15 **FIG. 36** is a cross sectional view taken against the section line 36-36 from previous FIG. 35.

FIG. 37 is a perspective view of an inducting magnet in the first exemplary embodiment of the present invention.

20 **FIG. 38** is a cross sectional view taken against the section line 38-38 from previous FIG. 37.

FIG. 39 is a perspective view of a supporter in axial flow mode in the first exemplary embodiment of the present invention.

FIG. 39a is a lateral view of the supporter in axial flow mode in the first exemplary embodiment of the present invention.

FIG. 40 is a cross sectional view taken against the section line 40-40 from previous FIG. 39.

5 **FIG. 41** is a first schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 42 is a second schematic view showing assembly of the first exemplary embodiment of the present invention.

10 **FIG. 43** is a third schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 44 is a fourth schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 45 is a fifth schematic view showing assembly of the first exemplary embodiment of the present invention.

15 **FIG. 46** is a sixth schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 47 is a seventh schematic view showing assembly of the first exemplary embodiment of the present invention.

20 **FIG. 48** is an eighth schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 49 is a ninth schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 50 is a tenth schematic view showing assembly of the first exemplary embodiment of the present invention.

FIG. 51 is a first illustrative view showing inserting of a battery lid into a battery mount or showing detaching of a battery lid from the battery mount in the first exemplary
5 embodiment of the present invention.

FIG. 52 is a second illustrative view showing inserting of the battery lid into a battery mount or showing detaching of the battery lid from the battery mount in the first exemplary embodiment of the present invention.

FIG. 53 is a first illustrative view showing assembly of a spray hood to a
10 showerhead lower shell in the first exemplary embodiment of the present invention.

FIG. 54 is a second illustrative view showing assembly of the spray hood with the showerhead lower shell in the first exemplary embodiment of the present invention.

FIG. 55 is a perspective schematic view showing assembly of a handle filter cartridge to the showerhead in the first exemplary embodiment of the present invention.

FIG. 56 is a cross sectional view taken against the section line 56-56 from
15 previous FIG. 55.

FIG. 57 is a cross sectional view taken against the section line 57-57 from previous FIG. 56.

FIG. 58 is a cross sectional view taken against the section line 58-58 from
20 previous FIG. 57.

FIG. 59 is an exploded perspective view of a modified showerhead lower shell and modified showerhead upper shell with integrated latches for joining the upper and lower shells according to a second exemplary embodiment of the present invention.

FIG. 60 is a cross sectional view taken against the section line 60-60 from
5 previous FIG. 59.

FIG. 61 is a cross sectional view taken against the section line 61-61 from previous FIG. 59.

FIG. 62 is a first illustrative view showing assembly of the modified showerhead lower shell and modified showerhead upper shell in the second exemplary embodiment of
10 the present invention.

FIG. 63 is second illustrative view showing assembly of the modified showerhead lower shell and modified showerhead upper shell in the second exemplary embodiment of the present invention.

FIG. 64 is a cross sectional view a modified showerhead lower shell according to a
15 third exemplary embodiment of the present invention.

FIG. 65 is a cross sectional view for the modified showerhead upper shell in the third exemplary embodiment of the present invention.

FIG. 66 is first assembly illustrative view the modified showerhead lower shell and modified showerhead upper shell in the third exemplary embodiment of the present
20 invention.

FIG. 67 is second illustrative view showing assembly of the modified showerhead lower shell and modified showerhead upper shell in the third exemplary embodiment of the present invention.

FIG. 68 is a cross sectional view showing assembly of the handle filter cartridge with the modified and joined together showerhead lower shell and showerhead upper shell in the third exemplary embodiment of the present invention.

Detailed Description Of The Preferred Embodiments

Please refer to **FIGS. 26 to 40** and **FIG. 49**. The hand-held shower head capable of measuring and suggesting replacement of filtering core handle of the first exemplary embodiment of the present invention includes an integrated showerhead lower shell **10**, upper shell **20**, and handle containing a handle filter cartridge **60**, an integrated battery mount **26** and battery lid **30** with an embedded button-shaped battery **B**, a signal circuit device **300**, a transparent cover **40**, a spray hood **90**, as well as a water flow measuring unit **50** containing an impeller shaft in axial flow mode **500**, an inducting magnet **600**, and a supporter in axial flow mode **700** (as shown in **FIG. 26**).

The showerhead lower shell **10**, which is a plastic hollow casing extruded into a unitary piece, includes a shelf **13** with a front side **11** and a reverse side **12** that form an integral body such that the shelf **13** has an extending lower adapting section **14** that includes a distal joint cylinder **141** with a set of male threads on an outer periphery thereof and that extends towards the handle of the showerhead for securely joining with the handle filter cartridge **60**. The front side **11** has an internal inwardly-extending water inlet groove **15**, with a water inlet channel **151** extending through a distal end of tubular adapter **16** towards the lower adapting section **14**, and a set of rim male threads **17** formed on an outer

periphery thereof for mating with the corresponding spray hood **90**. The reverse side **12** has two raised cylinders **121** with internal female threads, the cylinders **121** extending outwardly from a top surface of the shelf **13**.

The showerhead upper shell **20**, which is a plastic casing extruded into a unitary
5 piece for suitably covering the back side **12** of the showerhead lower shell **10**, includes a shelf **23** having a front side **21** and a reverse side **22** and formed as an integral body, wherein the shelf **23** has an extending upper handle filter cartridge mounting section **24** that extends towards the handle of the showerhead such that the profiles and sizes of the shelf **23** and extending upper handle filter cartridge mounting section **24** are the same as
10 those of the corresponding shelf **13** and lower handle filter cartridge mounting section **14** of the showerhead lower shell **10**. On the top surface of the front side **21**, a viewing window **25** is created over the rear thereof while near the upper handle filter cartridge mounting section **24**, a battery mount **26** is created with two internal projections **261** in the internal vertical wall and an internal electrical battery contact **262** in the internal bottom.

15 The battery lid **30**, which is embedded into the battery mount **26** of the showerhead upper shell **20**, includes a lid rotating notch **31** created on the top surface thereof, a battery cavity **32** created in the bottom section thereof for holding a button-shaped battery **B** available in the market (as shown in **FIGS. 49** and **50**), and two snap notches **33** created in the lateral wall thereof for securely latching with corresponding two internal projections
20 **261** of the battery mount **26** in the showerhead upper shell **20**.

The transparent cover **40**, which is a transparent cover extruded into a unitary piece for being wrapped by the viewing window **25** in the front side **21** of the showerhead upper shell **20**, includes a holding cavity **41** extending inwardly into the bottom side of the cover

40 for containing the microprocessor **301** and LCD display circuit **302** of the signal circuit device **300**, and a pair of bored holding lugs **42** extending from opposed sides of the cover **40** for mating with a corresponding pair of raised cylinders with internal female threads **121** in the back side **12** of showerhead lower shell **10** by means of screws **S**.

5 The water flow measuring unit **50**, which is a stacked body having a two-section configuration, includes an upper section of an upper hollow column **52**, a lower section of a base hollow column **51**, and a water channel **53** that runs through both the base hollow column **51** and upper hollow column **52**. The base hollow column **51** has a sealing ring **511** inlaid into the circumference thereof, and the upper hollow column **52** is flanked by a
10 hollow pillar **55** with a tubular opening **551** for accommodating a magnetic reed switch **304** (as shown in **FIGS. 32** and **44**), wherein the outer diameter of the base hollow column **51** is slightly less than the inner diameter of the distal joint cylinder **141** of the extending lower handle filter cartridge mounting section **14** in the showerhead lower shell **10**, which enables the water flow measuring unit **50** to be completely inserted into the distal
15 joint cylinder **141** in the showerhead lower shell **10**. The water channel **53** includes a plurality of blocking vanes **54** radially disposed in the upper portion thereof on a downstream side of the impeller such that the bushing formed by all inward blocking vanes **54** embraces a central suspended body composed of an upper baffle **541** and a lower docking notch **542** (as shown in **FIGS. 32** through **34**).

20 The spray hood **90**, which is a plastic disk extruded into a unitary piece, has female threads **91** extending around the bottom rim thereof and a plurality of water spray holes **92** spread over the surface of the spray hood **90** so that the female threads **91** can mate with the rim male threads **17** on the front side **11** of the showerhead lower shell **10** by screwing

engagement while the water spray holes **92** enable the water in the water inlet groove **15** on the front side **11** of the showerhead lower shell **10** to jet out.

The impeller shaft **500**, which is inserted into the water channel **53** in the water flow measuring unit **50**, includes a bottom central bushing **501**, an upper axial docking projection **502**, a plurality of circumferential spiral vanes **503** and a bottom round gapped receptacle **504** encompassed by the bottom ends of the spiral vanes **503** (as shown in **FIGS. 35 and 36**).

The inducting magnet **600**, which is a truncated section of a cylindrical magnet placed in the bottom round gapped receptacle **504** of the impeller shaft **500**, includes a central bushing **601** (as shown in **FIGS. 37 and 38**) that runs through the inducting magnet **600**. The diameter of the central bushing **601** is the same as and in alignment with that of the central bushing **501** in the impeller shaft **500** (as shown in **FIGS. 42 through 44**).

The supporter **700**, which coupled to the impeller shaft **900** via the inducting magnet **910**, includes a cylindrical mount **701**, a metallic supporting shaft **702**, a supporting tripod **703** with three radial ribs and a supporting base **704** located at an upstream end of the water channel. The supporting base **704** is configured under the radial ribs of the supporting tripod **703** (as shown in **FIG. 39a**), such that the metallic supporting shaft **702** is centrally erected at the bushing formed by all inward radial ribs of the supporting tripod **703** (as shown in **FIGS. 39 and 40**).

The signal circuit device **300**, which is accommodated in the holding cavity **41** under the transparent cover **40**, includes a microprocessor **301**, a LCD display circuit **302**, and a magnetic reed switch **304**, which is embedded in the tubular hollow **551** of the flanked hollow pillar **55** for the water flow measuring unit **50** (as shown in **FIGS. 26 and**

34), wherein the microprocessor **301** is respectively connected to the electrical battery contact **262** in the battery mount **26** of the showerhead upper shell **20** and the magnetic reed switch **304** in the tubular passage **551** of the hollow pillar **55** on the water flow measuring unit **50** via electric wires **L** (as shown in **FIG. 49**). The button-shaped battery **B**,
5 which is embedded in the battery cavity **32** under the battery lid **30**, supplies power to the related power-consuming components of the signal circuit device **300**. and may be either a nickel-chromium battery, a nickel battery or a lithium battery, with the magnetic reed switch **304** being replaceable by a Hall-effect component.

Please refer to **FIGS. 41** to **52**. The assembly procedure for the first exemplary
10 embodiment of the present invention is stepwise performed as follows.

a. First, the inducting magnet **600** is placed in the round gapped receptacle **504** of the impeller shaft **500** (as shown in **FIG. 41**) so that the diameter of the central bushing **601** is in alignment with that of the central bushing **501** in the impeller shaft **500**. The metallic supporting shaft **702** is then sequentially inserted through the central bushing **601**
15 of the inducting magnet **600** and the central bushing **501** of the impeller shaft **500** respectively (as shown in **FIG. 42**).

b. Second, the impeller shaft **500** is inserted into the water channel **53** of the water flow measuring unit **50** by facing the axial docking projection **502** thereof toward the entrance of the water channel **53** until the axial docking projection **502** touches against the
20 docking notch **542** of the blocking vanes **54** (as shown in **FIG. 43**), and the magnetic reed switch **304** is then placed into the tubular hollow **551** in the hollow pillar **55** of the water flow measuring unit **50** (as shown in **FIG. 44**).

c. Third, the upper hollow column **52** is oriented to face forwards, and the integral water flow measuring unit **50** from previous step b is placed into the distal joint cylinder with external male threads **141** in the lower handle filter cartridge mounting section **14** of the showerhead lower shell **10** such that the front opening of the upper hollow column **52** wraps over the tubular adapter **16** of the showerhead lower shell **10**. Meanwhile, the sealing ring **511** of the base hollow column **51** is allowed to hermetically contact the internal wall of the distal joint cylinder with external male threads **141** to prevent water leakage (as shown in **FIGS. 45** and **46**).

d. Fourth, the magnetic reed switch **304** is connected to the microprocessor **301** of the signal circuit device **300** via electric wire **L**, and the LCD display circuit **302** and microprocessor **301** of the signal circuit device **300** are embedded into the holding cavity **41** of the transparent cover **40** (as shown in **FIG. 46**), after which the two lugs **42** of the transparent cover **40** are jointed to the corresponding raised cylinders with internal female threads **121** in the back side **12** of the showerhead lower shell **10** by means of screws **S** (as shown in **FIG. 47**).

e. Fifth, the microprocessor **301** of the signal circuit device **300** is connected to the electrical battery contact **262** in the battery mount **26** of the showerhead upper shell **20** via electric wire **L**, and then the showerhead upper shell **20** is fused with the showerhead lower shell **10** via a high frequency fusing method after alignment and contact of the viewing window **25** of the showerhead upper shell **20** with the back side **12** of the showerhead lower shell **10**.

f. Finally, the two snap notches **33** of the battery lid **30** are firmly aligned with and latched to the corresponding two projections **261** in the battery mount **26** of the

showerhead upper shell **20** after insertion of the button-shaped battery **B** into the battery lid **30** (as shown in **FIGS. 47** through **52**). Meanwhile, the button-shaped battery **B** contacts the electrical battery contact **262** in the battery mount **26** of the showerhead upper shell **20** so that power from the button-shaped battery **B** can be suitably supplied to the microprocessor **301**, LCD display circuit **302** and magnetic reed switch **304** of the signal circuit device **300** to complete the assembly for the first exemplary embodiment of the present invention.

Based on the quantity of water flow (Q), the total filtered water quantity flowing through the handle filter cartridge **60** is measured and displayed on the LCD display circuit **302**, and the result is stored by the microprocessor **301**. The result can be processed to predict the remaining service life time of the handheld showerhead. Thereby, a user of the showerhead can get real time statistical data of the total filtered water quantity that has flowed through handle filter cartridge **60** by simply looking at the LCD display circuit **302** via the transparent cover **40** of the viewing window **25** in the showerhead upper shell **20**.

Once the total filtered water quantity that has flowed through handle filter cartridge **60** reaches (or nearly reaches) a predetermined critical value for the rated service life time of the specific handle filter cartridge **60**, the microprocessor **301** will send an alerting signal with current data of the total filtered water quantity to the LCD display circuit **302** for reminding the user that it is time to replace the handle filter cartridge **60** in order to assure good quality of the handle filter cartridge **60** and the water filtered thereby. Therefore, the user can avoid the harmful consequences to health caused by unclean shower water W that would result if the replacement time were to be missed and an ineffective handle filter cartridge **60** continued to be used.

Please refer to FIGS. 53 through 58. The operation for the first exemplary embodiment of the present invention is as follows. Before the operation of the present invention, the spray hood 90 is first screwed onto the rim male threads 17 on the showerhead lower shell 10 (as shown in FIGS. 53 and 54), and then the handle filter cartridge 60 is screwed to the distal joint cylinder with external male threads 141 on the lower handle filter cartridge mounting section 14 of the showerhead lower shell 10 to make the showerhead ready for use. Once the shower water W from the detachable water pipe P flows through the handle filter cartridge 60 of the showerhead, it passes through the supporting tripod 703 of the cylindrical mount 701 in the supporter in axial flow mode 700 to drive the spiral vanes 503 of the impeller shaft in axial flow mode 500 to rotate (as shown in FIG. 58), and finally the shower water W will jet out from the spray holes 92 of the spray hood 90 on the front side 11 of the showerhead lower shell 10 after it flows into the water inlet groove 15 via the water inlet channel 151 of the showerhead lower shell 10 to provide a bathing shower (as shown in FIGS. 56 and 57). During the foregoing bathing shower operation, for each rotation of the spiral vanes 503 and impeller shaft 500 driven by the running shower water W, the inducting magnet 600 in the round gapped receptacle 504 of the impeller shaft 500 will simultaneously cause the magnetic reed switch 304 in the hollow pillar 55 of the water flow measuring unit 50 to induce a switching signal (as shown in FIG. 58), which is relayed to the microprocessor 301 in the signal circuit device 300 via electric wire L for being processed to generate and accumulate data at certain preset intervals for further transmission to the LCD display circuit 302 in order to display the related quantity of water flow thereon in accordance with following formula:

quantity of water flow (Q) = cross sectional area (A) times flow velocity (V).

For replacing the button-shaped battery **B**, please further refer to **FIGS. 49, 51 and 52**. The power of the button-shaped battery **B** under the battery lid **30** may run out after several replacements of the handle filter cartridge **60**. Once the power of the button-shaped battery **B** runs out, the battery lid **30** can be taken off battery mount **26** by simply inserting a coin into the rotatable notch **31** of the battery lid **30**, and turning the battery lid **30** (as shown in **FIG. 51**) to let two snap notches **33** thereof detach from two projections **261** of the battery mount **26** in the showerhead upper shell **20** so that the integral battery lid **30** together with button-shaped battery **B** can be taken out of the battery mount **26** of the showerhead upper shell **20** (as shown in **FIG. 49**). A new button-shaped battery **B** can then be substituted for the depleted button-shaped battery **B** under the battery lid **30**, and the previous steps reversely performed so that the new button-shaped battery **B** will supply power to the magnetic reed switch **304** and LCD display circuit **302** of the signal circuit device **300** as well as the microprocessor **301**. Therefore, some drawbacks incurred by the redundant recharging procedures of the prior art handheld showerhead with filter replacing pre-alarm device, such as detaching the alerting pod **20** off the groove base **113** in the back side **102** of the showerhead shell **100** and reinserting the alerting pod **20** back to the groove base **113** in the back side **12** of the showerhead shell **100**, can be eliminated by the first exemplary embodiment of the present invention.

The water flow measuring unit **50** and impeller shaft **500** are disposed in the lower handle filter cartridge mounting section **14** of the showerhead lower shell **10** while the battery mount **26** and button-shaped battery **B** are disposed in the upper handle filter cartridge mounting section **24** of the showerhead upper shell **20**, wherein both the lower handle filter cartridge mounting section of handle **14** and the upper handle filter cartridge

mounting section of handle **24** about the handle filter cartridge **60** such that the overall weight distribution of the showerhead is more even than that of the prior art handheld showerhead with filter replacing pre-alarm device. Accordingly, the problem of uneven top-heavy weight distribution and the resulting harmful effects incurred in the prior art
5 handheld showerhead with filter replacing pre-alarm device are all eliminated.

Please refer to **FIGS. 59** through **63**, which show a modified showerhead lower shell and modified showerhead upper shell that are joined by integrated latches in accordance with a second exemplary embodiment of the present invention. A plurality of upwardly elastic extending hooked latching arms **19** are further disposed in the shelf **13** of
10 the modified showerhead lower shell **10** (as shown in **FIGS. 59** and **61**) while a plurality of corresponding latching notches **27** are also further disposed in the shelf **23** of the modified showerhead upper shell **20** (as shown in **FIG. 60**) so that both the modified showerhead lower shell **10** and modified showerhead upper shell **20** can be securely joined together by latching means of the upwardly extending elastic latching arms **19** and
15 corresponding latching notches **27**, instead of the high-frequency fusing method adopted in the first exemplary embodiment of the present invention.

Please refer to **FIGS. 64** through **68**, which show a modified showerhead lower shell and modified showerhead upper shell according to a third exemplary embodiment of the present invention. **FIG. 64** shows the modified showerhead lower shell **10a** while
20 **FIG. 65** shows the modified showerhead upper shell **20a** of the third exemplary embodiment of the present invention.

The modified showerhead lower shell **10a**, which is a plastic hollow casing extruded into a unitary piece, includes a shelf **13a** having a front side **11a** and a reverse

side **12a** and formed as an integral body such that the shelf **13a** has an extending lower handle filter cartridge mounting section **14a** that includes an externally threaded mounting cylinder **141** with a set of male threads that extend from a distal end of the lower shell **10a** towards the handle of the showerhead for securely joining with the handle filter cartridge **60**. The front side **11a** has an internal water inlet groove **15a** and a water inlet channel **151a** that extends through a distal end of tubular adapter **16a** towards the lower handle filter cartridge mounting section **14a**, and a set of male threads **17a** formed on an outer periphery of the front side **11a** of shelf **13a** for mating with the corresponding spray hood **90**. The reverse side **12a** has two raised cylinders with internal female threads **121a** extending from a top surface thereof, and a battery mount **18** with two projections **181** and an electrical battery contact **182** that extend inwardly into the lower handle filter mounting section **14a** near the distal externally-threaded cylinder **141a** such that the projections **181** are outwardly formed on the internal vertical wall and the electrical battery contact **182** is outwardly formed at the internal bottom of the battery mount **18** (as shown in **FIG. 64**).

The modified showerhead upper shell **20a**, which is a plastic casing extruded into a unitary piece for suitably covering the back side **12a** of the modified showerhead lower shell **10a**, includes a shelf **23a** having a front side **21a** and a reverse side **22a** and formed as an integral body, wherein the shelf **23a** has a modified upper handle filter cartridge mounting section **24a** that extends towards the handle of the showerhead such that the profiles and sizes of the shelf **23a** and a modified upper handle filter cartridge mounting section **24a** are the same as those of the corresponding shelf **13a** and modified lower handle filter cartridge mounting section **14a** in the modified showerhead lower shell **10a**, and on the top surface of the front side **21a**, a viewing window **25a** is created over the rear

side thereof near the upper handle filter cartridge mounting section of handle **24a** (as shown in **FIG. 65**).

The battery mount **18** in the lower handle filter cartridge mounting section **14a** of the adapted showerhead lower shell **10a**, which accommodates the battery lid **30** with
5 associated button-shaped battery **B** (as shown in **FIGS. 66** and **67**), has the same function as battery mount **26** of the first exemplary embodiment of the present invention (as shown in **FIG. 68**).

The handheld showerheads of the above-described preferred embodiments have advantages of tremendously reducing molds required in the manufacturing process and
10 labor-hours in the assembly procedure, and of solving issues of top-heavy awkwardness, accelerated aging fatigue and unnecessary purchase waste that occur in the prior art handheld showerhead with filter replacing pre-alarm device disclosed in R.O.C. Patent Published No. 201406337 and US Patent Publication No. 2014/0042240.

15

20

What Is Claimed Is:

1. A hand-held showerhead capable of measuring and suggesting replacement of a filtering core handle, comprising:
- 5 a lower shell and an upper shell arranged to be joined together to form a shell of the showerhead;
- a handle including a handle filter cartridge arranged to be mounted on the joined-together shell;
- an impeller arranged to rotate in response to passage of water through a water channel
- 10 from the handle filter cartridge into the showerhead;
- a water flow measuring unit for measuring water flow by detecting rotation of the impeller, the water flow measuring unit including a display that displays an indication that the handle filter cartridge needs to be replaced;
- a battery mount for mounting at least one battery that supplies electricity to the water
- 15 flow measuring unit,
- wherein the water flow measuring unit and impeller shaft are disposed in the lower shell while the battery mount is disposed in the upper shell, and both the lower and upper handle filter cartridge mounting sections abut the handle filter cartridge to provide even overall weight distribution of the showerhead.
- 20 2. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1, wherein the battery mount includes two inwardly extending projections that engage a surface of the battery lid to prevent removal of the battery lid from the battery mount, and wherein rotation of the battery lid aligns the projections with opposed snap notches in the lid to enable removal of the battery lid from

the battery mount, exposing a battery cavity including electrical contacts for electrically contacting terminals of the at least one battery when the at least one battery is situated in the battery compartment.

3. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 2, further comprising a rotating notch in a top surface of the battery lid for receiving an object to enable rotation of the battery lid and replacement of a battery situated in the battery mount.

4. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 3, wherein the at least one battery is a button-type battery.

5. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1,

wherein the measuring unit includes an upper section of an upper hollow column and a lower section of a base hollow column, and the water channel runs through both the base hollow column and upper hollow column,

wherein the base hollow column has a sealing ring inlaid into the circumference thereof, and the upper hollow column is flanked by a hollow pillar with a tubular opening for accommodating a magnetic reed switch or Hall effect device,

wherein the impeller shaft is inserted into the water channel and a magnetic element is included within a receptacle of the impeller shaft, the magnetic reed switch or Hall effect device supplying electrical signals to the water flow measuring unit in response to movement of the magnetic element as the impeller shaft rotates in response to water flowing through the water channel.

6. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1, wherein the water flow measuring unit includes a signal circuit device accommodated in a holding cavity of the upper shell under a transparent cover, said display being visible through said transparent cover.

5 7. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 6, wherein the signal circuit device includes a microprocessor and an LCD display circuit.

8. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1,

10 wherein the lower shell includes a lower shelf having a front side, a reverse side, and a threaded cylindrical handle filter cartridge mounting section, the front side having an internal water inlet groove in communication with said water channel, and the front side further including a threaded rim for securing a spray hood having openings for enabling water in the internal water inlet groove to jet out of the showerhead, and

15 wherein the upper shell has a front side and a reverse side, a viewing window on the reverse side through which the display is visible, and a handle filter cartridge mounting section, the battery mount being located adjacent the handle filter cartridge mounting section of the upper shell.

20 9. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 8, wherein the water flow measuring device is secured to the lower shell by screwing the water flow measuring device to internally threaded projections extending from the lower shelf.

10. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1, wherein the lower shell and upper shell are extruded plastic pieces joined by ultrasonic fusing.

11. A hand-held shower head capable of measuring and suggesting replacement of a
5 filtering core handle as claimed in claim 1, further comprising hooked arms extending from one of the lower shell and the upper shell, and corresponding notches in the other of the lower shell and the upper shell for securing the lower shell to the upper shell.

12. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 1, further comprising a supporter that includes a
10 supporting tripod with radial ribs and a supporting base located at an upstream end of the water channel within the handle filter cartridge mounting section of the lower shell, wherein the radial ribs form a bushing for rotatably supporting a shaft of the impeller while permitting passage of water past the impeller.

13. A hand-held shower head capable of measuring and suggesting replacement of a
15 filtering core handle as claimed in claim 12, wherein the water channel includes a plurality of blocking vanes radially disposed in an upper portion thereof to form a second bushing that embraces a central suspended body composed of an upper baffle and a lower docking notch for receiving and rotatably supporting downstream end of the impeller.

14. A hand-held shower head capable of measuring and suggesting replacement of a
20 filtering core handle as claimed in claim 1, wherein the impeller includes an impeller shaft, which is inserted into the water channel in the water flow measuring unit, a bottom central bushing, an upper axial docking projection, a plurality of circumferential spiral vanes, and a bottom round gapped receptacle encompassed by the bottom ends of the spiral vanes,

and wherein an inducting magnet whose rotation is detected by the water flow measuring unit is placed in the bottom round gapped receptacle of the impeller shaft.

15. A hand-held showerhead capable of measuring and suggesting replacement of a filtering core handle, comprising:

5 a lower shell and an upper shell arranged to be joined together to form a shell of the showerhead;

a handle including a handle filter cartridge arranged to be mounted on the joined-together shell;

10 an impeller arranged to rotate in response to passage of water through a water channel from the handle filter cartridge into the showerhead;

a water flow measuring unit for measuring water flow by detecting rotation of the impeller, the water flow measuring unit including a display that displays an indication that the handle filter cartridge needs to be replaced;

15 a battery mount for mounting at least one battery that supplies electricity to the water flow measuring unit,

wherein the battery mount includes two inwardly extending projections that engage a surface of the battery lid to prevent removal of the battery lid from the battery mount, and wherein rotation of the battery lid aligns the projections with opposed snap notches in the lid to enable removal of the battery lid from the battery mount, exposing a battery
20 cavity including electrical contacts for electrically contacting terminals of the at least one battery when the at least one battery is situated in the battery compartment, and

wherein the battery mount further comprises a rotating notch in a top surface of the battery lid for receiving an object to enable rotation of the battery lid and replacement of a battery situated in the battery mount.

16. A hand-held shower head capable of measuring and suggesting replacement
5 of a filtering core handle as claimed in claim 15, wherein the at least one battery is a button-type battery.

17. A hand-held shower head capable of measuring and suggesting replacement
of a filtering core handle as claimed in claim 15,

wherein the measuring unit includes an upper section of an upper hollow column
10 and a lower section of a base hollow column, and the water channel runs through both the base hollow column and upper hollow column,

wherein the base hollow column has a sealing ring inlaid into the circumference
thereof, and the upper hollow column is flanked by a hollow pillar with a tubular opening
for accommodating a magnetic reed switch or Hall effect device,

15 wherein the impeller shaft is inserted into the water channel and a magnetic
element is included within a receptacle of the impeller shaft, the magnetic reed switch or
Hall effect device supplying electrical signals to the water flow measuring unit in response
to movement of the magnetic element as the impeller shaft rotates in response to water
flowing through the water channel.

20 18. A hand-held shower head capable of measuring and suggesting replacement
of a filtering core handle as claimed in claim 15, wherein the water flow measuring unit
includes a signal circuit device accommodated in a holding cavity of the upper shell under
a transparent cover, said display being visible through said transparent cover.

19. A hand-held shower head capable of measuring and suggesting replacement of a filtering core handle as claimed in claim 18, wherein the signal circuit device includes a microprocessor and an LCD display circuit.

20. A hand-held shower head capable of measuring and suggesting replacement
5 of a filtering core handle as claimed in claim 15,

wherein the lower shell includes a lower shelf having a front side, a reverse side, and a threaded cylindrical handle filter cartridge mounting section, the front side having an internal water inlet groove in communication with said water channel, and the front side further including a threaded rim for securing a spray hood having openings for enabling
10 water in the internal water inlet groove to jet out of the showerhead, and

wherein the upper shell has a front side and a reverse side, a viewing window on the reverse side through which the display is visible, and a handle filter cartridge mounting section, the battery mount being located adjacent the handle filter cartridge mounting section of the upper shell.

15




FIG.1 (PRIOR ART)




FIG. 2 (PRIOR ART)




FIG. 3 (PRIOR ART)




FIG. 4 (PRIOR ART)




FIG. 5 (PRIOR ART)




FIG. 6 (PRIOR ART)




FIG. 7 (PRIOR ART)




FIG. 8 (PRIOR ART)




FIG. 9 (PRIOR ART)




FIG. 10 (PRIOR ART)




FIG. 11 (PRIOR ART)




FIG. 12 (PRIOR ART)




FIG. 13 (PRIOR ART)






FIG. 14 (PRIOR ART)






FIG. 17 (PRIOR ART)






FIG. 19 (PRIOR ART)






FIG. 22 (PRIOR ART)




FIG. 23 (PRIOR ART)




FIG. 24 (PRIOR ART)




FIG. 25 (PRIOR ART)




FIG. 26




FIG. 28




FIG. 27




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG.33




FIG.34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 39a




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG.57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 65




FIG. 64




FIG. 66




FIG. 67




FIG. 68

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2016/027714

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - B01D 35/143; B05B 1/18; B05B 12/00; B05B 12/02; E03C 1/02; E03C 1/04 (2016.01)

CPC - B01D 35/143; B05B 1/18; B05B 12/004; B05B 12/006; E03C 1/0408; E03C 1/0409 (2016.05)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - B01D 35/143; B05B 1/18; B05B 12/00; B05B 12/02; E03C 1/02; E03C 1/04 (2016.01)

CPC - B01D 35/143; B05B 1/18; B05B 12/004; B05B 12/006; E03C 1/0408; E03C 1/0409 (2016.05)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

USPC - 137/551, 553; 210/85, 87, 446, 449; 239/71, 74, 525, 553, 553.3 (keyword delimited)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Orbit, Google Patents, Google Scholar, Google

Search terms used: hand, held, handle, shower, head, shell, upper, lower, impeller, shaft, inducting, magnet, transparent, cover, lid, LCD, display, circuit, filter, cartridge, water, channel, groove, water, flow, measuring, suggest, electricity, signal, mount, rotate, notch, projection, snap, shelf, threaded

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2014/0042240 A1 (CAI et al) 13 February 2014 (13.02.2014) entire document	1-20
A	US 7,468,127 B2 (HSU) 23 December 2008 (23.12.2008) entire document	1-20
A	US 6,892,952 B2 (CHANG et al) 17 May 2005 (17.05.2005) entire document	1-20
A	US 2011/0031331 A1 (KLICPERA) 10 February 2011 (10.02.2011) entire document	1-20
A	US 2013/0333764 A1 (WRIGHT) 19 December 2013 (19.12.2013) entire document	1-20

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 June 2016

Date of mailing of the international search report

08 JUL 2016

Name and mailing address of the ISA/

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, VA 22313-1450

Facsimile No. 571-273-8300

Authorized officer

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774