

US011707130B2

# (12) United States Patent Simon

### (10) Patent No.: US 11,707,130 B2

### (45) **Date of Patent:** Jul. 25, 2023

#### (54) FLUID-FILLED CLEANING HEAD

#### (71) Applicant: L'Oreal, Paris (FR)

(72) Inventor: Danny Elery Simon, Redmond, WA

(US)

(73) Assignee: L'Oreal, Paris (FR)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 277 days.

(21) Appl. No.: 17/135,857

(22) Filed: **Dec. 28, 2020** 

(65) Prior Publication Data

US 2021/0196035 A1 Jul. 1, 2021

#### Related U.S. Application Data

(60) Provisional application No. 62/953,855, filed on Dec. 26, 2019.

(51)	Int. Cl.	
	A47K 7/04	(2006.01)
	A46B 9/00	(2006.01)
	A46B 7/04	(2006.01)
	A46B 13/02	(2006.01)
	A61B 17/54	(2006.01)

(52) U.S. Cl.

(58) Field of Classification Search

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

1,772,501 A	8/1930	Shelton			
3,103,679 A	9/1963	Clemens			
3,196,299 A	7/1965	Kott			
3,542,519 A	11/1970	Montalto			
3,605,347 A	9/1971	Barry			
3,699,952 A	10/1972	Waters			
4,014,064 A	3/1977	Okazaki			
4,161,050 A	7/1979	Sasaki et al.			
4,325,392 A	4/1982	Item et al.			
4,475,261 A	10/1984	Okumura et al.			
4,655,232 A	4/1987	Ficke			
(Continued)					

#### FOREIGN PATENT DOCUMENTS


GB	2 323 026 A	9/1998
JP	H1-185202 A	7/1989
	(Cont	inued)

Primary Examiner — Michael D Jennings (74) Attorney, Agent, or Firm — Christensen O'Connor Johnson Kindness PLLC

#### (57) ABSTRACT

A cleaning head for a personal care appliance includes an elastic bladder having a bladder wall enclosing a fluid. The bladder wall has an inner base portion with a base thickness, which may be non-uniform, and a plurality of spaced projections extending outwardly from the inner base portion. The bladder is fixedly attached to a receiver portion of a bladder support, and a retainer is provided for attaching the bladder support to the personal care appliance such that the bladder support is drivably engaged by the personal care appliance. At least some of the plurality of spaced projections are configured to dynamically engage and disengage with neighboring ones of the plurality of spaced projections during use.

#### 20 Claims, 8 Drawing Sheets



# US 11,707,130 B2 Page 2

(56)	Referen	ices Cited		07969 A1		Driesen et al.
U.S	. PATENT	DOCUMENTS	2014/00	85556 A1 82866 A1 94900 A1		Gillespie et al. Fishcher et al. Sedic
4,722,111 A 4,802,255 A		Brodey et al. Breuer	2014/02 2014/02	02493 A1 61380 A1	7/2014 9/2014	Zelickson et al. Rademacher et al.
4,858,600 A	8/1989			76255 A1		McGushion
5,062,209 A	11/1991			73871 A1 82290 A1	12/2014 7/2015	
5,313,909 A		Tseng et al. Lerner		89980 A1		Hwang et al.
5,322,031 A 5,388,331 A		Doroodian-Shoja Siamak		97393 A1		McGushion
5,416,942 A	5/1995	Baldacci	2015/03	33609 A1*	11/2015	Lattanzi H02K 1/34
5,500,975 A	3/1996					310/38
5,652,990 A	8/1997	Driesen et al.		59324 A1	12/2015	
5,860,183 A	1/1999			83671 A1		Skidmore
5,891,063 A	4/1999			84162 A1	6/2016 6/2016	
5,906,834 A	5/1999			84173 A1 06087 A1		Skidmore
5,998,431 A	12/1999 2/2000			31106 A1		Khormaei
6,020,425 A 6,058,541 A		Masterman et al.		86627 A1*		Fang A47K 7/043
6,295,733 B1	10/2001			89670 A1		Brunson
6,373,786 B1	4/2002			67471 A1		Straka et al.
6,412,139 B1	7/2002	Weihrauch		67543 A1*		Straka A61H 7/005
6,482,511 B1		Martinez-Antonio		92449 A1*		Straka A61H 7/004
6,546,586 B2	4/2003			95980 A1		Boersma
6,604,531 B2		Nakamura et al.		17640 A1 52934 A1	12/2018	Schar et al.
7,338,664 B2 7,547,737 B2	3/2008			29411 A1		Brewer et al.
7,695,207 B1	4/2010	Kochvar		42147 A1*		Quinn A46B 11/066
7,786,626 B2	8/2010	Reishus et al.			0.2020	4/606
8,448,286 B2		Driesen et al.	2020/01	70399 A1*	6/2020	Truong A46B 13/003
9,750,533 B2	9/2017	Brewer et al.		37085 A1		Miller et al.
9,788,693 B1	10/2017			53811 A1		Alexander
2002/0049399 A1		Stempf	2020/03	52317 A1	11/2020	Yeates et al.
2002/0088068 A1		Levy et al.				
2002/0138926 A1 2003/0035953 A1		Brown, Jr. et al. Weihrauch		FOREIG	N PATE	NT DOCUMENTS
2003/0033933 AT 2003/0077107 AT	4/2003		TD	117.000	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	10/1007
2004/0103492 A1		Kwon et al.	JP JP	H7-250		10/1995
2004/0134010 A1	7/2004		JP JP	H9-299 H10-225		11/1997 8/1998
2004/0147984 A1	7/2004	Altshuler	JP	2000-279		10/2000
2004/0249322 A1	12/2004		JP	2003-245		9/2003
2005/0277950 A1		Pilcher et al.	JP	2009-240	768 A	10/2009
2006/0100558 A1	5/2006		JP	2009240		10/2009
2006/0282963 A1 2007/0101530 A1		Brown et al. Furumoto	WO		649 A1	3/1993
2007/0206986 A1		Gueret	WO		5529 A2	8/2001
2007/0207440 A1	9/2007		WO WO	2004/002 2005/092		1/2004 10/2005
2008/0313835 A1		Russell et al.	WO	2005/092		12/2006
2009/0163984 A1	6/2009	Robinson et al.	WO	2009/084		7/2009
2009/0177125 A1		Pilcher et al.	WO	2012/125		9/2012
2009/0222072 A1		Robinson et al.	WO	2013/191	389 A1	12/2013
2010/0223745 A1		Kraemer et al.	WO	2017064		4/2017
2011/0040235 A1 2011/0200381 A1	2/2011	Bylsma et al.	WO	2017102		6/2017
2011/0200381 A1 2011/0220634 A1	9/2011		WO	2018152	2068 Al	8/2018
2012/0301210 A1		Sturgis et al.	* cited b	y examiner		




FIG. 1





FIG. 2



**FIG. 3** 






FIG. 4



**FIG.** 5






FIG. 7




FIG. 8

#### FLUID-FILLED CLEANING HEAD

## CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of Provisional Application No. 62/953,855, filed Dec. 26, 2019; the entire disclosure of said application is hereby incorporated by reference herein.

#### BACKGROUND

Handheld personal care appliances used to care for, clean, or otherwise treat the skin or hair (e.g., to clean, massage and/or apply creams, cleansing solutions, or other sub- 15 stances to the skin or hair) are known and have gained increasing popularity. Such devices are most often used to provide daily hygienic skin care, in particular care for the facial skin. These devices usually include a small handheld casing having an internal motor and a self-contained power 20 or synthetic rubber. source (such as a battery) for producing a particular movement/action of a workpiece (e.g., a brush or pad), which in turn produces desired functional results. Examples of such appliances include power skin brushes and power toothbrushes, among others. Such personal care appliances have 25 motor arrangements which produce either rotational movement or oscillating (back and forth) movement. For example, U.S. Patent Application Publication No. 2015/ 0333609 A1, to Lattanzi et al., which is hereby incorporated by reference in its entirety, discloses an oscillating motor for 30 a personal care appliance. These devices typically include replaceable brush heads having a plurality of elongate bristles, typically tufts of bristles, that are fixed to a base element that is driven to oscillate or rotate. The brush heads are pressed or positioned against a user's skin and activated 35 while moving the brush head over the desired dermal region to provide a cleansing action to remove dirt, makeup, and/or dead skin, and the like.

Some oscillating heads for handheld personal care appliances are known that have a working face having abrasive 40 exfoliating heads, for treating rough skin conditions such as calluses or corns. For example, U.S. Pat. No. 9,750,533, to Brewer et al., which is hereby incorporated by reference in its entirety, discloses an exfoliating head for a personal care appliance.

While many such devices are known, there is room for improvement in the field of personal care appliances such as handheld skin and hair treatment devices. For example, it is desirable to have a cleaning head for a personal care appliance with improved effectiveness in cleaning, massaging, and gently removing materials from a user's skin.

#### **SUMMARY**

This summary is provided to introduce a selection of 55 concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

A cleaning head for a personal care appliance includes an elastic bladder having a bladder wall enclosing a fluid. The bladder wall has an inner base portion with a base thickness, which may be non-uniform, and a plurality of spaced projections extending outwardly from the inner base portion. 65 The bladder is fixedly attached to a receiver portion of a bladder support, and a retainer is provided for attaching the

2

bladder support to the personal care appliance such that the bladder support is drivably engaged by the personal care appliance. At least some of the plurality of spaced projections are configured to dynamically engage and disengage with neighboring ones of the plurality of spaced projections during use.

In an embodiment the receiver portion of the bladder support comprises an annular wall configured to surround at least a portion of the elastic bladder.

In an embodiment the plurality of spaced projections have a polygonal cross section, for example, a square cross section.

In an embodiment the plurality of spaced projections have a transverse dimension between 0.060 inch and 0.125 inch.

In an embodiment the plurality of spaced projections have a nominal spacing in the range of 0.030 and 0.040 inch between adjacent spaced projections.

In an embodiment the elastic bladder comprises a natural or synthetic rubber.

In an embodiment the base thickness of the inner base portion is not constant.

In an embodiment the fluid in the elastic bladder comprises air.

In an embodiment the fluid in the elastic bladder comprises an oil or water.

In an embodiment the fluid in the elastic bladder is pressurized above atmospheric pressure.

In an embodiment the fluid in the elastic bladder is pressurized to at least 30 psia.

In an embodiment the elastic bladder comprises a relatively smaller diameter portion that engages the bladder support, and a relatively larger diameter portion extending from the smaller diameter portion.

In an embodiment the larger diameter portion defines a narrow circumferential surface, and wherein at least a portion of the plurality of spaced projections extend outwardly from the narrow circumferential surface.

In an embodiment the bladder support defines a cavity configured to receive the smaller diameter portion of the elastic bladder, and the larger diameter portion of the elastic bladder extends radially away from the bladder support.

In an embodiment the larger diameter portion of the elastic bladder extends radially beyond a radially outer edge 45 of the retainer.

A personal care appliance with a cleaning head is disclosed, wherein the personal care appliance is configured to releasable and drivably engage a cleaning head as described above.

A cleaning head for a personal care appliance includes a bladder support comprising a receiver portion defining a cavity, an elastic bladder having a first portion disposed in the cavity and fixedly attached to the bladder support and a second portion having a non-uniform thickness and a plurality of spaced projections extending outwardly from the second portion, wherein the elastic bladder encloses a liquid; and a retainer configured to releasably attach the bladder support to the personal care appliance such that the bladder support is drivably engaged by the personal care appliance, wherein the elastic bladder is configured to flex during use such that the plurality of spaced projections engage and disengage with neighboring ones of the plurality of spaced projections during use.

In an embodiment the plurality of spaced projections have a polygonal cross section and have a nominal spacing in the range of 0.030 and 0.040 inch between adjacent spaced projections.

In an embodiment the first portion of the elastic bladder has a smaller transverse dimension than the second portion of the elastic bladder.

In an embodiment at least some of the plurality of spaced projections extend radially outwardly from the second portion of the elastic bladder.

#### DESCRIPTION OF THE DRAWINGS

The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a cleaning head in 15 accordance with the present invention;

FIG. 2 is an exploded view of the cleaning head shown in FIG. 1:

FIG. 3 is a top plan view of the cleaning head shown in FIG. 1:

FIG. 4 is a sectional view of the cleaning head through section 4-4 indicated in FIG. 3, and showing an exemplary drive boss for driving the cleaning head;

FIG. 5 is a sectional and detail view of the pliable bladder of the cleaning head shown in FIG. 1;

FIG. 6 is a perspective view of a personal care appliance with the cleaning head shown in FIG. 1, with the cleaning head positioned to be attached to the personal care appliance:

FIG. 7 is a functional block diagram of the personal care  $^{30}$  appliance shown in FIG. 6; and

FIG. 8 is a sectional view of another embodiment of a cleaning head in accordance with the present invention.

#### DETAILED DESCRIPTION

The following disclosure provides examples of cleaning heads for a personal care appliance, and a personal care appliance configured to use the disclosed cleaning heads for cleaning and/or treating a user's skin. Personal care appliances and cleaning heads may be configured for deep cleaning, smoothing, exfoliating, and/or massaging the skin. The appliance and cleaning heads may be suitable for use on any area of a body. Cleaning heads in accordance with the present disclosure include a pliable fluid-filled bladder having a micro-engineered outer surface that is configured to facilitate skin cleaning, dead skin cell removal, or the like. It is contemplated that the cleaning heads may further include additional known components such as bristles, abrasive sections, and the like.

In some examples the personal care appliance oscillates the cleaning head during use, for example with rotational (i.e., clockwise/counterclockwise) oscillations, and may advantageously be used with a prior application of skin care formula. The oscillating action of the cleaning head may be 55 rotational and/or translational oscillations. Typically, the personal care appliance drives the cleaning head in a periodic motion while the user positions the cleaning head against the user's skin, and/or moves the cleaning head over a region of the user's skin, to clean the desired dermal 60 region. In some embodiments, the cleaning head may be configured to additionally treat rough skin conditions such as calluses, corns, or the like, by further including abrasive elements over a portion of an outer surface of the bladder.

In the following description certain details are described 65 to provide a thorough understanding of one or more contemplated embodiments of the present invention. It will be

4

apparent to persons skilled in the art that embodiments of the present disclosure may be practiced without all of the specific features or details described herein. In some instances well-known features or process steps are not described in detail to avoid unnecessarily obscuring novel aspects of the present disclosure. Further, it will be apparent to persons of skill in the art that embodiments of the present disclosure may employ any combination of features described herein.

FIG. 1 is a perspective view of a cleaning head 100 for a personal care appliance 22 (see FIG. 6) in accordance with the present disclosure. FIG. 2 shows an exploded view of the cleaning head 100, and FIG. 3 shows a top plan view of the cleaning head 100.

An exemplary personal care appliance 22 with the cleaning head 100 is illustrated in FIG. 6 and a functional block view of the assembly is shown in FIG. 7. Referring to FIG. 6, the appliance 22 includes a body 24 having a handle portion 26 and a head attachment portion 28. The head attachment portion 28 is configured to selectively attach a head, such as cleaning head 100, to the appliance 22. The appliance body 24 houses the operating structure of the appliance 22, and drivably engages the cleaning head 100 through a drive boss 50 located in the head attachment portion 28. In this embodiment the appliance 22 includes a drive motor assembly 30, a power storage source 32, such as a rechargeable battery, and a drive control circuit 34 (see FIG. 7). An on/off button 36 (see FIG. 6) enables the user to selectively deliver power from the power storage source 32 to the drive motor assembly 30. In some embodiments, the drive control circuit 34 includes one or more power adjust or mode control buttons 38 on the appliance 22 that are configured to provide user control of the drive motor assembly 30, such as a programmed microcontroller or processor, 35 which is configured to control the delivery of power to the drive motor assembly 30. The drive motor assembly 30 in some embodiments includes an electric drive motor 40 that drives an attached head, such as head 100, via a drive shaft or armature 42. The individual components illustrated in FIG. 7 are well known in the art, and therefore will not be further described herein. An example of a drive motor assembly 30 that may be employed by the appliance 22 to oscillate the head 100 is shown and described in U.S. Pat. No. 7,786,626, the disclosure of which is hereby incorporated by reference in its entirety. It will be understood that the particular drive motor assembly is merely an example of the structure and operation of one such appliance and that the structure, operation frequency, and oscillation amplitude of such an appliance could be different depending in part on its intended application and/or characteristics of the head, such as its inertial properties, etc. In some embodiments of the present disclosure, the frequency ranges are selected to drive the attached head at near resonance. Thus, selected frequency ranges are dependent, in part, on the inertial properties of the attached head. It will be appreciated that driving the attached head at near resonance provides many benefits, including the ability to drive the attached head at suitable amplitudes in loaded conditions (e.g., when contacting the skin).

Referring again to FIGS. 1-3, the cleaning head 100 in a current embodiment includes a pliable fluid-filled bladder 102, a housing or bladder support 110 that is fixed to and supports the bladder 102 such that at least a portion of an outward facing micro-engineered surface 104 of the bladder 102 extends beyond the bladder support 110 (FIG. 2), and an annular outer retainer 105 that is configured to receive and retain the bladder support 110. The outer retainer 105 is

configured to releasably engage the personal care appliance 22 to removably connect the cleaning head 100 to the appliance 22 (see FIG. 6).

In particular, the cleaning head 100 is configured to be attachable to the personal care appliance 22 such that the 5 appliance 22 selectively drives the cleaning head 100 in a periodic motion. For example, the bladder support 110 may be configured to move along a circular path, oscillate rotationally about an axis perpendicular to the bladder support 110, and/or oscillate linearly, for example, side-to-10 side and/or vibrate in an in-and-out direction perpendicular to the face of the cleaning head 100. In some embodiments the appliance 22 may include a drive mode to drive the cleaning head 100 in a continuous rotational mode, for example, providing suitable user drive controls 34 on the 15 handle portion 26. In some embodiments the bladder support 110 is, or may be, driven to oscillate at a sonic frequency, which can provide improved control and precision, for example, to facilitate the removal of dirt, dead skin, oils, hair, and the like.

The outer retainer 105 includes a plurality of engagement portions 105A that are configured to attach the cleaning head 100 to corresponding rods or pins 29 in the head attachment portion 28 of the appliance 22 (FIG. 6, one pin 29 visible). A central housing portion or opening 105B of the outer 25 retainer 105 is configured to receive and retain the bladder support 110 and pliable bladder 102 without interfering with oscillatory motion of the bladder support 110, and such that the bladder support 110 is drivably engaged by the appliance 22. In this embodiment the bladder support 110 defines a 30 recess or cavity 101 that is configured to receive and fixedly attach to the bladder 102. The outer retainer 105 and the bladder support 110 in some embodiments are constructed from plastic, such as nylon, polyurethane, polypropylene, polyethylene, etc., although other materials may be utilized, 35 including lightweight metals, such as aluminum, titanium,

In some embodiments the drive motor assembly **30** (FIG. **4**) is configured to oscillate the bladder support **110**, typically in the range of 90-300 Hz, for example, oscillating the 40 bladder support **110** within an angular range of 8-26 degrees. In some embodiments the bladder support **110** is driven at frequencies between about 100 Hz to 190 Hz with an amplitude or range of about 12-18 degrees. In other embodiments, the bladder support **110** is driven at frequencies of 45 about 168 Hz to 178 Hz, amplitudes of about 12-18 degrees, and a duty cycle of about 36-48%.

FIG. 4 is a sectional view of the cleaning head 100 through section 4-4 indicated in FIG. 3. The bladder support 110 includes a plurality of legs 153 that extend below the 50 cavity 101 and includes a projection 154 configured to engage a stop element 156 on the retainer 105, such that the bladder support 110 is releasably retained by the retainer 105 during use. The bladder support 110 is configured to interface directly or indirectly (e.g., via drive boss 50) with the 55 drive shaft or armature 42 of the drive motor assembly 30 at a first or inner end comprising the engagement member 152.

FIG. 5 shows a cross section of the fluid-filled pliable bladder 102 with a detail view showing a portion of the outward facing surface 104. The pliable bladder 102 in a 60 current embodiment is made from one or more natural or synthetic rubbers, for example, silicone rubber. The bladder 102 is filled with a fluid 118, for example, air, water, natural oils, non-Newtonian fluids, or the like. A non-Newtonian fluid is a fluid wherein the viscosity of the fluid depends on 65 the stress applied to the fluid. For example, in some embodiments the fluid 118 is pressurized above atmospheric pres-

6

sure such that the bladder 102 is maintained in tension by the pressurized fluid 118. For example, the bladder may be pressurized to between 15 and 30 psia, or greater than 30 psia.

At least a portion of the outward facing surface 104 of the bladder 102 includes a plurality of small, closely spaced elastic fingers or projections 106 that are configured to engage the surface of the user's skin. The elastic projections 106 are preferably integrally formed portions of the bladder 102. The bladder 102 has a wall base thickness T(x), wherein the "base thickness" is herein defined as the thickness of the bladder wall not including the projections 106. In some embodiments it is contemplated that the wall base thickness T(x) may be uniform. As illustrated in FIG. 5, in a currently preferred embodiment the wall base thickness T(x) varies. The variable base thickness T(x) is preferably configured to produces a desired non-uniform stiffness/ elastic properties of the bladder 102 along at least a portion of the outward facing surface 104. For example, the wall 20 base thickness T(x) may be greater near a center of the bladder 102 to provide a stiffer response to the forces encountered during use, and the thickness may be smaller near the perimeter. In one embodiment the thickness of the bladder 102 is non-uniform along a diameter of the bladder 102, and is constant circumferentially such that the bladder 102 is rotationally symmetric about a central axis of the bladder 102.

Other thickness profiles are contemplated and may be selected to produce a desired action against a user's skin. For example, the thickness may vary periodically, for example sinusoidally, in the radial direction and is uniform circumferentially, to produce annular rings with greater stiffness, separated by lower stiffness rings. It is contemplated that in some embodiments the wall base thickness T(x) may change discontinuously. In other embodiments the wall base thickness T(X) varies circumferentially, and is uniform radially, defining radial, relatively rigid "spokes" along at least the upper surface of the bladder.

The pliable projections 106 extending from the variable thickness wall base are sized, spaced, and shaped such that the projections 106 dynamically bend and elastically deform, causing adjacent projections 106 to interact during use, e.g., such that the projections 106 dynamically contact and move away from neighboring projections 106. During use the projections 106 may therefore be configured such that the projections 106 gently trap, "grab" or otherwise capture particles on (and in) the user's skin, for example, dead skin cells, dirt, makeup, hair follicles, and the like.

In the embodiment shown in FIG. 5 the projections 106 have a generally polygonal cross section, for example, a square cross section with transverse dimensions, or widths W that are between 0.060 inch and 0.125 inch and a height H that may be, for example, between 0.050 inch and 0.080 inch. The projections 106 are closely spaced, for example, a spacing S when at rest between 0.020 inch and 0.060 inch.

Another embodiment of a cleaning head 200 in accordance with the present invention is shown in sectional view in FIG. 8. The cleaning head 200 shares many of the features of the cleaning head 100 described above and are contemplated for the cleaning head 200. For brevity and clarity, common features and options described above are not be reiterated, and it is intended that features described for the embodiment described with reference to cleaning head 100 may be provided in cleaning head 200, as far as practicable.

In this embodiment the cleaning head 200 includes a pliable fluid-filled bladder 202 that is fixedly attached to a bladder support 210. The bladder support 210 is removably

retained by a retainer 205, and may be otherwise similar to the bladder support 110 discussed above. At least a portion of the outer surface of the fluid-filled bladder 202 defines a surface 204 that includes a plurality of small, closely spaced elastic fingers or projections 206 configured to engage the 5 user's skin. The individual projections 206 may be similar to the projections 106 described above with widths W, height H, spacing S, and the bladder 220 may have a variable base thickness T(x) as discussed above. In this embodiment the bladder 202 includes a narrower central portion 207, e.g., a smaller-diameter central portion 207 that extends into and is fixed in the cavity 201 defined by the bladder support 210, and a wider portion 208 (e.g., larger-diameter portion) that extends from the narrower portion 207 such that the bladder 202 has a generally mushroom shape. The plurality of projections 206 in this embodiment are also provided and cooperatively define the arcuate radially outer surface 209 of the bladder 202. For example, the wider portion 208 may extend to, or beyond, the radially outer perimeter of the outer 20 retainer 205. In a current embodiment the axial dimension, or thickness, of the narrower portion 207 and the axial dimension of the wider portion may be similar, for example within a factor of two, and the diameter or lateral dimension of the narrower portion 207 may be similar to the diameter 25 or lateral dimension of the wider portion 208, for example within a factor of two.

This second embodiment of the cleaning head 200 has certain advantages. The arcuate radially outer surface 209 of the bladder 202, which includes projections 206, is much 30 narrower (e.g., much shorter radius) than the central portion of the bladder 202, which facilitates positioning and maneuvering the bladder 202, and in particular the novel pliable fingers or projections 206 over contoured body regions, including for example around the user's nose and ears. In all 35 cases, it will be appreciated that the closely spaced fingers or projections 206 will, in general, tend to move toward each other when the bladder 202 is in use, because pressing the pliable bladder 202 against the user will naturally deform or urge the bladder 202 locally toward a flatter shape. This 40 ing: deforming action facilitates the projections 206 (adjacent to the skin) coming together to improve the cleaning action of the cleaning head 100, 200.

The detailed description set forth above in connection with the appended drawings, where like numerals reference 45 like elements, are intended as a description of various embodiments of the present disclosure and are not intended to represent the only embodiments. Each embodiment described in this disclosure is provided merely as an example or illustration and should not be construed as 50 preferred or advantageous over other embodiments. The illustrative examples provided herein are not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Similarly, any steps described herein may be interchangeable with other steps, or combinations of steps, 55 in order to achieve the same or substantially similar result.

In the foregoing description, specific details are set forth to provide a thorough understanding of exemplary embodiments of the present disclosure. It will be apparent to one skilled in the art, however, that the embodiments disclosed 60 herein may be practiced without embodying all of the specific details. In some instances, well-known process steps have not been described in detail in order not to unnecessarily obscure various aspects of the present disclosure. Further, it will be appreciated that embodiments of the 65 present disclosure may employ any combination of features described herein.

8

The present application may include references to directions, such as "forward," "rearward," "front," "back," "upward," "downward," "right hand," "left hand," "lateral," "medial," "in," "out," "extended," "advanced," "retracted," "proximal," "distal," "central," etc. These references, and other similar references in the present application, are only to assist in helping describe and understand the particular embodiment and are not intended to limit the present disclosure to these directions or locations.

The present application may also reference quantities and numbers. Unless specifically stated, such quantities and numbers are not to be considered restrictive, but exemplary of the possible quantities or numbers associated with the present application. Also in this regard, the present application may use the term "plurality" to reference a quantity or number. In this regard, the term "plurality" is meant to be any number that is more than one, for example, two, three, four, five, etc. The term "about," "approximately," etc., means plus or minus 5% of the stated value.

The principles, representative embodiments, and modes of operation of the present disclosure have been described in the foregoing description. However, aspects of the present disclosure, which are intended to be protected, are not to be construed as limited to the particular embodiments disclosed. Further, the embodiments described herein are to be regarded as illustrative rather than restrictive. It will be appreciated that variations and changes may be made by others, and equivalents employed, without departing from the spirit of the present disclosure. Accordingly, it is expressly intended that all such variations, changes, and equivalents fall within the spirit and scope of the present disclosure as claimed.

While illustrative embodiments have been illustrated and described, it will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

- 1. A cleaning head for a personal care appliance compris
  - an elastic bladder comprising a bladder wall enclosing a fluid, wherein the bladder wall comprises an inner base portion having a base thickness and a plurality of spaced projections extending outwardly from the inner base portion;
  - a bladder support comprising a receiver portion, wherein the elastic bladder is fixedly attached to the receiver portion; and
  - a retainer configured to attach the bladder support to the personal care appliance such that the bladder support is drivably engaged by the personal care appliance;
  - wherein at least some of the plurality of spaced projections are configured to dynamically engage and disengage with neighboring ones of the plurality of spaced projections during use.
- 2. The cleaning head of claim 1, wherein the receiver portion of the bladder support comprises an annular wall configured to surround at least a portion of the elastic bladder.
- 3. The cleaning head of claim 1, wherein the plurality of spaced projections have a polygonal cross section.
- **4**. The cleaning head of claim **1**, wherein the plurality of spaced projections have a transverse dimension between 0.060 inch and 0.125 inch.
- 5. The cleaning head of claim 1, wherein the plurality of spaced projections have a nominal spacing in the range of 0.030 and 0.040 inch between adjacent spaced projections.

- **6**. The cleaning head of claim **1**, wherein the elastic bladder comprises a natural or synthetic rubber.
- 7. The cleaning head of claim 1, wherein the base thickness of the inner base portion is not constant.
- **8**. The cleaning head of claim **1**, wherein the fluid in the belastic bladder comprises au.
- 9. The cleaning head of claim 1, wherein the fluid in the elastic bladder comprises oil or water.
- 10. The cleaning head of claim 1, wherein the fluid in the elastic bladder is pressurized above atmospheric pressure.
- 11. The cleaning head of claim 1, wherein the fluid in the elastic bladder is pressurized to at least 30 psi.
- 12. The cleaning head of claim 1, wherein the elastic bladder comprises a relatively smaller diameter portion that engages the bladder support, and a relatively larger diameter portion extending from the smaller diameter portion.
- 13. The cleaning head of claim 12, wherein the larger diameter portion defines a narrow circumferential surface, and wherein at least a portion of the plurality of spaced projections extend outwardly from the narrow circumferential surface.
- 14. The cleaning head of claim 13, wherein the bladder support defines a cavity configured to receive the smaller diameter portion of the elastic bladder, and the larger diameter portion of the elastic bladder extends radially away from the bladder support.
- 15. The cleaning head of claim 14, wherein the larger diameter portion of the elastic bladder extends radially beyond a radially outer edge of the retainer.
  - **16**. A personal care appliance comprising: a body having a head attachment portion; and

10

- a cleaning head in accordance with claim 1 wherein the cleaning head is configured to releasably engage the head attachment portion.
- 17. A cleaning head for a personal care appliance comprising: a bladder support comprising a receiver portion defining a cavity;
  - an elastic bladder having a first portion disposed in the cavity and fixedly attached to the bladder support and a second portion having a non-uniform thickness and a
  - plurality of spaced projections extending outwardly from the second portion, wherein the elastic bladder encloses a liquid; and
  - a retainer configured to releasably attach the bladder support to the personal care appliance such that the bladder support is drivably engaged by the personal care appliance;
  - wherein the elastic bladder is configured to flex during use such that the plurality of spaced projections engage and disengage with neighboring ones of the plurality of spaced projections during use.
- **18**. The cleaning head of claim **17**, wherein the plurality of spaced projections have a polygonal cross section and have a nominal spacing in the range of 0.030 and 0.040 inch between adjacent spaced projections.
- 19. The cleaning head of claim 17, wherein the first portion of the elastic bladder has a smaller transverse dimension than the second portion of the elastic bladder.
- 20. The cleaning head of claim 19, wherein at least some of the plurality of spaced projections extend radially out30 wardly from the second portion of the elastic bladder.

\* \* \* \* \*