




US 20090125809A1

(19) **United States**(12) **Patent Application Publication**
Trapani et al.(10) **Pub. No.: US 2009/0125809 A1**(43) **Pub. Date: May 14, 2009**(54) **SYSTEM AND METHOD FOR ADAPTING
INFORMATION CONTENT FOR AN
ELECTRONIC DEVICE**(60) Provisional application No. 60/199,858, filed on Apr.
26, 2000.**Publication Classification**(75) Inventors: **Matthew Frank Trapani**,
Deerfield, IL (US); **Leonid**
Polonsky, Wilmette, IL (US);
Bruce Wiatrak, Bolingbrook, IL
(US); **Francis Edward Simon**
Hunt, Naperville, IL (US)(51) **Int. Cl.**
G06F 3/14 (2006.01)
G06F 3/048 (2006.01)(52) **U.S. Cl.** **715/273; 715/853**(57) **ABSTRACT**

Correspondence Address:

**MCDONNELL BOEHNEN HULBERT & BERG-
HOFF LLP**
300 S. WACKER DRIVE, 32ND FLOOR
CHICAGO, IL 60606 (US)

A system and method is provided for efficiently adapting information content for an electronic device. A normalizer includes a template normalizer for matching and applying a document tree to a template tree, and applying changes to the document tree. If the template normalizer does not find an appropriate template match, an automatic normalizer is utilized. The automatic normalizer utilizes weighting heuristics and pattern recognition with formatting rules to partition content into folders. The automatic normalizer can also utilize embedded normalization markup in the information content to assist in normalizing the information content. Information content can be represented by a document object tree. A document object tree is created by storing information relating to the information content into arrays. The stored information describes a document object tree structure and tree dependencies as a mutable object.

(73) Assignee: **Novarra, Inc.**, Itasca, IL (US)(21) Appl. No.: **12/357,096**(22) Filed: **Jan. 21, 2009****Related U.S. Application Data**(63) Continuation of application No. 09/843,036, filed on
Apr. 25, 2001, now Pat. No. 7,500,188.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6





FIG. 7






FIG. 8









FIG. 11

FIG. 12



RIM 857

SYSTEM AND METHOD FOR ADAPTING INFORMATION CONTENT FOR AN ELECTRONIC DEVICE

REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. provisional application Ser. No. 60/199,858 filed on Apr. 26, 2000, and to U.S. patent application Ser. No. 09/843,036, filed on Apr. 25, 2001. This application is a continuation of U.S. patent application Ser. No. 09/843,036, which is entirely incorporated by reference herein.

FIELD OF THE INVENTION

[0002] This present invention relates generally to the field of network communications. More specifically, it relates to a system and method for accessing, adapting, and presenting information content for electronic devices.

BACKGROUND OF THE INVENTION

[0003] Today, an abundant amount of meaningful and feature rich information content is truly at one's fingertips. Currently, using a personal computer (PC) and PC-based browser, one can find information online regarding just about anything they desire. One can communicate with people on the other side of the U.S. or world, set up a teleconference call, tap into the resources of other computers across the earth, search through the world's finest libraries, and visit images from the world's most remarkable museums. One can even use the PC-based browser to watch videos and listen to their favorite music, monitor the financial markets, find the local weather forecast, go shopping, download application software, and so on. Currently, all of this can be done with a personal computer and a PC-based browser that is tapped into a feature rich network of computers such as the Internet, Intranet, or Extranet.

[0004] At the same time, the field of communications, and more specifically wireless telecommunications, is currently undergoing a radical expansion. This technological expansion allows an electronic device, such as mobile personal digital assistant (PDA), cellular phone, pager, and other electronic devices to connect to the same information sources, such as a web server or database, as one could with the PC and a PC-based browser.

[0005] Unfortunately, this feature rich information content was developed for a standard PC-based browser, not a mobile or portable electronic device that might be limited in memory, screen size, bandwidth, navigation capabilities, power consumption, processing power, etc. For example, an electronic device, such as portable PDA, with a small screen size may be inappropriate to display the same information content originally intended for a PC-based browser, and viewed on a 15-inch or greater size display monitor. Consequently, the PDA can not be able to faithfully access and display information content as it was originally intended to be viewed. Therefore, it would be desirable to access, organize, and navigate information content including applications.

[0006] In another example, a mobile or wireless device with only low bandwidth capability may be unable to view information content intended for only high bandwidth applications. Parameters such as the mobile or wireless device's network connection, memory capacity, power restrictions, or other limitations of the device may require customization of information content that is delivered to or from the device.

Therefore, it would be desirable to streamline the information content such that the desired content is received and presented at the mobile device as it was intended to be viewed.

[0007] In yet another example, current electronic devices cannot take full advantage of dynamically generated content and interactive Web sites that are typically hosted on today's Web servers. According to this example, scripting languages like JavaScript or Jscript allow a user on a PC-based browser to interact with markup language such as Hypertext Markup Language (HTML) source code, thus enabling the use of dynamic content. However, it would be desirable for a portable electronic device, although possibly having limited abilities, to also utilize the modern and current scripting languages.

[0008] Currently, information content is sent to the device, but often in a format that the appliance, user, or network cannot conveniently accommodate, which produces undesirable results. For example, the data content might be unreadable on the display, displayed in an unorganized fashion, be too voluminous or bandwidth intensive to be received or displayed, and so on.

[0009] Thus, it would be desirable to transparently extend internet and intranet technologies to an electronic device over a wired or wireless domain.

SUMMARY OF THE INVENTION

[0010] A system and method is provided that enables electronic devices with limited hardware or network capability to successfully access the same feature rich information content as full featured PC-based browsers with a large display screen, extensive user input facilities (e.g., mouse, keyboard, etc), high CPU power, large memory, reliable network connections, a reliable power supply, and so on.

[0011] In an aspect of the present embodiment, the system enables an electronic device to access a number of different information sources including, but not limited to, marked up content like HTML, XML, WML, voice and multimedia. In the exemplary embodiment, a script execution engine is utilized to support scripting technologies such as JavaScript that dynamically generate content.

[0012] According to another aspect of the present embodiment, a distributed browser includes separable components, a server browser and a client browser, that enable an electronic device with a small display to efficiently access information content. In the exemplary embodiment, the server browser and the client browser work together to access the information content by separating functionality between the browsers, irrespective of the component's location. Preferably, the functionality applied to optimize information content access, arrangement, transmission, and navigation can be performed by the server browser rather than the client browser hosted on the portable or mobile device.

[0013] According to another aspect of the present embodiment, a QDOM converts data content into a document object tree represented by a mutable object having an array structure. Based on the nodes of the object tree, the QDOM generates an array of primitive data types for efficiently developing an optimized standard structure for use by a normalizer or other processing modules. In the manner, the QDOM extends the World Wide Web Consortium (W3C) DOM interface definition to an efficient model that provides high speed parsing, storage, and access while minimizing memory resource requirements.

[0014] In another aspect of the present embodiment, a normalizer adaptively tailors and folderizes markup based information content to accommodate an electronic device's particular software, hardware, and network characteristics. In the exemplary embodiment, the normalizer organizes any markup based information content into folders of interest. The user of the electronic device can then further explore the folders of interest as desired.

[0015] In yet another aspect of the present embodiment, metatags embedded in a markup language at the information source can provide instructions to the normalizer to take appropriate actions. Use of metatags can allow customization of original information content if a modified outcome is desired at the electronic device. In the exemplary embodiment, the metatags provide instruction to an automatic normalizer including, but not limited to, direct output of information content without normalization, the promotion of content into or out of folders, and dropping or filtering information content from the serialized output to an electronic device.

[0016] In another aspect of the present embodiment, pattern-matching templates are utilized to normalize the presentation of accessed information content. In the exemplary embodiment, a template normalizer utilizes regular expression pattern-matching to impose a template over a document and attempts to match the template to the document.

[0017] In another aspect of the present invention, an event translator provides additional compatibility with commercially available client browsers or end user applications that employ standardized protocols. In the exemplary embodiment, the event translator can be utilized on the server browser or the client browser to provide compatibility with standard client browsers.

[0018] In an aspect of the present embodiment, a serializer dynamically formats normalized content to a form that is optimized for a particular electronic device. The serialized output can be formatted to suit industry standard browsers, or targeted to an electronic device using the client side browser.

[0019] The present embodiments allow for electronic devices with limited hardware capability to access, on the fly, feature rich static and dynamic content, and applications. The server browser enables a client browser that utilizes a particular markup language to access information content that is of any type of markup language or technology. The distributed browser minimizes the functionality required on the device and implements the CPU and memory intensive functions on a server in the network, thus allowing wireless devices, with intermittent, limited connectivity, processing power capability etc. to provide a similar experience achieved with a desktop PC.

[0020] Multiple components including a serializer, normalizer, client browser, and/or the event translator work in conjunction with each other to convert user events within one markup domain into another markup domain while staying in the transaction to translate the meaning of the interaction appropriately. Thus, for example, user events such as scrolling, clicking, voice commands interact with the QDOM to result in a change in presentation of the content.

[0021] Additionally, the present embodiments provide significantly higher speed and an efficient use of network bandwidth as desired information content can be cached on the server browser and on the client browser, if so desired, to enable quick access to the desired portions of the information content.

[0022] The present embodiments also provide for server browser-centric access to user profile and client browser state information (such as cookies), thereby facilitating the use of multiple devices by a single user.

[0023] The present embodiments provide a number of advantages and applications as will be more apparent to those skilled in the art. The exemplary embodiments utilize distributed architecture for adaptively tailoring information content to electronic device's hardware and network characteristics.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] FIG. 1 is a high-level diagram illustrating an exemplary system for accessing, adapting, and presenting information content to electronic devices;

[0025] FIG. 2 is a diagram further illustrating the server browser of FIG. 1;

[0026] FIG. 3 is a diagram further illustrating the event translator of FIG. 1;

[0027] FIG. 4 is a diagram further illustrating the client browser of FIG. 1;

[0028] FIG. 5 is a diagram illustrating an events message utilized in the exemplary system of FIG. 1;

[0029] FIG. 6 is a diagram illustrating a transmission ACK/NAK message utilized in the exemplary system of FIG. 1;

[0030] FIG. 7 is a diagram illustrating a security handshake request/response and ACK/NAK message utilized in the exemplary system of FIG. 1;

[0031] FIG. 8 is a diagram illustrating an exemplary process of the QDOM of FIG. 1;

[0032] FIG. 9 is a diagram further illustrating the process of the QDOM of FIG. 8;

[0033] FIG. 10 is a diagram illustrating the process of the normalizer of FIG. 1;

[0034] FIG. 11 is a diagram further illustrating the process of FIG. 10; and

[0035] FIG. 12 is a diagram showing an exemplary conversion of output from the system of FIG. 1.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0036] FIG. 1 shows a high-level block diagram illustrating an exemplary system **100** for accessing and adapting feature rich information content for presentation on an electronic device **104**. The accessed and adapted information content is transmitted between an information source **102** and the electronic device **104**.

[0037] The information source **102** includes any type of device such as a web server, application server, database or other backend system, or any interface to an information provider. Preferably, the information source **102** provides information content expressed in a markup language, such as those markup languages known in the art including Hypertext Markup Language (HTML), Extensible Markup Language (XML) with or without Extensible Style Sheets (XSL), VoiceXML, Extensible Hypertext Markup Language (XHTML), or Wireless Markup Language (WML). Furthermore, the information content can store images, video, audio information. Preferably, the information source **102** can be accessed through an information access network **106** such as a local area network (LAN) or wide area network (WAN).

[0038] The electronic device **104** includes any type of device such as a personal computer (PC), wireless telephone, personal digital assistant (PDA), hand-held computer, net-

work appliance, and a wide variety of other types of electronic devices that might have navigational capability (e.g., keyboard, touch screen, mouse, etc.) and an optional display for viewing downloaded information content. Furthermore, the electronic device **104** can also include a device such as a set-top box, internet access appliance, infra-red remote control used with a set-top box, and so forth. Moreover, the electronic device **104** can include any type of device that has the capability to utilize speech synthesis markups such as W3C (www.w3.org) Voice Extensible Markup Language (VoiceXML).

[0039] Information content from the information source **102** is preferably retrieved and tailored for use on the electronic device **104** by a distributed browser **108**. The distributed browser **108** is generally made up of a server browser **110** and a client browser **112**. By utilizing the distributed browser **108**, smaller electronic devices with limited hardware capability can access feature rich information or data. Moreover, the distributed browser **108** allows for efficient use of the communications network **114** bandwidth. Of course, electronic devices with high processing power, fast network connection, and large memory can also use the present embodiments.

[0040] In the exemplary embodiment, the server browser **110** and the client browser **112** are hosted on separate platforms. For example, the server browser **110** might be hosted on a back-end server, and the client browser **112** might be hosted on the electronic device **104**. However, it should be understood that the server browser **110** and client browser **112** can be hosted on the same platform such as on an electronic device, especially if the platform or electronic device has the appropriate hardware and network capabilities.

[0041] The server browser **110** can access information content at the information source **102** via the information access network **106**. In the exemplary embodiment, the server browser **110** operates as a client of the information source **102**. For example, using a known suite of communications protocols such as Transmission Control Protocol/Internet Protocol (TCP/IP), the server browser **110** can issue a Hypertext Transfer Protocol (HTTP) request to the information source **102** over the information access network **106**. By utilizing HTTP requests, such as is known in the art, the server browser **110** can access information content, including applications, static and dynamic content, at the information source **102**. Dynamic content can include script codes such as JavaScript, developed by Netscape (www.netscape.com), and Jscript, developed by Microsoft (www.microsoft.com).

[0042] Preferably, communications between the client and server browsers **112** and **110**, respectively, are via a defined application protocol implemented on top of a wired or wireless transport layer depending on the nature of the electronic device **104** and communications network **114**.

[0043] Therefore, the communications network **114** might include a wired network such as those that utilize Ethernet or similarly IEEE 802.3 protocols. The communications network **114** might also include a wireless network such as a local area wireless network (LAWN) or wireless local area network (WLAN). Moreover, the communications network **114** might include wireless networks that utilize other known protocols and technologies such as Bluetooth, wireless application protocol (WAP), time division multiple access (TDMA), or code division multiple access (CDMA). Furthermore, the communications network **114** is not limited to

terrestrial networks, but can utilize other forms of transmission, as is known in the art, such as a satellite connection.

[0044] To provide an exemplary illustration, assume that a PDA hosts a client browser, a PC hosts a server browser, and the PDA and PC are both connected to an Ethernet network. Then, the client browser and the server browser could perform information transactions over the Ethernet network. Such transactions would utilize Ethernet or similarly IEEE 802.3 protocols. Nevertheless, in this example, the client and server browsers communicate over a wired network.

[0045] In another example, assume that an internet-enabled refrigerator hosts a client browser, a set-top box hosts a server browser, and both could perform information transactions over a Bluetooth or IEEE 802.11 wireless LAN. Then, according to this example, the client and server browsers are communicating over a wireless network.

[0046] Referring again to FIG. 1, a commercially available or standard client browser **140** can also be supported. Preferably, an event translator **136** is used to convert a request/response protocol, such as an HTTP request, from the standard client browser **140** (e.g., WML, XHTML, cHTML, etc.) to an event that the server browser **110** recognizes. Preferably, the translation process includes event information, content information, and the context of the event such that transactions between the standard client browser **140** and the information source **102** (e.g. HTML form submission) are preserved. Therefore, by using the event translator **136**, the server browser **110** can provide an interface to any end user application with a known protocol. Thus, for example, an electronic device **104** can utilize the client browser **112** or standard client browser **140**, or both at the same time, if so desired.

[0047] The server browser **110** can be hosted on any platform with sufficient hardware capability for performing tasks by the server browser **110** described herein. Such platforms can include but are certainly not limited to desktop or laptop PCs, servers, computer clusters, or embedded devices. It should also be understood that the server browser **110** can also be hosted on the electronic device **104**, especially if the electronic device has the hardware and network connection capability.

[0048] According to the exemplary embodiment, the server browser **110** can authenticate itself with the information source **102**, facilitate the request of the information using a protocol acceptable to the information source **102** (e.g., an HTTP request for a web server), provide secure transactions with the information source **102**, provide secure transactions with the client browser **112**, execute embedded scripts or code segments, and resolve necessary external references (e.g., request HTML frames or script sources) to complete the information model. Preferably, the server browser **110** also includes information content caching and data pre-fetch for performance gain.

[0049] Furthermore, the server browser **110** can perform information content transformations or apply device specific style sheets to aid in presentation (e.g., display or voice) and navigation (e.g., keyboard, touch screen, or scrolling), and perform content grouping for electronic devices that accepts data in limited quantities.

[0050] To deliver these capabilities, the server browser **110** preferably contains the modules including user agent **113**, cookie handler **113**, QDOM **116**, script executor **120**, normalizer **124**, serializer **128**, and connectivity **132**, each described below. A session manager **108** is also included to

manage the session between the client browser **112** and the server browser **110**. Similarly, the session manager **108** can also manage the session between the standard client browser **24** and the server browser **110**.

[0051] FIG. 2 is a diagram further illustrating the server browser of FIG. 1. The server browser utilizes a user agent **113** for accessing information at the information source **102**. Preferably, the user agent **113** has the functionality of a traditional PC browser (e.g., Netscape Navigator, Internet Explorer, and so forth) as well as extended functionality, described below, due to the distributed nature of the electronic device **104**. To access the appropriate information content at the information source **102**, the user agent **113** communicates the requested resource identifier to the information source **102**.

[0052] For example, the user agent **113** might transmit an HTTP request to a remote web server that hosts yahoo.com. According to this example, the user agent **113** would transmit a resource identifier to request a specific web page or ask the remote web server to perform a database query. The request including the resource identifier is broken into HTTP packets and the packets are sent across the Internet's TCP/IP communications infrastructure to the remote web server. The resource identifier then enables the host computer to locate the requested page at yahoo.com and return the information content to the user agent **113**.

[0053] In addition to transmitting the resource identifier, the user agent **113** might inform the information source **102** of the client browser **112** type, electronic device **104** capabilities, and user preferences in the request headers and receives information identifying the properties of the data received (such as the content type, length and encoding) in the response headers. The headers that are sent back and forth between the information source **102** and the server browser **110** may also contain one or more cookies stored at the server browser **110** on behalf of the client browser **112**.

[0054] Preferably, the user agent **113** conforms to the broader industry definition of the term as a component of the server browser **110** that acts on behalf of the electronic device **104** to request information from an information source **102**. The requested information content can be from any information source including a web server as described above, but is not restricted to a web server. Other sources of information content might include an email server, Instant Messaging server, database or other storage of information. Additionally, the means through which the user agent **113** communicates with the information source **102** includes the HTTP protocol as described above, but of course, is not limited to that protocol.

[0055] Information content might also use XML information content and XSL style sheets instead of HTML as the preferred internet/intranet information content format. By using XML information content and an XSL style sheet, it can provide a clear separation of data and presentation. The XSL style sheet is applied to the XML information content by an XSLT engine to present the information content to an electronic device **104**.

[0056] The XSL style sheet is applied to the XML information content at the information source **102**, but preferably the client browser **112** can also apply the XSL style sheet to the XML information content. In this case, the server browser **110** preferably employs an XSLT engine to apply the XSL style sheet to the XML data before normalizing to produce

content. One such example would be a WML client browser used to request an XML+XSL combination that produces XHTML.

[0057] Alternatively, the information content author may choose to use the original XML and apply templates and/or wireless markup instead of or in combination with XSL style sheets.

[0058] In addition to providing normalizer functionality, the system can also use templates and meta-tag markup to alter the original information content to better suit an end user application for which it was not originally designed. This can be achieved through the addition, removal or substitution of sections of content, tags and attributes (separately or together) in the markup, described more below.

[0059] Information content might also use VoiceXML (www.voicexml.org) which is an XML based language for specifying voice dialogs, including audio prompts and text-to-speech (TTS) for output and touch-tone keys (DTMF) as well as automatic speech recognition (ASR) for input. VoiceXML technology enables consolidation of voice and web applications. For example, it can be used with voice-only devices to access a voice portal, or used to facilitate multi-modal (graphical and voice) dialogs to VoiceXML enabled client browsers).

[0060] Preferably, the system (**100** in FIG. 1) via the user agent **113** has the ability to read and process VoiceXML markup as well as convert from one markup (from WML for instance) to VoiceXML format. In addition, templates and/or wireless markup can be used to specify which parts of a web page are to be audible (i.e. converted to VoiceXML) and which are to be rendered visually by the browser. The server can interact with a VoiceXML gateway (much in the same way as it does with the WML gateway) to facilitate the VoiceXML based services.

[0061] Location based services might also prove to be very popular in this industry as they are well suited to mobile applications. Preferably, the server browser **110** via the user agent **113** has the ability to interact with the network entity supplying the location information via a defined protocol. The current coordinates of the electronic device accessing the network are preferably sent in the request headers to the content (web) server and/or be accessible via session cookies so that the device can easily utilize this location information. This functionality enables useful applications such as a restaurant locator that lists restaurants within a few miles of the user's current location.

[0062] Referring back to FIG. 1, the server browser **110** contains a cookie handler **115**. Cookies provide a means of personalizing the information content that is retrieved by the user agent **113** on behalf of the user of the electronic device **104**. Preferably, the cookie handler **115** supports session and persistent cookies. Session cookies are valid for the current user's session and persistent cookies can expire after a predetermined time specified in the cookie or be permanent. An added benefit to server side cookie processing is that the user is provided access to his or her cookies from multiple electronic devices and the user's cookies are not lost when the user changes electronic devices.

[0063] Referring back to FIG. 2, the user agent **113** translates the requested data content, if necessary, into a recognizable markup language for further processing. The markup language may be in the format of XML, WML, HTML, or any

other markup language or technology (e.g., video, audio, image) that incorporates the features used by the present embodiments.

[0064] The translated information is then organized into a logically structured format for further processing by the QDOM 116. The QDOM 116 efficiently constructs a nodal structure. The use of the QDOM 116 enables a standard structured interface to the retrieved content that can be utilized by all modules of the server browser 110. The QDOM 116 can effectively and efficiently store the information content in a standardized structure for use by the normalizer, more described below.

[0065] Referring back to FIG. 1, the server browser 110 has script executor 120 for assisting the QDOM 116 in interpreting embedded script code in the information content received from the information source 102. The script executor 120 is preferably capable of supporting the European Computer Manufacturers Association standard (ECMAScript revision 3), which is most prevalent in the industry, but may also be capable of handling other scripting languages, known in the art, such as JavaScript, Jscript (Microsoft's extending implementation of ECMAScript), Visual Basic Script (VBScript), or WMLScript. The script executor 120 enables programmatic access to the QDOM 116 representation of the document.

[0066] This extension to the QDOM 116 can allow executed script code to modify the resultant document that is sent to the client browser 112, thus enabling dynamic content generation via scripting. Script executor 120 can also allow programmatic access to the cookies for a particular user, giving the content author the ability to create, modify or retrieve cookies associated with a given resource via script code. To interact with the user, communications between the script executor 120 and the client browser 112 is done via script events that are part of the application protocol between the server browser 110 and the client browser 112.

[0067] Referring again to FIG. 2, data content that has been transformed into a DOM tree is then forwarded from the QDOM 116 to the normalizer 124. Preferably, the normalizer 124 sends the DOM tree first to a template normalizer. If the template normalizer is unsuccessful at normalization, the DOM tree is then forwarded to an automatic normalizer where the data is normalized and then forwarded to the serializer 128 to be sent to the electronic device 104 via the connectivity manager 132, further described below.

[0068] The serializer 128 utilizes the normalized tree as input and produces a media stream targeted for a specific electronic device 104. Applying a style sheet or formatting rules to the DOM tree outputs a document (e.g., an XML document) that will be streamed to the electronic device 104. Preferably, the formatting rules are electronic device 104 specific and take into account display size, font types, color etc. as well as the particular markup language(s) supported by the target electronic device 104.

[0069] The server browser 110 has connectivity manager 132 for interacting with the client browser 112. Connectivity manager 132 sends and receives information to the client browser 112 using an event format and protocol such as a proprietary format (e.g., OBML, described below) and XML event messages. According to the requirements of the electronic device 104, the events may be translated via the event translator 136 (FIG. 1) to use an externally defined format and protocol such as WML and WAP.

[0070] Referring back to FIG. 1, the event translator 136 preferably provides the server browser 110 with compatibility with any standard client browser 140 or end user application that employs a known protocol such as HTTP. Current examples of such standard client browsers 140 include both WAP and non-WAP based WML browsers, HTML browsers, XHTML browsers, as well as both iMode and non-iMode compact-HTML (cHTML) browsers.

[0071] FIG. 3 is a diagram further illustrating exemplary uses for the event translator of FIG. 1. The event translator 136 can be utilized on the server browser 110 side or the client browser 112 side, depending on which client browser 112 or standard client browser 140 is utilized. According to the server browser 110 side, the event translator 136 operates as the interface between a standard client browser 140 and the information content data stored in a DOM format at the server browser 110. Preferably, the DOM is a QDOM 116 that identifies each node in the document using a unique value. According to the client browser 112 side, the event translator 136 can exist on the client browser 112 and provide an interface between the third party viewer and the micro-gateway 144. One skilled in the art would appreciate that the event translator 136 is not limited to the server browser 110 side or the client browser 112 side, but can also operate between and externally to the server browser 110 and client browser 112, if so desired.

[0072] Preferably, the event translator 136 translates requests for information content to known events that can be used to generate or modify a DOM tree, dynamically assigns unique device identifiers to identify the information source 102 of standard client browser 140 events, sends events and receives responses to and from the server browser 110, and manages sessions and transactions (including timeouts, authentication, error handling etc.)

[0073] Referring back to FIG. 1, the client browser 112 can be hosted on an electronic device 104 such as a PDA, handheld PC, mobile phone or any device with sufficient navigation and presentation capability. The client browser 112 provides the user interface for presentation or rendering of the retrieved information as well navigational capability.

[0074] Furthermore, portions of the client browser 112 may be used by a standard or commercially available client browser. In such examples, the client browser 112 can provide distributed browser functionality that is compatible with the standard or commercially available client browser.

[0075] Moreover, the electronic device 104 is preferably validated by user/appliance ID, which can be stored within a database on a server. This ID authenticates the electronic device 104 and validates that it is allowed to access specific data content found in a particular data source.

[0076] In an exemplary embodiment, the client browser 112 can access information content via the server browser 110. Additionally, the client browser 112 preferably allows the user to submit information content or form data back to the information source 102. The form data is a response to a query posed by the data content of a particular document from the information source 102. Events containing the data for each component in the form are forwarded to the server browser 110 by the electronic device 104 where they are formatted in accordance with the content of that document by the server browser 110. The result may be an error notification (e.g. network timeout, bad data, etc.) or display of a new document received from the server browser 112 as a result of server side 112 processing of the submitted form data.

[0077] Referring now to FIG. 4, the client browser 112 preferably includes a microbrowser 148, event controller 152, and DOM store 124 according to the industry standard Model View Controller (MVC) representation. The microbrowser 148 is one example of an end user "View" application and represents information such as graphical or textual display, or audio to the user. The event controller 152 processes events to and from the server browser 110. The DOM store 124 is utilized for caching the information content received over the communications network 114.

[0078] The event controller 152 and the DOM store 124 operate as a micro-gateway 144 between the server browser 110 and an application 168 for interaction with the end user. In the exemplary embodiment the application 168 presents a typical browser interface allowing display and navigation of content, form interaction and submission and so forth. It should be understood, however, that the micro-gateway 144 can also support multiple different end user applications 172 on the electronic device depending on their availability and the nature and type of content data delivered to it. Examples of such end user applications include, but are not limited to, email, instant messaging, media players and other such plug-ins. Further, multiple different kinds of browsers designed for particular markup types (HTML, cHTML, WML, etc.) and so forth can also be supported by the micro-gateway 144.

[0079] In one aspect of the exemplary embodiment, the micro-gateway 144 presents an external interface to other applications 168 and 172 that consists of a well defined interface to the DOM Store 124 component and an interface to the event controller 152 using the same event model that is described below for communications internal to the distributed browser. In another embodiment, the micro-gateway 144 can be combined with the end user application 168 and 172 and use a more tightly coupled internal interface.

[0080] Additionally, the micro-gateway 144 can use an event translator (not shown in FIG. 4) to provide an interface to third party or commercially available applications such as HTML or WML or cHTML browsers. For example, according to an aspect of the present embodiment, a micro-gateway 144 and an event translator to cHTML can be used to provide an interface between the server browser component and the third party cHTML browser known as Pocket Internet Explorer on a Pocket PC device running the Microsoft Windows CE operating system.

[0081] The microbrowser 148, renders the information content transmitted to the client browser 112 by the server browser 110. In the exemplary embodiment, the rendering includes visual representations (both textual and graphical) of the markup elements, but can be extended to provide other representations (e.g., audio) according to the capabilities of the electronic device 104. The format of the representations can be fixed by particular microbrowser 148 implementations such as a WML or proprietary (e.g., OBML) browser, or can be modified according to an XSLT style defined in conjunction with the content markup.

[0082] Typically the microbrowser 148 is used to directly display markup based content received through the micro-gateway 172. In addition, the markup based content can be used to adaptively tailor the microbrowser 148 according to directives contained in the information content. Adaptations can include embedding application logic in the content presentation, modifications to the interface (menus, titles, etc.) and other configuration of the browser application or device.

[0083] It should be understood, however, that an additional property of the browser is the ability to download and install other applications or plug-ins as needed to support non-markup based content, including images, audio, video, and multipurpose internet mail extensions (MIME) or secure MIME (S/MIME) document formats such as plain text, Acrobat (e.g., ".pdf" format), Microsoft Word and so forth. Content of these types is can be viewed through the use of these other applications or plug-ins by the micro-gateway 144 or microbrowser 148, or both 144 and 148.

[0084] Preferably, the event controller 152 is an event handler. Events to and from the server browser 110 are formatted according to the particular electronic device 104 in use. In the exemplary embodiment, XML event messages and a proprietary protocol are interpreted by the event controller 152 to manage data and events to and from the server browser 110.

[0085] The DOM store 124 provides a secondary cache of the information content stored on the server browser 110. The secondary cache preferably resides on the electronic device 104 to reduce the need to pass data between the server and client browsers 110 and 112, respectfully. The information content that the user desires is transmitted to the client browser 112 from the server browser 110. In the exemplary embodiment, however, once the information has been transmitted, it is stored for reuse. The information content is retained on the electronic device 104 while it is valid and while there is sufficient space to store it. The information content is stored in a DOM structure according to the W3C definition of an XML document and can be accessed by the microbrowser 148 or other applications on the client browser 112.

[0086] When the DOM is examined or modified, the event controller 152 preferably delegates the event to the DOM facade 118. These events include click, blurchange, submit, expand, etc.

[0087] In the case of a click event, the DOM facade 118 preferably examines and executes the content and/or script associated with clicking on a given node. In the case of a blurchange event, the DOM facade 118 preferably modifies the DOM so it reflects that the user has provided data. In the case of a submit event, the DOM facade 118 preferably examines the existing user input to formulate an appropriate form submission request. In the case of an expand event, the DOM facade 118 preferably delegates to a serializer to server the contents of a given folder to the client browser.

[0088] In cases where a standard browser (cHTML, WML, XHTML, etc.) is used, there is preferably no event controller. The requests from the standard browser are interpreted and translated by the event translator into events that the DOM facade 118 understands.

[0089] An "active" page is a page from the information source that is of higher than normal interest to the user of the client browser 112. It is given an active status in the cache and retained on the electronic device 14 when it otherwise might have been deleted for space or timing reasons. Where a document has been made part of the "active" cache (either through a push from the server or explicitly requested by the user through a client application such as the micro-browser), the content and any related data for that document can be accessed when the electronic device 104 is out of coverage.

[0090] Preferably, the client browser 112 handles "active" page content submissions separately and can store form data for those submissions to allow repeated attempts to submit that data until either the submission is successful or the user

explicitly instructs the client browser application to delete the form data. Delivery of form submission data for the “active” content pages is guaranteed by the storage of the data in the client application browser.

[0091] Further, the client browser **112** retains the context of “active” page submissions and allows the user to access a history of chained interactions with the information source as a series of submissions of data and responses to the submissions. Note that each response can itself require a further submission and in turn generate another response, thus forming the chain. The status of an active submission in progress can also be viewed in the client browser.

[0092] The distributed browser **108** preferably utilizes send and receive events to convey information between the server and client browser **110** and **112**, respectively. Events between these components can be classed as an events message, acknowledgment/negative acknowledgment (ACK/NAK) message, security handshake request/response, and decrypt ACK/NAK message.

[0093] An events message preferably carries information between the server and client browsers **110** and **112**, respectively. An ACK/NAK message is used to confirm or deny receipt of an events message. A security handshake message is used to transport information used by encryption and decryption routines. A decrypt ACK/NAK is used to report success or failure in the security routines.

[0094] The first byte of the messages preferably contains an identifier that uniquely defines which type of message is contained in the data being sent. The 2-byte integral values are always “little endian” or bytes at lower addresses have lower significance.

[0095] FIG. 5 shows the structure of an exemplary events message that is transmitted between the server browser **110** and the microbrowser **148** (i.e., via the network interface **156** and event controller **152**). The event message may be modified or intercepted by the event controller **152**. The event message includes header identifier, header version number, and the unique message identifier. Additionally, the event message also includes the event type such as response, original, push, or stop. Moreover, event data is included at the end of the events message.

[0096] The event data area of the events message may be compressed and/or encrypted as specified in the header component. When converted to plain text, the data area is defined as having the following exemplary structure:

<p><XML Events Message> =</p> <p><Event Protocol Version> =</p> <p><Session ID> =</p>	<p><Event Protocol Version><Event Separator><Session ID><Event Separator><XML Events><EOM></p> <p>Integer</p> <p><Server Session ID> </p> <p><Server Session ID><integer separator><Client Session ID></p>
---	---

-continued

<p><Server Session ID> =</p> <p><Device Type> =</p> <p><Page ID> =</p> <p><Client Session ID> =</p> <p><XML Events> =</p> <p><Event> =</p> <p><Event ID> =</p> <p><XML Node> =</p> <p><Attributes> =</p> <p><value> =</p> <p><EOM> =</p> <p><Event Separator> =</p> <p><Field separator> =</p> <p><Value separator> =</p> <p><Integer separator> =</p>	<p><Device Type><integer separator><Page ID></p> <p>Integer (uniquely identifying different devices)</p> <p>Integer</p> <p>Integer</p> <p><Event> </p> <p><Event><Event Separator><XML Events></p> <p><Event ID><field separator><XML Node><field separator><Attributes></p> <p>integer (see table below)</p> <p>Integer</p> <p><value> </p> <p><value><value separator><Attributes></p> <p>ASCII text</p> <p>\r\n (0x0D 0x0A)</p> <p> </p> <p>*</p> <p>^</p> <p>,</p>
--	--

All events contained within an events message belong to the same session or page of content.

[0097] When there is only a single client browser **112** on the electronic device **104**, the session id information needs only to specify an identifier for the server browser **110** session or content page. When there are multiple client browsers on the electronic device **104** (e.g. multiple browser windows, browser+instant message client, or other combinations), the events message should identify which client browser **112** it is associated with.

[0098] Preferably, the page id is generated on the server browser **110**. When the client browser **112** has no valid server session id to send, a zero will be sent. Zero is not used as a valid session id.

[0099] For any Uniform Resource Locator (URL) data that is contained in an events message, standard URL encoding as is known in the art, is used to ensure that the information content does not include any of the characters special to a proprietary packet format (i.e., “|”, “*”, and “^”). For any XML content contained in an events message, standard HTML encoding, as is known in the art, is used (e.g., where characters can be represented by “&#n;” where n is the ASCII code for that character).

[0100] The node value maps directly to a node in the DOM tree (e.g., output of the QDOM **116** in FIG. 2) and signifies the node affected by the event. For some events (e.g. load, error) the node is set to 0, indicating that there is no direct connection to a particular node. Other events (e.g. expand, onblur-change, submit, onclick) have a direct correlation to an element in the QDOM and are targeted to that element by the value set in the events message.

[0101] The following table lists the different events that can be contained within an events message:

Event	Attribute list	Description
Cleaned	(none)	Notification to clients that old data has been purged so that clients can check any cached page references
Error	Error message	Description of an error on server
Expand	(none)	Client request for content of a normalizer folder

-continued

Event	Attribute list	Description
Expand	Document	Content of a normalizer folder
Load	URL, summary option, table option, JavaScript option	Client request for a new content page, including options on whether to normalize, include tables and allow JavaScript processing
Load	URL, summary option, table option, JavaScript option, document	Content page response or push from server, including options set in original request
Notify	Message data	Non-error message to client(s)
Onblurchange	new value for input element	The user has changed the content of an input element and moved focus away from it
Onclick	(none)	Click on link element
Reload	(none)	User wishes to force a reload of the current content page in the device application. The server will replace any existing session with a new load of the page from the web.
Stop	(none)	User request to stop any message identified by the MessageID in the header.
Submit	(none)	User has completed a form and is submitting all onblurchange data to the server
Authenticate	Realm	The remote HTTP server issued a challenge string requiring the user to prove possession of a valid user id and password for the realm <username>:<password>, encoded in Base64 to be submitted back to the origin server
Authenticate	Authentication tokens	Server initiated message. The device displays the alert message followed by an OK button.
Alert	Message	Device returns when the user presses OK.
Alert	(none)	Server initiated message. The device displays the question followed by an OK and Cancel button.
Confirm	confirmation status	Device returns the button pressed.
Prompt	Message, default	Server initiated message. The device displays the message followed by a text input field and OK, Clear and Cancel buttons. The default message is displayed as the initial input.
Prompt	Button pressed, return string	If the user clicks the cancel button, return string should be null. If the user clicks the OK button, Device returns the value currently displayed in the input field.

[0102] To conserve bandwidth over the communications network 114 between the connectivity manager 36 and the network interface 156, an events message may contain more than one event. In one exemplary embodiment, all onblurchange events are stored by the microbrowser 148 until a submit event is generated. At that point they are bundled together into a single events message for transmission to the server browser 110.

[0103] FIG. 6 shows the structure of an exemplary transmission ACK/NAK message that is transmitted between the radio interface (156 of FIG. 4) and connectivity (132 of FIG. 2). An ACK message is preferably used when the underlying communications network 114 does not provide message delivery confirmation to the network interface 156 and connectivity manager 132. A NAK message signifies that although an events message was received, it could not be processed (e.g. because of low memory conditions).

[0104] FIG. 7 shows the structure of an exemplary message used by the security subsystems of the connectivity manager 132 and the network interface 156. The security handshake request and security handshake response messages are used to exchange public keys between the connectivity manager 132 and network interface 156. The security ACK and NAK messages are used to signify successful decryption of events messages that have been encrypted using the shared public

keys. Receipt of a security NAK message at any time or a need to encrypt the data in an events message when public keys have not been shared preferably initiate a security handshake request.

[0105] The server browser 110 includes a QDOM 116. The QDOM 116 utilizes a in-memory representation of an document tree as a single mutable object or creation of a DOM does not require creation of a language object for every node of the tree, whether that language happens to be Java or C++ or another object oriented language.

[0106] The mutability of a QDOM 116 is preferred, because transformations of the DOM tree will be applied, resulting in a new tree structure within the same QDOM Object. The architecture of a QDOM 116 allows these transformations to be performed in an efficient manner with regard to both speed and resources used.

[0107] A QDOM 116 consists of an aggregation of N re-usable buffers that contain arrays of raw bytes. As the QDOM grows, additional re-usable buffers are added, only as needed. Some of the re-usable buffers contain binary information describing the DOM tree structure, tree dependencies, and references to information content data. Other buffers contain the actual content data.

[0108] FIG. 8 shows one exemplary embodiment in which separate QDOM 116 arrays 180 are used for the values rep-

representing the following properties of each element node **184**: element name tag **188**, parent node **192**, previous element sibling **196**, next element sibling **200**, first child element **204**, and first attribute **208**. Similarly, each attribute node can be described with the following properties including attribute name tag, attribute value tag, previous attribute sibling, and next attribute sibling. Separate arrays can be stored in the QDOM **116** for attribute data, or it can be overlaid in the same arrays used for element data.

[0109] In another exemplary embodiment, the same information can be stored in structures for each node and attribute. The QDOM **116** contains one or more arrays of each of these structures. The choice of the means of storage depends on the functionality of the programming language employed for the QDOM.

[0110] The actual string names of the tags and attributes of tree elements are replaced by a corresponding value equivalent. A dictionary of the strings and their corresponding value is preferably built up as necessary to deal with a particular set of XML tags. For performance reasons, pre-compiled dictionaries can be used for the well-known markup languages, such as HTML or WML.

[0111] FIG. 9 shows a re-usable content buffer **212** that the QDOM array **180** references when information content that is not well known (such as plain text data) is used. The QDOM array **180** preferably stores the start and end positions of the text in the content buffer **212**. In another exemplary embodiment, the content buffer **212** stores zero terminated strings and the QDOM array **180** stores the start position.

[0112] Preferably, the interface to the QDOM **116** is value based because every node (for example, see **184** in FIG. 8) of the tree has a unique value associated with it. All operations on the nodes in the tree that the interface provides can be carried out using that value as a reference to the affected nodes. All comparisons between nodes are also value based, so expensive string comparisons can be avoided.

[0113] Since the underlying structure of the QDOM **116** groups of raw bytes, it can easily and efficiently be serialized to and from permanent storage, thus reducing the amount of random access memory (RAM) memory necessary to support multiple users and multiple documents per user.

[0114] In situations where resources are limited, such as on a PDA, the QDOM **116** structure in the form of DOM store, XMLDocument, and XMLElement (**124**, **162**, and **164** in FIG. 4 respectfully) can also be used efficiently by the client browser **112**. The QDOM storage is divided into smaller groups that are held in a permanent storage area (e.g., FLASH). Only such groups as are needed for the current operations on the QDOM are retained in or moved to a fast memory area (e.g. RAM). This provides high performance through an efficient use of the data in RAM while still minimizing the actual resource load in use at any one time.

[0115] A QDOM **116** is implemented as a re-usable object, so rather than deleting it and having a "garbage collector" reclaim a space occupied by the document, the QDOM **116** can be easily and efficiently re-initialized and used to store some other XML Document.

[0116] A number of preliminary tests have been taken to determine the time saved using the QDOM **116** as compared to the node-based interface of the standard W3C DOM. The tests show more than 100x improvement over other W3C compliant models.

[0117] The normalizer organizes the DOM tree into tiers or folders under headings that contain related content. The result

is a set of hierarchical DOM node collections. The characteristics of font, font size, font color, hue saturation comparison of background and foreground color and Cascading Style Sheet or XSLT properties are used to determine the weight of a text node. The weight is then used to determine whether it will be inserted into a normalized document tree as a parent or child. The parent nodes become folder titles and the child nodes become the folder contents. Thus, higher weight document objects are pushed to the top of the tree so the user can decide whether to "walk" down the branch or not.

[0118] The normalizer dynamically streamlines and folderized the content automatically or via predefined additional rules to achieve automatically an experience similar to reading a newspaper. The normalizer including the template normalizer and meta-tags allow the content source to be redefined once for all networks and device types. The alternative technologies in the industry are large cycle time, re-development of the content, often specific to one or more of the following: each device ergonomics, or a particular client-only browser, or a particular network type.

[0119] The goal to normalizing is to adapt desktop focus web content to handheld browsers. This requires filtering unsupported content, dropping unneeded content, reordering and partitioning content to improve navigation and application flow for display on a limited device. Some of the functions to normalization are folderize/partition content, drop content not required on a handheld device, reorder content, provide prompts/names to input elements

[0120] The normalization process can utilize a weighted heuristic and pattern recognition to create a the contextual relationship of with nodes in the source tree. The output from the normalization process is a hierarchical content tree. Preferably, the normalized tree is not specific to a particular presentation language. Therefore it can be transcoded for display by any type of client browser.

[0121] Content collapsing rules in the automatic normalizer utilize the previous page loaded to determine if similar constructs exist in a page which can be collapsed into folders or selectable input elements on subsequent loads. This is performed by comparing the previous page loaded with the current page. The trees of the documents are compared to determine if similar fragments (list of links, table, image) exist. The similar fragments of the tree are collapsed into folders or select input elements. The effect is to conserve display space on the device.

[0122] Electronic devices can have limited display characteristics such as display size, font types, color etc. Most web content is tailored for display on desktop browsers which not only suppose a large screen, but also support a rich set of fonts, colors, and formatting constructs such as tables and frames. The normalizer adapts existing information content for display on the electronic device **104**. The normalizer **124** includes an automatic normalizer **80** and template normalizer **84**.

[0123] Referring back to FIG. 2, the automatic normalizer **80** in the normalizer **124** maintains the context of the information content before taking the electronic device **104** specifics into account. The automatic normalization process does this by organizing the information content into folders. The result of this approach is that sets of nested folders are created which the user can "walk" the information content on the electronic device **104**. The titles of the folders are sent to the electronic device **104** first and the user can determine if the contents of particular folders are of interest. This not only

increases usability in terms of reduced content to scroll through for the user and time spent scrolling through the page, it also optimizes wireless bandwidth utilization because less data is sent to the electronic device **104**.

[0124] It should be noted that while the exemplary embodiments of the normalizer processes concentrate on the normalization of HTML content, including that generated by scripting technologies such as JavaScript, these same processes can be applied to other markup content. It is well suited to any XML content.

[0125] The automatic normalization process traverses a DOM tree from the QDOM **116 40** and creates a new, normalized tree. Preferably, the original DOM is transformed rather than copied, so that it becomes the normalized tree itself. This provides both efficient performance and efficient memory utilization.

[0126] The normalization process begins with the root node of the document and traverses the tree along a depth first path to maintain context at all times.

[0127] If a node is the beginning of a table, a table pattern recognition process is preferably executed. The entire table is weighted and pattern recognition criteria are compared to determine if the table matches a defined pattern. The table recognition criteria define a profile for different data table types. Each cell in the criteria is defined to be either greater than, less than or equal to a root table weight, a “don’t care” or defined to contain certain nodes such as anchors or images. The root table weight can be derived from any cell in the table such as the cell at position row 0, column 0 or can be derived outside the context of the table. These criteria define the pattern that is attempting to be matched. If a pattern is recognized, the table cells are formatted corresponding to that pattern. If a pattern cannot be recognized, the weighted node processing continues.

[0128] The major part of the weighted node process is the maintenance of a weighted node stack. The first element of that stack is always the “DOCUMENT” itself, having by default the highest possible weight. The normalization process takes the next node from the DOM tree. The node is first filtered to determine if it has an effect on weighting or presentation. If the node is not significant it is preferably dropped. Nodes such as the HTML tag in HTML are not significant since the tag has no effect on presentation. Next it is determined whether the node is a weighting node or a content node. Weighting nodes are nodes that affect the display of rendered content such as a bold or heading format tag. Some weighted tags may have a negative weight that allows nesting of the tags and emulates a hierarchy of nodes weights such as nested list items. Content nodes are nodes such as text nodes, input nodes, and image nodes.

[0129] When a weighted node is encountered, the node weight is added to the accumulated weight. When a content node is encountered it is assigned the accumulated weight and becomes a weighted node. The weighted node finds its position on the weighted node stack by finding the lightest element on the stack with a weight greater than his (node’s parent). Stack nodes from that point on are preferably deleted from the stack. The new weighted node becomes a child node for that parent. When the node goes out of scope (e.g. if a TABLE is ended), the normalization process checks the weighted node stack to remove all nodes that belonged to the expired scope of influence.

[0130] For example, if the node on the weighted node stack is part of a table and the table scope of influence has expired,

then that node is removed from the weighted node stack. However, if that node belongs to more than one scope of influence (e.g. it is part of one table nested inside another table), all scopes of influences are checked against that node and it is removed preferably when they are all expired. When the inner table ends, node stays until it replaced by a heavier node or the outer table ends.

[0131] The template normalizer **84** is a tool for recognizing patterns within a document through a DOM tree and applying changes to those patterns as specified in the template syntax. Preferably the template normalizer **84** is part of a larger process of normalizing all documents. One step of the larger process is an attempt to match and apply templates where possible.

[0132] The template normalizer **84** preferably handles numerous variations of the same document as dictated by the application logic that produces it. For example, if a certain data table could have various numbers of columns and rows, or even not be present in the document at all, the template normalizer **84** is preferably still capable of dealing with those variations.

[0133] The template normalizer **84** is capable of recognizing an document from a set of potential documents that could be produced by the application. For example, if the application produces two completely different documents depending on whether a user is logged on or not, a single template could still recognize the outcome and apply its changes to either one.

[0134] The template normalizer **84** is also capable of recognizing a change in the overall structure of the document to determine when its rules are not applicable any longer. In that case, it will not attempt to apply the changes, but will convey the document to an automatic normalizer **80**.

[0135] The template normalizer **84** uses a regular expression pattern-matching machine as applicable to DOM trees. The syntax of a template is strict XML as described by the World Wide Web Consortium (www.w3c.org) and includes a number of proprietary regular expression tags and attributes that describe how the template normalizer **84** should match and modify original content.

Tags:

[0136]

<xgrp>	equivalent to a bracket in Regular Expressions
<xany>	equivalent to a wild card in Regular expressions
<xalt>	equivalent to ‘or’ in Regular expressions
<xadd>	signifies the addition of contained markup
<xnone>	equivalent to “empty” in Regular Expressions

Attributes:

[0137]

“xtimes”	the number of times to apply a recurring pattern
“xtitle”	specifies a new title for a matched pattern
“xid”	specifies a name of an XML node
“xparent”	re-parent an XML node to a specified element
“xdrop”	delete a node from the tree
“xformat”	produce a formatting attribute for an input field
“xaction”	apply a user-specified algorithm to the branch of a tree

[0138] The normalization process preferably scans a dictionary of templates and an initial comparison is made based on a URL specified for the template and the URL of a document to be processed. If the URLs match, then the template normalization process begins.

[0139] The template normalizer 84 deals with a document or XML document in two steps: first it uses the regular expression pattern-matching machine to impose itself over a document and attempts to match the template to the document content. The match is performed using the regular expression tags in the template to apply standard regular expression algorithms. If that process fails, the changes specified by the template are not applied, and the document is conveyed to the automatic normalizer 80.

[0140] If the match process succeeds, the template normalizer 84 will apply changes as specified by the attributes of the matched regular expression elements. Changes include dropping nodes, creation of new folders or tiers, re-parenting nodes, assigning new titles to nodes, etc.

[0141] During the application of the changes, the template normalizer 84 can use a complex state variable syntax to refer to the parts of the document. These variables can be set as pointers to nodes in the DOM or counters. Resolution of a variable expression starts with the inner most expression and is processed outward. This is similar to list processing in the LISP programming language. The inner resolutions are used to resolve subsequent resolutions.

[0142] Where a counter is used in a variable expression, the variable will be resolved using the current value of the counter.

Resolution Example

[0143] If \$z=a and \$ya="data" the expression \$(y(\$z)) would be resolved to

[0144] \$(y(\$z))=\$ya="data".

[0145] \$z gets resolved to a and this creates the expression \$ya which is then resolved to "data".

Counter Example

[0146] If xcounter="x" and the first iteration of an Xgrp is occurring, then the expression \$a(\$x) will be resolved to

[0147] \$a1.

[0148] If a variable is used in the context of an Xtitle attribute, the value for the variable is derived from the text value of the DOM node that is referenced by the variable.

[0149] If the variable is used in the context of an xparent, then the variable is resolved to a DOM node to which to move the referring node as a child.

[0150] The xid attribute is used to set the value of a variable to the DOM node.

[0151] Template normalization involves matching a template DOM tree with an input DOM tree and applying changes to the input DOM tree. The automatic normalization algorithms may be called during the apply step of template normalization where specified by the xaction attribute.

[0152] With integration of the automatic normalization algorithms, a template can be utilized to drop and reorder content while calling the automatic normalization algorithms to partition the content into a hierarchical set of folders.

[0153] FIGS. 10 and 11 illustrate the flow of logic in the exemplary embodiment for determining when to apply the automatic, markup assisted or template normalizer 84 algorithms. It should be noted, however, that the process is not

restricted to the current flow, but can include variations such as the application of the automatic normalizer before the application of the template normalizer.

[0154] At step 220, a DOM tree is preferably obtained from the QDOM and input into the normalizer.

[0155] At step 224, the normalizer determines if a template exists for the DOM tree of the document. If the template does not exist, the DOM tree is forwarded to the automatic normalizer for processing per step 232. If a template does exist, the DOM tree is forwarded to the template normalizer for processing per step 228.

[0156] At step 228, the template normalizer determines if the existing template matches the DOM tree per step 236. If the template does not match per step 236, the DOM tree is forwarded to the automatic normalizer for processing per step 232. If the template does match the DOM tree per step 236, the DOM tree is forwarded to the template application process per step 240 (and expanded in FIG. 10).

[0157] At step 244, if the template apply process fails, then the DOM tree is forwarded to the automatic normalizer per step 232. If the template apply process is successful, then the DOM tree has been normalized into a normalized tree.

[0158] At step 248, the normalized tree is forwarded to the serializer for transmission to the electronic device via the connectivity manager.

[0159] At step 232, the automatic normalizer is applied.

[0160] At step 252, it is determined if the DOM tree has normalization markup or meta-tags. If the document does not have normalization markup or meta-tags, the DOM tree is forwarded to step 260. If the document does have normalization markup or meta-tags, the DOM tree is forwarded to the markup assisted processing per step 256.

[0161] At step 256, the normalization markup or meta-tags are utilized to assist in normalizing the DOM tree into a normalized tree. The normalization markup can provide instruction to the automatic normalizer to create the normalized tree. The normalized tree is forwarded on to the serializer per step 248.

[0162] At step 260, the DOM tree is normalized using a "best guess" processing. After step 260, the DOM tree is normalized into a normalized tree and forward on to the serializer per step 248.

[0163] According to FIG. 11, the template apply process per step 240 is further illustrated.

[0164] At step 264, the template apply process determines to use the automatic normalizer process per step 268 or the template rules process per step 272. If the template apply process determines to use the automatic normalizer rules, the DOM tree is forwarded to step 268. If the template apply process determines to use the template rules, the DOM tree is forwarded to the apply the template rules per step 272. If the template rules are applied per step 272, the DOM tree has been successfully normalized and returns to the normalization process per step 288.

[0165] At step 268, the normalization rules such as user profile, statistics, keywords, history, are applied and the DOM tree is forwarded to step 276 to determine if the document contains normalization markup. If the document does not contain normalization markup, the DOM tree is forwarded to markup assisted processing per step 280. If the document contains normalization markup, the DOM tree is forwarded to the "best guessing" processing for applying pattern recognition and weighting heuristics to the DOM tree and forwarded to the normalization process per step 288.

[0166] Some devices (e.g. those with small screens) do not support the display of tables as in a traditional desktop browser. The problem is determining how to extract content from the table into a linear form so that it is presentable on the device. Table pattern recognition looks for tables that conform to some of the more common uses of the tables for data presentation. A weighting and comparison of table cell nodes in the DOM tree against each other is used to determine the order in which to extract cell data from the DOM tree. The comparison of weights attempts to determine if the nodes match a recognized table pattern. Cell weights are assigned in the same manner as the general normalization process, but other characteristics are also compared. 'Other characteristics' preferably includes the type of cell element (table heading or table data) and if the table cell contains an anchor or an image, but may extend to any particular attribute of the cell data.

[0167] FIG. 12 shows an example Table Pattern as formatted in the original content for a wide screen display (desktop) and reformatted for a small screen device. In this table the first row of table cells contain heavy weight text nodes. These nodes will become headings/parents for the columns. The following rows will become children of the parent nodes as shown in the small screen display result.

[0168] The general normalization rules may not apply to all web sites. Therefore it may be possible to specify specific rules on a URL basis. Preferably, URLs can be matched exactly or partially, such as in the matching of the domain name component only.

[0169] The concept behind adaptive browsing is that most users hit certain links or objects in a document more than others. The user's statistics can be used to increase the priority/weight of an object in the tree in order that the user be displayed that object first. This allows the page to be adapted to the user's tendency/habits. This mechanism will aide in browsing efficiency for the user. Content nodes will accumulate more weight based on the statistics on, for example, the click count on an anchor.

[0170] A User can provide keywords for his profile that can be used to assign weights to the document content. Content matching any keywords would be pushed to the top of the tree by assigning higher weights to the matched elements.

[0171] Markup assisted normalization defines a wireless specific markup that conforms to HTML 3.2 and 4.0 specifications and does not affect the page for display by other HTML browsers.

[0172] The markup defines a set of attributes that can be introduced to existing HTML content. These attributes are triggers for the automatic normalization process to perform certain operations such as move content or create a folder.

Tags:

[0173] HTML <meta> tag—<meta wireless:ml="true|false">

[0174] If a meta tag exists in the <head> of the HTML page with the wireless:ml attribute set to true, the automatic normalizer will be triggered to perform markup based normalization.

[0175] HTML <div> tag

[0176] A div tag with wireless attributes is used to encompass blocks of HTML which will be processed by the automatic normalizer. The wireless attributes assigned to the div tag will not affect display of the content on HTML desktop browsers.

[0177] The markup is extensible in that other attributes may be added in the future to trigger other automatic normalization behavior such as wireless specific javascript.

[0178] HTML <style> tag

[0179] The style tag is used to encompass arbitrary blocks of HTML that will only be processed by the automatic normalizer. Preferably, the content encompassed by the style tag will not be displayed on HTML desktop browsers.

Attributes:

[0180]

<div> attributes	
wireless:action: (default behaviour = autonormalize)	
	drop the content encompassed by the div from the wireless content
colbycoltablenormalizer	call a formatter on a table which extracts the data column by column
rowbyrowtablenormalizer	call a formatter on a table which extracts the data row by row
Folder	create a folder with a given title which will contain the encompassed content
Mark	mark a place in the content with an id
Move	move the encompassed content to marked position or folder
Include	include a block of html defined in a style block
Autonormalize	call the automatic normalizer on the encompassed content
Passthru	pass the content encompassed by the div to the handheld as is
wireless:id:	sets an identification string for the folder, mark, move or include action.
wireless:title:	used to name a folder.
wireless:href:	used in conjunction with the menu action and the folder action to define an anchor/href link in the wireless page

-continued

<style> attributes

wireless:id:
an identification string for the block of html which can be included into the wireless page.

For example:

```
<html>
  <head>
    <meta wireless:ml="true"/>
    <style wireless:id="html block">
      block of html which can be included in the wireless page
    </style>
  </head>
  <body>
    <div wireless:action="include" wireless:id="html block">
      </div>
    </body>
</html>
```

[0181] Referring back to FIG. 1, the distributed browser **108** preferably appears to the information source **102** as a client interface, such as a PC that is browsing an Intranet or Internet. However, when the server browser **110** receives the information content plus script code, it can create an XML based Document Object Model ("DOM") tree structure. This structure can organize the information content into a structured format that is interpreted and processed by the normalizer to organize the information content into folders or tiers. After the information content is in a structured format, the server browser **110** can forward the structured format to the client browser **112** hosted on the target electronic device **104**.

[0182] Furthermore, information content can be transmitted from the server browser **110** to the client browser **112**

client version of the DOM will thus represent a functionally equivalent, but stripped-down version of the original DOM, allowing for efficiency in both content transmission to the device and event handling between the server and client components.

[0185] In order to support this scheme, every node in the original server side DOM is assigned a unique number. Every DOM node that has a processing instruction associated with it (e.g. in HTML this could be a link to follow when it is clicked), a "P pointer" attribute for that node is sent down to the client browser. Since it is unique, the P pointer can identify the element back to the server.

For example:

A DOM on the server side contains the following anchor information at node **1234**

```
<a href="/hockey/nhl/2001/playoffs/news/2001/04/15/kings_red.wings_ap/?s=4"
>Kings beat Wings 2-1, end 14-game playoff skid</a>
```

without first receiving a request from the client browser **112**. Therefore, information content such as in channels of desirable content like sports, weather, and stocks can be forwarded to the server browser **110** at periodic intervals. Additionally, the information content sent to the client browser **112** can include a note. Such a note could inform the user of the client browser **112** that additional information content is stored at the information source **102** or server browser **110**, or both.

[0183] In any markup language (e.g. WML, HTML, cHTML, XHTML, etc.) the source content contains two distinct types of information—information that is visible to the user and information that carries processing instructions to the browser or viewer (e.g. a URI for new content to load when an element is selected, rules governing how to submit form data to the content source, etc.). The latter type of information, while not visible to the user, often occupies more than 50% of the total source HTML code.

[0184] Through the use of Object Based Markup Language (OBML), a proprietary markup language, an object aware distributed browser can take advantage of this distinction of information to leave the majority of the processing information on the server side and only send the end user visible information to the client browser. Under this scheme, the

When formatted in OBML, this node is represented as

[0186] Kings beat Wings 2-1, end 14-game playoff skid

This represents a significant savings on the amount of data that needs to be sent to the client over a network (e.g., wireless network). An event back to the server indicating that the anchor has been clicked on/selected need only carry the value of the P pointer. Note that a P pointer can also be used to identify the elements for other control events such as an input field or form submission button.

[0187] Similarly, OBML provides support for the folders that are the output of the normalizer through the use of an "x" pointer attribute. The presence of this X pointer indicates to an object aware browser that an element is an object representing a group of child elements and that those children can be requested from the server.

For example:

If the anchor shown above was identified as a folder title by the normalizer, it would be represented in OBML as

[0188] Kings beat Wings 2-1, end 14-game playoff skid

[0189] As with the use of the P pointer, events between the browser components requesting or delivering the content for expansion of the folder identify the element using the X pointer value only.

[0190] Note that an element can have a P pointer alone, an X pointer alone or both attributes together.

[0191] In the exemplary embodiment, the event translator can provide an interface to a WAP gateway and translates events in the following manner, an HTTP GET request for a URL of the format p+digits where digits is a number. (e.g. p174) is translated to an "onclick" event targeted at DOM node 174, an HTTP GET request for a URL of the format x+digits where digits is a number. (e.g. x174) is translated to an "expand" event targeted at DOM node 174, an HTTP POST request for a URL of the format s+digits where digits is a number. (e.g. s174) is translated to a "submit" event targeted at DOM node 174, an HTTP POST request containing postdata name value pairs in the format n+digits=somevalue (e.g. n323=foo) is translated to an "onblurchange" event targeted at DOM node 323 with value "foo".

[0192] An HTTP POST request containing postdata name value pairs in the format somename=n+digits (e.g. myName=n323) is translated to an "onblurchange" event targeted at DOM node 323 with value "1".

[0193] In another embodiment, XML documents or other documents may also originate from the electronic device 104. For example, a user may scan a product bar code with a electronic device 104 to produce a document with a client application on the electronic device 104, and send the document via the gateway cluster 18 to an e-commerce transaction server for processing.

[0194] FIG. 13 further illustrates the process of the distributed browser 108 of FIG. 1 by showing a screen shot 300 of an exemplary web page (www.yahoo.com) on both a standard PC-based desktop browser (e.g., Microsoft's Internet Explorer) and a screen shot 304 on the RIM 857 electronic device. To view the yahoo.com web page on a PC-based desktop browser, a user might use a mouse and/or keyboard to enter the Universal Resource Locator (URL) that identifies the page.

[0195] The same user can enter the URL in the RIM device to retrieve the same information as shown on the screen shot 300. However, the screen size of the RIM device is smaller than that of a typical computer screen of a desktop computer. To accommodate the RIM screen size, the information is displayed such that the important information is displayed first. In this example, Personal email, Departments, Stores, Features, Arts & Humanities, Business & Economy are displayed first. The user can then appropriately navigate through the rest of the Web site using events such as by clicking, loading, changing, etc. In this example, the Business & Economy folder was expanded to the more information relating to the Business & Economy section, described more below.

[0196] Upon receipt of the event from the RIM device, the server browser proceeds to perform the request. The user agent retrieves the information corresponding with the URL and appropriately forwards the bit stream to the QDOM. The QDOM then utilizes the QDOM to transform the data content into a DOM tree and forwards this tree to the normalizer. The normalizer (automatic, markup assisted and/or template) creates folders of content, typically by utilizing the characteristics of font, font size, and font color to determine the weight of a text node. In general, the titles of the folders are sent to the

electronic device 304 first. In some instances, however, folder content can be sent down to the electronic device with the folder titles. This can occur based on a request by the user or through a determination by the serializer that the content is sufficiently small to be sent in the initial load.

[0197] In this example, the automatic normalizer identifies elements that are of higher importance or visibility on the desktop display and uses them as folder titles. Elements identified by the normalizer are bold font items (e.g. "My Yahoo!" and "Auctions"), table headings (e.g. "Departments") and larger font items (e.g. "Business & Economy"). A folder title can be derived from both ordinary text (e.g. "Departments") or hyperlinks (e.g. "Business & Economy"). In the latter case, the link property is preserved on the device.

[0198] For example, assume the user has selected "Business & Economy" and requested an expansion of the folder. The electronic device 304 may already contain the content for this folder cached in the micro-gateway (FIG. 4), in which case it can display it immediately as shown. If the content is not cached on the electronic device 304, however, a request is sent to the session manager where the entire DOM is cached. The content of the folder being expanded is extracted by the serializer and sent to the electronic device where it can then be displayed. It should be noted that the normalizer is not restricted to a single level of folders but will produce an appropriate level of nested folders depending on the nature of the original content.

[0199] In accordance with the present embodiments, the server browser interacts with the network content and performs the primary functions unique to this architecture such as automatic translations, object based browsing, and object based personalization. In addition, the architecture uses XML as the protocol to exchange information between the various systems. Furthermore, the media managers can support instant messaging capabilities between desktop browsers and multiple electronic devices. Thus, the data is appropriately sent to the electronic device. Furthermore, the user is allowed to navigate through the Web site.

[0200] The normalizer also reduces the data content sent to the device by allowing the user to browse only the content of interest. It can achieve this by partitioning the web page content into expandable objects. The partitioning of content is achieved by a normalization process in which normalization rules are applied to the markup language tags, such as HTML tags. This feature enables the user to essentially walk a document tree and only query for content of interest.

[0201] Some tables which are small enough for an appliance may be sent directly to the appliance. These simple tables can be displayed as a table directly on the screen of the appliance. The default normalization for a table extracts the content of the table into an expandable object-based structure. Simple data type tables should be displayed on the device using a table control. Tables used for displaying for formatting or complex data (nested information, multiple fonts, mixed information such as text combined with links in the one cell, etc.) are not required. Limited support for merged cells in heading rows is required.

[0202] Additionally, a user may wish to see the entire contents of a Web site without utilizing the expandable object architecture. Therefore, the user can support a "Load All" of a Web site, which can result in the full content tree of the Web site being sent to the device. In this mode, there will be no

expandable objects, however the normalization can utilize white-space horizontal tabs to display the parent-child relationship.

[0203] The server browser can have a minimum character threshold used to determine if the children under a parent are small enough to send on a load. The server browser preferably has a maximum children threshold used to determine if the number of children under a parent is small enough to send on a load. If the maximum character threshold is not exceeded and the maximum children threshold is not exceeded, the children will be sent in the load. The server browser preferably has an inline threshold expansion parameter in which horizontal tabs will be used to show the parent-child relationship rather than expandable objects.

[0204] In addition, the user can utilize a find function on the electronic device. The find function can send a request to the server browser for a find to be performed on the page with a user input string. Options for loading a page and their effect on the content is specified in the following table.

	Threshold Exceeded	Threshold Not Exceeded/Threshold Inline On	Threshold Not Exceeded/Threshold Inline Off
Load All/ No Tables	Thresholding has no effect. All content will be sent formatted inline.	Thresholding has no effect. All content will be sent formatted inline.	Thresholding has no effect. All content will be sent formatted inline.
Load Summary/ No Tables	Normalized content will be sent formatted as expandable objects.	Children under the threshold will be sent formatted inline.	Children under the threshold will be sent formatted as expandable objects.
Load All/ with Tables	Thresholding has no effect. All content will be sent formatted Inline except for tables.	Thresholding has no effect. All content will be sent formatted Inline except for tables.	Thresholding has no effect. All content will be sent formatted Inline except for tables.
Load Summary/ with Tables	Normalized content will be sent formatted as expandable objects, except for tables.	Children under the threshold will be sent formatted Inline. Tables will be sent as is.	Children under the threshold will be sent formatted as expandable objects. Tables will be sent as is.

[0205] The server browser preferably employs methods to partition content based on user profile characteristics. These characteristics could be keywords or usage statistics. The data content sent to the electronic device may need to be adapted to a specific markup language or device dependent requirements (e.g. display size, color capability etc). The protocol and data content sent to the electronic device is preferably compressed and optimized to reduce bandwidth usage and cost to the user.

[0206] User authentication and secure communication is preferred by certain web sites for private end-to-end communication (from the Internet to the electronic device). This secure communication and authentication is accomplished by many mechanisms such as, SSL and HTTP Authentication. HTTP Basic Access Authentication scheme is a method of user authentication, by passing a user name and password back to a web server. Basic Authentication does not encrypt the username and password back to the web server.

[0207] The server browser preferably supports HTTP 1.1 Basic Access Authentication. The Device shall have the ability to allow the user to enter the username and password for authentication. The SSL Protocol preferably provides privacy

and reliability between at least two electronic devices. The protocol is composed of two layers. At the lowest level, layered on top of some reliable transport protocol (e.g., TCP), is the SSL Record Protocol.

[0208] The SSL Record Protocol can be used for encapsulation of various higher level protocols. One such encapsulated protocol, the SSL Handshake Protocol, allows the server and client to authenticate each other and to negotiate an encryption algorithm and cryptographic keys before the application protocol transmits or receives its first byte of data. One advantage of SSL is that it is application protocol independent. A higher level protocol can layer on top of the SSL Protocol Transparently." The Transport Layer Security ("TLS") protocol is a successor to SSLv3. It is an IETF RFC rather than a defacto industry standard. The server browser preferably supports SSL version 3.0 or later.

[0209] The present embodiments, described herein as exemplary embodiments, provide a unique approach to mobilizing critical enterprise content and applications without cus-

tomizations. By transforming and adapting data content in real-time, dynamic information that is organized particularly for small-screened, wireless devices can be delivered. The present embodiments optimize and organize data content such as Internet content, preferably eliminating the need for custom programming or "mirrored" Web sites in non-traditional markup languages such as WML, HDML, C-HTML or XML. Markup languages such as HTML, JavaScript and WML content can be read and transform the existing content into either XML or WML to adapt to the ergonomics of handheld devices, so no additional development costs are incurred.

[0210] It should be understood that the programs, processes, methods and systems described herein are not related or limited to any particular type of computer or network system (hardware or software), unless indicated otherwise. Various types of general purpose or specialized computer systems may be used with or perform operations in accordance with the teachings described herein.

[0211] In view of the wide variety of embodiments to which the principles of the present invention can be applied, it should be understood that the illustrated embodiments are

exemplary only, and should not be taken as limiting the scope of the present invention. For example, the steps of the flow diagrams may be taken in sequences other than those described, and more or fewer elements may be used in the block diagrams. While various elements of the preferred embodiments have been described as being implemented in software, in other embodiments in hardware or firmware implementations may alternatively be used, and vice-versa.

[0212] It will be apparent to those of ordinary skill in the art that methods involved in the system and method for compressing and decompressing a binary code image may be embodied in a computer program product that includes a computer usable medium. For example, such as, a computer usable medium can include a readable memory device, such as a hard drive device, CD-ROM, a DVD-ROM, or a computer diskette, having computer readable program code segments stored thereon.

[0213] The claims should not be read as limited to the described order or elements unless stated to that effect. Therefore, all embodiments that come within the scope and spirit of the following claims and equivalents thereto are claimed as the invention.

1. A method for normalizing a document tree representation, the document tree representing a format for displaying information content in a document on a device, the method comprising:

applying pattern recognition and weighting heuristics to the document tree representation to produce a normalized document tree that alters the format for displaying the information content, wherein the document tree is organized into a set of hierarchical nodes having respective weights that determine whether a node will be inserted into the normalized document tree as a folder title or folder contents;

assigning content having a higher visibility of display a weight indicative of a folder title; and

removing a node if the node has no effect on a visual display of the information content and if the node is not folder contents.

2. The method of claim 1, wherein the normalized document tree represents a hierarchical representation of information in the document tree.

3. A method for normalizing information content in a document, the method comprising:

matching and applying a template to the information content, wherein the template defines modifications to the document to adapt the document for display on a device other than an originally intended device, and if unsuccessful:

determining if the information content includes instructions indicating how to adapt the document for display on the device other than the originally intended device, and if so:

utilizing the instructions in the information content to normalize the information content.

4. The method of claim 3 further comprising:

determining if the information content includes instructions indicating how to adapt the document for display on the device other than the originally intended device, and if not:

applying pattern recognition and weighting heuristics on the information content to normalize the information content.

5. The method of claim 3 further comprising: recognizing patterns in the information content; and dynamically changing the information content to match the template.

6. The method of claim 3 further comprising:

determining if a variation in the information content is too great to match the template, and if so:

determining if the information content includes instructions indicating how to adapt the document for display on the device other than the originally intended device.

7. The method of claim 3, wherein the document tree is represented by a plurality of nodes, and wherein applying a template to the information content comprises adding a node to the plurality of nodes, dropping at least one of the plurality of nodes, moving at least one of the plurality of nodes, partitioning at least one of the plurality of nodes into a folder, or calling user defined formatting rules on at least one of the plurality of nodes.

8. The method of claim 3, wherein the instructions indicate which sections of the information content are to be modified for display on the device other than the originally intended device.

9. The method of claim 3, wherein the instructions comprise meta-tags embedded in the information content that provide at least one specific instruction for normalizing the information content.

10. The method of claim 9, wherein the meta-tags indicate to extract data from a table, create a folder with a given title, or move content to a marked position.

11. A method for normalizing a document tree that represents an organization of information content in a document for display on a device, wherein the document tree includes weighting nodes that affect a display of the information content on the device, and wherein the document tree includes content nodes that represent the information content to be displayed on the device, the method comprising:

determining node weighting criteria, wherein the node weighting criteria are used to define and alter the organization of the information content in the document;

weighting nodes in the document tree according to the determined criteria, wherein content having a higher visibility on a display are assigned a weight indicative of a folder title;

removing nodes that do not affect the visual display of the information content on the device and that do not represent the information content to be displayed on the device; and

determining parent-child relationships between the weighted nodes based on the weighted nodes to produce a normalized document tree, wherein a weighted node is established as a child of a parent having the lightest weight of all the parents that is also greater than the weight of the weighted node.

12. The method of claim 11 further comprising:

weighting nodes in a table; and

attempting to match the table to a predefined pattern of weights, and if successful:

extracting data in response to the predefined pattern.

13. The method of claim 12 further comprising:

attempting to match the table to a predefined pattern of weights, and if unsuccessful:

extracting data according to the weighted nodes.

14. The method of claim 11 further comprising:

applying changes to the document tree according to a normalization markup comprising adding nodes, removing nodes, moving nodes, partitioning nodes into folders, and calling user defined formatting rules on the nodes.