

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 November 2006 (30.11.2006)

PCT

(10) International Publication Number
WO 2006/125570 A1

(51) International Patent Classification:

G06T 11/00 (2006.01) *A61B 6/03* (2006.01)

(21) International Application Number:

PCT/EP2006/004781

(22) International Filing Date: 19 May 2006 (19.05.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
05011135.0 23 May 2005 (23.05.2005) EP

(71) Applicants (for all designated States except US):
GSF-FORSCHUNGSZENTRUM FÜR UMWELT UND GESUNDHEIT GMBH [DE/DE]; Ingolstädter Landstrasse 1, 85764 Neuherberg (DE). **THE STATE OF OREGON ACTING BY AND THROUGH THE STATE BOARD OF HIGHER EDUCATION ON BEHALF OF THE UNIVERSITY OF OREGON** [US/US]; 1238 University of Oregon, Eugene, OR 97403-1238 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TISCHENKO, Oleg**

[RU/DE]; Haushamerstr. 23, 85737 Ismaning (DE). **XU, Yuan** [CN/US]; 3450 Potter Street, Eugene, OR 97405 (US). **HOESCHEN, Christoph** [DE/DE]; Akazienring 11, 85241 Hebertshausen (DE).


(74) Agent: **HERTZ, Oliver**; v. Bezold & Sozien, Akademiestrasse 7, 80799 Munich (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR IMAGING TOMOGRAPHY



(57) Abstract: An imaging method for imaging a region of investigation (2) of an object (1), comprises the step of irradiating the region of investigation (2) with at least one energy input beam (3) along a plurality of projection directions, wherein the at least one energy input beam (3) comprises a plurality of individual energy input beam components, wherein the energy input beam (3) is shaped such that at least two of the energy input beam components have different cross-sections and groups (5) of parallel energy input beam components (5.1, 5.2, 5.3, ...) being parallel to one of the projection directions provide a continuous irradiation of the region of investigation (2). Furthermore, a device for imaging the object are described.

WO 2006/125570 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Method and device for imaging tomography5 Technical field

The present invention relates to a method for imaging an object being irradiated with at least one energy input beam along a plurality of projection directions, in particular to
10 a method for imaging an object on the basis of reconstructing an image function from Radon data comprising a plurality of projection functions measured corresponding to the plurality of projection directions. Furthermore, the present invention relates to a device for imaging an object on the basis of the
15 imaging method.

Technical Background

The non-destructive investigation of samples is an important
20 task in various technical fields like material sciences, medical examinations, archaeology, construction technique, techniques concerning security matters etc.. One approach for obtaining an image of a sample e.g. by computer tomography (CT) is based on an irradiation through an object plane from
25 different projection directions with X-rays, followed by a reconstruction of the object plane on the basis of attenuation data measured at different directions. The entirety of the measured attenuation data can be described in terms of so-called Radon data in a Radon space.

30

The most relevant conventional reconstruction methods known today can be summarized as methods based on the iterative reconstruction or those based on the so-called filtered back-projection. The iterative reconstruction methods have essen-

tial disadvantages in terms of extremely long calculation times. On the other hand, the filtered back-projection method, which relies on the so-called Fourier-slice theorem, has a general disadvantage due to an interpolation step in 5 the reconstruction, which results in errors and artifacts that have a tendency to increase with increasing space frequency. Another problem of the filtered back-projection method is related to the discretization of the Radon data from which the image data have to be reconstructed. To get an 10 optimal filtered back-projection reconstruction it would be necessary to exactly match the projected irradiation rays with detector elements of a detector. This is in general not the case. For this reason, uncertainties or smoothing effects from the reconstruction of Radon data by means of filtered 15 back-projection algorithms are introduced.

T. Bortfeld et al. have described an algorithm for the reconstruction of two-dimensional images from a plurality of projections along the projection directions ("Phys. Med. Biol.", 20 Vol. 44, 1999, p. 1105-1120). With this algorithm, the projections are represented as decompositions, which are subjected to the above filtered back-projection reconstruction. The projections are measured e.g. with a fan beam geometry, wherein attenuation values according to distinct projection 25 lines with even angular intervals relative to each other are measured. The single projection lines measured with different projection directions of the fan beam can be resorted for providing parallel projections to be used for the image reconstruction. The algorithm of T. Bortfeld et al. has not yielded a practical implementation. The algorithm assumes an 30 ideal fan beam geometry, which is not available in practice. Therefore, the T. Bortfeld et al. algorithm requires an interpolation step like the conventional filtered back-projection. Furthermore, the T. Bortfeld et al. algorithm has

an essential disadvantage in terms of artifacts occurring in the reconstructed images.

The disadvantages of the filtered back-projection procedures 5 and the method of T. Bortfeld et al. can be avoided with an image reconstruction method, which is described in the non-published European patent application EP 04031043.5. With this method, the image function is determined from Radon data comprising a plurality of projection functions measured corresponding 10 to the plurality of predetermined projection directions. The image function is determined as a sum of polynomials multiplied with values of the projection functions. In practical implementations, this image reconstruction is based on the measurement of attenuation values corresponding 15 to discrete irradiation beam components having equal angles relative to each other. According to non-published EP 04031043.5, the discrete beam components can be generated with a fan beam geometry by using a radiation source 210' equipped with a source mask 211' as schematically illustrated 20 in Figure 12. The source mask 211' comprises a shielding plate 212' for example made by tungsten with through holes 213'. The shielding plate 212' of the source mask 211' can have a planar shape as shown in Figure 12 or a cylindrical shape. The through holes 213' are arranged such that projection 25 lines starting at the radiation source cross a circle with detector elements with an equal arc length spacing.

In contrast to the T. Bortfeld et al. algorithm, the image reconstruction of unpublished EP 04031043.5 can be used to 30 replace the conventional filtered back-projection algorithm. Therefore, the artifacts introduced by the interpolation in filtered back-projection could be avoided. Nevertheless, it has been found that the image reconstruction according to EP 04031043.5 in practice may have disadvantages in terms of ar-

tifacts in the reconstructed image (so-called aliasing artifacts).

5 Current developments in computed tomography have provided so-called multi-slice-CT and CT-systems based on flat panel technology. These developments are suffering from three further major problems. First of all, the amount of data is very large, the reconstruction time for such an amount of data is too long or the computers needed to handle such data are too 10 expensive. The second problem results from the planar geometry of the detector, which generally is not adapted to the circle geometry of conventional CT devices. Finally, resolution of low contrast details is restricted due to scattered radiation.

15

The above disadvantages are associated not only with the conventional CT imaging, but also with all available reconstruction methods related to Radon data.

20 Objective of the invention

The objective of the invention is to provide improved methods for imaging an object, which avoid the disadvantages of the above conventional techniques and which in particular are capable of reducing artifacts in image reconstruction. Furthermore, the imaging method is to be improved so that it can use an application of flat panel detectors. Furthermore, the objective of the invention is to provide an improved imaging device, which is capable of improved imaging a region of investigation in particular with reduced aliasing artifacts.

30 The above objectives are achieved with methods or devices comprising the features of patent claims 1 and 19. Advanta-

geous embodiments and applications of the invention are defined in the dependent claims.

Summary of the invention

5

According to a first general aspect of the invention, an energy input beam for irradiating a region of investigation is provided with a plurality of individual, discrete energy input beam components at least two of which having different cross-sections. The energy input beam components are traveling through the region of investigation. Groups of parallel energy input beam components belonging to one or different energy input beams provide a step-less irradiation through the region of investigation. The energy input beam is formed such that the parallel energy input beam components are arranged with an abutting fashion so that the region of investigation is completely covered with the irradiation according to the respective projection direction.

20 The inventors have found that artifacts (in particular aliasing artifacts) can be generated by the conventional techniques. If the projection lines are spaced from each other with equal angles as required, the corresponding energy beam components intersect a reference plane perpendicular to the current projection direction of the energy beam at non-equidistant intersection points. Accordingly, the image reconstruction algorithm described in unpublished EP 04031043.5 and the conventional algorithm of T. Bortfeld et al. are characterized by a non-uniform sampling. With the conventional energy beam components having equal cross-sections, this non-uniform sampling yields in most cases either an overlap or gaps between neighboring parallel energy beam components. The inventors have found that these overlaps or gaps

are responsible for the aliasing artifacts obtained with the conventional imaging methods.

Contrary to the above techniques with non-uniform sampling, 5 the imaging method of the invention provides for a continuous irradiation of the region of investigation. As the energy beam components being parallel to a current projection direction have different cross-sections, the non-uniform sampling can be compensated. Accordingly, the parallel energy beam 10 components are abutting relative to each other. Any double irradiation or unintended shadowing is avoided so that the aliasing artifacts are suppressed.

The energy input beam shaping according to the invention has 15 a further important advantage with regard to the design of the detector device for measuring attenuation values obtained with the irradiation of the region of investigation. For providing the continuous irradiation of the region of investigation, the cross-sections of energy beam components are decreasing 20 with increasing distance from a central energy input beam component. The larger an angle between a particular energy input beam component and the central energy input beam component is, the smaller is the cross-section of the particular energy input beam component. This cross-section reduction 25 from the center towards the boundaries of a group of parallel energy input beam components even yields equal cross-sections of the projections of the energy input beam components on a straight, linear (1-dimensional) or a planar (2-dimensional) detector device oriented perpendicular to the 30 projection direction of the considered group of energy input beam components. As a result, each energy input beam component is sensed with the same number of detector elements of the detector device so that a further calibration or re-sizing of groups of the detector elements can be avoided.

While the conventional computer tomography is defined as being based on irradiating the region of investigation with beams having equal cross-sections, the inventors have 5 parted from this concept. Nevertheless, the term "computer tomography" is maintained in the following for describing embodiments of the imaging method according to the invention.

The term "region of investigation" (ROI) used herein generally refers to an object under investigation or a part thereof. The ROI can be described as a 2- or 3-dimensional entity. The term "projection direction" used herein generally refers to the linear course of an energy input through the ROI. The projection direction can be defined by angles relative to a coordinate system used. If fan or cone beams are considered, the term "projection direction" indicates the orientation of a central (or: main) beam component in the fan or cone beam.

20 Radon data measured at the ROI are obtained from a set of projection functions which have been determined corresponding to a plurality of predetermined projection directions running through the ROI. The data are collected with a certain number of "projections". These projections are characterized by integrating the interesting effect along strips covered by the 25 beam components. By measuring a sufficient number of these integrated "projections", the features of the object can be reconstructed from the Radon data.

30 The values of the projection functions generally are determined by the interaction (in particular attenuation, e.g. by absorption, scattering or reflection) of an energy input beam travelling through the ROI along the respective projection direction. While the projection function is a one-dimensional

function, the entirety of projection functions corresponding to all available projection directions spans a space (Radon space) of higher dimensions.

5 The term "energy input beam" (or: "radiation beam") used herein refers to all types of a physical quantity, which travels along a straight line (or an essentially straight line) through the ROI while the energy carried is changed due to an interaction with the ROI. In particular, the term "energy input beam" covers electromagnetic radiation, in particular X-rays, particle radiation or sound waves.

10

According to a preferred embodiment of the invention, the energy input beam components, which belong to different energy input beams or to one particular energy input beam, provide groups of parallel energy input beam components irradiating the ROI without gaps and without overlap between neighboring energy input beam components. The essential advantage of this embodiment of the invention is given by the fact that the

15

20 aliasing artifacts can be suppressed in a particular efficient manner. In practice, the boundaries of the energy input beam components are not jumps in a function, but rather a continuous function depending on the particular beam shaping technique. Therefore, the feature of gap-free and overlap-

25 free irradiation (or: complete irradiation) is fulfilled, if the physical quantity (e.g. electromagnetic field strength) between two energy beam components is not higher than 50 % compared with the respective physical quantity in the center of the adjacent energy beam components.

30

The present invention represents a further important advantage as the energy input beam shaping can be implemented with conventional imaging techniques, e.g. conventional computer tomography imaging techniques. Therefore, the energy input

beam shaped according to the invention preferably is a fan beam or a cone beam created with at least one beam source and having a particular beam angle describing the divergence of the fan or cone beam.

5

If the energy input beam is shaped with a beam mask, particular advantages can be obtained with regard to a precise and reproducible input method that provide the energy input beam components within a predetermined beam angle and with predetermined cross-sections. The beam mask includes through holes, which transmit the energy input beam components while remaining parts of the energy input beam are shielded. The beam mask can be arranged near a beam source and may even move as a source mask with the beam source, e.g. an X-ray source. In this case, the beam mask is called source mask.

Otherwise, a beam mask fixed to at the imaging device is called frame mask. Due to the geometrical size of beam sources typically used for Radon data based imaging methods, the beam mask allows a sharp profiling of the energy input beam. The inventors have found that the continuous irradiation of the ROI can be provided even at a distance from the beam source (combined with the beam mask) up to the range of 1 meter or more.

25 According to a preferred embodiment of the invention, the beam mask (as a movable source mask or as a fixed frame mask) comprises a planar solid plate made of a shielding material including the through holes. The solid plate is arranged with a distance s from the X-ray emitter. The through holes all 30 have an equal size. They are arranged at positions $s_j = s \cot \theta_j$ (with θ_j describing the orientation of the individual beam components). With the planar beam mask arranged perpendicular to the central projection direction of a fan or cone beam, the through holes with equal sizes automatically provide en-

ergy input beam components with decreasing cross-section at the boundaries of the energy input beam. The planar beam mask has particular advantages in terms of a simple construction and broad application range. Alternatively, the beam mask may 5 be formed by a curved, e.g. a cylindrical member of shielding material including the through holes. In this case, the through holes have different sizes for providing the different cross-sections of the energy input beam components. The cylindrical beam mask has particular advantages with regard 10 to a precise definition of the cross-sections independently on the adjustment relative to the beam source.

The curved geometry of the beam mask and the diameters of the through holes can be modified such that any projection of 15 beam components on a plane perpendicular to the current projection direction have the same size.

If the imaging method of the invention includes an adjustment of the beam mask relative to the energy input beam source, 20 the imaging and reconstruction results can be improved by a fine adjustment of the beam mask.

According to a further advantageous embodiment of the invention, the energy input beam is shaped not only with regard to 25 the profiling of the energy input beam components, but also with regard to the outer boundary of the energy input beam. To this end, the imaging method of the invention comprises a further step of setting the beam angle of the energy input beam. This embodiment has particular advantages with regard 30 to an adaptation of the beam source (possibly in combination with the beam mask) to a particular object to be investigated. For irradiating a small object, the beam angle can be decreased so that the overall irradiation dose can be reduced.

Preferably, the beam angle is set with an aperture serving as a diaphragm or shutter. Advantageously, the aperture has a simple construction. Furthermore, it can be simply mounted on 5 a conventional imaging device, like e.g. a conventional CT device for an adaptation to the present invention. Further advantages of the aperture arise from the availability of two degrees of freedom for adjusting the beam angle. With a first alternative, the beam angle is adjusted by setting a diameter 10 of the aperture. This allows a flexible adaptation of the aperture to the object under investigation. According to a second alternative, the beam angle is adjusted by setting a distance between the aperture and the beam source. With the decreasing distance, the beam angle is increased. Both alternatives 15 can be combined.

According to a second preferred embodiment of the invention the at least one energy input beam comprises a distribution of parallel pencil beams providing the energy input beam components. In this case, each group of parallel energy input 20 beam components belongs to one energy input beam only. This energy input beam is created with a linear beam source as it is known e.g. in conventional CT imaging devices.

25 Shaping the energy input beam for providing the at least two pencil beams with different cross-sections is obtained by modulating the output of the linear beam source or by a beam mask with adapted geometry.

30 The above reconstruction algorithms based on discrete projection lines inquire the measurement of attenuation values according to projection lines intersecting a reference plane perpendicular to the actual projection direction at non-equidistant intersection points. Therefore, the above consid-

eration concerning the effect of energy beam components with equal cross-sections is valid for parallel pencil beams as well. With this embodiment of the invention, the parallel pencil beams represent the energy input beam components of a 5 particular energy input beam. While it is possible to adjust the cross-sections of the pencil beams with a beam mask as outlined above, preferably, the different cross-sections of the parallel pencil beams are adjusted by modulating the beam source output.

10

With an X-ray beam source, the parallel pencil beams are preferably created subsequently with a moving beam source emitter. In this case, the electron current for generating the X-rays is modulated for adjusting the cross-section of 15 the pencil beams.

For taking a complete set of Radon data of the object under investigation, the ROI has to be irradiated along a plurality of projection directions. This irradiation can be obtained 20 with a plurality of energy input beams created with a plurality of beam sources. With this embodiment, beam sources are distributed around the object to be imaged. However, according to a preferred embodiment of the invention, the projection directions are set subsequently by moving the energy 25 beam source relative to the object. Preferably, the energy beam source is moved on a circle around the object. Advantageously, this embodiment is completely compatible with conventional imaging techniques, in particular with conventional computer tomography.

30

The imaging method of the invention can be implemented with any type of detector that is capable of measuring attenuation values of the energy beam transmitted through the ROI. If according to a preferred embodiment of the invention, at least

one straight or planar detector is used for measuring the attenuation values, particular advantages arise in terms of compatibility with conventional detection techniques and availability of detectors with simple (planar) geometry. Furthermore, if the energy input beam comprises a group of parallel pencil beams, the attenuation values of all pencil beams can be measured simultaneously with one detector only. With fan beams or cone beams, a plurality of detectors or one detector only can be used. In the latter case, the detector is moveable corresponding to the moving energy beam source.

The present invention provides another essential advantage in terms of data handling. Due to the adjustment of the cross-sections of the energy input beam components, attenuation values can be measured with predetermined groups of detector elements of the detector device. The groups of detector elements have equal sizes for all beam components. Only these predetermined groups are to be read out without resizing so that the amount of data to be processed is reduced.

For completing the image reconstruction, the imaging method of the invention preferably comprises a step of subjecting the measured attenuation values to an image reconstruction procedure. For compensating the dose reduction effect of the inclined projections, the attenuation values are scaled by dividing them by the ray thickness of the beam components contributing to the respective attenuation values. Preferably, the image reconstruction procedure comprises one of the algorithms mentioned above. EP 04031043.5 and the publication of T. Bortfeld et al. are introduced into the present specification by reference. This introduction comprises in particular the features concerning the implementation of the image reconstruction algorithms.

It is an essential advantage of the invention, that the imaging method and device can be used in various applications in medical imaging, for example CT, etc.. However, there are a lot more possible applications like light tomography, any

5 multidimensional imaging for industrial testing or biological research and so on. Preferably, the image function is determined from Radon data measured in an X-ray computer tomography (CT) device, or a neutron based transmission detection system.

10

According to a second general aspect of the invention, the above objective is solved by an imaging device including a measuring device, which comprises at least one energy input beam source for creating the above energy input beam with in-

15 individual energy input beam components, wherein the measuring device further comprises a shaping device for adjusting the cross-sections of the energy input beam components. According to a preferred embodiment of the invention, the shaping device comprises a beam mask with through holes arranged be-

20 tween the energy beam source and the ROI, preferably in front of the energy beam source. Alternatively, the shaping device comprises a control device for modulated operation of the energy beam source, like e.g. a current control device for modulating the electron current of an X-ray source.

25

According to further preferred embodiments of the invention, the imaging device comprises at least one of a first adjustment device for adjusting a distance between the source mask and the energy input beam source and a second adjustment de-
30 vice for adjusting a diameter of an beam angle aperture and/or a distance between the aperture and the energy input beam source.

Brief description of the drawings

Further details and advantages of the invention are described
5 in the following with reference to the attached drawings,
which show:

Figure 1 a schematic illustration of an embodiment of
beam shaping according to the invention;

10

Figures 2 and 3 illustrations of directing fan beams through
an object under investigation;

15

Figure 4 an illustration of the effect of conventional
irradiation with beam components having equal
cross-sections;

20

Figure 5 a schematic illustration of the effect of ir-
radiation with beam components having differ-
ent cross-sections according to the invention;

Figures 6 and 7 schematic illustrations of possible embodi-
ments of beam shaping masks used according to
the invention;

25

Figure 8 a schematic representation of an embodiment of
an imaging device according to the invention;

30

Figure 9 a further illustration of directing fan beams
through an object under investigation;

Figure 10 a schematic illustration of the combination of
a beam source with a beam angle aperture and a
source mask according to the invention;

Figure 11 a further illustration of directing pencil beams through an object under investigation; and

5

Figures 12 a schematic illustration of a beam shaping mask according to unpublished EP 04031043.5.

Embodiments of the invention

10

The invention is described in the following with reference to the application in computer tomography. It is emphasized that the invention can be implemented in an analogous way with the other applications mentioned above. Furthermore, the following description of the preferred embodiments mainly refers to the step of energy beam shaping. Details of CT or other imaging devices or image reconstruction algorithms used for implementing the invention are not described as far as they are known from conventional techniques or from EP 04031043.5.

15

Beam shaping according to the invention is schematically illustrated in Figure 1, which shows the 2-dimensional case of imaging a plane intersecting an object. With the circle 2 representing the ROI to be reconstructed, black dots 21 on the circle 2 are positions of an X-ray source for creating radiation beams each including one of the illustrated X-ray radiation beam components (arrows). White dots 31 represent the distribution of e. g. nine discrete beam components 5.1 to 5.9 (or: projection lines), which form a group 5 of parallel energy input beam components as required for the above algorithms based on a discrete sampling. Simultaneously, the white dots 31 are virtual representations of the positions of bins of the detector device. With the real arrangement, the

20

25

30

source and detector devices are positioned outside the ROI (see below, Figures 3, 12).

The above reconstruction algorithms with discrete sampling
5 require the measurement of projection functions (see Figure
2) comprising a plurality of attenuation values each measured
according to one of the radiation beam components. A plurality
of projection functions is measured along a plurality of
projection directions. As an example, the projection direc-
10 tion "x" (see arrow) is illustrated. According to the posi-
tions of the source and detector devices arranged for provid-
ing the beam 5, the beam components 5.1 to 5.9 are illus-
trated with opposite directions (+x/-x). For 3-dimensional
imaging in helical computer tomography, all radiation beam
15 components can be oriented with the same direction.

The required irradiation of the ROI with equi-angle geometry
of energy input beam components is associated with an inter-
secting of a reference plane (y-z) perpendicular to the cur-
20 rent projection direction at non equidistant intersection
points (see below, Figures 6, 7). After resorting energy in-
put beam components into groups of parallel components ac-
cording to a particular projection direction, these parallel
components still have intersection points with the reference
25 plane, which are not evenly distributed. This feature is
shown in Figure 1. The intersecting points (white dots 31)
form decreasing intervals with increasing distance from the
central beam component 5.5.

30 According to the invention, the cross-sections of the energy
input beam components (here: X-ray beam components) are se-
lected to have a decreasing cross-section with increasing
distance from the central beam component 5.5. Furthermore,
the cross-sections are selected such that the ROI is totally

covered by the irradiation and the white dots 31 are in the middle of the respective beam component.

The diameter d_j of one given beam component is defined by

5

$$d_j = 2 \tan\left(\frac{\pi}{2(2m+1)}\right) \sin(\theta_{j,2m}) \quad j=0,1,\dots,2m$$

or $d_j = d \sin \theta_{j,2m}$

10 wherein $\theta_{j,2m}$ corresponds to the equi-angle geometry of data collection and depends on geometry chosen and d is a measure for the resolution of imaging.

15 Further details of the provision of energy input beam components are illustrated below.

If the invention is applied in computer tomography, the imaging device is structured like a current medical CT-system.

20 Directing a continuous fan or cone beam 3 through ROI in a CT system for collecting projection data is schematically illustrated in Figure 2. The CT-system (not completely illustrated) includes the ring-shaped source carrier 220 in which the X-ray tube (radiation source 210) and the planar detector device 310 are rotating in a way that the whole system can 25 finish a complete turn within e.g. 0.3 to 0.5 s. The detector device 310 consists e. g. of 1 to 64 rows (or up to 256 rows or more) of detector elements (if it is more than one row it would be called a multi-slice-CT) and approximately 700 and 1000 detector elements per row. Within each single turn the 30 data are read according to the number of required projections, e. g. about 1000 times. The object under investigation, e.g. a patient, is moving through this CT-ring, lying on a patient table, that is moving continuously. By this

method a so-called helical or spiral CT data set can be gathered, because the data that are collected are located on a spiral net. The detector device 310 is a straight (1-dimensional) or a planar (2-dimensional) arrangement of detector elements being arranged on a plane reference surface perpendicular to the projection direction from the radiation source.

The selection of parallel beam components e.g. for a complete covering of the ROI can be done with a conventional CT-system as outlined in the following. Reference is made to fan beams, while cone beams are handled in an analogue way. Each fan beam 3 as illustrated in Figures 2 and 3 represents a bundle of fan beam components 4.1. 4.2, 4.3 Each of the fan beam components 4.1, 4.2, 4.3 ... can be considered as a straight pencil beam. While these pencil beams as such do not have the same projection directions, the determination of the discrete projection profiles according each required projection direction follows a concept, which is illustrated in Figure 3.

Figure 3 illustrates a plurality of fan beams (e.g. fan beam 3) each of which comprising the fan beam components 4.1 to 4.7. Black dots 21 are positions of the X-ray source creating the illustrated X-ray radiation fan beams. For a first main projection direction corresponding to the illustrated position of the radiation source 210, the fan beam component 4.5 runs through ROI 2 as a straight pencil beam being detected at the detector element 311 (or a group of detector elements) of the detector device (detector array). For obtaining an attenuation value of another projection line parallel to the fan beam component 4.5, e. g. the fan beam components 4.3' or 4.1'' of the fan beams 3' or 3'' radiated at changed positions of the radiation source 210 are detected at the detec-

tor element 312 or 313, resp.. With an appropriate selection of the detector element positions and the radiation source positions, in particular with an arrangement of these positions spaced with equal arc lengths, attenuation values measured with fan beam components having the same projection and in particular being parallel can be used for constructing the discrete projection profile. The fan beam components 4.5, 4.3' and 4.1'' have different relative positions within the fan beams 3, 3' and 3''. With the use of beam masks described below, the fan beam components 4.5, 4.3' and 4.1'' have different cross-sections (decreasing from the centre to the boundary of the beam), so that a distribution of cross-sections as illustrated in Figure 1 can be obtained in the group of parallel beam components.

15

This concept can be used for the reconstruction of image functions from projection data collected with a CT device e. g. according to Figure 8. As the positions of the radiation source 210 and the detector device and the positions of the detector elements 311, 312, 313,... within the detector device are known from each selected central projection direction of the fan beam, the integrated attenuation values for constructing discrete projection profiles corresponding to groups of parallel beam components can be simply obtained from the collection of raw data obtained with the CT device and resorting the sensed integrated attenuation values.

The effect of providing shaped beam components having different cross-sections according to the invention is illustrated with further details in Figures 4 and 5. Figure 4 shows the effect of a source mask according to Figure 12 as described in EP 04031043.5. For providing beam components with equal cross-sections, this source mask has through holes with varying diameters d_j . With increasing distance from the central

through hole, the diameters d_j are increasing. As a consequence, the projections of the beam components in the detector plane are increasing, e.g. the projection 7.1' is larger than the projection 7.2'. This effect is compensated with the 5 beam shaping according to the invention as shown in Figure 6. All projections 7.1, 7.2 and 7.3 onto the detector plane have the same size.

Figures 6 and 7 illustrate embodiments of beam shaping with 10 beam masks 211 used according to the invention. The seven discrete beam components 4.1 to 4.7 are generated with a fan beam geometry by using a radiation source 210 equipped with the source mask 211. According to Figure 6, the source mask 211 comprises a shielding plate 212 of e.g. tungsten with 15 through holes 213. The through holes 213 are arranged such that the projection lines starting at the radiation source 210 cross the circle in line with the detector elements at predetermined positions, in particular, they are arranged with an equal arc length spacing. In contrast to the shielding plate 212' shown in Figure 12, the through holes 213 in 20 the planar plate have identical diameters d . The thickness of the shielding plate 212 is with the use of tungsten in the range of about 100 μm to about 5 mm. Figure 6 illustrates seven beam components for clarity reasons only. In practice, 25 the shielding plate 212 includes e. g. about 200 holes with a diameter of approximately 100 μm . The size of the holes is selected in dependence on the imaging resolution to be obtained.

30 The central beam component 4.4 perpendicularly intersects the mask plate and correspondingly the detector plane (not shown). Accordingly, the cross-section of the central beam component 4.4 is equal to the diameter d . On the other hand, the beam component 4.1 at the boundary is tilted relative to

the mask plate. Therefore, the cross-section of the beam component 4.1 is reduced. Generally, with a numbering starting from a central through hole to the boundary (up to the m-th through hole), the cross-section of the corresponding m-th beam component is

$$d = 2 \tan \left(\frac{\pi}{2(2m+1)} \right)$$

According to Figure 7, the source mask 211 comprises a (half-)cylindrical shielding member 212 of e. g. tungsten with through holes 213. The cylindrical shielding member 212 is oriented with the cylinder axis parallel to the axis of the CT ring. The through holes 213 in the cylindrical member have different diameters for exactly providing the different cross-sections of the beam components.

15

Figure 8 schematically illustrates an embodiment of the imaging device 100. The imaging device 100 comprises the measuring device with an energy generator 200 and the detector device 300 and the reconstruction device 400 being connected with the measuring device. Furthermore, a holding device 500 is provided, which is e.g. a carrier table as it is known from CT systems or any other carrier or substrate holder for arranging an object 1 under investigation in the measuring device and for adjusting the geometry of the object relative to the energy generator 200 and the detector device 300. Further components like a control device, a display device etc. (not shown) are provided for as they are known per se from prior art devices.

30 The energy generator 200 comprises an energy input source 210, like e.g. a movable X-ray source arranged on a source carrier 220 (e.g. a guide rail or gantry) as it is known from conventional CT devices. The detector device comprises a de-

tector array 310 which is movably arranged on the source carrier 220 opposite of the energy input source 210. With this structure, the projection direction through the ROI (parallel in the plane of drawing) can be set by rotating the combination of components 210, 310 around the holding device 500. Alternatively, a detector device with a distribution of detector arrays around the object 1 is fixed relative to the source carrier 220.

10 Figure 9 shows further details of various embodiments of the source carrier 220. Firstly, the discrete fan beam 3 comprising fan beam components 4.1, 4.2, ... is generated with a radiation source combined with the source mask 211. The source mask 211 is adapted for shaping the energy distribution function of the radiation source as outlined above. The source mask is fixed to the radiation source (e.g. X-ray tube), in particular to a frame 214 of an output window 215 of the radiation source 210 by a detachable fixing element, like e.g. a clip element, a snap connection or an adjustable carrier

15 (see Figure 10). Secondly, the shielding function can be fulfilled by a ring-shaped shield 222 which is schematically illustrated with a plurality of radiation windows 223. The ring-shaped shield 222 can be detachably fixed to the source carrier 220 for adapting the geometric properties of the

20 shield 222 to the practical application and in particular to the mask used. As an example, the ring-shaped shield 222 comprises 201 radiation windows 223 each having a diameter of 6 mm (with a diameter of the CT-ring: 80 cm).

25 The source masks 211 described above can be omitted if each radiation windows 223 of the ring-shaped shield 222 is provided with a frame mask 224 which is illustrated in Figure 9 as one example only. In fact, the source and frame masks 211, 224 need not be provided simultaneously.

With the discrete fan beam generated by the mask illustrated above, the signals from the detector elements of the detector device detecting the integrated values of e.g. attenuation 5 along the corresponding projection lines are read-out at certain positions of the radiation source and the detector device only. The read out positions are those arc length positions on the ring-shaped source carrier, which fulfil the condition of selecting fan beam components with the same projection directions as illustrated in Figure 3.

Figure 10 shows an embodiment of combining the radiation source 210 with the source mask 211 and a beam angle aperture 216. The adjustable carrier 217 is arranged on the frame 214 15 of the output window 215 for holding at least one of the components 211 and 216. Generally, the adjustable carrier 217 serves as at least one adjustment device. The beam angle aperture 216 is made of a shielding plate with a central hole. The diameter and/or the perpendicular distance between the 20 beam angle aperture 216 and the radiation emitter 210.1 of the radiation source 210 can be adjusted with the adjustable carrier 217 for defining the beam angle α of the radiation beam 3. The source mask 211 is shaped as outlined above for defining the beam components 4.1, 4.2.. The distance between 25 the source mask 211 and the radiation emitter 210.1 can be varied for obtaining a required imaging resolution. The adjustable carrier 217 can be operated manually or electrically, e. g. with piezo-electric drive units.

30 According to a further embodiment to the invention, the object under investigation can be irradiated with straight, parallel pencil beams 6.1, 6.2, 6.3, ... emitted simultaneously at each position of the radiation source 210 as shown in Figure 10. The beam 5 comprising the straight parallel

pencil beams 6.1, 6.2, 6.3, ... is distributed on a radiation field, the extension of which is determined by a linear, elongated radiation source. The parallel pencil beams 6.1, 6.2, 6.3, ... are shaped with a mask provided on the radiation source as described above. Alternatively, a moving radiation source emitting one pencil beam can be used as it is known from the CT-systems of the first generation. In this case, the cross-section of the pencil beam is controlled with the current control 218 of the source 210. The embodiment of Figure 10 has the particular advantage that discrete projection profiles can be directly measured with the detector device 310 without the resorting component selection as shown in Figure 3.

CLAIMS

1. Imaging method for imaging a region of investigation (2) of an object (1), comprising the step of:

5 - irradiating the region of investigation (2) with at least one energy input beam (3) along a plurality of projection directions, wherein the at least one energy input beam (3) comprises a plurality of individual energy input beam components (4.1, 4.2, 4.3, ..., 6.1, 6.2, 6.3, ...),

10 **characterized by** the step of

- shaping the energy input beam (3) such that at least two of the energy input beam components (4.1, 4.2, 4.3, ..., 6.1, 6.2, 6.3, ...) are provided for irradiating the region of investigation (2), wherein the at least two of the energy input beam components (4.1, 4.2, 4.3, ..., 6.1, 6.2, 6.3, ...) have different cross-sections and groups (5) of parallel energy input beam components (5.1, 5.2, 5.3, ...) being parallel to one of the projection directions provide a continuous irradiation of the region of investigation (2).

2. Method according to claim 1, wherein the groups (5) of parallel energy input beam components (5.1, 5.2, 5.3, ...) provide a complete irradiation of the region of investigation (2) without the energy input beam components (5.1, 5.2, 5.3, ...) belonging to the respective group (5) overlapping.

3. Method according to claim 1 or 2, wherein the energy input beam (3) is a fan beam or a cone beam.

30

4. Method according to at least one of the foregoing claims, wherein the step of shaping the energy input beam (3) comprises transmitting the energy input beam through a beam

mask (211) made of an energy input shielding material with through holes (213).

5. Method according to claim 4, wherein the step of shaping the energy input beam (3) comprises transmitting the energy input beam through a plane beam mask (211) with through holes (213) all having an equal size or through a curved beam mask (211) with through holes (213) having different sizes.

10 6. Method according to at least one of the claims 4 or 5, further comprising the step of adjusting a distance between the beam mask (211) and an energy input beam source (210).

15 7. Method according to at least one of the foregoing claims, wherein the step of shaping the energy input beam (3) comprises a further step of setting a beam angle (α) of the energy input beam (3).

20 8. Method according to claim 7, wherein the beam angle (α) is set with an aperture (216).

25 9. Method according to claim 8, further comprising the step of adjusting at least one of the diameter the aperture (216) and the distance between the aperture (216) and the energy input beam source (210).

10. Method according to claim 1 or 2, wherein the energy input beam components of the energy input beam (3) comprise a distribution of parallel pencil beams (6.1, 6.2, 6.3, ...).

30

11. Method according to claim 10, wherein the step of shaping the energy input beam (3) comprises a source modulation for providing the different cross-sections of the parallel pencil beams (6.1, 6.2, 6.3, ...).

12. Method according to at least one of the foregoing claims, wherein the projection directions are set subsequently by moving the energy input beam source relative to
5 the object (1).

13. Method according to at least one of the foregoing claims, wherein a plurality of integrated attenuation values are measured by at least one 1-dimensional linear detector or
10 by at least one 2-dimensional planar detector.

14. Method according to claim 13, wherein the energy input beam components comprise the parallel pencil beams (6.1, 6.2, 6.3, ...) and the integrated attenuation values of all energy
15 input beam components having the same projection direction are simultaneously measured with the detector.

15. Method according to claim 13 or 14, wherein exclusively predetermined groups of detector elements of the detector are
20 read out for obtaining the integrated attenuation values.

16. Method according to at least one of the foregoing claims, comprising the step of determining a plurality of projection functions corresponding to the plurality of projection directions, wherein each of the projection functions comprises integrated attenuation values measured with energy input beam components being parallel to the current projection direction and intersecting a reference plane, which is perpendicular to this projection direction at non-equidistant
25 intersection points.
30

17. Method according to at least one of the foregoing claims, comprising the steps of

- subjecting the plurality of integrated attenuation values to a scaling by dividing them by the cross-sections of the respective beam components, and
- subjecting the plurality of scaled attenuation values to an image reconstruction procedure.

5 18. Method according to at least one of the foregoing claims, wherein the integrated attenuation values are measured for providing Radon data measured in:

10 - an X-ray computer tomography (CT) device,

- light tomography, or
- a neutron based transmission detection system.

15 19. Imaging device (100) for imaging a region of investigation (2) of an object (1), comprising:

- a measuring device (200, 300) for measuring projection functions corresponding to a plurality of projection directions, the measuring device (200, 300) including at least one energy input beam source (200, 210) for creating at least one energy input beam (3) with a plurality of individual energy input beam components (4.1, 4.2, 4.3, ..., 6.1, 6.2, 6.3, ...) and a detector device (300),
characterized by further comprising:
- a shaping device (211, 218) being adapted for shaping the energy input beam (3) such that at least two of the energy input beam components (4.1, 4.2, 4.3, ..., 6.1, 6.2, 6.3, ...) being provided for irradiating the region of investigation (2) have different cross-sections and groups (5) of parallel energy input beam components (5.1, 5.2, 5.3, ...) being parallel to one of the projection directions provide a continuous irradiation of the region of investigation (2).

20. Imaging device according to claim 19, wherein the shaping device comprises a beam mask (211, 224) made of an energy input shielding material with through holes (213).

5 21. Imaging device according to claim 20, wherein the beam mask (211, 224) is arranged between the at least one energy input beam source (200, 210) and the region of investigation (2).

10 22. Imaging device according to claim 20 or 21, wherein the shaping device comprises a plane beam mask (211, 224) with through holes (213) all having an equal size or a curved source mask (211) with through holes (213) having different sizes.

15

23. Imaging device according to at least one of the claims 20 to 22, further comprising a first adjustment device (217) for adjusting a distance between the beam mask (211) and the energy input beam source (200, 210).

20

24. Imaging device according to at least one of the claims 19 to 23, wherein the energy input beam source (200, 210) is adapted for creating a fan beam or a cone beam.

25 25. Imaging device according to at least one of the claims 19 or 24, further comprising an aperture (216) for setting a beam angle (α) of the energy input beam (3).

30 26. Imaging device according to claim 25, further comprising a second adjustment device (217) for adjusting at least one of the diameter of the aperture (216) and the distance between the aperture (216) and the energy input beam source (200, 210).

27. Imaging device according to at least one of the claims 19 to 26, wherein the detector device (310) comprises at least one 1-dimensional linear detector or at least one 2-dimensional planar detector.

5

28. Imaging device according to at least one of the claims 19 to 27, wherein the energy input beam source (200, 210) is movable relative to the object (1).

10 29. Imaging device according to at least one of the claims 19 to 23, wherein the energy input beam source (200, 210) is adapted for creating parallel pencil beams (6.1, 6.2, ...).

15 30. Imaging device according to claim 29, wherein the energy input beam source (200, 210) includes a movable radiation emitter (210.1) and the shaping device comprises a current control (218) for controlling the radiation emitter (210.1).

20 31. Imaging device according to at least one of the claims 19 to 30, further comprising a reconstruction circuit (400) for reconstructing an image function on the basis of measured projection functions.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5






FIG. 8






FIG. 9




FIG. 10




FIG. 11




FIG. 12

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2006/004781

A. CLASSIFICATION OF SUBJECT MATTER
INV. G06T11/00 A61B6/03

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G06T A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2005/006986 A (KONINKLIJKE PHILIPS ELECTRONICS N.V; MATTSON, RODNEY, A; BRUNNETT, WIL) 27 January 2005 (2005-01-27) abstract page 8, line 22 - page 9, line 12 -----	1-31
A	WO 92/00566 A (VARIAN ASSOCIATES, INC) 9 January 1992 (1992-01-09) abstract page 19, line 23 - line 28 page 21, line 14 - line 29 page 22, line 24 - line 30 ----- -/-	1-31

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

25 September 2006

Date of mailing of the international search report

04/10/2006

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

GONZALEZ ARIAS, P

INTERNATIONAL SEARCH REPORT

International application No PCT/EP2006/004781

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 094 469 A (DOBBS ET AL) 25 July 2000 (2000-07-25) abstract column 4, line 45 - line 57 figure 2 -----	1-31
A	US 2003/053597 A1 (FLOHR THOMAS ET AL) 20 March 2003 (2003-03-20) abstract paragraph [0039] paragraph [0047] -----	1-31
A	US 2005/089146 A1 (TOTH THOMAS L ET AL) 28 April 2005 (2005-04-28) abstract paragraph [0007] paragraph [0008] -----	1-31
A	US 2004/234021 A1 (HOFFMAN DAVID M) 25 November 2004 (2004-11-25) abstract -----	1-31
A	BORTFELD T ET AL: "Fast and exact 2D image reconstruction by means of Chebyshev decomposition and backprojection" PHYSICS IN MEDICINE AND BIOLOGY, TAYLOR AND FRANCIS LTD. LONDON, GB, vol. 44, no. 4, April 1999 (1999-04), pages 1105-1120, XP002317721 ISSN: 0031-9155 cited in the application the whole document -----	1-31
A	HANSON K M ET AL: "Local basis-function approach to computed tomography" APPLIED OPTICS, OSA, OPTICAL SOCIETY OF AMERICA, WASHINGTON, DC, US, vol. 24, no. 23, 1 December 1985 (1985-12-01), pages 4028-4039, XP002317722 ISSN: 0003-6935 the whole document -----	1-31

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/EP2006/004781

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
WO 2005006986	A 27-01-2005	EP	1648304 A1		26-04-2006
WO 9200566	A 09-01-1992	AU EP	8300191 A 0489907 A1		23-01-1992 17-06-1992
US 6094469	A 25-07-2000	CN DE JP	1256417 A 19942920 A1 2000126171 A		14-06-2000 27-04-2000 09-05-2000
US 2003053597	A1 20-03-2003	WO DE JP	0226133 A1 10048775 A1 2004509689 T		04-04-2002 18-04-2002 02-04-2004
US 2005089146	A1 28-04-2005	CN DE JP NL NL US	1611190 A 102004051518 A1 2005131398 A 1027338 C2 1027338 A1 2006198496 A1		04-05-2005 25-05-2005 26-05-2005 30-11-2005 28-04-2005 07-09-2006
US 2004234021	A1 25-11-2004	NONE			