

(19)



(11)

EP 1 352 603 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:
02.09.2009 Bulletin 2009/36

(51) Int Cl.:
A47L 9/04 (2006.01)

(21) Application number: 03008173.1

(22) Date of filing: 08.04.2003

(54) **Vacuum cleaner with a nozzle comprising an internally driven agitator**

Staubsauger mit einer Düse, welche einen intern angetriebenen Agitator umfasst

Aspirateur avec buse comprenant un agitateur avec moyen d'entraînement intégré

(84) Designated Contracting States:
DE ES FR GB IT

(30) Priority: 08.04.2002 US 117907

(43) Date of publication of application:
15.10.2003 Bulletin 2003/42

(73) Proprietor: Royal Appliance Mfg. Co.
Glenwillow, OH 44139 (US)

(72) Inventors:

- Syverson, Charles D.
North Mankato,
Minnesota 5601 (US)
- Cunningham, James Vernon
Aurora,
Ontario L4G 5T6 (CA)
- Gomes, Michael I.
Cambridge,
Ontario,
N1S 3K1 (CA)

- Reindle, Mark E.
Parma,
Ohio 44129 (US)

(74) Representative: Müller-Boré & Partner
Patentanwälte
Grafinger Strasse 2
81671 München (DE)

(56) References cited:
EP-A- 0 947 155 US-A- 5 940 927

- PATENT ABSTRACTS OF JAPAN vol. 1996, no. 04, 30 April 1996 (1996-04-30) & JP 07 327884 A (MATSUSHITA ELECTRIC IND CO LTD), 19 December 1995 (1995-12-19)
- PATENT ABSTRACTS OF JAPAN vol. 1999, no. 05, 31 May 1999 (1999-05-31) -& JP 11 042184 A (MATSUSHITA ELECTRIC IND CO LTD), 16 February 1999 (1999-02-16)
- PATENT ABSTRACTS OF JAPAN vol. 1999, no. 06, 31 March 1999 (1999-03-31) -& JP 01 166730 A (MATSUSHITA ELECTRIC IND CO LTD), 30 June 1989 (1989-06-30)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 352 603 B1

Description**Background of the Invention**

5 [0001] The present invention relates to the art of electric motors. The invention finds particular application in rotating a brush device in a vacuum cleaning apparatus. It is to be appreciated however, that the present invention may find further application in other environments where it is advantageous to controllably rotate cleaning devices or other parts.

10 [0002] Typically, upright vacuum cleaners use a belt driven brushroll or agitator which rotates and urges dust, dirt, and the like up from the floor or other surface meant to be cleaned. In general, these devices use a relatively high speed motor that drives the brushroll by means of a rubberized flat belt, cogged belt or round cross section belt. In many embodiments, the motor shaft is relatively small in diameter, while the diameter of the brushroll tube is significantly larger. This results in a speed reduction of several fold.

15 [0003] Historically, these belts have had a finite life and begin to slip and finally fail after a certain period of use. Operators must thus keep a supply of replacement belts on hand, and have the mechanical ability to replace these belts. If either the replacement belts or mechanical ability are lacking, there is some cost and inconvenience associated with the failure of these devices.

[0004] JP 07 3278884 A discloses a floor nozzle of a vacuum cleaner wherein a bracket of an outer rotor motor and a rotary brush are interlocked. A stator of the outer rotor motor is fixed to the floor nozzle, and blades with efficient heat conductivity being made of flexible material are placed on the outer surface of the rotary brush and the bracket.

20 [0005] US-A-5 940 927 discloses an autonomous device which is adapted to automatically move on a work surface removing dirt, such as gravel, sand, dust particles and the like, from said work surface. The device comprises a chassis provided with wheels and with a brush roller rotated by a drive motor during said movement for the purpose of brushing up the dirt towards a suction duct wherefrom, by means of a suction air stream, the dirt is conveyed to a dust container. An electronic control device is provided for the control of the drive motor of the brush roller. If the movement of the brush roller is blocked or obstructed to a predetermined extent the control device is arranged to stop the brush roller motor and then transitorily activate the motor in the opposite direction and, finally, after another stop, to reconnect the brush roller motor to operate in the original direction of rotation.

25 [0006] The present invention is based on the object to provide an improved brushroll which overcomes the above-referenced problems and others. This object is solved by a vacuum cleaner having the features of claim 1. Preferred embodiments of the invention are defined in the dependent claims.

Summary of the Invention

35 [0007] According to the present invention, a vacuum cleaner is provided comprising a nozzle; and an agitator positioned adjacent the nozzle, the agitator comprising a tube, defining an interior volume, having first and second ends and a longitudinal rotation axis; a shaft positioned in the tube and extending along the longitudinal axis; a rotor assembly fixedly mounted to an internal surface of the tube and, a magnetic assembly supported within the interior volume by the shaft, the magnetic assembly selectively magnetically interacting with the rotor assembly to induce rotation of the tube; wherein the agitator further comprises support cones mounted on the first and second ends of the shaft, said support cones having ventilation openings formed in a wall thereof, wherein the agitator further comprises stationary end caps located adjacent to the first and second ends of the tube, supporting respective ends of the support cones, and wherein the tube includes cooling holes wherein air enters through an opening in each of the end caps, flows through the ventilation openings of the respective support cone and exits through the respective cooling holes of the tube.

Brief Description of the Drawings

45 [0008] The invention may take physical form in certain parts and arrangements of parts and in various steps and arrangements of steps. The drawings are only for purposes of illustrating the preferred embodiments and are not to be construed as limiting the invention. The embodiments shown in Fig. 1, 3, 4, 5, 10 and 13 do not form part of the invention.

50 FIGURE 1 is a front elevational view of the brushroll according to an embodiment shown in partial cross section;
 FIGURE 2 is an enlarged end elevational view of an exemplary armature core of the motor of Figure 1;
 FIGURE 3 is an exploded perspective view of another motor assembly;
 FIGURE 4 is a functional block diagram of a speed regulating mechanism;
 55 FIGURE 5 is a functional block diagram of a speed regulating mechanism embodiment; and,
 FIGURE 6 is a perspective view of an upright vacuum cleaner together with an exploded perspective view of various components of an internally driven agitator employed therein;
 FIGURE 7 is a perspective view of a carpet extractor together with an exploded perspective view of an internally

driven brushroll employed therein;

FIGURE 8 is a perspective view of a carpet extractor together with an exploded perspective view of an internally driven agitator employed therein;

FIGURE 9 is a perspective view of a hand held portable vacuum cleaner together with an exploded perspective view of an internally driven agitator adapted for use therein;

FIGURE 10 is an exploded perspective view of an internally driven brushroll according to another embodiment;

FIGURE 11 is a see through perspective view of the internally driven brushroll according to Figure 10;

FIGURE 12 is a sectional view at the center of the internally driven brushroll according to Figure 11;

FIGURE 13 is a see through perspective view of another internally driven brushroll according to still another embodiment;

FIGURE 14 is a cross sectional view at the center of the internally driven brushroll according to Figure 13;

FIGURE 15 is an exploded perspective view of an internally driven brushroll according to an embodiment of the present invention;

FIGURE 16 is a perspective view of the internally driven brushroll according to Figure 15;

FIGURE 17 is a cross sectional view of the internally driven brushroll according to Figure 15; and

FIGURE 18 is a cross sectional view at the center of the internally driven brushroll according to Figure 15.

Detailed Description of the Preferred Embodiments

[0009] With reference to Figure 1, an internally driven brushroll **A** according to the present invention includes a dowel section **10** which optimally is formed from a continuous, solid piece of rigid material such as wood, hard plastic, or the like. Embedded in one end of the dowel **10** is a shaft **12** fixed within a closely shaped recess formed in the dowel. The shaft **12** is supported in an end cap **14**, by a bearing assembly **16**. This arrangement permits the shaft **12** and dowel **10** to rotate within the bearing **16** while the end cap **14** remains stationary. Attached to the dowel **10** is at least one agitating element **18**, illustrated as a tuft of brush material.

[0010] At an opposite end, a rigid cylindrical housing **20** is partially pressed and fixed over a portion of the dowel **10**. The housing **20** comprises a magnetic steel tube having an outside diameter matching the outside diameter of the dowel **10**. The housing **20** defines an interior volume or cavity **22** sized to accommodate a motor **M**.

[0011] In the illustrated embodiment, the motor **M** is a brushless type motor with a stationary armature and a rotating magnet. The stationary armature is supported in volume **22** by a stationary shaft **26**. Bearing assemblies **30**, **32** support stationary shaft **26** on opposing ends, permitting rotational movement of the dowel **10** and housing **20** around stationary shaft **26**. In the illustrated embodiment, bearing **30** is snugly fit into a bearing insert **38** which is fixed to, and rotates with, dowel **10**. Similarly, bearing **32** is positioned in insert **40** which is fixed to housing **20**. Electrical leads **42** connect with the motor **M** through a channel (not illustrated) in shaft **26**. The leads extend out through a second end cap **44**.

[0012] Motor **M**, as illustrated, includes a cylindrical permanent magnet sleeve **50** fixed in place on the interior wall of magnetic steel housing **20**. The magnet sleeve, which serves as the rotor of the electric motor **M**, can be an extruded magnet made from what is referred to in the industry as "bonded" magnet material. Typically, the magnet is extruded in long pieces and cut to length. Such magnets may be magnetized either before or after assembly into the housing **20**. These types of tubular magnets **50** can be magnetized with various numbers of discrete poles. Alternately, if the magnet sleeve **50** is a molded sintered magnet, then the magnet is not extruded but molded and ground to size after sintering and then magnetized. In yet another alternative, individual magnets can be spaced around the inside periphery of the housing **20** with alternating north, south polarity. The basic magnetic materials are ferrite magnets both bonded and sintered, and bonded neodymium magnets, however any conceivable magnetic material could be used without loss of functionality.

[0013] One means for preventing the metal tube **20** from spinning on the dowel **10** would be to provide tabs (not illustrated) locking the tube to the dowel.

[0014] With continued reference to Figure 2, motor **M** also includes a stator assembly **52**. The stator assembly includes an armature **54** which can be manufactured from a stack of armature laminations or as a single piece of advanced particulate material. Regardless of the core selected, a number of wire slots **56** consistent with the number of magnetic poles on sleeve **50** and torque requirements of the motor are incorporated. In general, the number of slots **56** is in the range of about 6-20. The slots **56**, positioned on the outside periphery of the core, permit armature windings **58** (Figure 1) to be inserted into the armature. The armature windings **58** comprise a three-phase winding in either a wye connection or a delta connection. The winding is fed a phase-sequenced current from a properly commuted power source and a controller (more fully discussed below).

[0015] The motor magnet, in general, will be multi-pole and usually will have on the order of 6-20 magnetized poles. Although the design could use individual magnets spaced around the inside periphery of the magnet yoke or housing **20** (which is a high permeability magnetic steel tube) with alternating north/south polarity, the current design employs a tubular magnet construction made by the extrusion process or the molding process so that the entire magnet is a one

piece component that fits snugly into the inside diameter of the housing 20 so that the magnet flux can be efficiently transferred to the housing or magnet yoke and back again without requiring high magnet NMF. If the magnet tube is individual magnets, they would be cemented into place with fixturing directly to the housing or magnet yoke. However the more probable design would employ a single piece magnet sleeve cemented into place in the housing 20.

5 [0016] The motor armature is made from a stack of armature laminations in most cases. However it would be possible to utilize new advanced particulate materials that demonstrate low eddy current loss. If the armature core is made of the new advanced particulate materials, the armature can be one piece with no requirement for individual laminations. However at the moment low cost laminations are still the most practical approach. These laminations or the one piece core would have a given number of wire slots incorporated into them consistent with the number of magnet poles in the magnet and consistent with the torque requirement and manufacturing considerations. In general, the number of slots that would probably be used would be in the range of 6-20. The slots would be positioned on the outside periphery of the lamination and after insulating the slots, the armature winding would be inserted from the outer diameter.

10 [0017] There are no limits in terms of the driving voltage necessary for driving the motor of the present invention. Thus, the voltage could be 9 or 24 volt DC, 110 volt AC, or 220 volt AC. In addition, the placement of the motor can be varied. While in the embodiments illustrated the motor is placed on the right hand end of the dowel, the placement could be anywhere in the dowel. For that matter a smaller motor could be placed at each end of the dowel if so desired. The motor may be placed in the middle of the dowel if the shaft bearing arrangement provides definite armature support that will maintain a uniform air gap between the armature 54 and the sleeve 50. The length of the motor is in direct ratio to the torque of the motor (assuming the same diameter). Thus, a longer motor would be employed if more torque was desired and a shorter motor could be used if less torque were desired. For example, in the motor design illustrated in Figures 1 and 6, approximately 2,881 kg (40-ounce inches of torque) would be developed. It has been determined that a smaller diameter, longer motor is advantageous from the standpoint of providing more surface area through which to dissipate heat losses inside the motor. In that connection, the metal shell is useful for heat dissipation. It should also be recognized that there is a required minimum thickness of the metal sleeve to carry the necessary flux. It would be disadvantageous to have a shell thin enough that the shell would not carry all of the magnetic flux. With that type of design, the shell or housing 20 would also pick up magnetized or magnetizable metal objects such as paper clips or the like on the subjacent surface being cleaned.

15 [0018] One supplier for the magnet sleeve is Seiko-Epson Company of Japan. The material is sold by Seiko-Epson under the code name NEODEX-10. The stator assembly can be made from laminations or can be a solid pressed metal part made from coated particulates.

20 [0019] The use of the magnetic material discussed above allows a rather high power density for a reasonable cost. It is made from a rare earth magnet.

25 [0020] With reference now to Figure 3, another embodiment of a motor M' includes a stationary shaft 126 illustrated with a square tip or end 160. The square end 160 is received in a plastic insert cap 140. The cap can be fitted with a complementary shaped insert 142 having a suitably shaped aperture 144 that accommodates the tip 160. Also provided is a standard ball bearing 132 through which one end of the shaft 126 passes. Mounted on the shaft is an armature 154. Rotating about the stationary armature 154 is a sleeve 150 which is mounted in a housing 120. Preferably the sleeve is made from a multi-pole bonded NdFeB magnet. The sleeve 120 can be made from a steel material. Located on the other end of the sleeve 120 is a second standard ball bearing 130. Positioned adjacent the second ball bearing 130 is an end cap 138. Another end 162 of the shaft 126 extends through a central opening 139 in the end cap 138.

30 [0021] Those skilled in the art will recognize that the permanent magnet brushless DC motor type illustrated, while the presently preferred embodiment, is not the only type of motor which can provide the functionality disclosed herein. For example, so-called switch reluctance type motors can also be suitably adapted as the motor M. Typically, these motors do not use magnets, only simple windings in the armature and notched rotors with lobes that are sequentially attracted to the next armature lobe or pole when the proper coils are energized. As above, an inside-out version, in which the coils and armature are stationary and the rotor has shallow lobes that rotate with the brushroll, could also achieve the functionality disclosed above.

35 [0022] Additionally, motor M could alternately be configured as an induction motor. Those skilled in the art will appreciate that this type of motor has an armature and winding similar to that discussed above. The rotor, however is different and employs what is commonly referred to as a "squirrel-cage" induction rotor usually with copper or aluminum bars extending from one end of the rotor to the other and shorted out end rings or cast connections. When the stator or armature is excited, induced current flows in the induction rotor causing torque in the motor. Again, an inside-out geometry is used with the squirrel-cage being positioned on the inner diameter of the motor tube and rotating along with the brushroll.

40 [0023] Control schemes for the above-described motors are all somewhat varied, but in general the motors typically use three-phase power or a commuted three-phase power source. Alternately, a stand alone system operating from one phase power sources, such as batteries and the like, can also be employed with suitable electronic controllers designed to provide appropriate power signals, no matter what style of motor is used. Those skilled in the art will appreciate that electronic control circuits are widespread for the various described motors, and are relatively straight-

forward to implement.

[0024] With reference now to Figure 4, electrical signals to the stator assembly 52 can be provided from a power source 70 through a speed adjusting circuit 72. Alternately, with reference to Figure 5, a sensor assembly 74, can be provided within the volume 22 (Figure 1), for calculating a position of the housing 20 relative to the stator 52. This position information is forwarded to the speed adjusting circuit 72 which permits selection of the proper commutated signal to be sent along leads 42 to the stator 52. The sensor assembly 74 may include a magnetic field detector which detects the magnetic polarity of a determined portion of the magnet sleeve 50. Alternately, the sensor assembly could include an optical type sensor configured to detect rotations of the housing. While the speed adjusting circuit 72 is illustrated as being located outside of the motor M, the circuitry could alternately be placed with the motor M inside the interior volume 22.

[0025] Moreover, the speed adjusting circuit or device 72 incorporates various functional capabilities such as constant brushroll speed maintenance; overload protection stopping brushroll rotation; reverse brushroll operation easing, for example, backward vacuum movement; and variable brushroll rotation depending on floor surface, e.g. no rotation on tile, wood and delicate floor coverings, and fast rotation for heavy duty carpeting or especially dirty environments.

[0026] With reference now to Figure 6, a vacuum cleaner 80 is illustrated with an exploded view of an internally driven agitator A' according to the present invention. The vacuum cleaner is illustrated as being of an upright design. It has a suction nozzle located on the floor. Positioned in the nozzle or adjacent thereto is the agitator according to the present invention. In the current design, the agitator A' rotates on its bearings 16, 30, and 32 while the shaft 26 remains stationary. Thus, the stator assembly 52 remains stationary and the magnet sleeve 50 rotates along with the housing (which is not illustrated in Figure 6).

[0027] This illustration shows that the motor is a separate entity from the roller and is indeed much shorter. This permits the use of short shafts and bearings enabling less expensive and more accurate manufacture of the motor components. Indeed, with shorter shafts, it is much easier to maintain an accurate air gap between the rotor and the stator thus avoiding rubbing and other undesirable operations. Additionally, motors can be assembled in incremental lengths where a magnet of a unit length and an armature stack of unit length comprise the smallest motor. When two magnets and two armatures are joined, a motor of roughly double the power and torque is provided, simplifying the manufacturing process for a variety of applications.

[0028] With reference now to Figure 7, an alternate embodiment includes a motorized brushroll A" in a carpet extractor 86. In this embodiment, dowel 10" is configured with agitator elements 18" disposed in a predetermined pattern around the exterior surface of the dowel formed from a plurality of discreet bristle groups.

[0029] With reference now to Figure 8, carpet extractor 86' is configured with an internally driven agitator A'" having grooves 88 disposed along the exterior surface of the dowel 10'" as a sponge-like cleaning element 87. In this embodiment, the grooves 88 are especially suited to assist in the extraction of water or other fluid on the floor surface. This type of motor is instantly reversible which is advantageous in a carpet extractor environment.

[0030] With reference now to Figure 9, a hand-held vacuum cleaner 90 includes the internally driven agitator A'''' having a continuous agitating element or fin 92 formed of rubber or the like.

[0031] Thus the present invention pertains to an inside out brushless motor having a stationary armature or "stator" and a rotating magnet sleeve or "rotor." This is just the opposite of a traditional electric motor. With the motor of the present invention, one can sense and control the speed of the rotating brushroll of the vacuum cleaner. In addition, this design eliminates the driving belt for the agitator or brushroll since the belt, as discussed above, is prone to failure.

[0032] With reference now to Figure 10, a brushroll B includes a brushroll tube 200 which rotates while a shaft 202 remains stationary. Thus, the stator assembly (not shown) of a custom motor N (as described above) remains stationary and a magnetic housing 204 rotates, having slotted tabs 205 fixedly mounted to the motor housing at each end, thus rotating with the magnetic housing 204. The brushroll tube 200 can be formed from a continuous piece of extruded rigid material such as aluminum, steel, or the like. Attached to the brushroll tube 200 is at least one agitating element 206, illustrated as bristles suitable for press-fitting into a plurality of holes 208 in the brushroll tube 200. Fitted within the brushroll tube 200 is the motor N, with motor supports 210 and bearing assemblies 212 fitted within each end of the brushroll tube 200. The motor supports 210 have cylindrically shaped outer ends 214 that extend through the bearings 212, partially protruding beyond the ends of the brushroll tube 200, and are fitted into cylindrical recesses 216 in stationary end caps 218 for support. The motor supports 210 have inner ends 220 that are configured to fit over respective ends of the motor shaft 202. As illustrated, each end of the motor shaft 202 is configured with a D shape so that the shaft 202 and the motor supports 210 are keyed together for rotation. Further, each of the motor supports 210 is formed with a slot 222 that fits over a tab 224 on the respective end cap. Since the end caps 218 are mounted in a manner to prevent rotation, the motor supports 210 and the motor shaft 202 are, likewise, prevented from rotating. While each end of the motor shaft 202 are illustrated as having a D shape, other shapes, square for example, can be employed with equal efficacy. Similarly, other suitable structures may be employed to interlock or key the motor shaft 202, motor support 210 and end cap 218 arrangement together so that they remain stationary while the brushroll tube 200 and the housing 204 are free to rotate in unison.

[0033] With reference now to Figure 11, it illustrates how motor N is cooled. Each end cap 218 is formed with an

opening 226 permitting air to pass through. One of the openings 226 serves as an air intake while the opening of the remaining end cap 218 serves as an air outlet. Air flows in one of the openings 226, past the respective motor support 210, through a gap between the motor N and the brushroll tube 200 (as shown in Figure 12), past the remaining motor support 210 and out of the remaining opening 226. The gap between the stator and the magnet sleeve is not shown in this embodiment.

[0034] Figure 13 illustrates another brushroll B' having a motor N'. In this embodiment, four openings 276 are provided in each end cap 268. These are partitioned by a heat sink 280 into an intake half 282 and an exhaust half 284. In this embodiment, no gap exists between the motor N' and a brushroll tube 250. Air thus enters the intake 282, passing over the heat sink 280 to a respective end of the motor N', thus cooling the respective end of the motor N', and exits through the respective exhaust 284, passing under heat sink 280, thus transferring heat from the motor N' and the heat sinks 280 to the environment. Figure 14 illustrates a section at the center of brushroll B', showing that no gap exists between the brushroll tube 250 and the motor N'. The gap between the stator and the magnet sleeve is not shown in this embodiment.

[0035] With reference now to Figure 15, another motorized brushroll B" is illustrated according to the present invention. As with the previously described brushroll B', a brushroll tube 300 rotates while a shaft 302 remains stationary. Brushroll B" includes a motor N", preferably employing a single piece magnet sleeve 304, cemented, or fixed by other means, into place in a housing 306, similar in concept to the magnet sleeve 50 and magnetic steel housing 20 of the embodiment described with respect to Figure 1. Also included in the brushroll B" are two motor bearings 308, respective bearing insulators 310, support cones 312, brush bearings 314 and end caps 316.

[0036] The support cones 312 are supported at their outer ends by the respective end caps 316 and are each prevented from rotating by a tab 318 on the adjacent end cap 316 that interlocks with a slot 320 on the support cones 312. Also shown are agitating elements 322 in the form of bristles (see Figure 16) and a drive fastener 324 for fixing the housing 306 inside the brushroll tube 300. The brushroll tube 300 has a plurality of mounting holes 326 suitable for press-fitting of agitating elements 322. The tube 300 accommodates the end caps 316 and the drive fastener 324. Cooling holes 328 are provided in the brushroll tube 300 and are described in further detail below. Each support cone 312 includes a plurality of ribs 332 separated by slots 336.

[0037] With reference now to Figure 17, the motor shaft 302 is fixedly mounted, rotation wise, into the inner ends of the support cones 312 so that a stator assembly 330 of the motor N" remains stationary while the magnet sleeve 304 and the housing 306 rotate with the brushroll tube 300. The motor shaft 302 is supported at its ends by respective bearings 308 which are in turn supported by bearing insulators 310 supported by the housing 306. The drive fastener 324 is shown locking the housing 306 to the brushroll tube 300.

[0038] Also illustrated in Figure 17 is a means of removing heat from the motor N". Heat generated by the motor travels by conduction, shown by arrows 340, and travels along the motor shaft 302 towards the ends of the shaft. From the ends of the motor shaft, heat is transferred by conduction to the support cones 312 and is conducted along the ribs 332 forming the center portion of the support cones, as shown by arrows 342. Air enters the brushroll tube 300 through openings 334 in the end caps 316 and flows, as shown by arrows 344, through ventilation openings or slots 336, between the support cone ribs 332, thus removing heat from the support cones and carrying it away through cooling holes 328 in the brushroll tube 300. Air flow may be facilitated by the vacuum present in the vicinity of the cooling holes 328.

[0039] Figure 18 illustrates the motor shaft 302, the stator 330, the magnet sleeve 304, the magnetic steel housing 306, the brushroll tube 300 and the agitator elements 322. A small gap 350, as previously described, is maintained between the stator 330 and the magnet sleeve 304 to allow relative rotation therebetween.

[0040] Exemplary dimensions for the embodiment of Figure 17 are as follows:

Magnetic steel housing 306 OD	2,86 cm (1.125")
Magnetic steel housing 306 ID	> 2,68 cm (1.055")
Magnet sleeve 304 OD	< 2,68 cm (1.055")
Magnet sleeve 304 ID	2,29 cm (0.90")
Stator assembly 330 stack length	8,89 cm (3.50")
Number of magnet sleeve 304 poles	8
Number of stator assembly 330 wire slots	6

[0041] The invention has been described with reference to the preferred embodiments. Modifications and alterations will occur to others upon a reading and understanding of the preceding detailed description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims.

Claims

1. A vacuum cleaner comprising:

5 a nozzle; and,
an agitator (A, A', A'', A''', A''''', B, B', B'') positioned adjacent the nozzle, the agitator comprising:

a tube (20, 120, 200, 250, 300), defining an interior volume, having first and second ends and a longitudinal rotation axis;

10 a shaft (26, 126, 202, 302) positioned in the tube and extending along the longitudinal axis;

a rotor assembly (50, 150, 306) fixedly mounted to an internal surface of the tube and, a magnetic assembly (52, 304) supported within the interior volume by the shaft, the magnetic assembly selectively magnetically interacting with the rotor assembly to induce rotation of the tube;

15 **characterized in that** the agitator further comprises support cones (312) mounted on the first and second ends of the shaft, said support cones having ventilation openings (336) formed in a wall thereof, wherein the agitator further comprises stationary end caps (218, 316) located adjacent to the first and second ends of the tube, supporting respective ends of the support cones; and wherein the tube includes cooling holes (328) wherein air enters through an opening in each of the end caps, flows through the ventilation openings of the respective support cone and exits through the respective cooling holes of the tube.

2. The vacuum cleaner as set forth in claim 1 wherein the magnetic assembly comprises a brushless motor assembly.

3. The vacuum cleaner as set forth in either of claims 1 or 2, further comprising a controller (72, 72') which selectively powers the magnetic assembly.

4. The vacuum cleaner as set forth in claim 3 wherein the controller varies power applied to the magnetic assembly for controlling speed and rotational direction of the rotor assembly.

5. The vacuum cleaner as set forth in claim 3 or 4 further comprising a sensor (74) which provides data indicative of rotational speed of the agitator to the controller.

6. The vacuum cleaner as set forth in claim 5 wherein the controller adjusts power to the motor assembly based on the sensed rotational speed.

7. The vacuum cleaner as set forth in any of the claims 1 to 6, further comprising:

a bearing assembly (212, 308, 310) operatively connected to the shaft (202, 302) permitting relative rotational motion.

8. The vacuum cleaner as set forth in any of the claim 1 to 7, where the rotor assembly comprises:

a magnetized rotor frame positioned adjacent or internal to an interior surface of the housing.

9. The vacuum cleaner as set forth in any of claims 1 to 7 wherein the rotor assembly comprises a permanent magnet of the ferrite type.

10. The vacuum cleaner as set forth in any of claims 1-9 further comprising agitating elements (18, 18'', 206, 322) mounted to the tube.

Patentansprüche

1. Staubsauger, der umfasst:

55 eine Düse; und
einen Agitator bzw. einen Aufwirbler (A, A', A'', A''', A''''', B, B', B''), der benachbart zu der Düse positioniert ist, wobei der Agitator umfasst:

ein Rohr (20, 120, 200, 250, 300), das ein Innenvolumen begrenzt, mit ersten und zweiten Enden und einer Längsdrehachse;

eine Welle (26, 126, 202, 302), die in dem Rohr positioniert ist und sich entlang der Längsachse erstreckt;
 eine Rotoranordnung (50, 150, 306), die fest an eine Innenfläche des Rohrs montiert ist, und eine magnetische Anordnung (52, 304), die von der Welle in dem Innenvolumen gehalten wird, wobei die magnetische Anordnung selektiv magnetisch mit der Rotoranordnung wechselwirkt, um die Drehung des Rohrs zu induzieren;

dadurch gekennzeichnet, dass der Agitator ferner Lager- bzw. Haltekegel (312) umfasst, die auf die ersten und zweiten Enden der Welle montiert sind, wobei die Haltekegel in einer Wand von ihnen Lüftungsöffnungen (336) haben, wobei der Agitator ferner ortsfeste Endkappen (218, 316) umfasst, die benachbart zu den ersten und zweiten Enden des Rohrs angeordnet sind, die jeweilige Enden der Haltekegel halten, und wobei das Rohr Kühllöcher (328) umfasst, in die durch eine Öffnung in jeder der Endkappen Luft eintritt, durch die Lüftungsöffnungen des jeweiligen Haltekegels strömt und durch die jeweiligen Kühllöcher des Rohrs austritt.

2. Staubsauger nach Anspruch 1, wobei die magnetische Anordnung eine bürstenlose Motoranordnung umfasst.
3. Staubsauger nach Anspruch 1 oder 2, der ferner eine Steuerung bzw. Regelung (72, 72') umfasst, welche die magnetische Anordnung selektiv mit Strom versorgt.
4. Staubsauger nach Anspruch 3, wobei die Steuerung bzw. Regelung den an die magnetische Anordnung angelegten Strom variiert, um die Drehzahl und die Drehrichtung der Rotoranordnung zu steuern bzw. zu regeln.
5. Staubsauger nach Anspruch 3 oder 4, der ferner einen Sensor (74) umfasst, der Daten bereitstellt, welche der Steuerung bzw. Regelung die Drehzahl des Agitators anzeigen.
6. Staubsauger nach Anspruch 5, wobei die Steuerung bzw. Regelung den Strom zu der Motoranordnung basierend auf der abgetasteten Drehzahl einstellt.
7. Staubsauger nach einem der Ansprüche 1 bis 6, der ferner umfasst:
 eine Lageranordnung (212, 308, 310), die betriebsfähig mit der Welle (202, 302) verbunden ist, welche die relative Drehbewegung erlaubt.
8. Staubsauger nach einem der Ansprüche 1 bis 7, wobei die Rotoranordnung umfasst:
 einen magnetisierten Rotorrahmen, der benachbart zu oder innerhalb einer Innenfläche des Gehäuses positioniert ist.
9. Staubsauger nach einem der Ansprüche 1 bis 7, wobei die Rotoranordnung einen Permanentmagneten vom Ferrittyp umfasst.
10. Staubsauger nach einem der Ansprüche 1 bis 9, der ferner an das Rohr montierte Aufwirbelelemente (18, 18", 206, 322) umfasst.

Revendications

1. Aspirateur comprenant :

une buse ; et

un agitateur (A, A', A", A"', A''', B, B', B'') positionné en adjacence à la buse, l'agitateur comprenant :

un tube (20, 120, 200, 250, 300) qui définit un volume intérieur et qui a une première et une seconde extrémité et un axe de rotation longitudinal ;

un arbre (26, 126, 202, 302) positionné dans le tube et s'étendant le long de l'axe longitudinal ;

un assemblage de rotor (50, 150, 306) à montage stationnaire sur une surface interne du tube et un assemblage magnétique (52, 304) soutenu dans le volume intérieur par l'arbre, l'assemblage magnétique

étant sélectivement en interaction magnétique avec l'assemblage de rotor pour induire la rotation du tube ;

5 caractérisé en ce que l'agitateur comprend en outre des cônes de support (312) montés sur la première et sur la seconde extrémité de l'arbre, lesdits cônes de support ayant des ouvertures de ventilation (336) ménagées dans une paroi de ceux-ci, dans lequel l'agitateur comprend en outre des capuchons terminaux stationnaires (218, 316) placés en adjacence à la première et à la seconde extrémité du tube, soutenant les extrémités respectives des cônes de support, et dans lequel le tube inclut des trous de refroidissement (328) dans lesquels l'air entre à travers une ouverture dans chacun des capuchons terminaux, s'écoule à travers les ouvertures de ventilation des cônes de support respectifs et s'échappe à travers les trous de refroidissement respectifs du tube.

- 10
2. Aspirateur tel qu'il est exposé dans la revendication 1, dans lequel l'assemblage magnétique comprend un assemblage de moteur sans balai.
- 15
3. Aspirateur tel qu'il est exposé dans l'une ou l'autre des revendications 1 et 2, comprenant en outre un contrôleur (72, 72') qui alimente sélectivement l'assemblage magnétique en puissance électrique.
- 20
4. Aspirateur tel qu'il est exposé dans la revendication 3, dans lequel le contrôleur varie la puissance électrique appliquée sur l'assemblage magnétique afin de commander la vitesse de rotation et le sens de rotation de l'assemblage de rotor.
- 25
5. Aspirateur tel qu'il est exposé dans l'une ou l'autre des revendications 3 et 4, comprenant en outre un capteur (74) qui fournit des données indicatives sur la vitesse de rotation de l'agitateur vers le contrôleur.
6. Aspirateur tel qu'il est exposé dans la revendication 5, dans lequel le contrôleur ajuste la puissance électrique vers l'assemblage de moteur sur la base de la vitesse de rotation captée.
- 30
7. Aspirateur tel qu'il est exposé dans l'une quelconque des revendications 1 à 6, comprenant en outre :
- un assemblage de paliers (212, 308, 310) relié opérationnellement à l'arbre (202, 302) permettant un déplacement en rotation relatif.
- 35
8. Aspirateur tel qu'il est exposé dans l'une quelconque des revendications 1 à 7, dans lequel l'assemblage de rotor comprend :
- un cadre de rotor magnétisé positionné en adjacence à ou en interne par rapport à une surface intérieure du boîtier.
- 40
9. Aspirateur tel qu'il est exposé dans l'une quelconque des revendications 1 à 7, dans lequel l'assemblage de rotor comprend un aimant permanent du type « ferrite ».
- 45
10. Aspirateur tel qu'il est exposé dans l'une quelconque des revendications 1 à 9, comprenant en outre des éléments d'agitation (18, 18", 206, 322) montés sur le tube.
- 50
- 55




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5







FIG. 7







FIG. 9






FIG. 11

FIG. 12




FIG. 13

FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 073278884 A [0004]
- US 5940927 A [0005]