



US 20170049455A1

(19) **United States**(12) **Patent Application Publication**
SEGUIN(10) **Pub. No.: US 2017/0049455 A1**(43) **Pub. Date: Feb. 23, 2017**(54) **SURGICAL DEVICE FOR CONNECTING
SOFT TISSUE****Publication Classification**(51) **Int. Cl.***A61B 17/128* (2006.01)*A61B 90/00* (2006.01)*A61B 17/122* (2006.01)*A61B 17/00* (2006.01)*A61B 17/068* (2006.01)(52) **U.S. Cl.**CPC *A61B 17/1285* (2013.01); *A61B 17/00234*(2013.01); *A61B 17/068* (2013.01); *A61B**17/122* (2013.01); *A61B 90/03* (2016.02);*A61B 2017/00243* (2013.01); *A61B 2017/081*

(2013.01)


(71) Applicant: **Evalve, Inc.**, Menlo Park, CA (US)(72) Inventor: **Jacques SEGUIN**, LAUENEN BEI
GSTAAD (CH)(73) Assignee: **Evalve, Inc.**, Menlo Park, CA (US)(21) Appl. No.: **15/342,580**(22) Filed: **Nov. 3, 2016****Related U.S. Application Data**

(60) Division of application No. 14/259,772, filed on Apr. 23, 2014, now Pat. No. 9,510,837, which is a division of application No. 13/156,760, filed on Jun. 9, 2011, now Pat. No. 8,740,918, which is a division of application No. 12/699,768, filed on Feb. 3, 2010, now Pat. No. 7,981,123, which is a division of application No. 11/354,612, filed on Feb. 14, 2006, now Pat. No. 7,682,369, which is a division of application No. 10/877,279, filed on Jun. 24, 2004, now Pat. No. 7,288,097, which is a division of application No. 10/202,599, filed on Jul. 24, 2002, now Pat. No. 6,770,083, which is a division of application No. 09/523,018, filed on Mar. 10, 2000, now Pat. No. 6,461,366, which is a continuation of application No. PCT/FR98/01960, filed on Sep. 12, 1997.

(57)

ABSTRACT

Provided is a surgical instrument including an external tube (2) and two elongated members (4) positioned in the tube (2), each of which includes a distal end (10a) for capturing one of the two tissue zones (M1, M2) to be attached. The instrument (1) may further include a catching member (22, 25) for each tissue (M1, M2) to be attached; a rod (15, 16) linked to each catching member (22, 25) enabling tension to move axially, the rod (15, 16) being separable from said catching member (22, 25) when a tension is exerted on it beyond a certain threshold; and a member (17a) forming a stop for locking axially each catching member (22, 25) during the tensioning.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

SURGICAL DEVICE FOR CONNECTING SOFT TISSUE

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] The present application is a divisional of U.S. patent application Ser. No. 14/259,772, filed Apr. 23, 2014, which is a divisional of U.S. patent application Ser. No. 13/156,760, now U.S. Pat. No. 8,740,918, filed Jun. 9, 2011, which is a divisional of U.S. patent application Ser. No. 12/699,768, now U.S. Pat. No. 7,981,123, filed Feb. 3, 2010, which is a continuation of U.S. patent application Ser. No. 11/354,612, now U.S. Pat. No. 7,682,369, filed on Feb. 14, 2006, which is a continuation U.S. patent application Ser. No. 10/877,279, now U.S. Pat. No. 7,288,097, filed on Jun. 24, 2004, which is a divisional of U.S. patent application Ser. No. 10/202,599, now U.S. Pat. No. 6,770,083, filed Jul. 24, 2002, which is a divisional of U.S. patent application Ser. No. 09/523,018, now U.S. Pat. No. 6,461,366, filed Mar. 10, 2000, which is a continuation of PCT/FR98/01960, which designated the United States, filed Sep. 12, 1997, the full disclosures of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] This invention provides a surgical device allowing the percutaneous connection of two soft tissue areas that are ordinarily separate. This device is particularly intended for reconstruction of heart valves, especially the mitral valve, and for the treatment of any malformation of a heart septum.

[0003] In a condition known as mitral insufficiency, the mitral valve does not completely shut, and does not prevent the back-flow of blood to the left atrium from the left ventricle. Surgical repair is then necessary. In a current procedure, a sternotomy is performed. The patient is then placed under extra-corporal blood circulation while the heart is stopped, and the heart chambers are opened to gain access to the mitral valve, usually through the left atrium. Once the mitral valve is accessed, repair procedures include annuloplasty and, more recently, suturing of the free edge of the anterior leaflet to the free edge of the back leaflet where the mitral insufficiency occurs.

[0004] These procedures are complicated and require general anesthesia, sternotomy and extra-corporal blood circulation. They also require high doses of anti-coagulant therapy adding to the operative risk of a myocardial infarction and hemorrhage.

SUMMARY OF THE INVENTION

[0005] The methods of the present invention are performed percutaneously, diminishing considerably these risks. A surgical device allows the connection of two zones of soft tissue that are usually separate. In a particular embodiment, a connection is formed between a free edge area of an anterior mitral leaflet and a free edge area of a back mitral leaflet. Suitable surgical devices for performing tissue connection are described for example in EP 558 031 and WO 94/18893, and may comprise:

[0006] (a) a tube which may be inserted percutaneously until its distal extremity reaches the area around the tissues to be connected; and

[0007] (b) two elongated elements inside that tube, each of which comprises a distal extremity having a device that grasps one of the two tissues to be connected;

[0008] (c) wherein the distal extremities of these elongated elements may be opened and closed in order to permit introduction into the desired area, allow the procedure.

[0009] Particular devices according to the present invention may further comprise:

[0010] (a) a grasping element, optionally having two parts for capturing each of the tissues to be connected, wherein the grasping or hooking element effects the connection of the two zones of tissue when brought close thereto by shifting of the portions of distal extremities to a position where they meet;

[0011] (b) a rod connected to each of the grasping or hooking elements and operated from the proximal end of the tube in order to axially shift the elongated element, wherein the rod can be separated from the grasping or hooking element upon pulling beyond a given threshold; and

[0012] (c) a wedge inside the tube, allowing the axial immobilization of each grasping or hooking element while pulling on them.

[0013] The rod positions the insertion of the hooking element up to the level of the tissue edges to be connected. The rod also engages the hooking element against the wedge in order to open the two hooking parts.

[0014] According to the present invention, the device may be used to remotely grasp through a percutaneous passage, to draw together, and to connect the two zones of tissue by a simple external manipulation.

[0015] Preferably, the tube, the elongated elements, and the rod are flexible enough to be inserted percutaneously and through a patient's vasculature for the treatment of the leaflets of a cardiac valve, in particular the mitral valve. Each of the elongated elements is made out of an elastically flexible material, and one of these elongated elements diverges from the longitudinal axis of the other. The two elongated elements can move axially in relation to the tube between (a) a retracted position within the tube where the ends of the elongated elements are flexibly bent and closed together, and (b) a position where the ends of the elongated elements spring open and diverge from each other in a way that permits those ends to capture the soft tissues in order to grasp them.

[0016] The elongated elements may be deployed to allow their distal extremities to grasp the tissue areas or may be retracted in order to make the insertion, shifting or removal of the apparatus easier. Each elongated element may comprise a rod made of elastic material, with a curved distal extremity and/or a harpoon shape, and a sheath able to slide axially in a forward position to cover the distal extremity and slide back to uncover it.

[0017] According to a variation, each elongated element can be composed of a tube linked to a system that contracts its internal volume in order to grasp the corresponding tissue area, and expands to release the tissue with no lesion. In this case, the wide-mouthed shape of the elongated element's distal extremity will insure a large enough grasping surface.

[0018] Preferably, the device includes two hooking elements. One is operated on the distal side of the tissues, and the other, to be operated on the proximal side of the tissues, is situated between the first hooking element and the wedge element. This way the two hooking elements can be operated

on both sides of the tissues and can be pressed together for a perfect attachment of those tissues.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] For greater clarity, the invention is described again in reference to the enclosed Figures representing two unrestricted examples of the invention in its optimal capacity.

[0020] FIG. 1 shows a longitudinal section of a heart with a mitral valve that does not shut properly and has to be treated with this device.

[0021] FIG. 2 shows the mitral valve before treatment.

[0022] FIG. 3 shows a mitral valve similar to FIG. 2 after treatment by suture according to the usual procedure.

[0023] FIG. 4 is a view similar to that of FIG. 1, with the device of the present invention inserted into a heart.

[0024] FIG. 5 is an enlarged view of a longitudinal section of the distal extremity of the device.

[0025] FIG. 6 shows a view of this distal extremity according to the line VI-VI of

[0026] FIG. 5.

[0027] FIG. 7 and FIG. 8 are similar views to FIG. 5 at different stages of the procedure.

[0028] FIG. 9 is a similar view to FIG. 2 of the mitral valve after treatment with the device.

[0029] FIG. 10 is a view of this valve according to line X-X of FIG. 9.

[0030] FIG. 11 illustrates an alternative embodiment of the device of the present invention.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

[0031] FIG. 1 shows a heart C with a mitral valve M having poorly opposed leaflets (M1, M2). Thus, the valve M does not shut tightly and no longer performs its back-flow function between the left atrium O and the left ventricle V. According to conventional procedures, after sternotomy, the patient is placed under extra-corporeal blood circulation. The heart is stopped and the heart chambers are opened to directly reach to the valve M and stitch together the free opposite edges of both leaflets (M1, M2) as shown on FIGS. 2 and 3. Connecting leaflets M1 to M2 restores a good attachment between them and restores the imperviousness of valve M.

[0032] FIGS. 4 to 5 show a device (1) according to the present invention which enables the percutaneous connection of leaflet M1 to leaflet M2. This device (1) comprises an external tube (2), guidewire (3), two elongated elements (4), and a clipping system (5). The apparatus is sufficiently flexible to be percutaneously inserted into the heart C, through the patient's vascular, e.g., the Vena Cava Ve and the intra-atrial septum S. Guidewire (3) is inserted through valve M and so the distal extremity of external tube (2) is located in the left atrium O, with its distal opening facing mitral valve M.

[0033] Each of the elongated elements (4) has a distal extremity (4a) that is normally curved to diverge outwardly. A rod (10) is made out of a relatively rigid but still elastic material, more particularly in metal, with a sheath (11) of synthetic material. The distal extremity (10a) of the rod (10) is sharp and more or less harpoon-shaped. The sheath (11) fits on the rod (10) and can slide axially to a forward position (as shown on left side of FIG. 5) in order to cover the distal

extremity of the rod, and can slide back (as shown on the right side of FIG. 5) in order to uncover that same distal extremity (10a).

[0034] The elongated elements (4) extend from the end of the tube (2). Because of this, they can be shifted axially in relation to the tube (2) between a retracted position where the extremities (10a) close together (FIGS. 7 and 8) and an extended position where these same extremities (10a) diverge from each other (FIG. 5). The clipping system (5) comprises three concentric tubular rods (15, 16, 17) that can be slidably introduced over the guidewire (3). Each rod can also slide axially in relation to the others. The internal rod (15) is linked to a disk (20) through a frangible area (21). The rod and disk (15 and 20) are made of molded synthetic material. The disk (20) is axially pierced in order to let the guidewire (3) pass through, and carries a clip (22). Side prongs (22a) of that clip extend from the proximal face (20a) of the disk (20). A central portion (22b) of the clip (22) having a central ring for receiving the guidewire (3) is embedded into the material of the disk (24).

[0035] The intermediate rod (16) is also connected by a frangible area (23) to a disk (24) with two clips (25). Side prongs (25a) of these clips extend from the distal face (24a) of this disk (24), and central portions of the prongs are embedded into the material of the disk (24). On each side, the disk (24) has two diametrically opposed notches (26, FIG. 6) to allow the passage of the elongated elements (4). The external rod (17) has an expanded distal extremity (17a) which engages the proximal face of the disk (24). Each of these rods (15, 16, 17) can be extended beyond the proximal extremity of tube (2) so they can be shifted by the operator.

[0036] A handle or other structure for manipulating the rods (15, 16, 17) will usually be provided at a proximal end of the device. The handle will permit deployment rod (15) while rod (17) is held in a desired position in relation to tube (2), and then deployment rod (16), while rod (17) is also held in the desired position in relation to tube (2).

[0037] In practice, under X-ray or echography control, the guidewire (3) is first inserted through Vena Cava Ve, the intra-atrial septum S, and mitral valve M. Then tube (2) and its internal parts are inserted into the Vena Cava Ve and through the septum S until the distal extremity of tube (2) is directed at mitral valve M (FIG. 4). At this stage, disk (20) should be held at the opening of tube 2 (FIG. 5), while elongate elements (4) are retracted so that their distal extremities are retracted into slots (26).

[0038] When the distal extremity of tube (2) is in the proper position, rod (15) is shifted to advance disk (20) beyond leaflets M1 and M2 and into the left ventricle V. Elongate elements (4) are then advanced to their extended positions, as shown in FIG. 5. As the elongate elements (4) are advanced, their distal extremities diverge. After the elements (4) are advanced, distal extremities (10a) of rods (10) are positioned close to leaflets (M1, M2). The sheaths (11) of elements (4) are then retracted in relation to the rods (10) in order to uncover the extremities (10a), each of which can then pierce and capture the adjacent leaflet M1 or M2. Tube (2) is then advanced over the elongate elements (4), drawing the distal extremities (4a) closer, as shown on FIG. 7. This action draws the free edges of leaflets M1 and M2 together.

[0039] Rod (17) is advanced distally in relation to tube (2), and rod (15) is pulled proximally in relation to tube (2) in order to insert the prongs (22a and 25a) of clips (22 and 25)

into the leaflets M1 and M2. The tension on rod (15) forces the prongs (22a and 25a) against the opposed walls (20a, 24a) of the disks (20, 24) and breaks frangible area (21). This break gives the prongs of the clips enough freedom of movement to ensure a good connection between leaflets M1 and M2. The sheaths (11) are then advanced distally in relation to the rods (10) to engage leaflets (M1, M2). This facilitates the extremities (10a) of the rods from the leaflets (M1, M2). Rod (16) is then pulled while holding rod (17) in position to break frangible area (25). Leaflets (M1, M2) have thus been clipped to each other by their free edges, as shown in FIGS. 9 and 10.

[0040] FIG. 11 shows a variation of the apparatus where rods (10) and sheaths (11) have been replaced by two catheters (40) having trumpeted distal extremities (40a). These catheters (40) project beyond the proximal end of tube (2) and may be attached to syringes that permit the creation of negative pressure. The grasping or releasing of leaflets (M1, M2) is then achieved by controlling the internal pressure within catheters (40). The trumpeted ends (40a) ensure a sufficient grip on leaflets (M1, M2). Those ends (40a) are preferably sufficiently flexible enough to bend slightly when they are drawn between the wall of tube (2) and two lateral slots (26) of disk (20). The other parts of this alternative device are the same as already described and bear the same record numbers.

[0041] It goes without saying that the invention is not limited to the above example and is opened to different variations. For instance, the unstressed shape of the extremities (10a) that hook the tissues could be of a curved J which is straightened when drawn into the sheaths (11). The elongated parts (4) and the connecting system could also be placed in separate tubes. The device (1) could be inserted arterially as well as veinously.

What is claimed is:

1. A method for percutaneously attaching valve leaflets, said method comprising:
 - percutaneously introducing a device through a patient's vasculature into a heart chamber;
 - capturing a first valve leaflet by applying a vacuum to the device;

- capturing a second valve leaflet by applying a vacuum to the device, wherein the second valve leaflet is captured separately from the first valve leaflet;

- drawing the first and second captured leaflets together; and

- attaching the first valve leaflet to the second valve leaflet.

2. The method of claim 1, wherein the valve leaflets comprise mitral valve leaflets.

3. The method of claim 1, wherein percutaneously introducing the device comprises advancing the device across the intra-atrial septum into the left atrium.

4. The method of claim 1, wherein capturing the first valve leaflet or the second valve leaflet comprises advancing an elongate member from the device and securing the first valve leaflet or the second valve leaflet thereto.

5. The method of claim 1, wherein drawing the first and second captured leaflets together comprises drawing a first elongate member and a second elongate member together, wherein the first elongate member and the second elongate member extend from the device.

6. The method of claim 5, wherein drawing the first elongate member and the second elongate member together comprises advancing a sheath over the first and the second elongate members.

7. The method of claim 1, wherein attaching the first valve leaflet to the second valve leaflet comprises clipping the first valve leaflet to the second valve leaflet using a pair of clips.

8. The method of claim 7, wherein clipping the first valve leaflet to the second valve leaflet comprises advancing the pair of clips toward one another from the ventricular side and the atrial side with the first valve leaflet and the second valve leaflet therebetween to thereby capture the first valve leaflet and the second valve leaflet between the pair of clips.

9. The method of claim 8, wherein at least one clip of the pair of clips comprises a pair of prongs, wherein advancing the pair of clips toward one another forces the pair of prongs of the at least one clip through the first valve leaflet and the second valve leaflet and into the other of the pair of clips.

10. The method of claim 7, further comprising detaching the pair of clips from the device.

* * * * *