(19) DANMARK

(10) **DK/EP 2822976 T3**



(12)

Oversættelse af europæisk patentskrift

Patent- og Varemærkestyrelsen

(51) Int.Cl.: C 08 F 2/10 (2006.01) C 08 F 2/38 (2006.01)

(45) Oversættelsen bekendtgjort den: 2017-02-06

(80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2016-10-19**

(86) Europæisk ansøgning nr.: 13710988.0

(86) Europæisk indleveringsdag: 2013-03-11

(87) Den europæiske ansøgnings publiceringsdag: 2015-01-14

(86) International ansøgning nr.: EP2013054905

(87) Internationalt publikationsnr.: WO2013132108

(30) Prioritet: 2012-03-09 FR 1200725

(84) Designerede stater: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(73) Patenthaver: Rhodia Operations, 25, rue de Clichy, 75009 Paris, Frankrig

(72) Opfinder: DESTARAC, Mathias, 13 Avenue de Frizac, F-31000 Toulouse, Frankrig WILSON, James, David, 19 route de Lamorlaye, F-60580 Coye La Foret, Frankrig STOILOVA, Silvia, 171 rue de Charenton, 75012 Paris, Frankrig

(74) Fuldmægtig i Danmark: RWS Group, Europa House, Chiltern Park, Chiltern Hill, Chalfont St Peter, Bucks SL9 9FG, Storbritannien

(54) Benævnelse: KONTROLLERET RADIKALPOLYMERISATION I VAND-I-VAND-DISPERSION

(56) Fremdragne publikationer:

WO-A1-2009/153162 WO-A2-2008/000766 WO-A2-2011/110841 FR-A1- 2 917 415

DK/EP 2822976 T3

Description

10

The present invention relates to a method for preparing water-soluble polymers, giving access to these polymers in the form of concentrated aqueous dispersions. The present invention gives access to aqueous dispersions of this type which have a high solids content, but which are nevertheless fluid and stable and therefore can easily be transported, handled and stored. The invention also relates to applications of the dispersions thus produced, which can in particular be easily diluted in an aqueous medium so as to release the polymers in solution, for example so as to modify the rheological properties of an aqueous medium.

15 When reference is made, in the present description, to an "aqueous" medium, it is a medium comprising water, optionally as a mixture with other water-soluble solvents (for instance ethanol or other alcohols, for example, or else glycerol), and in which salts or else other water-soluble compounds can be dissolved. For the purposes of the present description, in an 20 "aqueous" medium, the water is preferably a compound present in an amount of at least 30% by weight, more preferentially of at least 50% by weight. When water-soluble solvents other than water are used, it is preferable for the ratio of the weight 25 of water present in the aqueous medium relative to the total weight of the water and of the other water-soluble solvents present in the medium (water/solvents weight ratio) to be greater than 50%, or even than 60%.

30 For the purposes of the present description, "an aqueous dispersion of a polymer" denotes a composition comprising a polymer in the form of microscopically observable particles having dimensions of between 100 nm and 20 microns (most commonly between 500 nm and 15 microns, and typically between 1 and 10 microns) dispersed within a phase consisting of an aqueous medium as defined above. A dispersion of polymers, within the meaning given to the term as used in the present description, should be distinguished from a solution of

polymers, which does not contain polymers in the form of microscopically observable particles. For the purposes of the present description, it is considered that a polymer is solubilized in a medium in particular if the medium contains no aggregate of this polymer in the form of aggregates exceeding 100 nm. An aqueous dispersion of a water-soluble polymer is generally quite easily distinguished, visually, from a polymer solution: typically, the dispersion has a milky appearance and widely scatters light, whereas a solution usually has a transparent appearance.

10

15

20

For the purposes of the present description, the term "water-soluble polymer" denotes a polymer which can be dissolved in water, at least under certain pH and salinity conditions, at a concentration of more than 0.1 g/l, or even more than 0.5 g/l, without the appearance of aggregates/particles having dimensions greater than 100 nm, and typically without any appearance of aggregates or particles. Such polymers are well known to those skilled in the art and, by way of water-soluble polymers of this type, mention may in particular be made, by way of illustration, of the homo- and copolymers obtained by polymerization of a monomer of acrylamido, N-vinylpyrrolidone (NVP) and/or acrylic acid type.

It is well known that the synthesis of water-soluble polymers is difficult to carry out directly in an aqueous medium; the polymerization of water-soluble monomers in fact causes an increase in the viscosity of the polymerization medium, and, in order to avoid an effect of solidification of the medium (or at the very least to allow the recovery of the polymer obtained), it is necessary to limit the molecular weight and/or the concentration of the polymer synthesized. Solution polymerization makes it possible to achieve weights exceeding 1 000 000 to 2 000 000 g/mol only with low dry extracts (1% to 15% at most).

Alternative solutions, such as gel polymerization, have admittedly been described, said alternative solutions

resulting in polymers which are in more concentrated form, but which are difficult to efficiently be dispersed in aqueous media. In addition, gel polymerization systematically results in high-molecular-weight polymers (typically greater than 5 000 000 g/mol).

To obtain high-molecular-weight water-soluble polymers (greater than 500 000 g/mol), it is well-known practice to carry out an inverse emulsion polymerization, namely by carrying out the polymerization in droplets dispersed in a hydrophobic continuous medium. Polymerizations of this type (termed "inverse emulsion polymerizations") admittedly result in polymers of relatively high molecular weight, in particular in the range of from 500 000 to 10 000 000 g/mol, but, in order to subsequently use them in an aqueous medium, it is necessary to separate them from the hydrophobic phase, which results in additional costs. Moreover, the polymers obtained comprise surfactants used for their synthesis which can be detrimental to certain subsequent applications, unless they are extracted, which involves additional costs.

10

15

20

25

30

35

Variants have in the past been proposed in order to try to overcome these difficulties, and to attempt to dispersions of water-soluble polymers directly in an aqueous medium, for example by synthesizing polymers with an ionic nature in an aqueous medium comprising salts, the polymer precipitating when it reaches a sufficiently high molecular weight. In this type of process, sometimes "homogeneous dispersion polymerization", schematically, polymerization begins as in a solution polymerization of usual type, but finishes as in polymerization in a dispersed medium. By way of example of processes of this type, mention may, for example, be made of the methods proposed in US 3 658 772, US 3 493 500 or in FR 2 879 606 or else in American Chemical Society Symposium Series, vol 755, Chapter 4, 36-45. aqueous dispersions of water-soluble polymers which obtained by homogeneous dispersion polymerization admittedly advantageous (in particular by virtue of their

relatively low cost and by virtue of the access to dispersions directly usable in an aqueous medium), but they are limited to specific polymers and they also have two major drawbacks, namely:

- 5 a high viscosity:
 - although similar, in spirit, to an inverse phase polymerization, homogeneous dispersion polymerization results in polymers of which a part remains in solution and which therefore causes an increase in the viscosity of the medium,
- in a manner similar to solution polymerization. Thus, even though it is produced, the problem encountered in solution polymerization is still present, which imposes similar limitations in terms of polymer size and of concentration;
 - a relative stability:
- the polymer particles have a tendency to coalesce, during the polymerization and subsequently, which can cause solidification phenomena during the polymerization and/or sedimentation phenomena during transportation or storage of the dispersions, thereby, once again, involving limitations in terms of polymer size and/or of concentration.

Given these drawbacks, the polymer content in the dispersions obtained rarely exceeds 20% by weight.

In addition, this type of polymerization (homogeneous dispersion polymerization) exhibits poor control regarding the structure of the polymer chains formed, typically poor control of the molecular weight of the chains formed, which can result in a very high polydispersity.

30

An objective of the present invention is to provide a method for obtaining water-soluble polymers in the form of a dispersion in an aqueous medium, which dispenses with the abovementioned difficulties.

35

To this effect, it is proposed, according to the present invention, to carry out a polymerization of the abovementioned homogeneous dispersion polymerization type, but using, in

addition, a reactive stabilizer which provides increased stabilization compared with that obtained with the abovementioned processes, allowing in particular higher solids contents.

5

10

More specifically, a subject of the present invention is a process for preparing an aqueous dispersion of water-soluble polymers, which comprises a step (E) of radical polymerization, wherein the following are brought into contact in an aqueous medium (M) in which the synthesized polymer is not soluble:

- at least one ethylenically unsaturated monomer which is soluble in the aqueous medium (M);
- at least one source of free radicals; and
- 15 a reactive stabilizer which comprises:
 - a polymer chain (PC) which is soluble in the medium (M),
 - a group (G) providing the radical polymerization of step (E) with a living and controlled nature, such as, for example, a group carrying a thiocarbonylthio -S(C=S)- group.

20

25

30

35

The reactive stabilizer which is used in step (E) is a particular compound, which is used in the polymerization process (E), according to a mechanism that is well known per se, termed "living" controlled radical polymerization, for example described in patent applications WO 98/58974, 00/75207 and WO 01/42312. Schematically, according to this mechanism, the polymerization of step (E) results in formation of a polymer chain by gradual insertion of the monomer units between the polymer chain initially present on the reactive compound and the group providing the living nature. The polymerization is termed "living" insofar as the polymer being formed remains continually available for the incorporation of new monomer units between the polymer chain being formed and the group providing the living and controlled nature. Moreover, the polymerization is termed "controlled" since the size of the growing chains can be finely regulated, typically according to the ratio of the number of monomers to the number of groups providing a living and controlled nature

that are available in the medium (the higher this ratio, the higher the molecular weight obtained). It should be noted in this respect that, compared with the methods described in the past, the method of the present invention makes it possible to obtain a very fine control of the structure of the polymer chains formed, with in particular a very precise control of the molecular weight of the chains formed and a very low polydispersity index, which constitutes another advantage of the present invention. This control makes it possible in particular to scan through a very wide size range 10 for the polymers synthesized, with molecular weights which can range from 500 000 to 20 000 000 g/mol, for example between 1 000 000 and 15 000 000 g/mol and in particular between 2 000 and 10 000 000 g/mol. More generally, the molecular weights for the polymers synthesized can typically range from 15 5000 to a few million q/mol, for example from 10 000 to 10 000 000 g/mol, in particular from 20 000 to 5 000 000 g/mol.

The reactive stabilizer used in step (E) has, moreover, a polymer chain (PC) which is soluble in the aqueous medium (M) of step (E). The reactive stabilizer is typically a living polymer or oligomer, resulting from a step (E⁰) prior to step (E), wherein the following are brought into contact:

- at least one ethylenically unsaturated monomer which is soluble in the aqueous medium (M);
 - at least one source of free radicals; and

25

30

- an agent for controlling the radical polymerization, for example an agent carrying a thiocarbonylthio -S(C=S)- group and typically an agent carrying the same group (G) as the one desired on the reactive stabilizer of step (E).

The polymer chain which is present on the reactive stabilizer is specifically soluble in the medium (M). Given the specific conditions for carrying out step (E), this polymer chain remains continuously covalently bonded to the end of the growing polymer chains in step (E). The soluble polymer chain (PC) present from the beginning on the reactive stabilizer of step (E) is generally distinct in nature from the polymer

chain which is formed during step (E).

Although the polymer chain which forms in step (E) becomes gradually insoluble in the medium (M) following incorporation of monomer units, the polymer chain (PC) remains, for its part, continuously soluble in the medium (M). As a result, during the conducting of step (E), living polymer chains which are soluble in the medium (M) first form. followed by precipitation of the chains in the form of particles which have the stabilizing polymer chains (PC) at the periphery, and then the continuation of the polymerization within the particles thus formed, according to a mechanism similar to that of dispersion polymerization. The very fine control of the radical polymerization performed according to the invention allows, in this context, a better control of these steps, and in particular a better management of the nucleation step than that which is obtained for example in the homogeneous dispersion polymerization processes of the type described at the beginning of the present description.

20

25

15

10

As indicated above in the present description, the polymers synthesized at the end of step (E) are insoluble in the medium (M) where they are dispersed. Nevertheless, these polymers based on water-soluble units are, intrinsically, water-soluble polymers for the purposes of the present description, which can therefore be redissolved in an aqueous medium, for example by simple dilution in an aqueous medium.

Although it is not absolutely required, step (E) of 30 process of the invention can, according to one particular embodiment, can be brought together with additional agents, for nonreactive stabilizing example amphiphilic polymers which are block polymers or which more generally comprise a block which is not compatible with the medium (M) 35 a block which is compatible with the medium (M), advantageously obtained according to a controlled radical polymerization process, or else nonreactive stabilizing homoand copolymers. For the purposes of the present description,

the term "nonreactive stabilizer" is intended to mean a stabilizing agent which does not comprise a group (G). According to another embodiment of the invention, no nonreactive additional stabilizing agent is used during step (E).

5

10

15

20

25

30

35

According to another aspect, a subject of the present invention is the dispersions of the type obtained according to the abovementioned process, typically directly at the end of step (E). In addition to the advantages described above with regard to the control of the polymer chains formed, these dispersions have the advantage of being stable and of low viscosity, and therefore of being easy to handle and to transport, with solids contents which can be high. The present invention makes it possible in particular to obtain polymer dispersions where the polymer concentration can be greater than 10%, in particular greater than or equal to 15%, preferably greater than 20%, or even greater than 30%, or even greater than 35% or even than 40% in certain cases, which is not obtained with the current processes, to the inventors' knowledge. Typically, the polymer concentration nevertheless remains less than 60% by weight, or even than 50% by weight. Particularly advantageous dispersions that can be prepared according to the invention have, for example, polymer contents between 30% and 50% by weight, for example between 35% and 45% by weight.

The aqueous dispersions of polymer which are obtained in the context of the present invention also have the advantage that they can be used as they are as an additive for aqueous compositions without a subsequent purification or phaseinversion step (contrary, for example, to the dispersions resulting from inverse emulsion polymerization). The addition of a small amount of a dispersion according to the invention to an aqueous composition results, as a general rule, in a dissolution effect which induces rapid and direct solubilization of the polymer in said composition. This effect can advantageously be used to increase the viscosity of an

aqueous composition or more generally to modify the rheological properties of this aqueous composition. In this context, the polymer present in the dispersions of the invention performs the role of rheology-modifying agent only in the final composition, when it is in the solubilized state. It is interesting to note that it does not provide this effect in the dispersions of the present invention, where it is, on the contrary, present in the dispersed state. The dispersions of the invention constitute, in this respect, a very advantageous alternative to the aqueous solutions of polymer obtained by solution polymerization which are extremely viscose and difficult to handle.

The aqueous dispersions of the present invention can also act as a surface-modifying agent.

Various advantageous features and embodiments of the invention will now be described in greater detail.

20 The reactive stabilizer

25

The nature of the group (G) present on the reactive stabilizer and providing the polymerization step (E) with a living and controlled nature (group also hereinafter designated "control group") can vary to quite a large extent. According to one particular embodiment, the reactive stabilizer used in step (E) can carry several groups of this type, but it usually carries only one group (G).

- 30 The control group (G), which is suitable for inducing a controlled radical polymerization reaction of monomers, can for example be:
 - a xanthate group as described, for example, in WO 98/58974,
 - a dithiocarbamate group as described in WO 99/31144,
- 35 a dithiocarbazate group as described in WO 02/26836,
 - a dithiophosphoroester group as described in WO 02/10223.

Preferably, it is a xanthate, dithiocarbamate or

dithiocarbazate group, more preferentially a xanthate group.

More generally, step (E) can be carried out using one of the following processes:

- 5 the process of application WO 99/03894 which carries out a polymerization in the presence of nitroxide precursors,
 - the process of application WO 96/30421 which uses an atom transfer radical polymerization (ATRP),
- the process of controlled radical polymerization using control agents of iniferter type according to the teaching of Otu et al., Makromol. Chem. Rapid. Commun., 3, 127 (1982),
 - the process of controlled radical polymerization by degenerative transfer of iodine according to the teaching of Tatemoto et al., Jap. 50, 127, 991 (1975), Daikin Kogyo Co ltd Japan and Matyjaszewski et al., Macromolecules, 28, 2093
- 15 Japan and Matyjaszewski et al., Macromolecules, 28, 2093 (1995),
 - the process of controlled radical polymerization using tetraphenylethane derivatives, disclosed by D. Braun et al. in Macromol. Symp. 111, 63 (1996), or else
- the process of controlled radical polymerization using organocobalt complexes, described by Wayland et al. in J.Am.Chem.Soc. 116,7973 (1994),

25

30

35

- the process of controlled radical polymerization using diphenylethylene (WO 00/39169 or WO 00/37507).

More generally, the group (G) can be selected from all the groups suitable for carrying out a controlled polymerization of the monomers used in step (E), for example of ATRP (atom transfer radical polymerization), NMP (nitroxide-mediated polymerization), RAFT or MADIX type.

The control group comprising a thiocarbonylthio -S(C=S)-group, and particularly xanthates, dithioesters, trithiocarbonates, dithiocarbamates and dithiocarbazates, proved to be particularly advantageous as group (G) in the reactive stabilizers used in step (E).

According to one particularly advantageous embodiment, this

group is introduced via the control agent used in the controlled radical polymerization performed in the abovementioned step $(E^{\scriptscriptstyle 0})$, which is typically a RAFT or MADIX control agent.

5

The group (G) present on the reactive stabilizer typically corresponds to the formula -S(C=S)-Z where Z is as defined below, this group being typically obtained by using, in step (E^0) , a control agent which corresponds to formula (A) below:

10

$$R_1-S- \stackrel{S}{\swarrow}_Z$$
(A)

in which:

15 - Z represents:

- . a hydrogen atom,
- . a chlorine atom,
- . an optionally substituted alkyl or optionally substituted aryl radical,
- 20 . an optionally substituted heterocycle,
 - . an optionally substituted alkylthio radical,
 - . an optionally substituted arylthic radical,
 - . an optionally substituted alkoxy radical,
 - . an optionally substituted aryloxy radical,
- 25 . an optionally substituted amino radical,
 - . an optionally substituted hydrazine radical,
 - . an optionally substituted alkoxycarbonyl radical,
 - . an optionally substituted aryloxycarbonyl radical,
 - . an optionally substituted carboxyl, acyloxy radical,
- 30 . an optionally substituted aroyloxy radical,
 - . an optionally substituted carbamoyl radical,
 - . a cyano radical,
 - . a dialkyl- or diaryl-phosphonato radical,
 - . a dialkyl-phosphinato or diaryl-phosphinato radical,
- 35 or
 - . a polymer chain,

and

- R₁ represents:
- . an optionally substituted alkyl, acyl, aryl, aralkyl, alkene or alkyne group,
- . a saturated or unsaturated, aromatic, optionally substituted carbocycle or heterocycle, or
 - . a polymer chain.

The groups R1 or Z, when they are substituted, may be substituted with optionally substituted phenyl groups, 10 optionally substituted aromatic groups, saturated unsaturated carbocycles, saturated or unsaturated heterocycles, or groups selected from the following: alkoxycarbonyl or aryloxycarbonyl (-COOR), carboxyl (-COOH), acyloxy (-02CR), carbamoyl (-CONR2), cyano (-CN), alkylarylcarbonyl, alkylcarbonyl, 15 arylcarbonyl, arylalkylcarbonyl, phthalimido, maleimido, succinimido, amidino, guanidimo, hydroxyl (-OH), amino (-NR2), halogen, perfluoroalkyl CnF2n+1, allyl, epoxy, alkoxy (-OR), S-alkyl, S-aryl, groups of hydrophilic or ionic nature such as alkali metal salts of carboxylic acids, alkali metal salts of 20 sulfonic acid, polyalkylene oxide chains (PEO, PPO), cationic substituents (quaternary ammonium salts), R representing an alkyl or aryl group, or a polymer chain.

According to one particular embodiment, R_1 is a substituted or unsubstituted, preferably substituted, alkyl group.

The optionally substituted alkyl, acyl, aryl, aralkyl or alkyne groups to which reference is made in the present description generally contain 1 to 20 carbon atoms, preferably 1 to 12 and more preferentially 1 to 9 carbon atoms. They may be linear or branched. They may also be substituted with oxygen atoms, in particular in the form of esters or sulfur or nitrogen atoms.

35

30

Among the alkyl radicals, mention may be made especially of methyl, ethyl, propyl, butyl, pentyl, isopropyl, tert-butyl, pentyl, hexyl, octyl, decyl or dodecyl radicals.

For the purposes of the present description, the alkyne groups are radicals generally containing from 2 to 10 carbon atoms, and contain at least one acetylenic unsaturation, such as the acetylenyl radical.

For the purposes of the present description, the acyl groups are radicals generally containing from 1 to 20 carbon atoms with a carbonyl group.

10

Among the aryl radicals which may be used according to the invention, mention may be made in particular of the phenyl radical, optionally substituted especially with a nitro or hydroxyl function.

15

30

Among the aralkyl radicals, mention may be made in particular of the benzyl or phenethyl radical, optionally substituted especially with a nitro or hydroxyl function.

20 When R_1 or Z is a polymer chain, this polymer chain may be derived from a radical or ionic polymerization or derived from a polycondensation.

In the context of the present invention, it is especially advantageous to use, as control agents, xanthates, dithiocarbamates or dithiocarbazates.

Advantageously, use is made, as control agent in step (E^0) , of xanthate compounds, for instance O-ethyl-S-(1-methoxycarbonyl ethyl) xanthate of formula $(CH_3CH(CO_2CH_3))S(C=S)OCH_2CH_3$, and, more generally, the reactive stabilizer of step $(E^{\frac{1}{2}})$ preferably carries such groups.

A control agent that is particularly suited to the implementation of step (E^0) is the compound sold by the company Rhodia under the name Rhodixan A1.

The polymer chain (PC) which is present on the reactive

stabilizer may also vary to quite a large extent and it can be adjusted, case-by-case, according to the medium (M) used and to the type of composition into which it is desired to introduce the polymer of the dispersion.

5

10

- Typically, the polymer chain (PC) present on the reactive stabilizer can, for example, be selected from the homo- and copolymers (random, gradient or block) resulting from the homopolymerization or from the copolymerization of monomers of which at least one part is selected from:
- ethylenically unsaturated monocarboxylic and dicarboxylic acid, such as acrylic acid, methacrylic acid, itaconic acid, maleic acid or fumaric acid,
- unsaturated carboxylic acid amides, such as acrylamide,
 methacrylamide, N-methylolacrylamide or -methacrylamide,
 N-alkylacrylamides,
 - vinylamine amides, in particular vinylformamide, vinylacetamide, N-vinylpyrrolidone and N-vinylcaprolactam, or more generally from:
- 20 ethylenically unsaturated monocarboxylic and dicarboxylic acids, such as acrylic acid, methacrylic acid, itaconic acid, maleic acid or fumaric acid,
 - unsaturated carboxylic acid amides, such as acrylamide, methacrylamide, N-methylolacrylamide or -methacrylamide, N- \sim N-
- alkylacrylamides, N,N-dimethylaminomethylacrylamide or methacrylamide, 2-(N,N-dimethylamino)ethylacrylamide or methacrylamide, 3-(N,N-dimethylamino)propylacrylamide or methacrylamide, or 4-(N,N-dimethylamino)butylacrylamide or methacrylamide,
- 30 vinylamine amides, in particular vinylformamide, vinylacetamide, N-vinylpyrrolidone and N-vinylcaprolactam,
 - α , β monoethylenically unsaturated amino esters, such as 2-(dimethylamino)ethyl acrylate (ADAM), 2-(dimethylamino)ethyl méthacrylate (DMAM or MADAM), 3-(dimethylamino)propyl methacrylate, 2-(tert-butylamino)ethyl méthacrylate, 2-
- 35 methacrylate, 2-(tert-butylamino)ethyl méthacrylate, 2-(dipentylamino)ethyl méthacrylate, or 2-(diethylamino)ethyl méthacrylate,
 - vinylpyridines,

- vinylamine,
- vinylimidazolines,
- monomers which are precursors of amine functions, such as N-vinylformamide or N-vinylacetamide, which generate primary amine functions by simple acid or basic hydrolysis,
- ammoniumacryloyl or acryloyloxy monomers,
- trimethylammoniumpropylmethacrylate salts, in particular the chloride,
- trimethylammoniumethylacrylamide or -methacrylamide chloride 10 or bromide,
 - trimethylammoniumbutylacrylamide or -methacrylamide methylsulfate,
 - trimethylammoniumpropylmethacrylamide methylsulfate (MAPTA MeS),
- 15 (3-methacrylamidopropyl)trimethylammonium chloride (MAPTAC),
 - (3-acrylamidopropyl)trimethylammonium chloride or methylsulfate (APTAC or APTA MeS),
 - methacryloyloxyethyltrimethylammonium chloride or methylsulfate,
- acryloyloxyethyltrimethylammonium (ADAMQUAT) salts, such as
 acryloyloxyethyltrimethylammonium chloride or
 acryloyloxyethyltrimethylammonium methylsulfate (ADAMQUAT Cl
 or ADAMQUAT MeS),
- methyldiethylammoniumethyl acrylate methylsulfate (ADAEQUAT 25 MeS),
 - benzyldimethylammoniumethyle acrylate chloride or methylsulfate (ADAMQUAT BZ 80),
 - 1-ethyl 2-vinylpyridinium bromide, chloride or methylsulfate or 1-ethyl 4-vinylpyridinium bromide, chloride or methylsulfate,
 - N,N-dialkyldiallylamine monomers, such as N,N-dimethyldiallylammonium chloride (DADMAC),
 - dimethylaminopropylmethacrylamide, N-(3-chloro-2-hydroxypropyl)trimethylammonium chloride (DIQUAT chloride),
- 35 dimethylaminopropylmethacrylamide, N-(3-methylsulfate-2-hydroxypropyl)trimethylammonium methylsulfate (DIQUAT methylsulfate),
 - the monomer of formula

30

$$\begin{array}{c|c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & &$$

where X- is an anion, preferably chloride or methylsulfate,

- monomers carrying at least one vinyl phosphonate function,
such as vinylphosphonic acid, vinylphosphonic acid dimethyl
ester, vinylphosphonic acid bis(2-chloroethyl) ester,
vinylidenediphosphonic acid, vinylidenediphosphonic acid
tetraisopropyl ester or alpha-styrenephosphonic acid, or
mixtures thereof.

Alternatively, the monomers may comprise monomers selected from:

- ethylenically unsaturated carboxylic acids, sulfonic acids and phosphonic acids, and/or derivatives thereof such as 15 acrylic acid (AA), methacrylic acid, ethacrylic acid, α chloroacrylic acid, crotonic acid, maleic acid, maleic anhydride, itaconic acid, citraconic acid, mesaconic acid, glutaconic acid, aconitic acid, fumaric 20 monoethylenically unsaturated dicarboxylic acid monoesters comprising 1 to 3 and preferably 1 to 2 carbon atoms, for example monomethyl maleate, vinylsulfonic acid, (meth)allylsulfonic acid, sulfoethyl acrylate, sulfoethyl methacrylate, sulfopropyl acrylate, sulfopropyl methacrylate, 25 2-hydroxy-3-acryloyloxypropylsulfonic acid, 2-hydroxy-3methacryloyloxypropylsulfonic acid, styrenesulfonic acids, 2acrylamido-2-methylpropanesulfonic acid, vinylphosphonic acid, α -methylvinylphosphonic acid and allylphosphonic acid;

- esters of α , β -ethylenically unsaturated monocarboxylic and dicarboxylic acids with C2-C3 alkanediols, for example 2-hydroxyethyl acrylate, 2-hydroxyethyl methacrylate, 2-hydroxyethyl acrylate, 2-hydroxypropyl acrylate, 2-hydroxypropyl acrylate, 3-hydroxypropyl acrylate, 3-hydroxypropyl methacrylate and polyalkylene glycol (meth)acrylates;

- α , β -ethylenically unsaturated monocarboxylic acid amides and

- the N-alkyl and N,N-dialkyl derivatives thereof, such as acrylamide, methacrylamide, N-methyl (meth) acrylamide, N-ethyl (meth) acrylamide, N-propyl (meth) acrylamide, N,N-diethyl (meth) acrylamide, morpholinyl (meth) acrylamide, and metholylacrylamide (acrylamide and N,N-dimethyl (meth) acrylamide prove to be in particular advantageous);
 - N-vinyllactams and derivatives thereof, for example N-vinylpyrrolidone and N-vinylpiperidone;
- open-chain N-vinylamide compounds, for example N-vinylformamide, N-vinyl-N-methylformamide, N-vinylacetamide, N-vinyl-N-methylacetamide, N-vinyl-N-methylacetamide, N-vinylpropionamide, N-vinyl-N-methylpropionamide and N-vinylbutyramide;
- esters of α , β-ethylenically unsaturated monocarboxylic and dicarboxylic acids with aminoalcohols, for example N,N-dimethylaminomethyl (meth)acrylate, N,N-dimethylaminoethyl (meth)acrylate, N,N-diethylaminoethyl acrylate, and N,N-dimethylaminopropyl (meth)acrylate;
- amides of α , β -ethylenically unsaturated monocarboxylic and 20 dicarboxylic acids with diamines comprising at least one secondary primary or amino group, such as N-[2-(dimethylamino)ethyl]acrylamide, N[2-(dimethylamino)ethyl]methacrylamide, N - [3 -25 (dimethylamino)propyl]acrylamide, N-[3-(dimethylamino)propyl]methacrylamide, N - [4 -
 - (dimethylamino)butyl]methacrylamide;

(dimethylamino)butyl]acrylamide

- N-diallylamines, N,N-diallyl-N-alkylamines, acid-addition salts thereof and quaternization products thereof, the alkyl used here preferentially being C_1 - C_3 -alkyl;

and

N - [4 -

- N,N-diallyl-N-methylamine and N,N-diallyl-N,N-dimethylammonium compounds, for example the chlorides and bromides;
- nitrogenous heterocycles substituted with vinyl and allyl, for example N-vinylimidazole, N-vinyl-2-methylimidazole, heteroaromatic compounds substituted with vinyl and allyl, for example 2- and 4-vinylpyridine, 2- and 4-allylpyridine, and

salts thereof;

- sulfobetaines; and
- mixtures and combinations of two or more of the abovementioned monomers.

5

The polymer chain (PC) present on the reactive stabilizer can also comprise some units which are hydrophobic in nature, provided that the chain (PC) remains, overall, soluble in the medium (M).

10

Whatever its nature, the reactive stabilizer used in step (E+) can typically be used at a weight concentration ranging from 0.05% to 10%, for example between 0.1% and 5%, in the medium (M). The lower the reactive stabilizer/monomer ratio, the larger the size of the polymer chains synthesized in step (E). For low contents of reactive stabilizer, for example below 1%, it may prove to be advantageous to use nonreactive additional stabilizers of the type described above in the present description.

20

The water-soluble monomers

The water-soluble monomers used in step (E) can be selected from all the monomers which are soluble per se in the aqueous 25 medium (M), but which form polymers which are insoluble in this medium.

The polymers formed in step (E) are insoluble in the medium (M), in the sense that they are in the dispersed state in the medium (M) at the end of the reaction. As indicated above in the present description, these polymers are nevertheless intrinsically water-soluble.

For the purposes of the invention, the term "polymer insoluble in the medium (M)" is intended to mean a polymer which is able to form particles during its formation in step (E). Preferably, it is not a polymer which exhibits this property only in a given temperature range. In this respect, the

monomers used in step (E) are preferably distinct from NIPAM monomers.

The water-soluble monomers used in step (E) may, for example, be monomers which are soluble in the medium (M) and which are selected from:

- ethylenically unsaturated monocarboxylic and dicarboxylic acid, such as acrylic acid, methacrylic acid, itaconic acid, maleic acid or fumaric acid,
- or unsaturated carboxylic acid amides, such as acrylamide, methacrylamide, N-methylolacrylamide or -methacrylamide, N-alkylacrylamides, N,N-dimethylaminomethylacrylamide or -methacrylamide, 2-(N,N-dimethylamino)ethylacrylamide or -methacrylamide, 3-(N,N-dimethylamino)propylacrylamide or -methacrylamide, or 4-(N,N-dimethylamino)butylacrylamide or -methacrylamide,
 - vinylamine amides, in particular vinylformamide, vinylacetamide, N-vinylpyrrolidone and N-vinylcaprolactam,
- α , β monoethylenically unsaturated amino esters, such as 2-20 (dimethylamino)ethyl acrylate (ADAM), 2-(dimethylamino)ethyl méthacrylate (DMAM or MADAM), 3-(dimethylamino)propyl methacrylate, 2-(tert-butylamino)ethyl méthacrylate, 2-(dipentylamino)ethyl méthacrylate, or 2-(diethylamino)ethyl méthacrylate,
- 25 vinylpyridines,
 - vinylamine,

30

- vinylimidazolines,
- monomers which are precursors of amine functions, such as N-vinylformamide or N-vinylacetamide, which generate primary amine functions by simple acid or basic hydrolysis,
- ammoniumacryloyl or acryloyloxy monomers,
- trimethylammoniumpropylmethacrylate salts, in particular the chloride,
- trimethylammoniumethylacrylamide or -methacrylamide chloride 35 or bromide,
 - trimethylammonium butylacrylamide or -methacrylamide methylsulfate,
 - trimethylammoniumpropylmethacrylamide methylsulfate (MAPTA

MeS),

10

- (3-methacrylamidopropyl) trimethylammonium chloride (MAPTAC),
- (3-acrylamidopropyl)trimethylammonium chloride or methylsulfate (APTAC or APTA MeS),
- 5 methacryloyloxyethyltrimethylammonium chloride or methylsulfate,
 - acryloyloxyethyltrimethylammonium (ADAMQUAT) salts, such as acryloyloxyethyltrimethylammonium chloride or acryloyloxyethyltrimethylammonium methylsulfate (ADAMQUAT Cl or ADAMQUAT MeS),
 - methyldiethylammoniumethyl acrylate methylsulfate (ADAEQUAT MeS),
 - benzyldimethylammoniumethyle acrylate chloride or methylsulfate (ADAMQUAT BZ 80),
- 15 1-ethyl 2-vinylpyridinium bromide, chloride or methylsulfate or 1-ethyl 4-vinylpyridinium bromide, chloride or methylsulfate,
 - N,N-dialkyldiallylamine monomers, such as N,N-dimethyldiallylammonium chloride (DADMAC),
- 20 dimethylaminopropylmethacrylamide, N-(3-chloro-2-hydroxypropyl)trimethylammonium chloride (DIQUAT chloride),
 - dimethylaminopropylmethacrylamide, N-(3-methylsulfate-2-hydroxypropyl)trimethylammonium methylsulfate (DIQUAT methylsulfate),
- 25 the monomer of formula

$$\begin{array}{c|c} & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & &$$

where X⁻ is an anion, preferably chloride or methylsulfate,

- monomers carrying at least one vinyl phosphonate function,
such as vinylphosphonic acid, vinylphosphonic acid dimethyl
ester, vinylphosphonic acid bis(2-chloroethyl) ester,
vinylidenediphosphonic acid, vinylidenediphosphonic acid
tetraisopropyl ester or alpha-styrenephosphonic acid, or
mixtures thereof, mixtures of two or more of these monomers.

Alternatively, the monomers may comprise monomers selected from:

- ethylenically unsaturated carboxylic acids, sulfonic acids and phosphonic acids, and/or derivatives thereof such as 5 acrylic acid (AA), methacrylic acid, ethacrylic acid, α chloroacrylic acid, crotonic acid, maleic acid, maleic anhydride, itaconic acid, citraconic acid, mesaconic acid, aconitic acid, fumaric glutaconic acid, monoethylenically unsaturated dicarboxylic acid monoesters comprising 1 to 3 and preferably 1 to 2 carbon atoms, for 10 vinylsulfonic monomethyl maleate, (meth)allylsulfonic acid, sulfoethyl acrylate, sulfoethyl methacrylate, sulfopropyl acrylate, sulfopropyl methacrylate, 2-hydroxy-3-acryloyloxypropylsulfonic acid, 2-hydroxy-3methacryloyloxypropylsulfonic acid, styrenesulfonic acids, 2-15 acrylamido-2-methylpropanesulfonic acid, vinylphosphonic acid, α -methylvinylphosphonic acid and allylphosphonic acid;
- esters of α , β -ethylenically unsaturated monocarboxylic and dicarboxylic acids with C2-C3 alkanediols, for example 2-20 hydroxyethyl acrylate, 2-hydroxyethyl methacrylate, 2-hydroxyethyl acrylate, 2-hydroxypropyl acrylate, 2-hydroxypropyl acrylate, 3-hydroxypropyl acrylate, 3-hydroxypropyl methacrylate and polyalkylene glycol (meth)acrylates;
- 25 α,β-ethylenically unsaturated monocarboxylic acid amides and the N-alkyl and N,N-dialkyl derivatives thereof, such as acrylamide, methacrylamide, N-methyl (meth) acrylamide, N-ethyl (meth) acrylamide, N-propyl (meth) acrylamide, N,N-diethyl (meth) acrylamide, N,N-diethyl (meth) acrylamide, and metholylacrylamide (acrylamide and N,N-dimethyl (meth) acrylamide prove to be in particular advantageous);
 - N-vinyllactams and derivatives thereof, for example N-vinylpyrrolidone and N-vinylpiperidone;
- open-chain N-vinylamide compounds, for example N-vinylformamide, N-vinyl-N-methylformamide, N-vinylacetamide, N-vinyl-N-methylacetamide, N-vinyl-N-ethylacetamide, N-vinyl-N-methylpropionamide and N-vinylpropionamide, N-vinyl-N-methylpropionamide and N-vinyl-N-methylpropionamide

N - [4 -

vinylbutyramide;

5

10

- esters of α , β -ethylenically unsaturated monocarboxylic and dicarboxylic acids with aminoalcohols, for example N,N-dimethylaminomethyl (meth)acrylate, N,N-dimethylaminoethyl (meth)acrylate, N,N-diethylaminoethyl acrylate, and N,N-dimethylaminopropyl (meth)acrylate;
- amides of α , β -ethylenically unsaturated monocarboxylic and dicarboxylic acids with diamines comprising at least one primary or secondary amino group, as N-[2such (dimethylamino)ethyl]acrylamide, N[2-(dimethylamino)ethyl]methacrylamide, N - [3 -(dimethylamino)propyl]acrylamide, N - [3 -(dimethylamino)propyl]methacrylamide, N - [4 -
- (dimethylamino)butyl]acrylamide
 15 (dimethylamino)butyl]methacrylamide;
 - N-diallylamines, N,N-diallyl-N-alkylamines, acid-addition salts thereof and quaternization products thereof, the alkyl used here preferentially being C_1 - C_3 -alkyl;

and

- N,N-diallyl-N-methylamine and N,N-diallyl-N,N-20 dimethylammonium compounds, for example the chlorides and bromides;
 - nitrogenous heterocycles substituted with vinyl and allyl, for example N-vinylimidazole, N-vinyl-2-methylimidazole, heteroaromatic compounds substituted with vinyl and allyl, for example 2- and 4-vinylpyridine, 2- and 4-allylpyridine, and salts thereof;
 - sulfobetaines; and
 - mixtures and combinations of two or more of the abovementioned monomers.

30

25

The following monomers are in particular advantageous:

- ethylenically unsaturated monocarboxylic and dicarboxylic acid, such as acrylic acid, methacrylic acid, itaconic acid, maleic acid or fumaric acid,
- 35 unsaturated carboxylic acid amides, such as acrylamide, methacrylamide, N-methylolacrylamide or -methacrylamide, Nalkylacrylamides,
 - vinylamine amides, in particular vinylformamide,

vinylacetamide, N-vinylpyrrolidone and N-vinylcaprolactam.

The polymer chain synthesized in step (E) may be a homopolymer or else a random or gradient copolymer. According to one 5 particular embodiment, it may be a block polymer chain: for this, step (E) can be carried out in several steps, by first performing a first polymerization step with a first type of monomer, and then at least a second polymerization step while introducing other polymers into the medium, after exhaustion of the monomers of the first step.

The polymer chain synthesized in step (E) can more generally just as easily be cationic, anionic or zwitterionic, as nonionic.

10

20

15 According to one advantageous embodiment, water-soluble crosslinking monomers can be added together with or after the introduction of the water-soluble monomers. Advantageously, they make it possible to use nonreactive stabilizers in the process of the present invention.

Preferably, these monomers have two or three ethylenic unsaturations.

Thus, mention may in particular be made of acrylic, 25 methacrylic, acrylamido, methacrylamido, vinyl ester, vinyl diene, styrene, alpha-methylstyrene, derivatives. These monomers may thus contain functional groups other than ethylenic unsaturations, for example hydroxyl, carboxyl, ester, amide, amino or substituted amino, mercapto, 30 silane, epoxy or halo functions.

The monomers belonging to these families are divinylbenzene derivatives, vinyl methacrylate, divinylbenzene and methacrylic acid anhydride, allyl methacrylate, ethylene 35 glycol dimethylacrylate, phenylene dimethylacrylate, diethylene glycol dimethylacrylate, triethylene dimethylacrylate, tetraethylene glycol dimethylacrylate, polyethylene glycol 200 dimethylacrylate, polyethylene glycol

400 dimethylacrylate, 1,3-butanediol dimethylacrylate, 1,4butanediol dimethylacrylate, 1,6-hexanediol dimethylacrylate, 1,12-dodecanediol dimethylacrylate, 1,3-glyceryl dimethylacrylate, diurethane dimethylacrylate , 5 trimethylolpropane trimethylacrylate. For the family multifunctional acrylates, mention may particularly be made of vinyl acrylate, bisphenol A epoxy diacrylate, dipropylene diacrylate, tripropylene glycol glycol diacrylate, polyethylene glycol 600 diacrylate, ethylene 10 diacrylate, diethylene glycol diacrylate, triethylene glycol diacrylate, tetraethylene glycol diacrylate, ethoxylated neopentyl glycol diacrylate, butanediol diacrylate, hexanediol diacrylate, aliphatic urethane diacrylate, trimethylolpropane triacrylate, ethoxylated trimethylolpropane triacrylate, 15 propoxylated trimethylolpropane triacrylate, propoxylated glyceryl triacrylate, aliphatic urethane triacrylate, trimethylolpropane tetraacrylate, and dipentaerythritol pentaacrylate. With regard to the vinyl ethers, mention may particularly be made of vinyl crotonate, diethylene glycol divinyl ether, 1,4-butanediol divinyl ether, and triethylene 20 glycol divinyl ether. For the allyl derivatives, mention may particularly be made of diallyl phthalate, diallyldimethylammonium chloride, diallyl maleate, sodium diallyloxyacetate, diallylphenylphosphine, diallyl pyrocarbonate, diallyl succinate, N, N'-diallyltartardiamide, 25 N, N-dially1-2, 2, 2-30 trifluoroacetamide, the ally1 ester of diallyloxyacetic acid, 1,3-diallylurea, triallylamine, triallyl trimesate, triallyl cyanurate, triallyl trimellitate, triallyl-1,3,5-triazine-2,4,6(1H, 3H, 5H)-trione. For 30 acrylamido derivatives, mention may be made of methylenebisacrylamide, N, N'-methylenebismethacrylamide, glyoxal bisacrylamide, and diacrylamidoacetic acid. regard to the styrene 35 derivatives, mention may particularly be made of divinylbenzene and 1,3-diisopropenylbenzene.

35

In the case of the diene monomers, mention may particularly be made of butadiene, chloroprene and isoprene.

As multi-ethylenically unsaturated monomers, preference is given to N,N'-methylenebisacrylamide, divinylbenzene, ethylene glycol diacrylate, or trimethylolpropane triacrylate.

5 These multi-ethylenically unsaturated monomers may be used alone or as mixtures.

Typically, the water-soluble monomers initially present in the chain (PC) of the reactive stabilizer are more soluble in the medium (M) than the ethylenically unsaturated monomers used in step (E), often being barely sensitive to the presence of solvents and/or of salts of the medium (M), as appropriate.

More generally, it is advantageous for the chain (PC) to be as soluble as possible in the medium (M). For this to be the case, the constituent monomers of the chain (PC) are preferably selected from monomers of which the solubility is among the highest.

According to one possible embodiment, the reactive stabilizers and the ethylenically unsaturated monomers are introduced together into the medium (M), and the mixing thereof is typically carried out before or during the addition of the initiator.

25

10

According to another possible embodiment, ethylenically unsaturated monomers can be gradually added to the medium (M) after the addition of the reactive stabilizers, typically during or after the addition of the initiator.

30

35

The sources of free radicals

Any source of free radicals which is known per se as being suitable for polymerization processes in an aqueous medium may be used both in step (E) of the process of the invention and in the previous step (E^0) .

The radical polymerization initiator may, for example, be

selected from the following initiators:

- hydrogen peroxides such as: tert-butyl hydroperoxide, cumene hydroperoxide, t-butyl peroxyacetate, t-butyl peroxybenzoate, t-butyl peroxyoctoate, t-butyl peroxyneodecanoate, t-butyl peroxyisobutyrate, lauroyl peroxide, t-amyl peroxypivalate, t-butyl peroxypivalate, dicumyl peroxide, benzoyl peroxide, potassium persulfate, ammonium persulfate,
- azo compounds such as: 2-2'-azobis(isobutyronitrile), 2,2'-azobis(2-butanenitrile), 4,4'-azobis(4-pentanoic acid), 1,1'-
- azobis (cyclohexanecarbonitrile), 2-(t-butylazo)-2-cyanopropane, 2,2'-azobis [2-méthyl-N-(1,1)-bis (hydroxymethyl)-2-hydroxyethyl]propionamide, 2,2'-azobis (2-methyl-N-hydroxyethyl]propionamide, 2,2'-azobis (N,N'-dimethyleneisobutyramidine) dichloride, 2,2'-azobis (2-
- amidinopropane) dichloride, 2,2'-azobis(N,N'-diméthylèneisobutyramide), 2,2'-azobis(2-methyl-N-[1,1-bis(hydroxymethyl)-2-hydroxyethyl]propionamide), 2,2'-azobis(2-methyl-N-[1,1-bis(hydroxymethyl)ethyl]propionamide), 2,2'-azobis[2-methyl-N-(2-hydroxyethyl)propionamide] or 2,2'-
- 20 azobis (isobutyramide) dihydrate,

25

- redox systems comprising combinations such as:
- mixtures of hydrogen peroxide, alkyl peroxide, peresters, percarbonates and the like and any iron salts, titanous salts, zinc formaldehyde sulfoxylate or sodium formaldehyde sulfoxylate, and reducing sugars,
- alkali metal or ammonium persulfates, perborate or perchlorate in combination with an alkali metal bisulfite, such as sodium metabisulfite, and reducing sugars, and
- alkali metal persulfates in combination with an arylphosphinic acid, such as benzenephosphonic acid and the like, and reducing sugars.

According to one advantageous embodiment, use may be made of a radical initiator of redox type, which has the advantage of not requiring heating of the reaction medium (no thermal initiation).

Thus, the source of free radicals that is used can typically

be selected from the redox initiators conventionally used in radical polymerization, typically not requiring heating for thermal initiation thereof. It is typically a mixture of at least one water-soluble oxidizing agent with at least one water-soluble reducing agent.

The oxidizing agent present in the redox system may be selected, for example, from peroxides such as: hydrogen peroxide, tert-butyl hydroperoxide, cumene hydroperoxide, t-butyl peroxyacetate, t-butyl peroxybenzoate, t-butyl peroxyoctoate, t-butyl peroxyneodecanoate, t-butyl peroxyisobutyrate, lauroyl peroxide, t-amyl peroxypivalate, t-butyl peroxypivalate, dicumyl peroxide, benzoyl peroxide, sodium persulfate, potassium persulfate, ammonium persulfate or potassium bromate.

The reducing agent present in the redox system may typically be selected from sodium formaldehyde sulfoxylate (in particular in dihydrate form, known under the name Rongalit, or in the form of an anhydrite), ascorbic acid, erythorbic acid, sulfites, bisulfites or metasulfites (in particular alkali metal sulfites, bisulfites or metasulfites), nitrilotrispropionamides, and tertiary amines and ethanolamines (which are preferably water-soluble).

25

35

20

10

15

Possible redox systems comprise combinations such as:

- mixtures of water-soluble persulfates with water-soluble tertiary amines,
- mixtures of water-soluble bromates (for example alkali metal
 bromates) with water-soluble sulfites (for example alkali metal sulfites),
 - mixtures of hydrogen peroxide, alkyl peroxide, peresters, percarbonates and the like and any iron salts, titanous salts, zinc formaldehyde sulfoxylate or sodium formaldehyde sulfoxylate, and reducing sugars,
 - alkali metal or ammonium persulfates, perborate or perchlorate in combination with an alkali metal bisulfite, such as sodium metabisulfite, and reducing sugars, and

- alkali metal persulfates in combination with an arylphosphinic acid, such as benzenephosphonic acid and the like, and reducing sugars.
- 5 An advantageous redox system comprises (and preferably consists of) for example a combination of ammonium persulfate and sodium formaldehyde sulfoxylate.

Optionally, the aqueous medium (M) of step (E) may comprise at least one salt, selected for example from organic or inorganic salts which render the synthesized polymer insoluble or improve said rendering, and which generally aim to facilitate the obtaining of the dispersion of water-soluble polymers which is sought in the context of the invention.

15

20

Salts that are very suitable are those comprising sulfate, dihydrogenphosphate, phosphate and halide anions. The corresponding cations may be selected from sodium, potassium, calcium, magnesium, aluminum, zinc and ammonium cations, and mixtures thereof. The simultaneous use of two or more of these salts is also possible. For example, a mixture of sodium sulfate and ammonium sulfate may be used.

Optionally, the medium (M) of step (E) may also comprise at least one water-soluble solvent, for example a polyol, such as glycerol. According to one embodiment, the medium (M) comprises both salts and a solvent. For example, the medium (M) may comprise a mixture of sodium sulfate and ammonium sulfate, and a solvent, preferably a polyol.

30

Alternatively, the medium (M) may comprise only salts, with no solvent. For example, the medium (M) may comprise a mixture of sodium sulfate and ammonium sulfate, without solvent.

35 The conditions for carrying out steps (E⁰) and (E)

Given the use of the redox system in step (E^0) and/or step (E), this step is advantageously performed in an aqueous medium,

typically using water as sole solvent. It thus makes it possible to obtain a polymer directly in aqueous medium without the need to use organic solvents, which makes the process particularly suited to use at the industrial scale.

5

10

Moreover, steps (E^0) and (E) are advantageously carried out at low temperature, preferably below $40\,^{\circ}\text{C}$, more advantageously at a temperature of less than or equal to $30\,^{\circ}\text{C}$, especially between 5 and $25\,^{\circ}\text{C}$. These two steps can therefore be carried out, for example, at ambient temperature, which is another advantage of the process of the invention, in terms of energy costs.

The possibility of performing step (E⁰) at low temperature moreover makes it possible to envision carrying it out for the polymerization of N-vinylcaprolactam (NVCL) in an aqueous medium (in water or, advantageously, in a mixture of water and of a water-soluble solvent), which necessitates polymerization at a temperature below its cloud point, which is 32°C. In this context, the process of the invention may in particular be carried out for the synthesis of poly(N-vinylcaprolactam) or of polymers based both on amphiphilic or nonamphiphilic NVCL and NVP monomer units.

25 Applications

30

35

The dispersions obtained at the end of step (E) can be used in a very large number of applications, in particular for the preparation of an aqueous paint, coating or adhesive composition, of an aqueous composition for the preparation of construction materials, or else for the preparation of cosmetic or body care compositions, of phytosanitary formulations or formulations intended for the agricultural field, or else in fluids for oil extraction and/or production (including drilling, fracturing and enhanced oil recovery), or else for the treatment of water (domestic, municipal, industrial, waste aqueous effluents), the manufacturing of paper and/or cardboard, the treatment of ores and of minerals,

for instance fillers and pigments (for example the recovery of alumina according to the Bayer process), or the conditioning of soils.

- In particular in these compositions, the dispersion of the invention is generally introduced as an additive for modifying the rheological properties of the composition, in particular for increasing the viscosity. More generally, it can be used as a flocculant, a coagulant, a stabilizer, a thickener or a flotation agent. The dispersion of the invention can also be used as a surface agent, in particular as a surface-modifying additive.
- According to one particular aspect, the present invention relates to the preparation of an aqueous composition (such as one of the abovementioned compositions) comprising a step wherein a polymer dispersion resulting from step (E) is added to an aqueous pre-composition.
- 20 More generally, the dispersions of the invention can be used alone or as mixtures of several of said dispersions, in most of the applications that can be envisioned for water-soluble polymers.

25 Examples

The synthesis is carried out in two steps:

- 1. Synthesis of a living poly(sodium 2-acrylamido-2-30 methylpropanesulfonate) prepolymer P1
 - 2. Preparation of a homogeneous water-in-water dispersion of acrylamide/acrylic acid copolymers
- 35 Step 1: Synthesis of a living poly(sodium 2-acrylamido-2-methylpropanesulfonate) prepolymer P1
 - 320 g of sodium 2-acrylamido-2-methylpropanesulfonate (AMPS

2405 50%), 188 g of distilled water, 3.3 g of O-ethyl-S-(1-methoxycarbonylethyl) xanthate of formula $(CH_3CH(CO_2CH_3))S(C=S)OEt$, 146 g of ethanol and 1.12 g of ACP $(4'4-azobis-4-cyanovaleric\ acid)$ initiator were placed, at ambient temperature $(20\,^{\circ}C)$, in a 1-liter round-bottomed flask. The mixture was degassed by sparging with nitrogen for 30 minutes. The round-bottomed flask was then placed in a thermostated oil bath at 75 $^{\circ}C$, and the polymerization reaction was then allowed to take place with stirring for 4 hours at 75 $^{\circ}C$.

100% conversion was obtained (determined by ^{1}H NMR). The number-average molar mass of the prepolymer P1, determined by ^{1}H NMR, is 15 537g/mol.

15

20

10

The solvent was evaporated off under vacuum using a rotary evaporator (15 mbar, 50°C) and dried for 120 minutes at 50°C. Water was then added so as to have a solution of prepolymer at 25%. The dry extract measured after solvent exchange is 25% (115°C, 60 min) - SOLUTION A.

Step 2 Preparation of a homogeneous water-in-water dispersion of acrylamide/acrylic acid copolymers

25 Example A Poly(acrylamide/acrylic acid) 70/30 mol%

Conditions:

Prepolymer 1/ poly(acrylamide/acrylic acid) = 30% by weight.

30

Poly(Acrylamide/Acrylic Acid) concentration = 14.9% by weight.

24 g of solution A, 27.88 g of acrylamide (aqueous solution at 50% by weight), 6.06 g of acrylic acid, 3.48 g of sodium sulfate, 18.60 g of ammonium sulfate, 8 g of glycerol, 45.18 g of distilled water and 0.35 g of sodium hydroxide (aqueous solution at 50% by weight) were placed in a 250 ml round-bottomed flask, at ambient temperature (20°C). The mixture was

degassed by sparging with nitrogen with stirring for 30 minutes. After having added 0.045 g of VA044 (2,2'-azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride), the round-bottomed flask was placed in a thermostated oil bath at 30°C, still with stirring. After reaction for 4 hours, a further 0.045 g of VA044 was added. The polymerization reaction was then left to proceed, still with stirring, at 38°C for an additional 3 hours and 30 minutes.

10 At the end of the 8 hours and thirty minutes of reaction, a conversion of >99.9% was obtained for acrylic acid and for acrylamide (conversions determined by HPLC). An analysis by size exclusion chromatography in an aqueous buffer solution of 100 mM NaCl, 25 mM NaH₂PO₄ and 25 mM Na₂HPO₄, pH 7, with a Malls 3 angle detector gives the following weight-average molar mass (M_W) and polydispersity index values:

 $M_w = >210\ 000\ g/mol$ PI = >1.4

20 Using an analyzing polarizing microscope, the particle size was estimated between 1 and 3 μm .

The product is stable after 8 months of storage at ambient temperature.

Example B Poly(acrylamide/acrylic acid) 70/30 mol%

Conditions:

25

30 Prepolymer 1/ poly(acrylamide/acrylic acid) = 30% by weight.

Poly(Acrylamide/Acrylic Acid) concentration = 15.0% by weight.

24 g of solution A, 27.88 g of acrylamide (aqueous solution at 50% by weight), 6.06 g of acrylic acid, 3.48 g of sodium sulfate, 18.60 g of ammonium sulfate, 52.79 g of distilled water and 0.35 g of sodium hydroxide (aqueous solution at 50% by weight) were placed in a 250 ml round-bottomed flask, at

ambient temperature (20°C). The mixture was degassed by sparging with nitrogen with stirring for 30 minutes. After having added 0.045 g of VA044 (2,2'-azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride), the round-bottomed flask was placed in a thermostated oil bath at 38°C, still with stirring. After reaction for 4 hours, a further 0.045 g of VA044 was added. The polymerization reaction was then left to proceed, still with stirring, at 38°C for an additional 3 hours and 30 minutes.

10

15

At the end of the 8 hours and thirty minutes of reaction, a conversion of 99.8% was obtained for acrylic acid and of 100% was obtained for acrylamide (conversions determined by HPLC). An analysis by size exclusion chromatography in an aqueous buffer solution of 100 mM NaCl, 25 mM NaH₂PO₄ and 25 mM Na₂HPO₄, pH 7, with a Malls 3 angle detector gives the following weight-average molar mass ($M_{\rm W}$) and polydispersity index values: $M_{\rm W}$ = >156 000 g/mol

PI = >1.2

20

Using an analyzing polarizing microscope, the particle size was estimated between 1 and 3 μm .

The product is stable after 8 months of storage at ambient 25 temperature.

Example C Poly(acrylamide/acrylic acid) 70/30 mol%

Conditions:

30

Prepolymer 1/ poly(acrylamide/acrylic acid) = 23% by weight.

Poly(Acrylamide/Acrylic Acid) concentration = 15.4% by weight.

35 18.4 g of solution A, 3.37 g of sodium sulfate, 18 g of ammonium sulfate and 0.35 g of sodium hydroxide (aqueous solution at 50% by weight) were placed in a 250 ml round-bottomed flask, at ambient temperature (20°C). The mixture was

degassed by sparging with nitrogen with stirring for 30 minutes. After having added 0.045 g of VA044 (2,2'-azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride), the round-bottomed flask was placed in a thermostated oil bath at 38°C, still with stirring. The introduction of a solution containing 27.88 g of acrylamide (aqueous solution at 50% by weight) and 6.06 g of acrylic acid is jointly begun, at a flow rate of 0.113 ml/min. After reaction for 4 hours, a further 0.045 g of VA044 was added. The polymerization reaction was then left to proceed, still with stirring, at 38°C for an additional 3 hours and 30 minutes.

At the end of the 8 hours and thirty minutes of reaction, a conversion of 99.7% was obtained for acrylic acid and of 100% was obtained for acrylamide (conversions determined by HPLC). An analysis by size exclusion chromatography in an aqueous buffer solution of 100 mM NaCl, 25 mM NaH₂PO₄ and 25 mM Na₂HPO₄, pH 7, with a Malls 3 angle detector gives the following weight-average molar mass (M_W) and polydispersity index values:

 $20 M_w = >380 000$ PI = >1.9

The chromatograms of the copolymers clearly show the presence of the two species: the acrylamide/acrylic acid copolymer and prepolymer P1.

Example D Poly(acrylamide/acrylic acid) 70/30 mol%

Conditions:

30

25

Prepolymer 1/ poly(acrylamide/acrylic acid) = 40% by weight.

Poly(Acrylamide/Acrylic Acid) concentration = 22.1% by weight.

35 48 g of solution A, 2.81 g of sodium sulfate, 15 g of ammonium sulfate, 18.6 g of distilled water and 0.35 g of sodium hydroxide (aqueous solution at 50% by weight) were placed in a 250 ml round-bottomed flask, at ambient temperature (20°C).

The mixture was degassed by sparging with nitrogen with stirring for 30 minutes. After having added 0.068 g of VA044 (2,2'-azobis[2-(2-imidazolin-2-yl)propane] dihydrochloride), the round-bottomed flask was placed in a thermostated oil bath at 38°C, still with stirring. The introduction of a solution containing 41.82 g of acrylamide (aqueous solution at 50% by weight) and 9.09 g of acrylic acid is jointly begun, at a flow rate of 0.1697 ml/min. After reaction for 4 hours, a further 0.068 g of VA044 was added. The polymerization reaction was then left to proceed, still with stirring, at 38°C for an additional 3 hours and 30 minutes.

At the end of the reaction, a homogeneous dispersion is obtained despite a high polymer dry extract (22.1%).

Patentkrav

- Fremgangsmåde til fremstilling af en vandig dispersion af vandopløselige polymerer, som kan opløses i vand, i det mindste under visse pH- og salinitetsbetingelser, i koncentration på mere end 0,1 q/l, uden fremkomst aggregater/partikler, som har en størrelse på mere end 100 nm, de kan observeres i mikroskop, at fremgangsmåde omfatter et trin (E) til radikalpolymerisation,
- 10 hvor der etableres kontakt mellem følgende i et vandigt medium (M), hvor den syntetiserede polymer ikke er opløselig:
 - mindst én ethylenisk umættet monomer, som er opløselig i det vandige medium (M),
 - mindst én kilde til frie radikaler og
- en reaktiv stabilisator, som omfatter: 15
 - en polymerkæde (PK), som er opløselig i mediet (M),
 - en gruppe (G), som sikrer radikalpolymerisationen i trin (E) en levende og kontrolleret karakter, såsom for eksempel en gruppe, der bærer en thiocarbonylthiogruppe -S(C=S)-.

20

- 2. Fremgangsmåde ifølge krav 1, hvor gruppen (G) er en gruppe, der bærer en thiocarbonylthiogruppe -S(C=S)-.
- 3. Fremgangsmåde ifølge krav 1 eller 2, hvor trin 25 gennemføres i nærværelse af yderligere ikke-reaktive stabilisatorer, for eksempel amfifile blokpolymerer.
- 4. Fremgangsmåde ifølge krav 1 eller 2, hvor trin (E) ikke gennemføres i nærværelse af yderligere ikke-reaktive 30 stabilisatorer, for eksempel amfifile blokpolymerer.
 - 5. Fremgangsmåde ifølge et hvilket som helst af kravene 1-4, hvor gruppen (G), som forefindes på den reaktive stabilisator, typisk har formlen -S(C=S)-Z,
- 35 hvor Z betegner:
 - . et hydrogenatom,
 - . et chloratom,
 - . et eventuelt substitueret alkyl- eller eventuelt

substitueret arylradikal,

- . en eventuelt substitueret heterocykel,
- . et eventuelt substitueret alkylthioradikal,
- . et eventuelt substitueret arylthioradikal,
- 5 . et eventuelt substitueret alkoxyradikal,
 - . et eventuelt substitueret aryloxyradikal,
 - . et eventuelt substitueret aminoradikal,
 - . et eventuelt substitueret hydrazinradikal,
 - . et eventuelt substitueret alkoxycarbonylradikal,
- 10 . et eventuelt substitueret aryloxycarbonylradikal,
 - . et eventuelt substitueret carboxy- eller eventuelt substitueret acyloxyradikal,
 - . et eventuelt substitueret aroyloxyradikal,
 - . et eventuelt substitueret carbamoylradikal,
- 15 . et cyanoradikal,
 - . et dialkyl- eller diarylphosphonatoradikal,
 - . et dialkylphosphinato- eller diarylphosphinatoradikal, eller
 - . en polymerkæde.


20

- 6. Fremgangsmåde ifølge et hvilket som helst af kravene 1-5, hvor gruppen (G) er et xanthat eller et dithiocarbamat, fortrinsvis et xanthat.
- 7. Fremgangsmåde ifølge et hvilket som helst af kravene 1-6, hvor de i trin (E) anvendte monomerer er monomerer, som er opløselige i mediet (M), og som er valgt blandt:
 - ethylenisk umættede mono- og dicarboxylsyrer, såsom acrylsyre, methacrylsyre, itaconsyre, maleinsyre eller
- 30 fumarsyre,
 - umættede carboxylsyreamider, såsom acrylamid, methacrylamid, N-methylolacrylamid eller methacrylamid, N-alkylacrylamider, N,N-dimethylaminomethyl-acrylamid eller -methacrylamid, 2-(N,N-dimethylamino)ethyl-acrylamid eller -methacrylamid, 3-
- 35 (N,N-dimethylamino)propyl-acrylamid eller -methacrylamid, 4-(N,N-dimethylamino)butyl-acrylamid eller -methacrylamid,
 - vinylaminamider, navnlig vinylformamid, vinylacetamid, N-vinylpyrrolidon og N-vinylcaprolactam,

- α-β-monoethylenisk umættede aminoestere, såsom 2- (dimethylamino)ethylacrylat, 2- (dimethylamino)ethylmethacrylat, 3- (dimethylamino)propylmethacrylat, 2-(tert-butylamino)ethylmethacrylat, 2-(dipentylamino)ethylmethacrylat eller 2-(diethylamino)ethylmethacrylat, vinylpyridiner, vinylpyridiner, vinylamin,
- vinylimidazoliner,
- 10 monomerer, som er precursorer for aminfunktioner, såsom N-vinylformamid eller N-vinylacetamid, som danner primære aminfunktioner ved simpel sur eller basisk hydrolyse,
 - ammoniumacryloyl- eller acryloyloxymonomerer,
 - trimethylammoniumpropylmethacrylatsalte, navnlig chloridet,
- trimethylammoniumethylacrylamid- eller -methacrylamidchlorid eller -bromid,
 - trimethylammoniumbutylacrylamid- eller methacrylamidmethylsulfat,
 - trimethylammoniumpropylmethacrylamidmethylsulfat,
- 20 (3-methacrylamidopropyl) trimethylammoniumchlorid,
 - (3-acrylamidopropyl)trimethylammoniumchlorid eller methylsulfat,
 - methacryloyloxyethyltrimethylammoniumchlorid eller methylsulfat,
- 25 acryloyloxyethyltrimethylammoniumsalte, såsom acryloyloxyethyltrimethylammoniumchlorid eller acryloyloxyethyltrimethylammoniummethylsulfat,
 - methyldiethylammoniumethylacrylatmethylsulfat,
 - benzyldimethylammoniumethylacrylatchlorid eller -
- 30 methylsulfat,
 - 1-ethyl-2-vinylpyridinium- eller 1-ethyl 4-vinylpyridiniumbromid, -chlorid eller -methylsulfat,
 - N,N-dialkyldiallylaminmonomerer, såsom N,N-dimethyldiallylammoniumchlorid,
- 35 dimethylaminopropylmethacrylamid-N-(3-chlor-2-hydroxypropyl)trimethylammoniumchlorid,
 - dimethylaminopropylmethacrylamid-N-(3-methylsulfat-2-hydroxypropyl)trimethylammoniummethylsulfat,

- monomeren med formlen

5



hvor X- er en anion, fortrinsvis chlorid eller methylsulfat, - blandinger af to eller flere af disse monomerer.

8. Fremgangsmåde ifølge et hvilket som helst af kravene 1-7, hvor vandopløselige tværbindende monomerer tilsættes samtidig med eller efter indføringen af de vandopløselige monomerer.

9. Fremgangsmåde ifølge et hvilket som helst af kravene 1-8, hvor mediet (M) i trin (E) desuden omfatter mindst ét salt og/eller ét opløsningsmiddel, som er vandopløseligt.

10. Fremgangsmåde ifølge krav 9, hvor mediet (M) i trin (E) omfatter en blanding af natriumsulfat og ammoniumsulfat og et opløsningsmiddel, fortrinsvis en polyol.

11. Fremgangsmåde ifølge krav 9, hvor mediet (M) i trinet omfatter en blanding af natriumsulfat og ammoniumsulfat uden opløsningsmiddel.

12. Vandig dispersion af vandopløselige polymerer, som kan opnås ifølge et hvilket som helst af kravene 1-11.

25 13. Anvendelse af en dispersion ifølge krav 12 til fremstilling af en vandig malings-, belægnings- eller klæbemiddelsammensætning, en vandig sammensætning til af byggematerialer, til fremstilling fremstilling kosmetiske sammensætninger eller kropsplejesammensætninger, 30 plantebeskyttelsesformuleringer eller formuleringer beregnet til landbrugsområdet, i væsker til olieekstraktion og/eller produktion (herunder boring, frakturering og forbedret olieindvinding), til behandling af vand, fremstilling af papir og/eller pap, behandling af malme og/eller mineraler eller konditionering af jord. 35

- 14. Anvendelse af en dispersion ifølge krav 12 som tilsætningsstof til modificering af de reologiske egenskaber af en sammensætning eller som flokkuleringsmiddel, koaguleringsmiddel, stabilisator, fortykningsmiddel eller 5 flotationsmiddel.
 - 15. Anvendelse af en dispersion ifølge krav 12 som overflademiddel.