

UNITED STATES PATENT OFFICE

2,107,772

PROCESS FOR DEWAXING OIL

Maner L. Wade, Long Beach, Calif., assignor to
Union Oil Company of California, Los Angeles,
Calif., a corporation of California

No Drawing. Application September 22, 1934,
Serial No. 745,167

8 Claims. (Cl. 204—1)

This invention relates to the electrical separation of wax from wax-bearing oil and particularly to aids and accelerators to dewaxing wax-bearing oil by electrodeposition or electroplating.

In the processes for dewaxing oil electrically the wax-bearing oil is mixed with a suitable diluent, chilled to a temperature at which wax is precipitated out of solution as a finely divided wax suspension and the wax suspension removed from the mixture by electrodeposition upon electrically charged electrodes. In most cases the wax precipitates formed in unrefined oils are comprised of negatively charged wax crystals or particles and are deposited or plated in a solid cake or layer upon the positive electrode under the influence of an electric field.

Objects of this invention are to increase the rate and efficiency of dewaxing wax-bearing oil by electrodeposition methods.

It has been found that the rate of electrodeposition can be increased by the addition to the oil or oil diluent mixture prior to chilling and electrical treatment certain extraneous substances which act as promoters or accelerators. It is believed that these substances, upon chilling, may be co-precipitated with the wax to be removed from the oil, and that the effect of the co-precipitated substance upon the wax is favorable to electrodeposition.

For example, a number of dewaxing tests were run on Santa Fe Springs raw lubricating oil distillate with added extraneous aids to electrodeposition as follows. The wax-bearing lubricating oil distillate was first diluted with 50 volume

percent of light hydrocarbon distillate having a boiling point range of approximately 326° to 395° F., then a small quantity of an accelerator was added to the oil-diluent solution and the mixture chilled to a temperature at which wax precipitated from solution in the form of a fine suspension. This mixture was subsequently subjected to a unidirectional electric field between oppositely charged, flat plate, immersed electrodes having areas of 8 square inches and spaced $\frac{3}{4}$ inch apart from face to face. Under the influence of the unidirectional electric field the precipitated wax was removed from the wax-bearing mixture as a deposit or plated layer upon the positive electrode. Blank tests were simultaneously made in the same manner and under identical conditions but without the accelerators being added, in order to determine the relative rates of electrodeposition with and without the said accelerator. Table I indicates the conditions of the hereinbefore described tests.

It was discovered that the accelerators when added to the waxy oil solution at temperatures at or below the cloud point of the solution, were ineffective to increase the rate of wax deposition while those same accelerators when added at a temperature above the cloud point were effective in increasing the rate of electrodeposition. The electrodeposition accelerators listed hereinafter in Table I were therefore added to the waxy oil-diluent solutions at temperatures of 120° F., or higher, which were temperatures well above the cloud point of the oil solutions.

Table I

Test No.	Duration of electrodeposition—minutes	Temp. °F.	Voltage between electrodes	Electrodeposition accelerator	Deposit	
					Grams	Per cent increase
1.....	7	52	34,500	None.	70	-----
				0.5% I. G. S. wax.	210	300
				0.5% I. G. E. wax.	186	266
2.....	5	50	30,600	None.	78	-----
				0.5% Beeswax (purified)	200	256
3.....	7	52	34,500	None.	70	-----
				0.5% Montan wax (crude)	165	236
4.....	7	50	31,500	None.	89	-----
				0.5% Carnauba wax.	202	-----
5.....	5	51	34,200	None.	88	-----
				0.5% I. G. O. P. wax.	180	205
6.....	10	51	34,350	None.	93	-----
				0.5% Stearine pitch.	171	184
7.....	5	49	30,600	None.	78	-----
				0.5% I. G. B. wax.	139	179
8.....	10	50	34,200	None.	113	-----
				0.4% Calcium stearate.	174	154
9.....	10	50	33,900	None.	114	-----
				0.5% A-Grade asphalt.	181	156
10.....	10	48	33,900	None.	121	-----
				0.2% Formic acid.	177	146

Additional substances not included in Table I which were found to act as accelerators to electrodeposition of wax by the same test methods are as follows: acetic acid, alpha bromonaphthalene, p-dichlorodiphenyl, palmitic acid, naphthalene, pyrogallol, oleic acid, cresol, trioxymethylene, p-aminophenol, pyridine, albino asphalt, nitrobenzene, sodium phenoxide, benzoic acid, aniline and calcium naphthenate.

It is not known certainly what the chemical compositions of the waxes are, but they are believed to contain montanic, melissic, carnaubic, cerotic and other fatty acids of the general formula $C_nH_{2n}O_2$, high molecular weight alcohols and esters of these acids and alcohols.

The I. G. O. P., I. G. B., I. G. E. and I. G. S. waxes are standard products of the I. G. Farbenindustrie Aktiengesellschaft Albino asphalt comprises an acid treated naphtha extract of a 300° F. melting point cracked residuum. It has a melting point of approximately 120° F.

In Table II is found a list of the physical characteristics of the accelerators appearing in Table I, and the class of chemical compositions to which they are each believed to be related.

Table II

Electrodeposition accelerator	(a) Acid No.	(b) Sap. No.	(c) M. P. °F. (Ubbel.)	Chemical composition
I. G. O. P. wax	13.8	113	219	Esters of montanic acid.
I. G. B. wax	57.8	148	177.5	Esters of montanic acid.
I. G. E. wax	14.3	142	166	Esters of montanic acid.
I. G. S. wax	143.0	170	181	Esters of montanic acid.
Montan wax (refined)	64.0	67	180	Contains montanic acid.
Montan wax (crude)	28.0	92	183	Contains montanic acid.
Caranauba wax	4.0	71	184	Esters of carnaubic acid.
Beeswax	20.0	91	147	Contains melissic and cerotic acid.
A-Grade asphalt (d)			209-260	Petroleum pitch or residue.
Calcium stearate (e)				Insoluble metallic soap.
Formic acid (f)			47.5	Organic acid—40% aq. sol.
Stearine pitch				Fatty acid.

(a) Acid number (neutralization number) by the A. S. T. M. test D-188-27T.

(b) Sap. No.—Saponification number by the A. S. T. M. test D-94-28.

(c) M. P.—Melting point, Ubbelohde.

(d) 23–30% fixed carbon 75–95% sol. in CH_2Cl_2 ductility 0. sp. gr. 1.09.

(e) Insoluble in water. Sol. in alcohol. Forms colloidal suspension in oil.

(f) B. P. 100.8°C. sp. gr. 1.218.

Substances which have been found to produce the most pronounced promotion or acceleration of the rate of the electrodeposition of waxes from suspension in wax-bearing oils are therefore believed to be of the following classes:

1. Waxes which contain high molecular weight alcohols, montanic acid, carnaubic acid, melissic acid and esters thereof.

2. Petroleum asphalts, residues or pitches or extracts thereof.

3. Fatty acid bottoms or pitch.

4. Metallic soaps such as calcium stearate.

5. Organic acids.

6. Aromatic compounds such as naphthalene, a-bromonaphthalene and p-dichlorodiphenyl.

7. Aromatic nitrogen compounds such as nitrobenzene, pyridine and aniline.

8. Phenolic compounds such as cresol, sodium phenoxide and p-aminophenol.

9. Petroleum residues, pitches or extracts thereof such as A-grade asphalt or albino asphalt.

This invention resides in a process for increasing the rate of electrodeposition of precipitated wax from wax-bearing oil wherein extraneous electrodeposition aids are added to the wax-bearing oil prior to chilling and the subsequently precipitated wax resulting from chilling the mixture or solution removed from the oil by electro-depo-

sition under the influence of an electric current or electric field.

This invention also resides in the hereinbefore described electrodeposition dewaxing aids and the employment thereof as aids to the process of electrodeposition of wax from wax-bearing oil.

The accelerators or promoters to electrodeposition have been found effective when used in conjunction with various oil solvents and diluents such as liquid propane, gasoline, benzene, kerosene, carbon tetrachloride, and lubricating oil fractions.

An example of the practical application of the invention is as follows:

The wax-bearing oil to be dewaxed is mixed under pressure with a suitable diluent such as liquid propane in the approximate proportion of one part oil to two parts liquid propane by volume at a temperature well above the cloud point of the solution which may be approximately 100° F. An electrodeposition accelerator such as I. G. S. wax is added to the warm oil-propane solution in a small quantity ranging between 0.2% to 0.5% of the volume of the oil. The solution containing the accelerator is self-chilled by re-

duction of pressure and evaporation of propane to a temperature of -40° F. at which temperature wax precipitates in the form of a fine suspension. The chilled mixture containing the precipitate is then passed between metallic plate electrodes which are spaced approximately $\frac{3}{4}$ inch apart, face to face, and which are charged to a unidirectional electropotential difference of 34,500 volts. The precipitated wax, which is in most cases charged negatively, moves under the influence of the electric field between the electrodes and is deposited in a solid layer or coating on the surface of the positively charged electrode.

The positive electrode plates, after receiving a coating of wax may be removed from the oil solution and the wax subsequently removed therefrom by suitable mechanical means.

The quantity of wax deposited upon the electrode in a given period of time from the oil solution containing an accelerator is found to be increased to as much as 300% over that which is deposited upon the electrode under similar conditions but without the presence of the added accelerator.

The oil-propane solution from which the wax has been electrically deposited is subsequently freed from the dissolved propane diluent by distillation to produce a dewaxed depropanized oil.

It is to be understood that the foregoing is

merely illustrative of one method of operation and that the invention is not limited thereby but may include other methods to accomplish the same within the scope of the invention.

5 I claim:

1. A process for dewaxing oil comprising adding an extraneous high molecular weight natural ester type wax to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

2. A process for dewaxing oil comprising adding to the wax-bearing oil a high molecular weight wax material, chilling the solution to precipitate wax, and removing the wax from the mixture by electrodeposition, the added high molecular weight wax being chosen from the group consisting of esters of montanic, carnaubic, melissic, palmitic and cerotic acids.

3. A process for dewaxing oil comprising adding a high molecular weight wax material comprising an ester of montanic acid to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

4. A process for dewaxing oil comprising adding

Montan wax to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

5. A process for dewaxing oil comprising adding a high molecular weight wax material comprising an ester of carnaubic acid to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

6. A process for dewaxing oil comprising adding carnauba wax to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

7. A process for dewaxing oil comprising adding a high molecular weight wax material comprising an ester of melissic acid to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

8. A process for dewaxing oil comprising adding beeswax to the wax-bearing oil, chilling the solution to precipitate wax, subjecting the mixture to an electric field and separating wax from the oil.

MANER L. WADE.